

FCC Part 15C

Measurement and Test Report

For

Beijing Hanshow Technology Co., Ltd.

Floor 18, Building C, Ruipu Plaza, No.15 Hongjunying South Rd, Chaoyang

District, Beijing, China

FCC ID: 2AD43-HS-C0955

FCC Rule(s):	<u>FCC Part 15.249</u>
Product Description:	<u>ESL Transmitter</u>
Tested Model:	<u>HS-C09556 Senior</u>
Report No.:	<u>STR14128170I-1</u>
Tested Date:	<u>2014-12-23 to 2015-02-05</u>
Issued Date:	<u>2015-02-05</u>
Tested By:	<u>Mark Chen / Engineer</u>
Reviewed By:	<u>Lahm Peng / EMC Manager</u>
Approved & Authorized By:	<u>Jandy so / PSQ Manager</u>
Prepared By:	

Mark Chen

Lahm peng

Jandyso

Shenzhen SEM.Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY.....	4
1.4 TEST FACILITY	4
1.5 EUT SETUP AND TEST MODE.....	5
2. SUMMARY OF TEST RESULTS	6
3. ANTENNA REQUIREMENTS.....	7
3.1 STANDARD APPLICABLE.....	7
3.2 TEST RESULT.....	7
4. RADIATED EMISSIONS.....	8
4.1 MEASUREMENT UNCERTAINTY	8
4.2 STANDARD APPLICABLE.....	8
4.3 TEST EQUIPMENT LIST AND DETAILS	8
4.4 TEST PROCEDURE.....	9
4.5 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	10
4.6 ENVIRONMENTAL CONDITIONS	10
4.7 SUMMARY OF TEST RESULTS/PLOTS	10
5. OUT OF BAND EMISSIONS.....	19
5.1 STANDARD APPLICABLE.....	19
5.2 TEST EQUIPMENT LIST AND DETAILS	19
5.3 TEST PROCEDURE.....	19
5.4 ENVIRONMENTAL CONDITIONS	19
5.5 SUMMARY OF TEST RESULTS/PLOTS	19
6. EMISSION BANDWIDTH.....	22
6.1 STANDARD APPLICABLE.....	22
6.2 TEST EQUIPMENT LIST AND DETAILS	22
6.3 TEST PROCEDURE.....	22
6.4 ENVIRONMENTAL CONDITIONS	22
6.5 SUMMARY OF TEST RESULTS/PLOTS	22
7. CONDUCTED EMISSIONS	25
7.1 MEASUREMENT UNCERTAINTY	25
7.2 TEST EQUIPMENT LIST AND DETAILS	25
7.3 TEST PROCEDURE.....	25
7.4 BASIC TEST SETUP BLOCK DIAGRAM.....	25
7.5 ENVIRONMENTAL CONDITIONS	26
7.6 TEST RECEIVER SETUP	26
7.7 SUMMARY OF TEST RESULTS/PLOTS	26
7.8 CONDUCTED EMISSIONS TEST DATA.....	26

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Beijing Hanshow Technology Co., Ltd.
Address of applicant: Floor 18, Building C, Ruipu Plaza, No.15
Hongjunying South Rd, Chaoyang District, Beijing,
China
Manufacturer: Zhejiang Hanshow Technology Co., Ltd.
Address of manufacturer: Shanghai jiao Tong University Jiaxing Science Park,
No.321, Jiachuang Road, Xiuzhou District, Jiaxing
City, Zhejiang Province

General Description of EUT	
Product Name:	ESL Transmitter
Trade Name:	/
Model No.:	HS-C09556 Senior
Adding Model(s):	HS-C09556 Junior
Rated Voltage:	DC 5V from POE
Power Adapter Model:	MU24-1480050-A2 Input: AC100-240V, 50/60Hz; Output: DC 48V
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model HS-C09556 Senior; but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Frequency Range:	2410-2480MHz
Max. Field Strength:	83.73 dBuV/m (at 3m distance)
Data Rate:	2Kbps to 500Kbps
Modulation:	FSK/GFSK
Quantity of Channels:	141
Channel Separation:	500KHz
Antenna Type:	SMA reverse
Antenna Gain:	5dBi
Lowest Internal Frequency of EUT:	25MHz

1.2 Test Standards

The following report is prepared on behalf of the Beijing Hanshow Technology Co., Ltd. in accordance with FCC Part 15, Subpart B, Subpart C, and section 15.107, 15.203, 15.205, 15.207, 15.209 and 15.249 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.107, 15.203, 15.205, 15.207, 15.209 and 15.249 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which results in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.4 Test Facility

FCC – Registration No.: 934118

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

CNAS Registration No.: L4062

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101).

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low Channel	2410MHz
TM2	Middle Channel	2445MHz
TM3	High Channel	2480MHz

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
Reticle	1.2	Unshielded	Without Ferrite

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
AC Adapter	N/A	MU24-1480050-A2	/
POE	N/A	TL-POE150S	/
PC	DELL	OPTIPLEX 380	/
Display	LENOVO	L1950Wd	/

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 15.203	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.209(a)(f)	Radiated Spurious Emissions	Compliant
§15.249(a)	Field Strength of Emissions	Compliant
§15.249(d)	Out of Band Emission	Compliant
§15.215 (c)	Emission Bandwidth	Compliant

3. Antenna Requirements

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has a uniqueness antenna, fulfill the requirement of this section.

4. Radiated Emissions

4.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is ± 5.10 dB.

4.2 Standard Applicable

According to §15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field strength of fundamental (milli-volts/meter)	Field strength of Harmonics (micro-volts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

4.3 Test Equipment List and Details



Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2014-05-28	2015-05-27
EMI Test Receiver	R&S	ESVB	825471/005	2014-05-28	2015-05-27
Pre-amplifier	Agilent	8447F	3113A06717	2014-05-28	2015-05-27
Pre-amplifier	Compliance Direction	PAP-0118	24002	2014-05-28	2015-05-27
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2014-05-24	2015-05-23
Horn Antenna	ETS	3117	00086197	2014-05-24	2015-05-23
Horn Antenna	ETS	3116B	00088203	2014-05-24	2015-05-23
Loop Antenna	SCHWARZECK	HFRA 5165	9365	2014-05-24	2015-05-23

4.4 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.205 15.249(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

4.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15C Limit}$$

4.6 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	60 %
ATM Pressure:	1012 mbar

4.7 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.249 standards, and had the worst margin of:


-13.91 dB at 900.1474 MHz in the Horizontal polarization, Low Channel, 9 kHz to 25 GHz, 3Meters

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: ESL Transmitter
Tested Model: HS-C09556 Senior
Operating Condition: Transmitting Low Channel (2410MHz)
Comment: AC120V/60Hz; Adapter DC 48V

Test Specification: Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	46.9948	23.22	-7.45	15.77	40.00	-24.23	105	100	peak
2	192.4186	26.88	-9.81	17.07	43.50	-26.43	127	100	peak
3	348.0274	28.09	-4.31	23.78	46.00	-22.22	169	100	peak
4*	900.1474	26.71	5.38	32.09	46.00	-13.91	181	100	peak


Test Specification: Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1*	73.3593	32.85	-12.73	20.12	40.00	-19.88	125	100	peak
2	110.1816	29.18	-9.63	19.55	43.50	-23.95	139	100	peak
3	122.4040	32.53	-11.63	20.90	43.50	-22.60	184	100	peak
4	282.9852	28.39	-6.62	21.77	46.00	-24.23	201	100	peak


Operating Condition: Transmitting Middle Channel (2445MHz)
Comment: AC120V/60Hz; Adapter DC 48V

Test Specification: Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	46.3402	23.23	-7.46	15.77	40.00	-24.23	115	100	peak
2	97.4560	23.13	-9.87	13.26	43.50	-30.24	128	100	peak
3	372.0045	27.15	-3.78	23.37	46.00	-22.63	149	100	peak
4*	909.6667	23.56	5.49	29.05	46.00	-16.95	167	100	peak


Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1*	53.1313	23.91	-7.76	16.15	40.00	-23.85	116	100	peak
2	119.4361	27.52	-11.17	16.35	43.50	-27.15	147	100	peak
3	160.3457	29.09	-12.32	16.77	43.50	-26.73	195	100	peak
4	216.7828	30.95	-8.93	22.02	46.00	-23.98	224	100	peak


Operating Condition: *Transmitting High Channel (2480MHz)*
Comment: *AC120V/60Hz; Adapter DC 48V*

Test Specification: *Horizontal*



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	46.5030	23.62	-7.46	16.16	40.00	-23.84	125	100	peak
2	101.2885	23.07	-9.56	13.51	43.50	-29.99	149	100	peak
3	225.3080	29.66	-8.61	21.05	46.00	-24.95	167	100	peak
4*	396.2415	26.43	-3.06	23.37	46.00	-22.63	188	100	peak

Test Specification: Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	1*	47.8260	23.95	-7.46	16.49	40.00	-23.51	122	100
2	2	115.7256	29.81	-10.55	19.26	43.50	-24.24	134	100
3*	3	177.5092	28.47	-11.31	17.16	43.50	-26.34	149	100
4	4	234.9909	26.79	-8.06	18.73	46.00	-27.27	167	100

Spurious Emissions Above 1GHz

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2410MHz							
2410	80.55	-3.46	77.09	114	-36.91	H	PK
2410	69.15	-3.46	65.69	94	-28.31	H	AV
4820	42.45	0.60	43.05	74	-30.95	H	PK
4820	32.77	0.60	33.37	54	-20.63	H	AV
7230	34.84	3.72	38.56	74	-35.44	H	PK
7230	26.07	3.82	29.89	54	-24.11	H	AV
2410	83.96	-3.46	80.50	114	-33.50	V	PK
2410	72.64	-3.46	69.18	94	-24.82	V	AV
4820	42.66	0.60	43.26	74	-30.74	V	PK
4820	31.54	0.94	32.48	54	-21.52	V	AV
7230	36.58	3.72	40.30	74	-33.70	V	PK
7230	26.14	3.82	29.96	54	-24.04	V	AV
Middle Channel-2445 MHz							
2445	86.69	-3.38	83.31	114	-30.69	H	PK
2445	72.19	-3.38	68.81	94	-25.19	H	AV
4890	44.95	0.70	45.65	74	-28.35	H	PK
4890	32.71	0.70	33.41	54	-20.59	H	AV
7335	37.34	3.79	41.13	74	-32.87	H	PK
7335	26.06	3.82	29.88	54	24.12	H	AV
2445	84.29	-3.38	80.91	114	-33.09	V	PK
2445	69.77	-3.38	66.39	94	-27.61	V	AV
4890	44.90	0.70	45.60	74	-28.40	V	PK
4890	32.65	0.70	33.35	54	-20.65	V	AV
7335	37.57	3.79	41.36	74	-32.64	V	PK
7335	26.09	3.82	29.91	54	-24.09	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2480MHz							
2480	87.06	-3.33	83.73	114	-30.27	H	PK
2480	75.83	-3.33	72.50	94	-21.50	H	AV
4960	42.44	0.70	43.14	74	-30.86	H	PK
4960	32.15	0.77	32.92	54	-21.08	H	AV
7440	37.90	3.84	41.74	74	-32.26	H	PK
7440	26.05	3.82	29.87	54	-24.13	H	AV
2480	84.05	-3.33	80.72	114	-33.28	V	PK
2480	72.81	-3.33	69.48	94	-24.52	V	AV
4960	43.91	0.76	44.67	74	-29.37	V	PK
4960	32.27	0.77	33.04	54	-20.96	V	AV
7440	37.37	3.84	41.21	74	-32.79	V	PK
7440	26.12	3.82	29.94	54	-24.06	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 5th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

The measurements greater than 20dB below the limit from 9kHz to 30MHz..

5. Out of Band Emissions

5.1 Standard Applicable

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

5.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2014-05-28	2015-05-27
EMI Test Receiver	R&S	ESVB	825471/005	2014-05-28	2015-05-27
Pre-amplifier	Agilent	8447F	3113A06717	2014-05-28	2015-05-27
Pre-amplifier	Compliance Direction	PAP-0118	24002	2014-05-28	2015-05-27
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2014-05-24	2015-05-23
Horn Antenna	ETS	3117	00086197	2014-05-24	2015-05-23

5.3 Test Procedure

As the radiation test, set the Lowest and Highest Transmitting Channel, observed the outside band of 2400MHz to 2483.5MHz, than mark the higher-level emission for comparing with the FCC rules.

5.4 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	60 %
ATM Pressure:	1012 mbar


5.5 Summary of Test Results/Plots

Test mode	Frequency	Limit	Result
	MHz	dBuV / dBc	
Lowest	2310.00	<54 dBuV	Pass
	2390.00	<54 dBuV	Pass
	2400.00	<54 dBuV	Pass
Highest	2483.50	<54 dBuV	Pass
	2500.00	<54 dBuV	Pass

The edge emissions are below the FCC 15.209 Limits or complies with the 15.249 requirements.


Please refer to the test plots as below.

Lowest Bandedge
Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	23.47	16.34	39.81	54.00	-14.19	Ave Detector
	2310.000	34.77	16.34	51.11	74.00	-22.89	Peak Detector
2	2390.000	23.17	17.03	40.20	54.00	-13.80	Ave Detector
	2390.000	34.66	17.03	51.69	74.00	-22.31	Peak Detector
3	2400.000	23.27	17.11	40.38	54.00	-13.62	Ave Detector
	2400.000	33.78	17.11	50.89	74.00	-23.11	Peak Detector

Highest Bandedge
Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2480.140	74.96	17.71	92.67	/	/	Average Detector
	2480.170	75.37	17.71	93.08	/	/	Peak Detector
2	2483.500	35.39	17.73	53.12	54.00	-0.88	Average Detector
	2483.500	43.14	17.73	60.87	74.00	-13.13	Peak Detector
	2500.000	23.04	17.86	40.90	54.00	-13.10	Average Detector
	2500.000	35.01	17.86	52.87	74.00	-21.13	Peak Detector

6. Emission Bandwidth

6.1 Standard Applicable

According to 15.215 (c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

6.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	Agilent	E4402B	US41192821	2014-05-28	2015-05-27
Attenuator	ATTEN	ATS100-4-20	/	2014-05-28	2015-05-27

6.3 Test Procedure

According to the ANSI 63.4-2014, the emission bandwidth test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Set span = 1MHz, centered on a transmitting channel

RBW \geq 1% 20dB Bandwidth, VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down and 99% bandwidth of the emission.

6.4 Environmental Conditions


Temperature:	25 °C
Relative Humidity:	53%
ATM Pressure:	1018 mbar

6.5 Summary of Test Results/Plots


Channel	Frequency MHz	20dB Bandwidth kHz	99% Bandwidth kHz
Low Channel	2410	1055	1023.3
Middle Channel	2445	1053	1022.6
High Channel	2480	1052	1031.1

Please refer to the following test plots


Low Channel:



Middle Channel:



High Channel:



7. Conducted Emissions

7.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is ± 2.88 dB.

7.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2014-05-28	2015-05-27
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2014-05-28	2015-05-27
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2014-05-28	2015-05-27


7.3 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

7.4 Basic Test Setup Block Diagram



7.5 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

7.6 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency 150 kHz
Stop Frequency..... 30 MHz
Sweep Speed Auto
IF Bandwidth..... 10 kHz
Quasi-Peak Adapter Bandwidth 9 kHz
Quasi-Peak Adapter Mode Normal

7.7 Summary of Test Results/Plots

According to the data in section 7.8, the EUT complied with the FCC Part 15.207 Conducted margin for a Class B device, with the *worst* margin reading of:


-16.79 dB at 0.4060 MHz in the Line, Peak detector, 0.15-30MHz

7.8 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data


EUT: *ESL Transmitter*
 Tested Model: *HS-C09556 Senior*
 Operating Condition: *Transmitting*
 Comment: *AC120V/60Hz; Adapter DC 48V*

Test Specification: *Neutral*



No.	Frequency	Reading	Correct	Result	Limit	Margin	Detector
	(MHz)	(dBuV)	(dB/m)	(dBuV)	(dBuV)	(dB)	
1	0.1540	31.22	9.50	40.72	65.78	-25.06	peak
2	0.1540	15.24	9.50	24.74	55.78	-31.04	AVG
3	0.4060	26.03	9.50	35.53	57.73	-22.20	peak
4	0.4060	17.84	9.50	27.34	47.73	-20.39	AVG
5*	13.0860	22.20	10.62	32.82	50.00	-17.18	AVG
6	13.6980	28.45	10.74	39.19	60.00	-20.81	peak

Test Specification: Line



No.	Frequency	Reading	Correct	Result	Limit	Margin	Detector
	(MHz)	(dBuV)	(dB/m)	(dBuV)	(dBuV)	(dB)	
1	0.1580	33.84	9.50	43.34	65.57	-22.23	peak
2	0.1780	17.36	9.50	26.86	54.58	-27.72	AVG
3	0.4060	26.85	9.50	36.35	57.73	-21.38	peak
4*	0.4060	21.44	9.50	30.94	47.73	-16.79	AVG
5	13.0820	28.52	10.62	39.14	60.00	-20.86	peak
6	13.3900	22.53	10.68	33.21	50.00	-16.79	AVG

***** END OF REPORT *****