

**\* Standalone SAR test exclusion considerations**

- Min. transmitting frequency = 2480 MHz
- Min. test separation distance = 3 mm
- Max. Power with tune-up tolerance = 3.77 dBm = 2.38 mW  
(Measured power 3.27 dBm  $\pm$  0.5dB)

Step 1)

SAR Test exclusion thresholds for 100MHz to 6GHz at test separation distance  $\leq 50$  mm = **Used**[(max.power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] \* [ $\sqrt{f}$ (GHz)]

$$= [2.38 / 10] * [\sqrt{2.480}] = 1.251 \leq 3, \text{ for } 1\text{g SAR}$$

**Thus, SAR for this device is not required.**

Step 2)

SAR Test exclusion thresholds for 100MHz to 1500MHz at test separation distance  $> 50$  mm = **N/A**[Threshold at 50mm in step 1) + (test separation distance - 50 mm) \* ( $\sqrt{f}$ (MHz)/150)] mW

Step 3)

SAR Test exclusion thresholds for 1500MHz to 6GHz at test separation distance  $> 50$  mm = **N/A**

[Threshold at 50mm in step 1) + (test separation distance - 50 mm) \* 10] mW