

GUANGDONG CHEERSON HOBBY TECHNOLOGY CO., LTD.

Application For Certification
FCC ID: 2AD6LGC032431

UFO QUADCOPTERS

Model: CX-31
Additional models: See Page 2

2.4GHz Transmitter

Report No.: GZHH00175112-001

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-14]

Prepared and Checked by:

Approved by:

Sign on file

Terry Tang
Engineer

Andy Yan
Senior Project Engineer
Date: December 8, 2015

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF No.: FCC 15C_TX_b

INTERTEK TESTING SERVICES

LIST OF EXHIBITS

INTRODUCTION

| | |
|--------------------|---------------------------|
| <i>EXHIBIT 1:</i> | General Description |
| <i>EXHIBIT 2:</i> | System Test Configuration |
| <i>EXHIBIT 3:</i> | Emission Results |
| <i>EXHIBIT 4:</i> | Equipment Photographs |
| <i>EXHIBIT 5:</i> | Product Labelling |
| <i>EXHIBIT 6:</i> | Technical Specifications |
| <i>EXHIBIT 7:</i> | Instruction Manual |
| <i>EXHIBIT 8:</i> | Miscellaneous Information |
| <i>EXHIBIT 9:</i> | Confidentiality Request |
| <i>EXHIBIT 10:</i> | Test Equipment List |

INTERTEK TESTING SERVICES

MEASUREMENT/TECHNICAL REPORT

GUANGDONG CHEERSON HOBBY TECHNOLOGY CO., LTD.

Model: CX-31

FCC ID: 2AD6LGC032431

This report concerns (check one:) Original Grant X Class II Change

Equipment Type: DXX - Part 15 Low Power Communication Device Transmitter

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes No X

If yes, defer until:
date

Company Name agrees to notify the Commission by:
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes No X

If no, assumed Part 15, Subpart C for intentional radiator – the new 47 CFR [10-1-14 Edition] provision.

Report prepared by:

Terry Tang
Intertek Testing Services Shenzhen Ltd.
Kejiyuan Branch
6F, Block D, Huahan Building, Langshan Road,
Nanshan District, Shenzhen, P. R. China
Phone: (86 755) 8614 0629
Fax: (86 755) 8601 6751

INTERTEK TESTING SERVICES

Table of Contents

| | |
|--|----|
| 1.0 <u>General Description</u> | 2 |
| 1.1 Product Description | 2 |
| 1.2 Related Submittal(s) Grants | 2 |
| 1.3 Test Methodology | 2 |
| 1.4 Test Facility | 2 |
| 2.0 <u>System Test Configuration</u> | 4 |
| 2.1 Justification | 4 |
| 2.2 EUT Exercising Software | 4 |
| 2.3 Special Accessories | 4 |
| 2.4 Equipment Modification | 4 |
| 2.5 Measurement Uncertainty | 4 |
| 2.6 Support Equipment List and Description | 4 |
| 3.0 <u>Emission Results</u> | 6 |
| 3.1 Radiated Test Results | 7 |
| 3.1.1 Field Strength Calculation | 7 |
| 3.1.2 Radiated Emission Configuration Photograph | 8 |
| 3.1.3 Radiated Emissions | 8 |
| 3.1.4 Transmitter Spurious Emissions (Radiated) | 10 |
| 4.0 <u>Equipment Photographs</u> | 15 |
| 5.0 <u>Product Labelling</u> | 17 |
| 6.0 <u>Technical Specifications</u> | 19 |
| 7.0 <u>Instruction Manual</u> | 21 |
| 8.0 <u>Miscellaneous Information</u> | 23 |
| 8.1 Bandedge Plot | 24 |
| 8.2 Discussion of Pulse Desensitization | 26 |
| 8.3 Calculation of Average Factor | 27 |
| 8.4 Emissions Test Procedures | 28 |
| 9.0 <u>Confidentiality Request</u> | 31 |
| 10.0 <u>Test Equipment List</u> | 33 |

INTERTEK TESTING SERVICES

List of attached file

| Exhibit type | File Description | Filename |
|-----------------------|----------------------------|---------------------|
| Test Report | Test Report | report.pdf |
| Test Setup Photo | Radiated Emission | radiated photos.pdf |
| Test Report | Bandedge Plot | bandedge.pdf |
| Test Report | 20dB BW Plot | bw.pdf |
| Test Report | Timing Plot | af.pdf |
| External Photo | External Photo | external photos.pdf |
| Internal Photo | Internal Photo | internal photos.pdf |
| Block Diagram | Block Diagram | block.pdf |
| Schematics | Circuit Diagram | circuit.pdf |
| Operation Description | Technical Description | descri.pdf |
| ID Label/Location | Label Artwork and Location | label.pdf |
| User Manual | User Manual | manual.pdf |
| Cover Letter | Confidentiality Letter | request.pdf |
| Cover Letter | Letter of Agency | agency.pdf |

INTERTEK TESTING SERVICES

EXHIBIT 1

GENERAL DESCRIPTION

INTERTEK TESTING SERVICES

1.0 General Description

1.1 Product Description

The Equipment under Test (EUT) is transmitter unit for the UFO QUADCOPTERS model: CX-31 operating at 2.4GHz band. It is powered by DC 6.0V (4 x 1.5V AA batteries).

The Models: CX-30, CX-30W, CX-30W-TX, CX-32, CX-32W-TX, CX-32C, CX-32S, CX-30S, CX-22, CX-20, CX-23, CX-24, CX-STARS, 6049, CX-25, CX-26, CX-27, CX-28, CX-29, CX-50, CX-51, CX-52, CX-31C, CX-31I are the same as the Model: CX-31 in hardware and electrical aspect. The difference in appearance and model number serves as marketing strategy.

Antenna Type: Integral antenna

Type of modulation: GFSK modulation

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

1.2 Related Submittal(s) Grants

This is an application for certification of a transmitter unit for the UFO QUADCOPTERS.

1.3 Test Methodology

Radiated emission measurements were performed according to the procedures in ANSI C63.4 (2009). Radiated Emission measurement was performed in a Semi-anechoic chamber. Preliminary scans were performed in the Semi-anechoic chamber only to determine worst case modes. For each scan, the procedure for maximizing emissions in Appendices D and E were followed. All Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

1.4 Test Facility

The Semi-anechoic chamber facility used to collect the radiated data is Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch and located at 6F, D Block, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: 242492).

INTERTEK TESTING SERVICES

EXHIBIT 2

SYSTEM TEST CONFIGURATION

INTERTEK TESTING SERVICES

2.0 **System Test Configuration**

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2009).

The EUT was powered by new 4 x DC 1.5V AA batteries. Only the worst case data was reported.

For maximizing emissions below 30 MHz, the EUT was rotated through 360°, the centre of the loop antenna was placed 1 meter above the ground, and the antenna polarization was changed. For maximizing emission at and above 30 MHz, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data report in Exhibit 3.0.

The unit was operated standalone and placed in the centre of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

2.2 EUT Exercising Software

There was no special software to exercise the device.

2.3 Special Accessories

No special accessories used.

2.4 Equipment Modification

Any modifications installed previous to testing by GUANGDONG CHEERSON HOBBY TECHNOLOGY CO., LTD. will be incorporated in each production model sold / leased in the United States.

Some modifications were installed by Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch.

2.5 Measurement Uncertainty

When determining the test conclusion, the Measurement Uncertainty of test has been considered.

2.6 Support Equipment List and Description

N/A

INTERTEK TESTING SERVICES

EXHIBIT 3

EMISSION RESULTS

INTERTEK TESTING SERVICES

3.0 Emission Results

Data is included worst-case configuration (the configuration which resulted in the highest emission levels).

INTERTEK TESTING SERVICES

3.1 **Radiated Test Results**

A sample calculation, configuration photographs and data tables of the emissions are included.

3.1.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG$$

Where FS = Field Strength in dB μ V/m
 RA = Receiver Amplitude (including preamplifier) in dB μ V
 CF = Cable Attenuation Factor in dB
 AF = Antenna Factor in dB
 AG = Amplifier Gain in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG$$

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The net field strength for comparison to the appropriate emission limit is 42 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

RA = 62.0 dB μ V
AF = 7.4 dB
CF = 1.6 dB
AG = 29.0 dB
FS = 62 + 7.4 + 1.6 - 29 = 42 dB μ V/m

Level in μ V/m = Common Antilogarithm [(42 dB μ V/m)/20] = 125.9 μ V/m

INTERTEK TESTING SERVICES

3.1.2 Radiated Emission Configuration Photograph

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

3.1.3 Radiated Emissions

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Worst Case Radiated Emission
at
56.671 MHz

Judgement: Passed by 15.8 dB

TEST PERSONNEL:

Sign on file

Terry Tang, Engineer
Typed/Printed Name

June 17, 2015
Date

INTERTEK TESTING SERVICES

Applicant: GUANGDONG CHEERSON HOBBY TECHNOLOGY CO., LTD.

Date of Test: June 17, 2015

Model: CX-31

Sample: 1/1

Worst Case Operating Mode: Transmit

Table 1

Radiated Emissions

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|----------------------|-------------|
| Horizontal | 47.440 | 24.5 | 20.0 | 17.9 | 22.4 | 40.0 | -17.6 |
| Horizontal | 168.154 | 29.4 | 20.0 | 16.0 | 25.4 | 43.5 | -18.1 |
| Horizontal | 754.420 | 23.8 | 20.0 | 23.6 | 27.4 | 46.0 | -18.6 |
| Vertical | 56.671 | 26.6 | 20.0 | 17.6 | 24.2 | 40.0 | -15.8 |
| Vertical | 391.751 | 25.6 | 20.0 | 17.2 | 22.8 | 46.0 | -23.2 |
| Vertical | 775.150 | 33.0 | 20.0 | 15.4 | 28.4 | 46.0 | -17.6 |

- NOTES:
1. Quasi-Peak detector is used except for others stated.
 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. All emissions are below the QP limit.

INTERTEK TESTING SERVICES

3.1.4 Transmitter Spurious Emissions (Radiated)

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Worst Case Radiated Emission
at
4804.000 MHz

Judgement: Passed by 11.3 dB

TEST PERSONNEL:

Sign on file

Terry Tang, Engineer
Typed/Printed Name

June 17, 2015
Date

INTERTEK TESTING SERVICES

Applicant: GUANGDONG CHEERSON HOBBY TECHNOLOGY CO., LTD.

Date of Test: June 17, 2015

Model: CX-31

Sample: 1/1

Worst Case Operating Mode: Transmit

Table 2

Radiated Emissions

(2402.000MHz)

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|---------------------------|-------------|
| Vertical | 2402.000 | 102.3 | 36.7 | 28.5 | 94.1 | 114.0 | -19.9 |
| Vertical | 4804.000 | 64.8 | 36.7 | 34.6 | 62.7 | 74.0 | -11.3 |
| Vertical | 7206.000 | 65.6 | 36.1 | 33.1 | 62.6 | 74.0 | -11.4 |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Average Factor (-dB) | Net at 3m (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|----------------------|--------------------|------------------------------|-------------|
| Vertical | 2402.000 | 102.3 | 36.7 | 28.5 | 37.4 | 56.7 | 94.0 | -37.3 |
| Vertical | 4804.000 | 64.8 | 36.7 | 34.6 | 37.4 | 25.3 | 54.0 | -28.7 |
| Vertical | 7206.000 | 65.6 | 36.1 | 33.1 | 37.4 | 25.2 | 54.0 | -28.8 |

- Notes:
1. Peak detector Data unless otherwise stated.
 2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna is used for the emission over 1000MHz.

Test Engineer: Terry Tang

INTERTEK TESTING SERVICES

Applicant: GUANGDONG CHEERSON HOBBY TECHNOLOGY CO., LTD.

Date of Test: June 17, 2015

Model: CX-31

Sample: 1/1

Worst Case Operating Mode: Transmit

Table 3

Radiated Emissions

(2433.000MHz)

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|---------------------------|-------------|
| Vertical | 2433.000 | 100.0 | 36.7 | 28.6 | 91.9 | 114.0 | -22.1 |
| Vertical | 4866.000 | 63.3 | 36.7 | 35.2 | 61.8 | 74.0 | -12.2 |
| Vertical | 7299.000 | 65.1 | 36.1 | 33.1 | 62.1 | 74.0 | -11.9 |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Average Factor (-dB) | Net at 3m (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|----------------------|--------------------|------------------------------|-------------|
| Vertical | 2433.000 | 100.0 | 36.7 | 28.6 | 37.4 | 54.5 | 94.0 | -39.5 |
| Vertical | 4866.000 | 63.3 | 36.7 | 35.2 | 37.4 | 24.4 | 54.0 | -29.6 |
| Vertical | 7299.000 | 65.1 | 36.1 | 33.1 | 37.4 | 24.7 | 54.0 | -29.3 |

Notes: 1. Peak detector Data unless otherwise stated.

2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna is used for the emission over 1000MHz.

Test Engineer: Terry Tang

INTERTEK TESTING SERVICES

Applicant: GUANGDONG CHEERSON HOBBY TECHNOLOGY CO., LTD.

Date of Test: June 17, 2015

Model: CX-31

Sample: 1/1

Worst Case Operating Mode: Transmit

Table 4

Radiated Emissions

(2475.000MHz)

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|---------------------------|-------------|
| Vertical | 2475.000 | 101.6 | 36.7 | 28.9 | 93.8 | 114.0 | -20.2 |
| Vertical | 4950.000 | 62.1 | 36.7 | 35.6 | 61.0 | 74.0 | -13.0 |
| Vertical | 7425.000 | 65.0 | 36.1 | 33.1 | 62.0 | 74.0 | -12.0 |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Average Factor (-dB) | Net at 3m (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|----------------------|--------------------|------------------------------|-------------|
| Vertical | 2475.000 | 101.6 | 36.7 | 28.9 | 37.4 | 56.4 | 94.0 | -37.6 |
| Vertical | 4950.000 | 62.1 | 36.7 | 35.6 | 37.4 | 23.6 | 54.0 | -30.4 |
| Vertical | 7425.000 | 65.0 | 36.1 | 33.1 | 37.4 | 24.6 | 54.0 | -29.4 |

Notes: 1. Peak detector Data unless otherwise stated.

2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna is used for the emission over 1000MHz.

Test Engineer: Terry Tang

INTERTEK TESTING SERVICES

EXHIBIT 4

EQUIPMENT PHOTOGRAPHS

INTERTEK TESTING SERVICES

4.0 Equipment Photographs

For electronic filing, the photographs of the tested EUT are saved with filename: external photos.pdf & internal photos.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 5

PRODUCT LABELLING

INTERTEK TESTING SERVICES

5.0 **Product Labelling**

For electronic filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 6

TECHNICAL SPECIFICATIONS

INTERTEK TESTING SERVICES

6.0 Technical Specifications

For electronic filing, the block diagram and schematics of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

INTERTEK TESTING SERVICES

EXHIBIT 7

INSTRUCTION MANUAL

INTERTEK TESTING SERVICES

7.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

INTERTEK TESTING SERVICES

EXHIBIT 8

MISCELLANEOUS INFORMATION

INTERTEK TESTING SERVICES

8.0 **Miscellaneous Information**

This miscellaneous information includes details of the measured bandedge and the test procedure.

INTERTEK TESTING SERVICES

8.1 Bandedge Plot

For electronic filing, the plot shows the fundamental emission when modulated is saved with filename: be.pdf. From the plot, the field strength of any emissions outside of the specified frequency band are attenuated to the general radiated emission limits in section 15.209. It fulfils the requirement of 15.249(d).

Peak Measurement

Bandedge compliance is determined by applying marker-delta method, i.e (Bandedge Plot).

(i) Lower channel 2402.000MHz:

Peak Resultant field strength = Fundamental emissions (peak value) – delta
from the bandedge plot

$$\begin{aligned} &= 94.1\text{dB}\mu\text{V/m}-26.3\text{dB} \\ &= 67.8\text{dB}\mu\text{V/m} \end{aligned}$$

Average Resultant field strength = Fundamental emissions (Average value) –
delta from the bandedge plot

$$\begin{aligned} &= 56.7\text{dB}\mu\text{V/m}-26.3\text{dB} \\ &= 30.4\text{dB}\mu\text{V/m} \end{aligned}$$

(ii) Upper channel 2475.000MHz:

Peak Resultant field strength = Fundamental emissions (peak value) – delta
from the bandedge plot

$$\begin{aligned} &= 93.8\text{dB}\mu\text{V/m}-35.6\text{ dB} \\ &= 58.2\text{dB}\mu\text{V/m} \end{aligned}$$

Average Resultant field strength = Fundamental emissions (Average value) –
delta from the bandedge plot

$$\begin{aligned} &= 56.4\text{dB}\mu\text{V/m}-35.6\text{ dB} \\ &= 20.8\text{dB}\mu\text{V/m} \end{aligned}$$

The resultant field strength meets the general radiated emission limit in section 15.209, which does not exceed 74dB μ V/m (Peak Limit) and 54dB μ V/m (Average Limit).

INTERTEK TESTING SERVICES

8.1 Bandedge Plot (cont'd)

Pursuant to FCC part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

Figure 8.1 Bandwidth

INTERTEK TESTING SERVICES

8.2 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period (T_{eff}) is approximately 173.9 μ s for a digital "1" bit, as shown in the plots of Exhibit 8.3. With a resolution bandwidth (3 dB) of 100 kHz, the pulse desensitivity factor was 0 dB.

INTERTEK TESTING SERVICES

8.3 Calculation of Average Factor

Averaging factor in dB = $20 \log (\text{duty cycle})$

The specification for output field strengths in accordance with the FCC rules specify measurements with an average detector. During testing, a spectrum analyzer incorporating a peak detector was used. Therefore, a reduction factor can be applied to the resultant peak signal level and compared to the limit for measurement instrumentation incorporating an average detector.

The time period over which the duty cycle is measured is 100 milliseconds, or the repetition cycle, whichever is a shorter time frame. The worst case (highest percentage on) duty cycle is used for the calculation. The duty cycle is measured by placing the spectrum analyzer in zero scan (receiver mode) and linear mode at maximum bandwidth (3 MHz at 3 dB down) and viewing the resulting time domain signal output from the analyzer on a Tektronix oscilloscope. The oscilloscope is used because of its superior time base and triggering facilities.

A plot of the worst-case duty cycle as detected in this manner are saved with filename: af.pdf

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 12.9348ms

Effective period of the cycle = $173.9\mu\text{s} = 0.1739\text{ms}$

$\text{DC} = 0.1739\text{ms} / 12.9348\text{ms} = 0.0134$ or 1.34%

Therefore, the averaging factor is found by $20 \log_{10} 0.0134 = -37.4 \text{ dB}$

INTERTEK TESTING SERVICES

8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 - 2009.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

INTERTEK TESTING SERVICES

8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.4 - 2009.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.2). Above 1000 MHz, a resolution bandwidth of 1 MHz is used, RBW 3MHz used for fundamental emission.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.

INTERTEK TESTING SERVICES

EXHIBIT 9

CONFIDENTIALITY REQUEST

INTERTEK TESTING SERVICES

9.0 **Confidentiality Request**

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 10

TEST EQUIPMENT LIST

INTERTEK TESTING SERVICES

10.0 Test Equipment List

| Equipment No. | Equipment | Manufacturer | Model No. | Serial No. | Cal. Date | Due Date |
|---------------|------------------------|-----------------|--------------|------------|-----------|-----------|
| SZ061-03 | BiConiLog Antenna | ETS | 3142C | 00066460 | 14-May-15 | 14-May-16 |
| SZ185-01 | EMI Receiver | R&S | ESCI | 100547 | 7-Feb-15 | 7-Feb-16 |
| SZ061-07 | Pyramidal Horn Antenna | ETS | 3160-09 | 00083067 | 14-May-15 | 14-May-16 |
| SZ061-08 | Horn Antenna | ETS | 3115 | 00092346 | 14-May-15 | 14-May-16 |
| SZ061-06 | Active Loop Antenna | Electro-Metrics | EM-6876 | 217 | 29-Apr-15 | 29-Apr-16 |
| SZ056-03 | Spectrum Analyzer | R&S | FSP 30 | 101148 | 12-Mar-15 | 12-Mar-16 |
| SZ181-04 | Preamplifier | Agilent | 8449B | 3008A02474 | 7-Feb-15 | 7-Feb-16 |
| SZ188-01 | Anechoic Chamber | ETS | RFD-F/A-100 | 4102 | 19-Apr-14 | 19-Apr-16 |
| SZ062-02 | RF Cable | RADIAL | RG 213U | -- | 15-May-15 | 15-May-16 |
| SZ062-06 | RF Cable | RADIAL | 0.04-26.5GHz | -- | 15-May-15 | 15-May-16 |
| SZ062-12 | RF Cable | RADIAL | 0.04-26.5GHz | -- | 15-May-15 | 15-May-16 |
| SZ067-04 | Notch Filter | Micro-Tronics | BRM5070 2-02 | -- | 21-May-15 | 21-May-16 |