

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan

District Shenzhen, China 518057

Telephone: +86 (0) 755 2601 2053 Report No.: SZEM151100681302

Fax: +86 (0) 755 2671 0594 Page: 1 of 7

# **RF Exposure Evaluation Report**

Application No.: SZEM1511006813CR

Applicant: Guangdong Cheerson Hobby Technology Co., Ltd.

Manufacturer: Guangdong Cheerson Hobby Technology Co., Ltd.

Factory Guangdong Cheerson Hobby Technology Co., Ltd.

Product Name: WIFI camera

Model No.(EUT): C1

Add Model No.: C2, C3, C4, C5, CX-32C, CX-32W, CX-32W-TX, CX-32S, CX-33C,

CX-33W, CX-33W-TX, CX-33S, CX-35C, CX-35W, CX-35W-TX, CX-35S

**FCC ID:** 2AD6LGC23090609

**Standards:** 47 CFR Part 1.1307 (2014)

47 CFR Part 1.1310 (2014)

**Date of Receipt:** 2015-11-09

**Date of Test:** 2015-11-17 to 2015-11-27

**Date of Issue:** 2015-12-03

Test Result : PASS\*

#### Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

<sup>\*</sup> In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEM151100681302

Page: 2 of 7

## 2 Version

Revision Record					
Version	Chapter	Date	Modifier	Remark	
00		2015-12-03		Original	

Authorized for issue by:		
Tested By	Brix Chen	2015-11-27
	(Bill Chen) /Project Engineer	Date
Prepared By	Venus Wu	2015-10-28
	(Venus Wu) /Clerk	Date
Checked By	Eric Fu	2015-10-28
	(Eric Fu) /Reviewer	Date



Report No.: SZEM151100681302

Page: 3 of 7

### 3 Contents

		Pa	age
1	C	OVER PAGE	1
2	V	ERSION	2
3	C	CONTENTS	3
4	G	SENERAL INFORMATION	4
	4.1	CLIENT INFORMATION	4
	4.2	GENERAL DESCRIPTION OF EUT	4
	4.3	TEST LOCATION	5
	4.4	Test Facility	5
	4.5	DEVIATION FROM STANDARDS	5
	4.6	ABNORMALITIES FROM STANDARD CONDITIONS	5
	4.7	OTHER INFORMATION REQUESTED BY THE CUSTOMER	5
5	R	F EXPOSURE EVALUATION	6
	5.1	RF Exposure Compliance Requirement	6
	5.	.1.1 Limits	6
	5.	1.1.2 Test Procedure	6
		3 EUT RF Exposure Evaluation	



Report No.: SZEM151100681302

Page: 4 of 7

### 4 General Information

### 4.1 Client Information

Applicant:	Guangdong Cheerson Hobby Technology Co., Ltd.		
Address of Applicant:	FENGXIN NO.2 ROAD&LAIMEI ROAD FENGXIN INDUSTRIAL ZONE CHENGHAI SHANTOU GUANGDONG PROVINCE CHINA		
Manufacturer:	Guangdong Cheerson Hobby Technology Co., Ltd.		
Address of Manufacturer:	FENGXIN NO.2 ROAD&LAIMEI ROAD FENGXIN INDUSTRIAL ZONE CHENGHAI SHANTOU GUANGDONG PROVINCE CHINA		
Factory:	Guangdong Cheerson Hobby Technology Co., Ltd.		
Address of Factory:	FENGXIN NO.2 ROAD&LAIMEI ROAD FENGXIN INDUSTRIAL ZONE CHENGHAI SHANTOU GUANGDONG PROVINCE CHINA		

## 4.2 General Description of EUT

Product Name:	WIFI camera
Model No.:	C1
Operation Frequency:	2447MHz
Channel Numbers:	1
Channel Separation:	1 Channel (The manufacturer declare that only one channel was used.)
Type of Modulation:	IEEE for 802.11b: DSSS
Sample Type:	Mobile production
Antenna gain:	2.5dBi
Antenna Type:	Copper tube
Power supply:	DC 3.7V 700mAh 2.6Wh rechargeable battery

#### Remark:

Model No.: C1, C2, C3, C4, C5, CX-32C, CX-32W, CX-32W-TX, CX-32S, CX-33C, CX-33W,

CX-33W-TX, CX-33S, CX-35C, CX-35W, CX-35W-TX, CX-35S

Only the model C1 was tested, since the circuitry design, PCB layout, electrical components used, internal wiring and functions were identical for all above models. Only different on model name.



Report No.: SZEM151100681302

Page: 5 of 7

#### 4.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch E&E Lab

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

### 4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

#### A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

#### VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

#### FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

#### • Industry Canada (IC)

The 3m Semi-anechoic chambers and the 10m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-2, 4620C-3.

#### 4.5 Deviation from Standards

None

### 4.6 Abnormalities from Standard Conditions

None.

## 4.7 Other Information Requested by the Customer

None.



Report No.: SZEM151100681302

Page: 6 of 7

## 5 RF Exposure Evaluation

### 5.1 RF Exposure Compliance Requirement

#### **5.1.1 Limits**

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

Table 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)			
(A) Limits for Occupational/Controlled Exposures							
0.3–3.0 3.0–30 30–300 300–1500 1500–100,000	614 1842/f 61.4	1.63 4.89/f 0.163	*(100) *(900/f²) 1.0 f/300 5	6 6 6 6			
(B) Limits for General Population/Uncontrolled Exposure							
0.3–1.34 1.34–30 30–300 300–1500 1500–100,000	614 824/f 27.5	1.63 2.19/f 0.073	*(100) *(180/f²) 0.2 f/1500 1.0	30 30 30 30 30			

F= Frequency in MHz

Friis Formula

Friis transmission formula: Pd = (Pout\*G)/(4\* Pi \* R 2)

Where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### 5.1.2 Test Procedure

The battery provided by client enabled the EUT to transmit .



Report No.: SZEM151100681302

Page: 7 of 7

### 4.1.3 EUT RF Exposure Evaluation

Antenna Gain: 2.5dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.778 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Max Conducted	Output Power	Power Density	Limit	Result
Frequency	Peak Output	to Antenna	at R = 20 cm		
(MHz)	Power (dBm)	(mW)	(mW/cm <sup>2</sup> )		
2447	20.54	113.24	0.0225	1.0	PASS

Note: Refer to report No. SZEM151100681301 for EUT test Max Conducted Peak Output Power value. The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.