

FCC ID : 2AD7E-X500

Model No.: QuickScan II , X500

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB 447498 D01 General RF Exposure Guidance v06, section 4.3.1

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}^{16} \text{ where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

The test was performed with Bluetooth V4.0

This report is for BT classic mode

Antenna Gain = 2 dBi

GFSK mode

Frequency (MHz)	Output Power (dBm)	Target power (dBm)	Target power (mW)	Calculation Value	Threshold Value
2402	2.02	2 ± 1	1.995	0.618	3.0
2441	2.09	2 ± 1	1.995	0.623	3.0
2480	1.71	2 ± 1	1.995	0.628	3.0

$\pi/4$ DQPSK mode

Frequency (MHz)	Output Power (dBm)	Target power (dBm)	Target power (mW)	Calculation Value	Threshold Value
2402	1.80	2 ± 1	1.995	0.618	3.0
2441	1.74	2 ± 1	1.995	0.623	3.0
2480	1.33	2 ± 1	1.995	0.628	3.0

8DPSK mode

Frequency (MHz)	Output Power (dBm)	Target power (dBm)	Target power (mW)	Calculation Value	Threshold Value
2402	1.34	2 ±1	1.995	0.618	3.0
2441	1.73	2 ±1	1.995	0.623	3.0
2480	1.22	2 ±1	1.995	0.628	3.0

The test was performed with WiFi
Antenna Gain = 2 dBi

802.11b mode

Frequency (MHz)	Final Power (dBm)	Target power (dBm)	Target power (mW)	Calculation Value	Threshold Value
2412	9.28	9 ±0.5	8.913	2.768	3.0
2437	9.40	9 ±0.5	8.913	2.783	3.0
2462	9.34	9 ±0.5	8.913	2.797	3.0

802.11g mode

Frequency (MHz)	Final Power (dBm)	Target power (dBm)	Target power (mW)	Calculation Value	Threshold Value
2412	8.51	8 ±1	7.943	2.467	3.0
2437	8.86	8 ±1	7.943	2.480	3.0
2462	8.97	8 ±1	7.943	2.493	3.0

802.11n(20MHz) mode

Frequency (MHz)	Final Power (dBm)	Target power (dBm)	Target power (mW)	Calculation Value	Threshold Value
2412	8.99	8 ±1	7.943	2.467	3.0
2437	8.86	8 ±1	7.943	2.480	3.0
2462	8.55	8 ±1	7.943	2.493	3.0

802.11n(40MHz) mode

Frequency (MHz)	Final Power (dBm)	Target power (dBm)	Target power (mW)	Calculation Value	Threshold Value
2422	7.46	7 ±1	6.310	1.964	3.0
2437	7.29	7 ±1	6.310	1.970	3.0
2452	7.37	7 ±1	6.310	1.976	3.0

Threshold at which no SAR required is ≤ 3.0 for 1-g SAR, Separation distance is 5mm.

Conclusion: No SAR is required.

SIMULTANEOUS TRANSMISSION EVALUATION

N/A