

RF EXPOSURE INFORMATION**Arc Mobile Control Adapter**

HW version: 1.0

SW version: 1.0

Version 1.0 Draft

6.3.2015

Kemppi Oy

Postiosoite PL 13, 15801 Lahti Puhelin (03) 899 11
Pankki Nordea, Lahti Faksi (03) 899 428
ALV rek. FI 20518261 Sähköposti export@kemppi.com
Y-tunnus 2051826-1 Internet www.kemppi.com

Address PO Box 13, FIN-15801 Lahti, Finland
Bank Nordea, Lahti Finland
VAT number FI20518261
Business ID 2051826-1

Phone +358 3 899 11
Fax +358 3 899 428
E-mail export@kemppi.com
Internet www.kemppi.com

Table of Contents

Table of Contents	2
1 MPE limit for uncontrolled exposure at prediction frequency	3
2 Prediction of MPE limit at a given distance for Bluetooth	4
2.1 Power density	4
2.2 Duty cycle and duty factor	4
3 Prediction of MPE limit at a given distance for NFC.....	5
3.1 Power density	5
3.2 E/H field strength	5

Kemppi Oy

Postiosoite PL 13, 15801 Lahti Puhelin (03) 899 11
Pankki Nordea, Lahti Faksi (03) 899 428
ALV rek. FI 20518261 Sähköposti export@kemppi.com
Y-tunnus 2051826-1 Internet www.kemppi.com

Address PO Box 13, FIN-15801 Lahti, Finland
Bank Nordea, Lahti Finland
VAT number FI20518261
Business ID 2051826-1

Phone +358 3 899 11
Fax +358 3 899 428
E-mail export@kemppi.com
Internet www.kemppi.com

1 MPE limit for uncontrolled exposure at prediction frequency

For Bluetooth 1 mW/cm² , frequency range 1.5 – 100 GHz

For NFC $S = \frac{180}{f[\text{MHz}]^2} = \frac{180}{13.56^2} = 0.98 \mu\text{W}/\text{cm}^2$, frequency 13.56 MHz

Reference to OET Bulletin 65, ed. 97-01, page 73

Appendix A, Table 1, B, page 67

(B) Limits for General Population/Uncontrolled Exposure

Kemppi Oy

Postiosoite PL 13, 15801 Lahti Puhelin (03) 899 11
Pankki Nordea, Lahti Faksi (03) 899 428
ALV rek. FI 20518261 Sähköposti export@kemppi.com
Y-tunnus 2051826-1 Internet www.kemppi.com

Address PO Box 13, FIN-15801 Lahti, Finland
Bank Nordea, Lahti Finland
VAT number FI20518261
Business ID 2051826-1

Phone +358 3 899 11
Fax +358 3 899 428
E-mail export@kemppi.com
Internet www.kemppi.com

2 Prediction of MPE limit at a given distance for Bluetooth

2.1 Power density

Product category "Mobile device"

$$S = \frac{EIRP}{4\pi r^2}$$

where

EIRP	9.5 dBm = 8.9 mW
Prediction distance r	0.20 m
Time averaging	100 %
Prediction frequency	2450 MHz
Power density at prediction frequency	0.018 W/m ²
	equals to 0.0018 mW/cm²

MPE limit for uncontrolled exposure	1 mW/cm ²
-------------------------------------	----------------------

2.2 Duty cycle and duty factor

According to manufacturer's test specification:

	Duty cycle	Duty factor
Basic rate	77.93 %	1.08 dB
EDR	77.87 %	1.09 dB

Kemppi Oy

3 Prediction of MPE limit at a given distance for NFC

3.1 Power density

$$S = \frac{EIRP}{4\pi r^2}$$

where

EIRP		4.9 dBμA/m@10m
	equals to	-28.4 dBm
	equals to	0.0015 mW
Prediction distance r		0.20 m
Time averaging		100 %
Prediction frequency		13.56 MHz
Power density at prediction frequency		2.98 μW/m ²
	equals to	0.298 nW/cm²

MPE limit for uncontrolled exposure		97.9 μW/cm ²
-------------------------------------	--	-------------------------

3.2 E/H field strength

H-field strength		4.9 dBμA/m@10m
	equals to	1.8 μA/m
E-field strength		56.4 dBμV/m@10m
	equals to	661 μV/m
Prediction frequency		13.56 MHz
Time averaging		100%
MPE limit for uncontrolled exposure		
H-field limit = 2.19/f =		162 mA/m
E-field limit = 824/f =		60.8 V/m

Reference to OET Bulletin 65, ed. 97-01, page 73

Appendix A, Table 1, B, page 67

(B) Limits for General Population/Uncontrolled Exposure

Kemppi Oy