

APPLICATION CERTIFICATION
On Behalf of
SHENZHEN FORTAT SKYMARK TECHNOLOGY CO. LTD

Bluetooth Speaker
Model No.: MK-SPB11-BC8, MK-SPB11-BP8, MK-SPB11-TPC

FCC ID: 2AD8S-MKSPB11BC8

Prepared for : SHENZHEN FORTAT SKYMARK TECHNOLOGY
CO. LTD
Address : NO. 1, DUNBEI INDUSTRIAL AREA, LONGHUA
DISTRICT, SHENZHEN, CHINA
Prepared by : ACCURATE TECHNOLOGY CO., LTD
Address : F1, Bldg. A, Chan Yuan New Material Port, Keyuan
Rd. Science & Industry Park, Nan Shan, Shenzhen,
Guangdong P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report Number : ATE20150279
Date of Test : Feb 04, 2015-Feb 10, 2015
Date of Report : Feb 10, 2015

TABLE OF CONTENTS

Description	Page
Test Report Certification	
1. GENERAL INFORMATION	5
1.1. Description of Device (EUT).....	5
1.2. Description of Test Facility	6
1.3. Measurement Uncertainty	6
2. MEASURING DEVICE AND TEST EQUIPMENT	7
3. OPERATION OF EUT DURING TESTING	8
3.1. Operating Mode	8
3.2. Configuration and peripherals	8
4. TEST PROCEDURES AND RESULTS	9
5. 20DB BANDWIDTH TEST.....	10
5.1. Block Diagram of Test Setup.....	10
5.2. The Requirement For Section 15.247(a)(1).....	10
5.3. EUT Configuration on Measurement	10
5.4. Operating Condition of EUT	10
5.5. Test Procedure	11
5.6. Test Result	11
6. CARRIER FREQUENCY SEPARATION TEST.....	16
6.1. Block Diagram of Test Setup.....	16
6.2. The Requirement For Section 15.247(a)(1).....	16
6.3. EUT Configuration on Measurement	16
6.4. Operating Condition of EUT	16
6.5. Test Procedure	17
6.6. Test Result	17
7. NUMBER OF HOPPING FREQUENCY TEST	23
7.1. Block Diagram of Test Setup.....	23
7.2. The Requirement For Section 15.247(a)(1)(iii).....	23
7.3. EUT Configuration on Measurement	23
7.4. Operating Condition of EUT	23
7.5. Test Procedure	24
7.6. Test Result	24
8. DWELL TIME TEST	26
8.1. Block Diagram of Test Setup.....	26
8.2. The Requirement For Section 15.247(a)(1)(iii).....	26
8.3. EUT Configuration on Measurement	26
8.4. Operating Condition of EUT	26
8.5. Test Procedure	26
8.6. Test Result	27
9. MAXIMUM PEAK OUTPUT POWER TEST	42
9.1. Block Diagram of Test Setup.....	42
9.2. The Requirement For Section 15.247(b)(1).....	42
9.3. EUT Configuration on Measurement	42
9.4. Operating Condition of EUT	42
9.5. Test Procedure	42
9.6. Test Result	43

10. RADIATED EMISSION TEST	49
10.1. Block Diagram of Test Setup.....	49
10.2. The Limit For Section 15.247(d)	49
10.3. Restricted bands of operation	50
10.4. Configuration of EUT on Measurement	50
10.5. Test Procedure	51
10.6. The Field Strength of Radiation Emission Measurement Results	51
11. BAND EDGE COMPLIANCE TEST	64
11.1. Block Diagram of Test Setup.....	64
11.2. The Requirement For Section 15.247(d)	64
11.3. EUT Configuration on Measurement	64
11.4. Operating Condition of EUT	64
11.5. Test Procedure	65
11.6. Test Result	65
12. AC POWER LINE CONDUCTED EMISSION FOR FCC PART 15 SECTION 15.207(A) ..	88
12.1. Block Diagram of Test Setup.....	88
12.2. Shielding Room Test Setup Diagram	88
12.3. The Emission Limit	88
12.4. Configuration of EUT on Measurement	89
12.5. Operating Condition of EUT	89
12.6. Test Procedure	89
12.7. Power Line Conducted Emission Measurement Results	89
13. ANTENNA REQUIREMENT.....	93
13.1. The Requirement	93
13.2. Antenna Construction	93

Test Report Certification

Applicant& address : SHENZHEN FORTAT SKYMARK TECHNOLOGY CO. LTD
NO. 1, DUNBEI INDUSTRIAL AREA, LONGHUA DISTRICT,
SHENZHEN, CHINA

Manufacturer& address : SHENZHEN FORTAT SKYMARK TECHNOLOGY CO. LTD
NO. 1, DUNBEI INDUSTRIAL AREA, LONGHUA DISTRICT,
SHENZHEN, CHINA

Product : Bluetooth Speaker

Model No. : MK-SPB11-BC8, MK-SPB11-BP8, MK-SPB11-TPC

(Note: These samples are same except for the model number is different for the marketing requirement. So we prepare the MK-SPB11-BC8 for test.)

Trade name : MERKURY


Measurement Procedure Used:


FCC Rules and Regulations Part 15 Subpart C Section 15.247
ANSI C63.4- 2009

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.247 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.

Date of Test : Feb 04, 2015-Feb 10, 2015
Date of Report : Feb 10, 2015

Prepared by : 
(Tim.zhang, Engineer)

Approved & Authorized Signer : 
(Sean Liu, Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	:	Bluetooth Speaker
Model Number	:	MK-SPB11-BC8, MK-SPB11-BP8, MK-SPB11-TPC
Frequency Band	:	2402MHz-2480MHz
Number of Channels	:	79
Modulation type	:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Antenna Gain	:	-0.68 dBi
Bluetooth version	:	Bluetooth V2.1+EDR
Antenna type	:	PCB Antenna
Power Supply	:	DC3.7V(Lithium ion battery) & DC 5V(Powered by USB Port)
Applicant	:	SHENZHEN FORTAT SKYMARK TECHNOLOGY CO. LTD
Address	:	NO. 1, DUNBEI INDUSTRIAL AREA, LONGHUA DISTRICT, SHENZHEN, CHINA
Manufacturer	:	SHENZHEN FORTAT SKYMARK TECHNOLOGY CO. LTD
Address	:	NO. 1, DUNBEI INDUSTRIAL AREA, LONGHUA DISTRICT, SHENZHEN, CHINA
Date of sample received	:	Feb 04, 2015
Date of Test	:	Feb 04, 2015-Feb 10, 2015

1.2. Description of Test Facility

EMC Lab : Accredited by TUV Rheinland Shenzhen

Listed by FCC

The Registration Number is 752051

Listed by Industry Canada

The Registration Number is 5077A-2

Accredited by China National Accreditation Committee
for Laboratories

The Certificate Registration Number is L3193

Name of Firm : ACCURATE TECHNOLOGY CO. LTD

Site Location : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.
Science & Industry Park, Nanshan, Shenzhen, Guangdong
P.R. China

1.3. Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2

Radiated emission expanded uncertainty = 3.08dB, k=2
(9kHz-30MHz)

Radiated emission expanded uncertainty = 4.42dB, k=2
(30MHz-1000MHz)

Radiated emission expanded uncertainty = 4.06dB, k=2
(Above 1GHz)

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 11, 2015	Jan. 10, 2016
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 11, 2015	Jan. 10, 2016
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 11, 2015	Jan. 10, 2016
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 11, 2015	Jan. 10, 2016
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 15, 2015	Jan. 14, 2016
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 15, 2015	Jan. 14, 2016
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 15, 2015	Jan. 14, 2016
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1067	Jan. 15, 2015	Jan. 14, 2016
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 11, 2015	Jan. 10, 2016
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 11, 2015	Jan. 10, 2016
Highpass Filter	Wainwright Instruments	WHKX3.6/18 G-10SS	N/A	Jan. 11, 2015	Jan. 10, 2016
Band Reject Filter	Wainwright Instruments	WRCG2400/2 485-2375/2510 -60/11SS	N/A	Jan. 11, 2015	Jan. 10, 2016

3. OPERATION OF EUT DURING TESTING

3.1.Operating Mode

The mode is used: Transmitting mode


Low Channel: 2402MHz

Middle Channel: 2441MHz

High Channel: 2480MHz

Hopping

3.2.Configuration and peripherals



(EUT: Bluetooth Speaker)

Note: USB port of EUT is only used to charge, there is no data transfer function

4. TEST PROCEDURES AND RESULTS

FCC Rules	Description of Test	Result
Section 15.207	Power Line Conducted Emission	Compliant
Section 15.247(a)(1)	20dB Bandwidth Test	Compliant
Section 15.247(a)(1)	Carrier Frequency Separation Test	Compliant
Section 15.247(a)(1)(iii)	Number Of Hopping Frequency Test	Compliant
Section 15.247(a)(1)(iii)	Dwell Time Test	Compliant
Section 15.247(b)(1)	Maximum Peak Output Power Test	Compliant
Section 15.247(d) Section 15.209	Radiated Emission Test	Compliant
Section 15.247(d)	Band Edge Compliance Test	Compliant
Section 15.203	Antenna Requirement	Compliant

5. 20DB BANDWIDTH TEST

5.1. Block Diagram of Test Setup



(EUT: Bluetooth Speaker)

5.2. The Requirement For Section 15.247(a)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

5.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.4. Operating Condition of EUT

5.4.1. Setup the EUT and simulator as shown as Section 5.1.

5.4.2. Turn on the power of all equipment.

5.4.3. Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

5.5. Test Procedure

5.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

5.5.2. Set RBW of spectrum analyzer to 30 kHz and VBW to 100 kHz.

5.5.3. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.


5.6. Test Result

Channel	Frequency (MHz)	GFSK 20dB Bandwidth (MHz)	$\Pi/4$ -DQPSK 20dB Bandwidth (MHz)	8DPSK 20dB Bandwidth (MHz)	Result
Low	2402	0.975	1.285	1.256	Pass
Middle	2441	0.897	1.274	1.268	Pass
High	2480	0.929	1.274	1.256	Pass

The spectrum analyzer plots are attached as below.


Mode 1: GFSK Link Mode

Low Channel: 2402MHz




Date: 6.Feb.2015 16:35:21

Middle Channel: 2441MHz



Date: 6.Feb.2015 16:36:19


High Channel: 2480MHz



Date: 6.Feb.2015 16:37:34


Mode 2: $\pi/4$ DQPSK Link Mode

Low Channel: 2402MHz




Date: 6.Feb.2015 16:43:22

Middle Channel: 2441MHz



Date: 6.Feb.2015 16:42:18


High Channel: 2480MHz



Date: 6.Feb.2015 16:40:49


Mode 3: 8DPSK Link Mode

Low Channel: 2402MHz




Date: 6.Feb.2015 16:44:55

Middle Channel: 2441MHz



Date: 6.Feb.2015 16:46:20

High Channel: 2480MHz



Date: 6.Feb.2015 16:47:24

6. CARRIER FREQUENCY SEPARATION TEST

6.1. Block Diagram of Test Setup



(EUT: Bluetooth Speaker)

6.2. The Requirement For Section 15.247(a)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

6.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.4. Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 6.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

6.5. Test Procedure

6.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

6.5.2. Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz. Adjust Span to 3 MHz.

6.5.3. Set the adjacent channel of the EUT maxhold another trace.

6.5.4. Measurement the channel separation

6.6. Test Result

GFSK

Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.0058	25KHz or 20dB bandwidth	PASS
	2403			
Middle	2440	1.0029	25KHz or 20dB bandwidth	PASS
	2441			
High	2479	1.0029	25KHz or 20dB bandwidth	PASS
	2480			

Π/4-DQPSK

Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.0029	25KHz or 2/3*20dB bandwidth	PASS
	2403			
Middle	2440	1.0029	25KHz or 2/3*20dB bandwidth	PASS
	2441			
High	2479	1.0029	25KHz or 2/3*20dB bandwidth	PASS
	2480			


8DPSK

Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.0029	25KHz or 2/3*20dB bandwidth	PASS
	2403			
Middle	2440	1.0029	25KHz or 2/3*20dB bandwidth	PASS
	2441			
High	2479	1.0029	25KHz or 2/3*20dB bandwidth	PASS
	2480			

The spectrum analyzer plots are attached as below.


Mode 1: GFSK Link Mode

Low Channel: 2402MHz




Date: 6.Feb.2015 17:12:44

Middle Channel: 2441MHz



Date: 6.Feb.2015 17:13:21


High Channel: 2480MHz



Date: 6.Feb.2015 17:13:59


Mode 2: $\pi/4$ DQPSK Link Mode

Low Channel: 2402MHz




Date: 6.Feb.2015 17:10:06

Middle Channel: 2441MHz



Date: 6.Feb.2015 17:09:27


High Channel: 2480MHz



Date: 6.Feb.2015 17:08:33


Mode 3: 8DPSK Link Mode

Low Channel: 2402MHz




Date: 6.Feb.2015 17:06:10

Middle Channel: 2441MHz



Date: 6.Feb.2015 17:07:04


High Channel: 2480MHz



Date: 6.Feb.2015 17:07:48

7. NUMBER OF HOPPING FREQUENCY TEST

7.1. Block Diagram of Test Setup



(EUT: Bluetooth Speaker)

7.2. The Requirement For Section 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

7.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.4. Operating Condition of EUT

7.4.1. Setup the EUT and simulator as shown as Section 7.1.

7.4.2. Turn on the power of all equipment.

7.4.3. Let the EUT work in TX (Hopping on) modes measure it.

7.5. Test Procedure

7.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

7.5.2. Set the spectrum analyzer as Span=83.5MHz, RBW=100 kHz, VBW=300 kHz.


7.5.3. Max hold, view and count how many channel in the band.

7.6. Test Result

Total number of hopping channel	Measurement result(CH)	Limit(CH)
	79	≥ 15


The spectrum analyzer plots are attached as below.

Number of hopping channels(GFSK)




Date: 6.Feb.2015 17:11:55

Number of hopping channels($\Pi/4$ -DQPSK)



Date: 6.Feb.2015 17:04:26


Number of hopping channels(8DPSK)



Date: 6.Feb.2015 17:11:09

8. DWELL TIME TEST

8.1. Block Diagram of Test Setup



(EUT: Bluetooth Speaker)

8.2. The Requirement For Section 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

8.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

8.4. Operating Condition of EUT

8.4.1. Setup the EUT and simulator as shown as Section 8.1.

8.4.2. Turn on the power of all equipment.

8.4.3. Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

8.5. Test Procedure

8.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

8.5.2. Set center frequency of spectrum analyzer = operating frequency.

8.5.3. Set the spectrum analyzer as RBW=1MHz, VBW=3MHz, Span=0Hz, Adjust Sweep=5ms, 10ms, 15ms. Get the pulse time.

8.5.4.Repeat above procedures until all frequency measured were complete.

8.6.Test Result

GFSK Mode

Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2402	0.5362	171.58	400
	2441	0.5290	169.28	400
	2480	0.5362	171.58	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(2*79)) \times 31.6$				
DH3	2402	1.8261	292.18	400
	2441	1.8116	289.86	400
	2480	1.8116	289.86	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(4*79)) \times 31.6$				
DH5	2402	3.0725	327.73	400
	2441	3.0725	327.73	400
	2480	3.0725	327.73	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(6*79)) \times 31.6$				

Π/4-DQPSK


Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2402	0.5507	176.22	400
	2441	0.5507	176.22	400
	2480	0.5435	173.92	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(2*79)) \times 31.6$				
DH3	2402	1.8261	292.18	400
	2441	1.8261	292.18	400
	2480	1.8043	288.69	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(4*79)) \times 31.6$				
DH5	2402	3.0435	324.64	400
	2441	3.0652	326.95	400
	2480	2.9783	317.69	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(6*79)) \times 31.6$				

8DPSK Mode

Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2402	0.5435	173.92	400
	2441	0.5435	173.92	400
	2480	0.5435	173.92	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(2 \times 79)) \times 31.6$				
DH3	2402	1.8188	291.01	400
	2441	1.8188	291.01	400
	2480	1.8188	291.01	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(4 \times 79)) \times 31.6$				
DH5	2402	3.0797	328.50	400
	2441	3.0580	326.19	400
	2480	3.0797	328.50	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(6 \times 79)) \times 31.6$				


The spectrum analyzer plots are attached as below.

DH1 Low channel




Date: 6.Feb.2015 17:17:31

DH1 Middle channel




Date: 6.Feb.2015 17:16:42

DH1 High channel




Date: 6.Feb.2015 10:52:51

DH3 Low channel




Date: 6.Feb.2015 17:18:35

DH3 Middle channel




Date: 6.Feb.2015 17:19:27

DH3 High channel




Date: 6.Feb.2015 17:20:10

DH5 Low channel




Date: 6.Feb.2015 17:22:24

DH5 Middle channel




Date: 6.Feb.2015 17:21:42

DH5 High channel




Date: 6.Feb.2015 17:21:05

2DH1 Low channel




Date: 6.Feb.2015 17:29:05

2DH1 Middle channel




Date: 6.Feb.2015 17:29:38

2DH1 High channel




Date: 6.Feb.2015 17:30:15

2DH3 Low channel




Date: 6.Feb.2015 17:27:43

2DH3 Middle channel




Date: 6.Feb.2015 17:26:58

2DH3 High channel




Date: 6.Feb.2015 17:26:13

2DH5 Low channel




Date: 6.Feb.2015 11:01:07

2DH5 Middle channel




Date: 6.Feb.2015 10:59:49

2DH5 High channel




Date: 6.Feb.2015 10:58:57

3DH1 Low channel




Date: 6.Feb.2015 17:32:16

3DH1 Middle channel




Date: 6.Feb.2015 17:31:38

3DH1 High channel




Date: 6.Feb.2015 17:31:01

3DH3 Low channel




Date: 6.Feb.2015 17:33:04

3DH3 Middle channel




Date: 6.Feb.2015 17:33:38

3DH3 High channel




Date: 6.Feb.2015 17:34:16

3DH5 Low channel




Date: 6.Feb.2015 17:36:56

3DH5 Middle channel



Date: 6.Feb.2015 17:36:20


3DH5 High channel



Date: 6.Feb.2015 17:35:41

9. MAXIMUM PEAK OUTPUT POWER TEST

9.1. Block Diagram of Test Setup



(EUT: Bluetooth Speaker)

9.2. The Requirement For Section 15.247(b)(1)

Section 15.247(b)(1): For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

9.3. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

9.4. Operating Condition of EUT

9.4.1. Setup the EUT and simulator as shown as Section 9.1.

9.4.2. Turn on the power of all equipment.

9.4.3. Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

9.5. Test Procedure

9.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

9.5.2. Set RBW of spectrum analyzer to 1MHz and VBW to 3MHz for GFSK mode

9.5.3. Set RBW of spectrum analyzer to 3MHz and VBW to 3MHz for other mode

9.5.4. Measurement the maximum peak output power.

9.6. Test Result

GFSK Mode

Channel	Frequency (MHz)	Peak Output Power (dBm/W)	Limits dBm / W
Low	2402	2.31/0.0017	30 / 1.0
Middle	2441	1.65/0.0015	30 / 1.0
High	2480	-1.02/0.0008	30 / 1.0

Π/4-DQPSK Mode

Channel	Frequency (MHz)	Peak Output Power (dBm/W)	Limits dBm / W
Low	2402	1.98/0.0016	21 / 0.125
Middle	2441	1.23/0.0013	21 / 0.125
High	2480	-0.45/0.0009	21 / 0.125


8DPSK Mode

Channel	Frequency (MHz)	Peak Output Power (dBm/W)	Limits dBm / W
Low	2402	2.11/0.0016	21 / 0.125
Middle	2441	1.42/0.0014	21 / 0.125
High	2480	-0.24/0.0009	21 / 0.125

The spectrum analyzer plots are attached as below.


GFSK Mode

Low channel




Date: 6.Feb.2015 16:54:00

Middle channel



Date: 6.Feb.2015 16:53:28


High channel



Date: 6.Feb.2015 16:52:59


II/4-DQPSK Mode

Low channel




Date: 6.Feb.2015 16:50:45

Middle channel



Date: 6.Feb.2015 16:51:13


High channel



Date: 6.Feb.2015 16:52:02


8DPSK Mode

Low channel




Date: 6.Feb.2015 16:49:57

Middle channel



Date: 6.Feb.2015 16:49:21

High channel




Date: 6.Feb.2015 16:48:43

10. RADIATED EMISSION TEST


10.1. Block Diagram of Test Setup

10.1.1. Block diagram of connection between the EUT and simulators



(EUT: Bluetooth Speaker)

10.1.2. Anechoic Chamber Test Setup Diagram



10.2. The Limit For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

10.3.Restricted bands of operation

10.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510

²Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

10.4.Configuration of EUT on Measurement

The equipment is installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

10.5. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2009 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

The frequency range from 30MHz to 25000MHz is checked.

Result = Reading + Corrected Factor

Where Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

During the radiated emission test, the spectrum analyzer was set with the following configurations:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for peak measurement with peak detector at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average measurement with peak detection at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

10.6. The Field Strength of Radiation Emission Measurement Results

Note: 1. We tested GFSK mode, $\pi/4$ -DQPSK Mode & 8DPSK mode and recorded the worst case data (GFSK mode) for all test mode.

2. The 18-25GHz emissions are not reported, because the levels are too low against the limit.

Below 1GHz



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ricky2015 #194
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Bluetooth Speaker
Mode: TX 2402MHz
Model: MK-SPB11-BC8
Manufacturer: FORTAT SKYMARK

Polarization: Horizontal
Power Source: DC 5V
Date: 2015/02/08
Time: 13:42:51
Engineer Signature: STAR
Distance: 3m

Note: Report No.:ATE20150279




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	297.5459	55.07	-17.92	37.15	46.00	-8.85	QP			
2	413.9915	57.83	-15.42	42.41	46.00	-3.59	QP			
3	531.2910	44.64	-13.25	31.39	46.00	-14.61	QP			

Job No.: Ricky2015 #195
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Bluetooth Speaker
Mode: TX 2402MHz
Model: MK-SPB11-BC8
Manufacturer: FORTAT SKYMARK

Polarization: Vertical
Power Source: DC 5V
Date: 2015/02/08
Time: 13:44:37
Engineer Signature: STAR
Distance: 3m

Note: Report No.:ATE20150279




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	297.5459	59.55	-17.92	41.63	46.00	-4.37	peak			
2	413.9915	59.89	-15.42	44.47	46.00	-1.53	peak			
3	531.2910	46.28	-13.25	33.03	46.00	-12.97	peak			

Job No.: Ricky2015 #198
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Bluetooth Speaker
Mode: TX 2441MHz
Model: MK-SPB11-BC8
Manufacturer: FORTAT SKYMARK

Polarization: Horizontal
Power Source: DC 5V
Date: 2015/02/08
Time: 13:50:19
Engineer Signature: STAR
Distance: 3m

Note: Report No.:ATE20150279




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	297.5459	48.28	-17.92	30.36	46.00	-15.64	QP			
2	413.9915	56.06	-15.42	40.64	46.00	-5.36	QP			
3	425.7933	50.75	-15.28	35.47	46.00	-10.53	QP			

Job No.: Ricky2015 #197
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Bluetooth Speaker
Mode: TX 2441MHz
Model: MK-SPB11-BC8
Manufacturer: FORTAT SKYMARK

Polarization: Vertical
Power Source: DC 5V
Date: 2015/02/08
Time: 13:49:22
Engineer Signature: STAR
Distance: 3m

Note: Report No.:ATE20150279



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	297.5459	59.61	-17.92	41.69	46.00	-4.31	QP			
2	403.9335	54.65	-15.57	39.08	46.00	-6.92	QP			
3	413.9915	60.22	-15.42	44.80	46.00	-1.20	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ricky2015 #199
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Bluetooth Speaker
Mode: TX 2480MHz
Model: MK-SPB11-BC8
Manufacturer: FORTAT SKYMARK

Polarization: Horizontal
Power Source: DC 5V
Date: 2015/02/08
Time: 13:51:41
Engineer Signature: STAR
Distance: 3m

Note: Report No.:ATE20150279



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	297.5459	54.12	-17.92	36.20	46.00	-9.80	QP			
2	413.9915	54.97	-15.42	39.55	46.00	-6.45	QP			
3	531.2910	40.96	-13.25	27.71	46.00	-18.29	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ricky2015 #200
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Bluetooth Speaker
Mode: TX 2480MHz
Model: MK-SPB11-BC8
Manufacturer: FORTAT SKYMARK

Polarization: Vertical
Power Source: DC 5V
Date: 2015/02/08
Time: 13:52:37
Engineer Signature: STAR
Distance: 3m

Note: Report No.:ATE20150279



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	297.5459	59.48	-17.92	41.56	46.00	-4.44	QP			
2	413.9915	59.81	-15.42	44.39	46.00	-1.61	QP			
3	531.2910	47.18	-13.25	33.93	46.00	-12.07	QP			

Above 1GHz



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: alen #3597
Standard: FCC 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Bluetooth Speaker
Mode: TX 2402MHz
Model: MK-SPB11-BC8
Manufacturer: FORTAT SKYMARK

Polarization: Horizontal
Power Source: DC 5V
Date: 2015/02/08
Time: 9/39/04
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20150279




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2401.753	96.29	-6.76	89.53	114.00	35.53	peak			
2	2401.753	90.02	-6.76	83.26	94.00	29.26	peak			
3	4804.110	54.51	-1.59	52.92	54.00	-1.08	peak			
4	11735.245	42.89	6.25	49.14	54.00	-4.86	peak			

Job No.: alen #3596
Standard: FCC 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Bluetooth Speaker
Mode: TX 2402MHz
Model: MK-SPB11-BC8
Manufacturer: FORTAT SKYMARK

Polarization: Vertical
Power Source: DC 5V
Date: 2015/02/08
Time: 9/37/17
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20150279



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2401.753	97.03	-6.76	90.27	114.00	36.27	peak			
2	2401.753	90.58	-6.76	83.82	94.00	29.82	peak			
3	4804.110	54.64	-1.59	53.05	54.00	-0.95	peak			
4	13797.088	40.50	9.87	50.37	54.00	-3.63	peak			

Job No.: alen #3598

Standard: FCC 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Bluetooth Speaker

Mode: TX 2441MHz

Model: MK-SPB11-BC8

Manufacturer: FORTAT SKYMARK

Polarization: Horizontal

Power Source: DC 5V


Date: 2015/02/08

Time: 9/42/01

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20150279



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2440.751	99.30	-6.64	92.66	114.00	38.66	peak			
2	2440.751	93.01	-6.64	86.37	94.00	32.37	peak			
3	4888.151	53.33	-1.33	52.00	54.00	-2.00	peak			
4	11803.280	43.28	6.32	49.60	54.00	-4.40	peak			