

Nokia Solutions and Network, OY 2000 W. Lucent Lane, Naperville, IL 60563

June 11, 2018

Timco Engineering Inc. FCC Authorized Telecommunication Certification Body (TCB) 849 N.W. State Road 45 P.O. Box 370 Newberry, Florida 32669

Subject: Application for C2PC Equipment Authorization under FCC ID: 2AD8UAZRBRH1 for Nokia Low Power AirScale Micro LAA RRH with New Antenna, Operating in the Band 46 UNII-1/3 Bands

Dear Examiner:

The Nokia AirScale Micro Remote Radio Head (RRH) (hereinafter referred to as "AZRB") is a low power RRH operating in the Band 46 unlicensed spectrum of 5.18-5.24 GHz (UNII-1) and 5.745-5.825 MHz (UNII-3) under the regulations of FCC Title 47 Part 15 Subpart E, Unlicensed National Information Infrastructure (UNII) Devices. The AZRB received its FCC certification on April 25, 2018 under FCC ID: 2AD8UAZRBRH1 for operation in the UNII-1 and UNII-3 frequency spectrums as a Point-to-Multipoint Master Device.

The AZRB supports LTE (Long Term Evolution) License Assisted Access (LAA) technology and one to three 20MHz carriers with (aggregated) bandwidth of 20/40/60MHz and a maximum RF power of 0.5W at each of its two MIMO transmit ports.

In the original certification, two omni-directional antennas and three directional antennas have been approved. Among them, two antennas which have the highest gains of each type, i.e., GQ2410-06645 omni-directional antenna with a maximum gain of 5.9dBi and 2205 directional antenna with a maximum gain of 9.5dBi, were tested with the AZRB. Now a new omni-directional antenna GO4806-06664 with a maximum gain of 6.0 dBi is added which is 0.1dB higher than that of GQ2410-06645 omni-directional antenna tested. There is no change on the total power output, the software and the hardware of AZRB. There are no modifications in the transmitting and receiving frequency ranges.

Per FCC Section 15.204(c) and KDB 178919 D01 (Permissive Change Policy) Section II.A, any antenna that is of the same type and of equal or less directional gain as an antenna that is authorized with the intentional radiator may be marketed with, and used with, that intentional radiator. No retesting of this system configuration is required. The marketing or use of a system configuration that employs an antenna of a different type, or that operates at a higher gain, than the antenna authorized with the intentional radiator is not permitted unless the procedures specified in Section 2.1043 are followed. The antenna type refers to antennas that have similar in-band and out-of-band radiation patterns. Any new antenna type, or higher gain antenna, approved under Part 15 requires a Class II permissive change, and the requirements of Section 15.203 must be met.

A Class II permissive authorization is thus requested to authorize the new antenna GO4806-06664 for AZRB under the existing FCC ID 2AD8UAZRBRH1. Per FCC 2.1041(a), the technical requirements specified in FCC 15 Subpart E Section 15.407 needs to be met. Per 2.1043(b)(2), when a Class II permissive change is made by the grantee, the grantee shall provide complete information and the results of tests of the characteristics affected by such change.



Therefore, only the technical requirements in 15.407 affected were evaluated. The guidelines and guidance provided in the KDB 789033 D02 v02r01 (Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices, Part 15, Subpart E) were followed for the application and evaluation for compliance. The ANSI C63.10-2013 was followed for measurement methods and procedures.

Enclosed in this application package are FCC 731 Form, the required measurement data and other required exhibits specific to this request for authorization of the subject product. The measurement exhibits attached to this application demonstrate full compliance with FCC Part 15.407 following the procedural requirements specified in FCC Part 2 Subpart J – Equipment Authorization Procedures.

The key data are summarized below.

FCC ID: 2AD8UAZRBRH1

FCC Rules: Part 15 Subpart E Section 15.407 – UNII Devices

Frequency Range: E-UTRAN Band 46, 5.18-5.24GHz (UNII-1) & 5.745-5.825 GHz (UNII-3)

Output Power: Up to 1W

Operation Mode: Master Device, Point to Multipoint

Carriers: 1~3 20MHz Carriers with (Aggregated) Bandwidth 20/40/60MHz

The updated antenna list per 1.1033(b)(4), KDB 353028 D01 and KDB 178919 D01 Section II requirements includes the information of the newly added antenna in Exhibit 2.

The supporting exhibits are assembled and presented in accordance with the *Table of Contents* attached below.

Should there be any questions or procedural issues please feel free to contact me by email and/or phone. The contacts at Nokia will comply with any request for additional information should the need arise.

Sincerely,

Terry Schwenk

R&D Engineer

Nokia Solutions and Networks

Phone: 847-809-6952

email: terry.schwenk@nokia.com

12 CM



Primary Administrative Contact

Raymond J. Johnson Technical Manager Global Product Compliance Laboratory Building 5B-111 600 Mountain Avenue Murray Hill, NJ 07974

Phone: 908-582-5575

email: ray.johnson@nokia-bell-labs.com

Filing Engineer

Qin Yu

Global Product Compliance Laboratory

Phone 469-991-1892

email: q.yu@nokia-bell-labs.com



TABLE OF CONTENTS

Cover Letter

Confidentiality Request Letter

Required Exhibits*:

EXHIBIT	FCC RULES	CONTENTS
Exhibit 1	Section 2.1033(a)	TCB Application Form 731
Exhibit 2	Sections 2.1033 (b)(4), 15.203 & 15.204, KDB 353028 D01 & 178919 D01 II	Description of Antennas
Exhibit 3	Section 2.1033 (b)(14)	Setup Drawings or Photographs
Exhibit 4	Section 2.1033 (b)(3)	Installation and Operating Instructions → Confidential
Exhibit 5	Sections 2.1033 (b)(6), 2.911 (e) & 15.407	Test Report
Exhibit 6	Sections 1.1307 & 1.1310	RF Exposure Assessment

^{*}The information in the exhibits submitted in the original filing about Certification and Qualification of Engineers, Manufacturer, Applicant and Identifier, Descriptions of Operation and Security, Block Diagrams, Schematics and Parts List, Photos and Product Label are still valid and will not be resubmitted here.