

FCC PART 15.247 TEST REPORT

For

ENSAMBLADORA Y DISTRIBUIDORA DE TECNOLOGIA S.A.

OFICINA 440, EDIFICIO TRADE BUILDING, AV. JOAQUIN ORRANTIA Y LEOPOLDO BENITEZ, GUAYAQUIL, ECUADOR

FCC ID: 2AD9BQA4928

Report Type: Product Type:
Original Report 3G Smart Phone

Test Engineer: Dean Liu

Report Number: RDG150212003-00A

Report Date: 2015-03-25

Sula Huang

Reviewed By: RF Leader

Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan)

No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Sono Hugof

Tel: +86-769-86858888 Fax: +86-769-86858891

www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	
OBJECTIVE	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY TEST FACILITY	
SYSTEM TEST CONFIGURATION	
DESCRIPTION OF TEST CONFIGURATION	
EUT Exercise Software	
SUPPORT EQUIPMENT LIST AND DETAILS	
External Cable.	6
BLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	8
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	9
APPLICABLE STANDARD	
FCC §15.203 - ANTENNA REQUIREMENT	
APPLICABLE STANDARD	
Antenna Connector Construction	10
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	
APPLICABLE STANDARD	
MEASUREMENT UNCERTAINTY	
EUT SETUPEMI TEST RECEIVER SETUP	
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST EQUIPMENT LIST AND DETAILS.	
TEST RESULTS SUMMARY	
TEST DATA	13
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	
APPLICABLE STANDARD	
MEASUREMENT UNCERTAINTY	
EUT SETUPEMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	
TEST PROCEDURE	1/ 17
TEST FROCEDORE TEST EQUIPMENT LIST AND DETAILS.	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST RESULTS SUMMARY	18
TEST DATA	18
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST	27
APPLICABLE STANDARD	27
TEST EQUIPMENT LIST AND DETAILS.	27

TEST PROCEDURE	27
Test Data	27
FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING	33
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	33
TEST DATA	33
FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST	39
APPLICABLE STANDARD	39
TEST PROCEDURE	39
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	39
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)	43
APPLICABLE STANDARD	43
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	59
APPLICABLE STANDARD	
TEST PROCEDURE	59
TEST EQUIPMENT LIST AND DETAILS.	
TEST DATA	59
FCC §15.247(d) - BAND EDGES TESTING	65
APPLICABLE STANDARD	65
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	65
DECLAPATION LETTER	60

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The ENSAMBLADORA Y DISTRIBUIDORA DE TECNOLOGIA S.A.'s product, model number: QA4928 (FCC ID: 2AD9BQA4928) (the "EUT") in this report was a 3G Smart Phone, which was measured approximately: 12.4 cm (L) x 6.4 cm (W) x 0.8 cm (H), rated input voltage: DC 3.7V rechargeable Li-ion battery or DC5V charging from adapter.

Report No.: RDG150212003-00A

Adapter information: mondo Model: TPA-200510VU Input: AC100-240V, 50/60Hz Output: DC5.0V, 1000 mA

Note: The series product, model QA4928, Athos, B4022 are electrically identical, the difference between them is just the model name, we selected QA4928 for fully testing, the details was explained in the attached declaration letter.

All measurement and test data in this report was gathered from production sample serial number: 150212003 (Assigned by BACL, Dongguan). The EUT was received on 2015-03-13

Objective

This report is prepared on behalf of *ENSAMBLADORA Y DISTRIBUIDORA DE TECNOLOGIA S.A.* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: 2AD9BQA4928. FCC Part 15C DTS submissions with FCC ID: 2AD9BQA4928. FCC Part 22H, 24E PCE submissions with FCC ID: 2AD9BQA4928.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

FCC Part 15.247 Page 4 of 69

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FCC Part 15.247 Page 5 of 69

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

EUT Exercise Software

Test Software Version		Enginnering Mode		
Test Frequency		2402MHz 2441MHz 2480MHz		
DI1	GFSK	N/A	N/A	N/A
Power Level Setting	π/4-DQPSK	N/A	N/A	N/A
Setting	8DPSK	N/A	N/A	N/A

Report No.: RDG150212003-00A

Equipment Modifications

No modification was made to the EUT.

Support Equipment List and Details


Manufacturer	acturer Description		Serial Number
/	1	/	/

External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	То
USB Cable	Yes	No	1.0	USB Port of Adapter	EUT
Earphone Cable	No	No	1.2	Earphone port of EUT	Earphone

FCC Part 15.247 Page 6 of 69

Block Diagram of Test Setup



FCC Part 15.247 Page 7 of 69

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliace
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliace
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

FCC Part 15.247 Page 8 of 69

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Report No.: RDG150212003-00A

According to KDB447498 D01 General RF Exposure Guidance v05r02:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance,

mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is \leq 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The maximum conducted output power= 5.41 dBm (3.48 mW) at 2441 MHz [(max. power of channel, mW)/(min. test separation distance, mm)] [\sqrt{f} (GHz)] = $3.48/5*(\sqrt{2.441}) = 1.09 < 3.0$

So the stand-alone SAR evaluation is not necessary.

FCC Part 15.247 Page 9 of 69

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Report No.: RDG150212003-00A

Antenna Connector Construction

The EUT has one integral antenna arrangement, which was permanently attached and the antenna gain is -1.0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC Part 15.247 Page 10 of 69

FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

If $U_{\rm lab}$ is less than or equal to $U_{\rm cispr}$ of Table 1, then:


- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If U_{lab} is greater than U_{cispr} of Table 1, then:
- compliance is deemed to occur if no measured disturbance level, increased by $(U_{\text{lab}} U_{\text{cispr}})$, exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level, increased by $(U_{\text{lab}} U_{\text{cispr}})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of
$$U_{\text{cispr}}$$

Measurement	$U_{ m cispr}$
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

FCC Part 15.247 Page 11 of 69

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207 limits.

Report No.: RDG150212003-00A

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W	
150 kHz – 30 MHz	9 kHz	

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

 V_C : corrected voltage amplitude V_R : reading voltage amplitude A_c : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The "Margin" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

FCC Part 15.247 Page 12 of 69

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2014-10-16	2015-10-16
R&S	L.I.S.N	ESH3-Z5	843331/015	N/A	N/A
R&S	Two-line V-network	ENV 216	3560.6550.12	2014-12-11	2015-12-11
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

Report No.: RDG150212003-00A

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Part 15.207</u>, with the worst margin reading of:

5.4 dB at 0.554139 MHz in the Neutral conducted mode

Test Data

Environmental Conditions

Temperature:	20.3 °C
Relative Humidity:	32 %
ATM Pressure:	101.4 kPa


The testing was performed by Dean Liu on 2015-02-13.

FCC Part 15.247 Page 13 of 69

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Mode: Charging&Transmitting

AC120 V, 60 Hz, Line:




Report No.: RDG150212003-00A

				(0)0)0)0)0			
Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.151200	45.8	9.000	L1	10.1	20.2	65.9	Compliance
0.201433	44.1	9.000	L1	10.8	19.4	63.6	Compliance
0.357511	38.5	9.000	L1	10.7	20.2	58.8	Compliance
0.487810	40.3	9.000	L1	10.4	15.9	56.2	Compliance
0.558572	29.6	9.000	L1	10.3	26.4	56.0	Compliance
2.815577	30.1	9.000	L1	10.6	25.9	56.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.214692	33.1	9.000	L1	10.7	19.9	53.0	Compliance
0.351859	29.0	9.000	L1	10.7	19.9	48.9	Compliance
0.567545	24.2	9.000	L1	10.4	21.8	46.0	Compliance
1.310256	25.9	9.000	L1	10.4	20.1	46.0	Compliance
2.793231	10.6	9.000	L1	10.6	35.4	46.0	Compliance
4.651370	9.4	9.000	L1	10.7	36.6	46.0	Compliance

FCC Part 15.247 Page 14 of 69

AC120 V, 60 Hz, Neutral:



Report No.: RDG150212003-00A

			45.	AND N	4007		
Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.472507	47.2	9.000	N	10.5	9.3	56.5	Compliance
0.554139	50.6	9.000	N	10.3	5.4	56.0	Compliance
1.190776	47.2	9.000	N	10.5	8.8	56.0	Compliance
2.883693	50.1	9.000	N	10.6	5.9	56.0	Compliance
4.399032	46.7	9.000	N	10.8	9.3	56.0	Compliance
4.577832	45.5	9.000	N	10.8	10.5	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.472507	37.1	9.000	N	10.5	9.4	46.5	Compliance
0.572086	38.2	9.000	N	10.4	7.8	46.0	Compliance
1.135185	34.3	9.000	N	10.5	11.7	46.0	Compliance
1.430284	34.7	9.000	N	10.5	11.3	46.0	Compliance
2.749070	39.9	9.000	N	10.6	6.1	46.0	Compliance
4.329484	36.0	9.000	N	10.8	10.0	46.0	Compliance

FCC Part 15.247 Page 15 of 69

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

Report No.: RDG150212003-00A

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If U_{lab} is greater than U_{cispr} of Table 1, then:
- compliance is deemed to occur if no measured disturbance level, increased by $(U_{\text{lab}} U_{\text{cispr}})$, exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level, increased by $(U_{\text{lab}} U_{\text{cispr}})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:


30M~200MHz: 5.0 dB 200M~1GHz: 6.2 dB 1G~6GHz: 4.45 dB 6G~18GHz: 5.23 dB

Table 1 – Values of $U_{\rm cispr}$

Measurement					
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB				
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB				
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB				


EUT Setup

Below 1GHz:



FCC Part 15.247 Page 16 of 69

Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 CHz	1MHz	3 MHz	/	PK
Above 1 GHz	1MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and Average detection modes for frequencies above 1 GHz.

FCC Part 15.247 Page 17 of 69

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2014-05-09	2015-05-09
Sunol Sciences	Antenna	JB3	A060611-3	2014-07-28	2017-07-27
HP	Amplifier	8447E	2434A02181	2014-09-01	2015-09-01
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09
ETS LINDGREN	Horn Antenna	3115	000 527 35	2012-09-06	2015-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2014-02-15	2015-02-19
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09
Ducommun Technolagies	Horn Antenna	ARH-4223-02	1007726-01 1304	2014-06-16	2017-06-15
Quinstar	Amplifier	QLW- 18405536-JO	15964001001	2014-09-06	2015-09-06

Report No.: RDG150212003-00A

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit - Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Title 47, Part 15, Subpart C, and section 15.205, 15.209 and 15.247</u>, with the worst margin reading of:

10.63 dB at 2483.5 MHz in the Horizontal polarization of BDR Mode (GFSK

Test Data

Environmental Conditions

Temperature:	21.3 °C
Relative Humidity:	67 %
ATM Pressure:	101.1 kPa

The testing was performed by Dean Liu from 2015-02-15.

Mode: Transmitting

FCC Part 15.247 Page 18 of 69

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Report No.: RDG150212003-00A

BDR Mode (GFSK):

Frequency	de (GFSK): Ro	eceiver	Rx A	ntenna	Cable	Amplifier	Corrected	FCC 1	5.247		
(MHz)	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)	loss (dB)	Gain (dB)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)		
Low Channel: 2402 MHz											
2402	62.84	PK	Н	25.65	3.66	0.00	92.15	N/A	N/A		
2402	51.73	AV	Н	25.65	3.66	0.00	81.04	N/A	N/A		
2402	62.35	PK	V	25.65	3.66	0.00	91.66	N/A	N/A		
2402	51.28	AV	V	25.65	3.66	0.00	80.59	N/A	N/A		
2390	25.89	PK	Н	25.61	3.63	0.00	55.13	74.00	18.87		
2390	13.18	AV	Н	25.61	3.63	0.00	42.42	54.00	11.58		
4804	38.35	PK	Н	30.59	5.06	27.41	46.59	74.00	27.41		
4804	26.35	AV	Н	30.59	5.06	27.41	34.59	54.00	19.41		
7206	36.54	PK	Н	34.09	6.61	25.91	51.33	74.00	22.67		
7206	24.58	AV	Н	34.09	6.61	25.91	39.37	54.00	14.63		
9608	30.25	PK	Н	35.96	8.53	27.55	47.19	74.00	26.81		
9608	19.24	AV	Н	35.96	8.53	27.55	36.18	54.00	17.82		
4365	33.21	PK	Н	29.83	5.00	26.92	41.12	74.00	32.88		
4365	20.58	AV	H V	29.83	5.00	26.92	28.49	54.00	25.51		
204.83	30.8	QP		11.73 (iddle Chan	1.72	21.46	22.79	43.50	20.71		
2441	64.97	PK	Н	25.75	3.76	0.00	94.48	N/A	N/A		
2441	53.98	AV	Н	25.75	3.76	0.00	83.49	N/A	N/A		
2441	63.54	PK	V	25.75	3.76	0.00	93.05	N/A	N/A		
2441	52.37	AV	V	25.75	3.76	0.00	81.88	N/A	N/A		
4882	35.54	PK	Н	30.79	5.19	27.42	44.10	74.00	29.90		
4882	23.62	AV	Н	30.79	5.19	27.42	32.18	54.00	21.82		
7323	33.52	PK	Н	34.38	6.75	25.88	48.77	74.00	25.23		
7323	21.36	AV	Н	34.38	6.75	25.88	36.61	54.00	17.39		
9764	30.46	PK	Н	36.33	8.62	27.20	48.21	74.00	25.79		
9764	18.64	AV	Н	36.33	8.62	27.20	36.39	54.00	17.61		
4365	32.58	PK	Н	29.83	5.00	26.92	40.49	74.00	33.51		
4365	20.07	AV	Н	29.83	5.00	26.92	27.98	54.00	26.02		
1562	33.24	PK	Н	23.72	2.63	27.66	31.93	74.00	42.07		
1562	20.57	AV	Н	23.72	2.63	27.66	19.26	54.00	34.74		
204.83	30.9	QP	V	11.73	1.72	21.46	22.89	43.50	20.61		
	1			High Chann							
2480	66.32	PK	Н	25.85	3.68	0.00	95.85	N/A	N/A		
2480	55.53	AV	H	25.85	3.68	0.00	85.06	N/A	N/A		
2480	65.85	PK	V	25.85	3.68	0.00	95.38	N/A	N/A		
2480	54.22	AV	V	25.85	3.68	0.00	83.75	N/A	N/A		
2483.5	25.68	PK	Н	25.86	3.67	0.00	55.21	74.00	18.79		
2483.5	13.84	AV	Н	25.86	3.67	0.00	43.37	54.00	10.63		
4960 4960	33.64 21.57	PK AV	Н	31.00	5.34	27.43 27.43	42.55	74.00 54.00	31.45 23.52		
7440	32.16	PK	H H	34.66	6.89	25.97	30.48 47.74	74.00	26.26		
7440	20.24	AV	Н	34.66	6.89	25.97	35.82	54.00	18.18		
9920	30.75	PK	Н	36.71	8.71	26.66	49.51	74.00	24.49		
9920	18.67	AV	Н	36.71	8.71	26.66	37.43	54.00	16.57		
4365	33.05	PK	Н	29.83	5.00	26.92	40.96	74.00	33.04		
4365	20.57	AV	Н	29.83	5.00	26.92	28.48	54.00	25.52		
204.83	30.8	QP	V	11.73	1.72	21.46	22.79	43.50	20.71		

FCC Part 15.247 Page 19 of 69

EDR Mode ($\pi/4$ -DQPSK):

	111	eceiver	KX A	ntenna	Cable	Amplifier	Corrected	FCC 1	5.247		
(MHz)	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)	loss (dB)	Gain (dB)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)		
Low Channel: 2402 MHz											
2402	62.46	PK	Н	25.65	3.66	0.00	91.77	N/A	N/A		
2402	51.37	AV	Н	25.65	3.66	0.00	80.68	N/A	N/A		
2402	62.1	PK	V	25.65	3.66	0.00	91.41	N/A	N/A		
2402	50.08	AV	V	25.65	3.66	0.00	79.39	N/A	N/A		
2390	25.73	PK	Н	25.61	3.63	0.00	54.97	74.00	19.03		
2390	12.99	AV	Н	25.61	3.63	0.00	42.23	54.00	11.77		
4804	38.18	PK	Н	30.59	5.06	27.41	46.42	74.00	27.58		
4804	26.2	AV	Н	30.59	5.06	27.41	34.44	54.00	19.56		
7206	36.36	PK	Н	34.09	6.61	25.91	51.15	74.00	22.85		
7206	24.43	AV	Н	34.09	6.61	25.91	39.22	54.00	14.78		
9608	30.1	PK	Н	35.96	8.53	27.55	47.04	74.00	26.96		
9608	19.12	AV	Н	35.96	8.53	27.55	36.06	54.00	17.94		
4733	33.1	PK	Н	30.41	5.13	27.38	41.26	74.00	32.74		
4733	20.42	AV	H V	30.41	5.13 1.72	27.38	28.58	54.00	25.42		
204.83	31.7	QP		iddle Chan		21.46	23.69	43.50	19.81		
2441	64.63	PK	Н	25.75	3.76	0.00	94.14	N/A	N/A		
2441	53.62	AV	Н	25.75	3.76	0.00	83.13	N/A	N/A		
2441	63.27	PK	V	25.75	3.76	0.00	92.78	N/A	N/A		
2441	53.02	AV	V	25.75	3.76	0.00	82.53	N/A	N/A		
4882	35.41	PK	Н	30.79	5.19	27.42	43.97	74.00	30.03		
4882	23.47	AV	Н	30.79	5.19	27.42	32.03	54.00	21.97		
7323	33.34	PK	Н	34.38	6.75	25.88	48.59	74.00	25.41		
7323	21.23	AV	Н	34.38	6.75	25.88	36.48	54.00	17.52		
9764	30.33	PK	Н	36.33	8.62	27.20	48.08	74.00	25.92		
9764	18.53	AV	Н	36.33	8.62	27.20	36.28	54.00	17.72		
4733	32.4	PK	Н	30.41	5.13	27.38	40.56	74.00	33.44		
4733	19.91	AV	Н	30.41	5.13	27.38	28.07	54.00	25.93		
4365	33.14	PK	Н	29.83	5.00	26.92	41.05	74.00	32.95		
4365	20.39	AV	Н	29.83	5.00	26.92	28.30	54.00	25.70		
204.83	31.5	QP	V	11.73	1.72	21.46	23.49	43.50	20.01		
				High Chann			T				
2480	65.58	PK	Н	25.85	3.68	0.00	95.11	N/A	N/A		
2480	53.38	AV	H	25.85	3.68	0.00	82.91	N/A	N/A		
2480	64.46	PK	V	25.85	3.68	0.00	93.99	N/A	N/A		
2480	52.36	AV	V	25.85	3.68	0.00	81.89	N/A	N/A		
2483.5	25.53	PK	Н	25.86	3.67	0.00	55.06	74.00	18.94		
2483.5	13.73	AV	Н	25.86	3.67	0.00	43.26	54.00	10.74		
4960	33.45	PK	Н	31.00	5.34	27.43	42.36	74.00	31.64		
4960 7440	21.42 32.02	AV PK	H H	31.00	5.34 6.89	27.43 25.97	30.33 47.60	54.00 74.00	23.67 26.40		
7440	20.14	AV	Н	34.66	6.89	25.97	35.72	54.00	18.28		
9920	30.58	PK	Н	36.71	8.71	26.66	49.34	74.00	24.66		
9920	18.54	AV	Н	36.71	8.71	26.66	37.30	54.00	16.70		
4733	32.91	PK	Н	30.71	5.13	27.38	41.07	74.00	32.93		
T133			Н	30.41	5.13	27.38	28.55	54.00	25.45		
4733	20.39	AV	н .								

FCC Part 15.247 Page 20 of 69

Report No.: RDG150212003-00A

EDR Mode (8-DPSK):

Frequency	de (8-DPSK) Re	eceiver	Rx A	ntenna	Cable	Amplifier	Corrected	FCC 1	15.247		
(MHz)	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)	loss (dB)	Gain (dB)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)		
Low Channel: 2402 MHz											
2402	62.08	PK	Н	25.65	3.66	0.00	91.39	N/A	N/A		
2402	50.15	AV	Н	25.65	3.66	0.00	79.46	N/A	N/A		
2402	61.12	PK	V	25.65	3.66	0.00	90.43	N/A	N/A		
2402	49.83	AV	V	25.65	3.66	0.00	79.14	N/A	N/A		
2390	25.13	PK	Н	25.61	3.63	0.00	54.37	74.00	19.63		
2390	13.18	AV	Н	25.61	3.63	0.00	42.42	54.00	11.58		
4804	38.01	PK	Н	30.59	5.06	27.41	46.25	74.00	27.75		
4804	26.07	AV	Н	30.59	5.06	27.41	34.31	54.00	19.69		
7206	36.17	PK	Н	34.09	6.61	25.91	50.96	74.00	23.04		
7206	24.29	AV	Н	34.09	6.61	25.91	39.08	54.00	14.92		
9608	29.97	PK	Н	35.96	8.53	27.55	46.91	74.00	27.09		
9608	18.95	AV	Н	35.96	8.53	27.55	35.89	54.00	18.11		
6086	32.96	PK	Н	32.22	5.92	26.95	44.15	74.00	29.85		
6086	20.26	AV	H V	32.22 11.73	5.92 1.72	26.95	31.45 23.89	54.00	22.55		
204.83	31.9	QP		iddle Chan		21.46	23.89	43.50	19.61		
2441	64.37	PK	Н	25.75	3.76	0.00	93.88	N/A	N/A		
2441	52.38	AV	Н	25.75	3.76	0.00	81.89	N/A	N/A		
2441	62.89	PK	V	25.75	3.76	0.00	92.40	N/A N/A	N/A		
2441	50.78	AV	V	25.75	3.76	0.00	80.29	N/A	N/A		
4882	25.54	PK	Н	30.79	5.19	27.42	34.10	74.00	39.90		
4882	13.7	AV	Н	30.79	5.19	27.42	22.26	54.00	31.74		
7323	33.49	PK	Н	34.38	6.75	25.88	48.74	74.00	25.26		
7323	21.44	AV	Н	34.38	6.75	25.88	36.69	54.00	17.31		
9764	32.05	PK	Н	36.33	8.62	27.20	49.80	74.00	24.20		
9764	20.09	AV	Н	36.33	8.62	27.20	37.84	54.00	16.16		
6086	30.61	PK	Н	32.22	5.92	26.95	41.80	74.00	32.20		
6086	18.51	AV	Н	32.22	5.92	26.95	29.70	54.00	24.30		
4365	32.94	PK	Н	29.83	5.00	26.92	40.85	74.00	33.15		
4365	20.42	AV	Н	29.83	5.00	26.92	28.33	54.00	25.67		
204.83	31.5	QP	V	11.73	1.72	21.46	23.49	43.50	20.01		
2.100	67.21	Dir		High Chann				37/4	27/4		
2480	65.31	PK	Н	25.85	3.68	0.00	94.84	N/A	N/A		
2480	53.08	AV	Н	25.85	3.68	0.00	82.61	N/A	N/A		
2480	64.21	PK	V	25.85	3.68	0.00	93.74	N/A	N/A		
2480	52.08	AV	V	25.85	3.68	0.00	81.61	N/A	N/A		
2483.5	25.34	PK AV	Н	25.86	3.67	0.00	54.87	74.00	19.13		
2483.5 4960	13.55 33.27	AV PK	H H	25.86 31.00	3.67 5.34	0.00 27.43	43.08 42.18	54.00 74.00	10.92 31.82		
4960	21.32	AV	Н	31.00	5.34	27.43	30.23	54.00	23.77		
7440	31.84	PK	Н	34.66	6.89	25.97	47.42	74.00	26.58		
7440	19.95	AV	Н	34.66	6.89	25.97	35.53	54.00	18.47		
9920	30.39	PK	Н	36.71	8.71	26.66	49.15	74.00	24.85		
9920	18.38	AV	Н	36.71	8.71	26.66	37.14	54.00	16.86		
6086	32.76	PK	Н	32.22	5.92	26.95	43.95	74.00	30.05		
6086	20.21	AV	Н	32.22	5.92	26.95	31.40	54.00	22.60		
204.83	31.3	QP	V	11.73	1.72	21.46	23.29	43.50	20.21		


FCC Part 15.247 Page 21 of 69

Conducted Spurious Emissions at Antenna Port

Report No.: RDG150212003-00A


BDR Mode (GFSK):

Low Channel



Date: 15.FEB.2015 13:35:49

Middle Channel




Date: 15.FEB.2015 13:37:05

FCC Part 15.247 Page 22 of 69

High Channel


Report No.: RDG150212003-00A



Date: 15.FEB.2015 13:38:03

EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 15.FEB.2015 13:43:25

FCC Part 15.247 Page 23 of 69


Middle Channel

Report No.: RDG150212003-00A



Date: 15.FEB.2015 13:44:50

High Channel




Date: 15.FEB.2015 13:47:28

FCC Part 15.247 Page 24 of 69


Low Channel

Report No.: RDG150212003-00A



Date: 15.FEB.2015 13:54:48


Middle Channel



Date: 15.FEB.2015 13:49:34

FCC Part 15.247 Page 25 of 69





Date: 15.FEB.2015 13:51:12



FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hoping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Report No.: RDG150212003-00A

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

- 1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
- 2. Set the adjacent channel of the EUT maxhold another trace
- 3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	22.8 °C
Relative Humidity:	50 %
ATM Pressure:	101.1 kPa

^{*} The testing was performed by Dean Liu on 2015-02-15.

Test Result: Compliance.

Please refer to following tables and plots


FCC Part 15.247 Page 27 of 69

Test Mode: Transmitting

Mode	Channel	Frequency	Channel Seperation	Limit	Result
		MHz	MHz	MHz	
nnn	Low	2402	1.004	0.600	Pass
BDR (GFSK)	Middle	2441	1.000	0.600	Pass
(GFSK)	High	2480	1.000	0.600	Pass
EDD	Low	2402	1.000	0.844	Pass
EDR (π/4-DQPSK)	Middle	2441	1.000	0.844	Pass
(11/4-DQF3K)	High	2480	1.000	0.844	Pass
EDD	Low	2402	1.000	0.852	Pass
EDR (8DPSK)	Middle	2441	1.000	0.852	Pass
(ODFSK)	High	2480	1.004	0.852	Pass


BDR Mode (GFSK):

Low Channel




Date: 15.FEB.2015 11:47:24

FCC Part 15.247 Page 28 of 69



Date: 15.FEB.2015 11:53:23

High Channel




Date: 15.FEB.2015 11:54:20

FCC Part 15.247 Page 29 of 69


EDR Mode ($\pi/4$ -DQPSK):





Date: 15.FEB.2015 11:49:03


Middle Channel



Date: 15.FEB.2015 11:51:57

FCC Part 15.247 Page 30 of 69


High Channel



Date: 15.FEB.2015 11:56:25


EDR Mode (8-DPSK):

Low Channel




Date: 15.FEB.2015 11:50:07

FCC Part 15.247 Page 31 of 69



Date: 15.FEB.2015 11:51:02

High Channel



Date: 15.FEB.2015 11:58:42

FCC Part 15.247 Page 32 of 69

FCC $\S15.247(a)$ (1) – 20 dB BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Report No.: RDG150212003-00A

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	22.8 °C			
Relative Humidity:	50 %			
ATM Pressure:	101.1 kPa			

^{*} The testing was performed by Dean Liu on 2015-02-15.

Test Result: Compliance.

Please refer to following tables and plots

FCC Part 15.247 Page 33 of 69


Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
BDR Mode (GFSK)	Low	2402	0.900
	Middle	2441	0.894
(GI SIC)	High	2480	0.888
	Low	2402	1.266
EDR Mode (π/4-DQPSK):	Middle	2441	1.266
(W+DQI SIC).	High	2480	1.26
EDD 14.1	Low	2402	1.278
EDR Mode (8-DPSK):	Middle	2441	1.278
(0 DI 5K).	High	2480	1.278

Please refer to the following plots.


BDR Mode (GFSK):

Low Channel




Date: 15.FEB.2015 11:34:07

FCC Part 15.247 Page 34 of 69



Date: 15.FEB.2015 11:35:56

High Channel



Date: 15.FEB.2015 11:36:52

FCC Part 15.247 Page 35 of 69


Low Channel

Report No.: RDG150212003-00A



Date: 15.FEB.2015 11:38:38


Middle Channel



Date: 15.FEB.2015 11:39:42

FCC Part 15.247 Page 36 of 69


High Channel



Date: 15.FEB.2015 11:40:39


EDR Mode (8-DPSK):

Low Channel




Date: 15.FEB.2015 11:42:08

FCC Part 15.247 Page 37 of 69



Date: 15.FEB.2015 11:43:30

High Channel



Date: 15.FEB.2015 11:45:19

FCC Part 15.247 Page 38 of 69

FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

Report No.: RDG150212003-00A

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

- 1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- 2. Set the EUT in hopping mode from first channel to last.
- 3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Valuation of	
Temperature:	22.8 °C
Relative Humidity:	50 %
ATM Pressure:	101.1 kPa

^{*} The testing was performed by Dean Liu on 2015-02-15.

Test Result: Compliance.

Please refer to following tables and plots


FCC Part 15.247 Page 39 of 69

Test Mode: Transmitting

BDR Mode (GFSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15

Number of Hopping Channels




Date: 15.FEB.2015 13:33:45

FCC Part 15.247 Page 40 of 69

EDR Mode (\pi/4-DQPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15

Number of Hopping Channels



Date: 15.FEB.2015 13:29:47


FCC Part 15.247 Page 41 of 69

EDR Mode (8-DPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15

Report No.: RDG150212003-00A

Number of Hopping Channels



Date: 15.FEB.2015 12:24:35

FCC Part 15.247 Page 42 of 69

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Report No.: RDG150212003-00A

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 * channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time= time slot length * hope rate/ number of hopping channels * 31.6s Hop rate=1600/s

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Allerand	
Temperature:	22.4 °C
Relative Humidity:	57 %
ATM Pressure:	101.6 kPa

^{*} The testing was performed by Dean Liu on 2015-03-12.

Test Result: Compliance.

Please refer to following tables and plots

FCC Part 15.247 Page 43 of 69


Test Mode: Transmitting

BDR Mode (GFSK):

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result	
	Low	0.386	0.124	0.4	Pass	
DH1	Middle	0.386	0.124	0.4	Pass	
	High	0.386	0.124	0.4	Pass	
	Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s					
	Low	1.658	0.265	0.4	Pass	
DH3	Middle	1.658	0.265	0.4	Pass	
	High	1.658	0.265	0.4	Pass	
	Note: Dwell time=Pulse time (ms) \times (1600/4/79) \times 31.6 s					
	Low	2.918	0.311	0.4	Pass	
DH5	Middle	2.918	0.311	0.4	Pass	
DHS	High	2.918	0.311	0.4	Pass	
	Note: Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s					

Report No.: RDG150212003-00A

DH1: Low Channel




Date: 12.MAR.2015 12:16:58

FCC Part 15.247 Page 44 of 69


DH1: Middle Channel

Report No.: RDG150212003-00A



Date: 12.MAR.2015 12:17:08

DH1: High Channel




Date: 12.MAR.2015 12:17:37

FCC Part 15.247 Page 45 of 69


DH3: Low Channel

Report No.: RDG150212003-00A




Date: 12.MAR.2015 12:18:42


DH3: Middle Channel



Date: 12.MAR.2015 12:18:51


FCC Part 15.247 Page 46 of 69





Date: 12.MAR.2015 12:18:58

DH5: Low Channel




Date: 12.MAR.2015 12:20:17

FCC Part 15.247 Page 47 of 69


DH5: Middle Channel

Report No.: RDG150212003-00A



Date: 12.MAR.2015 12:20:27

DH5: High Channel



Date: 12.MAR.2015 12:20:36


FCC Part 15.247 Page 48 of 69

EDR Mode ($\pi/4$ -DQPSK):

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result		
	Low	0.392	0.125	0.4	Pass		
DH1	Middle	0.392	0.125	0.4	Pass		
DHI	High	0.392	0.125	0.4	Pass		
	Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s						
	Low	1.664	0.266	0.4	Pass		
DH3	Middle	1.664	0.266	0.4	Pass		
DH3	High	1.664	0.266	0.4	Pass		
	Note: Dwell time=Pulse time (ms) \times (1600/4/79) \times 31.6 s						
	Low	2.914	0.311	0.4	Pass		
DH5	Middle	2.914	0.311	0.4	Pass		
DHS	High	2.914	0.311	0.4	Pass		
	Note: Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s						

Report No.: RDG150212003-00A

DH1: Low Channel




Date: 12.MAR.2015 12:21:34

FCC Part 15.247 Page 49 of 69


DH1: Middle Channel

Report No.: RDG150212003-00A



Date: 12.MAR.2015 12:21:47


DH1: High Channel



Date: 12.MAR.2015 12:21:56


FCC Part 15.247 Page 50 of 69

DH3: Low Channel



Date: 12.MAR.2015 12:23:12


DH3: Middle Channel



Date: 12.MAR.2015 12:23:20


FCC Part 15.247 Page 51 of 69

DH3: High Channel




Date: 12.MAR.2015 12:23:27

DH5: Low Channel




Date: 12.MAR.2015 12:24:38

FCC Part 15.247 Page 52 of 69



Date: 12.MAR.2015 12:24:47

DH5: High Channel




Date: 12.MAR.2015 12:24:54

FCC Part 15.247 Page 53 of 69

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result	
	Low	0.394	0.126	0.4	Pass	
DH1	Middle	0.394	0.126	0.4	Pass	
DIII	High	0.394	0.126	0.4	Pass	
	Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s					
	Low	1.660	0.266	0.4	Pass	
DH3	Middle	1.660	0.266	0.4	Pass	
DH3	High	1.660	0.266	0.4	Pass	
Note: Dwell time=Pulse time (ms) \times (1600/4/79) \times				9) ×31.6 s		
	Low	2.920	0.311	0.4	Pass	
DH5	Middle	2.920	0.311	0.4	Pass	
DП3	High	2.920	0.311	0.4	Pass	
	Note: Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s					

DH1: Low Channel




Date: 12.MAR.2015 12:25:54

FCC Part 15.247 Page 54 of 69


DH1: Middle Channel

Report No.: RDG150212003-00A



Date: 12.MAR.2015 12:26:03


DH1: High Channel



Date: 12.MAR.2015 12:26:16


FCC Part 15.247 Page 55 of 69

DH3: Low Channel




Date: 12.MAR.2015 12:27:14


DH3: Middle Channel



Date: 12.MAR.2015 12:27:20


FCC Part 15.247 Page 56 of 69






Date: 12.MAR.2015 12:27:25

DH5: Low Channel




Date: 12.MAR.2015 12:28:15

FCC Part 15.247 Page 57 of 69



Date: 12.MAR.2015 12:28:29

DH5: High Channel



Date: 12.MAR.2015 12:28:39

FCC Part 15.247 Page 58 of 69

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Report No.: RDG150212003-00A

Test Procedure

- 1. Place the EUT on a bench and set in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI test receiver.
- 3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	22.8 °C
Relative Humidity:	50 %
ATM Pressure:	101.1 kPa

^{*} The testing was performed by Dean Liu on 2015-02-15.

Test Result: Compliance.

FCC Part 15.247 Page 59 of 69

Report No.: RDG150212003-00A


Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Output power (dBm)	Limit (dBm)
BDR Mode (GFSK)	Low	2402	5.14	30
	Middle	2441	5.41	30
	High	2480	5.35	30
EDR Mode (π/4-DQPSK)	Low	2402	4.77	30
	Middle	2441	5.01	30
	High	2480	4.95	30
EDR Mode (8-DPSK)	Low	2402	5.17	30
	Middle	2441	5.41	30
	High	2480	5.41	30

Note: The data above was tested in conducted mode.

BDR Mode (GFSK):


Output Power, Low Channel



Date: 15.FEB.2015 11:28:42


FCC Part 15.247 Page 60 of 69

Output Power, Middle Channel



Date: 15.FEB.2015 11:29:14

Output Power, High Channel




Date: 15.FEB.2015 11:29:31

FCC Part 15.247 Page 61 of 69

EDR Mode (π/4-DQPSK):


Output Power, Low Channel

Report No.: RDG150212003-00A



Date: 15.FEB.2015 11:30:02

Output Power, Middle Channel




Date: 15.FEB.2015 11:30:21

FCC Part 15.247 Page 62 of 69

Output Power, High Channel


Report No.: RDG150212003-00A



Date: 15.FEB.2015 11:30:35

EDR Mode (8-DPSK):

Output Power, Low Channel




Date: 15.FEB.2015 11:31:00

FCC Part 15.247 Page 63 of 69


Output Power, Middle Channel

Report No.: RDG150212003-00A



Date: 15.FEB.2015 11:31:21

Output Power, High Channel



Date: 15.FEB.2015 11:31:39

FCC Part 15.247 Page 64 of 69

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Report No.: RDG150212003-00A

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	22.8°C
Relative Humidity:	50 %
ATM Pressure:	101.1 kPa

^{*} The testing was performed by Dean Liu on 2015-02-15.


FCC Part 15.247 Page 65 of 69

Test Result: Compliance

BDR Mode (GFSK):


Band Edge, Left Side

Report No.: RDG150212003-00A



Date: 15.FEB.2015 12:12:12

Band Edge, Right Side




Date: 15.FEB.2015 12:11:02

FCC Part 15.247 Page 66 of 69

EDR Mode ($\pi/4$ -DQPSK):


Band Edge, Left Side

Report No.: RDG150212003-00A



Date: 15.FEB.2015 12:12:59

Band Edge, Right Side




Date: 15.FEB.2015 12:10:04

FCC Part 15.247 Page 67 of 69

EDR Mode (8-DPSK):


Band Edge, Left Side

Report No.: RDG150212003-00A



Date: 15.FEB.2015 12:13:58

Band Edge, Right Side



Date: 15.FEB.2015 12:09:20

FCC Part 15.247 Page 68 of 69

DECLARATION LETTER

ENSAMBLADORA Y DISTRIBUIDORA DE TECNOLOGIA S.A. Add: OFICINA 440, EDIFICIO TRADE BUILDING, AV. JOAQUIN ORRANTIA Y

LEOPOLDO BENITEZ, GUAYAQUIL, ECUADOR

Tel: +59345103027 Fax: 59342004140ext.104

Product Similarity Declaration

Report No.: RDG150212003-00A

Date: 2015-03-20

To Whom It May Concern,

We, ENSAMBLADORA Y DISTRIBUIDORA DE TECNOLOGIA S.A., hereby declare that our product 3G Smart Phone, Model Number: QA4928, Athos, B4022 are electrically identical with the same electromagnetic emissions and electromagnetic compatibility characteristics. Model Numbers: Athos, B4022 is electrically identical with the Model Number: QA4928 that was certified by BACL. Their only difference is the model name.

The rest are the same.

Please contact me if you have any question.

kenlyn Velez

Signature:

Kerlyn Velez

General Manager Assistant

*****END OF REPORT****

FCC Part 15.247 Page 69 of 69