




# RF TEST REPORT



Report No.: 16070815-FCC-R1

Supersede Report No.: N/A

Applicant	MOBIWIRE MOBILES (NINGBO) CO.,LTD	
Product Name	4G LTE SMARTPHONE	
Model No.	N503	
Serial No.	N/A	
Test Standard	FCC Part 22(H):2015 ;FCC Part 24(E):2015; ANSI/TIA-603-D: 2010	
Test Date	August 09 to September 05, 2016	
Issue Date	September 07, 2016	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification <input checked="" type="checkbox"/>		
Equipment did not comply with the specification <input type="checkbox"/>		
		
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

**SIEMIC (SHENZHEN-CHINA) LABORATORIES**

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: [China@siemic.com.cn](mailto:China@siemic.com.cn)

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	16070815-FCC-R1
Page	3 of 83

---

This page has been left blank intentionally.

## CONTENTS

1. REPORT REVISION HISTORY .....	5
2. CUSTOMER INFORMATION .....	5
3. TEST SITE INFORMATION .....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION .....	6
5. TEST SUMMARY .....	9
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS .....	10
6.1 RF EXPOSURE (SAR).....	10
6.2 RF OUTPUT POWER .....	11
6.3 PEAK-AVERAGE RATIO.....	23
6.4 OCCUPIED BANDWIDTH.....	27
6.5 SPURIOUS EMISSIONS AT ANTENNA TERMINALS .....	38
6.6 SPURIOUS RADIATED EMISSIONS .....	51
6.7 BAND EDGE.....	57
6.8 FREQUENCY STABILITY .....	67
ANNEX A. TEST INSTRUMENT.....	71
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	73
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	79
ANNEX C.II. EUT OPERATING CONKITIONS .....	81
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST .....	82
ANNEX E. DECLARATION OF SIMILARITY .....	83

## 1. Report Revision History

Report No.	Report Version	Description	Issue Date
16070815-FCC-R1	NONE	Original	September 07, 2016

## 2. Customer information

Applicant Name	MOBIWIRE MOBILES (NINGBO) CO.,LTD
Applicant Add	No.999,Dacheng East Road,Fenghua City,Zhejiang
Manufacturer	MOBIWIRE MOBILES (NINGBO) CO.,LTD
Manufacturer Add	No.999,Dacheng East Road,Fenghua City,Zhejiang

## 3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

## 4. Equipment under Test (EUT) Information

Description of EUT:	4G LTE SMARTPHONE
Main Model:	N503
Serial Model:	N/A
Date EUT received:	August 08, 2016
Test Date(s):	August 09 to September 05, 2016
Equipment Category :	PCE
Antenna Gain:	GSM850: 0dBi PCS1900: 1dBi UMTS-FDD Band V: 0dBi UMTS-FDD Band II: 1dBi LTE Band IV: 0.5dBi Bluetooth/BLE/WIFI: -3dBi GPS: -3dBi
Antenna Type:	PIFA antenna
Type of Modulation:	GSM / GPRS: GMSK EGPRS: GMSK,8PSK UMTS-FDD: QPSK LTE Band: QPSK, 16QAM 802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, $\pi$ /4DQPSK, 8DPSK BLE: GFSK GPS:BPSK
Input Power:	Adapter: Model: S005UA0500100 Input: AC100-240V~50/60Hz,150mA Output: DC 5.0V,1000mA Battery: Spec: 3.8V,2270mAh(8.63Wh)

	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz
	PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz
	UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz
	UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz;
	RX: 1932.4 ~ 1987.6 MHz
RF Operating Frequency (ies):	LTE Band IV TX: 1710.7 ~ 1754.3 MHz; RX : 2110.7 ~ 2154.3 MHz
	WIFI: 802.11b/g/n(20M): 2412-2462 MHz
	WIFI: 802.11n(40M): 2422-2452 MHz
	Bluetooth& BLE: 2402-2480 MHz
	GPS: 1575.42 MHz
	GSM 850: 124CH
	PCS1900: 299CH
	UMTS-FDD Band V: 102CH
	UMTS-FDD Band II: 277CH
Number of Channels:	WIFI :802.11b/g/n(20M): 11CH
	WIFI :802.11n(40M): 7CH
	Bluetooth: 79CH
	BLE: 40CH
	GPS:1CH
Port:	Power Port, Earphone Port, USB Port
	GSM Voice:GSM850: 33.10 dBm
	PCS1900: 30.48 dBm
	GPRS:GSM850: 33.08 dBm
	PCS1900: 30.46 dBm
	EGPRS(MCS1):GSM850: 33.07 dBm
	PCS1900: 30.45 dBm
Maximum Conducted	EGPRS(MCS5):GSM850: 26.00 dBm
AV Power to Antenna:	PCS1900: 26.70 dBm
	RMC:UMTS-FDD Band V: 22.25 dBm
	UMTS-FDD Band II: 22.50 dBm
	HSUPA:UMTS-FDD Band V: 21.41 dBm
	UMTS-FDD Band II : 21.68 dBm
	HSDPA:UMTS-FDD Band V: 21.39 dBm
	UMTS-FDD Band II : 21.60 dBm





## 5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§ 1.1307; § 2.1093	RF Exposure (SAR)	Compliance
§2.1046; § 22.913(a); § 24.232(c); § 27.50(c.10) ;	RF Output Power	Compliance
§ 24.232 (d) ;	Peak-Average Ratio	Compliance
§ 2.1049; § 22.905; § 22.917; § 24.238;	99% & -26 dB Occupied Bandwidth	Compliance
§ 2.1051; § 22.917(a); § 24.238(a);	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053; § 22.917(a); § 24.238(a);	Field Strength of Spurious Radiation	Compliance
§ 22.917(a); § 24.238(a);	Out of band emission, Band Edge	Compliance
§ 2.1055; § 22.355; § 24.235;	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: Testing was performed by configuring EUT to maximum output power status, the declared output power class for different

### Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

## 6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

### 6.1 RF Exposure (SAR)

Test Result: Pass


The EUT is a portable device, thus requires SAR evaluation;  
Please refer to RF Exposure Evaluation Report: 16070815-FCC-H.

## 6.2 RF Output Power

Temperature	23°C
Relative Humidity	55%
Atmospheric Pressure	1031mbar
Test date :	August 31, 2016
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable
§22.913 (a)	a)	ERP:38.45dBm	<input checked="" type="checkbox"/>
§24.232 (c)	b)	EIRP:33dBm	<input checked="" type="checkbox"/>

Test Setup	
------------	---

Test Procedure	<p>For Conducted Power:</p> <ul style="list-style-type: none"> <li>- The transmitter output port was connected to base station.</li> <li>- Set EUT at maximum power through base station.</li> <li>- Select lowest, middle, and highest channels for each band and different test mode.</li> </ul> <p>For ERP/EIRP:</p> <p>According with KDB 971168 v02r02</p> <ul style="list-style-type: none"> <li>- The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.</li> <li>- The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.</li> <li>- The frequency range up to tenth harmonic of the fundamental frequency was investigated.</li> </ul>
----------------	---

Test Report	16070815-FCC-R1
Page	12 of 83

	<ul style="list-style-type: none"> <li>- Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.</li> <li>- Spurious emissions in dB = <math>10 \log (\text{TX power in Watts}/0.001)</math> – the absolute level</li> <li>- Spurious attenuation limit in dB = <math>43 + 10 \log_{10} (\text{power out in Watts})</math>.</li> </ul>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

## Conducted Power

### GSM Mode:

Burst Average Power (dBm);								
Band	GSM850				PCS1900			
Channel	128	190	251	Tune up Power tolerant	512	661	810	Tune up Power tolerant
Frequency (MHz)	824.2	836.6	848.8	/	1850.2	1880	1909.8	/
GSM Voice (1 uplink),GMSK	33.07	33.09	<b>33.10</b>	33±1	30.44	30.45	<b>30.48</b>	30±1
GPRS Multi-Slot Class 8 (1 uplink),GMSK	33.04	<b>33.08</b>	33.06	33±1	30.43	30.45	<b>30.46</b>	30±1
GPRS Multi-Slot Class 10 (2 uplink) GMSK	32.4	32.41	32.34	32±1	29.97	29.96	29.98	29±1
GPRS Multi-Slot Class 12 (4 uplink) GMSK	29.76	29.73	29.7	29±1	27.24	27.18	27.23	27±1
EGPRS Multi-Slot Class 8 (1 uplink) GMSK MCS1	33.02	<b>33.07</b>	33.05	33±1	30.34	30.45	<b>30.45</b>	30±1
EGPRS Multi-Slot Class 10 (2 uplink) GMSK MCS1	32.38	32.39	32.34	32±1	29.96	29.95	29.98	29±1
EGPRS Multi-Slot Class 12 (4 uplink) GMSK MCS1	29.74	29.72	29.68	29.5±1	27.29	27.19	27.23	27±1
EGPRS Multi-Slot Class 8 (1 uplink) 8PSK MCS5	<b>26.00</b>	25.64	25.3	25.5±1	<b>26.70</b>	26.46	26.32	26±1
EGPRS Multi-Slot Class 10 (2 uplink) 8PSK MCS5	24.85	24.57	24.24	24.5±1	24.4	24.21	24.18	24±1
EGPRS Multi-Slot Class 12 (4 uplink) 8PSK MCS5	21.63	21.33	21.22	21±1	21.82	21.1	20.72	21±1

Test Report	16070815-FCC-R1
Page	14 of 83

Remark :

GPRS, CS1 coding scheme.

EGPRS, MCS1 coding scheme.

EGPRS, MCS5 coding scheme.

Multi-Slot Class 8 , Support Max 4 downlink, 1 uplink , 5 working link

Multi-Slot Class 10 , Support Max 4 downlink, 2 uplink , 5 working link

Multi-Slot Class 12 , Support Max 4 downlink, 4 uplink , 5 working link

## UMTS Mode:

### UMTS-FDD Band V

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	4132	826.4	21.74	21.5±1
	4175	835	21.97	21.5±1
	4233	846.6	<b>22.25</b>	21.5±1
HSDPA Subtest1	4132	826.4	21.23	21.5±1
	4175	835	<b>21.41</b>	21.5±1
	4233	846.6	21.33	21.5±1
HSDPA Subtest2	4132	826.4	21.16	21.5±1
	4175	835	21.38	21.5±1
	4233	846.6	21.39	21.5±1
HSDPA Subtest3	4132	826.4	21.34	21.5±1
	4175	835	21.32	21.5±1
	4233	846.6	21.33	21.5±1
HSDPA Subtest4	4132	826.4	21.36	21.5±1
	4175	835	21.30	21.5±1
	4233	846.6	21.39	21.5±1
HSUPA Subtest1	4132	826.4	21.37	21.5±1
	4175	835	21.35	21.5±1
	4233	846.6	21.36	21.5±1
HSUPA Subtest2	4132	826.4	21.33	21.5±1
	4175	835	<b>21.39</b>	21.5±1
	4233	846.6	21.32	21.5±1
HSUPA Subtest3	4132	826.4	21.36	21.5±1
	4175	835	21.37	21.5±1
	4233	846.6	21.35	21.5±1
HSUPA Subtest4	4132	826.4	21.35	21.5±1
	4175	835	21.36	21.5±1
	4233	846.6	21.38	21.5±1
HSUPA Subtest5	4132	826.4	21.32	21.5±1
	4175	835	21.31	21.5±1
	4233	846.6	21.33	21.5±1

## UMTS-FDD Band II

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	9262	1852.4	22.43	22±1
	9400	1880	<b>22.50</b>	22±1
	9538	1907.6	22.48	22±1
HSDPA Subtest1	9262	1852.4	21.59	21.5±1
	9400	1880	21.57	21.5±1
	9538	1907.6	<b>21.68</b>	21.5±1
HSDPA Subtest2	9262	1852.4	21.63	21.5±1
	9400	1880	21.67	21.5±1
	9538	1907.6	21.64	21.5±1
HSDPA Subtest3	9262	1852.4	21.53	21.5±1
	9400	1880	21.51	21.5±1
	9538	1907.6	21.49	21.5±1
HSDPA Subtest4	9262	1852.4	21.50	21.5±1
	9400	1880	21.48	21.5±1
	9538	1907.6	21.53	21.5±1
HSUPA Subtest1	9262	1852.4	21.51	21.5±1
	9400	1880	21.57	21.5±1
	9538	1907.6	21.59	21.5±1
HSUPA Subtest2	9262	1852.4	21.56	21.5±1
	9400	1880	21.55	21.5±1
	9538	1907.6	21.52	21.5±1
HSUPA Subtest3	9262	1852.4	21.53	21.5±1
	9400	1880	<b>21.60</b>	21.5±1
	9538	1907.6	21.56	21.5±1
HSUPA Subtest4	9262	1852.4	21.54	21.5±1
	9400	1880	21.52	21.5±1
	9538	1907.6	21.52	21.5±1
HSUPA Subtest5	9262	1852.4	21.49	21.5±1
	9400	1880	21.32	21.5±1
	9538	1907.6	21.53	21.5±1



## ERP & EIRP

### GSM Voice

#### ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	21.86	V	6.8	0.53	<b>28.13</b>	38.45
824.2	19.97	H	6.8	0.53	26.24	38.45
836.6	21.84	V	6.8	0.53	28.11	38.45
836.6	19.92	H	6.8	0.53	26.19	38.45
848.8	21.75	V	6.9	0.53	28.12	38.45
848.8	19.83	H	6.9	0.53	26.20	38.45

#### EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	22.59	V	7.88	0.85	<b>29.62</b>	33
1850.2	21.34	H	7.88	0.85	28.37	33
1880	22.36	V	7.88	0.85	29.39	33
1880	21.47	H	7.88	0.85	28.50	33
1909.8	22.47	V	7.86	0.85	29.48	33
1909.8	21.15	H	7.86	0.85	28.16	33

## GPRS:

### ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	21.74	V	6.8	0.53	28.01	38.45
824.2	20.16	H	6.8	0.53	26.43	38.45
836.6	21.83	V	6.8	0.53	<b>28.10</b>	38.45
836.6	20.22	H	6.8	0.53	26.49	38.45
848.8	21.69	V	6.9	0.53	28.06	38.45
848.8	20.08	H	6.9	0.53	26.45	38.45

### EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	22.41	V	7.88	0.85	<b>29.44</b>	33
1850.2	21.42	H	7.88	0.85	28.45	33
1880	22.32	V	7.88	0.85	29.35	33
1880	21.54	H	7.88	0.85	28.57	33
1909.8	22.24	V	7.86	0.85	29.25	33
1909.8	21.37	H	7.86	0.85	28.38	33

## EGPRS (MCS5):

### ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	14.35	V	6.8	0.53	20.62	38.45
824.2	13.25	H	6.8	0.53	19.52	38.45
836.6	14.58	V	6.8	0.53	20.85	38.45
836.6	13.16	H	6.8	0.53	19.43	38.45
848.8	14.83	V	6.9	0.53	21.20	38.45
848.8	13.27	H	6.9	0.53	19.64	38.45

### EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	18.52	V	7.88	0.85	25.55	33
1850.2	17.63	H	7.88	0.85	24.66	33
1880	18.69	V	7.88	0.85	<b>25.72</b>	33
1880	17.41	H	7.88	0.85	24.44	33
1909.8	18.51	V	7.86	0.85	25.52	33
1909.8	17.32	H	7.86	0.85	24.33	33

## RMC

### ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	13.43	V	7.88	0.85	20.46	38.45
826.4	12.23	H	7.88	0.85	19.26	38.45
835	13.64	V	7.88	0.85	20.67	38.45
835	12.5	H	7.88	0.85	19.53	38.45
846.6	13.71	V	7.86	0.85	<b>20.72</b>	38.45
846.6	12.43	H	7.86	0.85	19.44	38.45

### EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	14.58	V	7.88	0.85	21.61	33
1852.4	13.21	H	7.88	0.85	20.24	33
1880	14.46	V	7.88	0.85	21.49	33
1880	13.54	H	7.88	0.85	20.57	33
1907.6	14.72	V	7.86	0.85	<b>21.73</b>	33
1907.6	13.61	H	7.86	0.85	20.62	33

## HSDPA

### ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
(MHz)	(dBm)	(H/V)	(dBi)	(dB)	(dBm)	(dBm)
826.4	10.16	V	6.8	0.53	16.43	38.45
826.4	9.55	H	6.8	0.53	15.82	38.45
835	10.22	V	6.8	0.53	16.49	38.45
835	9.63	H	6.8	0.53	15.90	38.45
846.6	10.39	V	6.9	0.53	<b>16.76</b>	38.45

### EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	13.75	V	7.88	0.85	20.78	33
1852.4	12.56	H	7.88	0.85	19.59	33
1880	13.62	V	7.88	0.85	20.65	33
1880	12.49	H	7.88	0.85	19.52	33
1907.6	13.81	V	7.86	0.85	<b>20.82</b>	33
1907.6	12.57	H	7.86	0.85	19.58	33

## HSUPA

### ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	10.16	V	6.8	0.53	16.43	38.45
826.4	8.79	H	6.8	0.53	15.06	38.45
835	10.03	V	6.8	0.53	16.30	38.45
835	8.93	H	6.8	0.53	15.20	38.45
846.6	10.38	V	6.9	0.53	<b>16.75</b>	38.45
846.6	9.05	H	6.9	0.53	15.42	38.45


### EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	13.43	V	7.88	0.85	20.46	33
1852.4	12.23	H	7.88	0.85	19.26	33
1880	13.64	V	7.88	0.85	20.67	33
1880	12.5	H	7.88	0.85	19.53	33
1907.6	13.71	V	7.86	0.85	<b>20.72</b>	33
1907.6	12.43	H	7.86	0.85	19.44	33

### 6.3 Peak-Average Ratio

Temperature	23°C
Relative Humidity	55%
Atmospheric Pressure	1031mbar
Test date :	August 31, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§24.232(d)	a)	The peak-to-average ratio (PAR) of the transmission may not exceed 13dB.	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<p>According with KDB 971168 v02r02</p> <p><b>5.7.2 Alternate procedure for PAPR</b></p> <p><b>5.1.2 Peak power measurements with a peak power meter</b></p> <p>The total peak output power may be measured using a broadband peak RF power meter. The power meter must have a video bandwidth that is greater than or equal to the emission bandwidth and utilize a fast-responding diode detector.</p> <p><b>5.2.3 Average power measurement with average power meter</b></p> <p>As an alternative to the use of a spectrum/signal analyzer or EMI receiver to perform a measurement of the total in-band average output power, a wideband RF average power meter with a thermocouple detector or equivalent can be used under certain conditions</p> <p>If the EUT can be configured to transmit continuously (i.e., the burst duty cycle <math>\geq 98\%</math>) and at all times the EUT is transmitting at its maximum output</p>		

Test Report	16070815-FCC-R1
Page	24 of 83

	<p>power level, then a conventional wide-band RF power meter can be used.</p> <p>If the EUT cannot be configured to transmit continuously (i.e., the burst duty cycle &lt; 98%), then there are two options for the use of an average power meter. First, a gated average power meter can be used to perform the measurement if the gating parameters can be adjusted such that the power is measured only over active transmission bursts at maximum output power levels. A conventional average power meter can also be used if the measured burst duty cycle is constant (i.e., duty cycle variations are less than <math>\pm 2</math> percent) by performing the measurement over the on/off burst cycles and then correcting (increasing) the measured level by a factor equal to <math>10\log(1/\text{duty cycle})</math></p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A  
 Test Plot ☐ Yes (See below) ☒ N/A



#### GSM : GSM 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	31.09	30.44	0.65
1880	31.53	30.45	1.08
1909.8	31.26	30.46	0.8

#### GPRS 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	31.69	30.44	1.25
1880	31.54	30.45	1.09
1909.8	31.39	30.46	0.93

#### EGPRS (MSC5) 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	27.23	26.7	0.53
1880	27.29	26.46	0.83
1909.8	27.38	26.32	1.06

**RMC : UMTS-FDD Band 2 PK-AV POWER (PART 24E)**

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	24.97	22.43	2.54
1880	25.43	22.5	2.93
1907.6	25.56	22.48	3.08

**HSDPA : UMTS-FDD Band 2 PK-AV POWER (PART 24E)**

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	24.06	21.51	2.55
1880	24.18	21.57	2.61
1907.6	24.01	21.59	2.42


**HSUPA : UMTS-FDD Band 2 PK-AV POWER (PART 24E)**

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	24.23	21.59	2.64
1880	24.19	21.57	2.62
1907.6	24.34	21.68	2.66

## 6.4 Occupied Bandwidth

Temperature	22°C
Relative Humidity	53%
Atmospheric Pressure	1029mbar
Test date :	August 29, 2016
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable
§2.1049, §22.917, §22.905 §24.238	a)	99% Occupied Bandwidth(kHz)	<input checked="" type="checkbox"/>
	b)	26 dB Bandwidth(kHz)	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<ul style="list-style-type: none"> <li>- The EUT was connected to Spectrum Analyzer and Base Station via power divider.</li> <li>- The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers.</li> </ul>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

## GSM Voice:

### Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	249.2383	327.819
190	836.6	248.3655	327.728
251	848.8	246.9076	312.466

### PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	246.4390	316.952
661	1880.0	248.5657	317.405
810	1909.8	243.0313	320.997

## GPRS:

### Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	246.9545	319.715
190	836.6	249.8162	317.805
251	848.8	246.9805	320.976

### PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	247.9378	321.449
661	1880.0	247.9250	318.072
810	1909.8	250.3100	319.915

## EGPRS (MCS 5):

### Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	247.3105	326.517
190	836.6	246.0738	317.804
251	848.8	245.4278	311.636

### PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	248.2218	316.050
661	1880.0	245.8007	320.466
810	1909.8	245.2814	320.610

**RMC:**

**UMTS-FDD Band V (Part 22H)**

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.2347	4.950
4175	835.0	4.2136	4.918
4233	846.6	4.2196	4.898

**UMTS-FDD Band II (Part 24E)**

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.2212	4.863
9400	1880.0	4.2243	4.914
9538	1907.6	4.1942	4.867

**HSDPA:**

**UMTS-FDD Band V (Part 22H)**

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.2385	4.909
4175	835.0	4.2318	4.863
4233	846.6	4.2375	4.921

**UMTS-FDD Band II (Part 24E)**

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.2302	4.921
9400	1880.0	4.2260	4.923
9538	1907.6	4.1984	4.883

**HSUPA:**

**UMTS-FDD Band V (Part 22H)**


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.2239	4.908
4175	835.0	4.2307	4.904
4233	846.6	4.2284	4.939

**UMTS-FDD Band II (Part 24E)**

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.2285	4.919
9400	1880.0	4.2234	4.915
9538	1907.6	4.2101	4.868


## Test Plots

### GSM Voice:







## GPRS:




## EGPRS (MCS5):




RMC:



## HSDPA:




# HSUPA:



## 6.5 Spurious Emissions at Antenna Terminals

Temperature	22°C
Relative Humidity	53%
Atmospheric Pressure	1029mbar
Test date :	August 29 & August 30, 2016
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable
§2.1051, §22.917(a)& §24.238(a)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<ul style="list-style-type: none"> <li>- The EUT was connected to Spectrum Analyzer and Base Station via power divider.</li> <li>- The Band Edges of low and high channels for the highest RF powers were measured.</li> <li>- Setting RBW as roughly BW/100.</li> </ul>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		


Test Data    ☒ Yes      ☐ N/A

Test Plot    ☒ Yes (See below)      ☐ N/A


## Test Plots

### GSM Voice:


### Cellular Band (Part 22H) result




## PCS Band (Part24E) result




PCS1900 - Low Channel-1




PCS 1900 - Low Channel-2




PCS1900 - Middle Channel-1



PCS 1900 - Middle Channel-2



PCS1900 - High Channel-1




PCS 1900 - High Channel-2




## GPRS:


### Cellular Band (Part 22H) result




GSM 850 - Low Channel-1




GSM 850 - Low Channel-2




GSM 850 Middle Channel-1



GSM 850 Middle Channel-2




GSM 850 - High Channel-1




GSM 850 - High Channel-2

## PCS Band (Part24E) result




## EGPRS (MCS 5):

### Cellular Band (Part 22H) result




## PCS Band (Part24E) result




## RMC


### UMTS-FDD Band V (Part 22H)




Band V - Low Channel-1




Band V - Low Channel-2




Band V - Middle Channel-1



Band V - Middle Channel-2




Band V - High Channel-1




Band V - High Channel-2


## UMTS-FDD Band II (Part 24E)




Band II - Low Channel-1




Band II - Low Channel-2




Band II - Middle Channel-1



Band II - Middle Channel-2




Band II - High Channel-1




Band II - High Channel-2

## HSDPA:


### UMTS-FDD Band V (Part 22H)




Band V - Low Channel-1




Band V - Low Channel-2




Band V - Middle Channel-1



Band V - Middle Channel-2




Band V - High Channel-1




Band V - High Channel-2


## UMTS-FDD Band II (Part 24E)




Band II - Low Channel-1




Band II - Low Channel-2




Band II - Middle Channel-1



Band II - Middle Channel-2



Band II - High Channel-1




Band II - High Channel-2




HSUPA:


UMTS-FDD Band V (Part 22H)




Band V - Low Channel-1




Band V - Low Channel-2




Band V - Middle Channel-1



Band V - Middle Channel-2




Band V - High Channel-1




Band V - High Channel-2


## UMTS-FDD Band II (Part 24E)




Band II - Low Channel-1




Band II - Low Channel-2




Band II - Middle Channel-1



Band II - Middle Channel-2



Band II - High Channel-1




Band II - High Channel-2

## 6.6 Spurious Radiated Emissions

Temperature	23°C
Relative Humidity	55%
Atmospheric Pressure	1031mbar
Test date :	August 31, 2016
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable
§2.1053, §22.917 & §24.238	a)	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.	<input checked="" type="checkbox"/>

Test setup	
------------	--

Test Procedure	<ol style="list-style-type: none"> <li>The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.</li> <li>The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.</li> <li>Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.</li> </ol> <p>Sample Calculation:</p> <p>EUT Field Strength = Raw Amplitude (dBμV/m) – Amplifier Gain (dB) + Antenna Factor (dB) + Cable Loss (dB) + Filter Attenuation (dB, if used)</p>
----------------	---

Test Report	16070815-FCC-R1
Page	52 of 83

Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

## Cellular Band (Part 22H) result

### Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1648.4	-43.62	V	7.95	0.78	-36.45	-13	-23.45
1648.4	-44.25	H	7.95	0.78	-37.08	-13	-24.08
329.3	-52.78	V	6.4	0.26	-46.64	-13	-33.64
606.2	-53.03	H	6.8	0.37	-46.60	-13	-33.6

### Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1673.2	-43.56	V	7.95	0.78	-36.39	-13	-23.39
1673.2	-44.38	H	7.95	0.78	-37.21	-13	-24.21
329.7	-52.94	V	6.4	0.26	-46.80	-13	-33.8
606.8	-53.27	H	6.8	0.37	-46.84	-13	-33.84

### High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1697.6	-43.09	V	7.95	0.78	-35.92	-13	-22.92
1697.6	-43.72	H	7.95	0.78	-36.55	-13	-23.55
328.9	-52.48	V	6.4	0.26	-46.34	-13	-33.34
604.7	-52.64	H	6.8	0.37	-46.21	-13	-33.21

#### Note:

1, The testing has been conformed to  $10 \times 848.8 \text{ MHz} = 8,488 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, GSM voice, GPRS and EGPRS mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

## PCS Band (Part24E) result

### Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3700.4	-48.52	V	10.25	2.73	-41.00	-13	-28
3700.4	-49.37	H	10.25	2.73	-41.85	-13	-28.85
329.6	-53.69	V	6.4	0.26	-47.55	-13	-34.55
605.2	-53.81	H	6.8	0.37	-47.38	-13	-34.38

### Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-48.76	V	10.25	2.73	-41.24	-13	-28.24
3760	-49.61	H	10.25	2.73	-42.09	-13	-29.09
329.7	-53.79	V	6.4	0.26	-47.65	-13	-34.65
605.4	-53.93	H	6.8	0.37	-47.50	-13	-34.5

### High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3819.6	-48.56	V	10.36	2.73	-40.93	-13	-27.93
3819.6	-49.43	H	10.36	2.73	-41.80	-13	-28.8
328.7	-53.64	V	6.4	0.26	-47.50	-13	-34.5
604.6	-52.05	H	6.8	0.37	-45.62	-13	-32.62

#### Note:

1, The testing has been conformed to  $10 \times 1909.8 \text{ MHz} = 19,098 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, GSM voice, GPRS and EGPRS mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

## UMTS-FDD Band V (Part 22H)

### Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1652.8	-46.89	V	7.95	0.78	-39.72	-13	-26.72
1652.8	-45.26	H	7.95	0.78	-38.09	-13	-25.09
329.1	-52.68	V	6.4	0.26	-46.54	-13	-33.54
606.5	-53.07	H	6.8	0.37	-46.64	-13	-33.64

### Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1670	-46.39	V	7.95	0.78	-39.22	-13	-26.22
1670	-45.47	H	7.95	0.78	-38.30	-13	-25.3
328.5	-52.46	V	6.4	0.26	-46.32	-13	-33.32
606.3	-52.33	H	6.8	0.37	-45.90	-13	-32.9

### High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1693.2	-46.44	V	7.95	0.78	-39.27	-13	-26.27
1693.2	-45.38	H	7.95	0.78	-38.21	-13	-25.21
327.6	-52.49	V	6.4	0.26	-46.35	-13	-33.35
605.2	-52.16	H	6.8	0.37	-45.73	-13	-32.73

#### Note:

1, The testing has been conformed to  $10 \times 846.6 \text{ MHz} = 8,466 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

## UMTS-FDD Band II (Part 24E)

### Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3704.8	-49.67	V	10.25	2.73	-42.15	-13	-29.15
3704.8	-48.69	H	10.25	2.73	-41.17	-13	-28.17
330.1	-53.26	V	6.4	0.26	-47.12	-13	-34.12
604.8	-52.98	H	6.8	0.37	-46.55	-13	-33.55

### Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-49.75	V	10.25	2.73	-42.23	-13	-29.23
3760	-48.78	H	10.25	2.73	-41.26	-13	-28.26
329.6	-53.46	V	6.4	0.26	-47.32	-13	-34.32
305.1	-52.74	H	6.8	0.37	-46.31	-13	-33.31

### High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3815.2	-49.62	V	10.36	2.73	-41.99	-13	-28.99
3815.2	-48.65	H	10.36	2.73	-41.02	-13	-28.02
329.3	-53.44	V	6.4	0.26	-47.30	-13	-34.30
605.8	-53.12	H	6.8	0.37	-46.69	-13	-33.69

#### Note:

1, The testing has been conformed to  $10 \times 1907.6 \text{ MHz} = 19,076 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases


4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case



## 6.7 Band Edge

Temperature	22°C
Relative Humidity	53%
Atmospheric Pressure	1029mbar
Test date :	August 29 & August 31, 2016
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable
§22.917(a) §24.238(a)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.	<input checked="" type="checkbox"/>
Test setup			
Procedure	<ul style="list-style-type: none"> <li>- The EUT was connected to Spectrum Analyzer and Base Station via power divider.</li> <li>- The Band Edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.</li> </ul>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data    ☒ Yes      ☐ N/A

Test Plot    ☒ Yes (See below)      ☐ N/A

**GSM Voice:**

**Cellular Band (Part 22H) result**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9947	-16.24	-13
849.0150	-16.44	-13

**PCS Band (Part24E) result**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9950	-20.45	-13
1910.0175	-19.83	-13

**GPRS:**

**Cellular Band (Part 22H) result**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9775	-17.27	-13
849.0250	-16.74	-13

**PCS Band (Part24E) result**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9925	-20.35	-13
1910.0200	-19.67	-13

**EGPRS (MCS5):**

**Cellular Band (Part 22H) result**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9947	-16.59	-13
849.0225	-14.98	-13

**PCS Band (Part24E) result**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9990	-21.46	-13
1910.0225	-21.02	-13

**RMC:**

**UMTS-FDD Band V (Part 22H)**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.075	-21.11	-13
850.025	-16.99	-13

**UMTS-FDD Band II (Part 24E)**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.975	-24.52	-13
1910.025	-28.35	-13

### HSDPA:

#### UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.000	-21.83	-13
849.050	-18.65	-13

#### UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.625	-24.93	-13
1910.200	-27.12	-13

### HSUPA:

#### UMTS-FDD Band V (Part 22H)


		Limit (dBm)
823.975	-20.73	-13
849.225	-19.87	-13

#### UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.975	-23.99	-13
1910.200	-27.92	-13


## GSM Voice:

### Test Plots




Cellular Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log  
(3.28/3)=4.0+0.4=4.4dB




Cellular Band - High Channel

Note: Offset=Cable loss (4.0) + 10log  
(3.12/3)=4.0+0.2=4.2dB



PCS Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log  
(3.17/3)=4.0+0.2=4.2dB




PCS Band - High Channel

Note: Offset=Cable loss (4.0) + 10log  
(3.21/3)=4.0+0.3=4.3dB


## GPRS:

### Test Plots




## EGPRS (MCS5):

### Test Plots




**RMC:**




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log  
(49.50/30)=4.0+2.2=6.2 dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log  
(48.98/30)=4.0+2.1=6.1 dB



UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log  
(48.63/30)=4.5+2.1=6.6 dB




UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log  
(48.67/30)=4.5+2.1=6.6 dB




## HSDPA:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log  
(49.09/30)=4.0+2.1=6.1 dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log  
(49.21/30)=4.0+2.2=6.2 dB



UMTS-FDD Band II - Low Channel


Note: Offset=Cable loss (4.5) + 10log  
(49.21/30)=4.5+2.1=6.6 dB



UMTS-FDD Band II - High Channel


Note: Offset=Cable loss (4.5) + 10log  
(48.83/30)=4.5+2.1=6.6 dB

# HSUPA:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log  
(49.08/30)=4.0+2.1=6.1 dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log  
(49.39/30)=4.0+2.1=6.1 dB



UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log  
(49.19/30)=4.5+2.1=6.6dB





UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log  
(48.68/30)=4.5+2.1=6.6 dB

## 6.8 Frequency Stability

Temperature	23°C
Relative Humidity	55%
Atmospheric Pressure	1031mbar
Test date :	August 31, 2016
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable																																
§2.1055, §22.355 & §24.235	a)	<p>According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:</p> <p>Frequency Tolerance for Transmitters in the Public Mobile Services</p> <table border="1"> <thead> <tr> <th>Frequency Range (MHz)</th><th>Base, fixed (ppm)</th><th>Mobile ≤ 3 watts (ppm)</th><th>Mobile ≤ 3 watts (ppm)</th></tr> </thead> <tbody> <tr> <td>25 to 50</td><td>20.0</td><td>20.0</td><td>50.0</td></tr> <tr> <td>50 to 450</td><td>5.0</td><td>5.0</td><td>50.0</td></tr> <tr> <td>45 to 512</td><td>2.5</td><td>5.0</td><td>.0</td></tr> <tr> <td>821 to 896</td><td>1.5</td><td>2.5</td><td>2.5</td></tr> <tr> <td>928 to 29.</td><td>5.0</td><td>N/A</td><td>N/A</td></tr> <tr> <td>929 to 960.</td><td>1.5</td><td>N/A</td><td>N/A</td></tr> <tr> <td>2110 to 2220</td><td>10.0</td><td>N/A</td><td>N/A</td></tr> </tbody> </table> <p>According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized frequency block.</p>	Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)	25 to 50	20.0	20.0	50.0	50 to 450	5.0	5.0	50.0	45 to 512	2.5	5.0	.0	821 to 896	1.5	2.5	2.5	928 to 29.	5.0	N/A	N/A	929 to 960.	1.5	N/A	N/A	2110 to 2220	10.0	N/A	N/A	
Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)																																
25 to 50	20.0	20.0	50.0																																
50 to 450	5.0	5.0	50.0																																
45 to 512	2.5	5.0	.0																																
821 to 896	1.5	2.5	2.5																																
928 to 29.	5.0	N/A	N/A																																
929 to 960.	1.5	N/A	N/A																																
2110 to 2220	10.0	N/A	N/A																																
Test setup																																			

Test Report	16070815-FCC-R1
Page	68 of 83

Procedure	A communication link was established between EUT and base station. The frequency error was monitored and measured by base station under variation of ambient temperature and variation of primary supply voltage. Limit: The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ( $\pm 2.5\text{ppm}$ ) of the center frequency.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

**GSM Voice:**

**Cellular Band (Part 22H) result**

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	21	0.0251	2.5
0		19	0.0227	2.5
10		15	0.0179	2.5
20		15	0.0179	2.5
30		14	0.0167	2.5
40		20	0.0239	2.5
50		19	0.0227	2.5
55		20	0.0239	2.5
25	4.2	19	0.0227	2.5
	3.5	21	0.0251	2.5

**PCS Band (Part 24E) result**

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	11	0.0059	2.5
0		14	0.0074	2.5
10		13	0.0069	2.5
20		10	0.0053	2.5
30		16	0.0085	2.5
40		17	0.0090	2.5
50		13	0.0069	2.5
55		15	0.0080	2.5
25	4.2	17	0.0090	2.5
	3.5	19	0.0101	2.5

RMC:

**UMTS-FDD Band V (Part 22H)**

Middle Channel, $f_0 = 835$ MHz				
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	16	0.0192	2.5
0		14	0.0168	2.5
10		13	0.0156	2.5
20		14	0.0168	2.5
30		12	0.0144	2.5
40		11	0.0132	2.5
50		16	0.0192	2.5
55		16	0.0192	2.5
25	4.2	12	0.0144	2.5
	3.5	20	0.0240	2.5

**UMTS-FDD Band II (Part 24E)**

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	19	0.0101	2.5
0		10	0.0053	2.5
10		11	0.0059	2.5
20		11	0.0059	2.5
30		12	0.0064	2.5
40		15	0.0080	2.5
50		11	0.0059	2.5
55		13	0.0069	2.5
25	4.2	14	0.0074	2.5
	3.5	16	0.0085	2.5

## Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
<b>RF Conducted Test</b>					
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	MY45108319	09/16/2015	09/15/2016	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>
Temperature/Humidity Chamber	UHL-270	001	10/09/2015	10/08/2016	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
RF Power Sensor	Dare RPR3006C/P/W	AY554013	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
<b>Radiated Emissions</b>					
EMI test receiver	ESL6	100262	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/24/2016	03/23/2017	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/21/2015	09/20/2016	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~2GHz)	JB1	A112017	09/21/2015	09/20/2016	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71259	09/24/2015	09/23/2016	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	<input checked="" type="checkbox"/>
SYNTHESIZED SIGNAL GENERATOR	8665B	3744A01293	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Power Amplifier	SMC150D	R1553-0313	03/09/2016	03/08/2017	<input checked="" type="checkbox"/>
Power Amplifier	S41-25D	R1553-0314	05/27/2016	05/26/2017	<input checked="" type="checkbox"/>
Tunable Notch Filter	3NF-800/1000-S	AA4	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>


Test Report	16070815-FCC-R1
Page	72 of 83


Tunable Notch Filter	3NF- 1000/2000-S	AM 4	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
----------------------	---------------------	------	------------	------------	-------------------------------------




## Annex B. EUT And Test Setup Photographs

### Annex B.i. Photograph: EUT External Photo







EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View



## Annex B.ii. Photograph: EUT Internal Photo




Cover Off - Top View 1




Cover Off - Top View 2




Battery - Front View



Battery - Rear View




Mainboard with Shielding - Front View




Mainboard without Shielding - Front View







Mainboard with Shielding - Rear View



Mainboard without Shielding - Rear View



Small Board - Front View



Small Board - Rear View




LCD - Front View



LCD - Rear View





GSM/PCS/UMTS-FDD Antenna View




WIFI/BT/BLE/GPS - Antenna View




LTE Antenna View

**Annex B.iii. Photograph: Test Setup Photo**



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above  
1GHz

## Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

### Annex C.ii. TEST SET UP BLOCK

#### Block Configuration Diagram for Radiated Emissions



## **Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION**

The following is a description of supporting equipment and details of cables used with the EUT.

### **Supporting Equipment:**

Manufacturer	Equipment Description	Model	Serial No
MOBIWIRE MOBILES (NINGBO) CO.,LTD	Adapter	S005UA0500100	CBA3000AH0C1

### **Supporting Cable:**

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	CBA3000AH0C1



Test Report	16070815-FCC-R1
Page	81 of 83

## Annex C.ii. EUT OPERATING CONKITIONS

N/A

Test Report	16070815-FCC-R1
Page	82 of 83

## Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Test Report	16070815-FCC-R1
Page	83 of 83

## Annex E. DECLARATION OF SIMILARITY

N/A