

# Northwest Instrument INC

## MPE ASSESSMENT REPORT

**Report Type:**

FCC Part §2.1091, §2.1093 and §1.1307(b) assessment report

**Model:**

Carta

**REPORT NUMBER:**

190502535SHA-002

**ISSUE DATE:**

June 21, 2019

**DOCUMENT CONTROL NUMBER:**

TTRFFCCMPE-01\_V1 © 2018 Intertek



**Applicant:** Northwest Instrument INC  
69 King Street, Dover, NJ 07801, USA

**Manufacturer:** Northwest Instrument INC  
69 King Street, Dover, NJ 07801, USA

**Manufacturing Site:** Rosenberger Technology (kunshan)Co., Ltd  
No. 6, Shen'an Rd., Dianshanhu, Kunshan, Suzhou, Jiangsu, China, 215345

**Product Name:** Smart Wheel

**Type/Model:** Carta

**FCC ID:** 2ADA6CARTA

**SUMMARY:**

The equipment complies with the requirements according to the following standard(s) or Specification:

KDB447498 D01 General RF Exposure Guidance v06  
FCC Part2.1091, FCC Part2.1093 FCC Part1.1307(b)

**PREPARED BY:**

Project Engineer  
Wade Zhang

**REVIEWED BY:**

Reviewer  
Daniel Zhao

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

## Revision History

Report No.	Version	Description	Issued Date
190502535SHA-002	Rev. 01	Initial issue of report	June 21, 2019

## 1 GENERAL INFORMATION

### 1.1 Description of Equipment Under Test (EUT)

Product name:	Smart Wheel
Type/Model:	Carta
Description of EUT:	The EUT is a smart wheel which was installed a Bluetooth low energy module, there have only one model.
Rating:	DC4.5V
Category of EUT:	Class B
EUT type:	<input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing
Software Version:	/
Hardware Version:	/
Sample received date:	May 24, 2019
Date of test:	May 24, 2019 ~ June 21, 2019

### 1.2 Technical Specification

Frequency Range:	2400MHz ~ 2483.5MHz
Support Standards:	Bluetooth 4.2 (BLE)
Type of Modulation:	GFSK
Channel Number:	40 (0-39)
Data Rate:	1Mbps
Power Class:	Class II
Channel Separation:	2 MHz

Antenna information:			
No.	Antenna Type	Gain (dBi)	Note
1	Internal PCB antenna	3.3dBi	/

## TEST REPORT

### 1.3 Description of Test Facility

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN1175
	IC Registration Lab CAB identifier.: CN0051
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

## TEST REPORT

## 2 MPE Assessment

Test result: Pass

### 2.1 MPE Assessment Limit

Mobile device exposure for standalone operations:

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (uT)	Equivalent plane wave power density $S_{eq}$ (W/m <sup>2</sup> )
0-1 Hz	-	$3,2 \times 10^4$	$4 \times 10^4$	-
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	-
8-25 Hz	10 000	$4\,000/f$	$5\,000/f$	-
0,025-0,8 kHz	$250/f$	$4/f$	$5/f$	-
0,8-3 kHz	$250/f$	5	6,25	-
3-150 kHz	87	5	6,25	-
0,15-1 MHz	87	$0,73/f$	$0,92/f$	-
1-10 MHz	$87/f^{1/2}$	$0,73/f$	$0,92/f$	-
10-400 MHz	28	0,073	0,092	2
400-2 000 MHz	$1,375 f^{1/2}$	$0,0037 f^{1/2}$	$0,0046 f^{1/2}$	$f/200$
2-300 GHz	61	0,16	0,20	10

Mobile device exposure for simultaneous transmission operations: **the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is  $\leq 1.0$**

## 2.2 Assessment Results

Power density (S) is calculated according to the formula:

$$S = PG / (4\pi R^2)$$

Where S = power density in mW/cm<sup>2</sup>

P = Radiated transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

As we can see from the test report 190402511SHA-001:

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

Frequency band	Power		Antenna Gain		R	S	Limits
(MHz)	dBm	mW	dBi	(Numeric)	(cm)	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
2402 - 2480	-0.08	0.98	3.3	2.14	20	0.0004	1

Note: 1 mW/cm<sup>2</sup> from 1.310 Table 1

## Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended.

\*\*\*\*\* END \*\*\*\*\*