

**GREE Electric Appliances, Inc. of Zhuhai**

Application  
For  
Certification

**FCC ID: 2ADAP-CS532Y**

**WiFi Module**

**Model: CS532Y**

**Brand name: GREE**

**2.4GHz WiFi Transceiver Module**

**Report No.: 150715018SZN-001**

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-14]

Prepared and Checked by:

Approved by:

Sign on file

Jenner Liu  
Engineer

---

Andy Yan  
Senior Project Engineer  
Date: September 15, 2015

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF no.: FCC 15C\_Tx\_c

**Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch**

6F, D Block, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China  
Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751 Website: [www.china.intertek-etlsemko.com](http://www.china.intertek-etlsemko.com)

## LIST OF EXHIBITS

### *INTRODUCTION*

<i>EXHIBIT 1:</i>	Summary of Tests
<i>EXHIBIT 2:</i>	General Description
<i>EXHIBIT 3:</i>	System Test Configuration
<i>EXHIBIT 4:</i>	Measurement Results
<i>EXHIBIT 5:</i>	Equipment Photographs
<i>EXHIBIT 6:</i>	Product Labeling
<i>EXHIBIT 7:</i>	Technical Specifications
<i>EXHIBIT 8:</i>	Instruction Manual
<i>EXHIBIT 9:</i>	Confidentiality Request
<i>EXHIBIT 10:</i>	Miscellaneous Information
<i>EXHIBIT 11:</i>	Test Equipment List

# INTERTEK TESTING SERVICES

## MEASUREMENT/TECHNICAL REPORT

### WiFi Module

**Model: CS532Y**

**FCC ID: 2ADAP-CS532Y**

This report concerns (check one) Original Grant ☒ Class II Change ☐

Equipment Type: DTS - Part 15 Digital Transmission Systems (WiFi transmitter portion)

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes ☐ No ☒

If yes, defer until :   
date

Company Name agrees to notify the Commission by:   
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes ☐ No ☒

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-01-14] Edition] provision.

Report prepared by:

Jenner Liu  
Intertek Testing Services Shenzhen Ltd.  
Kejiyuan Branch  
6F, Block D, Huahan Building, Langshan Road,  
Nanshan District, Shenzhen, P. R. China  
Phone: (86 755) 8614 0639  
Fax: (86 755) 8614 6751

# INTERTEK TESTING SERVICES

---

## Table of Contents

1.0	<b><u>Summary of Test results</u></b>	2
2.0	<b><u>General Description</u></b>	4
2.1	Product Description	4
2.2	Related Submittal(s) Grants	5
2.3	Test Methodology	5
2.4	Test Facility	5
3.0	<b><u>System Test Configuration</u></b>	7
3.1	Justification	7
3.2	EUT Exercising Software	7
3.3	Special Accessories	8
3.4	Measurement Uncertainty	8
3.5	Equipment Modification	8
3.6	Support Equipment List and Description	8
4.0	<b><u>Measurement Results</u></b>	10
4.1	Maximum Conducted Output Power at Antenna Terminals	10
4.2	Minimum 6 dB RF Bandwidth	12
4.3	Maximum Power Density Reading	22
4.4	Out of Band Conducted Emissions	31
4.5	Out of Band Radiated Emissions	52
4.6	Transmitter Radiated Emissions in Restricted Bands	53
4.7	Field Strength Calculation	54
4.8	Radiated Spurious Emission	55
4.9	Conducted Emission	69
4.10	Radiated Emissions from Digital Section of Transceiver	72
4.11	Transmitter Duty Cycle Calculation and Measurements	73
5.0	<b><u>Equipment Photographs</u></b>	75
6.0	<b><u>Product Labelling</u></b>	77
7.0	<b><u>Technical Specifications</u></b>	79
8.0	<b><u>Instruction Manual</u></b>	81
9.0	<b><u>Confidentiality Request</u></b>	83
10.0	<b><u>Discussion of Pulse Desensitization</u></b>	85
11.0	<b><u>Test Equipment List</u></b>	87

## INTERTEK TESTING SERVICES

---

### List of attached file

Exhibit type	File Description	Filename
Test Report	Test Report	report.pdf
Test Setup Photo	Radiated Emission	radiated photos.pdf
Test Setup Photo	Conducted Emission	conducted photos.pdf
External Photo	External Photo	external photos.pdf
Internal Photo	Internal Photo	internal photos.pdf
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
Operation Description	Technical Description	descri.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Cover Letter	Confidentiality Letter	request.pdf
Cover Letter	Certification of Agreement	agreement.pdf
Cover Letter	Letter of Agency	agency.pdf

# **INTERTEK TESTING SERVICES**

---

## **EXHIBIT 1**

### **SUMMARY OF TEST RESULTS**

## INTERTEK TESTING SERVICES

---

### 1.0 Summary of Test results

#### WiFi Module

**Model: CS532Y**

**FCC ID: 2ADAP-CS532Y**

TEST	REFERENCE	RESULTS
Max. Output power	15.247(b)(3)	Pass
6 dB Bandwidth	15.247(a)(2)	Pass
Max. Power Density	15.247(e)	Pass
Out of Band Antenna Conducted Emission	15.247(d)	Pass
Radiated Emission in Restricted Bands	15.247(d)	Pass
AC Conducted Emission	15.207	Pass
Antenna Requirement	15.203	Pass (See Notes)

Notes: The EUT uses an Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

**EXHIBIT 2**

**GENERAL DESCRIPTION**



## INTERTEK TESTING SERVICES

---

### 2.0 **General Description**

#### 2.1 Product Description

The Equipment Under Test (EUT) is a WiFi Module with WiFi function operating at 2412-2462MHz for 802.11b/g/n-HT20, 11 channels with 5MHz channel spacing and 2422-2452MHz for 802.11n-HT40, 9 channels with 5MHz channel spacing. The EUT was powered by D.C. 3.3V. For more detailed features description, please refer to the user's manual.

Type of Modulation: BPSK, QPSK, 16QAM, 64QAM, CCK, DQPSK, DBPSK.

Antenna Type: Integral Antenna.

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

## INTERTEK TESTING SERVICES

---

### 2.2 Related Submittal(s) Grants

This is an application for certification of:

DTS- Part 15 Digital Transmission Systems (WiFi transmitter portion), and the 2.4GHz transmitter portion is subject to the report 150715018SZN-002.

### 2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10: 2013 and KDB 558074 D01 v03r03. Radiated emission was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the “**Justification Section**” of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

### 2.4 Test Facility

The Semi-Anechoic chamber and shield room used to collect the radiated data and conducted data are **Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch** and located at 6F, Block D, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: 242492).

**EXHIBIT 3**

**SYSTEM TEST CONFIGURATION**

## INTERTEK TESTING SERVICES

---

### 3.0 System Test Configuration

#### 3.1 Justification

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables were manipulated to produce worst case emissions. The EUT was powered by D.C. 3.3V through USB adaptor and the USB adaptor was powered by USB port of Laptop during the testing (AC 120V/60Hz for laptop power supply). Only the worst case data was reported.

The simultaneous transmission spurious was tested, only the worst case data was recorded in this report. On 802.11b, g, n (20MHz & 40MHz) mode, only one antenna is used, and all data rate were tested and only the worst case data is shown in the report.

For maximizing emissions, the EUT was rotated through 360°, the EUT was placed on the styrene turntable with 0.8m up to 1GHz and 1.5 m above 1GHz. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

The rear of unit was flushed with the rear of the table when it was powered by Laptop up to 1GHz and placed in the centre of turntable above 1GHz.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

#### 3.2 EUT Exercising Software

The EUT exercise program (provided by client) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The worst case configuration is used in all specified testing.

The parameters of test software setting:

During the test, Channel and power controlling software provided by the applicant was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the application and is going to be fixed on the firmware of the end product.

## INTERTEK TESTING SERVICES

---

### 3.3 Special Accessories

N/A.

### 3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

Uncertainty and Compliance – Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value.

### 3.5 Equipment Modification

Any modifications installed previous to testing by GREE Electric Appliances, Inc. of Zhuhai will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch.

### 3.6 Support Equipment List and Description

This product was tested in the following configuration:

Refer List:

Description	Manufacturer	Model No.
Laptop	LENOVO	X1
USB adaptor with USB cable (Un-shielded, 100cm)	N/A	N/A

## **INTERTEK TESTING SERVICES**

---

### **EXHIBIT 4**

### **MEASUREMENT RESULTS**

## INTERTEK TESTING SERVICES

Applicant: GREE Electric Appliances, Inc. of Zhuhai

Date of Test: September 14, 2015

Model: CS532Y

### 4.0 **Measurement Results**

#### 4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(3):

The antenna power of the EUT was connected to the input of a broadband peak RF power meter. The power meter have a video bandwidth that is greater than DTS bandwidth and utilize a fast-responding diode detector. Power was read directly at the EUT antenna terminals with cable loss added.

For antennas with gains of 6 dBi or less, maximum allowed Transmitter output is 1 watt (+30 dBm).

IEEE 802.11b (Antenna Gain = 1.0dBi) (CCK, 1Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2412	15.20	33.11
Middle Channel: 2437	15.60	36.31
High Channel: 2462	15.50	35.48

IEEE 802.11g (Antenna Gain = 1.0dBi) (16QAM, 6Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2412	14.40	27.54
Middle Channel: 2437	14.20	26.30
High Channel: 2462	14.30	26.92

## INTERTEK TESTING SERVICES

IEEE 802.11n-HT20 (Antenna Gain = 1.0dBi) (16QAM, 6.5Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2412	13.50	22.39
Middle Channel: 2437	13.00	19.95
High Channel: 2462	13.10	20.42

IEEE 802.11n-HT40 (Antenna Gain = 1.0dBi) (64QAM, 13.5Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2422	12.10	16.22
Middle Channel: 2437	12.00	15.85
High Channel: 2452	12.50	17.78

Cable loss: 0.5 dB    External Attenuation: 0 dB

Cable loss, external attenuation has been included in OFFSET function

EUT max. output level = 15.60dBm

For RF Exposure, the information is saved with filename: RF exposure.pdf.



## INTERTEK TESTING SERVICES

Applicant: GREE Electric Appliances, Inc. of Zhuhai

Date of Test: September 14, 2015

Model: CS532Y

### 4.2 Minimum 6 dB RF Bandwidth, FCC Rule 15.247(a)(2):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100 KHz according to FCC KDB 558074 D01 v03r03. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 6 dB lower than PEAK level. The 6dB bandwidth was determined from where the channel output spectrum intersected the display line.

Limit: The 6 dB Bandwidth is at least 500 kHz.

IEEE 802.11b (CCK, 1Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	10.116
2437	10.116
2462	10.116

IEEE 802.11g (16QAM, 6Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	16.368
2437	16.368
2462	16.368

IEEE 802.11n-HT20 (16QAM, 6.5Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	17.583
2437	17.583
2462	17.583

## INTERTEK TESTING SERVICES



---

IEEE 802.11n-HT40 (64QAM, 13.5Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2422	36.230
2437	36.230
2452	36.353

The test plots are attached as below.


# INTERTEK TESTING SERVICES

802.11b





TRF no.: FCC 15C\_TX\_c  
 FCC ID: 2ADAP-CS532Y  
 Report No.: 150715018SZN-001

# INTERTEK TESTING SERVICES




# INTERTEK TESTING SERVICES

802.11g





TRF no.: FCC 15C\_TX\_c  
 FCC ID: 2ADAP-CS532Y  
 Report No.: 150715018SZN-001

# INTERTEK TESTING SERVICES




# INTERTEK TESTING SERVICES

802.11n-HT20



TRF no.: FCC 15C\_TX\_c  
 FCC ID: 2ADAP-CS532Y  
 Report No.: 150715018SZN-001



# INTERTEK TESTING SERVICES






# INTERTEK TESTING SERVICES

802.11n-HT40



TRF no.: FCC 15C\_TX\_c  
FCC ID: 2ADAP-CS532Y  
Report No.: 150715018SZN-001

# INTERTEK TESTING SERVICES



## INTERTEK TESTING SERVICES

Applicant: GREE Electric Appliances, Inc. of Zhuhai

Date of Test: September 14, 2015

Model: CS532Y

### 4.3 Maximum Power Density Reading, FCC Rule 15.247(e):

The Measurement Procedure PKPSD was set according to the FCC KDB 558074 D01 v03r03.

Antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.

Limit: The Power Density does not exceed 8dBm/3 kHz.

IEEE 802.11b (CCK, 1Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2412	3.13
2437	4.04
2462	3.96

IEEE 802.11g (16QAM, 6Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2412	-7.60
2437	-7.42
2462	-7.46

IEEE 802.11n-HT20 (16QAM, 6.5Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2412	-8.13
2437	-8.49
2462	-8.64

IEEE 802.11n-HT40 (64QAM, 13.5Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2422	-12.31
2437	-12.27
2452	-12.57

The test plots are attached as below.



TRF no.: FCC 15C\_TX\_c

FCC ID: 2ADAP-CS532Y

Report No.: 150715018SZN-001


## INTERTEK TESTING SERVICES

802.11b





TRF no.: FCC 15C\_TX\_c  
FCC ID: 2ADAP-CS532Y  
Report No.: 150715018SZN-001

## INTERTEK TESTING SERVICES




## INTERTEK TESTING SERVICES

802.11g



TRF no.: FCC 15C\_TX\_c  
FCC ID: 2ADAP-CS532Y  
Report No.: 150715018SZN-001



## INTERTEK TESTING SERVICES



TRF no.: FCC 15C\_TX\_c  
FCC ID: 2ADAP-CS532Y  
Report No.: 150715018SZN-001

## INTERTEK TESTING SERVICES


802.11n-HT20



TRF no.: FCC 15C\_TX\_c  
FCC ID: 2ADAP-CS532Y  
Report No.: 150715018SZN-001





## INTERTEK TESTING SERVICES



TRF no.: FCC 15C\_TX\_c  
FCC ID: 2ADAP-CS532Y  
Report No.: 150715018SZN-001


## INTERTEK TESTING SERVICES

802.11n-HT40



TRF no.: FCC 15C\_TX\_c  
FCC ID: 2ADAP-CS532Y  
Report No.: 150715018SZN-001

## INTERTEK TESTING SERVICES



TRF no.: FCC 15C\_TX\_c  
FCC ID: 2ADAP-CS532Y  
Report No.: 150715018SZN-001

## INTERTEK TESTING SERVICES

---

Applicant: GREE Electric Appliances, Inc. of Zhuhai  
Date of Test: September 14, 2015  
Model: CS532Y

### 4.4 Out of Band Conducted Emissions, FCC Rule 15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. The Measurement Procedure was set according to the FCC KDB 558074 D01 v03r03.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.

Refer to the attached test plots for out of band conducted emissions data with rate of 1Mbps for 802.11b, 6Mbps for 802.11g, 6.5Mbps for 802.11n-HT20 and 13.5Mbps for 802.11n-HT40.



The test plots showed all spurious emission up to the tenth harmonic were measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

The test plots are attached as below.

# INTERTEK TESTING SERVICES


802.11b

Channel 01 (2412MHz) Reference Level: 3.13dBm





TRF no.: FCC 15C\_TX\_c  
FCC ID: 2ADAP-CS532Y  
Report No.: 150715018SZN-001

## INTERTEK TESTING SERVICES



## INTERTEK TESTING SERVICES



Channel 06 (2437MHz) Reference Level: 4.04dBm



TRF no.: FCC 15C\_TX\_c  
FCC ID: 2ADAP-CS532Y  
Report No.: 150715018SZN-001

# INTERTEK TESTING SERVICES

Channel 11 (2462MHz) Reference Level: 3.96dBm



TRF no.: FCC 15C\_TX\_c  
FCC ID: 2ADAP-CS532Y  
Report No.: 150715018SZN-001





## INTERTEK TESTING SERVICES



# INTERTEK TESTING SERVICES

802.11g

Channel 01 (2412MHz) Reference Level: -7.60dBm




TRF no.: FCC 15C\_TX\_c

FCC ID: 2ADAP-CS532Y



Report No.: 150715018SZN-001

## INTERTEK TESTING SERVICES



# INTERTEK TESTING SERVICES


Channel 06 (2437MHz) Reference Level: -7.42dBm



TRF no.: FCC 15C\_TX\_c  
 FCC ID: 2ADAP-CS532Y  
 Report No.: 150715018SZN-001


# INTERTEK TESTING SERVICES

Channel 11 (2462MHz) Reference Level: -7.46dBm



TRF no.: FCC 15C\_TX\_c  
 FCC ID: 2ADAP-CS532Y  
 Report No.: 150715018SZN-001



## INTERTEK TESTING SERVICES



# INTERTEK TESTING SERVICES


802.11n-HT20

Channel 01 (2412MHz) Reference Level: -8.13dBm



TRF no.: FCC 15C\_TX\_c  
FCC ID: 2ADAP-CS532Y  
Report No.: 150715018SZN-001



## INTERTEK TESTING SERVICES





## INTERTEK TESTING SERVICES



Channel 06 (2437MHz) Reference Level: -8.49dBm



TRF no.: FCC 15C\_TX\_c  
FCC ID: 2ADAP-CS532Y  
Report No.: 150715018SZN-001


## INTERTEK TESTING SERVICES

Channel 11 (2462MHz) Reference Level: -8.64dBm



TRF no.: FCC 15C\_TX\_c  
FCC ID: 2ADAP-CS532Y  
Report No.: 150715018SZN-001



## INTERTEK TESTING SERVICES



# INTERTEK TESTING SERVICES


802.11n-HT40

Channel 03 (2422MHz) Reference Level: -12.31dBm





TRF no.: FCC 15C\_TX\_c  
FCC ID: 2ADAP-CS532Y  
Report No.: 150715018SZN-001

## INTERTEK TESTING SERVICES



# INTERTEK TESTING SERVICES



Channel 06 (2437MHz) Reference Level: -12.27dBm



TRF no.: FCC 15C\_TX\_c  
 FCC ID: 2ADAP-CS532Y  
 Report No.: 150715018SZN-001


# INTERTEK TESTING SERVICES

Channel 09 (2452MHz) Reference Level: -12.57dBm



TRF no.: FCC 15C\_TX\_c  
FCC ID: 2ADAP-CS532Y  
Report No.: 150715018SZN-001

## INTERTEK TESTING SERVICES



TRF no.: FCC 15C\_TX\_c  
FCC ID: 2ADAP-CS532Y  
Report No.: 150715018SZN-001



## INTERTEK TESTING SERVICES

---

Applicant: GREE Electric Appliances, Inc. of Zhuhai

Date of Test: September 14, 2015

Model: CS532Y

### 4.5 Out of Band Radiated Emissions (for emissions in 4.4 above that are less than 20dB below carrier), FCC Rule 15.247(d):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

☒ Not required, since all emissions are more than 20dB below fundamental

☐ See attached data sheet

## **INTERTEK TESTING SERVICES**

---

Applicant: GREE Electric Appliances, Inc. of Zhuhai

Date of Test: September 14, 2015

Model: CS532Y

### **4.6 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b), (c):**

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

## INTERTEK TESTING SERVICES

---

Applicant: GREE Electric Appliances, Inc. of Zhuhai

Date of Test: September 14, 2015

Model: CS532Y

### 4.7 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD$$

Where      FS = Field Strength in dB $\mu$ V/m  
             RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V  
             CF = Cable Attenuation Factor in dB  
             AF = Antenna Factor in dB  
             AG = Amplifier Gain in dB  
             PD = Pulse Desensitization in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD$$

#### Example

Assume a receiver reading of 62.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB. The net field strength for comparison to the appropriate emission limit is 42 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

$$\begin{aligned} RA &= 62.0 \text{ dB}\mu\text{V} \\ AF &= 7.4 \text{ dB} \\ CF &= 1.6 \text{ dB} \\ AG &= 29.0 \text{ dB} \\ PD &= 0 \text{ dB} \\ FS &= 62 + 7.4 + 1.6 - 29 + 0 = 42 \text{ dB}\mu\text{V/m} \end{aligned}$$

$$\text{Level in mV/m} = \text{Common Antilogarithm } [(42 \text{ dB}\mu\text{V/m})/20] = 125.9 \mu\text{V/m}$$

TRF no.: FCC 15C\_TX\_c

FCC ID: 2ADAP-CS532Y

Report No.: 150715018SZN-001

## INTERTEK TESTING SERVICES

---

Applicant: GREE Electric Appliances, Inc. of Zhuhai

Date of Test: September 14, 2015

Model: CS532Y

### 4.8 Radiated Spurious Emission

Worst Case Radiated Spurious Emission (802.11n-HT20) at 2483.900MHz is passed by 6.5dB margin (The simultaneous transmission was considered).

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

## INTERTEK TESTING SERVICES

Applicant: GREE Electric Appliances, Inc. of Zhuhai

Date of Test: September 14, 2015

Model: CS532Y

Worst Case Operating Mode: 802.11n-HT20 (TX-Channel 01)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	63.465	37.0	20.0	7.8	24.8	40.0	-15.2
Horizontal	307.420	33.3	20.0	15.6	28.9	46.0	-17.1
Horizontal	480.080	31.0	20.0	19.9	30.9	46.0	-15.1
Vertical	63.465	41.3	20.0	7.8	29.1	40.0	-10.9
Vertical	297.235	32.7	20.0	15.2	27.9	46.0	-18.1
Vertical	518.395	32.1	20.0	20.5	32.6	46.0	-13.4

NOTES: 1. Quasi-Peak detector is used except for others stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. All emissions are below the QP limit.

TRF no.: FCC 15C\_TX\_c

FCC ID: 2ADAP-CS532Y

Report No.: 150715018SZN-001

## INTERTEK TESTING SERVICES

Applicant: GREE Electric Appliances, Inc. of Zhuhai

Date of Test: September 14, 2015

Model: CS532Y

Worst Case Operating Mode: 802.11b (TX-Channel 01)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	52.0	36.1	34.2	50.1	74.0	-23.9
Horizontal	*2389.300	67.8	36.7	28.3	59.4	74.0	-14.6

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	45.3	36.1	34.2	43.4	54.0	-10.6
Horizontal	*2389.300	54.4	36.7	28.3	46.0	54.0	-8.0

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
  2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C\_TX\_c

FCC ID: 2ADAP-CS532Y

Report No.: 150715018SZN-001

## INTERTEK TESTING SERVICES

Applicant: GREE Electric Appliances, Inc. of Zhuhai

Date of Test: September 14, 2015

Model: CS532Y

Worst Case Operating Mode: 802.11b (TX-Channel 06)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	*4874.000	52.3	36.1	34.6	50.8	74.0	-23.2
Horizontal	*7311.000	45.2	35.6	37.1	46.7	74.0	-27.3

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	*4874.000	45.2	36.1	34.6	43.7	54.0	-10.3
Horizontal	*7311.000	31.6	35.6	37.1	33.1	54.0	-20.9

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C\_TX\_c

FCC ID: 2ADAP-CS532Y

Report No.: 150715018SZN-001

## INTERTEK TESTING SERVICES

Applicant: GREE Electric Appliances, Inc. of Zhuhai

Date of Test: September 14, 2015

Model: CS532Y

Worst Case Operating Mode: 802.11b (TX-Channel 11)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	51.0	36.1	34.6	49.5	74.0	-24.5
Horizontal	*7386.000	45.0	35.6	37.2	46.6	74.0	-27.4
Horizontal	*2483.500	67.8	36.7	28.0	59.1	74.0	-14.9

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	42.6	36.1	34.6	41.1	54.0	-12.9
Horizontal	*7386.000	31.5	35.6	37.2	33.1	54.0	-20.9
Horizontal	*2483.500	53.6	36.7	28.0	44.9	54.0	-9.1

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C\_TX\_c

FCC ID: 2ADAP-CS532Y

Report No.: 150715018SZN-001



## INTERTEK TESTING SERVICES

Applicant: GREE Electric Appliances, Inc. of Zhuhai

Date of Test: September 14, 2015

Model: CS532Y

Worst Case Operating Mode: 802.11g (TX-Channel 01)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	50.3	36.1	34.2	48.4	74.0	-25.6
Horizontal	*2389.400	70.3	36.7	28.2	61.8	74.0	-12.2

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	36.1	36.1	34.2	34.2	54.0	-19.8
Horizontal	*2389.400	54.5	36.7	28.2	46.0	54.0	-8.0

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C\_TX\_c

FCC ID: 2ADAP-CS532Y

Report No.: 150715018SZN-001

## INTERTEK TESTING SERVICES

Applicant: GREE Electric Appliances, Inc. of Zhuhai

Date of Test: September 14, 2015

Model: CS532Y

Worst Case Operating Mode: 802.11g (TX-Channel 06)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	50.1	36.1	34.6	48.6	74.0	-25.4
Horizontal	*7311.000	45.6	35.6	37.1	47.1	74.0	-26.9

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	36.0	36.1	34.6	34.5	54.0	-19.5
Horizontal	*7311.000	31.8	35.6	37.1	33.3	54.0	-20.7

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
  2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C\_TX\_c

FCC ID: 2ADAP-CS532Y

Report No.: 150715018SZN-001

## INTERTEK TESTING SERVICES

Applicant: GREE Electric Appliances, Inc. of Zhuhai

Date of Test: September 14, 2015

Model: CS532Y

Worst Case Operating Mode: 802.11g (TX-Channel 11)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	49.9	36.1	34.6	48.4	74.0	-25.6
Horizontal	*7386.000	45.7	35.6	37.2	47.3	74.0	-26.7
Horizontal	*2484.100	72.5	36.7	28.0	63.8	74.0	-10.2

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	35.8	36.1	34.6	34.3	54.0	-19.7
Horizontal	*7386.000	31.6	35.6	37.2	33.2	54.0	-20.8
Horizontal	*2484.100	56.0	36.7	28.0	47.3	54.0	-6.7

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

Applicant: GREE Electric Appliances, Inc. of Zhuhai

Date of Test: September 14, 2015

Model: CS532Y

Worst Case Operating Mode: 802.11n-HT20 (TX-Channel 01)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	49.1	36.1	34.2	47.2	74.0	-26.8
Horizontal	*2390.000	71.2	36.7	28.2	62.7	74.0	-11.3

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	35.5	36.1	34.2	33.6	54.0	-20.4
Horizontal	*2390.000	54.4	36.7	28.2	45.9	54.0	-8.1

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

Applicant: GREE Electric Appliances, Inc. of Zhuhai

Date of Test: September 14, 2015

Model: CS532Y

Worst Case Operating Mode: 802.11n-HT20 (TX-Channel 06)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	49.1	36.1	34.2	47.2	74.0	-26.8
Horizontal	*7311.000	45.4	35.6	37.1	46.9	74.0	-27.1

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	35.9	36.1	34.2	34.0	54.0	-20.0
Horizontal	*7311.000	32.1	35.6	37.1	33.6	54.0	-20.4

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C\_TX\_c

FCC ID: 2ADAP-CS532Y

Report No.: 150715018SZN-001

## INTERTEK TESTING SERVICES

Applicant: GREE Electric Appliances, Inc. of Zhuhai

Date of Test: September 14, 2015

Model: CS532Y

Worst Case Operating Mode: 802.11n-HT20 (TX-Channel 11)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	*4924.000	49.6	36.1	34.6	48.1	74.0	-25.9
Horizontal	*2483.900	72.5	36.7	28.0	63.8	74.0	-10.2

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	*4924.000	35.8	36.1	34.6	34.3	54.0	-19.7
Horizontal	*2483.900	56.2	36.7	28.0	47.5	54.0	-6.5

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

Applicant: GREE Electric Appliances, Inc. of Zhuhai

Date of Test: September 14, 2015

Model: CS532Y

Worst Case Operating Mode: 802.11n-HT40 (TX-Channel 03)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4844.000	48.5	36.1	34.2	46.6	74.0	-27.4
Horizontal	*7266.000	46.9	36.8	37.1	47.2	74.0	-26.8
Horizontal	*2385.200	68.2	36.7	28.2	59.7	74.0	-14.3

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4844.000	35.5	36.1	34.2	33.6	54.0	-20.4
Horizontal	*7266.000	33.1	36.8	37.1	33.4	54.0	-20.6
Horizontal	*2385.200	54.1	36.7	28.2	45.6	54.0	-8.4

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

Applicant: GREE Electric Appliances, Inc. of Zhuhai

Date of Test: September 14, 2015

Model: CS532Y

Worst Case Operating Mode: 802.11n-HT40 (TX-Channel 06)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	*4874.000	49.2	36.1	34.2	47.3	74.0	-26.7
Horizontal	*7311.000	45.0	35.6	37.1	46.5	74.0	-27.5

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	*4874.000	36.0	36.1	34.2	34.1	54.0	-19.9
Horizontal	*7311.000	32.0	35.6	37.1	33.5	54.0	-20.5

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C\_TX\_c

FCC ID: 2ADAP-CS532Y

Report No.: 150715018SZN-001



## INTERTEK TESTING SERVICES

Applicant: GREE Electric Appliances, Inc. of Zhuhai

Date of Test: September 14, 2015

Model: CS532Y

Worst Case Operating Mode: 802.11n-HT40 (TX-Channel 09)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4904.000	48.3	36.1	34.6	46.8	74.0	-27.2
Horizontal	*7356.000	45.7	35.6	37.0	47.1	74.0	-26.9
Horizontal	*2483.500	68.4	36.7	28.0	59.7	74.0	-14.3

Polarization	Frequency (MHz)	Reading (dBμV)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4904.000	35.3	36.1	34.6	33.8	54.0	-20.2
Horizontal	*7356.000	32.1	35.6	37.0	33.5	54.0	-20.5
Horizontal	*2483.500	53.9	36.7	28.0	45.2	54.0	-8.8

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C\_TX\_c

FCC ID: 2ADAP-CS532Y

Report No.: 150715018SZN-001

## INTERTEK TESTING SERVICES

---

### 4.9 Conducted Emission

Worst Case Conducted emission at 0.254MHz is Passed by 4.8dB margin

For electronic filing, the worst case conducted emission configuration photograph is saved with filename: conducted photos.pdf.

## INTERTEK TESTING SERVICES

Applicant: GREE Electric Appliances, Inc. of Zhuhai


Date of Test: September 14, 2015

Model: CS532Y

Worst Case Operating Mode: 802.11n-HT20 (TX-Channel 01)

Line: Live

### Conducted Emission Test - FCC



### Result Table QP

Frequency (MHz)	QuasiPeak (dB μV)	Line	Corr. (dB)	Margin (dB)	Limit (dB μV)
0.150	44.4	L1	9.8	21.6	66.0
0.276	43.6	L1	9.9	17.3	60.9
0.342	41.5	L1	9.9	17.7	59.2
3.394	36.1	L1	10.0	19.9	56.0
4.730	38.2	L1	10.0	17.8	56.0
7.630	33.8	L1	10.0	26.2	60.0

### Result Table AV

Frequency (MHz)	Average (dB μV)	Line	Corr. (dB)	Margin (dB)	Limit (dB μV)
0.150	33.4	L1	9.8	22.6	56.0
0.276	37.9	L1	9.9	13.0	50.9
0.342	32.9	L1	9.9	16.3	49.2
3.394	31.0	L1	10.0	15.0	46.0
4.730	33.1	L1	10.0	12.9	46.0
7.630	28.6	L1	10.0	21.4	50.0

TRF no.: FCC 15C\_TX\_c

FCC ID: 2ADAP-CS532Y

Report No.: 150715018SZN-001

## INTERTEK TESTING SERVICES

Applicant: GREE Electric Appliances, Inc. of Zhuhai


Date of Test: September 14, 2015

Model: CS532Y

Worst Case Operating Mode: 802.11n-HT20 (TX-Channel 01)

Line: Neutral

### Conducted Emission Test - FCC



### Result Table QP

Frequency (MHz)	QuasiPeak (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.254	54.5	N	10.2	7.1	61.6
0.366	42.8	N	10.2	15.8	58.6
0.730	45.1	N	10.3	10.9	56.0
1.274	43.4	N	10.3	12.6	56.0
2.994	37.4	N	10.3	18.6	56.0
4.334	33.8	N	10.3	22.2	56.0

### Result Table AV

Frequency (MHz)	Average (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.254	46.8	N	10.2	4.8	51.6
0.366	34.8	N	10.2	13.8	48.6
0.730	35.1	N	10.3	10.9	46.0
1.274	32.9	N	10.3	13.1	46.0
2.994	29.8	N	10.3	16.2	46.0
4.334	28.4	N	10.3	17.6	46.0

TRF no.: FCC 15C\_TX\_c

FCC ID: 2ADAP-CS532Y

Report No.: 150715018SZN-001

## **INTERTEK TESTING SERVICES**

---

Applicant: GREE Electric Appliances, Inc. of Zhuhai

Date of Test: September 14, 2015

Model: CS532Y

4.10 Radiated Emissions from Digital Section of Transceiver, FCC Ref: 15.109

☒ [ x ] Not required - No digital part

☐ [ ] Test results are attached

☐ [ ] Included in the separated report.

## INTERTEK TESTING SERVICES

---

Applicant: GREE Electric Appliances, Inc. of Zhuhai

Date of Test: September 14, 2015

Model: CS532Y

### 4.11 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEP function on the analyzer was set to ZERO SPAN. The Transmitter ON time was determined from the resultant time-amplitude display:

	See attached spectrum analyzer chart (s) for Transmitter timing
	See Transmitter timing diagram provided by manufacturer
x	Not applicable, duty cycle was not used.

**EXHIBIT 5**  
**EQUIPMENT PHOTOGRAPHS**

## INTERTEK TESTING SERVICES

---

### 5.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf & internal photos.pdf.



**EXHIBIT 6**

**PRODUCT LABELLING**

## INTERTEK TESTING SERVICES

---

### 6.0 **Product Labeling**

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf.

**EXHIBIT 7**

**TECHNICAL SPECIFICATIONS**

## INTERTEK TESTING SERVICES

---

### 7.0 Technical Specifications

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

**EXHIBIT 8**  
**INSTRUCTION MANUAL**

## INTERTEK TESTING SERVICES

---

### 8.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

## **INTERTEK TESTING SERVICES**

---

### **EXHIBIT 9**

### **CONFIDENTIALITY REQUEST**

## INTERTEK TESTING SERVICES

---

### 9.0 **Confidentiality Request**

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.



## **INTERTEK TESTING SERVICES**

---

### **EXHIBIT 10**

### **MISCELLANEOUS INFORMATION**

## INTERTEK TESTING SERVICES

---

### 10.0 **Discussion of Pulse Desensitization**

The determination of pulse desensitivity was made in accordance with Hewlett Packard Application Note 150-2, *Spectrum Analysis ... Pulsed RF*.

Pulse desensitivity is not applicable for this device since the transmitter transmits the RF signal continuously.

## **INTERTEK TESTING SERVICES**

---

### **EXHIBIT 11**

#### **TEST EQUIPMENT LIST**

## INTERTEK TESTING SERVICES

### 11.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ182-02	RF Power Meter	Anritsu	ML2496A	1302005	20-May-2015	20-May-2016
SZ182-02-01	Power Sensor	Anritsu	MA2411B	1207429	20-May-2015	20-May-2016
SZ061-04	BiConiLog Antenna	ETS	3142C	00066460	19-Oct-2014	19-Oct-2015
SZ185-01	EMI Receiver	R&S	ESCI	100547	07-Feb-2015	07-Feb-2016
SZ061-09	Horn Antenna	ETS	3115	00092346	01-Nov-2014	01-Nov-2015
SZ061-07	Pyramidal Horn Antenna	ETS	3160-09	00083067	01-Sep-2015	01-Sep-2016
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	29-Apr-2015	29-Apr-2016
SZ056-06	Spectrum Analyzer	R&S	FSV40	101101	08-Jul-2015	08-Jul-2016
SZ181-04	Preamplifier	Agilent	8449B	3008A02474	07-Feb-2015	07-Feb-2016
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	19-Apr-2014	19-Apr-2016
SZ062-02	RF Cable	RADIALL	RG 213U	--	30-Jun-2015	30-Dec-2015
SZ062-05	RF Cable	RADIALL	0.04-26.5GHz	--	07-Apr-2015	07-Oct-2015
SZ062-12	RF Cable	RADIALL	0.04-26.5GHz	--	07-Apr-2015	07-Oct-2015
SZ067-04	Notch Filter	Micro-Tronics	BRM5070 2-02	--	20-May-2015	20-May-2016
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	01-Nov-2014	01-Nov-2015
SZ187-01	Two-Line V-Network	R&S	ENV216	100072	01-Nov-2014	01-Nov-2015
SZ187-02	Two-Line V-Network	R&S	ENV216	100073	24-Jun-2015	24-Jun-2016
SZ188-03	Shielding Room	ETS	RFD-100	4100	23-Aug-2014	23-Aug-2016