



# SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.  
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

## FCC RADIO TEST REPORT

Applicant's company	ALLNET ASIA Inc.
Applicant Address	8F.,NO255, Dong Sec1, Guangming 6th RD Jhubei City Hsinchu County 302 Taiwan
FCC ID	2ADB7-ALL0368
Manufacturer's company	ALLNET ASIA Inc.
Manufacturer Address	8F.,NO255, Dong Sec1, Guangming 6th RD Jhubei City Hsinchu County 302 Taiwan

Product Name	802.11b/g/n 2T2R AP_POE
Brand Name	ALLNET
Model No.	ALL0368, ALL0368S, ALS0368, WCM300aa, W232
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	Aug. 21, 2014
Final Test Date	Sep. 30, 2014
Submission Type	Original Equipment

### Statement

**Test result included in this report is for the IEEE 802.11n and IEEE 802.11b/g of the product.**

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2013, 47 CFR FCC Part 15 Subpart C, KDB 558074 D01 v03r02 and KDB 662911 D01 v02r01.**

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



## Table of Contents

<b>1. CERTIFICATE OF COMPLIANCE .....</b>	<b>1</b>
<b>2. SUMMARY OF THE TEST RESULT .....</b>	<b>2</b>
<b>3. GENERAL INFORMATION .....</b>	<b>3</b>
3.1. Product Details.....	3
3.2. Accessories.....	4
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies .....	6
3.5. Table for Test Modes .....	7
3.6. Table for Testing Locations.....	8
3.7. Table for Multiple Listing.....	8
3.8. Table for Supporting Units .....	9
3.9. Table for Parameters of Test Software Setting .....	10
3.10. EUT Operation during Test .....	10
3.11. Duty Cycle .....	10
3.12. Test Configurations .....	11
<b>4. TEST RESULT .....</b>	<b>14</b>
4.1. AC Power Line Conducted Emissions Measurement.....	14
4.2. Maximum Conducted Output Power Measurement.....	18
4.3. Power Spectral Density Measurement .....	21
4.4. 6dB Spectrum Bandwidth Measurement .....	29
4.5. Radiated Emissions Measurement .....	34
4.6. Emissions Measurement .....	53
4.7. Antenna Requirements .....	71
<b>5. LIST OF MEASURING EQUIPMENTS .....</b>	<b>72</b>
<b>6. MEASUREMENT UNCERTAINTY.....</b>	<b>74</b>
<b>APPENDIX A. TEST PHOTOS .....</b>	<b>A1 ~ A5</b>
<b>APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE .....</b>	<b>B1 ~ B3</b>


## History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR482161	Rev. 01	Initial issue of report	Oct. 29, 2014
FR482161	Rev. 02	Change equipment name	Nov. 25, 2014

## 1. CERTIFICATE OF COMPLIANCE

Product Name : 802.11b/g/n 2T2R AP\_POE  
Brand Name : ALLNET  
Model No. : ALL0368, ALL0368S, ALS0368, WCM300aa, W232  
Applicant : ALLNET ASIA Inc.  
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Aug. 21, 2014 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Sam Chen

SPORTON INTERNATIONAL INC.

## 2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	10.33 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	3.74 dB
4.3	15.247(e)	Power Spectral Density	Complies	7.27 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	0.21 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.10 dB
4.7	15.203	Antenna Requirements	Complies	-

Note1: The Adapter and PoE are for measurement only, would not be marketed.

### 3. GENERAL INFORMATION

#### 3.1. Product Details

##### IEEE 802.11n

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From power adapter or PoE
Modulation	see the below table for IEEE 802.11n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11 for 20MHz bandwidth ; 7 for 40MHz bandwidth
Channel Band Width (99%)	MCS0 (HT20): 17.92 MHz ; MCS0 (HT40): 36.64 MHz
Maximum Conducted Output Power	MCS0 (HT20): 25.96 dBm ; MCS0 (HT40): 20.91 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

##### IEEE 802.11b/g

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From power adapter or PoE
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11
Channel Band Width (99%)	11b: 14.00 MHz ; 11g: 16.64 MHz
Maximum Conducted Output Power	11b: 19.20 dBm ; 11g: 26.26 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Items	Description	
Beamforming Function	<input type="checkbox"/> With beamforming	<input checked="" type="checkbox"/> Without beamforming

#### Antenna and Band width

Antenna	Two (TX)	
Band width Mode	20 MHz	40 MHz
IEEE 802.11b	V	X
IEEE 802.11g	V	X
IEEE 802.11n	V	V

#### IEEE 11n Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	2	MCS 0-15
802.11n (HT40)	2	MCS 0-15
<p>Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput). Then EUT support HT20 and HT40.</p> <p>Note 2: Modulation modes consist of below configuration: HT20/HT40: IEEE 802.11n</p>		

### 3.2. Accessories

1. RJ-45\*1, Non-Shielded, 1.2m
2. Cradle\*1

### 3.3. Table for Filed Antenna


Ant.	Brand Holder	Model Name	Antenna Type	Connector	Gain (dBi)		
					Antenna Gain (dBi)	Cable Loss (dBi)	True Gain (dBi)
1	Master Wave Technology Co., Ltd.	98P2PMIPF000	PCB Antenna	I-PEX	5.38	0.51	4.87
2	Master Wave Technology Co., Ltd.	98P2PMIPF000	PCB Antenna	I-PEX	5.38	0.51	4.87

Note: The EUT has two antennas.

**For IEEE 802.11b/g/n mode (2TX/2RX):**

Chain 1 and Chain 2 will transmit/receive the same signal simultaneously.

Chain 1 and Chain 2 can be used as transmitting/receiving antennas.





### 3.4. Table for Carrier Frequencies

There are two bandwidth systems.

For 20MHz bandwidth systems, use Channel 1~Channel 11.

For 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

### 3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Chain
AC Power Line Conducted Emissions	Normal Link	-	-	-
Maximum Conducted Output Power	802.11n HT20	MCS0	1/6/11	1+2
	802.11n HT40	MCS0	3/6/9	1+2
	11b/BPSK	1 Mbps	1/6/11	1+2
	11g/BPSK	6 Mbps	1/6/11	1+2
Power Spectral Density	802.11n HT20	MCS0	1/6/11	1+2
	802.11n HT40	MCS0	3/6/9	1+2
	11b/BPSK	1 Mbps	1/6/11	1+2
	11g/BPSK	6 Mbps	1/6/11	1+2
6dB Spectrum Bandwidth	802.11n HT20	MCS0	1/6/11	1+2
	802.11n HT40	MCS0	3/6/9	1+2
	11b/BPSK	1 Mbps	1/6/11	1+2
	11g/BPSK	6 Mbps	1/6/11	1+2
Radiated Emissions 9kHz~1GHz	Normal Link	-	-	-
Radiated Emissions 1GHz~10 <sup>th</sup> Harmonic	802.11n HT20	MCS0	1/6/11	1+2
	802.11n HT40	MCS0	3/6/9	1+2
	11b/BPSK	1 Mbps	1/6/11	1+2
	11g/BPSK	6 Mbps	1/6/11	1+2
Band Edge Emissions	802.11n HT20	MCS0	1/6/11	1+2
	802.11n HT40	MCS0	3/6/9	1+2
	11b/BPSK	1 Mbps	1/6/11	1+2
	11g/BPSK	6 Mbps	1/6/11	1+2

The following test modes were performed for all tests:

#### For Conducted Emission test:

Mode 1. EUT + AC Adapter

#### For Radiated Emission test below 1GHz:

Mode 1. Place EUT in X axis + AC Adapter

Mode 2. Place EUT in Y axis + AC Adapter

Mode 3. Place EUT in Y axis + AC Adapter

Mode 1 has been evaluated to be the worst case among Mode 1~3, thus measurement for Mode 4 will follow this same test mode.

Mode 4. Place EUT in X axis + PoE

Mode 4 is the worst case, so it was selected to record in this test report.

#### For Radiated Emission test above 1GHz:

The EUT was performed at X axis, Y axis and Z axis position for Radiated emission above 1GHz test, and the worst case was found at Z axis. So the measurement will follow this same test configuration.

Mode 1. CTX - Place EUT in Z axis

### 3.6. Table for Testing Locations

Test Site Location				
Address:	No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.			
TEL:	886-3-656-9065			
FAX:	886-3-656-9085			
Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

### 3.7. Table for Multiple Listing

The model names in the following table are all refer to the identical product.

Model Name	Description
ALL0368	All the models are identical, the difference model for difference brand served as marketing strategy.
ALL0368S	
ALS0368	
WCM300aa	
W232	

From the above models, model: ALL0368 was selected as representative model for the test and its data was recorded in this report.

### 3.8. Table for Supporting Units

For Test Site No: CO01-CB

Support Unit	Brand	Model	FCC ID
NB*3	DELL	E6430	DoC
Adapter	APD	WA-24E12	N/A

For Test Site No: TH01-CB

Support Unit	Brand	Model	FCC ID
NB	DELL	E6430	DoC
PoE	Power Dsine	PD-9001GR	N/A

For Test Site No: 03CH01-CB <For below 1GHz>

Support Unit	Brand	Model	FCC ID
NB	DELL	M1330	E2K4965AGNM
NB	DELL	M1340	E2K4965AGNM
NB	DELL	E6430	DoC
PoE	Power Dsine	PD-9001GR	N/A
PoE Load	ALLNET	ALL0T01PD	N/A

For Test Site No: 03CH01-CB <For above 1GHz>

Support Unit	Brand	Model	FCC ID
NB	DELL	M1330	E2K4965AGNM
PoE	Power Dsine	PD-9001GR	N/A

### 3.9. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

#### Power Parameters of IEEE 802.11n

Test Software Version	ART2-GUI Version : 2.3		
Frequency	2412 MHz	2437 MHz	2462 MHz
MCS0 HT20	16	23	16
Frequency	2422 MHz	2437 MHz	2452 MHz
MCS0 HT40	12	17	12

#### Power Parameters of IEEE 802.11b/g

Test Software Version	ART2-GUI Version : 2.3		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	15.5	16	16.5
IEEE 802.11g	17	23	17

### 3.10. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

### 3.11. Duty Cycle

Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
802.11n MCS0 HT20	1.250	1.300	96.15	0.17	0.80
802.11n MCS0 HT40	0.624	0.660	94.55	0.24	1.60
802.11b	8.180	8.220	99.51	0.02	0.01
802.11g	1.350	1.390	97.12	0.13	0.74

## 3.12. Test Configurations


### 3.12.1. AC Power Line Conduction Emissions Test Configuration



Item	Connection	Shielded	Length
1	Power cable	No	1.8m
2	RJ-45 cable	No	10m
3	RJ-45 cable	No	50m
4	RJ-45 cable	No	1m
5	RJ-45 cable	No	1.2m


### 3.12.2. Radiation Emissions Test Configuration

Test Configuration: 30MHz~1GHz



Item	Connection	Shielded	Length
1	Power cable	No	1.8m
2	RJ-45 cable	No	10m
3	RJ-45 cable	No	10m
4	RJ-45 cable	No	1m
5	RJ-45 cable	No	1m
6	RJ-45 cable	No	1.2m

Test Configuration: above 1GHz



Item	Connection	Shielded	Length
1	Power cable	No	1.8m
2	RJ-45 cable	No	10m
3	RJ-45 cable	No	1.5m



## 4. TEST RESULT

### 4.1. AC Power Line Conducted Emissions Measurement

#### 4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

#### 4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

#### 4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

#### 4.1.4. Test Setup Layout



##### LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50  $\Omega$ . LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

#### 4.1.5. Test Deviation


There is no deviation with the original standard.

#### 4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


#### 4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	24°C	Humidity	53%
Test Engineer	Da Deng	Phase	Line
Configuration	Normal Link	Test Mode	Mode 1



	Freq	Level	Over Limit	Limit Line	LISN Factor	Read Level	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dB	dBuV	dB		
1	0.15403	55.45	-10.33	65.78	9.96	45.33	0.16	LINE	QP
2	0.15403	38.28	-17.50	55.78	9.96	28.16	0.16	LINE	AVERAGE
3	0.16414	54.13	-11.12	65.25	9.96	44.01	0.16	LINE	QP
4	0.16414	40.36	-14.89	55.25	9.96	30.24	0.16	LINE	AVERAGE
5	0.20614	45.56	-17.80	63.36	9.96	35.43	0.17	LINE	QP
6	0.20614	29.08	-24.28	53.36	9.96	18.95	0.17	LINE	AVERAGE
7	0.26303	40.38	-20.96	61.34	9.96	30.25	0.17	LINE	QP
8	0.26303	29.48	-21.86	51.34	9.96	19.35	0.17	LINE	AVERAGE
9	2.190	34.84	-21.16	56.00	10.04	24.55	0.26	LINE	QP
10	2.190	26.40	-19.60	46.00	10.04	16.11	0.26	LINE	AVERAGE
11	10.288	34.90	-25.10	60.00	10.23	24.29	0.39	LINE	QP
12	10.288	30.56	-19.44	50.00	10.23	19.95	0.39	LINE	AVERAGE

Temperature	24°C	Humidity	53%
Test Engineer	Da Deng	Phase	Neutral
Configuration	Normal Link	Test Mode	Mode 1



	Freq	Level	Over Limit	Limit Line	LISN Factor	Read Level	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dB	dBuV	dB		
1	0.15650	54.02	-11.63	65.65	9.95	43.91	0.16	NEUTRAL	QP
2	0.15650	41.58	-14.07	55.65	9.95	31.47	0.16	NEUTRAL	AVERAGE
3 @	0.16677	54.24	-10.88	65.12	9.95	44.13	0.16	NEUTRAL	QP
4	0.16677	37.85	-17.27	55.12	9.95	27.74	0.16	NEUTRAL	AVERAGE
5	0.20614	46.16	-17.20	63.36	9.95	36.04	0.17	NEUTRAL	QP
6	0.20614	31.40	-21.96	53.36	9.95	21.28	0.17	NEUTRAL	AVERAGE
7	0.30509	41.93	-18.17	60.10	9.94	31.81	0.17	NEUTRAL	QP
8	0.30509	32.06	-18.05	50.10	9.94	21.94	0.17	NEUTRAL	AVERAGE
9	1.249	34.70	-21.30	56.00	10.00	24.49	0.22	NEUTRAL	QP
10	1.249	27.52	-18.48	46.00	10.00	17.31	0.22	NEUTRAL	AVERAGE
11	10.397	35.52	-24.48	60.00	10.21	24.92	0.39	NEUTRAL	QP
12	10.397	28.11	-21.89	50.00	10.21	17.51	0.39	NEUTRAL	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

## 4.2. Maximum Conducted Output Power Measurement

### 4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

### 4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Average

### 4.2.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03r02 section 9.2.3.2 Measurement using a power meter (PM).
2. Multiple antenna systems was performed in accordance with KDB 662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
3. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

### 4.2.4. Test Setup Layout



### 4.2.5. Test Deviation

There is no deviation with the original standard.

### 4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.2.7. Test Result of Maximum Conducted Output Power

Temperature	23°C	Humidity	52%
Test Engineer	Robert Chang	Configurations	IEEE 802.11n
Test Date	Sep. 12, 2014		

##### Configuration IEEE 802.11n MCS0 HT20

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Chain 1	Chain 2	Total		
1	2412 MHz	17.07	16.53	19.82	30.00	Complies
6	2437 MHz	23.21	22.67	25.96	30.00	Complies
11	2462 MHz	16.37	15.87	19.14	30.00	Complies

##### Configuration IEEE 802.11n MCS0 HT40

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Chain 1	Chain 2	Total		
3	2422 MHz	13.21	11.84	15.59	30.00	Complies
6	2437 MHz	18.16	17.63	20.91	30.00	Complies
9	2452 MHz	12.37	11.90	15.15	30.00	Complies

Temperature	23°C	Humidity	52%
Test Engineer	Robert Chang	Configurations	IEEE 802.11b/g
Test Date	Sep. 12, 2014		

Configuration IEEE 802.11b

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Chain 1	Chain 2	Total		
1	2412 MHz	16.23	15.78	19.02	30.00	Complies
6	2437 MHz	16.61	15.72	19.20	30.00	Complies
11	2462 MHz	16.67	15.52	19.14	30.00	Complies

Configuration IEEE 802.11g

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Chain 1	Chain 2	Total		
1	2412 MHz	19.90	18.63	22.32	30.00	Complies
6	2437 MHz	23.14	23.35	26.26	30.00	Complies
11	2462 MHz	17.25	16.83	20.06	30.00	Complies

### 4.3. Power Spectral Density Measurement

#### 4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### 4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100\text{kHz}$
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

#### 4.3.3. Test Procedures

1. Test was performed in accordance with KDB 558074 D01 v03r02 for Performing Compliance Measurements on Digital Transmission Systems (DTS) - section 10.2 Method PKPSD (peak PSD) and KDB 662911 D01 v02r01 section In-Band Power Spectral Density (PSD) Measurements option (b) Measure and sum spectral maximal across the outputs.
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span/RBW}$  (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The resulting PSD level must be  $\leq 8 \text{ dBm}$ .

#### 4.3.4. Test Setup Layout





#### **4.3.5. Test Deviation**

There is no deviation with the original standard.

#### **4.3.6. EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

#### 4.3.7. Test Result of Power Spectral Density

Temperature	23°C	Humidity	52%
Test Engineer	Robert Chang	Configurations	IEEE 802.11n

##### Configuration IEEE 802.11n MCS0 HT20

Channel	Frequency	Power Density (dBm/3kHz)			Power Density Limit (dBm/3kHz)	Result
		Chain 1	Chain 2	Total		
1	2412 MHz	-6.85	-8.52	-4.59	8.00	Complies
6	2437 MHz	-2.07	-2.89	0.55	8.00	Complies
11	2462 MHz	-8.76	-9.54	-6.12	8.00	Complies

Note:  $DirectionalGain = 10 \cdot \log \left[ \frac{\sum_{j=1}^{N_{CH}} \left\{ \sum_{i=1}^{N_{ANT}} g_{i,j} \right\}^2}{N_{ANT}} \right] = 4.87 \text{ dBi} < 6 \text{ dBi}$ , So Power Density Limit = 8dBm/3kHz

##### Configuration IEEE 802.11n MCS0 HT40

Channel	Frequency	Power Density (dBm/3kHz)			Power Density Limit (dBm/3kHz)	Result
		Chain 1	Chain 2	Total		
3	2422 MHz	-15.97	-15.05	-12.48	8.00	Complies
6	2437 MHz	-10.45	-11.39	-7.88	8.00	Complies
9	2452 MHz	-16.08	-16.20	-13.13	8.00	Complies

Note:  $DirectionalGain = 10 \cdot \log \left[ \frac{\sum_{j=1}^{N_{CH}} \left\{ \sum_{i=1}^{N_{ANT}} g_{i,j} \right\}^2}{N_{ANT}} \right] = 4.87 \text{ dBi} < 6 \text{ dBi}$ , So Power Density Limit = 8dBm/3kHz

Temperature	23°C	Humidity	52%
Test Engineer	Robert Chang	Configurations	IEEE 802.11b/g

#### Configuration IEEE 802.11b

Channel	Frequency	Power Density (dBm/3kHz)			Power Density Limit (dBm/3kHz)	Result
		Chain 1	Chain 2	Total		
1	2412 MHz	-8.14	-8.80	-5.45	8.00	Complies
6	2437 MHz	-7.00	-7.86	-4.40	8.00	Complies
11	2462 MHz	-7.65	-7.43	-4.53	8.00	Complies

Note:  $DirectionalGain = 10 \cdot \log \left[ \frac{\sum_{j=1}^{N_{ANT}} \left\{ \sum_{k=1}^{N_{CH}} G_{j,k} \right\}^2}{N_{ANT}} \right] = 4.87\text{dBi} < 6\text{dBi}$ , So Power Density Limit = 8dBm/3kHz

#### Configuration IEEE 802.11g


Channel	Frequency	Power Density (dBm/3kHz)			Power Density Limit (dBm/3kHz)	Result
		Chain 1	Chain 2	Total		
1	2412 MHz	-7.00	-7.84	-4.39	8.00	Complies
6	2437 MHz	-2.04	-2.54	0.73	8.00	Complies
11	2462 MHz	-8.26	-8.81	-5.52	8.00	Complies

Note:  $DirectionalGain = 10 \cdot \log \left[ \frac{\sum_{j=1}^{N_{ANT}} \left\{ \sum_{k=1}^{N_{CH}} G_{j,k} \right\}^2}{N_{ANT}} \right] = 4.87\text{dBi} < 6\text{dBi}$ , So Power Density Limit = 8dBm/3kHz

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

### Power Density Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Chain 1




Date: 12.SEP.2014 19:28:49

### Power Density Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Chain 2




Date: 12.SEP.2014 19:43:43

### Power Density Plot on Configuration IEEE 802.11n MCS0 HT40 / 2437 MHz / Chain 1




Date: 12.SEP.2014 19:33:14

### Power Density Plot on Configuration IEEE 802.11n MCS0 HT40 / 2437 MHz / Chain 2




Date: 12.SEP.2014 19:39:18

### Power Density Plot on Configuration IEEE 802.11b / 2437 MHz / Chain 1




Date: 12.SEP.2014 19:16:43

### Power Density Plot on Configuration IEEE 802.11b / 2437 MHz / Chain 2




Date: 12.SEP.2014 19:18:08

### Power Density Plot on Configuration IEEE 802.11g / 2437 MHz / Chain 1



Date: 12.SEP.2014 19:25:31

### Power Density Plot on Configuration IEEE 802.11g / 2437 MHz / Chain 2



Date: 12.SEP.2014 19:42:08

#### 4.4. 6dB Spectrum Bandwidth Measurement

##### 4.4.1. Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

##### 4.4.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RBW	100kHz
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

##### 4.4.3. Test Procedures

For Radiated 6dB Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB 558074 D01 v03r02 for Performing Compliance Measurements on Digital Transmission Systems (DTS) - section 8.0 DTS bandwidth=> 8.1 Option 1.
3. Multiple antenna system was performed in accordance with KDB 662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

##### 4.4.4. Test Setup Layout

For Radiated 6dB Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.5.4.

##### 4.4.5. Test Deviation

There is no deviation with the original standard.

##### 4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.



#### 4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	23°C	Humidity	52%
Test Engineer	Robert Chang	Configurations	IEEE 802.11n

##### Configuration IEEE 802.11n MCS0 HT20 / Chain 1 + Chain 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	17.60	17.92	500	Complies
6	2437 MHz	17.60	17.92	500	Complies
11	2462 MHz	17.60	17.92	500	Complies

##### Configuration IEEE 802.11n MCS0 HT40 / Chain 1 + Chain 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	36.32	36.64	500	Complies
6	2437 MHz	36.48	36.64	500	Complies
9	2452 MHz	36.48	36.48	500	Complies

Temperature	23°C	Humidity	52%
Test Engineer	Robert Chang	Configurations	IEEE 802.11b/g

#### Configuration IEEE 802.11b / Chain 1 + Chain 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	10.08	14.00	500	Complies
6	2437 MHz	10.08	13.92	500	Complies
11	2462 MHz	9.92	13.92	500	Complies


#### Configuration IEEE 802.11g / Chain 1 + Chain 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.16	16.64	500	Complies
6	2437 MHz	16.32	16.64	500	Complies
11	2462 MHz	16.08	16.64	500	Complies

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

### 6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT20 / 2412 MHz / Chain 1 + Chain 2




Date: 12.SEP.2014 20:14:03

### 6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT40 / 2422 MHz / Chain 1 + Chain 2




Date: 12.SEP.2014 20:15:04

### 6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2462 MHz / Chain 1 + Chain 2



Date: 12.SEP.2014 20:04:29

### 6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2462 MHz / Chain 1 + Chain 2



Date: 12.SEP.2014 20:11:44

## 4.5. Radiated Emissions Measurement

### 4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

#### 4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 1/T VBW for average reading in spectrum analyzer.
7. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
8. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
9. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

#### 4.5.4. Test Setup Layout


For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



For Radiated Emissions: Above 1GHz



#### **4.5.5. Test Deviation**

There is no deviation with the original standard.

#### **4.5.6. EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.



#### 4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	25°C	Humidity	58%
Test Engineer	Nick Peng	Configurations	Normal Link
Test Date	Sep. 30, 2014	Test Mode	Mode 4

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

**Note:**

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

#### 4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	25°C	Humidity	58%
Test Engineer	Nick Peng	Configurations	Normal Link
Test Mode	Mode 4		

##### Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	184.23	36.07	43.50	-7.43	57.59	1.63	8.36	31.51	125	116	HORIZONTAL	Peak
2	375.32	39.09	46.00	-6.91	53.15	2.44	14.93	31.43	100	86	HORIZONTAL	Peak
3	500.45	38.20	46.00	-7.80	49.87	2.82	16.92	31.41	100	11	HORIZONTAL	Peak
4	624.61	39.11	46.00	-6.89	48.72	3.18	18.61	31.40	150	128	HORIZONTAL	Peak
5	749.74	38.20	46.00	-7.80	46.35	3.53	19.69	31.37	150	207	HORIZONTAL	Peak
6	875.84	41.98	46.00	-4.02	48.97	3.90	20.25	31.14	100	128	HORIZONTAL	Peak

### Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	40.67	38.70	40.00	-1.30	57.97	0.75	11.85	31.87	100	229 VERTICAL	QP
2	65.89	34.77	40.00	-5.23	60.73	0.96	4.90	31.82	300	8 VERTICAL	Peak
3	375.32	40.55	46.00	-5.45	54.61	2.44	14.93	31.43	150	92 VERTICAL	Peak
4	625.58	39.79	46.00	-6.21	49.39	3.19	18.62	31.41	100	180 VERTICAL	Peak
5	750.71	39.86	46.00	-6.14	48.01	3.53	19.69	31.37	100	244 VERTICAL	Peak
6	875.84	41.29	46.00	-4.71	48.28	3.90	20.25	31.14	100	359 VERTICAL	Peak

### Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

#### 4.5.9. Results for Radiated Emissions (1GHz~10<sup>th</sup> Harmonic)

Temperature	25°C	Humidity	58%
Test Engineer	Nick Peng	Configurations	IEEE 802.11n MCS0 HT20 CH 1 / Chain 1 + Chain 2
Test Date	Sep. 10, 2014		

##### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4821.95	44.65	54.00	-9.35	41.51	5.68	32.76	35.30	144	281	HORIZONTAL Average
2	4825.30	50.72	74.00	-23.28	47.56	5.69	32.77	35.30	144	281	HORIZONTAL Peak

##### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4820.45	52.14	74.00	-21.86	49.00	5.68	32.76	35.30	143	263	VERTICAL Peak
2	4823.10	45.56	54.00	-8.44	42.42	5.68	32.76	35.30	143	263	VERTICAL Average

Temperature	25°C	Humidity	58%
Test Engineer	Nick Peng	Configurations	IEEE 802.11n MCS0 HT20 CH 6 / Chain 1 + Chain 2
Test Date	Sep. 10, 2014		

### Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4868.20	56.79	74.00	-17.21	53.56	5.74	32.80	35.31	126	277	HORIZONTAL Peak
2	4869.95	49.75	54.00	-4.25	46.52	5.74	32.80	35.31	126	277	HORIZONTAL Average

### Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4872.25	61.37	74.00	-12.63	58.13	5.75	32.80	35.31	212	265	VERTICAL Peak
2	4872.70	53.35	54.00	-0.65	50.11	5.75	32.80	35.31	212	265	VERTICAL Average

Temperature	25°C	Humidity	58%
Test Engineer	Nick Peng	Configurations	IEEE 802.11n MCS0 HT20 CH 11 / Chain 1 + Chain 2
Test Date	Sep. 10, 2014		

#### Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4923.10	40.35	54.00	-13.65	37.04	5.81	32.83	35.33	162	283	HORIZONTAL	Average
2	4924.50	47.20	74.00	-26.80	43.88	5.81	32.84	35.33	162	283	HORIZONTAL	Peak

#### Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4923.25	50.89	74.00	-23.11	47.58	5.81	32.83	35.33	133	257	VERTICAL	Peak
2	4923.30	44.91	54.00	-9.09	41.60	5.81	32.83	35.33	133	257	VERTICAL	Average

Temperature	25°C	Humidity	58%
Test Engineer	Nick Peng	Configurations	IEEE 802.11n MCS0 HT40 CH 3 / Chain 1 + Chain 2
Test Date	Sep. 10, 2014		

**Horizontal**

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4843.79	45.28	74.00	-28.72	42.09	5.71	32.78	35.30	174	206	HORIZONTAL	Peak
2	4843.94	35.57	54.00	-18.43	32.38	5.71	32.78	35.30	174	206	HORIZONTAL	Average

**Vertical**

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4843.66	36.86	54.00	-17.14	33.67	5.71	32.78	35.30	152	273	VERTICAL	Average
2	4843.91	47.93	74.00	-26.07	44.74	5.71	32.78	35.30	152	273	VERTICAL	Peak

Temperature	25°C	Humidity	58%
Test Engineer	Nick Peng	Configurations	IEEE 802.11n MCS0 HT40 CH 6 / Chain 1 + Chain 2
Test Date	Sep. 10, 2014		

### Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4870.35	47.72	74.00	-26.28	44.49	5.74	32.80	35.31	149	285	HORIZONTAL Peak
2	4872.50	41.48	54.00	-12.52	38.24	5.75	32.80	35.31	149	285	HORIZONTAL Average

### Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4872.95	44.57	54.00	-9.43	41.33	5.75	32.80	35.31	227	276	VERTICAL Average
2	4873.65	51.73	74.00	-22.27	48.49	5.75	32.80	35.31	227	276	VERTICAL Peak



Temperature	25°C	Humidity	58%
Test Engineer	Nick Peng	Configurations	IEEE 802.11n MCS0 HT40 CH 9 / Chain 1 + Chain 2
Test Date	Sep. 10, 2014		

#### Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4903.84	36.10	54.00	-17.90	32.83	5.78	32.82	35.33	200	205	HORIZONTAL	Average
2	4904.39	45.79	74.00	-28.21	42.52	5.78	32.82	35.33	200	205	HORIZONTAL	Peak

#### Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4903.99	36.24	54.00	-17.76	32.97	5.78	32.82	35.33	179	241	VERTICAL	Average
2	4904.09	46.02	74.00	-27.98	42.75	5.78	32.82	35.33	179	241	VERTICAL	Peak

#### Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	25°C	Humidity	58%
Test Engineer	Nick Peng	Configurations	IEEE 802.11b CH 1 / Chain 1 + Chain 2
Test Date	Sep. 09, 2014		

### Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4824.00	53.31	74.00	-20.69	50.16	5.69	32.76	35.30	214	282	HORIZONTAL Peak
2	4824.09	51.00	54.00	-3.00	47.85	5.69	32.76	35.30	214	282	HORIZONTAL Average

### Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4823.94	53.69	54.00	-0.31	50.54	5.69	32.76	35.30	216	271	VERTICAL Average
2	4824.06	56.51	74.00	-17.49	53.36	5.69	32.76	35.30	216	271	VERTICAL Peak

Temperature	25°C	Humidity	58%
Test Engineer	Nick Peng	Configurations	IEEE 802.11b CH 6 / Chain 1 + Chain 2
Test Date	Sep. 09, 2014		

### Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4873.76	53.36	74.00	-20.64	50.12	5.75	32.80	35.31	217	282	HORIZONTAL Peak
2	4874.10	50.45	54.00	-3.55	47.21	5.75	32.80	35.31	217	282	HORIZONTAL Average

### Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4874.02	53.79	54.00	-0.21	50.55	5.75	32.80	35.31	223	265	VERTICAL Average
2	4874.07	55.61	74.00	-18.39	52.37	5.75	32.80	35.31	223	265	VERTICAL Peak

Temperature	25°C	Humidity	58%
Test Engineer	Nick Peng	Configurations	IEEE 802.11b CH 11 / Chain 1 + Chain 2
Test Date	Sep. 09, 2014		

### Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4924.01	46.38	54.00	-7.62	43.06	5.81	32.84	35.33	210	277	HORIZONTAL Average
2	4924.18	50.44	74.00	-23.56	47.12	5.81	32.84	35.33	210	277	HORIZONTAL Peak

### Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4924.02	53.61	54.00	-0.39	50.29	5.81	32.84	35.33	214	257	VERTICAL Average
2	4924.02	56.23	74.00	-17.77	52.91	5.81	32.84	35.33	214	257	VERTICAL Peak

Temperature	25°C	Humidity	58%
Test Engineer	Nick Peng	Configurations	IEEE 802.11g CH 1 / Chain 1 + Chain 2
Test Date	Sep. 10, 2014		

### Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4823.45	45.51	54.00	-8.49	42.36	5.69	32.76	35.30	193	280	HORIZONTAL Average
2	4824.60	52.26	74.00	-21.74	49.11	5.69	32.76	35.30	193	280	HORIZONTAL Peak

### Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4819.10	53.92	74.00	-20.08	50.77	5.68	32.76	35.29	129	262	VERTICAL Peak
2	4823.55	46.87	54.00	-7.13	43.72	5.69	32.76	35.30	129	262	VERTICAL Average

Temperature	25°C	Humidity	58%
Test Engineer	Nick Peng	Configurations	IEEE 802.11g CH 6 / Chain 1 + Chain 2
Test Date	Sep. 10, 2014		

### Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4873.30	51.80	54.00	-2.20	48.56	5.75	32.80	35.31	218	281	HORIZONTAL Average
2	4873.45	57.76	74.00	-16.24	54.52	5.75	32.80	35.31	218	281	HORIZONTAL Peak

### Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4873.00	60.66	74.00	-13.34	57.42	5.75	32.80	35.31	203	272	VERTICAL Peak
2	4873.10	53.18	54.00	-0.82	49.94	5.75	32.80	35.31	203	272	VERTICAL Average

Temperature	25°C	Humidity	58%
Test Engineer	Nick Peng	Configurations	IEEE 802.11g CH 11 / Chain 1 + Chain 2
Test Date	Sep. 10, 2014		

#### Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4923.50	40.78	54.00	-13.22	37.47	5.81	32.83	35.33	143	285	HORIZONTAL Average
2	4928.00	47.17	74.00	-26.83	43.85	5.81	32.84	35.33	143	285	HORIZONTAL Peak

#### Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4923.10	46.03	54.00	-7.97	42.72	5.81	32.83	35.33	135	261	VERTICAL Average
2	4928.25	52.35	74.00	-21.65	49.03	5.81	32.84	35.33	135	261	VERTICAL Peak

#### Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

## 4.6. Emissions Measurement

### 4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average
RBW / VBW (30dBc in any 100 kHz bandwidth emission)	100 kHz / 300 kHz for Peak

### 4.6.3. Test Procedures

#### For Radiated band edges Measurement:

- The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around band edges.

#### For Radiated Out of Band Emission Measurement:

- Test was performed in accordance with KDB 558074 D01 v03r02 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 10.1 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure.
- The radiated emission test is performed on each TX port of operating mode without summing or adding 10log (N) since the limit is relative emission limit.  
Only worst data of each operating mode is presented.



#### **4.6.4. Test Setup Layout**

For Radiated band edges Measurement:

This test setup layout is the same as that shown in section 4.5.4.

For Radiated Out of Band Emission Measurement:

This test setup layout is the same as that shown in section 4.5.4.

#### **4.6.5. Test Deviation**

There is no deviation with the original standard.

#### **4.6.6. EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

#### 4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	25°C	Humidity	58%
Test Engineer	Nick Peng	Configurations	IEEE 802.11n MCS0 HT20 CH 1, 6, 11 / Chain 1 + Chain 2
Test Date	Sep. 09, 2014		

##### Channel 1

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2390.00	53.57	54.00	-0.43	21.99	3.68	27.90	0.00	180	291	VERTICAL Average
2	2390.00	65.14	74.00	-8.86	33.56	3.68	27.90	0.00	180	291	VERTICAL Peak
3	2404.80	103.03			71.44	3.69	27.90	0.00	180	291	VERTICAL Average
4	2405.00	110.58			78.99	3.69	27.90	0.00	180	291	VERTICAL Peak

Item 3, 4 are the fundamental frequency at 2412 MHz.

##### Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2354.00	52.49	54.00	-1.51	20.93	3.66	27.90	0.00	100	250	HORIZONTAL Average
2	2387.40	65.43	74.00	-8.57	33.85	3.68	27.90	0.00	100	250	HORIZONTAL Peak
3	2430.80	118.57			86.97	3.70	27.90	0.00	100	250	HORIZONTAL Peak
4	2432.20	111.26			79.66	3.70	27.90	0.00	100	250	HORIZONTAL Average
5	2483.50	53.70	54.00	-0.30	22.07	3.73	27.90	0.00	100	250	HORIZONTAL Average
6	2483.50	62.81	74.00	-11.19	31.18	3.73	27.90	0.00	100	250	HORIZONTAL Peak

Item 3, 4 are the fundamental frequency at 2437 MHz.

##### Channel 11

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2460.80	102.53			70.91	3.72	27.90	0.00	264	288	HORIZONTAL Average
2	2460.80	110.24			78.62	3.72	27.90	0.00	264	288	HORIZONTAL Peak
3	2483.50	53.90	54.00	-0.10	22.27	3.73	27.90	0.00	264	288	HORIZONTAL Average
4	2484.30	66.99	74.00	-7.01	35.36	3.73	27.90	0.00	264	288	HORIZONTAL Peak

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	25°C	Humidity	58%
Test Engineer	Nick Peng	Configurations	IEEE 802.11n MCS0 HT40 CH 3, 6, 9 / Chain 1 + Chain 2
Test Date	Sep. 09, 2014		

### Channel 3

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2390.00	53.62	54.00	-0.38	22.04	3.68	27.90	0.00	179	296	VERTICAL Average
2	2390.00	67.03	74.00	-6.97	35.45	3.68	27.90	0.00	179	296	VERTICAL Peak
3	2432.40	95.97			64.37	3.70	27.90	0.00	179	296	VERTICAL Average
4	2434.80	104.08			72.48	3.70	27.90	0.00	179	296	VERTICAL Peak

Item 3, 4 are the fundamental frequency at 2422 MHz.

### Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2390.00	53.66	54.00	-0.34	22.08	3.68	27.90	0.00	256	281	VERTICAL Average
2	2390.00	66.06	74.00	-7.94	34.48	3.68	27.90	0.00	256	281	VERTICAL Peak
3	2420.80	101.44			69.84	3.70	27.90	0.00	256	281	VERTICAL Average
4	2432.80	109.55			77.95	3.70	27.90	0.00	256	281	VERTICAL Peak
5	2483.50	49.39	54.00	-4.61	17.76	3.73	27.90	0.00	256	281	VERTICAL Average
6	2483.50	63.33	74.00	-10.67	31.70	3.73	27.90	0.00	256	281	VERTICAL Peak

Item 3, 4 are the fundamental frequency at 2437 MHz.

### Channel 9

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2437.00	95.70			64.09	3.71	27.90	0.00	262	281	VERTICAL Average
2	2447.80	104.16			72.55	3.71	27.90	0.00	262	281	VERTICAL Peak
3	2483.50	53.37	54.00	-0.63	21.74	3.73	27.90	0.00	262	281	VERTICAL Average
4	2483.50	67.53	74.00	-6.47	35.90	3.73	27.90	0.00	262	281	VERTICAL Peak

Item 1, 2 are the fundamental frequency at 2452 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	25°C	Humidity	58%
Test Engineer	Nick Peng	Configurations	IEEE 802.11b CH 1, 6, 11 / Chain 1 + Chain 2
Test Date	Sep. 09, 2014		

### Channel 1

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2386.80	58.57	74.00	-15.43	26.99	3.68	27.90	0.00	240	251	HORIZONTAL Peak
2	2389.00	46.06	54.00	-7.94	14.48	3.68	27.90	0.00	240	251	HORIZONTAL Average
3	2409.40	104.80			73.21	3.69	27.90	0.00	240	251	HORIZONTAL Peak
4	2410.20	102.57			70.98	3.69	27.90	0.00	240	251	HORIZONTAL Average
5	2490.30	49.59	54.00	-4.41	17.96	3.73	27.90	0.00	240	251	HORIZONTAL Average
6	2493.30	61.44	74.00	-12.56	29.80	3.74	27.90	0.00	240	251	HORIZONTAL Peak

Item 3, 4 are the fundamental frequency at 2412 MHz.

### Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2354.40	50.80	54.00	-3.20	19.24	3.66	27.90	0.00	181	286	VERTICAL Average
2	2356.40	60.80	74.00	-13.20	29.24	3.66	27.90	0.00	181	286	VERTICAL Peak
3	2436.20	106.47			74.86	3.71	27.90	0.00	181	286	VERTICAL Average
4	2436.20	108.52			76.91	3.71	27.90	0.00	181	286	VERTICAL Peak
5	2483.50	45.20	54.00	-8.80	13.57	3.73	27.90	0.00	181	286	VERTICAL Average
6	2483.50	57.78	74.00	-16.22	26.15	3.73	27.90	0.00	181	286	VERTICAL Peak

Item 3, 4 are the fundamental frequency at 2437 MHz.

### Channel 11

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2380.20	50.90	54.00	-3.10	19.33	3.67	27.90	0.00	224	283	VERTICAL Average
2	2382.80	60.93	74.00	-13.07	29.35	3.68	27.90	0.00	224	283	VERTICAL Peak
3	2461.20	105.91			74.29	3.72	27.90	0.00	224	283	VERTICAL Average
4	2461.20	107.93			76.31	3.72	27.90	0.00	224	283	VERTICAL Peak
5	2483.50	46.89	54.00	-7.11	15.26	3.73	27.90	0.00	224	283	VERTICAL Average
6	2485.30	59.10	74.00	-14.90	27.47	3.73	27.90	0.00	224	283	VERTICAL Peak

Item 3, 4 are the fundamental frequency at 2462 MHz.

Temperature	25°C	Humidity	58%
Test Engineer	Nick Peng	Configurations	IEEE 802.11g CH 1, 6, 11 / Chain 1 + Chain 2
Test Date	Sep. 09, 2014		

#### Channel 1

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	2390.00	53.28	54.00	-0.72	21.70	3.68	27.90	0.00	247	282	VERTICAL Average
2	2390.00	66.68	74.00	-7.32	35.10	3.68	27.90	0.00	247	282	VERTICAL Peak
3	2408.20	112.63			81.04	3.69	27.90	0.00	247	282	VERTICAL Peak
4	2417.80	105.15			73.55	3.70	27.90	0.00	247	282	VERTICAL Average

Item 3, 4 are the fundamental frequency at 2412 MHz.

#### Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	2389.20	52.88	54.00	-1.12	21.30	3.68	27.90	0.00	100	247	HORIZONTAL Average
2	2389.40	62.15	74.00	-11.85	30.57	3.68	27.90	0.00	100	247	HORIZONTAL Peak
3	2433.40	110.88			79.28	3.70	27.90	0.00	100	247	HORIZONTAL Average
4	2433.40	117.52			85.92	3.70	27.90	0.00	100	247	HORIZONTAL Peak
5	2483.50	53.81	54.00	-0.19	22.18	3.73	27.90	0.00	100	247	HORIZONTAL Average
6	2483.90	63.86	74.00	-10.14	32.23	3.73	27.90	0.00	100	247	HORIZONTAL Peak

Item 3, 4 are the fundamental frequency at 2437 MHz.

#### Channel 11

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	2458.40	104.53			72.91	3.72	27.90	0.00	130	244	HORIZONTAL Average
2	2458.80	111.91			80.29	3.72	27.90	0.00	130	244	HORIZONTAL Peak
3	2483.50	53.32	54.00	-0.68	21.69	3.73	27.90	0.00	130	244	HORIZONTAL Average
4	2483.50	65.92	74.00	-8.08	34.29	3.73	27.90	0.00	130	244	HORIZONTAL Peak

Item 1, 2 are the fundamental frequency at 2462 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band

Plot on Configuration IEEE 802.11n MCS0 HT20 / Reference Level




Date: 10.SEP.2014 11:56:32

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 10.SEP.2014 11:57:40

### Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 10.SEP.2014 11:58:01

### Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 11 / 30MHz~2400MHz (down 30dBc)



Date: 10.SEP.2014 11:58:53


# Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 11 / 2500MHz~26500MHz (down 30dBc)



Date: 10.SEP.2014 11:59:23




### Plot on Configuration IEEE 802.11n MCS0 HT40 / Reference Level




Date: 10.SEP.2014 12:00:50

### Plot on Configuration IEEE 802.11n MCS0 HT40 / CH 3 / 30MHz~2400MHz (down 30dBc)




Date: 10.SEP.2014 12:02:04

### Plot on Configuration IEEE 802.11n MCS0 HT40 / CH 3 / 2500MHz~26500MHz (down 30dBc)




Date: 10.SEP.2014 12:02:23

### Plot on Configuration IEEE 802.11n MCS0 HT40 / CH 9 / 30MHz~2400MHz (down 30dBc)




Date: 10.SEP.2014 12:03:25

# Plot on Configuration IEEE 802.11n MCS0 HT40 / CH 9 / 2500MHz~26500MHz (down 30dBc)




Date: 10.SEP.2014 12:03:02

### Plot on Configuration IEEE 802.11b / Reference Level




Date: 10.SEP.2014 11:50:03

### Plot on Configuration IEEE 802.11b / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 10.SEP.2014 11:50:41

### Plot on Configuration IEEE 802.11b / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 10.SEP.2014 11:51:06

### Plot on Configuration IEEE 802.11b / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 10.SEP.2014 11:51:58

# Plot on Configuration IEEE 802.11b / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 10.SEP.2014 11:51:40

### Plot on Configuration IEEE 802.11g / Reference Level




Date: 10.SEP.2014 11:53:33

### Plot on Configuration IEEE 802.11g / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 10.SEP.2014 11:54:20

### Plot on Configuration IEEE 802.11g / CH 1 / 2500MHz~26500MHz (down 30dBc)



Date: 10.SEP.2014 11:54:54


### Plot on Configuration IEEE 802.11g / CH 11 / 30MHz~2400MHz (down 30dBc)



Date: 10.SEP.2014 11:55:34



# Plot on Configuration IEEE 802.11g / CH 11 / 2500MHz~26500MHz (down 30dBc)



Date: 10.SEP.2014 11:55:22

## **4.7. Antenna Requirements**

### **4.7.1. Limit**

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

### **4.7.2. Antenna Connector Construction**

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

## 5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100355	9kHz ~ 2.75GHz	Apr. 23, 2014	Conduction (CO01-CB)
MXE EMI Receiver	Agilent	N9038A	MY52260140	9kHz ~ 8GHz	Dec. 25, 2013	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Nov. 23, 2013	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Nov. 23, 2013	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	150kHz ~ 30MHz	Dec. 04, 2013	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-	N.C.R.	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	May 26, 2014	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Nov. 05, 2012*	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 01, 2013	Radiation (03CH01-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Aug. 22, 2014	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 12, 2013	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Dec. 16, 2013	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26GHz ~ 40GHz	Oct. 23, 2013	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100019	9kHz~40GHz	Dec. 02, 2013	Radiation (03CH01-CB)
EMI Test Receiver	Agilent	N9038A	MY52260123	9kHz ~ 8GHz	Dec. 12, 2013	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R.	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO 2000	N/A	1 m - 4 m	N.C.R.	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
Signal analyzer	R&S	FSV40	100979	9kHz~40GHz	Nov. 29, 2013	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 03, 2014	Conducted (TH01-CB)
Signal Generator	R&S	SMR40	100302	10MHz-40GHz	Dec. 02, 2013	Conducted (TH01-CB)
RF Power Divider	Woken	2 Way	0120A02056002D	2GHz ~ 18GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Power Divider	Woken	3 Way	MDC2366	2GHz ~ 18GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Power Divider	Woken	4 Way	0120A04056002D	2GHz ~ 18GHz	Nov. 17, 2013	Conducted (TH01-CB)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Signal generator	R&S	SMU200A	102782	25MHz-6GHz	Nov. 15, 2013	Conducted (TH01-CB)
Horn Antenna	COM-POWER	AH-118	071187	1GHz – 18GHz	Aug. 26, 2014	Conducted (TH01-CB)
Horn Antenna	COM-POWER	AH-118	071042	1GHz – 18GHz	Nov. 20, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
Power Sensor	Agilent	E9327A	US40442088	50MHz~18GHz	Dec. 02, 2013	Conducted (TH01-CB)
Power Meter	Agilent	E4416A	GB41291199	50MHz~18GHz	Dec. 02, 2013	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

“\*” Calibration Interval of instruments listed above is two years.

N.C.R. means Non-Calibration required.

## 6. MEASUREMENT UNCERTAINTY

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	2.4 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	3.7 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.7 dB	Confidence levels of 95%