

FCC REPORT

(WIFI)

Applicant: Libre Wireless Technologies, Inc.

Address of Applicant: 5405 Alton Parkway, Suite A-563, Irvine, CA 92604, USA

Equipment Under Test (EUT)

Product Name: Wireless Audio Module

Model No.: LS6-N22S

Trade mark: Libre

FCC ID: 2ADBM-LS6-N22S

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: 07 Dec., 2016

Date of Test: 07 Dec., to 16 Dec., 2016

Date of report issued: 20 Dec., 2016

Test Result: PASS*

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	20 Dec., 2016	Original

Tested by:

Date:

20 Dec., 2016

Test Engineer

Reviewed by:

Date:

20 Dec., 2016

Project Engineer

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 TEST SUMMARY.....	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF E.U.T.....	5
5.3 TEST ENVIRONMENT AND MODE	6
5.4 MEASUREMENT UNCERTAINTY.....	6
5.5 LABORATORY FACILITY.....	6
5.6 LABORATORY LOCATION	7
5.7 TEST INSTRUMENTS LIST.....	7
6 TEST RESULTS AND MEASUREMENT DATA.....	8
6.1 ANTENNA REQUIREMENT:.....	8
6.2 CONDUCTED EMISSION	9
6.3 CONDUCTED OUTPUT POWER	12
6.4 OCCUPY BANDWIDTH	20
6.5 POWER SPECTRAL DENSITY	34
6.6 BAND EDGE	41
6.6.1 Conducted Emission Method.....	41
6.6.2 Radiated Emission Method.....	46
6.7 SPURIOUS EMISSION.....	59
6.7.1 Conducted Emission Method.....	59
6.7.2 Radiated Emission Method.....	72
7 TEST SETUP PHOTO	79
8 EUT CONSTRUCTIONAL DETAILS	81

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(3)	Pass
6dB Emission Bandwidth 99% Occupied Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247(d)	Pass
Spurious Emission	15.205/15.209	Pass

Pass: The EUT complies with the essential requirements in the standard.

5 General Information

5.1 Client Information

Applicant:	Libre Wireless Technologies, Inc.
Address of Applicant:	5405 Alton Parkway, Suite A-563, Irvine, CA 92604, USA
Manufacturer:	RF-Link Technology Investments Co. Ltd.
Address of Manufacturer:	6 th Floor, Building 56A, Baotian 3 rd Road, Xixiang Sub-District, Bao'An District, Shenzhen City, PRC

5.2 General Description of E.U.T.

Product Name:	Wireless Audio Module
Model No.:	LS6-N22S
Operation Frequency:	2412MHz~2462MHz (802.11b/802.11g/802.11n(H20))
Channel numbers:	11 for 802.11b/802.11g/802.11n(H20)
Channel separation:	5MHz
Modulation technology: (IEEE 802.11b)	Direct Sequence Spread Spectrum (DSSS)
Modulation technology: (IEEE 802.11g/802.11n)	Orthogonal Frequency Division Multiplexing(OFDM)
Data speed (IEEE 802.11b):	1Mbps, 2Mbps, 5.5Mbps, 11Mbps
Data speed (IEEE 802.11g):	6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps
Data speed (IEEE 802.11n):	Up to 150Mbps
MIMO Support:	2T2R
Antenna Type:	PCB Antenna
Antenna gain:	1.5dBi ; Directional gain=1.5+10log2=4.51dBi
Power supply:	DC 3.3V

Operation Frequency each of channel For 802.11b/g/n(H20)

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

802.11b/802.11g/802.11n (H20)

Channel	Frequency
The lowest channel	2412MHz
The middle channel	2437MHz
The Highest channel	2462MHz

5.3 Test environment and mode

Operating Environment:	
Temperature:	24.0 °C
Humidity:	54 % RH
Atmospheric Pressure:	1010 mbar
Test mode:	
Operation mode	Keep the EUT in continuous transmitting with modulation
The sample was placed 0.8m (below 1GHz)/1.5m (above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:								
Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.								
<table border="1"> <thead> <tr> <th>Mode</th><th>Data rate</th></tr> </thead> <tbody> <tr> <td>802.11b</td><td>1Mbps</td></tr> <tr> <td>802.11g</td><td>6Mbps</td></tr> <tr> <td>802.11n(H20)</td><td>6.5Mbps</td></tr> </tbody> </table>	Mode	Data rate	802.11b	1Mbps	802.11g	6Mbps	802.11n(H20)	6.5Mbps
Mode	Data rate							
802.11b	1Mbps							
802.11g	6Mbps							
802.11n(H20)	6.5Mbps							
Final Test Mode:								
According to ANSI C63.4 standards, the test results are both the "worst case" and "worst setup" 1Mbps for 802.11b, 6Mbps for 802.11g, 6.5Mbps for 802.11n(H20). Duty cycle setting during the transmission is 100% with maximum power setting for all modulations.								

5.4 Measurement Uncertainty

Items	Expanded Uncertainty (Confidence of 95%)
Conducted Emission (9kHz ~ 30MHz)	2.14 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	4.24 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	4.35 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	4.44 dB (k=2)
Radiated Emission (18GHz ~ 26.5GHz)	4.56 dB (k=2)

5.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:
• FCC - Registration No.: 817957 Shenzhen Zhongjian Nanfang Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in out files. Registration 817957, February 27, 2012.
• IC - Registration No.: 10106A-1 The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.
• CNAS - Registration No.: CNAS L6048 Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

5.6 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
 Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
 Bao'an District, Shenzhen, Guangdong, China
 Tel: +86-755-23118282
 Fax: +86-755-23116366


5.7 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	3m SAC	SAEMC	9(L)*6(W)* 6(H)	CCIS0001	08-23-2014	08-22-2017
2	BiConiLog Antenna	SCHWARZBECK	VULB9163	CCIS0005	03-25-2016	03-25-2017
3	Horn Antenna	SCHWARZBECK	BBHA9120D	CCIS0006	03-25-2016	03-25-2017
4	Pre-amplifier (10kHz-1.3GHz)	HP	8447D	CCIS0003	04-01-2016	03-31-2017
5	Pre-amplifier (1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	CCIS0011	04-01-2016	03-31-2017
6	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	04-01-2016	03-31-2017
7	Horn Antenna	ETS-LINDGREN	3160	GTS217	04-01-2016	03-31-2017
8	Spectrum analyzer 9k-30GHz	Rohde & Schwarz	FSP30	CCIS0023	03-28-2016	03-28-2017
9	EMI Test Receiver	Rohde & Schwarz	ESRP7	CCIS0167	03-28-2016	03-28-2017
10	Loop antenna	Laplace instrument	RF300	EMC0701	04-01-2016	03-31-2017
11	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
12	Coaxial Cable	N/A	N/A	CCIS0018	04-01-2016	03-31-2017
13	Coaxial Cable	N/A	N/A	CCIS0020	04-01-2016	03-31-2017

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	Shielding Room	ZhongShuo Electron	11.0(L)x4.0(W)x3.0(H)	CCIS0061	08-23-2014	08-22-2017
2	EMI Test Receiver	Rohde & Schwarz	ESCI	CCIS0002	03-24-2016	03-24-2017
3	LISN	CHASE	MN2050D	CCIS0074	03-26-2016	03-26-2017
4	Coaxial Cable	CCIS	N/A	CCIS0086	04-01-2016	03-31-2017
5	EMI Test Software	AUDIX	E3	N/A	N/A	N/A


6 Test results and Measurement Data

6.1 Antenna requirement:

Standard requirement:	FCC Part 15 C Section 15.203 /247(c)
15.203 requirement:	<p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p>
15.247(c) (1)(i) requirement:	<p>(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</p>
E.U.T Antenna:	<p>The WiFi antenna used unique connector which cannot replace by end-user, the best case gain of the antenna is 1.5 dBi. Directional gain=1.5+10log2=4.51dBi</p> 


6.2 Conducted Emission

Test Requirement:	FCC Part 15 C Section 15.207		
Test Method:	ANSI C63.4: 2014		
Test Frequency Range:	150 kHz to 30 MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9 kHz, VBW=30 kHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test procedure	<ol style="list-style-type: none"> The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.), which provides a 50ohm/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement. 		
Test setup:	<p>Reference Plane</p> <p>LISN → AUX Equipment → E.U.T</p> <p>LISN → Filter → EMI Receiver</p> <p>Test table/Insulation plane</p> <p>40cm 80cm</p> <p><i>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</i></p>		
Test Instruments:	Refer to section 5.7 for details		
Test mode:	Refer to section 5.3 for details		
Test results:	Passed		

Measurement Data:**Neutral:****Notes:**

1. An initial pre-scan was performed on the live and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss.

Line:



Trace: 15


Site : CCIS Shielding Room
 Condition : FCC CLASS-B QP LISN LINE
 Pro :
 EUT : Wireless Audio Module
 Model : LS6-M22S
 Test Mode : WIFI MODE
 Power Rating : AC 120V/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: YT
 Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.166	28.82	0.14	10.77	39.73	65.16	-25.43	QP
2	0.166	11.91	0.27	10.77	22.95	55.16	-32.21	Average
3	0.202	28.57	0.15	10.76	39.48	63.54	-24.06	QP
4	0.361	24.15	0.21	10.73	35.09	58.69	-23.60	QP
5	0.369	10.96	0.27	10.73	21.96	48.52	-26.56	Average
6	0.555	27.75	0.26	10.77	38.78	56.00	-17.22	QP
7	0.555	20.42	0.27	10.77	31.46	46.00	-14.54	Average
8	0.759	22.10	0.31	10.80	33.21	56.00	-22.79	QP
9	0.759	10.82	0.23	10.80	21.85	46.00	-24.15	Average
10	1.060	20.84	0.26	10.88	31.98	56.00	-24.02	QP
11	2.915	4.00	0.27	10.92	15.19	46.00	-30.81	Average
12	9.552	4.55	0.31	10.92	15.78	50.00	-34.22	Average

Notes:

1. An initial pre-scan was performed on the live and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss.

6.3 Conducted Output Power

Test Requirement:	FCC Part 15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.10:2013 and KDB558074v03r05 section 9.2.2.2
Limit:	30dBm
Test setup:	
Test Instruments:	Refer to section 5.7 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:

Mode	Test CH	Ant. Port	Conducted Output power (dBm)	Total power (dBm)	Limit (dBm)	Result
802.11b	Lowest	TX0	17.74	20.15	30.00	Pass
		TX1	16.44			
	Middle	TX0	16.90	19.75	30.00	Pass
		TX1	16.57			
	Highest	TX0	16.47	19.67	30.00	Pass
		TX1	16.85			
802.11g	Lowest	TX0	16.43	19.23	30.00	Pass
		TX1	15.99			
	Middle	TX0	15.75	18.63	30.00	Pass
		TX1	15.49			
	Highest	TX0	15.36	18.56	30.00	Pass
		TX1	15.74			
802.11n(H20)	Lowest	TX0	16.54	19.08	30.00	Pass
		TX1	15.54			
	Middle	TX0	15.82	18.87	30.00	Pass
		TX1	15.89			
	Highest	TX0	15.41	18.25	30.00	Pass
		TX1	15.06			


Remark:

1. The directional Gain of antenna is less than 6 dBi, so the limit of power is 30 dBm.


Test plot as follows:

TX0


Test mode: 802.11b



Lowest channel




Middle channel




Highest channel

Test mode: 802.11g






Lowest channel



Middle channel




Highest channel


Test mode: 802.11n(H20)

Lowest channel

Middle channel

Highest channel

TX1


Test mode: 802.11b



Lowest channel




Middle channel



Highest channel


Test mode: 802.11g



Lowest channel




Middle channel



Highest channel


Test mode: 802.11n(H20)



Lowest channel




Middle channel



Highest channel

6.4 Occupy Bandwidth

Test Requirement:	FCC Part 15 C Section 15.247 (a)(2)
Test Method:	ANSI C63.10:2013 and KDB558074v03r05 section 8.1
Limit:	>500kHz
Test setup:	 <p>The diagram illustrates the test setup for measuring occupied bandwidth. A Spectrum Analyzer is positioned at the top left, displaying a green waveform on its screen. A red cable connects the analyzer to a gray rectangular box labeled "E.U.T". This entire assembly rests on a light-colored rectangular table labeled "Non-Conducted Table". Below the table is a thick, dark gray horizontal bar labeled "Ground Reference Plane".</p>
Test Instruments:	Refer to section 5.7 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed


Measurement Data:**TX0**

Test CH	6dB Emission Bandwidth (MHz)			Limit (kHz)	Result
	802.11b	802.11g	802.11n(H20)		
Lowest	9.92	16.80	17.92	>500	Pass
Middle	10.00	16.80	17.92		
Highest	9.92	16.80	18.00		
Test CH	99% Occupy Bandwidth (MHz)			Limit (kHz)	Result
	802.11b	802.11g	802.11n(H20)		
Lowest	12.56	16.64	17.76	N/A	N/A
Middle	12.48	16.64	17.68		
Highest	12.48	16.64	17.68		

TX1


Test CH	6dB Emission Bandwidth (MHz)			Limit (kHz)	Result
	802.11b	802.11g	802.11n(H20)		
Lowest	10.00	17.92	17.92	>500	Pass
Middle	10.00	17.92	17.92		
Highest	10.00	18.00	18.00		
Test CH	99% Occupy Bandwidth (MHz)			Limit (kHz)	Result
	802.11b	802.11g	802.11n(H20)		
Lowest	12.48	17.68	17.68	N/A	N/A
Middle	12.48	17.68	17.68		
Highest	12.48	17.68	17.68		

Test plot as follows:
TX0




Date: 13.DEC.2016 20:01:43

Lowest channel



Date: 13.DEC.2016 20:03:34


Middle channel



Date: 13.DEC.2016 20:04:18


Highest channel

Test mode: 802.11g




Date: 13.DEC.2016 20:07:36

Lowest channel



Date: 13.DEC.2016 20:08:25


Middle channel



Date: 13.DEC.2016 20:10:15


Highest channel

Test mode: 802.11n(H20)




Date: 13.DEC.2016 20:11:13

Lowest channel



Date: 13.DEC.2016 20:12:40

Middle channel




Date: 13.DEC.2016 20:14:02

Highest channel

TX1


6dB EBW

Test mode: 802.11b




Date: 13.DEC.2016 20:42:37

Lowest channel



Date: 13.DEC.2016 20:44:31


Middle channel



Date: 13.DEC.2016 20:45:23


Highest channel

Test mode: 802.11g




Date: 13.DEC.2016 20:48:19

Lowest channel



Date: 13.DEC.2016 20:49:18


Middle channel



Date: 13.DEC.2016 20:51:37


Highest channel

Test mode: 802.11n(H20)




Date: 13.DEC.2016 20:52:52

Lowest channel



Date: 13.DEC.2016 20:54:59

Middle channel




Date: 13.DEC.2016 20:55:49


Highest channel

TX0


99% OBW
Test mode: 802.11b



Lowest channel




Middle channel




Highest channel

Test mode: 802.11g




Date: 13.DEC.2016 20:07:00

Lowest channel



Date: 13.DEC.2016 20:08:51


Middle channel



Date: 13.DEC.2016 20:09:24


Highest channel

Test mode: 802.11n(H20)




Date: 13.DEC.2016 20:11:33

Lowest channel



Date: 13.DEC.2016 20:11:56

Middle channel




Date: 13.DEC.2016 20:14:25

Highest channel


TX1

99% OBW
Test mode: 802.11b




Date: 13.DEC.2016 20:43:12

Lowest channel



Date: 13.DEC.2016 20:43:41


Middle channel



Date: 13.DEC.2016 20:45:48


Highest channel

Test mode: 802.11g




Date: 13.DEC.2016 20:47:14

Lowest channel



Date: 13.DEC.2016 20:49:50


Middle channel



Date: 13.DEC.2016 20:50:22


Highest channel

Test mode: 802.11n(H20)




Date: 13.DEC.2016 20:53:17

Lowest channel



Date: 13.DEC.2016 20:53:53


Middle channel



Date: 13.DEC.2016 20:56:17

Highest channel

6.5 Power Spectral Density


Test Requirement:	FCC Part 15 C Section 15.247 (e)
Test Method:	ANSI C63.10:2013 and KDB558074v03r05 section 10.2
Limit:	8dBm
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to the E.U.T (Equipment Under Test) via a cable. The E.U.T is placed on a Non-Conducted Table. The entire assembly sits on a Ground Reference Plane.</p>
Test Instruments:	Refer to section 5.7 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:

Mode	Test Channel	Ant. Port	PSD (dBm)	Total PSD (dBm)	Limit (dBm)	Result
802.11b	Lowest	TX0	4.12	7.58	8.00	Pass
		TX1	4.97			
	Middle	TX0	4.47	7.49	8.00	Pass
		TX1	4.49			
	Highest	TX0	4.89	7.88	8.00	Pass
		TX1	4.84			
802.11g	Lowest	TX0	1.53	3.96	8.00	Pass
		TX1	0.28			
	Middle	TX0	0.68	3.45	8.00	Pass
		TX1	0.19			
	Highest	TX0	0.16	3.32	8.00	Pass
		TX1	0.46			
802.11n(H20)	Lowest	TX0	0.82	3.38	8.00	Pass
		TX1	-0.14			
	Middle	TX0	0.29	3.08	8.00	Pass
		TX1	-0.16			
	Highest	TX0	-0.20	3.02	8.00	Pass
		TX1	0.21			


Test plot as follows:

TX0




Date: 20.DEC.2016 15:21:25

Lowest channel



Date: 20.DEC.2016 15:22:23


Middle channel



Date: 13.DEC.2016 20:17:20


Highest channel

Test mode: 802.11g




Date: 13.DEC.2016 20:18:22

Lowest channel



Date: 13.DEC.2016 20:18:53


Middle channel



Date: 13.DEC.2016 20:20:50


Highest channel

Test mode: 802.11n(H20)




Date: 13.DEC.2016 20:21:47

Lowest channel



Date: 13.DEC.2016 20:22:14

Middle channel




Date: 13.DEC.2016 20:22:54

Highest channel


TX1

Test mode: 802.11b




Date: 13.DEC.2016 20:57:24

Lowest channel



Date: 20.DEC.2016 15:23:17


Middle channel



Date: 20.DEC.2016 15:24:44


Highest channel

Test mode: 802.11g




Date: 13.DEC.2016 21:00:35

Lowest channel



Date: 13.DEC.2016 21:02:13


Middle channel



Date: 13.DEC.2016 21:03:11


Highest channel

Test mode: 802.11n(H20)




Date: 13.DEC.2016 21:04:09

Lowest channel



Date: 13.DEC.2016 21:04:50

Middle channel




Date: 13.DEC.2016 21:05:37

Highest channel



6.6 Band Edge

6.6.1 Conducted Emission Method

Test Requirement:	FCC Part 15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 and KDB558074v03r05 section 13
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 5.7 for details
Test mode:	Refer to section 5.3 for details
Test results:	Comply with 30dBc requirement , Pass

Test plot as follows:

TX0





Date: 20.DEC.2016 15:27:37

Lowest channel

Date: 13.DEC.2016 20:30:47

Highest channel




Date: 13.DEC.2016 20:28:05

Lowest channel

Date: 13.DEC.2016 20:31:46


Highest channel

802.11n(H20)



Date: 8.DEC.2016 12:47:03

Lowest channel





Date: 13.DEC.2016 20:32:34

Highest channel

TX1

802.11b





Date: 13.DEC.2016 21:08:00

Lowest channel

Date: 20.DEC.2016 15:28:56

Highest channel

802.11g




Date: 8.DEC.2016 12:48:03

Lowest channel

Date: 13.DEC.2016 21:11:21


Highest channel

802.11n(H20)



Date: 13.DEC.2016 21:09:27

Lowest channel



Date: 13.DEC.2016 21:12:03

Highest channel


6.6.2 Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.209 and 15.205								
Test Method:	ANSI C63.10: 2013 and KDB 558074v03r05 section 12.1								
Test Frequency Range:	2.3GHz to 2.5GHz								
Test site:	Measurement Distance: 3m								
Receiver setup:	Frequency	Detector	RBW	VBW	Remark				
	Above 1GHz	Peak	1MHz	3MHz	Peak Value				
Limit:	Frequency	Limit (dBuV/m @ 3m)		Remark					
	Above 1GHz	54.00		Average Value					
		74.00		Peak Value					
Test Procedure:	<ol style="list-style-type: none"> The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 								
Test setup:									
Test Instruments:	Refer to section 5.7 for details								
Test mode:	Keeping MIMO TX mode								
Test results:	Passed								

802.11b

Test channel: Lowest

Horizontal:




Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
 EUT : Wireless Audio Module
 Model : LS6-N22S
 Test mode : 802.11b-L mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Huni:55% 101KPa
 Test Engineer: YT
 REMARK : ANT1

	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2338.612	22.99	23.67	4.64	0.00	51.30	74.00	-22.70 Peak
2	2338.612	12.34	23.67	4.64	0.00	40.65	54.00	-13.35 Average
3	2390.000	18.05	23.68	4.69	0.00	46.42	74.00	-27.58 Peak
4	2390.000	7.64	23.68	4.69	0.00	36.01	54.00	-17.99 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Vertical:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 EUT : Wireless Audio Module
 Model : LS6-N22S
 Test mode : 802.11b-L mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55% 101KPa
 Test Engineer: YT
 REMARK : ANT1


Freq	Read	Antenna	Cable	Preamp	Limit	Over	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	
1	2321.952	22.31	23.67	4.62	0.00	50.60	74.00 -23.40 Peak
2	2321.952	13.34	23.67	4.62	0.00	41.63	54.00 -12.37 Average
3	2390.000	18.72	23.68	4.69	0.00	47.09	74.00 -26.91 Peak
4	2390.000	7.25	23.68	4.69	0.00	35.62	54.00 -18.38 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test channel: Highest

Horizontal:




Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
 EUT : Wireless Audio Module
 Model : LS6-N22S
 Test mode : 802.11b-H mode
 Power Rating : AC120W/60Hz
 Environment : Temp:25.5°C Huni:55% 101KPa
 Test Engineer: YT
 REMARK : ANT1

Freq	Read	Antenna	Cable	Preampl	Limit	Over	Remark
	Level	Factor	Loss	Factor			
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1 2483.500	19.88	23.70	4.81	0.00	48.39	74.00	-25.61 Peak
2 2483.500	7.67	23.70	4.81	0.00	36.18	54.00	-17.82 Average
3 2483.672	20.04	23.70	4.81	0.00	48.55	74.00	-25.45 Peak
4 2483.672	8.33	23.70	4.81	0.00	36.84	54.00	-17.16 Average

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- The emission levels of other frequencies are very lower than the limit and not show in test report.

Vertical:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 EUT : Wireless Audio Module
 Model : LS6-N22S
 Test mode : 802.11b-H mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Huni:55% 101KPa
 Test Engineer: YT
 REMARK : ANT1

Freq	Read	Antenna	Cable	Preampl	Limit	Over	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	
1	2483.500	18.52	23.70	4.81	0.00	47.03	74.00 -26.97 Peak
2	2483.500	7.63	23.70	4.81	0.00	36.14	54.00 -17.86 Average
3	2492.257	20.70	23.70	4.82	0.00	49.22	74.00 -24.78 Peak
4	2492.257	10.45	23.70	4.82	0.00	38.97	54.00 -15.03 Average


Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11g

Test channel: Lowest

Horizontal:




Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
 EUT : Wireless Audio Module
 Model : LS6-N22S
 Test mode : 802.11g-L mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Huni:55% 101KPa
 Test Engineer: YT
 REMARK : ANT1

	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier Factor	Limit Level	Line Limit	Over Limit	Remark
Freq	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2389.538	26.64	23.68	4.69	0.00	55.01	74.00	-18.99 Peak
2	2389.538	13.67	23.68	4.69	0.00	42.04	54.00	-11.96 Average
3	2390.000	25.45	23.68	4.69	0.00	53.82	74.00	-20.18 Peak
4	2390.000	13.11	23.68	4.69	0.00	41.48	54.00	-12.52 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Vertical:



Site : 3m chamber
Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
EUT : Wireless Audio Module
Model : LS6-N22S
Test mode : 802.11g-L mode
Power Rating : AC120W/60Hz
Environment : Temp:25.5°C Huni:55% 101KPa
Test Engineer: YT
REMARK : ANT1


Freq	Read	Antenna	Cable	Preamp	Limit	Over	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	
1	2390.000	23.83	23.68	4.69	0.00	52.20	74.00 -21.80 Peak
2	2390.000	9.57	23.68	4.69	0.00	37.94	54.00 -16.06 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test channel: Highest

Horizontal:




Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
 EUT : Wireless Audio Module
 Model : LS6-N22S
 Test mode : 802.11g-H mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Huni:55% 101KPa
 Test Engineer: YT
 REMARK : ANT1

Freq	ReadAntenna	Cable	Preamp	Limit	Over	Remark		
	MHz	Level	Factor	Loss	Level	Line	Limit	Remark
	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	31.03	23.70	4.81	0.00	59.54	74.00	-14.46 Peak
2	2483.500	16.73	23.70	4.81	0.00	45.24	54.00	-8.76 Average

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- The emission levels of other frequencies are very lower than the limit and not show in test report.

Vertical:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 EUT : Wireless Audio Module
 Model : LS6-N22S
 Test mode : 802.11g-H mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55% 101KPa
 Test Engineer: YT
 REMARK : ANT1

Freq	ReadAntenna	Cable	Preamp	Limit	Over	Remark	
	Level	Factor	Loss	Level	Line		
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1 2483.500	25.65	23.70	4.81	0.00	54.16	74.00	-19.84 Peak
2 2483.500	12.96	23.70	4.81	0.00	41.47	54.00	-12.53 Average


Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11n (H20)

Test channel: Lowest

Horizontal:




Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
 EUT : Wireless Audio Module
 Model : LS6-N22S
 Test mode : 802.11n20-L mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55% 101KPa
 Test Engineer: YT
 REMARK : ANT1

Freq	Read	Antenna	Cable	Preampl	Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line	
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	22.82	23.68	4.69	0.00	51.19	74.00 -22.81 Peak
2	2390.000	9.46	23.68	4.69	0.00	37.83	54.00 -16.17 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Vertical:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 EUT : Wireless Audio Module
 Model : LS6-N22S
 Test mode : 802.11n20-L mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55% 101KPa
 Test Engineer: YT
 REMARK : ANT1


	ReadAntenna Freq	Cable Level	Preamp Factor	Limit Loss Factor	Over Level	Line dBuV/m	Over Line dBuV/m	Over Limit dB	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2389.198	21.61	23.68	4.69	0.00	49.98	74.00	-24.02	Peak
2	2389.198	10.24	23.68	4.69	0.00	38.61	54.00	-15.39	Average
3	2390.000	21.39	23.68	4.69	0.00	49.76	74.00	-24.24	Peak
4	2390.000	9.61	23.68	4.69	0.00	37.98	54.00	-16.02	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test channel: Highest

Horizontal:




Site : 3m chamber
Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
EUT : Wireless Audio Module
Model : LS6-N22S
Test mode : 802.11n20-H mode
Power Rating : AC120V/60Hz
Environment : Temp:25.5°C Humi:55% 101KPa
Test Engineer: YT
REMARK : ANT1

	ReadAntenna Freq	Cable Freq	Preamp Factor	Loss Factor	Limit Level	Over Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	31.56	23.70	4.81	0.00	60.07	74.00	-13.93 Peak
2	2483.500	16.84	23.70	4.81	0.00	45.35	54.00	-8.65 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Vertical:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 EUT : Wireless Audio Module
 Model : LS6-N22S
 Test mode : 802.11n20-H mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55% 101KPa
 Test Engineer: YT
 REMARK : ANT1


	ReadAntenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	29.11	23.70	4.81	0.00	57.62	74.00 -16.38 Peak
2	2483.500	12.97	23.70	4.81	0.00	41.48	54.00 -12.52 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

6.7 Spurious Emission

6.7.1 Conducted Emission Method


Test Requirement:	FCC Part 15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 and KDB558074v03r05 section 11
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
Test setup:	
Test Instruments:	Refer to section 5.7 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Test plot as follows:

TX0

Test mode: 802.11b


Lowest channel



Date: 13.DEC.2016 21:51:04


30MHz~25GHz

Middle channel



Date: 13.DEC.2016 21:51:30

30MHz~25GHz




Date: 7.DEC.2016 17:29:46

30MHz~25GHz

Test mode: 802.11g


Lowest channel



Date: 7.DEC.2016 17:30:42


30MHz~25GHz

Middle channel



Date: 7.DEC.2016 17:31:23

30MHz~25GHz




Date: 7.DEC.2016 17:31:59

30MHz~25GHz

Test mode: 802.11n(H20)


Lowest channel



Date: 7.DEC.2016 17:32:54


30MHz~25GHz

Middle channel



Date: 7.DEC.2016 17:33:37

30MHz~25GHz




Date: 7.DEC.2016 17:34:31

30MHz~25GHz

TX1

Test mode: 802.11b


Lowest channel



Date: 7.DEC.2016 17:15:32


30MHz~25GHz

Middle channel



Date: 13.DEC.2016 21:51:50

30MHz~25GHz




Date: 13.DEC.2016 21:52:25

30MHz~25GHz

Test mode: 802.11g


Lowest channel



Date: 7.DEC.2016 17:19:23


30MHz~25GHz

Middle channel



Date: 7.DEC.2016 17:19:56

30MHz~25GHz




Date: 7.DEC.2016 17:20:45


30MHz~25GHz


Test mode: 802.11n(H20)

Lowest channel



Middle channel





Date: 7.DEC.2016 17:26:57

30MHz~25GHz


6.7.2 Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
Limit:	RMS	1MHz	3MHz	Average	Average Value
	Frequency	Limit (dBuV/m @3m)		Remark	
	30MHz-88MHz	40.0		Quasi-peak Value	
	88MHz-216MHz	43.5		Quasi-peak Value	
	216MHz-960MHz	46.0		Quasi-peak Value	
	960MHz-1GHz	54.0		Quasi-peak Value	
Test Procedure:	Above 1GHz	54.0		Average Value	
		74.0		Peak Value	
<ol style="list-style-type: none"> The EUT was placed on the top of a rotating table 0.8m(below 1GHz)/1.5m(above 1GHz) above the ground at a 3 meter chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 					

Test setup:	<p>Below 1GHz</p> <p>Above 1GHz</p>
Test Instruments:	Refer to section 5.7 for details
Test mode:	Keeping MIMO TX MODE
Test results:	Passed
Remark:	<ol style="list-style-type: none"> Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis is the worst case. 9 kHz to 30MHz is too low, so only shows the data of above 30MHz in this report.

Below 1GHz


Horizontal:



Site : 3m chamber
Condition : FCC PART15 CLASS B 3m VULB9163(30M1G) HORIZONTAL
EUT : Wireless Audio Module
Model : LS6-N22S
Test mode : WIFI Mode
Power Rating : AC 120W/60Hz
Environment : Temp:25.5°C Humi:55%
Test Engineer: YT
REMARK :

Freq	Read	Antenna	Cable	Preamp	Limit	Over	Remark
	Level	Factor	Loss	Factor			
MHz	dB _{UV}	dB/m	dB	dB	dB _{UV} /m	dB _{UV} /m	dB
1	37.285	29.47	0.00	0.00	0.00	29.47	40.00 -10.53 QP
2	53.693	26.52	0.00	0.00	0.00	26.52	40.00 -13.48 QP
3	182.559	26.47	0.00	0.00	0.00	26.47	43.50 -17.03 QP
4	248.552	31.09	0.00	0.00	0.00	31.09	46.00 -14.91 QP
5	321.061	24.07	0.00	0.00	0.00	24.07	46.00 -21.93 QP
6	863.056	23.51	0.00	0.00	0.00	23.51	46.00 -22.49 QP

Vertical:



Site : 3m chamber
Condition : FCC PART15 CLASS B 3m VULB9163(30M1G) VERTICAL
EUT : Wireless Audio Module
Model : LS6-N22S
Test mode : WIFI Mode
Power Rating : AC 120V/60Hz
Environment : Temp:25.5°C Humi:55%
Test Engineer: YT
REMARK :

Freq	ReadAntenna		Cable Preamp		Limit Level	Over Line Limit	Remark	
	MHz	dBuV	Level Factor	Cable Loss Factor	dB	dBuV/m	dBuV/m	dB
1	37.025	35.07	0.00	0.00	0.00	35.07	40.00	-4.93 QP
2	53.882	34.71	0.00	0.00	0.00	34.71	40.00	-5.29 QP
3	131.758	29.71	0.00	0.00	0.00	29.71	43.50	-13.79 QP
4	261.975	30.22	0.00	0.00	0.00	30.22	46.00	-15.78 QP
5	517.248	30.05	0.00	0.00	0.00	30.05	46.00	-15.95 QP
6	833.317	30.68	0.00	0.00	0.00	30.68	46.00	-15.32 QP

Above 1GHz

Test mode: 802.11b			Test channel: Lowest			Remark: Peak		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
4824.00	53.32	36.06	6.81	41.82	54.37	74.00	-19.63	Vertical
4824.00	57.69	36.06	6.81	41.82	58.74	74.00	-15.26	Horizontal
Test mode: 802.11b			Test channel: Lowest			Remark: Average		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
4824.00	46.32	36.06	6.81	41.82	47.37	54.00	-6.63	Vertical
4824.00	49.21	36.06	6.81	41.82	50.26	54.00	-3.74	Horizontal

Test mode: 802.11b			Test channel: Middle			Remark: Peak		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
4874.00	56.35	36.32	6.85	41.84	57.68	74.00	-16.32	Vertical
4874.00	52.17	36.32	6.85	41.84	53.50	74.00	-20.50	Horizontal
Test mode: 802.11b			Test channel: Middle			Remark: Average		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
4874.00	50.03	36.32	6.85	41.84	51.36	54.00	-2.64	Vertical
4874.00	45.69	36.32	6.85	41.84	47.02	54.00	-6.98	Horizontal

Test mode: 802.11b			Test channel: Highest			Remark: Peak		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
4924.00	53.14	36.58	6.89	41.86	54.75	74.00	-19.25	Vertical
4924.00	48.62	36.58	6.89	41.86	50.23	74.00	-23.77	Horizontal
Test mode: 802.11b			Test channel: Highest			Remark: Average		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
4924.00	48.19	36.58	6.89	41.86	49.80	54.00	-4.20	Vertical
4924.00	41.27	36.58	6.89	41.86	42.88	54.00	-11.12	Horizontal

Remark:

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test mode: 802.11g			Test channel: Lowest			Remark: Peak		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
4824.00	52.34	36.06	6.81	41.82	53.39	74.00	-20.61	Vertical
4824.00	57.61	36.06	6.81	41.82	58.66	74.00	-15.34	Horizontal
Test mode: 802.11g			Test channel: Lowest			Remark: Average		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
4824.00	45.97	36.06	6.81	41.82	47.02	54.00	-6.98	Vertical
4824.00	48.97	36.06	6.81	41.82	50.02	54.00	-3.98	Horizontal

Test mode: 802.11g			Test channel: Middle			Remark: Peak		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
4874.00	56.31	36.32	6.85	41.84	57.64	74.00	-16.36	Vertical
4874.00	52.49	36.32	6.85	41.84	53.82	74.00	-20.18	Horizontal
Test mode: 802.11g			Test channel: Middle			Remark: Average		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
4874.00	50.01	36.32	6.85	41.84	51.34	54.00	-2.66	Vertical
4874.00	46.79	36.32	6.85	41.84	48.12	54.00	-5.88	Horizontal

Test mode: 802.11g			Test channel: Highest			Remark: Peak		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
4924.00	53.21	36.58	6.89	41.86	54.82	74.00	-19.18	Vertical
4924.00	48.75	36.58	6.89	41.86	50.36	74.00	-23.64	Horizontal
Test mode: 802.11g			Test channel: Highest			Remark: Average		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
4924.00	48.74	36.58	6.89	41.86	50.35	54.00	-3.65	Vertical
4924.00	42.21	36.58	6.89	41.86	43.82	54.00	-10.18	Horizontal

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- The emission levels of other frequencies are very lower than the limit and not show in test report.

Test mode: 802.11n(H20)			Test channel: Lowest			Remark: Peak		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
4824.00	53.31	36.06	6.81	41.82	54.36	74.00	-19.64	Vertical
4824.00	58.67	36.06	6.81	41.82	59.72	74.00	-14.28	Horizontal
Test mode: 802.11n(H20)			Test channel: Lowest			Remark: Average		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
4824.00	46.25	36.06	6.81	41.82	47.30	54.00	-6.70	Vertical
4824.00	47.58	36.06	6.81	41.82	48.63	54.00	-5.37	Horizontal

Test mode: 802.11n(H20)			Test channel: Middle			Remark: Peak		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
4874.00	55.79	36.32	6.85	41.84	57.12	74.00	-16.88	Vertical
4874.00	52.15	36.32	6.85	41.84	53.48	74.00	-20.52	Horizontal
Test mode: 802.11n(H20)			Test channel: Middle			Remark: Average		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
4874.00	49.67	36.32	6.85	41.84	51.00	54.00	-3.00	Vertical
4874.00	46.21	36.32	6.85	41.84	47.54	54.00	-6.46	Horizontal

Test mode: 802.11n(H20)			Test channel: Highest			Remark: Peak		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
4924.00	53.27	36.58	6.89	41.86	54.88	74.00	-19.12	Vertical
4924.00	48.95	36.58	6.89	41.86	50.56	74.00	-23.44	Horizontal
Test mode: 802.11n(H20)			Test channel: Highest			Remark: Average		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
4924.00	47.72	36.58	6.89	41.86	49.33	54.00	-4.67	Vertical
4924.00	43.36	36.58	6.89	41.86	44.97	54.00	-9.03	Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.