

FCC PART 15.247 TEST REPORT

For

Shenzhen Kaliho Technology Development Limited

19F. Block A, Stars plaza, Huaqiang North Road, FuTian District, Shenzhen, China

FCC ID: 2ADBRK918

Report Type:
Original Report

Smart Phone

Test Engineer: Dean Liu

Report Number: RDG150121005-00B

Report Date: 2015-03-16

Sula Huang

Reviewed By: RF Engineer

Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan)

No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Sona Hugof

Tel: +86-769-86858888

Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT Exercise Software	7
SUPPORT EQUIPMENT LIST AND DETAILS	
EXTERNAL I/O CABLE	
BLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	9
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	10
APPLICABLE STANDARD	
FCC §15.203 - ANTENNA REQUIREMENT	11
APPLICABLE STANDARD	
ANTENNA CONNECTOR CONSTRUCTION	
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	12
APPLICABLE STANDARD	
MEASUREMENT UNCERTAINTY	
EUT SETUP	
EMI TEST RECEIVER SETUP.	
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST EQUIPMENT LIST AND DETAILS	
TEST RESULTS SUMMARY	
TEST DATA	14
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	
APPLICABLE STANDARD	
MEASUREMENT UNCERTAINTY	
EUT SETUP	17
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH	
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS.	
TEST DATA	28

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER	35
APPLICABLE STANDARD	35
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	35
Test Data	35
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE	37
APPLICABLE STANDARD	37
TEST PROCEDURE	37
TEST EQUIPMENT LIST AND DETAILS	37
Test Data	37
FCC §15.247(e) - POWER SPECTRAL DENSITY	41
APPLICABLE STANDARD	41
TEST PROCEDURE	41
TEST EQUIPMENT LIST AND DETAILS	41
TEST DATA	41
DECLARATION LETTER	48

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The Shenzhen Kaliho Technology Development Limited's product, model number: K918(FCC ID: 2ADBRK918) (or the "EUT") in this report was a Smart Phone, which was measured approximately: 11.5 cm (L) x 6.15 cm (W) x 1.1cm (H), rated input voltage: DC3.7 V rechargeable Li-ion or DC5V charging from adapter.

Report No.: RDG150121005-00B

Adapter Information: HUAJING

Model:TN-050100E2

Input: 100-240V~50/60Hz 0.15A

Output: 5V 1.0A

Note: The series product, model K918 and K928, K938, K948, K958 are electrically identical, the differences between them is model name, we selected K918 for testing, the details was explained in the attached declaration letter.

* All measurement and test data in this report was gathered from production sample serial number: 150121005 (Assigned by applicant). The EUT was received on 2015-01-21.

Objective

This report is prepared on behalf of *Shenzhen Kaliho Technology Development Limited* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: 2ADBRK918. FCC Part 22H, 24E PCE submissions with FCC ID: 2ADBRK918. FCC Part 15C DSS submissions with FCC ID: 2ADBRK918.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

FCC Part 15.247 Page 4 of 48

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Report No.: RDG150121005-00B

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FCC Part 15.247 Page 5 of 48

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in testing mode, which was provided by manufacturer. For 2.4GHz band, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

Report No.: RDG150121005-00B

For 802.11b, 802.11g, and 802.11n ht20 modes were tested with Channel 1, 6 and 11.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

Equipment Modifications

No modification was made to the EUT tested.

FCC Part 15.247 Page 6 of 48

EUT Exercise Software

The worst condition (maximum power with 100% duty cycle) was setting by the software as following table:

Report No.: RDG150121005-00B

Test Mode	Test Software Version	Engineer Mode				
	Test Frequency	2412MHz	2437MHz	2462MHz		
802.11b	Data Rate	1Mbps	1Mbps	1Mbps		
002.110	Power Level Setting	8	8.5	9.5		
	Test Frequency	2412MHz	2437MHz	2462MHz		
802.11g	Data Rate	6Mbps	6Mbps	6Mbps		
0020119	Power Level Setting	10	11.5	12		
	Test Frequency	2412MHz	2437MHz	2462MHz		
802.11n	Data Rate	MCS0	MCS0	MCS0		
ht20	Power Level Setting	10	11.5	12.5		

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Shielding Type	Ferrite Core	Length (m) From Port		То
USB Cable	no	no	1.0	USB port of Adapter	EUT
Earphone Cable	no	no	1.1	Aduio Port of EUT	Earphone

FCC Part 15.247 Page 7 of 48

Block Diagram of Test Setup



FCC Part 15.247 Page 8 of 48

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
\$15.205, \$15.209, \$15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum conducted output power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

Report No.: RDG150121005-00B

FCC Part 15.247 Page 9 of 48

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Report No.: RDG150121005-00B

According to KDB447498 D01 General RF Exposure Guidance v05r02:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance,

mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is ≤ 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The maximum conducted output power= 9.79 dBm (9.53mW) at 2412MHz [(max. power of channel, mW)/(min. test separation distance, mm)] $[\sqrt{f(GHz)}]$ = 9.53/5*($\sqrt{2}$.412) = 2.96 < 3.0

So the stand-alone SAR evaluation is not necessary.

FCC Part 15.247 Page 10 of 48

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

Report No.: RDG150121005-00B

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has one internal antenna arrangement and the antenna gain is 2.0 dBi, which fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC Part 15.247 Page 11 of 48

FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

Report No.: RDG150121005-00B

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:


- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If U_{lab} is greater than U_{cispr} of Table 1, then:
- compliance is deemed to occur if no measured disturbance level, increased by $(U_{\text{lab}} U_{\text{cispr}})$, exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} U_{cispr})$, exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cispr}

Measurement	$U_{ m cispr}$
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMIN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

FCC Part 15.247 Page 12 of 48

Report No.: RDG150121005-00B

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W	
150 kHz – 30 MHz	9 kHz	

Test Procedure

During the conducted emission test, the adapter was connected to the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

 V_R : reading voltage amplitude A_c : attenuation caused by cable loss VDF: voltage division factor of AMN

C_f: Correction Factor

The "Margin" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

FCC Part 15.247 Page 13 of 48

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2014-10-20	2015-10-20
R&S	L.I.S.N	ESH2-Z5	892107/021	2014-06-09	2015-06-09
R&S	Two-line V-network	ENV 216	3560.6550.12	2014-12-11	2015-12-11
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

Report No.: RDG150121005-00B

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Part 15.207</u>, with the worst margin reading of:

3.6 dB at 0.812315MHz in the Neutral conducted mode

Test Data

Environmental Conditions

Temperature:	22.4 °C	
Relative Humidity:	36 %	
ATM Pressure:	101.7 kPa	


The testing was performed by Dean Liu on 2015-01-22.

FCC Part 15.247 Page 14 of 48

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

AC120 V, 60 Hz, Line:

Test Mode: Transmitting




Report No.: RDG150121005-00B

				Visited			
Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.687153	40.8	9.000	L1	10.6	15.2	56.0	Compliance
0.726569	42	9.000	L1	10.6	14.0	56.0	Compliance
0.768247	43.1	9.000	L1	10.5	12.9	56.0	Compliance
0.812315	44.4	9.000	L1	10.5	11.6	56.0	Compliance
0.852094	41.8	9.000	L1	10.5	14.2	56.0	Compliance
1.352690	32.5	9.000	L1	10.4	23.5	56.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.692650	31.8	9.000	L1	10.6	14.2	46.0	Compliance
0.732382	34.7	9.000	L1	10.6	11.3	46.0	Compliance
0.768247	34.9	9.000	L1	10.5	11.1	46.0	Compliance
0.812315	34.6	9.000	L1	10.5	11.4	46.0	Compliance
0.852094	33.1	9.000	L1	10.5	12.9	46.0	Compliance
1.418932	28.7	9.000	L1	10.4	17.3	46.0	Compliance

FCC Part 15.247 Page 15 of 48

AC120 V, 60 Hz, Neutral:



Report No.: RDG150121005-00B

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.360371	49.9	9.000	N	11.0	8.8	58.7	Compliance
0.715082	48.1	9.000	N	10.6	7.9	56.0	Compliance
0.762149	50.8	9.000	N	10.5	5.2	56.0	Compliance
0.818813	46	9.000	N	10.5	10.0	56.0	Compliance
0.865782	31.7	9.000	N	10.5	24.3	56.0	Compliance
0.915445	45.6	9.000	N	10.6	10.4	56.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.360371	41.1	9.000	N	11.0	7.6	48.7	Compliance
0.454052	40	9.000	N	10.5	6.8	46.8	Compliance
0.715082	40.7	9.000	N	10.6	5.3	46.0	Compliance
0.768247	42.2	9.000	N	10.5	3.8	46.0	Compliance
0.812315	42.4	9.000	N	10.5	3.6	46.0	Compliance
0.915445	39.2	9.000	N	10.6	6.8	46.0	Compliance

FCC Part 15.247 Page 16 of 48

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

Report No.: RDG150121005-00B

If U_{lab} is less than or equal to U_{cispr} of Table 2, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If U_{lab} is greater than U_{cispr} of Table 2, then:
- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} U_{cispr})$, exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} U_{cispr})$, exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:


30M~200MHz: 5.0 dB 200M~1GHz: 6.2 dB 1G~6GHz: 4.45 dB 6G~18GHz: 5.23 dB

Table 2 – Values of U_{cispr}

Measurement					
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB				
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB				
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB				


EUT Setup

Below 1GHz:



FCC Part 15.247 Page 17 of 48

Above 1GHz:



Report No.: RDG150121005-00B

The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits. The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

TOTAL AND THE PROPERTY OF THE				
Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
Above I GHZ	1MHz	10 Hz	/	Ave.

Test Procedure

During the radiated emission test, the adapter was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

FCC Part 15.247 Page 18 of 48

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Report No.: RDG150121005-00B

Corrected Amplitude = Meter Reading + Antenna Loss + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit –Corrected Amplitude

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2014-05-09	2015-05-09
Sunol Sciences	Antenna	JB3	A060611-3	2014-07-28	2017-07-27
HP	Amplifier	8447E	2434A02181	2014-09-01	2015-09-01
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09
ETS LINDGREN	Horn Antenna	3115	000 527 35	2012-09-06	2015-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2015-02-19	2016-02-19
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09
Ducommun Technolagies	Horn Antenna	ARH-4223-02	1007726-01 1304	2014-06-16	2017-06-15
Quinstar	Amplifier	QLW- 18405536-JO	15964001001	2014-09-06	2015-09-06

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Title 47, Part 15, Section 15.205, 15.209 and 15.247</u>, with the worst margin reading of:

6.20 dB at **2483.5MHz** in the **Vertical** polarization for 802.11 n ht20 Mode

Test Data

Environmental Conditions

Temperature:	21.6°C
Relative Humidity:	58 %
ATM Pressure:	101.4 kPa

^{*} The testing was performed by Dean Liu on 2015-03-13.

Test Mode: Transmitting

FCC Part 15.247 Page 19 of 48

Report No.: RDG150121005-00B

802 11h Mode

802.	802.11b Mode								
	R	eceiver	Rx A	ntenna	Cable	Amplifier	Corrected	T **4	N/
Frequency (MHz)	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)	loss (dB)	Gain (dB)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
			I	ow Chani	nel: 2412	MHz			
2412	66.86	PK	Н	25.67	3.68	0.00	96.21	N/A	N/A
2412	63.28	AV	Н	25.67	3.68	0.00	92.63	N/A	N/A
2412	67.36	PK	V	25.67	3.68	0.00	96.71	N/A	N/A
2412	64.38	AV	V	25.67	3.68	0.00	93.73	N/A	N/A
2390	29.46	PK	V	25.61	3.63	0.00	58.70	74.00	15.30
2390	15.73	AV	V	25.61	3.63	0.00	44.97	54.00	9.03
4824	39.17	PK	V	30.64	5.03	27.41	47.43	74.00	26.57
4824	31.59	AV	V	30.64	5.03	27.41	39.85	54.00	14.15
7236	33.86	PK	V	34.17	6.65	25.90	48.78	74.00	25.22
7236	20.96	AV	V	34.17	6.65	25.90	35.88	54.00	18.12
9648	32.23	PK	V	36.06	8.55	27.46	49.38	74.00	24.62
9648	20.28	AV	V	36.06	8.55	27.46	37.43	54.00	16.57
2335	34.66	PK	V	25.47	3.50	27.31	36.32	74.00	37.68
2335	22.52	AV	V	25.47	3.50	27.31	24.18	54.00	29.82
266.9	33.47	QP	V	13.51	2.00	21.50	27.48	46.00	18.52
			M	iddle Chai					
2437	66.33	PK	Н	25.74	3.75	0.00	95.82	N/A	N/A
2437	63.72	AV	Н	25.74	3.75	0.00	93.21	N/A	N/A
2437	67.05	PK	V	25.74	3.75	0.00	96.54	N/A	N/A
2437	64.2	AV	V	25.74	3.75	0.00	93.69	N/A	N/A
4874	38.93	PK	V	30.77	5.14	27.42	47.42	74.00	26.58
4874	28.68	AV	V	30.77	5.14	27.42	37.17	54.00	16.83
7311	34.04	PK	V	34.35	6.74	25.88	49.25	74.00	24.75
7311	21.24	AV	V	34.35	6.74	25.88	36.45	54.00	17.55
9748	31.98	PK	V	36.30	8.61	27.24	49.65	74.00	24.35
9748	20.23	AV	V	36.30	8.61	27.24	37.90	54.00	16.10
2335	34.52	PK	V	25.47	3.50	27.31	36.18	74.00	37.82
2335	22.37	AV	V	25.47	3.50	27.31	24.03	54.00	29.97
2501	35.24	PK	V	25.90	3.62	27.37	37.39	74.00	36.61
2501	22.29	AV	V	25.90	3.62	27.37	24.44	54.00	29.56
266.9	33.52	QP	V	13.51	2.00	21.50	27.53	46.00	18.47
			Н	ligh Chan					
2462	66.79	PK	Н	25.80	3.75	0.00	96.34	N/A	N/A
2462	62.96	AV	Н	25.80	3.75	0.00	92.51	N/A	N/A
2462	67.36	PK	V	25.80	3.75	0.00	96.91	N/A	N/A
2462	63.86	AV	V	25.80	3.75	0.00	93.41	N/A	N/A
2483.5	27.35	PK	V	25.86	3.67	0.00	56.88	74.00	17.12
2483.5	15.45	AV	V	25.86	3.67	0.00	44.98	54.00	9.02
4924	38.43	PK	V	30.90	5.34	27.43	47.24	74.00	26.76
4924	30.92	AV	V	30.90	5.34	27.43	39.73	54.00	14.27
7386	33.91	PK	V	34.53	6.83	25.86	49.41	74.00	24.59
7386	21.05	AV	V	34.53	6.83	25.86	36.55	54.00	17.45
9848	32.15	PK	V	36.54	8.66	26.94	50.41	74.00	23.59
9848	20.38	AV	V	36.54	8.66	26.94	38.64	54.00	15.36
2335	34.44	PK	V	25.47	3.50	27.31	36.10	74.00	37.90
2335	22.53	AV	V	25.47	3.50	27.31	24.19	54.00	29.81
266.9	33.27	QP	V	13.51	2.00	21.50	27.28	46.00	18.72

FCC Part 15.247 Page 20 of 48

Report No.: RDG150121005-00B

802.11g Mode

п	Re	eceiver	Rx A	Antenna	Cable	Amplifier	Corrected	T,	37
Frequency (MHz)	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)	loss (dB)	Gain (dB)	Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
			I	Low Channe	1: 2412 N	ſНz			
2412	66.73	PK	Н	25.67	3.68	0.00	96.08	N/A	N/A
2412	56.99	AV	Н	25.67	3.68	0.00	86.34	N/A	N/A
2412	68.26	PK	V	25.67	3.68	0.00	97.61	N/A	N/A
2412	57.29	AV	V	25.67	3.68	0.00	86.64	N/A	N/A
2390	28.83	PK	V	25.61	3.63	0.00	58.07	74.00	15.93
2390	16.8	AV	V	25.61	3.63	0.00	46.04	54.00	7.96
4824	40.53	PK	V	30.64	5.03	27.41	48.79	74.00	25.21
4824	26.98	AV	V	30.64	5.03	27.41	35.24	54.00	18.76
7236	33.92	PK	V	34.17	6.65	25.90	48.84	74.00	25.16
7236	21.1	AV	V	34.17	6.65	25.90	36.02	54.00	17.98
9648	31.79	PK	V	36.06	8.55	27.46	48.94	74.00	25.06
9648	20.35	AV	V	36.06	8.55	27.46	37.50	54.00	16.50
2335	34.31	PK	V	25.47	3.50	27.31	35.97	74.00	38.03
2335	22.5	AV	V	25.47	3.50	27.31	24.16	54.00	29.84
266.9	33.83	QP	V	13.51	2.00	21.50	27.84	46.00	18.16
2427	((12	DIZ		iddle Chann			05.62	NT/A	NT/A
2437	66.13	PK	Н	25.74	3.75	0.00	95.62	N/A	N/A
2437 2437	56.42 67.63	AV PK	H V	25.74	3.75	0.00	85.91 97.12	N/A N/A	N/A N/A
	57.69		V	25.74 25.74	3.75	0.00		N/A N/A	
2437 4874	39.85	AV PK	V	30.77	3.75 5.14	0.00 27.42	87.18 48.34	74.00	N/A 25.66
4874	26.52	AV	V	30.77	5.14	27.42	35.01	54.00	18.99
7311	33.97	PK	V	34.35	6.74	25.88	49.18	74.00	24.82
7311	20.82	AV	V	34.35	6.74	25.88	36.03	54.00	17.97
9748	31.55	PK	V	36.30	8.61	27.24	49.22	74.00	24.78
9748	19.98	AV	V	36.30	8.61	27.24	37.65	54.00	16.35
2501	34.18	PK	V	25.90	3.62	27.24	36.33	74.00	37.67
2501	22.4	AV	V	25.90	3.62	27.37	24.55	54.00	29.45
2335	35.4	PK	V	25.47	3.50	27.31	37.06	74.00	36.94
2335	23.29	AV	V	25.47	3.50	27.31	24.95	54.00	29.05
266.9	33.51	QP	V	13.51	2.00	21.50	27.52	46.00	18.48
	22.01			High Channe					
2462	66.77	PK	Н	25.80	3.75	0.00	96.32	N/A	N/A
2462	56.68	AV	Н	25.80	3.75	0.00	86.23	N/A	N/A
2462	67.6	PK	V	25.80	3.75	0.00	97.15	N/A	N/A
2462	58.42	AV	V	25.80	3.75	0.00	87.97	N/A	N/A
2483.5	27.97	PK	V	25.86	3.67	0.00	57.50	74.00	16.50
2483.5	16.64	AV	V	25.86	3.67	0.00	46.17	54.00	7.83
4924	41.51	PK	V	30.90	5.34	27.43	50.32	74.00	23.68
4924	27.8	AV	V	30.90	5.34	27.43	36.61	54.00	17.39
7386	33.85	PK	V	34.53	6.83	25.86	49.35	74.00	24.65
7386	20.99	AV	V	34.53	6.83	25.86	36.49	54.00	17.51
9848	31.57	PK	V	36.54	8.66	26.94	49.83	74.00	24.17
9848	19.97	AV	V	36.54	8.66	26.94	38.23	54.00	15.77
2335	34.24	PK	V	25.47	3.50	27.31	35.90	74.00	38.10
2335	22.33	AV	V	25.47	3.50	27.31	23.99	54.00	30.01
266.9	33.16	QP	V	13.51	2.00	21.50	27.17	46.00	18.83

FCC Part 15.247 Page 21 of 48

802 11 n ht20 Mode

	nt20 Mode	eceiver	Rv A	ntenna	Calda	A 1: C .	Commented		
Frequency (MHz)	Reading (dBµV)	Detector (PK/QP/AV)	Polar	Factor (dB)	Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	(авил)	(PK/QP/AV)	(H/V)	()	` /	()	(dDµ v/III)		
	T			ow Chann			T		
2412	66.1	PK	H	25.67	3.68	0.00	95.45	N/A	N/A
2412	56.35	AV	Н	25.67	3.68	0.00	85.70	N/A	N/A
2412	67.82	PK	V	25.67	3.68	0.00	97.17	N/A	N/A
2412	56.72	AV	V	25.67	3.68	0.00	86.07	N/A	N/A
2390	28.29	PK	V	25.61	3.63	0.00	57.53	74.00	16.47
2390	16.26	AV	V	25.61	3.63	0.00	45.50	54.00	8.50
4824	40.08	PK	V	30.64	5.03	27.41	48.34	74.00	25.66
4824	26.38	AV	V	30.64	5.03	27.41	34.64	54.00	19.36
7236	34.94	PK	V	34.17	6.65	25.90	49.86	74.00	24.14
7236	22.01	AV	V	34.17	6.65	25.90	36.93	54.00	17.07
9648	32.06	PK	V	36.06	8.55	27.46	49.21	74.00	24.79
9648	20.2	AV	V	36.06	8.55	27.46	37.35	54.00	16.65
2274	34.54	PK	V	25.31	3.42	27.30	35.97	74.00	38.03
2274	22.48	AV	V	25.31	3.42	27.30	23.91	54.00	30.09
266.9	33.1	QP	V	13.51	2.00	21.50	27.11	46.00	18.89
				ddle Chan					37/1
2437	66.18	PK	H	25.74	3.75	0.00	95.67	N/A	N/A
2437	56.18	AV	Н	25.74	3.75	0.00	85.67	N/A	N/A
2437	66.98	PK	V	25.74	3.75	0.00	96.47	N/A	N/A
2437	57.76	AV	V	25.74	3.75	0.00	87.25	N/A	N/A
4874	27.36	PK	V	30.77	5.14	27.42	35.85	74.00	38.15
4874	16.16	AV	V	30.77	5.14	27.42	24.65	54.00	29.35
7311	40.86	PK	V	34.35	6.74	25.88	56.07	74.00	17.93
7311	26.31	AV	V	34.35	6.74	25.88	41.52	54.00	12.48
9748	31.93	PK	V	36.30	8.61	27.24	49.60	74.00	24.40
9748	20.46	AV	V	36.30	8.61	27.24	38.13	54.00	15.87
2274	34.36	PK	V	25.31	3.42	27.30	35.79	74.00	38.21
2274	22.58	AV	V	25.31	3.42	27.30	24.01	54.00	29.99
2501	35.32	PK	V	25.90	3.62	27.37	37.47	74.00	36.53
2501	23.51	AV	V	25.90	3.62	27.37	25.66	54.00	28.34
266.9	33.05	QP	V	13.51	2.00	21.50	27.06	46.00	18.94
2462	66.5	DV		igh Chann			06.20	37/4	31/4
2462	66.65	PK	H	25.80	3.75	0.00	96.20	N/A	N/A
2462	56.87	AV	H	25.80	3.75	0.00	86.42	N/A	N/A
2462	67.74	PK	V	25.80	3.75	0.00	97.29	N/A	N/A
2462	57.05	AV	V	25.80	3.75	0.00	86.60	N/A	N/A
2483.5	28.63	PK	V	25.86	3.67	0.00	58.16	74.00	15.84
2483.5	18.27	AV	V	25.86	3.67	0.00	47.80	54.00	6.20
4924	43.27	PK	V	30.90	5.34	27.43	52.08	74.00	21.92
4924	30.19	AV	V	30.90	5.34	27.43	39.00	54.00	15.00
7386	34.18	PK	V	34.53	6.83	25.86	49.68	74.00	24.32
7386	21.4	AV	V	34.53	6.83	25.86	36.90	54.00	17.10
9848	32.1	PK	V	36.54	8.66	26.94	50.36	74.00	23.64
9848	20.54	AV	V	36.54	8.66	26.94	38.80	54.00	15.20
2274	34.79	PK	V	25.31	3.42	27.30	36.22	74.00	37.78
2274	22.68	AV	V	25.31	3.42	27.30	24.11	54.00	29.89
266.9	33.93	QP	V	13.51	2.00	21.50	27.94	46.00	18.06


Report No.: RDG150121005-00B

FCC Part 15.247 Page 22 of 48

Conducted Spurious Emissions at Antenna Port


Report No.: RDG150121005-00B

802.11b Low Channel



Date: 13.MAR.2015 13:11:06


802.11b Middle Channel



Date: 13.MAR.2015 13:16:27


FCC Part 15.247 Page 23 of 48

an) Report No.: RDG150121005-00B



Date: 13.MAR.2015 13:23:23

802.11g Low Channel




Date: 13.MAR.2015 14:50:43

FCC Part 15.247 Page 24 of 48


Report No.: RDG150121005-00B





Date: 13.MAR.2015 14:46:02

802.11g High Channel




Date: 13.MAR.2015 14:41:11

FCC Part 15.247 Page 25 of 48


802.11n ht20 Low Channel

Report No.: RDG150121005-00B



Date: 13.MAR.2015 15:11:04


802.11n ht20 Middle Channel



Date: 13.MAR.2015 15:18:56

FCC Part 15.247 Page 26 of 48

802.11n ht20 High Channel



Date: 13.MAR.2015 15:23:13

FCC Part 15.247 Page 27 of 48

FCC $\S15.247(a)$ (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Report No.: RDG150121005-00B

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r02 clause8.1 Option 1:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times RBW$.
- c) Detector = Peak.
- d) Trace mode = \max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	21.8 °C
Relative Humidity:	57 %
ATM Pressure:	101.4 kPa

The testing was performed by Dean Liu on 2015-03-13.

FCC Part 15.247 Page 28 of 48

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots.


Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	10.24	≥0.5
	Middle	2437	10.24	≥0.5
	High	2462	10.24	≥0.5
802.11g	Low	2412	16.56	≥0.5
	Middle	2437	16.56	≥0.5
	High	2462	16.56	≥0.5
802.11n20	Low	2412	17.76	≥0.5
	Middle	2437	17.76	≥0.5
	High	2462	17.76	≥0.5

Report No.: RDG150121005-00B

FCC Part 15.247 Page 29 of 48


802.11b Low Channel

Report No.: RDG150121005-00B



Date: 13.MAR.2015 13:08:34

802.11b Middle Channel




Date: 13.MAR.2015 13:15:05

FCC Part 15.247 Page 30 of 48


Report No.: RDG150121005-00B

802.11b High Channel



Date: 13.MAR.2015 13:19:08

802.11g Low Channel




Date: 13.MAR.2015 14:49:01

FCC Part 15.247 Page 31 of 48


802.11g Middle Channel

Report No.: RDG150121005-00B



Date: 13.MAR.2015 14:44:07

802.11g High Channel




Date: 13.MAR.2015 14:38:00

FCC Part 15.247 Page 32 of 48


802.11n ht20 Low Channel

Report No.: RDG150121005-00B



Date: 13.MAR.2015 14:56:39

802.11n ht20 Middle Channel




Date: 13.MAR.2015 15:15:02

FCC Part 15.247 Page 33 of 48

Report No.: RDG150121005-00B

802.11n ht20 High Channel



Date: 13.MAR.2015 15:21:37

FCC Part 15.247 Page 34 of 48

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Report No.: RDG150121005-00B

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r02

- 1. Place the EUT on a bench and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
- 3. Add a correction factor to the display.



Test Equipment List and Details

Manufacturer Description		Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Wideband Power Sensor	N1921A	MY54210016	2014-11-03	2015-11-03
Agilent	Wideband Power Sensor	N1921A	MY54170013	2014-11-03	2015-11-03
Agilent	P-Series Power Meter	N1912A	MY5000448	2014-11-03	2015-11-03
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	21.3 °C	
Relative Humidity:	56 %	
ATM Pressure:	101.6 kPa	

The testing was performed by Dean Liu on 2015-03-12

FCC Part 15.247 Page 35 of 48

Test Mode: Transmitting (Wi-Fi)

Test Result: Compliant. Please refer to the following table.

Test mode	Channel	Frequency (MHz)	Max Peak Conducted Output Power (dBm)	Limit (dBm)	Result
802.11b	Low	2412	9.90	30	PASS
	Middle	2437	9.74	30	PASS
	High	2462	9.68	30	PASS
802.11g	Low	2412	14.52	30	PASS
	Middle	2437	14.85	30	PASS
	High	2462	14.75	30	PASS
802.11n20	Low	2412	14.86	30	PASS
	Middle	2437	15.14	30	PASS
	High	2462	15.08	30	PASS

Report No.: RDG150121005-00B

Test mode	Channel	Frequency	Max Conducted Average Output Power	Limit	Result	
		(MHz)	(dBm)	(dBm)		
802.11b	Low	2412	9.53	30	PASS	
	Middle	2437	9.44	30	PASS	
	High	2462	9.63	30	PASS	
802.11g	Low	2412	9.50	30	PASS	
	Middle	2437	9.71	30	PASS	
	High	2462	9.44	30	PASS	
802.11n20	Low	2412	9.79	30	PASS	
	Middle	2437	9.76	30	PASS	
	High	2462	9.72	30	PASS	

FCC Part 15.247 Page 36 of 48

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Report No.: RDG150121005-00B

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	22 °C
Relative Humidity:	59 %
ATM Pressure:	101.4 kPa


The testing was performed by Dean Liu on 2015-03-13

Test mode: Transmitting

FCC Part 15.247 Page 37 of 48


802.11b: Band Edge, Left Side

Report No.: RDG150121005-00B



Date: 13.MAR.2015 13:10:26

802.11b: Band Edge, Right Side




Date: 13.MAR.2015 13:20:59

FCC Part 15.247 Page 38 of 48


802.11g: Band Edge, Left Side

Report No.: RDG150121005-00B



Date: 13.MAR.2015 14:50:13

802.11g: Band Edge, Right Side




Date: 13.MAR.2015 14:39:36

FCC Part 15.247 Page 39 of 48


802.11n ht20 Band Edge, Left Side

Report No.: RDG150121005-00B



Date: 13.MAR.2015 15:09:59

802.11n ht20 Band Edge, Right Side



Date: 13.MAR.2015 15:22:41

FCC Part 15.247 Page 40 of 48

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Report No.: RDG150121005-00B

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r02 clause10.2:

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \le \text{RBW} \le 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 \times RBW$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	22 °C	
Relative Humidity:	59 %	
ATM Pressure:	101.4 kPa	

The testing was performed by Dean Liu on 2015-03-13

FCC Part 15.247 Page 41 of 48

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots


Test mode	Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	Low	2412	-17.07	≤8
	Middle	2437	-16.80	≤8
	High	2462	-17.22	≤8
802.11g	Low	2412	-19.92	≤8
	Middle	2437	-19.79	≤8
	High	2462	-20.01	€8
802.11n20	Low	2412	-20.52	≤8
	Middle	2437	-20.13	≤8
	High	2462	-20.31	≤8

Report No.: RDG150121005-00B

FCC Part 15.247 Page 42 of 48


Power Spectral Density, 802.11b Low Channel

Report No.: RDG150121005-00B



Date: 13.MAR.2015 13:09:03

Power Spectral Density, 802.11b Middle Channel




Date: 13.MAR.2015 13:15:37

FCC Part 15.247 Page 43 of 48


Power Spectral Density, 802.11b High Channel

Report No.: RDG150121005-00B



Date: 13.MAR.2015 13:20:04

Power Spectral Density, 802.11g Low Channel




Date: 13.MAR.2015 14:51:06

FCC Part 15.247 Page 44 of 48


Power Spectral Density, 802.11g Middle Channel

Report No.: RDG150121005-00B



Date: 13.MAR.2015 14:44:50

Power Spectral Density, 802.11g High Channel




Date: 13.MAR.2015 14:38:42

FCC Part 15.247 Page 45 of 48


Power Spectral Density, 802.11n ht20 Low Channel

Report No.: RDG150121005-00B



Date: 13.MAR.2015 15:12:11


Power Spectral Density, 802.11n ht20 Middle Channel



Date: 13.MAR.2015 15:17:57

FCC Part 15.247 Page 46 of 48

Report No.: RDG150121005-00B



Date: 13.MAR.2015 15:21:59

FCC Part 15.247 Page 47 of 48

DECLARATION LETTER

Shenzhen Kaliho Technology Development Limited

19F. Block A, Stars plaza, HuaQiang North Road, FuTian District, ShenZhen, China
Contact Phone: 0755-36886291 Contact Fax: 0755-36886291

Report No.: RDG150121005-00B

Product Similarity Declaration

Date: 2015-03-17

To Whom It May Concern,

We, Shenzhen Kaliho Technology Development Limited, hereby declare that our product Smart phone, Model Number: K918, K928, K938, K948, K958 are electrically identical with the same electromagnetic emissions and electromagnetic compatibility characteristics. Model Number: K928, K938, K948, K958 is electrically identical with the Model Number: K918 that was certified by BACL. Their only difference is the model name.

The rest are the same.

Please contact me if you have any question.

Franti

Signature:

Evan Li

Manager

***** END OF REPORT *****

FCC Part 15.247 Page 48 of 48