

FCC PART 22H, PART 24E
MEASUREMENT AND TEST REPORT

For

Shenzhen Kaliho Technology Development Limited

19F, Block A, Stars Plaza, HuaQiang North Road, FuTian District, Shenzhen, China

FCC ID: 2ADBR-K204

| | |
|---|---------------------------------------|
| Report Type: Original Report | Product Type: Feature Phone |
| Test Engineer: <u>Dean Liu</u> <i>Dean Liu</i> | |
| Report Number: <u>RDG160224007-00C</u> | |
| Report Date: <u>2016-04-19</u> | |
| Reviewed By: <u>Jerry Zhang</u> <i>Jerry Zhang</i> EMC Manager | |
| Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn | |

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

TABLE OF CONTENTS

| | |
|---|-----------|
| GENERAL INFORMATION..... | 4 |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) | 4 |
| OBJECTIVE | 4 |
| RELATED SUBMITTAL(S)/GRANT(S)..... | 4 |
| TEST METHODOLOGY | 4 |
| TEST FACILITY | 5 |
| SYSTEM TEST CONFIGURATION..... | 6 |
| JUSTIFICATION | 6 |
| EQUIPMENT MODIFICATIONS | 6 |
| SUPPORT EQUIPMENT LIST AND DETAILS | 6 |
| CONFIGURATION OF TEST SETUP | 6 |
| BLOCK DIAGRAM OF TEST SETUP | 7 |
| SUMMARY OF TEST RESULTS | 8 |
| FCC §1.1310 & §2.1093- RF EXPOSURE | 9 |
| APPLICABLE STANDARD | 9 |
| TEST RESULT | 9 |
| FCC §2.1047 - MODULATION CHARACTERISTIC | 10 |
| FCC § 2.1046, § 22.913 (A) & § 24.232 (C) - RF OUTPUT POWER..... | 11 |
| APPLICABLE STANDARD | 11 |
| TEST PROCEDURE | 11 |
| TEST EQUIPMENT LIST AND DETAILS..... | 12 |
| TEST DATA | 12 |
| FCC §2.1049, §22.917, §22.905 & §24.238 - OCCUPIED BANDWIDTH | 14 |
| APPLICABLE STANDARD | 14 |
| TEST PROCEDURE | 14 |
| TEST EQUIPMENT LIST AND DETAILS..... | 14 |
| TEST DATA | 15 |
| FCC §2.1051, §22.917(A) & §24.238(A) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS | 17 |
| APPLICABLE STANDARD | 17 |
| TEST PROCEDURE | 17 |
| TEST EQUIPMENT LIST AND DETAILS..... | 17 |
| TEST DATA | 18 |
| FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS | 22 |
| APPLICABLE STANDARD | 22 |
| TEST PROCEDURE | 22 |
| TEST EQUIPMENT LIST AND DETAILS..... | 22 |
| TEST DATA | 23 |
| FCC §22.917(A) & §24.238(A) - BAND EDGES..... | 24 |
| APPLICABLE STANDARD | 24 |
| TEST PROCEDURE | 24 |
| TEST EQUIPMENT LIST AND DETAILS..... | 24 |
| TEST DATA | 25 |

FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY.....28

 APPLICABLE STANDARD28

 TEST PROCEDURE28

 TEST EQUIPMENT LIST AND DETAILS.....29

 TEST DATA29

DECLARATION LETTER31

FINAL

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Shenzhen Kaliho Technology Development Limited*'s product, model number: *AO002(FCC ID:2ADBR-K204)* (the "EUT") in this report was a *Feature Phone*, which was measured approximately: 113.7 mm (L) x 47.8 mm (W) x 12.7 mm (H), rated input voltage: DC3.7V rechargeable Li-ion battery or DC 5V charging from adapter.

Adapter information:

Model: UTC-20

INPUT: AC 110-220V 50/60Hz 0.15A

OUTPUT: DC 5.0V, 500mA

Note: The series product, model AO002 and K204 are electrically identical, the difference them is the model name, we selected AO002 for fully testing, the details was explained in the attached declaration letter.

All measurement and test data in this report was gathered from production sample serial number: 160224007 (Assigned by BACL, Dongguan). The EUT was received on 2016-02-15.

Objective

This report is prepared on behalf of *Shenzhen Kaliho Technology Development Limited* in accordance with: Part 2-Subpart J, Part 22-Subpart H, and Part 24-Subpart E of the Federal Communications Commission's rules.

The objective is to determine compliance with FCC rules for output power, modulation characteristic, occupied bandwidth, spurious emissions at antenna terminal, spurious radiated emission, frequency stability and band edge.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: 2ADBR-K204.

FCC Part 15C DSS submissions with FCC ID: 2ADBR-K204.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

Part 22 Subpart H - Public Mobile Services

Part 24 Subpart E - Personal Communication Services

Applicable Standards: TIA/EIA-603-D-2010.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp.(Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FINAL

SYSTEM TEST CONFIGURATION

Justification

The EUT was configured for testing according to TIA/EIA-603-D-2010.

The test items were performed with the EUT operating at testing mode.


Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

| Manufacturer | Description | Model | Serial Number |
|--------------|--------------------------------------|--------|---------------|
| R&S | Universal Radio Communication Tester | CMU200 | 109 038 |

Configuration of Test Setup



Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

| FCC Rules | Description of Test | Result |
|--|--|----------------|
| §1.1310, §2.1093 | RF Exposure | Compliance |
| §2.1046; § 22.913 (a); § 24.232 (c) | RF Output Power | Compliance |
| § 2.1047 | Modulation Characteristics | Not Applicable |
| § 2.1049; § 22.905 § 22.917; § 24.238 | Occupied Bandwidth | Compliance |
| § 2.1051, § 22.917 (a); § 24.238 (a) | Spurious Emissions at Antenna Terminal | Compliance |
| § 2.1053 § 22.917 (a); § 24.238 (a) | Field Strength of Spurious Radiation | Compliance |
| § 22.917 (a); § 24.238 (a) | Out of band emission, Band Edge | Compliance |
| § 2.1055 § 22.355; § 24.235 | Frequency stability vs. temperature Frequency stability vs. voltage | Compliance |

FCC §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

FCC§1.1310 and §2.1093.

Test Result

Compliant, please refer to the SAR report: RDG160224007-20.

FINAL

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E, there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

FINAL

FCC § 2.1046, § 22.913 (a) & § 24.232 (c) - RF OUTPUT POWER

Applicable Standard

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (C), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications..

According to §24.232 (d) Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

Test Procedure

GSM/GPRS

Function: Menu select > GSM Mobile Station > GSM 850/1900

Press Connection control to choose the different menus

Press RESET > choose all the reset all settings

Connection Press Signal Off to turn off the signal and change settings

Network Support > GSM + GPRS or GSM + EGSM

Main Service > Packet Data

Service selection > Test Mode A – Auto Slot Config. off

MS Signal Press Slot Config Bottom on the right twice to select and change the number of time slots and power setting

> Slot configuration > Uplink/Gamma

> 33 dBm for GPRS 850

> 30 dBm for GPRS 1900

BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel

Frequency Offset > + 0 Hz

Mode > BCCH and TCH

BCCH Level > -85 dBm (May need to adjust if link is not stable)

BCCH Channel > choose desire test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]

Channel Type > Off

P0 > 4 dB

Slot Config > Unchanged (if already set under MS signal)

TCH > choose desired test channel

Hopping > Off

Main Timeslot > 3

Network Coding Scheme > CS4 (GPRS)

Bit Stream > 2E9-1 PSR Bit Stream

AF/RF Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input

Connection Press Signal on to turn on the signal and change settings

Radiated method:

TIA-603-D section 2.2.17

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|----------------|---------------------------|-------------|---------------|------------------|----------------------|
| R&S | EMI Test Receiver | ESCI | 100224 | 2015-08-03 | 2016-08-02 |
| Sunol Sciences | Antenna | JB3 | A060611-3 | 2014-11-06 | 2017-11-05 |
| HP | Amplifier | 8447E | 2434A02181 | 2015-09-01 | 2016-09-01 |
| Agilent | Spectrum Analyzer | E4440A | SG43360054 | 2015-11-23 | 2016-11-22 |
| ETS LINDGREN | Horn Antenna | 3115 | 000 527 35 | 2013-09-06 | 2016-09-06 |
| Mini-Circuit | Amplifier | ZVA-213-S+ | 054201245 | 2016-02-19 | 2017-02-19 |
| Giga | Signal Generator | 1026 | 320408 | 2015-05-09 | 2016-05-09 |
| EMCO | Adjustable Dipole Antenna | 3121C | 9109-753 | N/A | N/A |
| TDK RF | Horn Antenna | HRN-0118 | 130 084 | 2013-09-06 | 2016-09-06 |
| N/A | Coaxial Cable | 14m | N/A | 2015-05-06 | 2016-05-06 |
| N/A | Coaxial Cable | 8m | N/A | 2015-05-06 | 2016-05-06 |
| N/A | Coaxial Cable | 0.1m | N/A | 2015-05-06 | 2016-05-06 |
| E-Microwave | DC Blocking | EMDCB-00036 | 0E01201047 | 2015-05-06 | 2016-05-06 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

| | |
|---------------------------|-----------|
| Temperature: | 24.5 °C |
| Relative Humidity: | 41 % |
| ATM Pressure: | 102.4 kPa |

The testing was performed by Dean Liu on 2016-02-25.

Conducted Output Power**Cellular Band (Part 22H) & PCS Band (Part 24E)**

| Band | Channel No. | Peak Output Power (dBm) | | | | |
|----------|-------------|-------------------------|----------------|----------------|----------------|----------------|
| | | GSM | GPRS 1 TX Slot | GPRS 2 TX Slot | GPRS 3 TX Slot | GPRS 4 TX Slot |
| Cellular | 128 | 32.10 | 32.06 | 30.98 | 29.65 | 28.32 |
| | 190 | 32.00 | 32.03 | 30.90 | 29.63 | 28.28 |
| | 251 | 31.90 | 31.85 | 30.86 | 29.51 | 28.30 |
| PCS | 512 | 29.30 | 29.24 | 28.70 | 27.41 | 26.12 |
| | 661 | 29.50 | 29.53 | 28.89 | 27.56 | 26.25 |
| | 810 | 29.70 | 29.66 | 28.95 | 27.60 | 26.21 |

ERP & EIRP**Part 22H**

| Frequency (MHz) | Polar (H/V) | Receiver Reading (dBμV) | Substituted Method | | | Absolute Level (dBm) | Limit (dBm) | Margin (dB) |
|------------------------|----------------|-------------------------------|------------------------|------------------------------|--------------------|----------------------------|----------------|----------------|
| | | | S.G. Level (dBm) | Antenna Gain (dBd/dBi) | Cable Loss (dB) | | | |
| GSM 850_Middle Channel | | | | | | | | |
| 836.600 | H | 91.00 | 16.1 | 0.0 | 1 | 15.1 | 38.5 | 23.4 |
| 836.600 | V | 102.00 | 30.2 | 0.0 | 1 | 29.2 | 38.5 | 9.3 |

Part 24E

| Frequency (MHz) | Polar (H/V) | Receiver Reading (dBμV) | Substituted Method | | | Absolute Level (dBm) | Limit (dBm) | Margin (dB) |
|-------------------------|----------------|-------------------------------|------------------------|------------------------------|--------------------|----------------------------|----------------|----------------|
| | | | S.G. Level (dBm) | Antenna Gain (dBd/dBi) | Cable Loss (dB) | | | |
| PCS 1900_Middle Channel | | | | | | | | |
| 1880.000 | H | 90.65 | 19.1 | 8.4 | 1.4 | 26.1 | 33.0 | 6.9 |
| 1880.000 | V | 93.16 | 21.7 | 8.4 | 1.4 | 28.7 | 33.0 | 4.3 |

Note:

- 1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
- 2) Absolute Level = SG Level - Cable loss + Antenna Gain
- 3) Margin = Limit-Absolute Level

FCC §2.1049, §22.917, §22.905 & §24.238 - OCCUPIED BANDWIDTH


Applicable Standard

FCC §2.1049, §22.917 and §22.905, §24.238.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The 26 dB & 99% bandwidth was recorded.



Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|--------------------------------------|-------------|---------------|------------------|----------------------|
| R&S | Spectrum Analyzer | FSEM | 831259/019 | 2015-07-28 | 2016-07-27 |
| R&S | Universal Radio Communication Tester | CMU200 | 109 038 | 2015-07-28 | 2016-07-27 |
| N/A | Coaxial Cable | 0.1m | N/A | 2015-05-06 | 2016-05-06 |
| E-Microwave | DC Blocking | EMDCB-00036 | OE01201047 | 2015-05-06 | 2016-05-06 |
| E-Microwave | Attenuator | EMCA10-5RN | OE01203239 | 2015-05-08 | 2016-05-08 |
| Pasternack | RF Coaxial Cable | RF-01 | N/A | 2015-05-06 | 2016-05-06 |
| Pasternack | RF Coaxial Cable | RF-02 | N/A | 2015-05-06 | 2016-05-06 |
| N/A | Two-way Splitter | ODP-1-6-2S | OE0120142 | 2015-05-06 | 2016-05-06 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

| | |
|---------------------------|-----------|
| Temperature: | 24.7 °C |
| Relative Humidity: | 39 % |
| ATM Pressure: | 101.9 kPa |


The testing was performed by Dean Liu on 2016-02-17.

Test Mode: Transmitting


Test Result: Compliant. Please refer to the following table and plots.

| Band | Channel No. | Mode | 99% Occupied Bandwidth | 26 dB Occupied Bandwidth |
|-------------|--------------------|-------------|-------------------------------|---------------------------------|
| | | | kHz | kHz |
| Cellular | 190 | GSM | 238.48 | 314.63 |
| PCS | 661 | PCS | 242.48 | 318.64 |

GMSK 850 Cellular Band



GMSK PCS Band



FCC §2.1051, §22.917(a) & §24.238(a) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standard

FCC §2.1051, §22.917(a) and §24.238(a).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|--------------------------------------|-------------|---------------|------------------|----------------------|
| R&S | Spectrum Analyzer | FSEM | 831259/019 | 2015-07-28 | 2016-07-27 |
| R&S | Universal Radio Communication Tester | CMU200 | 109 038 | 2015-07-28 | 2016-07-27 |
| N/A | Coaxial Cable | 0.1m | N/A | 2015-05-06 | 2016-05-06 |
| E-Microwave | DC Blocking | EMDCB-00036 | 0E01201047 | 2015-05-06 | 2016-05-06 |
| E-Microwave | Attenuator | EMCA10-5RN | 0E01203239 | 2015-05-08 | 2016-05-08 |
| Pasternack | RF Coaxial Cable | RF-01 | N/A | 2015-05-06 | 2016-05-06 |
| Pasternack | RF Coaxial Cable | RF-02 | N/A | 2015-05-06 | 2016-05-06 |
| N/A | Two-way Splitter | ODP-1-6-2S | 0E0120142 | 2015-05-06 | 2016-05-06 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**



| | |
|---------------------------|-----------|
| Temperature: | 24.7°C |
| Relative Humidity: | 39 % |
| ATM Pressure: | 101.9 kPa |

The testing was performed by Dean Liu on 2016-02-17.


Test Mode: Transmitting-Worst case

Please refer to the following plots.


GSM850_Middle Channel



Date: 17.FEB.2016 11:20:26



Fundamental



FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS

Applicable Standard

FCC § 2.1053, §22.917 and § 24.238.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \lg(\text{TXpwr in Watts}/0.001)$ – the absolute level

Spurious attenuation limit in dB = $43 + 10 \log_{10}(\text{power out in Watts})$

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|----------------|---------------------------|------------|---------------|------------------|----------------------|
| R&S | EMI Test Receiver | ESCI | 100224 | 2015-08-03 | 2016-08-02 |
| Sunol Sciences | Antenna | JB3 | A060611-3 | 2014-11-06 | 2017-11-05 |
| HP | Amplifier | 8447E | 2434A02181 | 2015-09-01 | 2016-09-01 |
| Agilent | Spectrum Analyzer | E4440A | SG43360054 | 2015-11-23 | 2016-11-22 |
| ETS-Lindgren | Horn Antenna | 3115 | 9808-5557 | 2015-09-06 | 2018-09-06 |
| Mini-Circuit | Amplifier | ZVA-213-S+ | 054201245 | 2016-02-19 | 2017-02-19 |
| Giga | Signal Generator | 1026 | 320408 | 2015-05-09 | 2016-05-09 |
| EMCO | Adjustable Dipole Antenna | 3121C | 9109-753 | N/A | N/A |
| TDK RF | Horn Antenna | HRN-0118 | 130 084 | 2015-09-06 | 2018-09-06 |
| N/A | Coaxial Cable | 14m | N/A | 2015-05-06 | 2016-05-06 |
| N/A | Coaxial Cable | 8m | N/A | 2015-05-06 | 2016-05-06 |
| N/A | Coaxial Cable | 2m | N/A | 2015-05-06 | 2016-05-06 |
| Mini Circuit | High Pass Filter | VHF-3100+ | 31251 | 2015-05-06 | 2016-05-06 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

| | |
|---------------------------|-----------|
| Temperature: | 26.1°C |
| Relative Humidity: | 49 % |
| ATM Pressure: | 100.3 kPa |

The testing was performed by Dean Liu on 2016-04-15.

EUT Operation Mode: Transmitting

Cellular Band (PART 22H)**30 MHz-10 GHz:**

| Frequency (MHz) | Polar (H/V) | Receiver Reading (dBμV) | Substituted Method | | | Absolute Level (dBm) | Limit (dBm) | Margin (dB) |
|----------------------|----------------|-------------------------------|------------------------|------------------------------|--------------------|----------------------------|----------------|----------------|
| | | | S.G. Level (dBm) | Antenna Gain (dBd/dBi) | Cable Loss (dB) | | | |
| Frequency: 836.6 MHz | | | | | | | | |
| 1673.200 | H | 65.86 | -35.2 | 10.6 | 1.5 | -26.1 | -13.0 | 13.1 |
| 1673.200 | V | 64.58 | -36.8 | 10.6 | 1.5 | -27.7 | -13.0 | 14.7 |
| 2509.800 | H | 61.41 | -36.6 | 13.1 | 2.8 | -26.3 | -13.0 | 13.3 |
| 2509.800 | V | 61.23 | -35.9 | 13.1 | 2.8 | -25.6 | -13.0 | 12.6 |
| 351.200 | H | 30.25 | -71 | 0.0 | 0.6 | -71.6 | -13.0 | 58.6 |
| 351.200 | V | 30.82 | -67.9 | 0.0 | 0.6 | -68.5 | -13.0 | 55.5 |

PCS Band (PART 24E)**30 MHz-20 GHz:**

| Frequency (MHz) | Polar (H/V) | Receiver Reading (dBμV) | Substituted Method | | | Absolute Level (dBm) | Limit (dBm) | Margin (dB) |
|--------------------|----------------|-------------------------------|------------------------|------------------------------|--------------------|----------------------------|----------------|----------------|
| | | | S.G. Level (dBm) | Antenna Gain (dBd/dBi) | Cable Loss (dB) | | | |
| Frequency:1880 MHz | | | | | | | | |
| 3760.000 | H | 55.21 | -39.1 | 13.8 | 2.9 | -28.2 | -13.0 | 15.2 |
| 3760.000 | V | 54.85 | -38.2 | 13.8 | 2.9 | -27.3 | -13.0 | 14.3 |
| 351.200 | H | 30.12 | -71.1 | 0.0 | 0.6 | -71.7 | -13.0 | 58.7 |
| 351.200 | V | 30.66 | -68 | 0.0 | 0.6 | -68.6 | -13.0 | 55.6 |

Note:

- 1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
- 2) Absolute Level = SG Level - Cable loss + Antenna Gain
- 3) Margin = Limit - Absolute Level

FCC §22.917(a) & §24.238(a) - BAND EDGES

Applicable Standard


According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency.



Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|--------------------------------------|-------------|---------------|------------------|----------------------|
| R&S | Spectrum Analyzer | FSEM | 831259/019 | 2015-07-28 | 2016-07-27 |
| R&S | Universal Radio Communication Tester | CMU200 | 109 038 | 2015-07-28 | 2016-07-27 |
| N/A | Coaxial Cable | 0.1m | N/A | 2015-05-06 | 2016-05-06 |
| E-Microwave | DC Blocking | EMDCB-00036 | 0E01201047 | 2015-05-06 | 2016-05-06 |
| E-Microwave | Attenuator(10dB) | EMCA10-5RN | OE01203239 | 2015-05-08 | 2016-05-08 |
| Pasternack | RF Coaxial Cable | RF-01 | N/A | 2015-05-06 | 2016-05-06 |
| Pasternack | RF Coaxial Cable | RF-02 | N/A | 2015-05-06 | 2016-05-06 |
| N/A | Two-way Splitter | ODP-1-6-2S | OE0120142 | 2015-05-06 | 2016-05-06 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).



Test Data**Environmental Conditions**

| | |
|---------------------------|-----------|
| Temperature: | 24.7 °C |
| Relative Humidity: | 39 % |
| ATM Pressure: | 101.9 kPa |


The testing was performed by Dean Liu on 2016-02-17.

Test Mode: Transmitting-Worst case


Test Result: Compliant. Please refer to the following plots.

GSM 850, Left Band Edge**GSM 850, Right Band Edge**

PCS 1900, Left Band Edge



PCS 1900, Right Band Edge



FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY

Applicable Standard

FCC § 2.1055 (a), § 2.1055 (d), §22.355, §24.235

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

| Frequency Range (MHz) | Base, fixed (ppm) | Mobile > 3 watts (ppm) | Mobile ≤ 3 watts (ppm) |
|-----------------------|-------------------|------------------------|------------------------|
| 25 to 50 | 20.0 | 20.0 | 50.0 |
| 50 to 450 | 5.0 | 5.0 | 50.0 |
| 450 to 512 | 2.5 | 5.0 | 5.0 |
| 821 to 896 | 1.5 | 2.5 | 2.5 |
| 928 to 929. | 5.0 | N/A | N/A |
| 929 to 960. | 1.5 | N/A | N/A |
| 2110 to 2220 | 10.0 | N/A | N/A |


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: An external variable DC power supply was connected to the battery terminals of the equipment under test. The voltage was set from 85% to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the battery end point. The output frequency was recorded for each battery voltage.



Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|--------------------------------------|--------|---------------|------------------|----------------------|
| Dongzhixu | High Temperature Test Chamber | DP1000 | 201105083-3 | 2015-09-10 | 2016-09-09 |
| R&S | Universal Radio Communication Tester | CMU200 | 109 038 | 2015-07-28 | 2016-07-27 |
| UNI-T | Multimeter | UT39A | M130199938 | 2015-04-10 | 2016-04-10 |
| Pasternack | RF Coaxial Cable | RF-01 | / | 2015-05-06 | 2016-05-06 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

| | |
|---------------------------|-----------|
| Temperature: | 26.1°C |
| Relative Humidity: | 49 % |
| ATM Pressure: | 100.3 kPa |

The testing was performed by Dean Liu on 2016-04-15.

Cellular Band (Part 22H)

| GMSK, Middle Channel, $f_c = 836.6$ MHz | | | | |
|---|-----------------|-----------------|-----------------|-------|
| Temperature | Voltage | Frequency Error | Frequency Error | Limit |
| °C | V _{DC} | Hz | ppm | ppm |
| -30 | 3.7 | -11 | -0.013 | 2.5 |
| -20 | | -15 | -0.018 | |
| -10 | | -18 | -0.022 | |
| 0 | | -3 | -0.004 | |
| 10 | | -7 | -0.008 | |
| 20 | | -10 | -0.012 | |
| 30 | | -11 | -0.013 | |
| 40 | | -17 | -0.020 | |
| 50 | | -9 | -0.011 | |
| 25 | 3.5 | -12 | -0.014 | 2.5 |
| | 4.2 | -2 | -0.002 | |

PCS Band (Part 24E)

| GMSK, Middle Channel, $f_c = 1880$ MHz | | | | |
|--|-----------------|-----------------|-----------------|--------|
| Temperature | Voltage | Frequency Error | Frequency Error | Result |
| °C | V _{DC} | Hz | ppm | |
| -30 | 3.7 | -23 | -0.012 | Pass |
| -20 | | -17 | -0.009 | |
| -10 | | -28 | -0.015 | |
| 0 | | -30 | -0.016 | |
| 10 | | -19 | -0.010 | |
| 20 | | -14 | -0.007 | |
| 30 | | -13 | -0.007 | |
| 40 | | -25 | -0.013 | |
| 50 | | -27 | -0.014 | |
| 25 | 3.5 | -20 | -0.011 | |
| | 4.2 | -11 | -0.006 | |

DECLARATION LETTER

Shenzhen Kaliho Technology Development Limited
19F. Block A, Stars plaza, HuaQiang North Road, FuTian District, ShenZhen, China
Contact Phone: 0755-36886291 Contact Fax: 0755-36886291

Product Similarity Declaration

Date: 2016-03-25

To:

FEDERAL COMMUNICATIONS COMMISSION

Authorization and Evaluation Division

7435 Oakland Mills Road

Columbia, MD 21046

Dear Sir/Madam,

We, Shenzhen Kaliho Technology Development Limited, hereby declare that our product Feature Phone, Model Number: AO002, K204, FCC ID: 2ADBR-K204 are electrically identical with the same electromagnetic emissions and electromagnetic compatibility characteristics. Model Number: K204 is electrically identical with the Model Number: AO002 that was certified by BACL. Their only difference is the model name.

The rest are the same.

Please contact me if you have any question.

Signature:

Evan Li

Manager

Evan@kaliho.com



***** END OF REPORT *****