




Test Report issued under the responsibility of:

**ITC ENGINEERING SERVICES, INC.**

FCC CFR Title 47 Part 15 Subpart C 15.205, 15.209, 15.247	
Report Reference No. .... :	20140924-01R1 Finger Controller_FCC
Date of Issue .....	December 2, 2014
Total Number of Pages .....	33
Testing Laboratory..... :	ITC Engineering Services, Inc.
Address .....	9959 Calaveras Road, Box 543, Sunol CA 94586
Applicant's Name .....	Osterhout Design Group
Address .....	153 Townsend Street, Suite 570, San Francisco, CA USA 94107
Contact .....	Mr. Brian Donnelly
Phone.....	415-644-4000
Fax.....	415-644-4039
Test Specification Standard..... :	FCC CFR Title 47 Part 15 Subpart C 15.205, 15.209, 15.247
Test Procedure .....	ANSI C63.4:2009, ANSI C63.10:2009 (Test Procedures) & Public Notice DA 00-705:2000
Judgment .....	Complies
Test Item Description..... :	Bluetooth 2.0 Finger Controller for R-6 Glasses
Manufacturer Logo.....	
Manufacturer .....	Osterhout Design Group
Model/Type Reference.....	Wireless Finger Controller
RF Operating Frequency Band.....	2.400 - 2.4835 GHz



ISO/IEC 17025:2005 Accredited Laboratory



## TABLE OF CONTENTS

<b>1</b>	<b>DOCUMENTATION .....</b>	<b>5</b>
1.1	TESTING LOCATION .....	5
1.2	REVISION HISTORY .....	5
1.3	DECLARATION/DISCLAIMER .....	6
1.4	CONDITION OF EUT .....	6
1.5	GENERAL DESCRIPTION OF EUT .....	6
1.6	OPERATIONAL DESCRIPTION OF EUT .....	6
1.7	LIST OF APPLICANT PERIPHERALS/SUPPORTING EQUIPMENT USED DURING TEST .....	6
1.8	GENERAL TEST REMARKS .....	7
1.9	SUMMARY OF TESTS .....	7
1.10	MEASUREMENT UNCERTAINTY .....	8
1.11	TEST SET UP PHOTOS .....	8
<b>2</b>	<b>RADIATED EMISSIONS PER FCC PART 15.209.....</b>	<b>9</b>
2.1	ADMINISTRATIVE AND ENVIRONMENTAL DETAILS .....	9
2.2	TEST EQUIPMENT .....	10
2.3	TEST SET UP PHOTO(S) .....	10
2.4	LIMITS/REQUIREMENTS .....	10
2.5	TEST DESCRIPTION AND PROCEDURE .....	10
2.6	TEST DATA PLOTS .....	11
<b>3</b>	<b>MINIMUM 6 DB BANDWIDTH PER FCC PART 15.247 (A)(2) – BLUETOOTH 2.0 + EDR.....</b>	<b>13</b>
3.1	ADMINISTRATIVE AND ENVIRONMENTAL DETAILS .....	13
3.2	TEST EQUIPMENT .....	13
3.3	TEST SET UP PHOTO(S) .....	13
3.4	LIMITS/REQUIREMENTS .....	13
3.5	TEST DESCRIPTION AND PROCEDURE .....	13
3.6	6DB BANDWIDTH MEASUREMENT PLOTS .....	14
3.7	CARRIER FREQUENCY SEPARATION PLOT .....	15
<b>4</b>	<b>PEAK CONDUCTED OUTPUT POWER PER FCC PART 15.247 (B)(3) – BLUETOOTH 2.0 + EDR .....</b>	<b>15</b>
4.1	ADMINISTRATIVE AND ENVIRONMENTAL DETAILS .....	15
4.2	TEST EQUIPMENT .....	15
4.3	TEST SET UP PHOTO(S) .....	15
4.4	LIMITS/REQUIREMENTS .....	15
4.5	TEST DESCRIPTION AND PROCEDURE .....	16
4.6	TEST DATA TABLES .....	16
4.7	PEAK POWER PLOTS .....	16
<b>5</b>	<b>POWER SPECTRAL DENSITY PER FCC PART 15.247 (D) – BLUETOOTH 2.0 + EDR .....</b>	<b>17</b>
5.1	ADMINISTRATIVE AND ENVIRONMENTAL DETAILS .....	17
5.2	TEST EQUIPMENT .....	17
5.3	TEST SET UP PHOTO(S) .....	17
5.4	LIMITS/REQUIREMENTS .....	17
5.5	TEST DESCRIPTION AND PROCEDURE .....	17
5.6	POWER SPECTRAL DENSITY PLOTS .....	18



<b>6</b>	<b>LOWER/UPPER BAND EDGE PER FCC PART 15 SECTION 15.247 (D) – BLUETOOTH 2.0 + EDR.....</b>	<b>18</b>
6.1	ADMINISTRATIVE AND ENVIRONMENTAL DETAILS .....	18
6.2	TEST EQUIPMENT.....	18
6.3	TEST SET UP PHOTO(S).....	18
6.4	LIMITS/REQUIREMENTS.....	19
6.5	TEST DESCRIPTION AND PROCEDURE .....	19
6.6	TEST PLOTS.....	19
<b>7</b>	<b>OCCUPIED BANDWIDTH PER FCC PART 2 SECTION 2.1049 (H) – BLUETOOTH 2.0 + EDR .....</b>	<b>20</b>
7.1	ADMINISTRATIVE AND ENVIRONMENTAL DETAILS .....	20
7.2	TEST EQUIPMENT.....	20
7.3	TEST SET UP PHOTO(S).....	20
7.4	LIMITS/REQUIREMENTS.....	21
7.5	TEST DESCRIPTION AND PROCEDURE .....	21
7.6	TEST PLOTS.....	21
<b>8</b>	<b>TIME OF OCCUPANCY PER FCC PART 15.247 (A)(1).....</b>	<b>22</b>
8.1	ADMINISTRATIVE AND ENVIRONMENTAL DETAILS .....	22
8.2	TEST EQUIPMENT.....	22
8.3	LIMITS/REQUIREMENTS.....	22
8.4	TEST SET UP PHOTO(S).....	22
8.5	TEST DESCRIPTION .....	22
8.6	TIME OF OCCUPANCY MEASUREMENT PLOTS.....	23
<b>9</b>	<b>SPURIOUS &amp; RESTRICTED BANDS EMISSIONS PER FCC PART 15 SECTIONS 15.209 &amp; 15.205 .....</b>	<b>24</b>
9.1	ADMINISTRATIVE AND ENVIRONMENTAL DETAILS .....	24
9.2	TEST EQUIPMENT.....	24
9.3	TEST SET UP PHOTO(S).....	24
9.4	LIMITS/REQUIREMENTS.....	24
9.5	TEST DESCRIPTION AND PROCEDURE .....	25
9.6	SPURIOUS EMISSIONS PLOTS.....	26
<b>10</b>	<b>GAIN OF TRANSMISSION ANTENNA PER FCC PART 15.247 (B)(4) .....</b>	<b>31</b>
10.1	LIMITS/REQUIREMENTS.....	31
<b>11</b>	<b>APPENDIX .....</b>	<b>32</b>
11.1	EUT TECHNICAL SPECIFICATIONS.....	32
11.2	EUT PHOTOS .....	32

## LIST OF FIGURES

<b>FIGURE 1: CONDUCTED RF TEST SETUP .....</b>	<b>8</b>
<b>FIGURE 2: RE TEST SETUP - ACTIVE LOOP ANTENNA - BICONICAL ANTENNA .....</b>	<b>9</b>
<b>FIGURE 3: RE TEST SETUP – LOG PERIODIC ANTENNA - DRG HORN ANTENNA .....</b>	<b>9</b>
<b>FIGURE 4: RADIATED EMISSIONS – ACTIVE LOOP, HORIZONTAL POLARIZATION .....</b>	<b>11</b>
<b>FIGURE 5: RADIATED EMISSIONS – BICONICAL, HORIZONTAL POLARIZATION .....</b>	<b>11</b>
<b>FIGURE 6: RADIATED EMISSIONS – LOG-PERIODIC, HORIZONTAL POLARIZATION .....</b>	<b>12</b>
<b>FIGURE 7: RADIATED EMISSIONS – DRG HORN, HORIZONTAL POLARIZATION .....</b>	<b>12</b>
<b>FIGURE 8: BLUETOOTH 2.0 + EDR CHANNELS (79).....</b>	<b>14</b>
<b>FIGURE 9: 6DB GFSK BANDWIDTH (CH0 SHOWN, CH20 &amp; 39 SIMILAR) .....</b>	<b>14</b>
<b>FIGURE 10: GFSK CARRIER FREQUENCY SEPARATION 1 MHZ (CH0, 1 &amp; 2).....</b>	<b>15</b>






FIGURE 11: GFSK PEAK POWER (CH0 SHOWN, CH20 & 39 SIMILAR) .....	16
FIGURE 12: GFSK POWER SPECTRAL DENSITY (CH0 SHOWN, CH20 & 39 SIMILAR) .....	18
FIGURE 13: GFSK CH0 LOWER BAND EDGE .....	19
FIGURE 14: GFSK CH39 UPPER BAND EDGE .....	20
FIGURE 15: GFSK OCCUPIED BANDWIDTH (CH0 SHOWN, CH20 & 39 SIMILAR) .....	21
FIGURE 16: TRANSMIT TIME (CH0 SHOWN, CH20 & 39 SIMILAR).....	23
FIGURE 17: TRANSMIT INTERVAL (CH0 SHOWN, CH20 & 39 SIMILAR).....	23
FIGURE 18: DRG HORN, HORIZONTAL POLARIZATION .....	26
FIGURE 19: DRG HORN, HORIZONTAL POLARIZATION .....	26
FIGURE 20: LOG-PERIODIC, HORIZONTAL POLARIZATION .....	27
FIGURE 21: LOG-PERIODIC, VERTICAL POLARIZATION .....	27
FIGURE 22: BICONICAL, HORIZONTAL POLARIZATION .....	28
FIGURE 23: BICONICAL, VERTICAL POLARIZATION .....	28
FIGURE 24: ACTIVE LOOP, HORIZONTAL POLARIZATION .....	29
FIGURE 25: DRG HORN, HORIZONTAL POLARIZATION .....	29
FIGURE 26: DRG HORN, HORIZONTAL POLARIZATION .....	30
FIGURE 27: 15-40 GHZ HORN, HORIZONTAL POLARIZATION .....	30
FIGURE 28: FRONT VIEW .....	32
FIGURE 29: SIDE OBLIQUE VIEW .....	33



## 1 DOCUMENTATION

### 1.1 TESTING LOCATION

<input checked="" type="checkbox"/> ITC Testing Laboratory:	:	ITC Engineering Services, Inc.	
Testing Location/Address	:	9959 Calaveras Road, PO Box 543, Sunol, CA 94586, USA	
Prepared By (Name + Signature)	:	D.E. Waldbeser	
Tested By (Name + Signature)	:	D.E. Waldbeser	
Approved By (Name + Signature)	:	Michael Gbadebo, P.E.	
<input type="checkbox"/> Manufacturer Facility	:		
Testing Location/Address	:		
Tested By (Name + Signature)	:		
Approved By (+ Signature)	:		
<input type="checkbox"/> 3 <sup>rd</sup> Party Test Facility	:		
Testing Location/Address	:		
Tested By (Name + Signature)	:		
Approved By (+ Signature)	:		

### 1.2 REVISION HISTORY

#	Revision Date	Old Report Number	New Report Number	Revision
1	12/2/14	20140924-01 Finger Controller_FCC	20140924-01R1 Finger Controller_FCC	Section 1.9 added test: Time of Occupancy; added Section 8 Time of Occupancy; corrected wording in Test Description and Procedure Sections 2.5, 3.5, 4.5 & 5.5.

**1.3 DECLARATION/DISCLAIMER**

It is the manufacturer's responsibility to assure that additional production units of these models are manufactured with identical electrical and mechanical characteristics. This report is the confidential property of the applicant. As a mutual protection to our applicants, the public, and ourselves, extracts from the test report shall not be reproduced except in full without ITC Engineering Service's written approval. The applicant/manufacturer shall not use this report to claim product endorsement by any US Government agency.

**1.4 CONDITION OF EUT**

Equipment Under Test (EUT) was tested as it was received. The radiated mode tests utilize the EUT internal antenna. For the conducted mode tests, the internal antenna is bypassed and an RF cable is connected from the PCB to the spectrum analyzer. The EUT Bluetooth radio is software controllable by means of a laptop and a USB connection.

**1.5 GENERAL DESCRIPTION OF EUT**

Product	Wireless Finger Controller
Model No.	N/A
Power Supply	Removable rechargeable Lithium Polymer battery
I/O Ports	Battery terminal, custom
Operating Frequency Range	2.400- 2.4835 GHz
<b>Bluetooth 2.0 + EDR</b>	
FCC ID	2ADCMF-1
Modulation Type	GFSK (1 Mbps), $\pi/4$ -DPSK (2 Mbps), 8DPSK (3 Mbps)
Modulation Technology	FHSS, AFH
Transfer Rate	1 – 3 Mbps
Number of Channels	79
Maximum Output Power	0 dBm typ.
<b>Antenna</b>	
Antenna Type	Multilayer Ceramic Chip, Monopole
Antenna Gain, Peak	0.9 dBi (2450 MHz)
Radiation Pattern	Toroidal

**1.6 OPERATIONAL DESCRIPTION OF EUT**

The Wireless Finger Controller is a HID intended to work exclusively with the ODG R-6 Smart Glasses platform to control all functions without physical interaction with the head-mounted eyewear.

**1.7 LIST OF APPLICANT PERIPHERALS/SUPPORTING EQUIPMENT USED DURING TEST**

Description	Manufacturer	Model Name	Serial Number
Laptop	Apple	MacBook Pro	
AC Adapter	Apple		-

**1.8 GENERAL TEST REMARKS**

The EUT was operated under the following conditions during the testing:

<input type="checkbox"/>	Standby	<input type="checkbox"/>	Test Program (H – Pattern)
<input type="checkbox"/>	Test Program (Color Bar)	<input type="checkbox"/>	Test Program (Applicant Specific)
<input type="checkbox"/>	TV/VCR Signal Input	<input type="checkbox"/>	Signal Generator Input
<input type="checkbox"/>	Continuous Audio Tone (1kHz)	<input type="checkbox"/>	Cycled Audio Tone (1kHz)
<input type="checkbox"/>	Printer/Parallel Function	<input type="checkbox"/>	Modem/Serial Function
<input type="checkbox"/>	Serpentine Program with I/O	<input type="checkbox"/>	Serpentine Program without I/O
<input type="checkbox"/>	Practice Operation	<input type="checkbox"/>	Normal Operating Mode
<input type="checkbox"/>	Essential Operation (Functional Safety)	<input type="checkbox"/>	Continuous Unmonitored Operation
<input checked="" type="checkbox"/>	Continuous Monitored Operation	<input type="checkbox"/>	Non-Continuous Operation

The requirements according to the technical regulations are:

<input checked="" type="checkbox"/>	Met	<input type="checkbox"/>	Not Met
-------------------------------------	-----	--------------------------	---------

The Equipment Under Test does:

<input checked="" type="checkbox"/>	Fulfill the general approval requirements	<input type="checkbox"/>	Not fulfill the general approval requirements
-------------------------------------	---	--------------------------	---

**1.9 SUMMARY OF TESTS**

ITC Engineering Services, Inc. as an independent testing laboratory, declares that the equipment specified above was tested to the requirements of:

Section of FCC Title 47 CFR	Test Description	Result
15.209	Radiated Emissions, general	Passed
15.207	Conducted Emissions	Passed
15.247 (a)(2)	6 dB Bandwidth	Passed
15.247 (b)(3)	Peak Conducted Output Power	Passed
15.247 (e)	Power Spectral Density	Passed
15.247 (d)	Band-Edge Measurement	Passed
2.1049 (h)	Occupied Bandwidth	Passed
15.247 (a)(1)	Time of Occupancy	Passed
15.209/.205	Spurious & Restricted Band Emissions	Passed
15.247 (b)(4)	Gain of Transmission Antenna	Passed



## 1.10 MEASUREMENT UNCERTAINTY

The measurement of uncertainty levels were estimated based on calculation in accordance with TR 100-028-1. Using the value  $k = 2$  for expanded uncertainty, this provides a 95% level of confidence.





	Measurement Method	Calculated Uncertainty (dB)
1	RF Power, Conducted	$\pm 1.5$
2	Radiated emission of transmitter (30MHz - 1 GHz ) @ 3m	$\pm 3.2$
3	Radiated emission of transmitter (1 GHz - 24 GHz) @ 3m	$\pm 2.5$

## 1.11 TEST SET UP PHOTOS



**FIGURE 1: Conducted RF Test Setup**



**FIGURE 2: RE Test Setup - Active Loop Antenna****- Biconical Antenna****FIGURE 3: RE Test Setup – Log Periodic Antenna****- DRG Horn Antenna**

## 2 RADIATED EMISSIONS PER FCC PART 15.209

### 2.1 ADMINISTRATIVE AND ENVIRONMENTAL DETAILS

Site Used:	EMC Lab 2A
Test Date:	11/12/14
Test Engineer:	D.E. Waldbeser
Temperature	21°C
Humidity:	48%

## 2.2 TEST EQUIPMENT

Equipment Description	Manufacturer	Model Name	Serial Number	Calibration Due Date	Calibration Interval
EMC Analyzer	Agilent	E7402A	MY45112375	7/31/15	2 yr
Active Loop Antenna	EMCO	6502	1071/1001	10/14/16	2 yr
Bi-Conical Antenna	EMCO	3104	3459	10/14/16	2 yr
Log Periodic Antenna	EMCO	3146	9510-4202	6/16/16	2 yr
DRG Horn Antenna	A.H. Systems	SAS-571	887	10/14/16	2 yr

## 2.3 TEST SET UP PHOTO(S)

Refer to Section 1.11 (Figures 2-3).

## 2.4 LIMITS/REQUIREMENTS

Frequency (MHz)	Field strength Average ( $\mu\text{V/m}$ )	Field strength Average ( $\text{dB}\mu\text{V/m}$ )	Field strength Peak ( $\text{dB}\mu\text{V/m}$ )	Measurement distance (m)	Average Limit @ 3m ( $\text{dB}\mu\text{V/m}$ )	Peak Limit @ 3m ( $\text{dB}\mu\text{V/m}$ )
0.009-0.49	267 – 4.9 <sup>+</sup>	48.5 - 13.8	68.5 – 33.8	300*	88.5 – 53.8	108.5 – 73.8
0.49-1.705	49 – 14.1 <sup>x</sup>	33.8 - 23	53.8 - 43	30*	53.8 - 43	73.8 - 63
1.705-30	30	29.5	49.5	30*	49.5	69.5
30-88	100	40	60	3	-	-
88-216	150	43.5	63.5	3	-	-
216-960	200	46	66	3	-	-
Above 960	500	54	74	3	-	-


<sup>+</sup> 2400/F(kHz)    <sup>x</sup> 24000/F(kHz)

\*Measurement performed at 3m per 47 CFR 15.31 (f)(2) distance scaling factor.


## 2.5 TEST DESCRIPTION AND PROCEDURE

The EUT was placed on a non-conducting table whose surface is 80 cm above the ground plane. The table may be rotated in order to maximize the signal received by the measurement system. RF emissions from 9 kHz to 1 GHz are received by a series of antennas. The active loop, biconical, log-periodic and DRG horn are located 3m away from the EUT. The elevation of the antennas above the ground plane is adjusted (1-4 m) for maximum signal, except for the active loop which is fixed at 1m. Both horizontally and vertically polarized signals are detected and recorded. Data presented below represents worst case signal levels.

## 2.6 TEST DATA PLOTS



**FIGURE 4: Radiated Emissions – Active Loop, Horizontal Polarization**



**FIGURE 5: Radiated Emissions – Biconical, Horizontal Polarization**

**A = ambient**




FIGURE 6: Radiated Emissions – Log-periodic, Horizontal Polarization




FIGURE 7: Radiated Emissions – DRG Horn, Horizontal Polarization

**3 MINIMUM 6 DB BANDWIDTH PER FCC PART 15.247 (A)(2) – BLUETOOTH 2.0 + EDR****3.1 ADMINISTRATIVE AND ENVIRONMENTAL DETAILS**

Site Used:	EMC Lab 2A
Test Date:	11/7/14
Test Engineer:	D.E. Waldbeser
Temperature	21°C
Humidity:	48%

**3.2 TEST EQUIPMENT**

Equipment Description	Manufacturer	Model Name	Serial Number	Calibration Due Date	Calibration Interval
CSA Spectrum Analyzer	Agilent	N1996A	MY45371881	1/17/15	2 yr

**3.3 TEST SET UP PHOTO(S)**

Refer to Section 1.11 (Figure1).

**3.4 LIMITS/REQUIREMENTS**

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

**3.5 TEST DESCRIPTION AND PROCEDURE**

The EUT is connected to the spectrum analyzer by opening the connection to the internal chip antenna and attaching a suitable patch cable. The minimum 6dB bandwidth is determined by measuring the width of the carrier signal between the lowest frequency and the highest frequency of the carrier signal where the level is 6dB below the maximum signal power. The EUT is set to transmit single channel, modulated and maximum controlled power output. The test is performed at or near the low, mid and high channel of the operating band.




FIGURE 8: Bluetooth 2.0 + EDR Channels (79)

### 3.6 6DB BANDWIDTH MEASUREMENT PLOTS





FIGURE 9: 6dB GFSK bandwidth (Ch0 shown, Ch20 &amp; 39 similar)

**3.7 CARRIER FREQUENCY SEPARATION PLOT****FIGURE 10: GFSK Carrier Frequency Separation 1 MHz (Ch0, 1 & 2)****4 PEAK CONDUCTED OUTPUT POWER PER FCC PART 15.247 (B)(3) – BLUETOOTH 2.0 + EDR****4.1 ADMINISTRATIVE AND ENVIRONMENTAL DETAILS**

Site Used:	EMC Lab 2A
Test Date:	10/21/14
Test Engineer:	D.E. Waldbeser
Temperature	23°C
Humidity:	41%

**4.2 TEST EQUIPMENT**

Equipment Description	Manufacturer	Model Name	Serial Number	Calibration Due Date	Calibration Interval
CSA Spectrum Analyzer	Agilent	N1996A	MY45371881	1/17/15	2 yr

**4.3 TEST SET UP PHOTO(S)**

Refer to section 1.11 (Figure 1).

**4.4 LIMITS/REQUIREMENTS**

- (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:
- (3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.



## 4.5 TEST DESCRIPTION AND PROCEDURE


The EUT is connected to the spectrum analyzer by opening the connection to the internal chip antenna and attaching a suitable patch cable. The maximum peak conducted output power was measured at the center peak of the selected channel. Measurements are performed at each of the low, mid and high frequencies in the band.

## 4.6 TEST DATA TABLES

Channel	Freq. (MHz)	MPP (dBm)	CPP (dBm)	Margin = 30 - CPP (dB)	Result
0	2412	-6.8	-6.1	36.1	Passed
20	2442	-6.8	-6.1	36.1	Passed
39	2480	-6.1	-5.4	35.4	Passed

MPP = Measured Peak Power      CPP = Corrected Peak Power = MPP + Cable Loss (0.7 dB)

## 4.7 PEAK POWER PLOTS



**FIGURE 11: GFSK Peak Power (Ch0 shown, Ch20 & 39 similar)**

## 5 POWER SPECTRAL DENSITY PER FCC PART 15.247 (D) – BLUETOOTH 2.0 + EDR

### 5.1 ADMINISTRATIVE AND ENVIRONMENTAL DETAILS

Site Used:	EMC Lab 2A
Test Date:	11/7/14
Test Engineer:	D.E. Waldbeser
Temperature	23°C
Humidity:	41%

### 5.2 TEST EQUIPMENT

Equipment Description	Manufacturer	Model Name	Serial Number	Calibration Due Date	Calibration Interval
CSA Spectrum Analyzer	Agilent	N1996A	MY45371881	1/17/15	2 yr

### 5.3 TEST SET UP PHOTO(S)

Refer to section 1.11 (Figure1).


### 5.4 LIMITS/REQUIREMENTS

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### 5.5 TEST DESCRIPTION AND PROCEDURE

The EUT is connected to the spectrum analyzer by opening the connection to the internal chip antenna and attaching a suitable patch cable. The spectrum analyzer power spectral density measurement function is performed at each of the low, mid and high frequencies in the band.

## 5.6 POWER SPECTRAL DENSITY PLOTS



**FIGURE 12: GFSK Power Spectral Density (Ch0 shown, Ch20 & 39 similar)**  
 $10 \cdot \log(3k) = 34.8$   $-67.8 \text{ dBm/Hz} + 34.8 = -33 \text{ dBm/3kHz} < 8 \text{ dBm/3kHz}$

## 6 LOWER/UPPER BAND EDGE PER FCC PART 15 SECTION 15.247 (D) – BLUETOOTH 2.0 + EDR

### 6.1 ADMINISTRATIVE AND ENVIRONMENTAL DETAILS

Site Used:	EMC Lab 2A
Test Date:	11/7/14
Test Engineer:	D.E. Waldbeser
Temperature	23°C
Humidity:	41%

### 6.2 TEST EQUIPMENT

Equipment Description	Manufacturer	Model Name	Serial Number	Calibration Due Date	Calibration Interval
CSA Spectrum Analyzer	Agilent	N1996A	MY45371881	1/17/15	2 yr

### 6.3 TEST SET UP PHOTO(S)

Refer to section 1.11 (Figure1).

## 6.4 LIMITS/REQUIREMENTS

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

## 6.5 TEST DESCRIPTION AND PROCEDURE

Using the conducted test method, the band edge measurement was made at the peak level of the emission at the band edge (outside of the operating band) relative to the center peak of the operating frequency channel by using marker delta function. The span was set to be wide enough to capture the highest peak level of the operating channel to the band edge.

## 6.6 TEST PLOTS




FIGURE 13: GFSK Ch0 Lower Band Edge




FIGURE 14: GFSK Ch39 Upper Band Edge

## 7 OCCUPIED BANDWIDTH PER FCC PART 2 SECTION 2.1049 (H) – BLUETOOTH 2.0 + EDR

### 7.1 ADMINISTRATIVE AND ENVIRONMENTAL DETAILS

Site Used:	EMC Lab 2A
Test Date:	11/7/14
Test Engineer:	D.E. Waldbeser
Temperature	23°C
Humidity:	41%

### 7.2 TEST EQUIPMENT

Equipment Description	Manufacturer	Model Name	Serial Number	Calibration Due Date	Calibration Interval
CSA Spectrum Analyzer	Agilent	N1996A	MY45371881	1/17/15	2 yr

### 7.3 TEST SET UP PHOTO(S)

Refer to section 1.11 (Figure1).


## 7.4 LIMITS/REQUIREMENTS

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission. Transmitters employing digital modulation techniques—when modulated by an input signal such that its amplitude and symbol rate represent the maximum rated conditions under which the equipment will be operated.

## 7.5 TEST DESCRIPTION AND PROCEDURE

Using the conducted test method, the occupied bandwidth measurement was made utilizing the CSA Analyzer's OBW function. The span was set to be wide enough to capture the entire operating channel.

## 7.6 TEST PLOTS



**FIGURE 15: GFSK Occupied Bandwidth (Ch0 shown, Ch20 & 39 similar)**

**8 TIME OF OCCUPANCY PER FCC PART 15.247 (A)(1)****8.1 ADMINISTRATIVE AND ENVIRONMENTAL DETAILS**

Site Used:	EMC Lab 2A
Test Date:	12/1-2/14
Test Engineer:	D.E. Waldbeser
Temperature	23°C avg.
Humidity:	51% avg.

**8.2 TEST EQUIPMENT**

Equipment Description	Manufacturer	Model Name	Serial Number	Calibration Due Date	Calibration Interval
CSA Spectrum Analyzer	Agilent	N1996A	MY45371881	1/17/15	2 yr

**8.3 LIMITS/REQUIREMENTS**

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

$$0.4s * 79 \text{ ch} = 31.6s \text{ period}$$

**8.4 TEST SET UP PHOTO(S)**

Refer to section 1.11 (Figure1).

**8.5 TEST DESCRIPTION**

The EUT is connected to the spectrum analyzer by opening the connection to the internal chip antenna and attaching a suitable patch cable. The time of occupancy requires two measurements to be performed while the EUT is frequency hopping:

Transmit time – The center frequency is set to the frequency to be measured. The span is set to zero span and the sweep time and trigger delay adjusted to isolate the pulse for marker-delta measurement and recording.

Transmit interval – The sweep time is then adjusted in order to see subsequent transmit pulses. As the maximum sweep time for this analyzer is much less than the 31.6s period, a convenient sample interval is:



$$31.6s / (100/3) = 948ms.$$

Time of occupancy then is:

$$\# \text{ of pulses in the sample interval} \times \text{transmit time} \times (100/3)$$

$$[(100/3) \text{ is the \# of sample intervals in } 31.6s]$$



**8.6 TIME OF OCCUPANCY MEASUREMENT PLOTS****FIGURE 16: Transmit time (Ch0 shown, Ch20 & 39 similar)****FIGURE 17: Transmit interval (Ch0 shown, Ch20 & 39 similar)**

$$3 \times 2.925\text{ms} \times (100/3) = 292.5\text{ms} = 0.293\text{s} < 0.4\text{s}$$

## 9 SPURIOUS & RESTRICTED BANDS EMISSIONS PER FCC PART 15 SECTIONS 15.209 & 15.205

### 9.1 ADMINISTRATIVE AND ENVIRONMENTAL DETAILS

Site Used:	Semi-Anechoic Chamber
Test Date:	11/12/2014
Test Engineer:	D.E. Waldbeser
Temperature	20°C
Humidity:	47%

### 9.2 TEST EQUIPMENT

Equipment Description	Manufacturer	Model Name	Serial Number	Calibration Due Date	Calibration Interval
EMC Analyzer	Agilent	E7405A	US40240257	5/30/15	2 yr
Amplifier	Gigatronics	GT-1040A	1116009	N/A	N/A
Amplifier	Agilent	83051	9025	N/A	N/A
Active Loop Antenna	EMCO	6502	1071/1001	10/14/16	2 yr
Biconical Antenna	EMCO	3104	3459	10/14/16	2 yr
Log-Periodic Antenna	EMCO	3146	9510-4202	6/16/16	2 yr
DRG Horn Antenna	A.H. Systems	SAS-571	887	10/14/16	2 yr
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170267	10/16/16	2 yr

### 9.3 TEST SET UP PHOTO(S)

Refer to section 1.11 (Figures 2-3).

### 9.4 LIMITS/REQUIREMENTS

#### FCC Part 15 section 15.209 Radiated emission limits

Frequency (MHz)	Field strength Average (microvolts/meter)	Field strength Average (dBuV/meter)	Field strength Peak (dBuV/meter)	Measurement distance (meters)
30-88	100	40	60	3
88-216	150	43.5	63.5	3
216-960	200	46	66	3
Above 960	500	54	74	3

**FCC Part 15 section 15.205 Restricted Bands**

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	<b>4.5-5.15</b>
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	<b>7.25-7.75</b>
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	<b>2483.5-2500</b>	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	
13.36-13.41			

**9.5 TEST DESCRIPTION AND PROCEDURE**

For radiated emissions, the EUT was placed 80 cm above the ground plane on a non-conducting table. The transmit and receive configuration of the EUT was controlled by the same means as the conducted tests. Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

## 9.6 SPURIOUS EMISSIONS PLOTS




FIGURE 18: DRG Horn, Horizontal Polarization




FIGURE 19: DRG Horn, Horizontal Polarization





FIGURE 20: Log-Periodic, Horizontal Polarization

FIGURE 21: Log-Periodic, Vertical Polarization  
(USB interface board, not EUT @ 417 MHz)





FIGURE 22: Biconical, Horizontal Polarization

FIGURE 23: Biconical, Vertical Polarization  
(USB interface board, not EUT @ 56 MHz)





FIGURE 24: Active Loop, Horizontal Polarization

FIGURE 25: DRG Horn, Horizontal Polarization  
Blue trace – EUT off, Yellow trace – EUT on







FIGURE 26: DRG Horn, Horizontal Polarization

FIGURE 27: 15-40 GHz Horn, Horizontal Polarization  
Blue trace – EUT off, Yellow trace – EUT on

**10 GAIN OF TRANSMISSION ANTENNA PER FCC PART 15.247 (B)(4)****10.1 LIMITS/REQUIREMENTS**

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi.

The EUT antenna used has a stated peak gain of 0.9 dBi @ 2450 MHz.

**2.4GHz Multilayer Monopole Antenna (for Bluetooth®, W-LAN)**

Date: Sep/01/2011

**AH 212M245001****Shapes**

L= 2.0 ± 0.3 mm  
W= 1.25 ± 0.2 mm  
T= 0.85 ± 0.2 mm

**Feature**

\* Ultra Small  
\* Low Profile

**Actual data**

Efficiency : -1.8dB (66%)  
Peak Gain : 0.9dBi  
Average Gain : -0.9dBi (ZX plane-Vertical polarization)  
@2450MHz





\*on Taiyo Yuden's Evaluation Board  
(52 x 10 mm)

\*Element-GND Distance : 4.0 mm

**Electrical Characteristics**

			2400MHz	2450MHz	2500MHz
Efficiency [dB]			-1.9 (64%)	-1.8 (66%)	-1.7 (68%)
Peak gain [dBi]			0.9	0.9	1.3
Average gain [dB]	XY-plane	TX-H	-4.1	-4.0	-3.9
		TX-V	-9.8	-9.4	-8.7
	YZ-plane	TX-H	-3.0	-3.0	-2.9
		TX-V	-35.7	-35.1	-34.9
	ZX-plane	TX-H	-10.1	-9.8	-9.3
		TX-V	-1.0	-0.9	-0.9

**VSWR****Radiation Pattern**

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.  
TAIYO YUDEN reserves the right to make change to the Date at any time without notice.  
Before making final selection, please check product specification

**TAIYO YUDEN**<http://www.ty-top.com>

## 11 APPENDIX

### 11.1 EUT TECHNICAL SPECIFICATIONS

<b>Manufacturer:</b>	Osterhout Design Group		
<b>General Description:</b>	The Wireless Finger Controller is a HID intended to work exclusively with the ODG R-6 Smart Glasses platform to control all functions without physical interaction with the head-mounted eyewear.		
<b>EUT Name:</b>	Wireless Finger Controller	<b>Model:</b>	WFC
<b>Dimensions:</b>	6cm x 2.3cm x 3.2cm	<b>Serial Number:</b>	None
<b>Operating Frequency:</b>	2.400 GHz- 2.4835 GHz	<b>Power Cord Type:</b>	<input type="checkbox"/> Shielded <input type="checkbox"/> Un-Shielded

### 11.2 EUT PHOTOS



**FIGURE 28: Front View**



**FIGURE 29: Side Oblique View**