




Test Report Issued Under the Responsibility of:

**ITC ENGINEERING SERVICES, INC.**

<b>FCC CFR Title 47 Part E15.407</b>	
<b>Report Reference No.</b> .....	20151015-01R-7 Glasses_DFS
<b>Date of Issue</b> .....	1/15/2016
<b>Total Number of Pages</b> .....	15
<b>Testing Laboratory</b> .....	ITC Engineering Services, Inc.
<b>Address</b> .....	9959 Calaveras Road, Box 543, Sunol CA 94586
<b>Applicant's Name</b> .....	Osterhout Design Group
<b>Address</b> .....	153 Townsend Street, Suite 570, San Francisco, CA USA 94107
<b>Contact</b> .....	Mr. Brian Donnelly
<b>Phone</b> .....	415-644-4000
<b>Fax</b> .....	415-644-4039
<b>Test Specification Standard</b> .....	FCC CFR Title 47 Part 15.407 KDB 905462 D02 UNII DFS Compliance Procedures New Rules v01r02. KDB 789033 D02 General UNII Test Procedures New Rules v01
<b>Test Procedure</b> .....	KDB 905462 D02 UNII DFS Compliance Procedures New Rules v01r02.
<b>Judgment</b> .....	Complies as tested
<b>Test Item Description</b> .....	802.11 b/g/n, Bluetooth 4.1 Smart, 802.11n 5GHz (BW 20MHz), GPS/GLONASS Enabled Augmentation Eyewear
<b>Manufacturer Logo</b> .....	
<b>Manufacturer</b> .....	Osterhout Design Group
<b>Model/Type Reference</b> .....	R-7 Glasses
<b>RF Operating Frequency Bands</b> .....	2.402 - 2.48 GHz, 5.18 - 5.240 GHz, 5.260 - 5.320 GHz, 5.500 - 5.700 GHz, 5.745 - 5.825 GHz (only BW20MHz for 5 GHz wifi)

## Table of Contents




<b>TABLE OF FIGURES.....</b>	<b>6</b>
<b>LIST OF TABLES.....</b>	<b>8</b>
<b>1 DOCUMENTATION.....</b>	<b>4</b>
1.1 Testing Location .....	4
1.2 Declaration/Disclaimer .....	4
1.3 Revision History .....	4
01/14/16 .....	4
Tested Channel Move Time, Close Time and Non Occupancy .....	4
1.4 Condition of EUT .....	4
1.5 General Description of EUT .....	5
1.6 Operational Description of EUT .....	5
1.7 List of Applicant Peripherals/ Supporting Equipment Used During Test .....	5
1.8 General Test Remarks .....	6
1.9 Summary of Tests .....	6
1.10 Measurement Uncertainty .....	6
1.11 Test Setup Photos .....	7
<b>2 NON-OCCUPANCY PER FCC PART 15.407 AND KDB 905462 D02 V01R02 .....</b>	<b>8</b>
2.1 Administrative and Environmental Details .....	8
2.2 Test Equipment .....	8
2.3 Test Set up Photo .....	8
2.4 Limits/Requirements .....	8
2.5 Test Description and Procedure .....	8
2.6 Non-Occupancy Test Data .....	9
2.7 Non-Occupancy Plots .....	10
<b>3 CHANNEL CLOSING TIME PER FCC PART 15.407 AND KDB905462 D02 V01R02 .....</b>	<b>11</b>
3.1 Administrative and Environmental Details .....	11
3.2 Test Equipment .....	11
3.3 Test Set up Photo .....	11
3.4 Limits/Requirements .....	11
3.5 Test Description and Procedure .....	11
3.6 Channel Closing Time Test Data .....	11
3.7 Channel Closing Time Plots .....	12
<b>4 CHANNEL MOVE TIME PER FCC PART 15.407 AND KDB905462 D02 V01R02 .....</b>	<b>13</b>
4.1 Administrative and Environmental Details .....	13
4.2 Test Equipment .....	13
4.3 Test Set up Photo .....	13
4.4 Limits/Requirements .....	13
4.5 Test Description and Procedure .....	13
4.6 Channel Move Time Test Data .....	13
4.7 Channel Move Time Plots .....	14
<b>5 APPENDIX .....</b>	<b>15</b>
5.1 EUT Technical Specification .....	15
5.2 EUT Photos- attached in the submittal documents .....	15

---

## Table of Figures

Figure 1: Conducted Test Setup.....	7
Figure 2: 4 Port Power Splitter Test Setup .....	7
Figure3: Setup for DFS Conducted Measurements where the EUT .....	7
Figure 4: Radar Pulse Type 0.....	9
Figure 5: U-NII-2A Non-Occupancy ( Channel 60 ).....	10
Figure 6: U-NII-2C Non-Occupancy ( Channel 100 ).....	10
Figure 7: U-NII-2A Channel Closing Time(Channel 60 ).....	12
Figure 8: U-NII-2C Channel Closing Time (Channel 100).....	12
Figure 9: U-NII-2A Channel Move Time (Channel 60 ).....	14
Figure 10: U-NII-2C Channel Move Time(Channel 100 ).....	14

**1 DOCUMENTATION****1.1 Testing Location**

<input checked="" type="checkbox"/>	ITC Testing Laboratory:	:	ITC Engineering Services, Inc.	
	Testing Location/Address	:	9959 Calaveras Road, PO Box 543, Sunol, CA 94586, USA	
	Prepared By (Name + Signature)	:	Shane Duncan	
	Tested By (Name + Signature)	:	Michael Gbadebo, PE	
	Approved By (Name + Signature)	:	Michael Gbadebo, PE	
<input type="checkbox"/>	Manufacturer Facility	:		
	Testing Location/Address	:		
	Tested By (Name + Signature)	:		
	Approved By (+ Signature)	:		
<input type="checkbox"/>	3 <sup>rd</sup> Party Test Facility	:		
	Testing Location/Address	:		
	Tested By (Name + Signature)	:		
	Approved By (+ Signature)	:		

**1.2 Declaration/Disclaimer**

It is the manufacturer's responsibility to assure that additional production units of these models are manufactured with identical electrical and mechanical characteristics. This report is the confidential property of the applicant. As a mutual protection to our applicants, the public, and ourselves, extracts from the test report shall not be reproduced except in full without ITC Engineering Service's written approval. The applicant/manufacturer shall not use this report to claim product endorsement by any US Government agency.

**1.3 Revision History**

01/14/16	Tested Channel Move Time, Close Time and Non Occupancy for both U-NII-2A and U-NII-2C pages 8, 11, 13
----------	----------------------------------------------------------------------------------------------------------

**1.4 Condition of EUT**

Equipment Under Test (EUT) was tested as it was received. For the conducted tests, the internal antenna RF cable connector is disconnected from the PCB and a suitable patch cable to the spectrum analyzer is used. The EUT WiFi is software controllable by means of a laptop and a USB connection.

## 1.5 General Description of EUT

Product	R-7 Glasses
Model No.	N/A
Power Supply	Internal rechargeable Lithium Polymer battery, 1300 mAH (2)
I/O Ports	Custom magnetic USB / charging receptacle
Operating Frequency Range	2.402- 2.48 GHz, 5.18- 5.825 GHz
<b>802.11 b/g/n</b>	
FCC ID	2ADCMR7
Modulation Type	CCK, BPSK, QPSK, 16-QAM, 64-QAM
Modulation Technology	b: DSSS; g: DSSS, OFDM; n: OFDM
Transfer Rate	b: 1-11 Mbps, g: 6-54 Mbps, n: 7.2-72.2 Mbps (20 MHz channel)
Number of Channels	11
Maximum Output Power	+20dBm
<b>Bluetooth 4.1 Smart</b>	
FCC ID	2ADCMR7
Modulation Type	GFSK (1 Mbps)
Modulation Technology	FHSS, AFH
Transfer Rate	1 Mbps
Number of Channels	40
Maximum Output Power	0 dBm typ.
<b>802.11n (5 GHz , BW 20 MHz)</b>	
FCC ID	2ADCMR7
Modulation Type	CCK, BPSK, QPSK, 16-QAM, 64-QAM
Modulation Technology	n: OFDM
Transfer Rate	n: 7.2-72.2 Mbps ( BW 20 MHz only)
Number of Channels	45
Maximum Output Power	+11 to +16 dBm typ.
<b>Antenna</b>	
Antenna Type	Chip antenna
Antenna Gain, Peak	1.5
Radiation Pattern	Omni-directional

## 1.6 Operational Description of EUT

The R-7 Smart Glasses offers immersive 3D HD viewing of stored or streaming video content, with stereo audio, in a static setting, or in a head orientation tracking augmented vision mode.

For 5 GHz bands, The EUT operates under 802.11n BW 20 MHz only.

## 1.7 List of Applicant Peripherals/ Supporting Equipment Used During Test

Description	Manufacturer	Model Name	Serial Number
Laptop	Apple	MacBook Pro	N/A*
AC Adapter	Apple	N/A*	N/A*
WiFi Master AP	Juniper	WLA322	N/A

\*N/A- Not Applicable

## 1.8 General Test Remarks

The EUT was operated under the following conditions during the testing:

<input type="checkbox"/>	Standby	<input type="checkbox"/>	Test Program (H – Pattern)
<input type="checkbox"/>	Test Program (Color Bar)	<input type="checkbox"/>	Test Program (Applicant Specific)
<input type="checkbox"/>	TV/VCR Signal Input	<input type="checkbox"/>	Signal Generator Input
<input type="checkbox"/>	Continuous Audio Tone (1kHz)	<input type="checkbox"/>	Cycled Audio Tone (1kHz)
<input type="checkbox"/>	Printer/Parallel Function	<input type="checkbox"/>	Modem/Serial Function
<input type="checkbox"/>	Serpentine Program with I/O	<input type="checkbox"/>	Serpentine Program without I/O
<input type="checkbox"/>	Practice Operation	<input type="checkbox"/>	Normal Operating Mode
<input type="checkbox"/>	Essential Operation (Functional Safety)	<input type="checkbox"/>	Continuous Unmonitored Operation
<input checked="" type="checkbox"/>	Continuous Monitored Operation	<input type="checkbox"/>	Non-Continuous Operation

The requirements according to the technical regulations are:

<input checked="" type="checkbox"/>	Met	<input type="checkbox"/>	Not Met
-------------------------------------	-----	--------------------------	---------

The Equipment Under Test does:

<input checked="" type="checkbox"/>	Fulfill the general approval requirements	<input type="checkbox"/>	Not fulfill the general approval requirements
-------------------------------------	-------------------------------------------	--------------------------	-----------------------------------------------

## 1.9 Summary of Tests

ITC Engineering Services, Inc. as an independent testing laboratory, declares that the equipment specified above was tested to the requirements of:

Section of FCC Title 47 CFR	Test Description	Result
15.407 and KDB 905462 D02 v01r02	Non-Occupancy	Passed
15.407 and KDB 905462 D02 v01r02	Channel Move Time	Passed
15.407 and KDB 905462 D02 v01r02	Channel Close Time	Passed

**Note :** This EUT is a client device without radar detection capability.  
This EUT operates under 802.11n BW 20MHz mode only.

## 1.10 Measurement Uncertainty

The measurement of uncertainty levels were estimated based on calculation in accordance with TR 100-028-1. Using the value  $k = 2$  for expanded uncertainty, this provides a 95% level of confidence.

	Measurement Method	Calculated Uncertainty (dB)
1	RF Conducted	$\pm 1.5$

## 1.11 Test Setup Photos





Figure 1: Conducted Test Setup



Figure 2: 4 Port Power Splitter Test Setup



## 2 Non-Occupancy Per FCC Part 15.407 and KDB 905462 D02 v01r02

### 2.1 Administrative and Environmental Details

Site Used:	EMC LAB 2A
Test Date:	12/5/15, 1/13/16
Test Engineer:	Michael Gbadebo
Temperature	20°C
Humidity:	47%

### 2.2 Test Equipment

Equipment Description	Mfg.	Model #	Serial #	Cal. Due Date	Cal. Interval
EMC Analyzer	Agilent	E7402A	MY45112375	7/16/16	2 yr
Vector Signal Generator	Agilent	E4438C	MY47271103	10/12/17	2 yr
Spectrum Analyzer	Rhode & Schwarz	FSU 20Hz-8Ghz	200235	9/25/16	1 yr
4 port power splitter	Mini-circuits	ZB-3PD-63-S+	SF273901542	NA*	NA
Desktop PC	HP	PJ518AAR	CNY44003QK	NA*	NA
Mouse	Microsoft	Optical USB	X802382	NA*	NA
10dB attenuator	Weinschel Corp	3330-10	B9029	NA*	NA

\*NA- Not Applicable

### 2.3 Test Set up Photo

Refer to Figures 1,2,3.

### 2.4 Limits/Requirements

EUT as a client device is monitored for more than 30 minutes following the channel close/move time to verify no transmissions resume on this Channel.


### 2.5 Test Description and Procedure

The EUT is a client device without radar detection capability. The master access point allowed the client to operate at 5.3 and 5.5 GHz. The master was connected to a 4 port power splitter with the client (R-7 EUT), as long as the vector signal generator(radar waveforms), and the spectrum analyzer. A 10dB attenuator was connected to the glasses. The analyzer was set to zero-span in order to monitor the EUT for DFS testing after injecting type 0 radar bursts into the master device.



## Pulse Radar Test Waveforms

Radar Type	Pulse Width( $\mu$ sec)	PRI ( $\mu$ sec)	Number of Pulses
0	1	1428	18



Date: 5.DEC.2015 20:00:01

Figure 4: Radar Pulse Type 0

## 2.6 Non-Occupancy Test Data

U-NII-2A Non-Occupancy Measurement	Requirement Value	Result
>30 minutes	> 30 minutes	Pass

U-NII-2C Non-Occupancy Measurement	Requirement Value	Result
>30 minutes	> 30 minutes	Pass

## 2.7 Non-Occupancy Plots




Figure 5: U-NII-2A Non-Occupancy ( Channel 60 )




Figure 6: U-NII-2C Non-Occupancy ( Channel 100 )

### 3 Channel Closing Time Per FCC part 15.407 and KDB905462 D02 v01r02

#### 3.1 Administrative and Environmental Details

Site Used:	EMC LAB 2A
Test Date:	12/5/15, 1/13/16
Test Engineer:	Michael Gbadebo
Temperature	20°C
Humidity:	47%

#### 3.2 Test Equipment

Equipment Description	Mfg.	Model #	Serial #	Cal. Due Date	Cal. Interval
EMC Analyzer	Agilent	E7402A	MY45112375	7/16/16	2 yr
Vector Signal Generator	Agilent	E4438C	MY47271103	10/12/17	2 yr
Spectrum Analyzer	Rhode & Schwarz	FSU 20Hz-8Ghz	200235	9/25/16	1 yr
4 port power splitter	Mini-circuits	ZB-3PD-63-S+	SF273901542	NA*	NA
Desktop PC	HP	PJ518AAR	CNY44003QK	NA*	NA
Mouse	Microsoft	Optical USB	X802382	NA*	NA
10dB attenuator	Weinschel Corp	3330-10	B9029	NA*	NA

\*NA- Not Applicable

#### 3.3 Test Set up Photo

Refer to Figures 1,2,3.

#### 3.4 Limits/Requirements

After Master AP is injected with a radar signal, EUT as a client must stop operating on that channel within 260 ms , the measurement timing begins at the end of the Radar Type 0 burst.

#### 3.5 Test Description and Procedure

A Type Oradar signal was injected into the Master associated with the EUT.The test system was set-up to capture all transmission data for EUT events. The test equipment time stamps all captured events with respect to T1 (zero time indicating the start of the measurements sequence) followed by the radar type 0 burst period.

Radar Type 0 burst period: 25.704 ms

Channel Closing Transmission Time starts immediately after the last radar pulse is injected.

The EUT needs to demonstrate closing transmissions on the channel once a DFS radar pulse is injected into the Master AP.

#### 3.6 Channel Closing Time Test Data

U-NII-2A Channel Closing Time Measurement	Requirement Value	Result
20ms	<260 ms	Pass

U-NII-2C Channel Closing Time Measurement	Requirement Value	Result
40ms	<260 ms	Pass

Note : After the Type 0 radar burst was injected into the Master, the EUT as a client shut down .

### 3.7 Channel Closing Time Plots




Figure 7: U-NII-2A Channel Closing Time(Channel 60 )




Figure 8: U-NII-2C Channel Closing Time  
(Channel 100 Shown)

#### 4 Channel Move Time Per FCC part 15.407 and KDB905462 D02 v01r02

##### 4.1 Administrative and Environmental Details

Site Used:	EMC LAB 2A
Test Date:	12/5/15, 1/13/16
Test Engineer:	Michael Gbadebo
Temperature	20°C
Humidity:	47%

##### 4.2 Test Equipment

Equipment Description	Mfg.	Model #	Serial #	Cal. Due Date	Cal. Interval
EMC Analyzer	Agilent	E7402A	MY45112375	7/16/16	2 yr
Vector Signal Generator	Agilent	E4438C	MY47271103	10/12/17	2 yr
Spectrum Analyzer	Rhode & Schwarz	FSU 20Hz-8Ghz	200235	9/25/16	1 yr
4 port power splitter	Mini-circuits	ZB-3PD-63-S+	SF273901542	NA*	NA
Desktop PC	HP	PJ518AAR	CNY44003QK	NA*	NA
Mouse	Microsoft	Optical USB	X802382	NA*	NA
10dB attenuator	Weinschel Corp	3330-10	B9029	NA*	NA

\*NA- Not Applicable

##### 4.3 Test Set up Photo

Refer to Figures 1,2,3.

##### 4.4 Limits/Requirements

After Master AP is injected to a radar signal, EUT as a client must move channel or shut down within 10 seconds , measurement timing begins at the end of the Radar Type 0 burst.

##### 4.5 Test Description and Procedure

A Type 0 radar signal was injected to the Master associated with the EUT. The test system was set-up to capture all transmission and beacon for EUT events. The test equipment time stamps all captured events with respect to T1 (zero time indicating the start of the measurements sequence) at the end of the radar type 0 burst , and a 10 second period was monitored.

Radar Type 0 burst period: 25.704 ms.

##### 4.6 Channel Move Time Test Data

U-NII-2A Channel Move Time Measurement	Requirement Value	Result
75 ms	< 10 s	Pass

U-NII-2C Channel Move Time Measurement	Requirement Value	Result
48.1 ms	< 10 s	Pass

Note : After the Type 0 radar burst was injected into the Master, this EUT as a client shut down .

## 4.7 Channel Move Time Plots





Figure 9: U-NII-2A Channel Move Time(Channel 60 )



Date: 5.DEC.2015 19:45:08

Figure 10: U-NII-2C Channel Move Time(Channel 100 )

## 5 APPENDIX

### 5.1 EUT Technical Specification

<b>Manufacturer:</b>	Osterhout Design Group		
<b>General Description:</b>	The R-7 Smart Glasses offers immersive 3D HD viewing of stored or streaming video content, with stereo audio, in a static setting, or in a head orientation tracking augmented vision mode.		
<b>EUT Name:</b>	Smart Glasses	<b>Model:</b>	R-7
<b>Dimensions:</b>	19cm x 14cm x 4.5cm	<b>Serial Number:</b>	R7-P12
<b>Operating Frequency:</b>	2.402 - 2.48 GHz, 5.18 - 5.240 GHz, 5.260 - 5.320 GHz, 5.500 - 5.700 GHz, 5.745 - 5.825 GHz (only 802.11n 20 MHz BW for 5 GHz wifi)	<b>Power Cord Type:</b>	<input type="checkbox"/> Shielded <input checked="" type="checkbox"/> Shielded Un-

### 5.2 EUT Photos- attached in the submittal documents