



FCC Radio Test Report

FCC ID: 2ADD4-CR10iNG

FCC 47 CFR Part 15 Subpart C

Product : NETWORK SECURITY EQUIPMENTR

Trade Name : CYBEROAM

Model Number : CR10iNG

Issued for

Cyberoam Technologies Pvt Ltd

CYBEROAM HOUSE, Sai Gulshan Complex, Beside White House, Gulbai Tekra
Road, Gulbai Tekra Road, Ahmedabad, India

Issued by

Shenzhen STONE Testing Technology Co., Ltd.

F/6, Bldg.12, Zhongxing Industrial City, Chuangye Rd.,
Nanshan District, Shenzhen, Guangdong, China

Tel.: +86-0755-26582862 Fax.: +86-0755-61673854

Website: www.stt-lab.org

*Note: This report shall not be reproduced except in full, without the written approval of Shenzhen STONE Testing Technology Co., Ltd.. This document may be altered or revised by Shenzhen STONE Testing Technology Co., Ltd. personnel only, and shall be noted in the revision section of the document.
The test results in the report only apply to the tested sample.*

**TEST RESULT CERTIFICATION**

Product : NETWORK SECURITY EQUIPMENTR
Applicant..... : Cyberoam Technologies Pvt Ltd
Address : CYBEROAM HOUSE,Sai Gulshan Complex,Beside White
House,Gulbai Tekra Road,Gulbai Tekra Road, Ahmedabad, India
Manufacturer..... : HAXUN TECHNOLOGY CO.,LTD
Address : A702 Huangjia Commercial Plaza, Minzhi Avenue, Longhua
Town, BaoAn District, Shenzhen, Guangdong, 518131, China
Model No. : CR10iNG
Standards : FCC Part 15 Subpart C (15.247)
Test Method..... : ANSI C63.4: 2003
KDB 558074 D01 v03r02 and KDB 662911 D01v02r01

The above equipment has been tested by Shenzhen STONE Testing Technology Co., Ltd. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Test..... :

Date of receipt of test item 2014-09-22

Date(s) of performance of test 2014-09-22 to 2014-10-15

Test Result..... : Pass

Testing by	:	<u>Linna Liu</u>	Date	:	<u>2014-10-15</u>
		(Linna Liu)			
Check by	:	<u>Andy Huang</u>	Date	:	<u>2014-10-16</u>
		(Andy Huang)			
Approved by	:	<u>Ethan Chen</u>	Date	:	<u>2014-10-17</u>
		(Ethan Chen)			



Table of Contents	Page
1 . TEST SUMMARY	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	9
2.3 DESCRIPTION OF TEST SETUP	10
2.4 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL	11
2.5 EUT Exercise Software	11
3 . CONDUCTED EMISSION TEST	12
3.1 CONDUCTED EMISSION MEASUREMENT (Frequency Range 150KHz-30MHz)	12
3.2 TEST PROCEDURE	12
3.3 TEST SETUP	13
3.4 TEST INSTRUMENTS	13
3.5 EUT OPERATING CONDITIONS	13
3.6 TEST RESULTS	14
4 . RADIATED EMISSION MEASUREMENT	16
4.1 RADIATED EMISSION LIMIT (Frequency Range 9KHz-1000MHz)	16
4.2 TEST PROCEDURE	16
4.3 TEST SETUP	17
4.4 TEST INSTRUMENTS	18
4.5 EUT OPERATING CONDITIONS	18
4.6 TEST RESULTS	19
5 . MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT	47
5.1 LIMITS	47
5.2 TEST PROCEDURE	47
5.3 TEST SETUP	47
5.4 TEST INSTRUMENTS	47
5.5 EUT OPERATING CONDITIONS	47
5.6 TEST RESULTS	47
6 . OCCUPIED BANDWIDTH MEASUREMENT	49
6.1 LIMITS	49



Table of Contents	Page
6.2 TEST PROCEDURE	49
6.3 TEST SETUP	49
6.4 TEST INSTRUMENTS	49
6.5 EUT OPERATING CONDITIONS	49
6.6 TEST RESULTS	49
7 . POWER SPECTRAL DENSITY	58
7.1 LIMITS	58
7.2 TEST PROCEDURE	58
7.3 TEST SETUP	58
7.4 TEST INSTRUMENTS	58
7.5 EUT OPERATING CONDITIONS	58
7.6 TEST RESULTS	58
8 . ANTENNA CONDUCTED SPURIOUS EMISSION	71
8.1 LIMITS	71
8.2 TEST PROCEDURE	71
8.3 TEST SETUP	71
8.4 TEST INSTRUMENTS	71
8.5 EUT OPERATING CONDITIONS	71
8.6 TEST RESULTS	71
9 . ANTENNA REQUIREMENT	88
9.1 REQUIREMENT	88
9.2 ANTENNA CONNECTOR CONSTRUCTION	88



1. TEST SUMMARY

Test procedures according to the technical standards:

FCC Part 15 Subpart C (15.247)			
Standard Section	Test Item	Judgment	Remark
15.207	AC Power Conducted Emission	PASS	
15.247(d)	Antenna Conducted Spurious Emissions	PASS	
15.247(b)(3)	Output Power	PASS	
15.247(a)(2)	6dB RF Bandwidth	PASS	
15.247(e)	Power Spectral Density	PASS	
15.209/15.205	Transmitter Radiated Emissions	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

(2) The test results of this report relate only to the tested sample(s) identified in this report.



1.1 TEST FACILITY

Shenzhen STONE Testing Technology Co., Ltd.

Add. : F/6, Bldg.12, Zhongxing Industrial City, Chuangye Rd., Nanshan District, Shenzhen, Guangdong, China

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

FCC Registration No.: 323508

IC Registration No.: 11043A

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

A. Conducted Emission :

The measurement uncertainty is evaluated as ± 3.2 dB.

B. Radiated Measurement :

The measurement uncertainty is evaluated as ± 3.7 dB.



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	NETWORK SECURITY EQUIPMENT R
Model Name	CR10ING
Additional Model Number(s)	N/A
Model Difference	N/A
Frequency Range	2400~2483.5 MHz
Modulation Type	802.11b: DSSS 802.11g: OFDM 802.11n: OFDM
Data Rate	802.11b: 1/2/5.5/11 Mbps 802.11g: 6/9/12/18/24/36/48/54 Mbps 802.11n: 450 Mbps
RF Output Power	802.11b: 16.54 dBm 802.11g: 15.18 dBm 802.11n(HT20): 16.86 dBm 802.11n(HT40): 16.79 dBm
Antenna Type	Dipole Antenna (Max. Gain: 2 dBi)
Power Source	AC power by AC system.
Power Rating	AC/DC Adapter: Input: AC 120~240V 50/60 Hz Output: DC12V, 4A, 48W
Remark	More details EUT technical specifications, please refer to the User's Manual.

Note:

- (1) This Test Report is FCC Part 15 Subpart C, 15.247 for IEEE 802.11b/g/n. And the Test procedure follows the FCC KDB 558075 D01 DTS Meas Guidance V03R02.
- (2) Transmitting mode with antennas

Mode	TX Antenna (s)
802.11b	1
802.11g	1
802.11n(HT20)	2
802.11n(HT40)	2



(3) Channel List.

2.4 GHz Band				
Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz		
For 802.11b/g/n(HT20), use channel 1~11				
For 802.11n(HT40), use channel 3~9				



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	WiFi TX Mode
Mode 2	WiFi TX 802.11b Mode
Mode 3	WiFi TX 802.11g Mode
Mode 4	WiFi TX 802.11n(HT20)Mode
Mode 5	WiFi TX 802.11n(HT40) Mode

For Conducted Test	
Final Test Mode	Description
Mode 2	WiFi TX Mode


For Radiated Test	
Final Test Mode	Description
Mode 1	WiFi TX Mode
Mode 2	WiFi TX 802.11b Mode
Mode 3	WiFi TX 802.11g Mode
Mode 4	WiFi TX 802.11n(HT20)Mode
Mode 5	WiFi TX 802.11n(HT40) Mode

Note:

- (1) Software used to control the EUT for staying in continuous transmitting mode was programmed. After verification, all tests were carried out with the worst case test modes as shown below.
- (2) IEEE 802.11b Mode:
Channel (2412/2437/2462 MHz) with 1Mbps data rate were chosen for full testing.
- (3) IEEE 802.11g Mode:
Channel (2412/2437/2462 MHz) with 6 Mbps data rate were chosen for full testing.
- (4) IEEE 802.11n(HT20) Mode:
Channel (2412/2437/2462 MHz) with MCS 0 data rate were chosen for full testing.
- (5) IEEE 802.11n(HT40) Mode:
Channel (2422/2437/2452 MHz) with MCS 0 data rate were chosen for full testing.
- (6) By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "X axis" position was the worst, then the final test was executed the worst condition and test data were recorded in this report.
- (7) By preliminary testing and verifying the EUT Antenna positioned horizontal and vertical. And found the worst condition is the antenna positioned vertical.


2.3 DESCRIPTION OF TEST SETUP

Conducted Emission



Radiated Emission

USB Charging and Loading Data





2.4 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	NETWORK SECURITY EQUIPMENT	/	CR10iNG	N/A	EUT
E-2	Notebook	N/A	8.3R	N/A	
E-3	Printer	HP	5015N	N/A	
E-4	Flash Disk	Kinston	2GB	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	0.5m	USB Cable
C-2	YES	NO	1.5m	USB Cable

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” means “shielded” “with core”; “NO” means “unshielded” “without core”.

2.5 EUT Exercise Software

Power Parameters for Testing			
Test Software Version	Atheros Radio Test 2 (ART2-GUI).exe		
Mode	Frequency/ Parameters		
802.11b	2412 MHz	2437 MHz	2462 MHz
	17	17	17
802.11g	2412 MHz	2437 MHz	2462 MHz
	16	16	16
802.11n(HT20)	2412 MHz	2437 MHz	2462 MHz
	15	15	15
802.11n(HT40)	2422 MHz	2437 MHz	2452 MHz
	15	15	15



3. CONDUCTED EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Quasi-peak	Average
	dBuV	dBuV
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.4 TEST INSTRUMENTS

Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
LISN	R&S	NSLK81	8126466	Jul. 06, 2014	Jul. 05. 2015	1 year
LISN	R&S	NSLK81	8126487	Dec. 25, 2013	Dec. 24, 2014	1 year
50Ω Switch	ANRITSU CORP	MP59B	6200983704	Jul. 06, 2014	Jul. 05. 2015	1 year
Test Cable	N/A	C01	N/A	Jul. 06, 2014	Jul. 05. 2015	1 year
Test Cable	N/A	C02	N/A	Jul. 06, 2014	Jul. 05. 2015	1 year
Test Cable	N/A	C03	N/A	Jul. 06, 2014	Jul. 05. 2015	1 year
EMI Test Receiver	R&S	ESCI	1166.595	Jul. 06, 2014	Jul. 05. 2015	1 year
Passive Voltage Probe	ESH2-Z3	R&S	100196	Jul. 06, 2014	Jul. 05. 2015	1 year

3.5 EUT OPERATING CONDITIONS


The EUT tested system was configured as the statements of **2.3** Unless otherwise a special operating condition is specified in the follows during the testing.



3.6 TEST RESULTS

EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10iNG
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-09-30
Test Mode :	Mode 1	Phase :	Line
Test Voltage :	120V/ 60Hz		


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1548	39.25	10.12	49.37	65.74	-16.37	QP	
2		0.1548	23.98	10.12	34.10	55.74	-21.64	AVG	
3		0.1980	37.15	10.12	47.27	63.69	-16.42	QP	
4		0.1980	23.92	10.12	34.04	53.69	-19.65	AVG	
5		0.6740	35.44	10.02	45.46	56.00	-10.54	QP	
6	*	0.6740	28.60	10.02	38.62	46.00	-7.38	AVG	
7		3.5860	29.93	10.06	39.99	56.00	-16.01	QP	
8		3.5860	24.18	10.06	34.24	46.00	-11.76	AVG	
9		6.8100	37.55	10.06	47.61	60.00	-12.39	QP	
10		6.8100	31.21	10.06	41.27	50.00	-8.73	AVG	
11		25.7060	34.08	10.07	44.15	60.00	-15.85	QP	
12		25.7060	28.94	10.07	39.01	50.00	-10.99	AVG	





EUT :	NETWORK SECURITY EQUIPMENT	Model Name. :	CR10iNG
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-09-30
Test Mode :	Mode 1	Phase :	Neutral
Test Voltage :	120V/ 60Hz		

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
		MHz	Level	Factor	ment			Detector	Comment
			dBuV	dB	dBuV	dBuV	dB		
1		0.1540	0.86	10.12	10.98	65.78	-54.80	QP	
2		0.1540	-3.62	10.12	6.50	55.78	-49.28	AVG	
3		0.2220	36.19	10.11	46.30	62.74	-16.44	QP	
4		0.2220	8.66	10.11	18.77	52.74	-33.97	AVG	
5		0.6380	34.11	10.02	44.13	56.00	-11.87	QP	
6		0.6380	26.34	10.02	36.36	46.00	-9.64	AVG	
7		3.4500	26.20	10.06	36.26	56.00	-19.74	QP	
8		3.4500	19.36	10.06	29.42	46.00	-16.58	AVG	
9		7.2260	36.79	10.07	46.86	60.00	-13.14	QP	
10	*	7.2260	30.68	10.07	40.75	50.00	-9.25	AVG	
11		25.8340	32.17	10.08	42.25	60.00	-17.75	QP	
12		25.8340	26.89	10.08	36.97	50.00	-13.03	AVG	





4. RADIATED EMISSION MEASUREMENT

4.1 RADIATED EMISSION LIMIT (Frequency Range 9KHz-1000MHz)

20 dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a) and RSS-210 Section 2.2&A8.5, then the 15.209(a) and RSS-General limit in the table below has to be followed.

FREQUENCY (MHz)	Field Strength (uV/m at meter)	Measurement Distance (meters)
0.009 -0.490	2400/F(KHz)	300
0.490 -1.705	24000/F(KHz)	30
1.705 -30.0	30	30
30 -88	100	3
88 -216	150	3
216~960	200	3
Above 960	500	3

RADIATED EMISSION LIMITS (Above 1000MHz)

FREQUENCY (MHz)	Class A (dBuV/m)(at 3 M)		Class B (dBuV/m)(at 3 M)	
	Peak	Average		Peak
Above 1000	80	60	74	54

Note:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (2) Emission Level(dBuV/m)=20log Emission Level(uV/m)

The following table is the setting of the receiver

Receiver Parameter	Setting
Attenuation	Auto
Start Frequency~ Stop Frequency	9kHz~150kHz/ RB 200Hz for QP
Start Frequency~ Stop Frequency	150kHz~30MHz/ RB 9kHz for QP
Start Frequency~ Stop Frequency	30MHz~1000MHz/ RB120kHz for QP

The following table is the setting of the spectrum

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10 th carrier harmonic
RB/ VB (emission in restricted band)	1MHz/ 3 MHz for Peak, 1MHz/ 10Hz for Average

4.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.

- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured, above 1G Average detector mode will be instead.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.


Note:

Both horizontal and vertical antenna polarities were tested.


And performed pretest to three orthogonal axis. The worst case emissions were reported.

4.3 TEST SETUP

(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1GHz



4.4 TEST INSTRUMENTS

Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
Broadband Antenna	R&S	VULB 9168	VULB 9168-456	Jul. 06, 2014	Jul. 05. 2015	1 year
Test Cable	N/A	R-01	N/A	Dec. 25, 2013	Dec. 24, 2014	1 year
Test Cable	N/A	R-02	N/A	Dec. 25, 2013	Dec. 24, 2014	1 year
EMI Test Receiver	R&S	ESCI	101324	Jul. 06, 2014	Jul. 05. 2015	1 year
Antenna Mast	EM	SC100_1	N/A	N/A	N/A	N/A
Turn Table	EM	SC100	060531	N/A	N/A	N/A
50Ω Switch	Anritsu Corp	MP59B	6200983705	Jul. 06, 2014	Jul. 05. 2015	1 year
Spectrum Analyzer	R&S	FSP40	100154	Jul. 06, 2014	Jul. 05. 2015	1 year
Horn Antenna	R&S	HF906	10029	Jul. 06, 2014	Jul. 05. 2015	1 year
Amplifier	EM	EM-30180	060538	Jul. 06, 2014	Jul. 05. 2015	1 year

4.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of **2.3** Unless otherwise a special operating condition is specified in the follows during the testing.



4.6 TEST RESULTS

4.6.1 TEST RESULTS (Bellow 1GHz)

EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	TX B Mode 2412	Polarization :	Horizontal
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		117.3602	54.36	-22.34	32.02	43.50	-11.48	peak	
2		185.7880	55.03	-20.76	34.27	43.50	-9.23	peak	
3	!	372.0045	54.79	-14.48	40.31	46.00	-5.69	peak	
4	!	483.9094	51.99	-11.63	40.36	46.00	-5.64	peak	
5	!	556.7744	51.64	-10.12	41.52	46.00	-4.48	peak	
6	*	903.3093	46.80	-5.02	41.78	46.00	-4.22	peak	

Remark:

Factor = Antenna Factor + Cable Loss.



EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	Mode 1	Polarization :	Vertical
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		116.5400	51.55	-22.29	29.26	43.50	-14.24	peak	
2		185.7880	53.33	-20.76	32.57	43.50	-10.93	peak	
3	*	372.0045	55.01	-14.48	40.53	46.00	-5.47	peak	
4		483.9094	51.11	-11.63	39.48	46.00	-6.52	peak	
5		556.7744	49.41	-10.12	39.29	46.00	-6.71	peak	
6		903.3093	43.76	-5.02	38.74	46.00	-7.26	peak	

Remark:

Factor = Antenna Factor + Cable Loss.



4.6.2 TEST RESULTS (Above 1GHz)

EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	B Mode 2412 TX Mode	Polarization :	Horizontal
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		2390.000	46.81	3.40	50.21	74.00	-23.79	peak	
2		2390.000	36.96	3.40	40.36	54.00	-13.64	AVG	
3	*	2409.300	97.78	3.42	101.20	54.00	47.20	AVG	Fudamental Frequency
4	X	2410.600	102.8	3.42	106.24	74.00	32.24	peak	Fudamental Frequency

EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	B Mode 2412 TX Mode	Polarization :	Vertical
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		2390.000	46.74	3.40	50.14	74.00	-23.86	peak	
2		2390.000	37.34	3.40	40.74	54.00	-13.26	AVG	
3	*	2409.300	98.96	3.42	102.38	54.00	48.38	AVG	Fudamental Frequency
4	X	2410.600	102.8	3.42	106.25	74.00	32.25	peak	Fudamental Frequency



EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	B Mode 2437 TX Mode	Polarization :	Horizontal
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4824.000	44.58	6.77	51.35	74.00	-22.65	peak	
2	*	4824.000	37.70	6.77	44.47	54.00	-9.53	AVG	

EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	B Mode 2437 TX Mode	Polarization :	Vertical
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4824.000	42.24	8.77	51.01	74.00	-22.99	peak	
2	*	4824.000	34.78	8.77	43.55	54.00	-10.45	AVG	



EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	B Mode 2437 TX Mode	Polarization :	Horizontal
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector Comment
1		4874.210	45.79	6.78	52.57	74.00	-21.43	peak
2	*	4874.210	37.91	6.78	44.69	54.00	-9.31	AVG

EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	B Mode 2437 TX Mode	Polarization :	Vertical
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector Comment
1		4874.210	42.57	8.78	51.35	74.00	-22.65	peak
2	*	4874.210	34.67	8.78	43.45	54.00	-10.55	AVG



EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	B Mode 2462 TX Mode	Polarization :	Horizontal
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	X	2463.400	102.2	3.48	105.75	74.00	31.75	peak	Fudamental Frequency
2	*	2464.700	97.86	3.48	101.34	54.00	47.34	AVG	Fudamental Frequency
3		2483.500	46.96	3.51	50.47	74.00	-23.53	peak	
4		2483.500	39.22	3.51	42.73	54.00	-11.27	AVG	

EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	B Mode 2462 TX Mode	Polarization :	Vertical
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	X	2463.400	101.6	3.48	105.14	74.00	31.14	peak	Fudamental Frequency
2	*	2464.700	96.94	3.48	100.42	54.00	46.42	AVG	Fudamental Frequency
3		2483.500	45.84	3.51	49.35	74.00	-24.65	peak	
4		2483.500	36.92	3.51	40.43	54.00	-13.57	AVG	



EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	B Mode 2462 TX Mode	Polarization :	Horizontal
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4924.300	44.83	6.80	51.63	74.00	-22.37	peak	
2	*	4924.300	36.44	6.80	43.24	54.00	-10.76	AVG	

EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	B Mode 2462 TX Mode	Polarization :	Vertical
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4924.300	43.56	8.80	52.36	74.00	-21.64	peak	
2	*	4924.300	35.67	8.80	44.47	54.00	-9.53	AVG	



EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	G Mode 2412 TX Mode	Polarization :	Horizontal
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		2390.000	48.61	3.40	52.01	74.00	-21.99	peak	
2		2390.000	38.61	3.40	42.01	54.00	-11.99	AVG	
3	*	2417.900	88.71	3.43	92.14	54.00	38.14	AVG	Fudamental Frequency
4	X	2418.100	98.82	3.43	102.25	74.00	28.25	peak	Fudamental Frequency

EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	G Mode 2412 TX Mode	Polarization :	Vertical
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		2390.000	46.73	3.40	50.13	74.00	-23.87	peak	
2		2390.000	36.87	3.40	40.27	54.00	-13.73	AVG	
3	*	2418.600	84.81	3.43	88.24	54.00	34.24	AVG	Fudamental Frequency
4	X	2418.700	95.19	3.43	98.62	74.00	24.62	peak	Fudamental Frequency



EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	G Mode 2412 TX Mode	Polarization :	Horizontal
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4824.200	41.58	6.77	48.35	74.00	-25.65	peak	
2	*	4824.200	33.66	6.77	40.43	54.00	-13.57	AVG	

EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	G Mode 2412 TX Mode	Polarization :	Vertical
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4824.200	41.47	8.77	50.24	74.00	-23.76	peak	
2	*	4824.200	33.28	8.77	42.05	54.00	-11.95	AVG	



EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	G Mode 2437 TX Mode	Polarization :	Horizontal
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4874.100	42.57	6.78	49.35	74.00	-24.65	peak	
2	*	4874.100	34.20	6.78	40.98	54.00	-13.02	AVG	

EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	G Mode 2437 TX Mode	Polarization :	Vertical
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4874.100	41.58	8.78	50.36	74.00	-23.64	peak	
2	*	4874.100	32.84	8.78	41.62	54.00	-12.38	AVG	



EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	G Mode 2462 TX Mode	Polarization :	Horizontal
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	2455.400	88.26	3.48	91.74	54.00	37.74	AVG	Fudamental Frequency
2	X	2455.700	98.00	3.48	101.48	74.00	27.48	peak	Fudamental Frequency
3		2483.500	46.96	3.51	50.47	74.00	-23.53	peak	
4		2483.500	36.85	3.51	40.36	54.00	-13.64	AVG	

EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	G Mode 2462 TX Mode	Polarization :	Vertical
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	2465.900	85.52	3.48	89.00	54.00	35.00	AVG	Fudamental Frequency
2	X	2466.100	96.10	3.48	99.58	74.00	25.58	peak	Fudamental Frequency
3		2483.500	47.51	3.51	51.02	74.00	-22.98	peak	
4		2483.500	38.18	3.51	41.69	54.00	-12.31	AVG	



EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	G Mode 2462 TX Mode	Polarization :	Horizontal
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4924.200	42.83	6.80	49.63	74.00	-24.37	peak	
2	*	4924.200	33.53	6.80	40.33	54.00	-13.67	AVG	

EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	G Mode 2462 TX Mode	Polarization :	Vertical
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4924.200	41.56	8.80	50.36	74.00	-23.64	peak	
2	*	4924.200	33.23	8.80	42.03	54.00	-11.97	AVG	



EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	N20 Mode 2412 TX Mode	Polarization :	Horizontal
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		2390.000	47.63	3.40	51.03	74.00	-22.97	peak	
2		2390.000	37.86	3.40	41.26	54.00	-12.74	AVG	
3	X	2416.400	98.76	3.43	102.19	74.00	28.19	peak	Fudamental Frequency
4	*	2417.200	88.89	3.43	92.32	54.00	38.32	AVG	Fudamental Frequency

EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	N20 Mode 2412 TX Mode	Polarization :	Vertical
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		2390.000	46.96	3.40	50.36	74.00	-23.64	peak	
2		2390.000	36.77	3.40	40.17	54.00	-13.83	AVG	
3	*	2417.800	86.02	3.43	89.45	54.00	35.45	AVG	Fudamental Frequency
4	X	2417.900	93.97	3.43	97.40	74.00	23.40	peak	Fudamental Frequency



EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	N20 Mode 2412 TX Mode	Polarization :	Horizontal
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4824.200	40.86	6.77	47.63	74.00	-26.37	peak	
2	*	4824.200	31.78	6.77	38.55	54.00	-15.45	AVG	

EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	N20 Mode 2412 TX Mode	Polarization :	Vertical
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4824.200	39.28	8.77	48.05	74.00	-25.95	peak	
2	*	4824.200	30.26	8.77	39.03	54.00	-14.97	AVG	



EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	N20 Mode 2437 TX Mode	Polarization :	Horizontal
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4874.200	40.80	6.78	47.58	74.00	-26.42	peak	
2	*	4874.200	32.11	6.78	38.89	54.00	-15.11	AVG	

EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	N20 Mode 2437 TX Mode	Polarization :	Vertical
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4874.200	39.11	8.78	47.89	74.00	-26.11	peak	
2	*	4874.200	30.89	8.78	39.67	54.00	-14.33	AVG	



EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	N20 Mode 2462 TX Mode	Polarization :	Horizontal
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	2467.100	88.38	3.49	91.87	54.00	37.87	AVG	Fudamental Frequency
2	X	2467.800	98.52	3.49	102.01	74.00	28.01	peak	Fudamental Frequency
3		2483.500	46.70	3.51	50.21	74.00	-23.79	peak	
4		2483.500	37.62	3.51	41.13	54.00	-12.87	AVG	

EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	N20 Mode 2462 TX Mode	Polarization :	Vertical
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	X	2467.300	95.83	3.49	99.32	74.00	25.32	peak	Fudamental Frequency
2	*	2467.900	86.05	3.49	89.54	54.00	35.54	AVG	Fudamental Frequency
3		2483.500	47.51	3.51	51.02	74.00	-22.98	peak	
4		2483.500	38.18	3.51	41.69	54.00	-12.31	AVG	



EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	N20 Mode 2462 TX Mode	Polarization :	Horizontal
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4924.300	40.45	6.80	47.25	74.00	-26.75	peak	
2	*	4924.300	31.42	6.80	38.22	54.00	-15.78	AVG	


EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	N20 Mode 2462 TX Mode	Polarization :	Vertical
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4924.300	39.45	8.80	48.25	74.00	-25.75	peak	
2	*	4924.300	30.89	8.80	39.69	54.00	-14.31	AVG	



EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-11-20
Test Mode :	N40 Mode 2422 TX Mode	Polarization :	Horizontal
Test Power :	AC 120V/60 Hz		


Peak Values



Date: 20.NOV.2014 20:54:36



Average Values




Date: 20.NOV.2014 20:56:14

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		2390.000	47.31	3.40	50.71	74.00	-23.29	peak	
2		2390.000	35.53	3.40	38.93	54.00	-15.07	AVG	
3	X	2419.600	93.11	3.43	96.54	74.00	22.54	peak	Fudamental Frequency
4	*	2419.600	82.00	3.43	85.43	54.00	31.43	AVG	Fudamental Frequency



EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-11-20
Test Mode :	N40 Mode 2422 TX Mode	Polarization :	Vertical
Test Power :	AC 120V/60 Hz		


Peak Values



Date: 20.NOV.2014 20:58:03



Average Values



Date: 20.NOV.2014 21:02:16

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
		MHz	Level	Factor	ment			Detector	Comment
			dBuV	dB	dBuV/m	dBuV/m	dB		
1		2390.000	48.50	3.40	51.90	74.00	-22.10	peak	
2		2390.000	35.19	3.40	38.59	54.00	-15.41	AVG	
3	*	2420.700	78.75	3.43	82.18	54.00	28.18	AVG	Fudamental Frequency
4	X	2425.600	89.81	3.45	93.26	74.00	19.26	peak	Fudamental Frequency



EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-11-20
Test Mode :	N40 Mode 2422 TX Mode	Polarization :	Horizontal
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4844.500	39.62	6.77	46.39	74.00	-27.61	peak	
2	*	4844.500	31.78	6.77	38.55	54.00	-15.45	AVG	

EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-11-20
Test Mode :	N40 Mode 2422 TX Mode	Polarization :	Vertical
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4844.500	38.47	8.78	47.25	74.00	-26.75	peak	
2	*	4844.500	30.76	8.78	39.54	54.00	-14.46	AVG	



EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	N40 Mode 2437 TX Mode	Polarization :	Horizontal
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4874.300	39.79	6.78	46.57	74.00	-27.43	peak	
2	*	4874.300	31.27	6.78	38.05	54.00	-15.95	AVG	


EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	N40 Mode 2437 TX Mode	Polarization :	Vertical
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4874.300	38.80	8.78	47.58	74.00	-26.42	peak	
2	*	4874.300	29.69	8.78	38.47	54.00	-15.53	AVG	



EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-11-10
Test Mode :	N40 Mode 2452 TX Mode	Polarization :	Horizontal
Test Power :	AC 120V/60 Hz		


Peak Values



Date: 20.NOV.2014 20:48:52



Average Values




Date: 20.NOV.2014 20:51:57

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	2452.900	81.68	3.48	85.16	54.00	31.16	AVG	Fudamental Frequency
2	X	2455.800	92.91	3.48	96.39	74.00	22.39	peak	Fudamental Frequency
3		2483.500	48.23	3.51	51.74	74.00	-22.26	peak	
4		2483.500	34.93	3.51	38.44	54.00	-15.56	AVG	



EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-11-20
Test Mode :	N40 Mode 2452 TX Mode	Polarization :	Vertical
Test Power :	AC 120V/60 Hz		


Peak Values



Date: 20.NOV.2014 20:40:47



Average Values



Date: 20.NOV.2014 20:45:39

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2452.500	89.82	3.48	93.30	74.00	19.30	peak	Fudamental Frequency
2	*	2455.400	78.51	3.48	81.99	54.00	27.99	AVG	Fudamental Frequency
3		2483.500	48.42	3.51	51.93	74.00	-22.07	peak	
4		2483.500	34.67	3.51	38.18	54.00	-15.82	AVG	



EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	N40 Mode 2452 TX Mode	Polarization :	Horizontal
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4904.200	40.07	6.80	46.87	74.00	-27.13	peak	
2	*	4904.200	31.78	6.80	38.58	54.00	-15.42	AVG	

EUT :	NETWORK SECURITY EQUIPMENTR	Model Name. :	CR10ING
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Test Date :	2014-10-10
Test Mode :	N40 Mode 2452 TX Mode	Polarization :	Vertical
Test Power :	AC 120V/60 Hz		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4904.200	38.56	8.79	47.35	74.00	-26.65	peak	
2	*	4904.200	30.43	8.79	39.22	54.00	-14.78	AVG	



5. MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT

5.1 LIMITS


FCC Part 15.247, subpart C	
Frequency Range (MHz)	2400~2483.5
Limits	30

5.2 TEST PROCEDURE

The measurement is according to section 9.1.2 of KDB 558074 D01 DTS Meas Guidance v03r02.

The EUT was directly connected to the power meter and antenna output port as show in the block diagram as bellow.

5.3 TEST SETUP



5.4 TEST INSTRUMENTS

Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
Power Meter	Anritsu	ML2495A	0917201	Jul. 06, 2014	Jul. 05. 2015	1 year
Power Sensor	Anritsu	MA2411B	1035004	Jul. 06, 2014	Jul. 05. 2015	1 year

5.5 EUT OPERATING CONDITIONS

The EUT was set to continuously transmitting in the maximum power during the test.

5.6 TEST RESULTS



2.4 G Band Conducted Power					
802.11b Power					
Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)
		ANT 0	ANT 1	Total	
1	2412 MHz	16.25			30
6	2437 MHz	16.21			
11	2462 MHz	16.54			
802.11g Power					
Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)
		ANT 0	ANT 1	Total	
1	2412 MHz	15.11			30
6	2437 MHz	15.18			
11	2462 MHz	15.01			
802.11n(HT20) Power					
Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)
		ANT 0	ANT 1	Total	
1	2412 MHz	14.30	13.20	16.79	30
6	2437 MHz	14.28	13.24	16.80	
11	2462 MHz	14.41	13.21	16.86	
802.11n(HT40) Power					
Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)
		ANT 0	ANT 1	Total	
1	2412 MHz	14.21	13.05	16.67	30
6	2437 MHz	14.26	13.09	16.72	
11	2462 MHz	14.35	13.14	16.79	



6. OCCUPIED BANDWIDTH MEASUREMENT

6.1 LIMITS


FCC Part 15.247, subpart C	
Frequency Range (MHz)	2400~2483.5
Limits	6 dB Bandwidth>500 KHz

6.2 TEST PROCEDURE

The EUT was directly connected to the power meter and antenna output port as show in the block diagram as bellow.

Spectrum Parameters	Setting
Attenuation	Auto
Span	>6 dB Bandwidth
RBW	100 kHz
VBW	$\geq 3\text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

6.3 TEST SETUP



6.4 TEST INSTRUMENTS

Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
Spectrum Analyzer	Agilent	E4407B	MY57802541	Jul. 06, 2014	Jul. 05. 2015	1 year


6.5 EUT OPERATING CONDITIONS



The EUT was set to continuously transmitting in the maximum power during the test.

6.6 TEST RESULTS




801.11b Mode			
Frequency (MHz)	6dB Bandwidth (MHz)	99% OBW (MHz)	Limit
2412	10.009	15.2229	>=500 kHz
2437	10.050	15.0882	
2462	9.580	15.1957	
Note: The worst mode is the TX AN0, only showed the worst mode plots.			



B Mode 2412 MHz

**B Mode 2437 MHz****B Mode 2462 MHz**



801.11g Mode			
Frequency (MHz)	6dB Bandwidth (MHz)	99% OBW (MHz)	Limit
2412	16.543	16.4865	>=500 kHz
2437	16.543	16.4735	
2462	16.522	16.4821	
Note: The worst mode is the TX AN0, only showed the worst mode plots.			


G Mode 2412 MHz



**G Mode 2437 MHz****G Mode 2462 MHz**

801.11n(HT20) Mode			
Frequency (MHz)	6dB Bandwidth (MHz)	99% OBW (MHz)	Limit
2412	17.849	17.7030	>=500 kHz
2437	17.870	17.7212	
2462	17.858	17.7210	

Note: The worst mode is the TX AN0, only showed the worst mode plots.

N Mode 2412 MHz






**N Mode 2437 MHz****N Mode 2462 MHz**



801.11n(HT40) Mode			
Frequency (MHz)	6dB Bandwidth (MHz)	99% OBW (MHz)	Limit
2422	36.439	35.9468	>=500 kHz
2437	36.456	35.9818	
2452	36.474	36.9865	
Note: The worst mode is the TX AN0, only showed the worst mode plots.			

N Mode 2422 MHz



**N Mode 2437 MHz****N Mode 2452 MHz**



7. POWER SPECTRAL DENSITY

7.1 LIMITS


FCC Part 15.247, Subpart C	
Frequency Range (MHz)	2400~2483.5
99% Occupied Bandwidth	8 dBm in any 3 kHz

7.2 TEST PROCEDURE

The EUT was directly connected to the power meter and antenna output port as show in the block diagram as below.

Spectrum Parameters	Setting
Attenuation	Auto
Span	Set the span to 1.5 times the DTS channel bandwidth
RBW	3 kHz
VBW	$\geq 3\text{RBW}$
Detector	Reak
Trace	Max Hold
Sweep Time	Auto

7.3 TEST SETUP



7.4 TEST INSTRUMENTS

Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
Spectrum Analyzer	Agilent	E4407B	MY57802541	Jul. 06, 2014	Jul. 05. 2015	1 year

7.5 EUT OPERATING CONDITIONS


The EUT was set to continuously transmitting in the maximum power during the test.



7.6 TEST RESULTS



801.11b Mode					
Frequency (MHz)	Power Density (3 kHz/dBm)			Limit (dBm/3KHz)	Result
	ANT 0	ANT 1	Total		
2412	-15.69			8	Pass
2437	-15.90				
2462	-15.57				
Note: The worst mode is ANT 0, only showed the worst data of ANT 0.					

B Mode 2412 MHz






**B Mode 2437 MHz****B Mode 2462 MHz**



801.11g Mode					
Frequency (MHz)	Power Density (3 kHz/dBm)			Limit (dBm/3KHz)	Result
	ANT 0	ANT 1	Total		
2412	-17.76			8	Pass
2437	-17.74				
2462	-17.62				
Note: The worst mode is ANT 0, only showed the worst data of ANT 0.					

G Mode 2412 MHz-ANT 0




**G Mode 2437 MHz-ANT 0****G Mode 2462 MHz-ANT 0**




801.11n(HT20) Mode					
Frequency (MHz)	Power Density (3 kHz/dBm)			Limit (dBm/3KHz)	Result
	ANT 0	ANT 1	Total		
2412	-17.78	-18.80	-15.25	8	Pass
2437	-17.23	-19.04	-15.03		
2462	-16.98	-18.42	-14.63		

N (HT20) Mode 2412 MHz-ANT 0






N (HT20) 2437 MHz-ANT 0




N (HT20) 2462 MHz-ANT 0






N (HT20) 2412 MHz-ANT 1




N (HT20) 2437 MHz-ANT 1






N (HT20) 2462 MHz-ANT 1






801.11n(HT40) Mode					
Frequency (MHz)	Power Density (3 kHz/dBm)			Limit (dBm/3KHz)	Result
	ANT 0	ANT 1	Total		
2422	-18.45	-20.27	-16.25	8	Pass
2437	-19.08	-19.48	-16.26		
2452	-20.18	-20.20	-17.18		

N (HT40) Mode 2422 MHz-ANT 0






N (HT40) 2437 MHz-ANT 0




N (HT40) 2452 MHz-ANT 0






N (HT40) 2422 MHz-ANT 1




N (HT40) 2437 MHz-ANT 1





N (HT40) 2452 MHz-ANT 1





8. ANTENNA CONDUCTED SPURIOUS EMISSION

8.1 LIMITS

FCC Part 15.247, Subpart C	
Frequency Range (MHz)	2400~2483.5
Limit	In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the desired power, based on either an RF conducted measurement, provide the transmitter demonstrates compliance with the peak conducted power limits.


8.2 TEST PROCEDURE

The EUT was directly connected to the power meter and antenna output port as show in the block diagram as bellow.

- Set frequency range to capture low band-edge from 2310 MHz up to 2390 MHz, and for up band-edge from 2483.5 MHz up to 2500 MHz
- For low band-edge set the equipment transmit at the lowest channel, and for up band-edge set the equipment transmit at the highest channel
- Set the VBW ≥ 3 RBW (100kHz/ 300kHz) for conducted measurement
- For radiated measurements the RBW set to 1 MHz, and the VBW set to 1 MHz for peak measurements and 10 Hz for average measurement

8.3 TEST SETUP

Conducted Emission Test Setup



8.4 TEST INSTRUMENTS



Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
Spectrum Analyzer	Agilent	E4407B	MY57802541	Jul. 06, 2014	Jul. 05. 2015	1 year



8.5 EUT OPERATING CONDITIONS



The EUT was set to continuously transmitting in the maximum power during the test.



8.6 TEST RESULTS



Only showed the worst mode data of ANT 0 transmitting.



**B Mode Low CH****B Mode High CH**



**B Mode Low CH (30MHz~1GHz)****B Mode Low CH (1GHz~26.5GHz)**



**B Mode Middle CH (30MHz~1GHz)****B Mode Middle CH (1GHz~26.5GHz)**

**B Mode High CH (30MHz~1GHz)****B Mode High CH (1GHz~26.5GHz)**

**G Mode Low CH****G Mode High CH**


**G Mode Low CH (30MHz~1GHz)****G Mode Low CH (1GHz~26.5GHz)**

**G Mode Middle CH (30MHz~1GHz)****G Mode Middle CH (1GHz~26.5GHz)**


**G Mode High CH (30MHz~1GHz)****G Mode High CH (1GHz~26.5GHz)**





N(HT20) Mode Low CH




N(HT20) Mode High CH




**N(HT20) Mode Low CH (30MHz~1GHz)****N(HT20) Mode Low CH (1GHz~26.5GHz)**



N(HT20) Mode Middle CH (30MHz~1GHz)




N(HT20) Mode Middle CH (1GHz~26.5GHz)










N(HT20) Mode High CH (30MHz~1GHz)







N(HT20) Mode High CH (1GHz~26.5GHz)



**N(HT40) Mode Low CH****N(HT40) Mode High CH**

**N(HT40) Mode Low CH (30MHz~1GHz)****N(HT40) Mode Low CH (1GHz~26.5GHz)**

**N(HT40) Mode Middle CH (30MHz~1GHz)****N(HT40) Mode Middle CH (1GHz~26.5GHz)**

**N(HT40) Mode High CH (30MHz~1GHz)****N(HT40) Mode High CH (1GHz~26.5GHz)**



9. ANTENNA REQUIREMENT

9.1 REQUIREMENT

Antenna Requirement (15.203)	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
Antenna Requirement (15.247)	If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

9.2 ANTENNA CONNECTOR CONSTRUCTION

The EUT antenna is a Dipole Antenna. And the maximum gain of this antenna is 2 dBi. It complies with the standard requirement.