

# RF TEST REPORT



Report No.: 15070843-FCC-R2

Supersede Report No.: N/A

Applicant	WUXI IDATA TECHNOLOGY COMPANY LTD.	
Product Name	New Mobile Computer	
Model No.	iData 95W	
Serial No.	N/A	
Test Standard	FCC Part 15.247: 2014, ANSI C63.10: 2013	
Test Date	September 24 to October 19, 2015	
Issue Date	October 19, 2015	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification		<input checked="" type="checkbox"/>
Equipment did not comply with the specification		<input type="checkbox"/>
<i>Winnie Zhang</i>	<i>David Huang</i>	
Winnie Zhang Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

**SIEMIC (SHENZHEN-CHINA) LABORATORIES**

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: [China@siemic.com.cn](mailto:China@siemic.com.cn)

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	15070843-FCC-R2
Page	3 of 59

This page has been left blank intentionally.

## CONTENTS

1. REPORT REVISION HISTORY .....	5
2. CUSTOMER INFORMATION .....	5
3. TEST SITE INFORMATION .....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION .....	6
5. TEST SUMMARY .....	8
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS .....	9
6.1 ANTENNA REQUIREMENT .....	9
6.2 CHANNEL SEPARATION .....	10
6.3 20DB BANDWIDTH .....	14
6.4 PEAK OUTPUT POWER .....	18
6.5 NUMBER OF HOPPING CHANNEL .....	22
6.6 TIME OF OCCUPANCY (DWEIL TIME) .....	24
6.7 BAND EDGE .....	28
6.8 AC POWER LINE CONDUCTED EMISSIONS .....	36
6.9 RADIATED EMISSIONS .....	42
ANNEX A. TEST INSTRUMENT .....	47
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS .....	48
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT .....	54
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST .....	58
ANNEX E. DECLARATION OF SIMILARITY .....	59

## 1. Report Revision History

Report No.	Report Version	Description	Issue Date
15070843-FCC-R2	NONE	Original	October 19, 2015

## 2. Customer information

Applicant Name	WUXI IDATA TECHNOLOGY COMPANY LTD.
Applicant Add	Floor 11,Building B1,Wuxi Binhu National Sensing, Information Center,No.999 Gaolang East Road, Wuxi
Manufacturer	WUXI IDATA TECHNOLOGY COMPANY LTD.
Manufacturer Add	Floor 11,Building B1,Wuxi Binhu National Sensing, Information Center,No.999 Gaolang East Road, Wuxi

## 3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

#### 4. Equipment under Test (EUT) Information

Description of EUT:	New Mobile Computer
Main Model:	iData 95W
Serial Model:	N/A
Date EUT received:	September 23, 2015
Test Date(s):	September 24 to October 19, 2015
Equipment Category :	DSS
Antenna Gain:	GSM850: 0dBi PCS1900: 1dBi UMTS-FDD Band V: 0dBi Bluetooth/BLE/WIFI: 2.5dBi GPS: 1.5dBi
Type of Modulation:	GSM / GPRS: GMSK UMTS-FDD: QPSK, 16QAM 802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, $\pi/4$ DQPSK, 8DPSK BLE: GFSK GPS: BPSK
RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz WIFI: 802.11b/g/n(20M): 2412-2462 MHz WIFI: 802.11n(40M): 2422-2452 MHz Bluetooth & BLE: 2402-2480 MHz GPS RX: 1575.42 MHz
Max. Output Power:	-4.036dBm
Number of Channels:	GSM 850: 124CH PCS1900: 299CH

Test Report	15070843-FCC-R2
Page	7 of 59

UMTS-FDD Band V : 102CH

WIFI :802.11b/g/n(20M): 11CH

WIFI :802.11n(40M): 7CH

Bluetooth: 79CH

BLE: 40CH

GPS:1CH

Port:

Power Port, Earphone Port, USB Port

Adapter:

Model: FJ-SW0502000UC

Input: AC 100-240V; 50/60Hz;0.35Amax

Output: DC5.0V;2000mA

Battery:

Input Power:

Model: iData 70/90/95

Spec: 4000mAh,14.8Wh

Limited charger voltage:4.2V

Backup Battery:

Model: KPL501633

Spec: 3.7V 2000mAh,0.74Wh

Trade Name :

iData

GPRS Multi-slot class

8/10/12

FCC ID:

2ADE3IDATA95W

## 5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247(a)(1)	Channel Separation	Compliance
§15.247(a)(1)	20 dB Bandwidth	Compliance
§15.247(b)(1)	Peak Output Power	Compliance
§15.247(a)(1)(iii)	Number of Hopping Channel	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(d)	Band Edge	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions	Compliance

### Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-



## 6. Measurements, Examination And Derived Results

### 6.1 Antenna Requirement

#### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **Antenna Connector Construction**

The EUT has 3 antennas:

A permanently attached PIFA antenna for Bluetooth/BLE/WIFI, the gain is 2.5dBi.

A permanently attached PIFA antenna for GSM and UMTS, the gain is 0dBi for GSM850, 1dBi for PCS1900, 0dBi for UMTS-FDD Band V.

A permanently attached PIFA antenna for GPS, the gain is 1.5dBi.



**The antenna meets up with the ANTENNA REQUIREMENT.**

**Result:** Compliance.

## 6.2 Channel Separation

Temperature	23°C
Relative Humidity	54%
Atmospheric Pressure	1030mbar
Test date :	September 30, 2015
Tested By :	Winnie Zhang

### Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247(a)(1)	a)	Channel Separation < 20dB BW and 20dB BW < 25KHz ; Channel Separation Limit=25KHz Chanel Separation < 20dB BW and 20dB BW > 25kHz ; Channel Separation Limit=2/3 20dB BW	
Test Setup	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings:</p> <ul style="list-style-type: none"> <li>- The EUT must have its hopping function enabled</li> <li>- Span = wide enough to capture the peaks of two adjacent channels</li> <li>- Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span</li> <li>- Video (or Average) Bandwidth (VBW) ≥ RBW</li> <li>- Sweep = auto</li> <li>- Detector function = peak</li> <li>- Trace = max hold</li> <li>- Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.</li> </ul>		

Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail


Test Data ☒ Yes ☐ N/A  
 Test Plot ☒ Yes (See below) ☐ N/A

### Channel Separation measurement result


Type/ Modulation	CH	CH Freq (MHz)	CH Separation (MHz)	Limit (MHz)	Result
CH Separation GFSK	Low Channel	2402	1.002	0.683	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.963	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.680	Pass
	Adjacency Channel	2479			
CH Separation $\pi/4$ DQPSK	Low Channel	2402	1.002	0.857	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.855	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.855	Pass
	Adjacency Channel	2479			
CH Separation 8DPSK	Low Channel	2402	1.002	0.859	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.867	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.847	Pass
	Adjacency Channel	2479			

## Test Plots


### Channel Separation measurement result



GFSK - Low Channel




GFSK - Middle Channel



GFSK - High Channel



$\pi/4$  DPSK - Low Channel



$\pi/4$  DQPSK - Middle Channel



$\pi/4$  DQPSK - High Channel



8DPSK - Low Channel



8DPSK - Middle Channel




8DPSK - High Channel

### 6.3 20dB Bandwidth

Temperature	23°C
Relative Humidity	54%
Atmospheric Pressure	1030mbar
Test date :	September 30, 2015
Tested By :	Winnie Zhang

#### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)	a)	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings:</p> <ul style="list-style-type: none"> <li>- Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel</li> <li>- RBW <math>\geq</math> 1% of the 20 dB bandwidth</li> <li>- VBW <math>\geq</math> RBW</li> <li>- Sweep = auto</li> <li>- Detector function = peak</li> <li>- Trace = max hold.</li> <li>- The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference</li> </ul>		

Test Report	15070843-FCC-R2
Page	15 of 59

	marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

#### Measurement result


Modulation	CH	CH Freq (MHz)	20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
GFSK	Low	2402	1.024	0.8959
	Mid	2441	0.963	0.8912
	High	2480	1.020	0.8938
$\pi/4$ DQPSK	Low	2402	1.285	1.1668
	Mid	2441	1.283	1.1663
	High	2480	1.282	1.1635
8-DPSK	Low	2402	1.288	1.1743
	Mid	2441	1.301	1.1747
	High	2480	1.271	1.1732

## Test Plots

### 20dB Bandwidth measurement result








8DPSK - Low Channel



8DPSK - Middle Channel




8DPSK - High Channel

## 6.4 Peak Output Power

Temperature	23°C
Relative Humidity	54%
Atmospheric Pressure	1030mbar
Test date :	September 30, 2015
Tested By :	Winnie Zhang

### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (2)	a)	FHSS in 2400-2483.5MHz with $\geq 75$ channels: $\leq 1$ Watt	<input checked="" type="checkbox"/>
	b)	FHSS in 5725-5850MHz: $\leq 1$ Watt	<input type="checkbox"/>
	c)	For all other FHSS in the 2400-2483.5MHz band: $\leq 0.125$ Watt.	<input checked="" type="checkbox"/>
	d)	FHSS in 902-928MHz with $\geq 50$ channels: $\leq 1$ Watt	<input type="checkbox"/>
	e)	FHSS in 902-928MHz with $\geq 25$ & $< 50$ channels: $\leq 0.25$ Watt	<input type="checkbox"/>
	f)	DSSS in 902-928MHz, 2400-2483.5MHz, 5725-5850MHz: $\leq 1$ Watt	<input type="checkbox"/>

Test Setup	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>
------------	--

Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings:</p> <ul style="list-style-type: none"> <li>- Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel</li> <li>- RBW <math>&gt;</math> the 20 dB bandwidth of the emission being measured</li> <li>- VBW <math>\geq</math> RBW</li> <li>- Sweep = auto</li> <li>- Detector function = peak</li> <li>- Trace = max hold</li> </ul>
----------------	--

	<ul style="list-style-type: none"> <li>- Allow the trace to stabilize.</li> <li>- Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (see the note above regarding external attenuation and cable loss). The limit is specified in one of the subparagraphs of this Section. Submit this plot. A peak responding power meter may be used instead of a spectrum analyzer.</li> </ul>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail


Test Data ☒ Yes ☐ N/A  
 Test Plot ☒ Yes (See below) ☐ N/A

**Peak Output Power measurement result**

Type	Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Limit (mW)	Result
Output power	GFSK	Low	2402	-4.036	125	Pass
		Mid	2441	-4.330	1000	Pass
		High	2480	-4.599	125	Pass
	$\pi/4$ DQPSK	Low	2402	-4.276	125	Pass
		Mid	2441	-4.222	125	Pass
		High	2480	-5.122	125	Pass
	8-DPSK	Low	2402	-5.122	125	Pass
		Mid	2441	-4.211	125	Pass
		High	2480	-4.606	125	Pass

## Test Plots


### Output Power measurement result



GFSK Output power - Low CH 2402




GFSK Output power - Mid CH 2441




GFSK Output power - High CH 2480




$\pi/4$  DQPSK Output power - Low CH 2402



$\pi/4$  DQPSK Output power - Mid CH 2441




$\pi/4$  DQPSK Output power - High CH 2480



8DPSK Output power - Low CH 2402



8DPSK Output power - Mid CH 2441




8DPSK Output power - High CH 2480

## 6.5 Number of Hopping Channel

Temperature	23°C
Relative Humidity	54%
Atmospheric Pressure	1030mbar
Test date :	September 30, 2015
Tested By :	Winnie Zhang

### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	FHSS in 2400-2483.5MHz $\geq$ 15 channels	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.  <u>Use the following spectrum analyzer settings:</u>  The EUT must have its hopping function enabled.</p> <ul style="list-style-type: none"> <li>- Span = the frequency band of operation</li> <li>- RBW <math>\geq</math> 1% of the span</li> <li>- VBW <math>\geq</math> RBW</li> <li>- Sweep = auto</li> <li>- Detector function = peak</li> <li>- Trace = max hold</li> <li>- Allow trace to fully stabilize.</li> <li>- It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).</li> </ul>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data    ☒ Yes                      ☐ N/A


Test Plot    ☒ Yes (See below)                      ☐ N/A

### Number of Hopping Channel measurement result


Type	Modulation	Frequency Range	Number of Hopping Channel	Limit
Number of Hopping Channel	GFSK	2400-2483.5	79	15
	$\pi$ /4 DQPSK	2400-2483.5	79	15
	8-DPSK	2400-2483.5	79	15

### Test Plots


#### Number of Hopping Channels measurement result



GFSK



$\pi$  /4DQPSK




8DPSK

## 6.6 Time of Occupancy (Dwell Time)

Temperature	23°C
Relative Humidity	54%
Atmospheric Pressure	1030mbar
Test date :	September 30, 2015
Tested By :	Winnie Zhang

### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	Dwell Time < 0.4s	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. <u>Use the following spectrum analyzer</u></p> <ul style="list-style-type: none"> <li>- Span = zero span, centered on a hopping channel</li> <li>- RBW = 1 MHz</li> <li>- VBW ≥ RBW</li> <li>- Sweep = as necessary to capture the entire dwell time per hopping channel</li> <li>- Detector function = peak</li> <li>- Trace = max hold</li> <li>- use the marker-delta function to determine the dwell time</li> </ul>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data    ☒ Yes                      ☐ N/A

Test Plot    ☒ Yes (See below)                      ☐ N/A



Type	Modulation	CH	Pulse Width (ms)	Dwell Time (ms)	Limit (ms)	Result
Dwell Time	GFSK	Low	2.867	305.813	400	Pass
		Mid	2.875	306.667	400	Pass
		High	2.875	306.667	400	Pass
	$\pi/4$ DQPSK	Low	2.867	305.813	400	Pass
		Mid	2.875	306.667	400	Pass
		High	2.875	306.667	400	Pass
	8-DPSK	Low	2.875	306.667	400	Pass
		Mid	2.883	307.520	400	Pass
		High	2.875	306.667	400	Pass
Note: Dwell time=Pulse Time (ms) $\times$ (1600 $\div$ 6 $\div$ 79) $\times$ 31.6						

## Test Plots


### Dwell Time measurement result




GFSK - Low CH 2402




GFSK - Mid CH 2441




GFSK - High CH 2480




$\pi/4$  DQPSK - Low CH 2402




$\pi/4$  DQPSK - Mid CH 2441




$\pi/4$  DQPSK - High CH 2480



8DPSK - Low CH 2402



8DPSK - Mid CH 2441




8DPSK - High CH 2480

## 6.7 Band Edge

Temperature	22°C
Relative Humidity	55%
Atmospheric Pressure	1013mbar
Test date :	October 13 to 15, 2015
Tested By :	Winnie Zhang

### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Radiated Method Only</p> <ul style="list-style-type: none"> <li>1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.</li> <li>2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range,</li> </ul>		

Test Report	15070843-FCC-R2
Page	29 of 59


	<p>and make sure the instrument is operated in its linear range.</p> <ul style="list-style-type: none"> <li>- 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: <ul style="list-style-type: none"> <li>a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz.</li> <li>b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.</li> <li>c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</li> </ul> </li> <li>- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.</li> <li>- 5. Repeat above procedures until all measured frequencies were complete.</li> </ul>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail



Test Data ☐ Yes ☒ N/A

Test Plot ☒ Yes (See below) ☐ N/A

## Test Plots

### GFSK Mode:






GFSK-Left Side-PK

Note: F1 is frequency 2400MHz

GFSK-Right Side-PK

Note: F1 is frequency 2483.5MHz




Note: (no need if PK value less than the AV limit)

GFSK-Left Side-AV


GFSK-Right Side-AV

$\pi/4$  DQPSK Mode:




$\pi/4$  DQPSK-Hopping Left Side-PK

Note: F1 is frequency 2400MHz



$\pi/4$  DQPSK-Hopping Right Side-PK

Note: F1 is frequency 2483.5MHz




Note: (no need if PK value less than the AV limit)

$\pi/4$  DQPSK-Hopping Left-AV

$\pi/4$  DQPSK-Hopping Right-AV






Date: 13.OCT.2015 14:48:02

$\pi/4$  DQPSK-Left Side-PK


Note: F1 is frequency 2400MHz



Date: 13.OCT.2015 14:58:42

$\pi/4$  DQPSK-Right Side-PK

Note: F1 is frequency 2483.5MHz




Date: 13.OCT.2015 14:48:28

$\pi/4$  DQPSK-Left Side-AV

Note: (no need if PK value less than the AV limit)


$\pi/4$  DQPSK-Right Side-AV

## 8-DPSK Mode:




### 8DPSK-Hopping Left Side-PK

Note: F1 is frequency 2400MHz



### 8DPSK-Hopping Right Side-PK


Note: F1 is frequency 2483.5MHz



### 8DPSK-Hopping Left-AV


Note: (no need if PK value less than the AV limit)

### 8DPSK-Hopping Right-AV




8DPSK-Left Side-PK

Note: F1 is frequency 2400MHz



8DPSK-Left Side-AV



8DPSK-Right Side-PK

Note: F1 is frequency 2483.5MHz


Note: (no need if PK value less than the AV limit)

8DPSK-Right Side-AV

## 6.8 AC Power Line Conducted Emissions

Temperature	23°C
Relative Humidity	54%
Atmospheric Pressure	1030mbar
Test date :	September 30, 2015
Tested By :	Winnie Zhang

### Requirement(s):

Spec	Item	Requirement	Applicable														
47CFR§15.207, RSS210 (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu]H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.	<div><input checked="" type="checkbox"/></div>														
		<table><tr><th rowspan="2">Frequency ranges (MHz)</th><th colspan="2">Limit (dBµV)</th></tr><tr><th>QP</th><th>Average</th></tr><tr><td>0.15 ~ 0.5</td><td>66 – 56</td><td>56 – 46</td></tr><tr><td>0.5 ~ 5</td><td>56</td><td>46</td></tr><tr><td>5 ~ 30</td><td>60</td><td>50</td></tr></table>		Frequency ranges (MHz)	Limit (dBµV)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50
		Frequency ranges (MHz)			Limit (dBµV)												
				QP	Average												
		0.15 ~ 0.5		66 – 56	56 – 46												
0.5 ~ 5	56	46															
5 ~ 30	60	50															
Test Setup	<div></div>																
Procedure		1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table.															
		2. The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains.															
		3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss															


Test Report	15070843-FCC-R2
Page	37 of 59

	<p>coaxial cable.</p> <ol style="list-style-type: none"> <li>4. All other supporting equipment were powered separately from another main supply.</li> <li>5. The EUT was switched on and allowed to warm up to its normal operating condition.</li> <li>6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.</li> <li>7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz.</li> <li>8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).</li> </ol>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

**Test Mode:** Bluetooth Mode




### Test Data

### Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	L1	0.1851	37.43	QP	10.03	47.46	64.25	-16.79
2	L1	0.1851	20.98	AVG	10.03	31.01	54.25	-23.24
3	L1	0.2046	35.71	QP	10.03	45.74	63.42	-17.68
4	L1	0.2046	18.02	AVG	10.03	28.05	53.42	-25.37
5	L1	0.2943	31.16	QP	10.03	41.19	60.40	-19.21
6	L1	0.2943	17.71	AVG	10.03	27.74	50.40	-22.66
7	L1	0.3489	35.33	QP	10.03	45.36	58.99	-13.63
8	L1	0.3489	28.03	AVG	10.03	38.06	48.99	-10.93
9	L1	0.3762	24.18	QP	10.03	34.21	58.36	-24.15
10	L1	0.3762	7.22	AVG	10.03	17.25	48.36	-31.11
11	L1	0.4698	23.04	QP	10.03	33.07	56.52	-23.45
12	L1	0.4698	10.04	AVG	10.03	20.07	46.52	-26.45

**Test Mode:** Bluetooth Mode




### Test Data

#### Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	N	0.1890	35.82	QP	10.02	45.84	64.08	-18.24
2	N	0.1890	19.17	AVG	10.02	29.19	54.08	-24.89
3	N	0.1968	35.56	QP	10.02	45.58	63.74	-18.16
4	N	0.1968	18.75	AVG	10.02	28.77	53.74	-24.97
5	N	0.2748	32.97	QP	10.02	42.99	60.97	-17.98
6	N	0.2748	21.85	AVG	10.02	31.87	50.97	-19.10
7	N	0.3489	35.56	QP	10.02	45.58	58.99	-13.41
8	N	0.3489	28.89	AVG	10.02	38.91	48.99	-10.08
9	N	0.5868	22.05	QP	10.02	32.07	56.00	-23.93
10	N	0.5868	6.38	AVG	10.02	16.40	46.00	-29.60
11	N	6.7128	24.73	QP	10.09	34.82	60.00	-25.18
12	N	6.7128	9.99	AVG	10.09	20.08	50.00	-29.92

**Test Mode:** Bluetooth Mode




### Test Data

#### Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	L1	0.1890	32.97	QP	10.03	43.00	64.08	-21.08
2	L1	0.1890	18.65	AVG	10.03	28.68	54.08	-25.40
3	L1	0.2943	34.21	QP	10.03	44.24	60.40	-16.16
4	L1	0.2943	20.19	AVG	10.03	30.22	50.40	-20.18
5	L1	0.3450	33.93	QP	10.03	43.96	59.08	-15.12
6	L1	0.3450	27.11	AVG	10.03	37.14	49.08	-11.94
7	L1	1.7841	23.30	QP	10.04	33.34	56.00	-22.66
8	L1	1.7841	6.92	AVG	10.04	16.96	46.00	-29.04
9	L1	6.3852	26.61	QP	10.10	36.71	60.00	-23.29
10	L1	6.3852	12.20	AVG	10.10	22.30	50.00	-27.70
11	L1	19.7817	18.86	QP	10.30	29.16	60.00	-30.84
12	L1	19.7817	9.64	AVG	10.30	19.94	50.00	-30.06



**Test Mode:** Bluetooth Mode



**Test Data**


**Phase Neutral Plot at 240Vac, 60Hz**

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	N	0.1929	38.10	QP	10.02	48.12	63.91	-15.79
2	N	0.1929	25.35	AVG	10.02	35.37	53.91	-18.54
3	N	0.2787	42.20	QP	10.02	52.22	60.85	-8.63
4	N	0.2787	28.65	AVG	10.02	38.67	50.85	-12.18
5	N	0.2982	40.22	QP	10.02	50.24	60.29	-10.05
6	N	0.2982	25.99	AVG	10.02	36.01	50.29	-14.28
7	N	0.3489	38.14	QP	10.02	48.16	58.99	-10.83
8	N	0.3489	31.31	AVG	10.02	41.33	48.99	-7.66
9	N	0.3918	29.28	QP	10.02	39.30	58.03	-18.73
10	N	0.3918	15.18	AVG	10.02	25.20	48.03	-22.83
11	N	6.7128	26.88	QP	10.09	36.97	60.00	-23.03
12	N	6.7128	13.82	AVG	10.09	23.91	50.00	-26.09

## 6.9 Radiated Emissions

Temperature	23°C
Relative Humidity	54%
Atmospheric Pressure	1030mbar
Test date :	September 30, 2015
Tested By :	Winnie Zhang

### Requirement(s):

Spec	Item	Requirement	Applicable											
47CFR§15.205, §15.209, §15.247(d)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges												
		<table><tr><th>Frequency range (MHz)</th><th>Field Strength (µV/m)</th></tr><tr><td>30 – 88</td><td>100</td></tr><tr><td>88 – 216</td><td>150</td></tr><tr><td>216 960</td><td>200</td></tr><tr><td>Above 960</td><td>500</td></tr></table>		Frequency range (MHz)	Field Strength (µV/m)	30 – 88	100	88 – 216	150	216 960	200	Above 960	500	
		Frequency range (MHz)		Field Strength (µV/m)										
		30 – 88		100										
		88 – 216		150										
		216 960		200										
Above 960	500													

Test Setup	
------------	--

Procedure	<ol style="list-style-type: none"> <li>The EUT was switched on and allowed to warm up to its normal operating condition.</li> <li>The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: <ol style="list-style-type: none"> <li>Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen.</li> </ol> </li> </ol>
-----------	---

Test Report	15070843-FCC-R2
Page	43 of 59

	<p>b. The EUT was then rotated to the direction that gave the maximum emission.</p> <p>c. Finally, the antenna height was adjusted to the height that gave the maximum emission.</p> <p>3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz.</p> <p>4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</p> <p>5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

**Test Mode:** Bluetooth Mode

**Below 1GHz**




**Test Data**

**Horizontal Polarity Plot @3m**

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	( )
1	H	73.1025	46.37	peak	-13.68	32.69	40.00	-7.31	100	179
2	H	77.3212	41.47	peak	-13.76	27.71	40.00	-12.29	100	191
3	H	83.2298	40.40	peak	-13.60	26.80	40.00	-13.20	100	179
4	H	130.8369	34.60	peak	-7.98	26.62	43.50	-16.88	100	206
5	H	208.5803	33.62	peak	-8.81	24.81	43.50	-18.69	100	217
6	H	280.0238	34.49	peak	-7.82	26.67	46.00	-19.33	100	232

### Below 1GHz



### Test Data

#### Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	( )
1	V	50.9420	44.64	peak	-13.28	31.36	40.00	-8.64	100	338
2	V	67.2022	43.10	peak	-13.81	29.29	40.00	-10.71	100	124
3	V	78.6149	42.46	QP	-13.75	28.71	40.00	-11.29	100	169
4	V	83.0192	43.85	QP	-13.61	30.24	40.00	-9.76	100	117
5	V	128.5630	34.46	peak	-7.85	26.61	43.50	-16.89	100	169
6	V	277.0935	35.22	peak	-7.95	27.27	46.00	-18.73	100	210

Test Mode:	Transmitting Mode
------------	-------------------

Mode: GFSK (Worst Case)

Low Channel (2402 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4804	38.22	AV	V	33.83	6.86	31.72	47.19	54	-6.81
4804	37.69	AV	H	33.83	6.86	31.72	46.66	54	-7.34
4804	46.15	PK	V	33.83	6.86	31.72	55.12	74	-18.88
4804	45.63	PK	H	33.83	6.86	31.72	54.60	74	-19.40

Middle Channel (2441 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4882	38.16	AV	V	33.86	6.82	31.82	47.02	54	-6.98
4882	37.81	AV	H	33.86	6.82	31.82	46.67	54	-7.33
4882	46.09	PK	V	33.86	6.82	31.82	54.95	74	-19.05
4882	45.52	PK	H	33.86	6.82	31.82	54.38	74	-19.62

High Channel (2480 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4960	38.07	AV	V	33.9	6.76	31.92	46.81	54	-7.19
4960	37.85	AV	H	33.9	6.76	31.92	46.59	54	-7.41
4960	46.12	PK	V	33.9	6.76	31.92	54.86	74	-19.14
4960	45.58	PK	H	33.9	6.76	31.92	54.32	74	-19.68

## Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
<b>AC Line Conducted</b>					
EMI test receiver	ESCS30	8471241027	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191106	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191107	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>
LISN	ISN T800	34373	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	<input checked="" type="checkbox"/>
Transient Limiter	LIT-153	531118	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
<b>RF conducted test</b>					
Agilent ESA-E SERIES	E4407B	MY45108319	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
<b>Radiated Emissions</b>					
EMI test receiver	ESL6	100262	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Positioning Controller	UC3000	MF780208282	11/20/2014	11/19/2015	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/25/2015	03/24/2016	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/21/2015	09/20/2016	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/25/2015	09/23/2016	<input checked="" type="checkbox"/>




## Annex B. EUT And Test Setup Photographs

### Annex B.i. Photograph: EUT External Photo



Whole Package - Top View



Adapter - Front View



EUT - Front View



EUT - Rear View



Test Report	15070843-FCC-R2
Page	49 of 59



EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View



## Annex B.ii. Photograph: EUT Internal Photo



Cover Off - Top View 1




Cover Off - Top View 2



Cover Off - Top View 3



Battery - Front View




Battery - Rear View




Backup Battery- Front View




Test Report	15070843-FCC-R2
Page	51 of 59




Backup Battery- Rear View




Mainboard With Shielding - Front View




Mainboard Without Shielding - Front View



Mainboard - Rear View




LCD - Front View




LCD - Rear View






GSM/PCS/UMTS-FDD Antenna View



WIFI/BT/BLE - Antenna View



GPS - Antenna View


**Annex B.iii. Photograph: Test Setup Photo**




Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above  
1GHz


## Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

### Annex C.ii. TEST SET UP BLOCK


#### Block Configuration Diagram for AC Line Conducted Emissions



**Block Configuration Diagram for Radiated Emissions ( Below 1GHz ) .**



**Block Configuration Diagram for Radiated Emissions ( Above 1GHz ) .**





## **Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION**

The following is a description of supporting equipment and details of cables used with the EUT.

Manufacturer	Equipment Description	Model	Calibration Date	Calibration Due Date
N/A	N/A	N/A	N/A	N/A

Test Report	15070843-FCC-R2
Page	58 of 59

## Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see attachment

Test Report	15070843-FCC-R2
Page	59 of 59

## Annex E. DECLARATION OF SIMILARITY

N/A