

# FCC TEST REPORT

For

Jiangmen Yuanmeidao Technology Co., Ltd.

REMOTE AIR PRO

Model No.: REMOTE AIR PRO, PD3-P1, PD3-P2, PD3-P3, PD3-S1, PD3-S2, PD3-S3,  
PD3-X1, PD3-X2, PD3-X3, PD3-T, PD3-R, PD3-M, PD3-B, PD3-TS,  
PD3-RS, PD3-MS, PD3-BS, PD3-TX, PD3-RX, PD3-MX, PD3-BX

Prepared For : Jiangmen Yuanmeidao Technology Co., Ltd.  
Address : Room 605-606, Building 2, Huoju Technopark, No.10 West St.,  
Huangzhuang, Jiangmen, China

Prepared By : Shenzhen Anbotek Compliance Laboratory Limited  
Address : 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road, Nanshan  
District, Shenzhen, Guangdong, China  
Tel: (86) 755-26066544 Fax: (86) 755-26014772

Report Number : R0117020727W2  
Date of Test : Feb. 24~Apr. 07, 2017  
Date of Report : Apr. 10, 2017

# Contents

1. General Information.....	5
1.1. Client Information.....	5
1.2. Description of Device (EUT).....	5
1.3. Auxiliary Equipment Used During Test.....	5
1.4. Description of Test Modes.....	6
1.5. List of channels.....	6
1.6. Description Of Test Setup.....	7
1.7. Test Equipment List.....	8
1.8. Measurement Uncertainty.....	8
1.9. Description of Test Facility.....	9
2. Summary of Test Results.....	10
3. Conducted Emission Test.....	11
3.1. Test Standard and Limit.....	11
3.2. Test Setup.....	11
3.3. Test Procedure.....	11
3.4. Test Data.....	11
4. Radiation Spurious Emission and Band Edge.....	16
4.1. Test Standard and Limit.....	16
4.2. Test Setup.....	16
4.3. Test Procedure.....	17
4.4. Test Data.....	18
5. Output Power Test.....	25
5.1. Test Standard and Limit.....	25
5.2. Test Setup.....	25
5.3. Test Procedure.....	25
5.4. Test Data.....	25
6. Dutycycle.....	26
7. 6DB Occupy Bandwidth Test.....	28
7.1. Test Standard and Limit.....	28
7.2. Test Setup.....	28
7.3. Test Procedure.....	28
7.4. Test Data.....	28
8. Power Spectral Density Test.....	31
8.1. Test Standard and Limit.....	31
8.2. Test Setup.....	31
8.3. Test Procedure.....	31
8.4. Test Data.....	31
9. 100kHz Bandwidth of Frequency Band Edge Requirement.....	34
9.1. Test Standard and Limit.....	34
9.2. Test Setup.....	34
9.3. Test Procedure.....	34
9.4. Test Data.....	34

10. Antenna Requirement.....	36
10.1. Test Standard and Requirement.....	36
10.2. Antenna Connected Construction.....	36
APPENDIX I -- TEST SETUP PHOTOGRAPH.....	38
APPENDIX II -- EXTERNAL PHOTOGRAPH.....	40
APPENDIX III -- INTERNAL PHOTOGRAPH.....	44

Anbotech

## TEST REPORT

Applicant : Jiangmen Yuanmeidao Technology Co., Ltd.  
Manufacturer : Jiangmen Yuanmeidao Technology Co., Ltd.  
Product Name : REMOTE AIR PRO  
Model No. : REMOTE AIR PRO, PD3-P1, PD3-P2, PD3-P3, PD3-S1, PD3-S2, PD3-S3, PD3-X1,  
PD3-X2, PD3-X3, PD3-T, PD3-R, PD3-M, PD3-B, PD3-TS, PD3-RS, PD3-MS,  
PD3-BS, PD3-TX, PD3-RX, PD3-MX, PD3-BX  
Trade Mark : PDMOVIE  
Rating(s) : Input DC 5V ( Battery: DC 3.7V, 6000mAh)

**Test Standard(s) : FCC Part15 Subpart C 2016, Section 15.247**

**Test Method(s) : ANSI C63.10: 2013, KDB558074 D01 DTS Meas Guidance v04**

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Test : Feb. 24~Apr. 07, 2017

Prepared by :



*Kyle Xu*  
(Tested Engineer / Kyle Xu)

Reviewer :

*Brown Lu*  
(Project Manager / Brown Lu)

Approved & Authorized Signer :

*Tom Chen*  
(Manager / Tom Chen)

## 1. General Information

### 1.1. Client Information

Applicant	:	Jiangmen Yuanmeidao Technology Co., Ltd.
Address	:	Room 605-606, Building 2, Huoju Technopark, No.10 West St., Huangzhuang, Jiangmen, China
Manufacturer	:	Jiangmen Yuanmeidao Technology Co., Ltd.
Address	:	Room 605-606, Building 2, Huoju Technopark, No.10 West St., Huangzhuang, Jiangmen, China

### 1.2. Description of Device (EUT)

Product Name	:	REMOTE AIR PRO
Model No.	:	REMOTE AIR PRO, PD3-P1, PD3-P2, PD3-P3, PD3-S1, PD3-S2, PD3-S3, PD3-X1, PD3-X2, PD3-X3, PD3-T, PD3-R, PD3-M, PD3-B, PD3-TS, PD3-RS, PD3-MS, PD3-BS, PD3-TX, PD3-RX, PD3-MX, PD3-BX (Note: All samples are the same except the model number and colour, so we prepare "REMOTE AIR PRO" for test only.)
Trade Mark	:	PDMOVIE
Test Power Supply	:	AC 120V, 60Hz for adapter/AC 240V, 60Hz for adapter/ DC 3.7V By Battery
Product Description	Operation Frequency:	BT4.0: 2402MHz~2480MHz 2.4G: 2405MHz~2480MHz
	Number of Channel:	BT4.0: 40 Channels 2.4G: 16 Channels
	Modulation Type:	BT4.0: GFSK 2.4G: GFSK
	Antenna Type:	BT4.0: PCB Antenna 2.4G: External Antenna
	Antenna Gain(Peak):	BT4.0: 2.0dBi 2.4G: 2.33dbi
<b>Remark:</b> 1)For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. 2)This report is for 2.4G		

### 1.3. Auxiliary Equipment Used During Test

Adapter	:	Model No.: 1621 Input: 100-240V~, 50/60Hz, 0.18A Output: DC 5V, 1.2A
---------	---	--

## 1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH01
Mode 2	CH08
Mode 3	CH16
Mode 4	Keeping TX mode

For Conducted Emission	
Final Test Mode	Description
Mode 4	Keeping TX mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH01
Mode 2	CH08
Mode 3	CH16

Note:


- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2)The data rate was set in 1Mbps for radiated emission due to the highest RF output power.

## 1.5. List of channels


Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
01	2405	05	2425	09	2445	13	2465
02	2410	06	2430	10	2450	14	2470
03	2415	07	2435	11	2455	15	2475
04	2420	08	2440	12	2460	16	2480

## 1.6. Description Of Test Setup

CE



RE



## 1.7. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Two-Line V-network	Rohde & Schwarz	ENV216	100055	Jul. 19, 2016	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Jun. 17, 2016	1 Year
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Jun. 17, 2016	1 Year
4.	Spectrum Analysis	Agilent	E4407B	US39390582	Jul. 12, 2016	1 Year
5	Preamplifier	Instruments corporation	EMC011830	980100	Jun. 17, 2016	1 Year
6.	EMI Test Receiver	Rohde & Schwarz	ESPI	101604	Jun. 17, 2016	1 Year
7.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	May 06, 2016	1 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	May 06, 2016	1 Year
9.	Loop Antenna	Schwarzbeck	FMZB1519	012	May 11, 2016	1 Year
10.	Pre-amplifier	SONOMA	310N	186860	Jun. 17, 2016	1 Year
11	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
12.	Power Sensor	Agilent	KFSW150502	15I00041SN045	Jun. 17, 2016	1 Year
13.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Jun. 17, 2016	1 Year
14.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Jun. 17, 2016	1 Year
15	Signal Generator	Agilent	E4421B	MY41000743	Jun. 17, 2016	1 Year
16.	DC Power supply	IV	IV-8080	YQSB0096	Jun. 17, 2016	1 Year
17.	TEMP&HUMI PROGRAMMABLE CHAMBER	Bell Group	BE-THK-150 M8	SE-0137	Jun. 17, 2016	1 Year
14	Power Meter	Anritsu	ML2495A	1204003	Jun. 17, 2016	1 Year
15	Power Sensor	Anritsu	MA2411B	1126150	Jun. 17, 2016	1 Year

## 1.8. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 4.1 dB (Horizontal)
		Ur = 4.3 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4dB



## 1.9. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

### **FCC-Registration No.: 752021**

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 752021, July 06, 2016.

### **IC-Registration No.: 8058A-1**

Shenzhen Anbotek Compliance Laboratory Limited., EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration 8058A, June 13, 2016.

### **Test Location**

All Emissions tests were performed at

Shenzhen Anbotek Compliance Laboratory Limited. at 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road, Nanshan District, Shenzhen, Guangdong, China

## 2. Summary of Test Results

Standard Section	Test Item	Result
15.203/15.247(c)	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209	Spurious Emission	PASS
15.247(b)(3)	Maximum Peak Output Power	PASS
15.247(a)(2)	6dB Occupied Bandwidth	PASS
15.247(e)	Power Spectral Density	PASS
15.247(d)	Band Edge	PASS
<b>Remark:</b> “N/A” is an abbreviation for Not Applicable.		


### 3. Conducted Emission Test

#### 3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50

**Remark:** (1) \*Decreasing linearly with logarithm of the frequency.  
(2) The lower limit shall apply at the transition frequency.

#### 3.2. Test Setup



#### 3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.


The frequency range from 150kHz to 30MHz is checked.

#### 3.4. Test Data

Please to see the following pages

## Conducted Emission Test Data


Test Site: 1# Shielded Room  
Operating Condition: Keeping TX mode  
Test Specification: AC 120V, 60Hz for adapter  
Comment: Live Line  
Tem.:25℃ Hum.:50%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1539	41.13	19.90	61.03	65.78	-4.75	QP	
2	0.1539	30.33	19.90	50.23	55.78	-5.55	AVG	
3	0.2340	23.98	19.89	43.87	52.30	-8.43	AVG	
4	0.2900	33.64	19.89	53.53	60.52	-6.99	QP	
5	0.3140	17.95	19.90	37.85	49.86	-12.01	AVG	
6	0.3899	26.84	19.93	46.77	58.06	-11.29	QP	
7	0.4740	25.38	19.97	45.35	56.44	-11.09	QP	
8	0.4740	10.12	19.97	30.09	46.44	-16.35	AVG	
9	0.5780	20.87	20.00	40.87	56.00	-15.13	QP	
10	27.3500	24.14	20.28	44.42	60.00	-15.58	QP	
11	27.3500	11.80	20.28	32.08	50.00	-17.92	AVG	
12	28.0460	11.63	20.27	31.90	50.00	-18.10	AVG	

## Conducted Emission Test Data


Test Site: 1# Shielded Room  
Operating Condition: Keeping TX mode  
Test Specification: AC 120V, 60Hz for adapter  
Comment: Neutral Line  
Tem.:25℃ Hum.:50%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1539	41.95	19.90	61.85	65.78	-3.93	QP	
2	0.1580	32.21	19.90	52.11	55.56	-3.45	AVG	
3	0.2380	34.56	19.89	54.45	62.16	-7.71	QP	
4	0.2380	24.32	19.89	44.21	52.16	-7.95	AVG	
5	0.3180	15.47	19.90	35.37	49.76	-14.39	AVG	
6	0.3899	25.37	19.93	45.30	58.06	-12.76	QP	
7	0.4660	23.39	19.96	43.35	56.58	-13.23	QP	
8	0.4700	6.57	19.97	26.54	46.51	-19.97	AVG	
9	0.6260	17.50	20.02	37.52	56.00	-18.48	QP	
10	1.5140	12.47	20.13	32.60	56.00	-23.40	QP	
11	27.3460	8.49	20.28	28.77	50.00	-21.23	AVG	
12	28.0500	8.59	20.27	28.86	50.00	-21.14	AVG	

## Conducted Emission Test Data


Test Site: 1# Shielded Room  
Operating Condition: Keeping TX mode  
Test Specification: AC 240V, 60Hz for adapter  
Comment: Live Line  
Tem.:25℃ Hum.:50%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1532	43.36	19.90	63.26	65.82	-2.56	QP	
2	0.1539	33.77	19.90	53.67	55.78	-2.11	AVG	
3	0.2300	27.77	19.89	47.66	52.45	-4.79	AVG	
4	0.3060	22.76	19.89	42.65	50.08	-7.43	AVG	
5	0.3140	34.86	19.90	54.76	59.86	-5.10	QP	
6	0.4620	13.66	19.96	33.62	46.66	-13.04	AVG	
7	0.4699	28.68	19.97	48.65	56.52	-7.87	QP	
8	0.5819	23.60	20.00	43.60	56.00	-12.40	QP	
9	25.9420	22.52	20.28	42.80	60.00	-17.20	QP	
10	25.9420	11.41	20.28	31.69	50.00	-18.31	AVG	
11	26.6460	10.80	20.28	31.08	50.00	-18.92	AVG	
12	27.3419	22.65	20.28	42.93	60.00	-17.07	QP	

### Conducted Emission Test Data

Test Site: 1# Shielded Room  
Operating Condition: Keeping TX mode  
Test Specification: AC 240V, 60Hz for adapter  
Comment: Neutral Line  
Tem.:25℃ Hum.:50%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1539	41.33	19.90	61.23	65.78	-4.55	QP	
2	0.1539	30.26	19.90	50.16	55.78	-5.62	AVG	
3	0.2300	39.53	19.89	59.42	62.45	-3.03	QP	
4	0.2300	24.86	19.89	44.75	52.45	-7.70	AVG	
5	0.3059	35.67	19.89	55.56	60.08	-4.52	QP	
6	0.3060	20.00	19.89	39.89	50.08	-10.19	AVG	
7	0.4580	12.32	19.96	32.28	46.73	-14.45	AVG	
8	0.4620	27.88	19.96	47.84	56.66	-8.82	QP	
9	0.6139	20.13	20.01	40.14	56.00	-15.86	QP	
10	0.6140	6.56	20.01	26.57	46.00	-19.43	AVG	
11	1.4499	17.76	20.13	37.89	56.00	-18.11	QP	
12	26.6420	9.87	20.28	30.15	50.00	-19.85	AVG	

## 4. Radiation Spurious Emission and Band Edge

### 4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

**Remark:**

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

### 4.2. Test Setup




Figure 1. Below 30MHz






Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

### 4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9\*6\*6 Chamber. The device is evaluated in xyz orientation.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW = 300kHz, Detector = Quasi-Peak, Trace mode = Max hold, Sweep = auto couple.

For above 1GHz, Set the spectrum analyzer as:

RBW = 1MHz, VBW = 10Hz, Detector = Peak, Trace mode = Max hold, Sweep = auto couple.

#### **4.4. Test Data**


##### **PASS**

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.

The test results of 9kHz-30MHz and above 18000MHz are attenuated more than 20dB below the permissible limits, so the results don't record in the report.


**Test Results (30~1000MHz)**

Job No.: 0117020727W Temp.(°C)/Hum.(%RH): 24.3°C/55%RH  
Standard: FCC PART 15C Power Source: AC 120V, 60Hz for adapter  
Test Mode: TX Mode Polarization: Horizontal



**Test Results (30~1000MHz)**

Job No.: 0117020727W Temp.(°C)/Hum.(%RH): 24.3°C/55%RH  
Standard: FCC PART 15C Power Source: AC 120V, 60Hz for adapter  
Test Mode: TX Mode Polarization: Vertical



### Test Results (Above 1000MHz)

Test Mode: TX Mode					Test channel: Lowest			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4810.00	38.72	34.04	6.58	34.09	45.25	74.00	-28.75	V
7215.00	32.77	37.11	7.73	34.50	43.11	74.00	-30.89	V
9620.00	32.30	39.31	9.23	34.79	46.05	74.00	-27.95	V
12025.00	*					74.00		V
14430.00	*					74.00		V
4810.00	43.30	34.04	6.58	34.09	49.83	74.00	-24.17	H
7215.00	34.65	37.11	7.73	34.50	44.99	74.00	-29.01	H
9620.00	31.86	39.31	9.23	34.79	45.61	74.00	-28.39	H
12025.00	*					74.00		H
14430.00	*					74.00		H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4810.00	27.27	34.04	6.58	34.09	33.80	54.00	-20.20	V
7215.00	21.30	37.11	7.73	34.50	31.64	54.00	-22.36	V
9620.00	20.28	39.31	9.23	34.79	34.03	54.00	-19.97	V
12025.00	*					54.00		V
14430.00	*					54.00		V
4810.00	31.65	34.04	6.58	34.09	38.18	54.00	-15.82	H
7215.00	23.56	37.11	7.73	34.50	33.90	54.00	-20.10	H
9620.00	20.13	39.31	9.23	34.79	33.88	54.00	-20.12	H
12025.00	*					54.00		H
14430.00	*					54.00		H

### Test Results (Above 1000MHz)

Test Mode: TX Mode					Test channel: Middle			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4880.00	36.96	34.38	6.69	34.09	43.94	74.00	-30.06	V
7320.00	31.60	37.22	7.78	34.53	42.07	74.00	-31.93	V
9760.00	31.27	39.46	9.35	34.80	45.28	74.00	-28.72	V
12200.00	*					74.00		V
14640.00	*					74.00		V
4880.00	41.18	34.38	6.69	34.09	48.16	74.00	-25.84	H
7320.00	33.33	37.22	7.78	34.53	43.80	74.00	-30.20	H
9760.00	30.66	39.46	9.35	34.80	44.67	74.00	-29.33	H
12200.00	*					74.00		H
14640.00	*					74.00		H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4880.00	25.85	34.38	6.69	34.09	32.83	54.00	-21.17	V
7320.00	20.34	37.22	7.78	34.53	30.81	54.00	-23.19	V
9760.00	19.43	39.46	9.35	34.80	33.44	54.00	-20.56	V
12200.00	*					54.00		V
14640.00	*					54.00		V
4880.00	30.05	34.38	6.69	34.09	37.03	54.00	-16.97	H
7320.00	22.49	37.22	7.78	34.53	32.96	54.00	-21.04	H
9760.00	19.14	39.46	9.35	34.80	33.15	54.00	-20.85	H
12200.00	*					54.00		H
14640.00	*					54.00		H

### Test Results (Above 1000MHz)

Test Mode: TX Mode					Test channel: Highest			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4960.00	36.18	34.72	6.79	34.09	43.60	74.00	-30.40	V
7440.00	31.09	37.34	7.82	34.57	41.68	74.00	-32.32	V
9920.00	30.81	39.62	9.46	34.81	45.08	74.00	-28.92	V
12400.00	*					74.00		V
14880.00	*					74.00		V
4960.00	40.24	34.72	6.79	34.09	47.66	74.00	-26.34	H
7440.00	32.74	37.34	7.82	34.57	43.33	74.00	-30.67	H
9920.00	30.12	39.62	9.46	34.81	44.39	74.00	-29.61	H
12400.00	*					74.00		H
14880.00	*					74.00		H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4960.00	25.26	34.72	6.79	34.09	32.68	54.00	-21.32	V
7440.00	19.93	37.34	7.82	34.57	30.52	54.00	-23.48	V
9920.00	19.08	39.62	9.46	34.81	33.35	54.00	-20.65	V
12400.00	*					54.00		V
14880.00	*					54.00		V
4960.00	29.37	34.72	6.79	34.09	36.79	54.00	-17.21	H
7440.00	22.04	37.34	7.82	34.57	32.63	54.00	-21.37	H
9920.00	18.72	39.62	9.46	34.81	32.99	54.00	-21.01	H
12400.00	*					54.00		H
14880.00	*					54.00		H

Remark:

1. Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.

**Radiated Band Edge:**

Test Mode: GFSK					Test channel: Lowest			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
2390.00	45.18	29.15	3.41	34.01	43.73	74.00	-30.27	H
2400.00	47.90	29.16	3.43	34.01	46.48	74.00	-27.52	H
2390.00	45.95	29.15	3.41	34.01	44.50	74.00	-29.50	V
2400.00	45.85	29.16	3.43	34.01	44.43	74.00	-29.57	V
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
2390.00	35.21	29.15	3.41	34.01	33.76	54.00	-20.24	H
2400.00	34.18	29.16	3.43	34.01	32.76	54.00	-21.24	H
2390.00	35.32	29.15	3.41	34.01	33.87	54.00	-20.13	V
2400.00	35.18	29.16	3.43	34.01	33.76	54.00	-20.24	V

Test Mode: GFSK					Test channel: Highest			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
2483.50	47.56	29.28	3.53	34.03	46.34	74.00	-27.66	H
2500.00	46.29	29.30	3.56	34.03	45.12	74.00	-28.88	H
2483.50	48.79	29.28	3.53	34.03	47.57	74.00	-26.43	V
2500.00	47.51	29.30	3.56	34.03	46.34	74.00	-27.66	V
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
2483.50	38.07	29.28	3.53	34.03	36.85	54.00	-17.15	H
2500.00	35.74	29.30	3.56	34.03	34.57	54.00	-19.43	H
2483.50	39.47	29.28	3.53	34.03	38.25	54.00	-15.75	V
2500.00	35.85	29.30	3.56	34.03	34.68	54.00	-19.32	V

Remark:

1. Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor




## 5. Output Power Test

### 5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (b)(3)
Test Limit	30dBm

### 5.2. Test Setup



### 5.3. Test Procedure

1. The Transmitter output (antenna port) was connected to the power meter.
2. Turn on the EUT and power meter and then record the power value.
3. Repeat above procedures on all channels needed to be tested.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

### 5.4. Test Data

Test Item	: output power	Test Mode	: CH Low ~ CH High
Test Voltage	: AC 120V, 60Hz for adapter	Temperature	: 24°C
Test Result	: PASS	Humidity	: 55%RH

Channel Frequency (MHz)	Maximum Power output(AV) (dBm)	Limit (dBm)	Results
2405	<b>9.686</b>	30	PASS
2440	9.432	30	PASS
2480	9.317	30	PASS

For power test the duty cycle is 100% in continous transmitting mode

## 6. Dutycycle

### a. Test Procedure

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set  $RBW \geq OBW$  if possible; otherwise, set RBW to the largest available value.

Set  $VBW \geq RBW$ . Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are  $> 50/T$  and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if  $T \leq 16.7$  microseconds.)

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = Zero Span

RBW = 8MHz

VBW = 8MHz


Number of points in Sweep  $> 100$

Detector function = peak


Trace = Clear write Measure Ttotal and Ton

Calculate Duty Cycle =  $Ton / Ttotal$  and Duty Cycle Factor =  $10 \cdot \log(1/Duty\ Cycle)$

### b. TEST SETUP



Test plot of Duty Cycle for Middle Channel




## 7. 6dB Occupy Bandwidth Test

### 7.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(2)
Test Limit	>500kHz

### 7.2. Test Setup




### 7.3. Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:  
RBW = 100kHz, VBW  $\geq$  3\*RBW = 300kHz,  
Detector= Peak  
Trace mode= Max hold.  
Sweep- auto couple.
4. Mark the peak frequency and -6dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.


### 7.4. Test Data

Test Item	: 6dB Bandwidth	Test Mode	: CH Low ~ CH High
Test Voltage	: AC 120V, 60Hz for adapter	Temperature	: 24°C
Test Result	: PASS	Humidity	: 55%RH


Channel	Frequency(MHz)	Bandwidth (kHz)	Limit (kHz)	Results
Low	2405	980.3	>500	PASS
Middle	2440	982.7		PASS
High	2480	1016.0		PASS



CH: Low



CH: Middle



CH: High

## 8. Power Spectral Density Test

### 8.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (e)
Test Limit	8dBm

### 8.2. Test Setup




### 8.3. Test Procedure

1. Place the EUT on the table and set it in transmitting mode. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 1.5xDTS BW
3. Record the max. reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.


### 8.4. Test Data

Test Item	: Power Spectral Density	Test Mode	: CH Low ~ CH High
Test Voltage	: AC 120V, 60Hz for adapter	Temperature	: 24°C
Test Result	: PASS	Humidity	: 55%RH

Channel	Frequency (MHz)	PSD (dBm/3KHz)	Limit (dBm/3KHz)	Results
Low	2405	4.003	8.00	PASS
Middle	2440	3.318	8.00	PASS
High	2480	3.606	8.00	PASS




CH: Low



CH: Middle






CH: High

## 9. 100kHz Bandwidth of Frequency Band Edge Requirement

### 9.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (d)
Test Limit	in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

### 9.2. Test Setup



### 9.3. Test Procedure


Using the following spectrum analyzer setting:

1. Set the RBW = 100KHz.
2. Set the VBW = 300KHz.
3. Sweep time = auto couple.
4. Detector function = peak.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.


### 9.4. Test Data

Test Item	: Band edge	Test Mode	: CH Low ~ CH High
Test Voltage	: AC 120V, 60Hz for adapter	Temperature	: 24°C
Test Result	: PASS	Humidity	: 55%RH

Frequency Band (MHz)	Delta Peak to Band Emission (dBc)	Limit (dBc)	Results
2400	45.598	>30	PASS
2483.5	41.992	>30	PASS



CH: Low



CH: High

## 10. Antenna Requirement


### 10.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	<p>1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.</p>

### 10.2. Antenna Connected Construction

The bluetooth antenna is a external antenna which permanently attached, and the best case gain of the antenna is 2.33dbi. It complies with the standard requirement.







## APPENDIX I -- TEST SETUP PHOTOGRAPH

Photo of Conducted Emission Measurement







Photo of Radiation Emission Test






## APPENDIX II -- EXTERNAL PHOTOGRAPH













## APPENDIX III -- INTERNAL PHOTOGRAPH

