

FCC TEST REPORT  
for  
Jiangmen Yuanmeidao Technology Co., Ltd.

REMOTE AIR (Transmitter)  
Model No.: PD1, PD1-HT, PD2, PD2-HT, PD3-HT

Prepared for : Jiangmen Yuanmeidao Technology Co., Ltd.  
Address : Room 605-606, Building 2, Huoju Technopark, No.10 West St.,  
Huangzhuang, Jiangmen, China

Prepared By : Shenzhen Anbotech Compliance Laboratory Limited  
Address : 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road,  
Nanshan District, Shenzhen, Guangdong, China  
Tel: (86) 755-26066544  
Fax: (86) 755-26014772

Report Number : R011409085E  
Date of Test : Sept. 09~ Oct. 28, 2014  
Date of Report : Oct. 29, 2014

## TABLE OF CONTENT

Description

Page

Test Report

<b>1. GENERAL INFORMATION .....</b>	<b>4</b>
1.1. Description of Device (EUT).....	4
1.2. Auxiliary Equipment Used during Test .....	5
1.3. Description of Test Facility .....	5
1.4. Measurement Uncertainty .....	5
<b>2. TEST METHODOLOGY .....</b>	<b>6</b>
2.1. Summary of Test Results.....	6
2.2. Description of Test Modes.....	6
<b>3. FCC PART 15.247 REQUIREMENTS FOR DSSS &amp; OFDM MODULATION.....</b>	<b>7</b>
3.1 Test Setup .....	7
3.2 6dB Bandwidth .....	7
3.3. Maximum Peak output power test .....	10
3.4. Band Edges Measurement .....	13
3.5. Peak Power Spectral Density .....	16
3.6. Radiated Emissions.....	19
<b>4. PHOTOGRAPH.....</b>	<b>30</b>
4.1. Photo of Radiation Emission Test .....	30
<b>APPENDIX I (EXTERNAL PHOTOS).....</b>	<b>31</b>
<b>APPENDIX II (INTERNAL PHOTOS) .....</b>	<b>34</b>

APPENDIX I (External Photos) (3 pages)

APPENDIX II (Internal Photos) (3 pages)

## TEST REPORT

Applicant : Jiangmen Yuanmeidao Technology Co., Ltd.  
Manufacturer : Jiangmen Yuanmeidao Technology Co., Ltd.  
EUT : REMOTE AIR (Transmitter)  
Model No. : PD1, PD1-HT, PD2, PD2-HT, PD3-HT  
Serial No. : N.A.  
Trade Mark : pdmovie  
Rating : DC 3.7V


Measurement Procedure Used:  
FCC Part15 Subpart C, Paragraph 15.247

The device described above is tested by Shenzhen Anbotech Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotech Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.


This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotech Compliance Laboratory Limited.

Date of Test : Sept. 09~ Oct. 28, 2014


Prepared by :

  
(Tested Engineer / Kebo Zhang)

Reviewer :

  
(Project Manager / Amy Ding)

Approved & Authorized Signer :

  
(Manager / Tom Chen)

## 1. GENERAL INFORMATION

### 1.1. Description of Device (EUT)

EUT : REMOTE AIR (Transmitter)

Model Number : PD1, PD1-HT, PD2, PD2-HT, PD3-HT  
(Note: All samples are the same except the model number and appearance, so we prepare "PD1" for EMC test only.)

Test Power Supply : DC 3.7V

RF Transmission : Zigbee: 2405-2480MHz  
Frequency

No. of Channels : 16

Channel Space : 5MHz

Modulation : DSSS

Antenna Gain: : 5 dBi

Applicant : Jiangmen Yuanmeidao Technology Co., Ltd.  
Address : Room 605-606, Building 2, Huoju Technopark, No.10 West St.,  
Huangzhuang, Jiangmen, China

Manufacturer : Jiangmen Yuanmeidao Technology Co., Ltd.  
Address : Room 605-606, Building 2, Huoju Technopark, No.10 West St.,  
Huangzhuang, Jiangmen, China

Factory : Jiangmen Yuanmeidao Technology Co., Ltd.  
Address : Room 605-606, Building 2, Huoju Technopark, No.10 West St.,  
Huangzhuang, Jiangmen, China

Date of receipt : Sept. 05, 2014

Date of Test : Sept. 09~ Oct. 28, 2014

## 1.2. Auxiliary Equipment Used during Test

REMOTE AIR (Receiver) : PD1  
Adapter : P/N: 157-10130-00  
Input: AC 100-240V, 50/60Hz, 0.2A  
Output: DC 5.0V, 1.0A

## 1.3. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

### **CNAS - LAB Code: L3503**

Shenzhen Anbotek Compliance Laboratory Limited., Laboratory has been assessed and in compliance with CNAS/CL01: 2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

### **FCC-Registration No.: 752021**

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 752021, July 10, 2013.

### **IC-Registration No.: 8058A-1**

Shenzhen Anbotek Compliance Laboratory Limited., EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration 8058A, February 22, 2013.

### **Test Location**

All Emissions tests were performed at  
Shenzhen Anbotek Compliance Laboratory Limited. at 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road, Nanshan District, Shenzhen, Guangdong, China

## 1.4. Measurement Uncertainty

Radiation Uncertainty : Ur = 4.3dB  
Conduction Uncertainty : Uc = 3.4dB

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4: 2009 and FCC Part 15, Paragraph 15.247.

### 2.1. Summary of Test Results

The EUT has been tested according to the following specifications:

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.107, 15.207	Conducted Emission Test	PASS	Complies
FCC Part 15, Paragraph 15.247(b)(1)	Peak Output Power	PASS	Complies
FCC Part 15, Paragraph 15.247(a)(2)	6dB Bandwidth	PASS	Complies
FCC Part 15, Paragraph 15.247(c)	100kHz Bandwidth of Frequency Band Edges	PASS	Complies
FCC Part 15, Paragraph 15.209(a)(f)	Spurious Emission	PASS	Complies
FCC Part 15, Paragraph 15.247(a)(1)	Frequency Separation	-	N/A
FCC Part 15, Paragraph 15.247(a)(1)(iii)	Number of Hopping Frequency	-	N/A
FCC Part 15, Paragraph 15.247(a)(1)(iii)	Time of Occupancy	-	N/A
FCC Part 15, Paragraph 15.247(c)	Peak Power Density	PASS	Complies

### 2.2. Description of Test Modes

The EUT has been tested under operating condition.


Software used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2405	7	2435	13	2465
2	2410	8	2440	14	2470
3	2415	9	2445	15	2475
4	2420	10	2450	16	2480
5	2425	11	2455	--	--
6	2430	12	2460		

Channel 1(2405MHz), Channel 8(2440MHz) and Channel 16(2480MHz) are chosen for the final testing.

### 3. FCC Part 15.247 Requirements for DSSS & OFDM Modulation

#### 3.1 Test Setup



#### 3.2 6dB Bandwidth

##### a. Limit

For the direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz.

##### b. Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:  
RBW = 100kHz, VBW  $\geq$  3\*RBW = 300kHz,  
Detector= Peak  
Trace mode= Max hold.  
Sweep- auto couple.
4. Mark the peak frequency and -6dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

##### c. Test Setup See 3.1

##### d. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analysis	Agilent	E4407B	US39390582	Aug. 08, 2014	1 Year
2.	Preamplifier	Instruments corporation	EMC011830	980100	Aug. 08, 2014	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESPI	101604	Apr. 22, 2014	1 Year
4.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Apr. 04, 2014	1 Year
5.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Apr. 24, 2014	1 Year
6.	Pre-amplifier	SONOMA	310N	186860	Aug. 08, 2014	1 Year
7.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A

##### e. Test Results

Pass.


## f. Test Data

Test mode: IEEE 802.15.4

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Results
Low	2405	912		Pass
Mid	2440	920	>500	Pass
High	2480	904		Pass


Test Plots See the following page.

2405MHz:






2440MHz:



2480MHz:




### 3.3. Maximum Peak output power test

#### a. Limit

The maximum peak output power of the intentional radiator shall not exceed the following:

1. For systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 watt (30dBm).
2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antenna of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### b. Configuration of Measurement



#### c. Test Procedure

**This test was according the kDB 558074 9.2.2:**

1. This procedure may be used when the maximum available RBW of the measurement instrument is great than the DTS bandwidth.
2. Set the RBW = 3 MHz.
3. Set the VBW  $\geq 3 \times \text{RBW} = 10 \text{ MHz}$ .
4. Set the span  $\geq 3 \times \text{RBW}$ .
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select peak detector). If the instrument does not have a band power function, sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS bandwidth.

#### d. Test Equipment

Same as the equipment listed in 3.2.

#### e. Test Results


Pass.

**f. Test Data**


Test mode: IEEE 802.15.4

Channel	Frequency (MHz)	Maximum transmit power	Limit		Result
		(dBm)	(dBm)	(watts)	
Low	2405	21.56	30	1	Pass
Mid	2440	21.41			Pass
High	2480	20.98			Pass


2405MHz:



2440MHz:



2480MHz:



### 3.4. Band Edges Measurement

#### a. Limit

According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


#### b. Test Procedure

##### 1. Conducted Method:

- 1) Set RBW=100KHz, VBW=300KHz
- 2) Detector=peak
- 3) Sweep time= auto
- 4) Trace mode=max hold.

##### 2. Radiated Method:

- 1) The EUT is placed on a turntable, which is 0.8m above the ground plane.
- 2) The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3) EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
- 4) Peak detector: RBW=1MHz, VBW=3MHz, SWT=AUTO  
Average detector: RBW=1MHz, VBW=10Hz, SWT=AUTO  
The EUT is tested in 9\*6\*6 Chamber.
- 5) Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.



#### c. Test Equipment

Same as the equipment listed in 3.2.

#### d. Test Results

Pass.

#### e. Test Plots

See the following page.

Test Item	: Band eadge	Test Mode	: CH Low ~ CH High
Test Voltage	: DC 3.7V	Temperature	: 24℃
Test Result	: PASS	Humidity	: 55%RH



## 1. Conducted Test

Frequency (MHz)	Peak Power Output(dBm)	Emission read Value(dBm)	Result of Band edge(dBc)	Band edge Limit(dBc)
<2400	18.18	-35.19	53.37	>30dBc
>2483.5	17.27	-26.96	44.23	>30dBc

## 2. Radiated emission Test

Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)	
		PK	AV	PK	AV
<2400	V	56.65	36.45	74.00	54.00
	H	52.42	37.51	74.00	54.00
>2483.5	V	50.81	37.49	74.00	54.00
	H	53.03	35.32	74.00	54.00

Test Mode: IEEE 802.15.4



### 3.5. Peak Power Spectral Density

#### a. Limit

1. For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.
2. The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

#### b. Test Procedure

1. Place the EUT on the table and set it in transmitting mode. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 1.5MHz, Sweep=500s
3. Record the max. reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.

#### c. Test Equipment

Same as the equipment listed in 3.2.

#### d. Test Setup

See 3.1

#### e. Test Results

Pass

#### f. Test Data

Please refer to the following data.

#### g. Test Plot


 See the following pages

Test mode: IEEE 802.15.4


Channel	Frequency (MHz)	PPSD (dBm/3KHz)	ΣPPSD (dBm/3KHz)	Limit (dBm)	Result
Low	2405	5.87	-	8.00	Pass
Mid	2440	5.11	-		Pass
High	2480	4.23	-		Pass




2405MHz:



2440MHz:



2480MHz:



### 3.6. Radiated Emissions

#### 3.6.1.1. Test Limits (< 30 MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meter)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

#### 3.6.1.2. Test Limits ( $\geq$ 30 MHz)

FIELD STRENGTH of Fundamental: @3M	FIELD STRENGTH of Harmonics	S15.209 30 - 88 MHz	40 dBuV/m
902-928 MHz		88 - 216 MHz	43.5
2.4-2.4835 GHz		216 - 960 MHz	46
94 dBuV/m @3m	54 dBuV/m @3m	ABOVE 960 MHz	54dBuV/m


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

#### Test Equipment


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analysis	Agilent	E4407B	US39390582	Aug. 08, 2014	1 Year
2.	Preamplifier	Instruments corporation	EMC011830	980100	Aug. 08, 2014	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESPI	101604	Apr. 22, 2014	1 Year
4.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Apr. 04, 2014	1 Year
5.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Apr. 24, 2014	1 Year
6.	Pre-amplifier	SONOMA	310N	186860	Aug. 08, 2014	1 Year
7.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A

### 3.6.2. Test Configuration:


Block diagram of connection between the EUT and simulators




#### 3.6.2.1. 9k to 30MHz emissions:



#### 3.6.2.2. 30M to 1G emissions:



#### 3.6.2.3. 1G to 40G emissions:



#### 3.6.3. Test Procedure

The EUT is placed on a turn table which is 0.8 meter high above the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

Measurements are made on 9KHz to 30MHz and 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.

All readings from 30MHz to 1GHz are quasi-peak values with a resolution bandwidth of 120kHz. All reading are above 1GHz, peak & average values with a resolution bandwidth of 1MHz.

The EUT is tested in 9\*6\*6 Chamber.


The test results are listed in Section 3.6.4.

#### 3.6.4. Test Results

PASS.


Please refer to the following pages.

Job No.:	011409085E	Polarization:	Horizontal
Standard:	(RE)FCC PART15 C _3m	Power Source:	DC 3.7V
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.3(C)/55%RH
Test Mode:	On	Distance:	3m




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	36.3814	36.81	-13.21	23.60	40.00	-16.40	peak			
2	59.2325	33.34	-15.32	18.02	40.00	-21.98	peak			
3	84.9995	33.59	-20.35	13.24	40.00	-26.76	peak			
4	218.3085	40.16	-20.17	19.99	46.00	-26.01	peak			
5	519.0649	32.70	-11.00	21.70	46.00	-24.30	peak			
6	982.6200	34.76	-3.42	31.34	54.00	-22.66	peak			

Job No.:	011409085E	Polarization:	Vertical
Standard:	(RE)FCC PART15 C _3m	Power Source:	DC 3.7V
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.3(C)/55%RH
Test Mode:	On	Distance:	3m



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	38.0783	42.12	-11.88	30.24	40.00	-9.76	peak			
2	64.6594	38.56	-17.33	21.23	40.00	-18.77	peak			
3	71.8320	39.03	-19.98	19.05	40.00	-20.95	peak			
4	80.9275	39.08	-19.68	19.40	40.00	-20.60	peak			
5	218.3085	35.16	-15.17	19.99	46.00	-26.01	peak			
6	982.6200	33.76	-2.42	31.34	54.00	-22.66	peak			


<b>Job No.:</b>	<b>011409085E</b>	<b>Polarization:</b>	<b>Horizontal</b>
<b>Standard:</b>	<b>(RE)FCC PART15 C _3m</b>	<b>Power Source:</b>	<b>DC 3.7V</b>
<b>Test item:</b>	<b>Radiation Test</b>	<b>Temp.(C)/Hum.(%RH):</b>	<b>24.3(C)/55%RH</b>
<b>Note:</b>	<b>2405MHz</b>	<b>Distance:</b>	<b>3m</b>



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	7205.000	49.64	8.43	58.07	74.00	-15.93	peak			
2	7205.000	40.44	8.43	48.87	54.00	-5.13	AVG			
3	9627.500	43.77	9.64	53.41	74.00	-20.59	peak			
4	9627.500	34.34	9.64	43.98	54.00	-10.02	AVG			




Job No.:	011409085E	Polarization:	Vertical
Standard:	(RE)FCC PART15 C_3m	Power Source:	DC 3.7V
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.3(C)/55%RH
Note:	2405MHz	Distance:	3m




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	4825.000	49.03	3.34	52.37	74.00	-21.63	peak			
2	4825.000	39.40	3.34	42.74	54.00	-11.26	AVG			
3	8097.500	36.16	9.66	45.82	74.00	-28.18	peak			
4	8097.500	25.98	9.66	35.64	54.00	-18.36	AVG			

Job No.:	011409085E	Polarization:	Horizontal
Standard:	(RE)FCC PART15 C _3m	Power Source:	DC 3.7V
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.3(C)/55%RH
Note:	2440MHz	Distance:	3m




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	7332.500	52.24	8.58	60.82	74.00	-13.18	peak			
2	7332.500	42.16	8.58	50.74	54.00	-3.26	AVG			
3	12220.000	45.27	12.36	57.63	74.00	-16.37	peak			
4	12220.000	35.61	12.36	47.97	54.00	-6.03	AVG			

Job No.:	011409085E	Polarization:	Vertical
Standard:	(RE)FCC PART15 C _3m	Power Source:	DC 3.7V
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.3(C)/55%RH
Note:	2440MHz	Distance:	3m




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	4867.500	53.41	3.41	56.82	74.00	-17.18	peak			
2	4867.500	43.34	3.41	46.75	54.00	-7.25	AVG			
3	7332.500	43.26	8.58	51.84	74.00	-22.16	peak			
4	7332.500	33.28	8.58	41.86	54.00	-12.14	AVG			

Job No.:	011409085E	Polarization:	Horizontal
Standard:	(RE)FCC PART15 C _3m	Power Source:	DC 3.7V
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.3(C)/55%RH
Note:	2480MHz	Distance:	3m



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	4952.500	56.64	3.57	60.21	74.00	-13.79	peak			
2	4952.500	46.54	3.57	50.11	54.00	-3.89	AVG			
3	7460.000	50.16	8.73	58.89	74.00	-15.11	peak			
4	7460.000	39.92	8.73	48.65	54.00	-5.35	AVG			


Job No.:	011409085E	Polarization:	Vertical
Standard:	(RE)FCC PART15 C _3m	Power Source:	DC 3.7V
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.3(C)/55%RH
Note:	2480MHz	Distance:	3m



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	4952.500	55.88	3.57	59.45	74.00	-14.55	peak			
2	4952.500	46.17	3.57	49.74	54.00	-4.26	AVG			
3	6610.000	41.47	7.73	49.20	74.00	-24.80	peak			
4	6610.000	32.16	7.73	39.89	54.00	-14.11	AVG			

## 4. PHOTOGRAPH

### 4.1. Photo of Radiation Emission Test





## APPENDIX I (EXTERNAL PHOTOS)

Figure 1  
The EUT-Top View




Figure 2  
The EUT-Bottom View



Figure 3  
The EUT-Front View




Figure 4  
The EUT-Back View





Figure 5  
The EUT-Right View



Figure 6  
The EUT-Left View



## APPENDIX II (INTERNAL PHOTOS)

Figure 7  
The EUT-Inside View



Figure 8  
PCB of the EUT-Front View






Figure 9  
PCB of the EUT-Back View




Figure 10  
PCB of the Module View




Figure 11  
PCB of the EUT-Front View



Figure 12  
PCB of the EUT-Back View

