Report Number: D60501R1

FCC PART 15 SUBPART C SECTION 15.247

&

RSS 247, RSS GEN TEST REPORT

for

BLE MODULE

Model: ATSAMB11-ZR210CA

Prepared for

MICROCHIP TECHNOLOGY INC. 2355 W Chandler Blvd. CHANDLER, AZ 85224

Prepared by:	
1	

MATT HARRISON

Reviewed by: _____

JOEY MADLANGBAYAN

COMPATIBLE ELECTRONICS INC. 20621 PASCAL WAY LAKE FOREST, CALIFORNIA 92630 (949) 587-0400

DATE: MAY 1st, 2016

	REPORT		APPENDICES			TOTAL	
	BODY	\boldsymbol{A}	В	C	D	E	
PAGES	19	2	2	2	15	37	77

This report shall not be reproduced except in full, without the written approval of Compatible Electronics.



FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report

TABLE OF CONTENTS

Section / Title	PAGE
GENERAL REPORT SUMMARY	4
1. PURPOSE	6
2. ADMINISTRATIVE DATA	7
2.1 Location of Testing	7
2.2 Traceability Statement	
2.3 Cognizant Personnel	7 7
2.4 Date Test Sample was Received	7
2.5 Disposition of the Test Sample	7
2.6 Abbreviations and Acronyms	7
3. APPLICABLE DOCUMENTS	8
4. DESCRIPTION OF TEST CONFIGURATION	9
4.1 Description of Test Configuration	9
4.1.1 Photograph Test Configuration (X-Axis Shown)	9
4.1.2 Cable Construction and Termination	10
5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT	11
5.1 EUT and Accessory List 5.2 EMI Test Equipment	11
1 1	12
6. TEST SITE DESCRIPTION 6.1 Test English Description	13
6.1 Test Facility Description6.2 EUT Mounting, Bonding and Grounding	13 13
6.3 Facility Environmental Characteristics	13
7. CHARACTERISTICS OF THE TRANSMITTER7.1 Channel Number and Frequencies	14 14
7.1 Channel Number and Frequencies 7.2 Antenna	14
8. TEST PROCEDURES	15
8.1 RF Emissions	15
8.1.1 Conducted Emissions Test	15
8.1.2 Radiated Emissions (Spurious and Harmonics) Test	16
8.1.3 DTS Bandwidth	17
8.1.4 Maximum Peak Conducted Output Power	17
8.1.5 Maximum Peak Power Spectral Density Level In The Fundamental Emis	
8.1.6 Emissions in Non-Restricted Frequency Bands (in 100kHz Bandwidth)	18
8.1.7 Emissions in the Restricted Bands (Radiated)	18
8.1.8 Emissions Radiated Outside of the Fundamental Frequency Band	18
9. TEST PROCEDURE DEVIATIONS	19
10. CONCLUSIONS	19

(818) 597-0600

FCC ID: 2ADHKBZR

1 wit is suspine a section 1012 ..., 1155 021 (w 1155 2 ... 105

LIST OF APPENDICES

APPENDIX	TITLE	
A	Laboratory Accreditations and Recognitions	
В	Modifications to the EUT	
C	Additional Models Covered Under This Report	
D	Diagrams, Factors, Charts, and Photos	
	Test Setup Diagrams	
	Antenna and Amplifier Factors	
	Radiated and Conducted Emissions Photos	
Е	Radiated and Conducted Emissions Data Sheets	

LIST OF FIGURES

FIGURE	TITLE
1	Plot Map and Layout of Test Site Below 1GHz
2	Plot Map and Layout of Test Site Above 1GHz
3	Conducted Emissions Test Setup



FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report

GENERAL REPORT SUMMARY

This electromagnetic emission test report is generated by Compatible Electronics Inc., which is an independent testing and consulting firm. The test report is based on testing performed by Compatible Electronics personnel according to the measurement procedures described in the test specifications given below and in the "Test Procedures" section of this report.

The measurement data and conclusions appearing herein relate only to the sample tested and this report may not be reproduced in any form unless done so in full with the written permission of Compatible Electronics.

This report must not be used to claim product certification, approval or endorsement by NVLAP, NIST, or any agency of the federal government.

Device Tested: BLE Module

Model: ATSAMB11-ZR210CA

S/N: None

Product Description: The EUT is a BLE Wireless Shielded Module with a chip antenna.

Modifications: The EUT was not modified in order to comply with specifications.

Manufacturer: Microchip Technology Inc.

2355 W Chandler Blvd. Chandler, AZ 85224

Test Dates: March 17 & 18, 2016

Test Specifications Covered by Accreditation:



EMI requirements

CFR Title 47, Part 15 Subpart C Sections 15.205, 15.207, 15.209, & 15.247.

RSS 247 & RSS GEN

Test Procedure: ANSI C63.4 & C63.10, and KDB 558074 D01 v03r03.



FCC ID: 2ADHKBZR FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report

Report Number: D60501R1

SUMMARY OF TEST RESULTS

TEST	DESCRIPTION	RESULTS	
1	Conducted RF Emissions, 150 kHz - 30 MHz	Complies with the limits of CFR Title 47 Part 15 Subpart C Section 15.207 and RSS GEN	
2	Radiated RF Emissions & Harmonics, 9 kHz – 25,000 MHz	Complies with the limits of CFR Title 47 Part 15 Subpart C Sections 15.205, 15.209, and RSS GEN	
3	DTS Bandwidth	Complies with CFR Title 47 Part 15 Subpart C Section 15.247 and RSS 247	
4	Maximum Peak Conducted Output Power	Complies with CFR Title 47 Part 15 Subpart C Section 15.247 and RSS 247	
5	Maximum Peak Power Spectral Density Level In The Fundamental Emission	Complies with CFR Title 47 Part 15 Subpart C Section 15.247 and RSS 247	
6	Emissions in Non-Restricted Frequency Bands (in 100kHz Bandwidth)	Complies with CFR Title 47 Part 15 Subpart C Section 15.247 and RSS 247	
7	Emissions in the Restricted Bands	Complies with CFR Title 47 Part 15 Subpart C Section 15.247 and RSS 247	



FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report

Report Number: D60501R1

FCC ID: 2ADHKBZR

1. PURPOSE

This document is a qualification test report based on the Electromagnetic Interference (EMI) tests performed on the BLE Module Model: ATSAMB11-ZR210CA. The EMI measurements were performed according to the measurement procedure described in ANSI C63.10 & C63.4. The tests were performed in order to determine whether the electromagnetic emissions from the equipment under test, referred to as EUT (equipment under test) hereafter, are within the specification limits defined by the Code of Federal Regulations Title 47, Part 15 Subpart C sections 15.207, 15.205, 15.209, 15.247, RSS GEN, and RSS 247.





FCC ID: 2ADHKBZR FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report

Report Number: D60501R1

2. ADMINISTRATIVE DATA

2.1 **Location of Testing**

The tests described herein were performed at the test facility of Compatible Electronics, 20621 Pascal Way Lake Forest, California 92630.

2.2 **Traceability Statement**

The calibration certificates of all test equipment used during the test are on file at the location of the test. The calibration is traceable to the National Institute of Standards and Technology (NIST).

2.3 **Cognizant Personnel**

Microchip Technology Inc.

Sanjay Malani

Compatible Electronics Inc.

Torey Oliver Test Technician Matt Harrison Lab Manager

2.4 **Date Test Sample was Received**

The test sample was received on March 17, 2016.

2.5 **Disposition of the Test Sample**

The test sample remains at Compatible Electronics as of the date of this test report.

2.6 **Abbreviations and Acronyms**

The following abbreviations and acronyms may be used in this document.

RF Radio Frequency Electromagnetic Interference **EMI EUT** Equipment Under Test P/N Part Number Serial Number S/N HP Hewlett Packard ITE Information Technology Equipment Corrected Meter Limit

CML

LISN Line Impedance Stabilization Network

NVLAP National Voluntary Laboratory Accreditation Program

Code of Federal Regulations **CFR PCB** Printed Circuit Board

TXTransmit RXReceive



FCC ID: 2ADHKBZR

3.

APPLICABLE DOCUMENTS

The following documents are referenced or used in the preparation of this Test Report.

SPEC	TITLE
CFR Title 47, Part 15	FCC Rules – Radio frequency devices (including digital devices)
ANSI C63.4 2014	Methods of measurement of radio-noise emissions from low-voltage electrical and electronic equipment in the range of 9 kHz to 40 GHz.
RSS 247	Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices
RSS GEN	General Requirements for Compliance of Radio Apparatus
ANSI C63.10: 2013	American National Standard for Testing Unlicensed Wireless Devices
KDB 558074 D01 v03r05	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247



FCC ID: 2ADHKBZR

FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report

DESCRIPTION OF TEST CONFIGURATION

4.1 **Description of Test Configuration**

The BLE Module Model: ATSAMB11-ZR210CA (EUT) was setup in a tabletop configuration. The EUT was powered by a DC Supply (for Conducted Emissions the EUT was connected to a USB Power Adapter). The EUT was continuously transmitting a data stream during transmit tests and continuously receiving during receiver tests. The EUT was checked in all axes and the X-Axis was found to be the worst case.

The voltage was varied + 15% and the transmitting signal amplitude and frequency did not vary.

It was determined that the emissions were at their highest level fwhen the EUT was transmitting in the configuration described above for Radiated Emissions. The final radiated data was taken in the above configuration. Please see Appendix E for the test data.

4.1.1 Photograph Test Configuration (X-Axis Shown)





FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report

4.1.2 Cable Construction and Termination

Cable 1-2

These are 2 meter, un-shielded, round cables that connect the EUT to the DC Power Supply. The cables were hardwired into the EUT and have banana connectors at the DC Supply end. The cables were not bundled.

Cable 3

This is a 10 centimeter, un-shielded, round cables that connect the EUT to the EUT Control Board. The cable is hardwired into both ends of the cable. The cable was not bundled.

Cable 4

This is a 1 meter, foil shielded, USB cable that connect the EUT to the USB Power Adapter. The cable is hardwired into both ends of the cable. The cable was not bundled. The shield of the cable was terminated at the connectors.







LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT 5.

5.1 EUT and Accessory List

#	EQUIPMENT TYPE	MANU-FACTURER	MODEL	SERIAL NUMBER
1	BLE MODULE(EUT)	MICROCHIP TECHNOLOGY INC.	ATSAMB11-ZR210CA	N/A
2	DC SUPPLY	MPJA	0-30V / 0-5A	017687
3	EUT CONTROL BOARD	MICROCHIP TECHNOLOGY INC.	NONE	NONE
4	USB POWER ADAPTER (CONDUCTED EMISSIONS)	BELKIN	F8J052	NONE





FCC ID: 2ADHKBZR

5.2 EMI Test Equipment

EQUIPMENT TYPE	MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	CAL. DATE	CAL. DUE DATE
Computer	Compatible Electronics	NONE	NONE	N/A	N/A
EMI Receiver	Rohde & Schwarz	ESIB40	100219	9/3/2015	9/3/2016
Antenna, Loop	Com Power	AL-130	121049	12/06/2013	12/06/2016
Antenna, CombiLog	Com Power	AC-220	25857	5/21/2014	5/21/2016
Antenna, Horn 1- 18GHz	Com Power	AH-118	071250	7/1/2014	7/1/2016
Antenna, Horn 18- 26 GHz	Com Power	AH-826	081033	NCR	NCR
Pre-Amp, 1-18GHz	Com Power	PAM-118A	551034	8/25/2015	8/25/2016
Pre-Amp, 18- 40GHz	Com Power	PA-840	181289	6/16/2014	6/16/2016
LISN	Com Power	LI-215	191937	4/16/2015	4/16/2016
RF Peak Power Meter/Analyzer	Boonton	4500A	1282	12/2/2014	12/2/2016
Peak Power Sensor	Boonton	57318	3723	12/2/2014	12/2/2016
High Pass Filter	AMTI Microwave Circuits	H3G020G4	481230	6/4/2015	6/4/2016
Mast, Antenna Positioner	Sunol Science Corporation	TWR 95-4	020808-3	N/A	N/A
Antenna Mast	Sunol Science Corporation	TWR 95-4	020808-3	N/A	N/A
Turntable	Sunol Science Corporation	FM 2001	N/A	N/A	N/A
Mast and Turntable Controller	Sunol Science Corporation	SC104V	020808-1	N/A	N/A



6. TEST SITE DESCRIPTION

6.1 Test Facility Description

Please refer to section 2.1 and the figures in Appendix D of this report for test location.

6.2 EUT Mounting, Bonding and Grounding

The EUT was mounted on a 1.0 by 1.5 by 0.8 meters high non-conductive table, which was placed on the ground plane.

For testing above 1 GHz the EUT was mounted 1.5 meter above the ground plane.

The EUT was grounded through the USB Cable.

6.3 Facility Environmental Characteristics

When applicable refer to the data sheets in Appendix E for the relative humidity, air temperature, and barometric pressure.





7. CHARACTERISTICS OF THE TRANSMITTER

7.1 Channel Number and Frequencies

There is a total of 40 channels. The low channel is at 2402.0 MHz and the high channel is at 2480.0 MHz. There is approximately 2 MHz separation between channels and the EUT uses GFSK modulation. Below are the channels and power settings:

Frequency	Gain Setting
-----------	--------------

2402 MHz	DigGain=	DG=30
2404-2478 MHz	DigGain=	DG=3B
2480 MHz	DigGain=	DG=30

7.2 Antenna

The antenna is a chip antenna.





8. TEST PROCEDURES

The following sections describe the test methods and the specifications for the tests. Test results are also included in this section.

8.1 RF Emissions

8.1.1 Conducted Emissions Test

The EMI receiver was used as a measuring meter. A quasi-peak and/or average reading was taken only where indicated in the data sheets. The LISN output was measured using the EMI receiver. The output of the second LISN was terminated by a 50-ohm termination. The effective measurement bandwidth used for this test was 9 kHz.

Please see section 6.2 of this report for mounting, bonding, and grounding of the EUT. The EUT received its power through the LISN, which was bonded to the ground plane. The EUT was set up with the minimum distances from any conductive surfaces as specified in ANSI 63.4. The excess power cord was wrapped in a figure eight pattern to form a bundle not exceeding 0.4 meters in length.

The conducted emissions from the EUT were maximized for operating mode as well as cable placement. The final data was collected under program control by the computer software. The final qualification data is located in Appendix E.

Test Results:

The EUT complies with the limits of CFR Title 47 Part 15 Subpart C section 15.207 & RSS GEN.



FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report

Report Number: D60501R1

FCC ID: 2ADHKBZR

8.1.2 Radiated Emissions (Spurious and Harmonics) Test

The R&S receiver was used as a measuring meter. The receiver was used in the peak detect mode with the "Max Hold" feature activated. In this mode, the receiver records the highest measured reading over all the sweeps. Amplifiers were used to increase the sensitivity of the instrument. There were two Microwave Preamplifier used for frequencies above 1 GHz.

For spurious emissions, the quasi-peak detector was used for frequencies below 1GHz and the average detector was used for frequencies above 1 GHz.

For the radiated Harmonic emissions and Band Edges a linear average detector was used.

The measurement bandwidths and transducers used for the radiated emissions test were:

FREQUENCY RANGE (MHz)	TRANSDUCER	EFFECTIVE MEASUREMENT BANDWIDTH
.009 to .150	Active Loop Antenna	200 Hz
.150 to 30	Active Loop Antenna	9 kHz
30 to 1000	Combilog Antenna	100 kHz (120kHz for QP Measurements)
1000 to 25000	Horn Antenna	1 MHz

The TDK FAC-3 shielded test chamber of Compatible Electronics, Inc. was used for radiated emissions testing. This test site is in full compliance with ANSI, EN 50147-2, and CISPR 22. Please see section 6.2 of this report for mounting, bonding and grounding of the EUT. The turntable supporting the EUT is remote controlled using a motor. The turntable permits EUT rotation of 360 degrees in order to maximize emissions. Also, the antenna mast allows height variation of the antenna from 1 meter to 4 meters. Data was collected in the worst case (highest emission) configuration of the EUT. At each reading, the EUT was rotated 360 degrees and the antenna height was varied from 1 to 4 meters in both vertical and horizontal polarizations (for E field radiated field strength).

Test Results:

The EUT complies with the limits of CFR Title 47 Part 15 Subpart C sections 15.205, 15.209, 15.247, RSS 247, and RSS GEN.



Report Number: D60501R1

8.1.3 **DTS Bandwidth**

The DTS Bandwidth was measured directly connected to the EMI Receiver using a RBW of 100 kHz and a VBW of 300 kHz. A peak detector and a max hold trace were used with auto sweep time. The trace was allowed to fully maximize. We measured the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. The automatic bandwidth measurement capability of the EMI Receiver was employed using the n dB bandwidth mode with n set to 6 dB. The final qualification data sheets are located in Appendix E.

Test Results:

The EUT complies with Part 15, Subpart C, Section 15.247 and RSS 247.

8.1.4 **Maximum Peak Conducted Output Power**

The maximum peak conducted output power was measured using a Peak Power Meter. The Peak Power Meter used a resolution bandwidth that is greater than the DTS bandwidth and a video bandwidth greater than 3 x RBW. The final qualification data sheets are located in Appendix E.

Test Results:

The EUT complies with Part 15, Subpart C, Section 15.247 and RSS 247.

8.1.5 Maximum Peak Power Spectral Density Level in The Fundamental Emission

The Maximum Peak Power Spectral Density Level in the Fundamental Emission was measured directly connected to the EMI Receiver. Tuned to the center frequency of the DTS channel and set the span to 1.5 times the DTS bandwidth. RBW was set to minimum 3 kHz but not > 100kHz and VBW 3 * RBW. A peak detector was used with the sweep time set to auto. A max hold trace was used and allowed to fully stabilize. The peak marker function was used to determine the maximum amplitude level within the RBW. The final qualification data sheets are located in Appendix E.

Test Results:

The EUT complies with Part 15, Subpart C, Section 15.247 and RSS 247.



FCC ID: 2ADHKBZR FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report

8.1.6 **Emissions in Non-Restricted Frequency Bands (in 100kHz Bandwidth)**

The Emissions in Non-Restricted Frequency Bands (in 100kHz Bandwidth) measurements were performed using the EMI Receiver directly connected to the EUT. A reference level was established by setting the instrument center frequency to DTS channel center frequency. The span was set to \geq 1.5 times the DTS bandwidth. The RBW was 100 kHz and VBW 300 kHz. A peak detector was used with a sweep time set to auto. A max hold trace was used and allowed to fully stabilize. The peak marker function was used to determine the level and 20dB below that was the reference level. For Emission Level Measurement, the center frequency and span were set to encompass the frequency range to be measured. RBW was set to 100 kHz and VBW to 300 kHz. A peak detector was used with a sweep time set to auto. The number of measurement points were greater than span/RBW. A max hold trace was used and allowed to fully stabilize. The peak marker function was used to determine the maximum amplitude level. The final qualification data sheets are located in Appendix E.

Test Results:

The EUT complies with Part 15, Subpart C, Section 15.247 and RSS 247.

8.1.7 **Emissions in the Restricted Bands (Radiated)**

The Emissions in the Restricted Bands measurement was performed using the EMI Receiver at a 3meter test distance to obtain the final test data. The final qualification data sheets are located in Appendix E.

Test Results:

The EUT complies with Part 15 Subpart C, Section 15.205 and RSS GEN.

8.1.8 **Emissions Radiated Outside of the Fundamental Frequency Band**

The Band Edge measurement was performed using the EMI Receiver at a 3-meter test distance to obtain the final test data. The low and high channels were tuned to during the low and high band edge tests. The final qualification data sheets are located in Appendix E.

Test Results:

The EUT complies with Part 15, Subpart C, Section 15.247 and RSS 247.





9. TEST PROCEDURE DEVIATIONS

The test procedures were not deviated from throughout all tests.

10. CONCLUSIONS

The BLE Module Model: ATSAMB11-ZR210CA meets all of the relevant specification requirements defined in the Code of Federal Regulations Title 47, Part 15 Subpart C sections 15.205, 15.207, 15.209, 15.247, RSS GEN & RSS 247.





Report Number: D60501R1 FCC ID: 2ADHKBZR

APPENDIX A

LABORATORY ACCREDITATIONS AND RECOGNITIONS



FCC ID: 2ADHKBZR FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report

Report Number: D60501R1

LABORATORY ACCREDITATIONS AND RECOGNITIONS



For US, Canada, Australia/New Zealand, Japan, Taiwan, Korea, and the European Union, Compatible Electronics is currently accredited by NVLAP to ISO/IEC 17025.

For the most up-to-date version of our scopes and certificates please visit

http://celectronics.com/quality/scope/

Quote from ISO-ILAC-IAF Communiqué on 17025:

"A laboratory's fulfilment of the requirements of ISO/IEC 17025:2005 means the laboratory meets both the technical competence requirements and management system requirements that are necessary for it to consistently deliver technically valid test results and calibrations. The management system requirements in ISO/IEC 17025:2005 (Section 4) are written in language relevant to laboratory operations and meet the principles of ISO 9001:2008 Quality Management Systems — Requirements."

IC OAT's Test Site Registration Number: 2154C-1



APPENDIX B

MODIFICATIONS TO THE EUT



FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report

MODIFICATIONS TO THE EUT

There were no modifications made during testing.





FCC ID: 2ADHKBZR FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report

Report Number: D60501R1

APPENDIX C

ADDITIONAL MODELS COVERED **UNDER THIS REPORT**



FCC ID: 2ADHKBZR

ADDITIONAL MODELS COVERED UNDER THIS REPORT

USED FOR THE PRIMARY TEST

BLE Module

Model: ATSAMB11-ZR210CA

S/N: None

No additional models were tested.





Report Number: D60501R1 FCC ID: 2ADHKBZR

APPENDIX D


DIAGRAMS, FACTORS, CHARTS, AND PHOTOS



FCC ID: 2ADHKBZR

FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report


FIGURE 1: PLOT MAP AND LAYOUT OF TEST SITE **BELOW 1GHZ**





Report Number: D60501R1 FCC ID: 2ADHKBZR


FIGURE 2: PLOT MAP AND LAYOUT OF TEST SITE ABOVE 1GHZ





Report Number: D60501R1

FIGURE 3: CONDUCTED EMISSIONS TEST SETUP





Report Number: D60501R1

COM-POWER AL-130

LOOP ANTENNA

S/N: 121049

CALIBRATION DUE: DECEMBER 6, 2016

FREQUENCY	MAGNETIC	ELECTRIC	FREQUENCY	MAGNETIC	ELECTRIC
(MHz)	(dB/m)	(dB/m)	(MHz)	(dB/m)	(dB/m)
0.009	-34.64	16.86	0.8	-36.32	15.18
0.01	-34.78	16.72	0.9	-36.22	15.28
0.02	-35.91	15.59	1.0	-36.22	15.28
0.03	-35.48	16.02	2.0	-35.91	15.59
0.04	-35.82	15.68	3.0	-35.91	15.59
0.05	-36.49	15.01	4.0	-36.01	15.49
0.06	-36.30	15.20	5.0	-35.80	15.70
0.07	-36.43	15.07	6.0	-36.00	15.50
0.08	-36.30	15.20	7.0	-35.90	15.60
0.09	-36.39	15.11	8.0	-35.70	15.80
0.1	-36.41	15.09	9.0	-35.70	15.80
0.2	-36.61	14.89	10.0	-35.60	15.90
0.3	-36.63	14.87	15.0	-36.52	14.98
0.4	-36.52	14.99	20.0	-35.75	15.75
0.5	-36.63	14.87	25.0	-37.78	13.72
0.6	-36.62	14.88	30.0	-38.62	12.88
0.7	-36.53	14.97			



FCC ID: 2ADHKBZR FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report

Report Number: D60501R1

COM-POWER AC-220

LAB R - COMBILOG ANTENNA

S/N: 25857

CALIBRATION DUE: MAY 21, 2016

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
30	22.5	160	13.3
35	22.5	180	15.0
40	23.0	200	14.6
45	21.5	250	16.5
50	21.3	300	18.1
60	18.2	400	19.4
70	13.2	500	21.4
80	11.6	600	21.6
90	11.9	700	23.7
100	12.6	800	26.0
120	15.1	900	26.6
140	13.6	1000	28.5



Report Number: D60501R1

COM-POWER AH-118

HORN ANTENNA

S/N: 071250

CALIBRATION DUE: JULY 1, 2016

FREQUENCY (MHz)	FACTOR	FREQUENCY (MHz)	FACTOR
	(dB)		(dB)
1000	30.1	9500	44.2
1500	29.2	10000	43.4
2000	31.6	10500	44.6
2500	35.5	11000	45.1
3000	33.7	11500	45.7
3500	36.0	12000	46.2
4000	35.4	12500	45.4
4500	35.5	13000	44.8
5000	40.1	13500	46.7
5500	37.8	14000	47.8
6000	39.0	14500	46.4
6500	39.9	15000	47.2
7000	40.4	15500	45.5
7500	44.4	16000	45.0
8000	44.1	16500	44.5
8500	43.1	17000	47.0
9000	43.0	17500	47.8
	-	18000	44.2



Report Number: D60501R1

COM-POWER PAM-118A

1-18GHz - PREAMPLIFIER

S/N: 551034

CALIBRATION DUE: AUGUST 25, 2017

FREQUENCY	FACTOR	FREQUENCY	FACTOR
(MHz)	(dB)	(MHz)	(dB)
500	36.77	5500	39.82
1000	38.63	6000	38.74
1100	38.72	6500	39.60
1200	38.97	7000	35.52
1300	38.59	7500	36.61
1400	39.18	8000	36.92
1500	38.71	8500	37.13
1600	39.28	9000	36.50
1700	39.25	9500	38.92
1800	39.06	10000	38.74
1900	40.34	11000	35.23
2000	40.07	12000	35.64
2500	39.69	13000	36.73
3000	40.94	14000	36.48
3500	40.41	15000	37.57
4000	40.44	16000	38.10
4500	41.20	17000	37.34
5000	39.35	18000	36.80



FCC ID: 2ADHKBZR FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report

Report Number: D60501R1

COM-POWER PA-840

18-40 GHz PREAMPLIFIER

S/N: 181289

CALIBRATION DUE: JUNE 16, 2016

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
18000	29.4	31500	28.2
19000	28.8	32000	28.6
20000	30.5	32500	28.8
21000	31.4	33000	28.2
22000	31.2	33500	27.7
23000	30.1	34000	27.2
24000	30.3	34500	28.2
25000	29.8	35000	27.3
26000	30.5	35500	27.2
26500	30.7	36000	27.2
27000	30.8	36500	27.5
27500	30.2	37000	27.0
28000	30.1	37500	26.7
28500	30.2	38000	26.2
29000	30.1	38500	26.5
29500	29.8	39000	26.3
30000	29.2	39500	26.9
30500	28.4	40000	27.6
31000	29.8		



Report Number: D60501R1



FRONT VIEW

MICROCHIP TECHNOLOGY INC. **BLE MODULE** Model: ATSAMB11-ZR210CA FCC SUBPART C - RADIATED EMISSIONS < 1GHz

PHOTOGRAPH SHOWING THE EUT CONFIGURATION FOR MAXIMUM EMISSIONS

Report Number: D60501R1



REAR VIEW

MICROCHIP TECHNOLOGY INC.
BLE MODULE
Model: ATSAMB11-ZR210CA
FCC SUBPART C - RADIATED EMISSIONS < 1GHz

PHOTOGRAPH SHOWING THE EUT CONFIGURATION FOR MAXIMUM EMISSIONS

Report Number: D60501R1



FRONT VIEW

MICROCHIP TECHNOLOGY INC. **BLE MODULE** Model: ATSAMB11-ZR210CA FCC SUBPART C - RADIATED EMISSIONS > 1GHz

PHOTOGRAPH SHOWING THE EUT CONFIGURATION FOR MAXIMUM EMISSIONS



REAR VIEW

MICROCHIP TECHNOLOGY INC. **BLE MODULE** Model: ATSAMB11-ZR210CA FCC SUBPART C - RADIATED EMISSIONS > 1GHz

PHOTOGRAPH SHOWING THE EUT CONFIGURATION FOR MAXIMUM EMISSIONS



FRONT VIEW

MICROCHIP TECHNOLOGY INC. **BLE MODULE** Model: ATSAMB11-ZR210CA FCC SUBPART C - CONDUCTED EMISSIONS

PHOTOGRAPH SHOWING THE EUT CONFIGURATION FOR MAXIMUM EMISSIONS

FCC ID: 2ADHKBZR



REAR VIEW

MICROCHIP TECHNOLOGY INC.
BLE MODULE
Model: ATSAMB11-ZR210CA
FCC SUBPART C - CONDUCTED EMISSIONS

PHOTOGRAPH SHOWING THE EUT CONFIGURATION FOR MAXIMUM EMISSIONS

Report Number: D60501R1

APPENDIX E

RADIATED EMISSIONS DATA SHEETS





FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report

Title: FCC 15.209 3/18/2016 12:01:10 PM File: Radiated Pre-Scan 30-1000Mhz.set Sequence: Preliminary Scan

Operator: Torey Oliver


EUT Type: BLE Module / ATSAMB11-ZR210CA

EUT Condition: The EUT is constantly transmitting 2440 MHz.

Comments: Connected to remote laptop.

Temp: 71f Hum: 43% 5VDC

Compatible Electronics, Inc. FAC-3 (Lab R)



This was worst case for all modes and channels

There were no radiated emissions besides harmonics found between 9kHz-30 MHz or 1GHz-25GHz.







Title: FCC 15.209 3/18/2016 1:28:41 PM

File: Radiated Final 30-1000Mhz.set Sequence: Final Measurements

Operator: Torey Oliver

EUT Type: BLE Module / ATSAMB11-ZR210CA

EUT Condition: The EUT is constantly transmitting 2440 MHz.

Comments: Connected to remote laptop.

Temp: 71f Hum: 43% 5VDC

Compatible Electronics, Inc. FAC-3 (Lab R)

Freq (MHz)	(QP) Margin (dB)	(QP) EMI (dBµV/m)	(PEAK) EMI (dBµV/m)	Limit (dBµV/m)	Pol	Ttbl Agl (deg)	Twr Ht (cm)	Transducer(dB)	Cable(dB)
43.40	-10.51	29.94	34.03	40.45	V	307.75	111.43	21.96	0.64
48.00	-10.63	29.82	33.27	40.45	V	327.25	116.08	21.38	0.68
51.40	-11.02	29.43	33.72	40.45	V	171.75	105.10	20.87	0.70
60.10	-6.97	33.48	36.90	40.45	V	360.00	112.08	18.20	0.70
72.10	-7.67	32.78	36.19	40.45	V	203.25	118.35	12.85	0.82
96.00	-14.12	26.33	29.66	40.45	V	85.00	130.89	12.33	1.00

This was worst case for all modes and channels

There were no radiated emissions besides harmonics found between 9kHz-30 MHz or 1GHz-25GHz.



Report Number: D60501R1

APPENDIX E

CONDUCTED EMISSIONS DATA SHEETS



FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report

Title: FCC 15.209 3/18/2016 3:11:25 PM

File: Conducted Pre-Line.set Sequence: Preliminary Scan

Operator: Torey Oliver

EUT Type: BLE Module / ATSAMB11-ZR210CA


EUT Condition: The EUT is constantly transmitting 2440 MHz.

Comments: Connected to remote laptop.

Temp: 71f Hum: 43% 5VDC

Host: 120V 60Hz

Compatible Electronics, Inc. FAC-3 (LAB R)







Sequence: Final Measurements





Title: FCC 15.209 3/18/2016 3:15:15 PM

File: Conducted Final-Line.set

Operator: Torey Oliver

EUT Type: BLE Module / ATSAMB11-ZR210CA

EUT Condition: The EUT is constantly transmitting 2440 MHz.

Comments: Connected to remote laptop.

Temp: 71f Hum: 43% 5VDC

Host: 120V 60Hz

Compatible Electronics, Inc. FAC-3 (LAB R)

Freq (MHz)	(AVG) Margin AVL (dB)	(QP) Margin QPL (dB)	(AVG) EMI (dBµV)	(QP) EMI (dBμV)	(PEAK) EMI (dBµV)	(AVG) Limit (dBµV)	(QP) Limit (dBµV)	Transducer (dB)	Cable (dB)
0.51	-12.94	-14.38	33.06	41.62	46.89	46.00	56.00	0.03	0.10
0.52	-9.95	-11.46	36.05	44.54	48.96	46.00	56.00	0.03	0.10
2.14	-17.81	-15.75	28.19	40.25	47.64	46.00	56.00	0.04	0.01
2.15	-17.14	-14.41	28.86	41.59	48.05	46.00	56.00	0.04	0.02
2.20	-18.08	-15.06	27.92	40.94	47.63	46.00	56.00	0.04	0.02
2.23	-17.69	-14.59	28.31	41.41	48.05	46.00	56.00	0.04	0.02
2.29	-17.23	-14.44	28.77	41.56	48.36	46.00	56.00	0.04	0.03
2.33	-17.77	-16.81	28.23	39.19	46.37	46.00	56.00	0.04	0.03



Sequence: Preliminary Scan

FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report

Title: FCC 15.209 3/18/2016 3:19:14 PM

File: Conducted Pre-Neutral.set

Operator: Torey Oliver

EUT Type: BLE Module / ATSAMB11-ZR210CA


EUT Condition: The EUT is constantly transmitting 2440 MHz.

Comments: Connected to remote laptop.

Temp: 71f Hum: 43% 5VDC

Host: 120V 60Hz

Compatible Electronics, Inc. FAC-3 (LAB R)







COMPATIBLE ELECTRONICS

Title: FCC 15.209 3/18/2016 3:23:27 PM

File: Conducted Final-Neutral.set Sequence: Final Measurements

Operator: Torey Oliver

EUT Type: BLE Module / ATSAMB11-ZR210CA

EUT Condition: The EUT is constantly transmitting 2440 MHz.

Comments: Connected to remote laptop.

Temp: 71f Hum: 43% 5VDC

Host: 120V 60Hz

Compatible Electronics, Inc. FAC-3 (LAB R)

Freq (MHz)	(AVG) Margin AVL (dB)	(QP) Margin QPL (dB)	(AVG) EMI (dBµV)	(QP) EMI (dBμV)	(PEAK) EMI (dBµV)	(AVG) Limit (dBµV)	(QP) Limit (dBµV)	Transducer (dB)	Cable (dB)
2.14	-27.69	-15.62	18.31	40.38	46.82	46.00	56.00	0.03	0.01
2.17	-26.80	-14.10	19.20	41.90	48.63	46.00	56.00	0.03	0.02
2.18	-27.42	-14.41	18.58	41.59	48.23	46.00	56.00	0.03	0.02
2.20	-27.50	-15.18	18.50	40.82	48.11	46.00	56.00	0.03	0.02
2.22	-27.56	-14.97	18.44	41.03	48.17	46.00	56.00	0.03	0.02
2.24	-27.23	-14.91	18.77	41.09	48.63	46.00	56.00	0.03	0.02
2.28	-27.05	-14.79	18.95	41.21	48.30	46.00	56.00	0.03	0.03
2.31	-27.58	-14.85	18.42	41.15	48.57	46.00	56.00	0.03	0.03
2.32	-27.91	-16.40	18.09	39.60	46.98	46.00	56.00	0.03	0.03



DTS BANDWIDTH

DATA SHEETS



Report Number: D60501R1 FCC ID: 2ADHKBZR

DTS BANDWIDTH

FCC 15.247 & RSS 247

Company: Microchip Technology Inc. Date: 3/18/2016

EUT: BLE Module Lab: R

Model: ATSAMB11-ZR210CA Test ENG: Torey Oliver


Compatible Electronics, Inc. FAC-3 (Lab R)

DTS Bandwidth

Freq. (MHz)	Measured BW (kHz)	Limit (Min) (kHz)	Margin (kHz)	Peak / QP / Avg	Comments
2402	697.39	500.00	197.39	Peak	
2440	689.38	500.00	189.38	Peak	
2480	689.38	500.00	189.38	Peak	








400 kHz/

Comment A: DTS Bandwidth 2402MHz 18.MAR.2016 09:33:03 Date:

Center 2.402 GHz



Span 4 MHz




Comment A: DTS Bandwidth 2440MHz 18.MAR.2016 09:34:46 Date:





FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report



Comment A: DTS Bandwidth 2480MHz 18.MAR.2016 09:36:54 Date:



FCC ID: 2ADHKBZR

MAXIMUM PEAK CONDUCTED OUTPUT POWER

DATA SHEETS



FCC ID: 2ADHKBZR

Report Number: D60501R1

MAXIMUM PEAK CONDUCTED OUTPUT POWER

FCC 15.247

Company: Microchip Technology Inc. Date: 3/17/2016

EUT: BLE Module Lab: R

Model: ATSAMB11-ZR210CA Test ENG: Torey Oliver

Mode: BLE

Compatible Electronics, Inc. FAC-3 (Lab R)

Freq. (MHz)	Level (dBm)	Limit (dBm)	Margin (dB)	Peak / QP / Avg	Comments
2402	4.25	30.00	-25.75	Peak	
2440	4.50	30.00	-25.50	Peak	
2480	3.82	30.00	-26.18	Peak	





Report Number: D60501R1

FCC ID: 2ADHKBZR

MAXIMUM PEAK POWER SPECTRAL DENSITY LEVEL IN THE FUNDAMENTAL EMISSION

DATA SHEETS



FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report

Report Number: D60501R1

FCC ID: 2ADHKBZR

PEAK POWER SPECTRAL DENSITY

FCC 15.247

Company: Microchip Technology Inc. Date: 3/18/2016

EUT: **BLE Module** Lab: R

Model: ATSAMB11-ZR210CA Test ENG: Torey Oliver

Compatible Electronics, Inc. FAC-3 (Lab R)


Freq. (MHz)	Peak (dBm)	Limit (dBm)	Margin (dB)	Peak / QP / Avg	Comments
2402	-0.31	8.00	-8.31	Peak	
2440	0.01	8.00	-7.99	Peak	
2480	-0.59	8.00	-8.59	Peak	







FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report




Comment A: Power Spectral Density 2402MHz

18.MAR.2016 09:45:05



FCC ID: 2ADHKBZR

FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report



103.4068 kHz/

Comment A: Power Spectral Density 2440MHz 18.MAR.2016 09:52:53


Center 2.44 GHz



Span 1.034068 MHz

FCC ID: 2ADHKBZR

FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report



103.4068 kHz/

Comment A: Power Spectral Density 2480MHz Date: 18.MAR.2016 09:49:13

Center 2.48 GHz



Span 1.034068 MHz

Report Number: D60501R1

FCC ID: 2ADHKBZR

HARMONIC EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS (IN 100KHZ BANDWIDTH) / CONDUCTED

DATA SHEETS



FCC ID: 2ADHKBZR

Report Number: D60501R1

HARMONIC EMISSIONS IN NON-RESTRICTED FREQUENCY **BANDS**

FCC 15.247

Company: Microchip Technology Inc. Date: 3/18/2016

EUT: **BLE Module** Lab: R

Model: ATSAMB11-ZR210CA Test ENG: Torey Oliver

Mode: **BLE**

Compatible Electronics, Inc. FAC-3 (Lab R)


Freq. (MHz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Peak / QP / Avg	Comments
9621.24	58.10	85.15	-27.05	Peak	Low Channel
9761.52	57.36	85.13	-27.77	Peak	Mid Channel
9929.86	55.02	85.13	-30.11	Peak	High Channel







Reference Level Measurements



Comment A: Conducted Spurious 2480MHz Date: 18.MAR.2016 12:44:11



Report Number: D60501R1

EMISSIONS IN RESTRICTED FREQUENCY BANDS (RADIATED FIELD STRENGTH)

DATA SHEETS



Report Number: D60501R1 FCC ID: 2ADHKBZR

HARMONIC EMISSIONS IN RESTRICTED FREQUENCY BANDS Low Channel, Horizontal & Vertical

FCC 15.247

Microchip Technology

Company: Inc.

EUT: BLE Module

Model: ATSAMB11-ZR210CA

Date: 3/18/2016

Lab: R

Test ENG: T. Oliver

Compatible Electronics, Inc. FAC-3 (Lab R)

		_				to o (Eab it	/	
Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
4804.00	50.65	Н	73.98	-23.33	Peak	1.08	313	In Restricted Band
4804.00	33.97	Н	53.98	-20.01	Avg	1.08	313	
12010.00	73.03	Н	73.98	-0.95	Peak	1.21	24	In Restricted Band
12010.00	52.79	Н	53.98	-1.19	Avg	1.21	24	
19216.00		Н	73.98		Peak			In Restricted Band
19216.00		Н	54.93		Avg			No Emissions Found
4804.00	48.71	V	73.98	-25.27	Peak	1.07	140	In Restricted Band
4804.00	34.97	V	53.98	-19.01	Avg	1.07	140	
12010.00	70.25	V	73.98	-3.73	Peak	1.00	177	In Restricted Band
12010.00	51.01	V	53.98	-2.97	Avg	1.00	177	No Emissions Found
19216.00		V	73.98		Peak			In Restricted Band
19216.00		V	54.93		Avg			No Emissions Found

Test distance



FCC ID: 2ADHKBZR

Report Number: D60501R1

HARMONIC EMISSIONS IN RESTRICTED FREQUENCY BANDS Mid Channel, Horizontal & Vertical

FCC 15.247

EUT:

Microchip Technology

Company: Inc.

BLE Module

Model: ATSAMB11-ZR210CA

Date: 3/18/2016

Lab: R

Test ENG: Torey Oliver

Compatible Electronics, Inc. FAC-3 (Lab R)

			Unipatib	ic Licoti on	103, 1110. 1 7	C-3 (Lab K	<i></i>	
Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
4880.00	53.06	Н	73.98	-20.92	Peak	1.35	33	In Restricted Band
4880.00	35.71	Н	53.98	-18.27	Avg	1.35	33	
7320.00	72.44	Н	73.98	-1.54	Peak	1.09	17.00	In Restricted Band
7320.00	52.57	Н	53.98	-1.41	Avg	1.09	17.00	
12200.00	73.19	Н	73.98	-0.79	Peak	1.34	33.00	In Restricted Band
12200.00	52.57	Н	53.98	-1.41	Avg	1.34	33.00	
19520.00		Н	73.98		Peak			In Restricted Band
19520.00		Н	53.98		Avg			No Emission Found
4880.00	49.88	V	73.98	-24.10	Peak	1.18	84	In Restricted Band
4880.00	36.11	V	53.98	-17.87	Avg	1.18	84	
7320.00	65.74	V	73.98	-8.24	Peak	2.66	159	In Restricted Band
7320.00	47.20	V	53.98	-6.78	Avg	2.66	159	
12200.00	73.06	V	73.98	-0.92	Peak	2.18	175	In Restricted Band
12200.00	52.96	V	53.98	-1.02	Avg	2.18	175	
19520.00		V	73.98		Peak			In Restricted Band
19520.00		V	53.98		Avg			No emissions found

Test distance



Report Number: D60501R1 FCC ID: 2ADHKBZR

HARMONIC EMISSIONS IN RESTRICTED FREQUENCY BANDS High Channel, Horizontal & Vertical

FCC 15.247

Microchip Technology

Company:

EUT: **BLE Module**

Model: ATSAMB11-ZR210CA Date: 3/18/2016

R Test ENG: Torey Oliver

Lab:

Compatible Electronics, Inc. FAC-3 (Lab R)

Freq.	Level				Peak / QP /	Ant. Height	Table Angle	
(MHz)	(dBuV)	Pol (v/h)	Limit	Margin	Avg	(m)	(deg)	Comments
4960.00	56.34	Н	73.98	-17.64	Peak	1.34	65	In Restricted Band
4960.00	38.27	Н	53.98	-15.71	Avg	1.34	65	
7440.00	73.89	Н	73.98	-0.09	Peak	1.04	15	In Restricted Band
7440.00	52.09	Н	53.98	-1.89	Avg	1.04	15	
12400.00	71.48	Н	73.98	-2.50	Peak	1.24	344	In Restricted Band
12400.00	51.02	Н	53.98	-2.96	Avg	1.24	344	
19840.00		Н	73.98		Peak			In Restricted Band
19840.00		Н	53.98		Avg			No Emission Found
22320.00		Н	73.98		Peak			In Restricted Band
22320.00		Н	53.98	7, 2011-01, 2011-01	Avg			No Emission Found
4960.00	53.48	V	73.98	-20.50	Peak	3.07	177	In Restricted Band
4960.00	40.15	V	53.98	-13.83	Avg	3.07	177	
7440.00	67.04	V	73.98	-6.94	Peak	2.46	165	In Restricted Band
7440.00	48.48	V	53.98	-5.50	Avg	2.46	165	
12400.00	73.62	V	73.98	-0.36	Peak	2.27	169	In Restricted Band
12400.00	53.23	V	53.98	-0.75	Avg	2.27	169	
19840.00		V	73.98		Peak			In Restricted Band
19840.00		V	53.98		Avg			No Emission Found
22320.00		V	73.98		Peak			In Restricted Band
22320.00		V	53.98		Avg			No Emission Found
								NVV I

Test distance



FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report

Report Number: D60501R1

FCC ID: 2ADHKBZR

EMISSIONS RADIATED OUTSIDE OF THE FUNDAMENTAL FREQUENCY BAND AT BAND EDGES

DATA SHEETS



Report Number: D60501R1 FCC ID: 2ADHKBZR

BAND EDGES- VERTICAL

FCC 15.247

Company: Microchip Technology Inc. Date: 3/18/2016

EUT: BLE Module Lab: R

Model: ATSAMB11-ZR210CA Test ENG: Torey Oliver

Mode: BLE

Compatible Electronics, Inc. FAC-3 (Lab R)

Freq. (MHz)	Level (dBµV/m)	Po I	Limit (dBµV/m)	Margin (dB)	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
2402.00	82.02	V			Peak	1.33	198	
2400.00	52.80	V	62.02	-9.22	Delta	1.33	198	From Peak
2376.77	51.77	V	73.98	-22.21	Peak	1.33	198	
2376.77	38.27	V	53.98	-15.71	Avg	1.33	198	
2480.00	81.15	V			Peak	2.47	120	
2483.62	52.72	V	73.98	-21.26	Peak	2.47	120	
2483.62	38.76	V	53.98	-15.22	Avg	2.47	120	

Test distance



Report Number: D60501R1 FCC ID: 2ADHKBZR

BAND EDGES- HORIZONTAL

FCC 15.247

Company: Microchip Technology Inc. Date: 3/18/2016

EUT: BLE Module Lab: R

Model: ATSAMB11-ZR210CA Test ENG: Torey Oliver

Mode: BLE

Compatible Electronics, Inc. FAC-3 (Lab R)


Freq. (MHz)	Level (dBµV/m)	Pol	Limit (dBµV/m)	Margin (dB)	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
2402.00	93.22	Н			Peak	1.57	290	
2400.00	59.85	Н	73.22	-13.37	Delta	1.57	290	From Peak
2379.58	51.91	Н	73.98	-22.07	Peak	1.57	290	
2379.58	38.32	Н	53.98	-15.66	Avg	1.57	290	
2480.00	90.14	Н	1		Peak	1.17	40	
2499.85	53.11	Н	73.98	-20.87	Peak	1.17	40	
2499.85	38.72	Н	53.98	-15.26	Avg	1.17	40	

Test distance





LOWER BAND EDGE (Horizontal)



4 MHz/

Comment A: Lower Band Edge Horizontal Date: 18.MAR.2016 08:10:31


Center 2.3872 GHz



Span 40 MHz



LOWER BAND EDGE



4 MHz/

Comment A: Lower Band Edge Vertical Date: 18.MAR.2016 08:22:10

Center 2.3872 GHz




Span 40 MHz



UPPER BAND EDGE (Horizontal)






Comment A: Upper Band Edge Horizontal 18.MAR.2016 07:48:04



Date:



UPPER BAND EDGE (Vertical)



Comment A: Upper Band Edge Vertical Date: 18.MAR.2016 07:54:31





OCCUPIED BANDWIDTH



Report Number: D60501R1 FCC ID: 2ADHKBZR

IC BANDWIDTH

RSS GEN

Microchip Technology

Company: Inc. Date: 3/18/2016


EUT: BLE Module Lab: R

Model: ATSAMB11-ZR210CA Test ENG: Torey Oliver

Mode: BLE

Compatible Electronics, Inc. FAC-3 (Lab R)

Freq. (MHz)	Measured BW (kHz)	Comments
2402	1083.50	
2440	1083.90	
2480	1079.80	





FCC Part 15 Subpart C Section 15.247, RSS GEN, & RSS 247 Test Report

