

Test Report No.50209102 001

Appendix D: Radiated and Mains Spurious Emission Data



(File: 50209102 001 AppendixD)

Contents



Module with Shielded Case, Class 1	3
Spurious Emissions, Band Edges, 2.35-2.5G.....	3
Spurious Emissions, TX Mode, 1-18G.....	11
Spurious Emissions, TX Mode, 18-26.5G	23
Spurious Emissions, TX Mode, 30M-1G	35
Spurious Emissions, TX Mode, 9K-30M	37
Spurious Emissions, RX Mode, 1-18G.....	39
Spurious Emissions, RX Mode, 18-26.5G.....	43
Spurious Emissions, RX Mode, 30M-1G	47
Spurious Emissions, RX Mode, 9K-30M	49
Module with Shielded Case, Class 2	51
Spurious Emissions, TX Mode, 1-18G.....	51
Spurious Emissions, TX Mode, 18-26.5G	55
Spurious Emissions, TX Mode, 30M-1G	59
Spurious Emissions, TX Mode, 9K-30M	61
Spurious Emissions, RX Mode, 1-18G.....	63
Spurious Emissions, RX Mode, 18-26.5G.....	67
Spurious Emissions, RX Mode, 30M-1G	71
Spurious Emissions, RX Mode, 9K-30M	73
Module without Shielded Case, Class 1	75
Spurious Emissions, Band Edges, 2.35-2.5G.....	75
Spurious Emissions, TX Mode, 1-18G.....	83
Spurious Emissions, TX Mode, 18-26.5G	95
Spurious Emissions, TX Mode, 30M-1G	107
Spurious Emissions, TX Mode, 9K-30M	109
Spurious Emissions, RX Mode, 1-18G.....	111
Spurious Emissions, RX Mode, 18-26.5G.....	115
Spurious Emissions, RX Mode, 30M-1G	119
Spurious Emissions, RX Mode, 9K-30M	121
Module without Shielded Case, Class 2	123
Spurious Emissions, TX Mode, 1-18G.....	123
Spurious Emissions, TX Mode, 18-26.5G	127
Spurious Emissions, TX Mode, 30M-1G	131
Spurious Emissions, TX Mode, 9K-30M	133
Spurious Emissions, RX Mode, 1-18G.....	135
Spurious Emissions, RX Mode, 18-26.5G.....	139
Spurious Emissions, RX Mode, 30M-1G	143
Spurious Emissions, RX Mode, 9K-30M	145
Mains	147

Radiated Bandedge (GFSK)



Low Channel (Hor)





Low Channel (Ver)



High Channel (Hor)





High Channel (Ver)





Radiated Bandedge (8DPSK)



Low Channel (Hor)





Low Channel (Ver)



High Channel (Hor)



High Channel (Ver)




Spurious Emissions, TX Mode, 1-18G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 20:46:56
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2402-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4804.000	3.30	47.74	51.04	74.00	-22.96	peak	100	347	
2	7206.000	4.77	45.85	50.62	74.00	-23.38	peak		0	
3	8310.000	4.86	44.99	49.85	74.00	-24.15	peak	100	360	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 20:47:49
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2402-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4804.000	3.30	50.33	53.63	74.00	-20.37	peak	100	27	
2	4804.000	3.30	43.40	46.70	54.00	-7.30	AVG	100	27	
3	7206.000	4.77	46.14	50.91	74.00	-23.09	peak			
4	8293.000	4.85	45.72	50.57	74.00	-23.43	peak	100	20	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 20:51:32
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4882.000	3.61	46.46	50.07	74.00	-23.93	peak	100	359	
2	7323.000	4.66	46.72	51.38	74.00	-22.62	peak			
3	8718.000	5.40	44.57	49.97	74.00	-24.03	peak	100	174	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 20:52:24
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4882.000	3.61	48.21	51.82	74.00	-22.18	peak	100	356	
2	7323.000	4.66	45.72	50.38	74.00	-23.62	peak			
3	8395.000	4.91	45.43	50.34	74.00	-23.66	peak	100	39	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 20:54:53
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2480-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4960.000	3.93	45.98	49.91	74.00	-24.09	peak	100	187	
2	7440.000	4.54	45.04	49.58	74.00	-24.42	peak			
3	8429.000	4.94	45.68	50.62	74.00	-23.38	peak	100	287	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 20:55:46
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2480-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4960.000	3.93	47.20	51.13	74.00	-22.87	peak	100	32	
2	7440.000	4.54	44.97	49.51	74.00	-24.49	peak			
3	8293.000	4.85	45.07	49.92	74.00	-24.08	peak	100	360	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 20:58:44
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2402-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4804.000	3.30	46.87	50.17	74.00	-23.83	peak	100	360	
2	7206.000	4.77	44.90	49.67	74.00	-24.33	peak			
3	8310.000	4.86	45.08	49.94	74.00	-24.06	peak	100	0	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 20:59:37
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2402-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4804.000	3.30	48.28	51.58	74.00	-22.42	peak	100	32	
2	7206.000	4.77	45.57	50.34	74.00	-23.66	peak			
3	8327.000	4.87	45.51	50.38	74.00	-23.62	peak	100	360	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 21:02:21
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2441-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4882.000	3.61	45.63	49.24	74.00	-24.76	peak	100	359	
2	7323.000	4.66	46.41	51.07	74.00	-22.93	peak			
3	8446.000	4.95	45.51	50.46	74.00	-23.54	peak	100	297	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 21:03:14
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2441-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4882.000	3.61	47.39	51.00	74.00	-23.00	peak	100	1	
2	7323.000	4.66	45.53	50.19	74.00	-23.81	peak			
3	8157.000	4.75	44.19	48.94	74.00	-25.06	peak	100	278	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 21:05:35
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2480-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4960.000	3.93	45.39	49.32	74.00	-24.68	peak	100	187	
2	7440.000	4.54	46.92	51.46	74.00	-22.54	peak			
3	8633.000	5.24	45.41	50.65	74.00	-23.35	peak	100	102	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 21:06:27
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2480-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4960.000	3.93	46.47	50.40	74.00	-23.60	peak	100	360	
2	7440.000	4.54	44.23	48.77	74.00	-25.23	peak			
3	8123.000	4.72	44.63	49.35	74.00	-24.65	peak	100	108	


Spurious Emissions, TX Mode, 18-26.5G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel: +886-2172-7000 fax: +886-2528-0018




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 21:23:21
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2402-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20660.500	4.38	39.09	43.47	74.00	-30.53	peak		0	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 21:23:28
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2402-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20507.500	4.19	39.94	44.13	74.00	-29.87	peak			




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 21:23:52
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	23525.000	5.85	37.47	43.32	74.00	-30.68	peak			




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 21:23:59
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20949.500	4.73	38.85	43.58	74.00	-30.42	peak			




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 21:24:27
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2480-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21128.000	4.67	39.20	43.87	74.00	-30.13	peak			




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 21:24:34
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2480-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20915.500	4.69	38.61	43.30	74.00	-30.70	peak			




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 21:25:09
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2402-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20915.500	4.69	39.88	44.57	74.00	-29.43	peak			




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 21:25:16
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2402-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20354.500	4.22	39.76	43.98	74.00	-30.02	peak			




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 21:25:48
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2441-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20830.500	4.59	39.90	44.49	74.00	-29.51	peak			




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 21:25:55
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2441-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20992.000	4.79	38.94	43.73	74.00	-30.27	peak			



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 21:26:13
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2480-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	23304.000	5.65	38.50	44.15	74.00	-29.85	peak			



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 21:26:20
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2480-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20771.000	4.51	38.87	43.38	74.00	-30.62	peak			


Spurious Emissions, TX Mode, 30M-1G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Class B 3M Radiation	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 21:42:16
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	63.9500	-13.56	38.71	25.15	40.00	-14.85	QP	100	52	
2	167.7400	-8.76	39.24	30.48	43.50	-13.02	QP	100	117	
3	318.0899	-4.39	33.44	29.05	46.00	-16.95	QP	100	82	
4	398.6000	-2.37	31.63	29.26	46.00	-16.74	QP	100	131	
5	468.4400	-1.69	33.40	31.71	46.00	-14.29	QP	100	134	
6	782.7200	2.88	28.85	31.73	46.00	-14.27	QP	100	0	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Class B 3M Radiation	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 21:43:10
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	35.8200	-3.37	36.94	33.57	40.00	-6.43	QP	100	255	
2	63.9500	-13.56	39.04	25.48	40.00	-14.52	QP	100	255	
3	119.2400	-7.46	32.91	25.45	43.50	-18.05	QP	100	157	
4	219.1500	-8.29	32.82	24.53	46.00	-21.47	QP	100	58	
5	399.5700	-2.33	31.68	29.35	46.00	-16.65	QP	100	49	
6	497.5400	-1.21	35.62	34.41	46.00	-11.59	QP	100	107	


Spurious Emissions, TX Mode, 9K-30M



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC 15.209_9k-30M_3m	Ant. Polarization:	N/A
Test item:	Radiation Emission	Test Time:	2018/11/29 21:49:59
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.0097	18.46	31.37	49.83	127.85	-78.02	QP	100	233	
2	0.0411	19.10	24.54	43.64	115.32	-71.68	QP	100	157	
3	0.0476	18.97	24.65	43.62	114.04	-70.42	QP	100	164	
4	0.0809	18.55	18.36	36.91	109.44	-72.53	QP	100	151	
5	0.0952	18.39	20.38	38.77	108.02	-69.25	QP	100	164	
6	0.1428	18.35	15.73	34.08	104.50	-70.42	QP	100	174	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC 15.209_9k-30M_3m	Ant. Polarization:	N/A
Test item:	Radiation Emission	Test Time:	2018/11/29 21:52:47
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-TX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.2992	18.44	27.43	45.87	98.08	-52.21	QP	100	108	
2	0.7171	18.66	22.80	41.46	70.50	-29.04	QP	100	154	
3	1.1947	18.66	23.41	42.07	66.08	-24.01	QP	100	115	
4	7.7617	20.01	14.17	34.18	69.50	-35.32	QP	100	359	
5	11.9407	20.66	12.33	32.99	69.50	-36.51	QP	100	157	
6	22.1494	21.68	11.19	32.87	69.50	-36.63	QP	100	358	


Spurious Emissions, RX Mode, 1-18G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel: +886-2172-7000 fax: +886-2528-0018




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 21:09:09
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-RX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	3023.000	-2.16	46.19	44.03	74.00	-29.97	peak	100	140	
2	3737.000	-1.04	45.90	44.86	74.00	-29.14	peak	100	34	
3	4111.000	0.12	45.34	45.46	74.00	-28.54	peak	100	54	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 21:10:01
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-RX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	3193.000	-2.00	46.69	44.69	74.00	-29.31	peak	100	316	
2	3924.000	-0.52	45.35	44.83	74.00	-29.17	peak	100	131	
3	4400.000	1.21	45.36	46.57	74.00	-27.43	peak	100	265	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 21:11:19
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2441-RX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	3244.000	-1.95	45.82	43.87	74.00	-30.13	peak	100	303	
2	3975.000	-0.38	45.46	45.08	74.00	-28.92	peak	100	163	
3	4485.000	1.54	44.69	46.23	74.00	-27.77	peak	100	204	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 21:12:11
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2441-RX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	3210.000	-1.98	46.03	44.05	74.00	-29.95	peak	100	330	
2	3839.000	-0.77	45.92	45.15	74.00	-28.85	peak	100	91	
3	4485.000	1.54	45.25	46.79	74.00	-27.21	peak	100	118	


Spurious Emissions, RX Mode, 18-26.5G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel: +886-2172-7000 fax: +886-2528-0018




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 21:26:55
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-RX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	23108.500	5.44	38.08	43.52	74.00	-30.48	peak			




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 21:27:02
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-RX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20966.500	4.75	38.92	43.67	74.00	-30.33	peak			



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 21:27:33
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2441-RX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20490.500	4.20	38.51	42.71	74.00	-31.29	peak			



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 21:27:40
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2441-RX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21068.500	4.73	38.42	43.15	74.00	-30.85	peak			


Spurious Emissions, RX Mode, 30M-1G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Class B 3M Radiation	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 21:44:32
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-RX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	63.9500	-13.56	39.99	26.43	40.00	-13.57	QP	100	163	
2	167.7400	-8.76	38.59	29.83	43.50	-13.67	QP	100	124	
3	300.6300	-4.55	32.83	28.28	46.00	-17.72	QP	100	65	
4	330.7000	-3.89	33.20	29.31	46.00	-16.69	QP	100	124	
5	468.4400	-1.69	33.10	31.41	46.00	-14.59	QP	100	131	
6	566.4100	0.07	29.78	29.85	46.00	-16.15	QP	100	88	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Class B 3M Radiation	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 21:45:26
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-RX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	35.8200	-3.37	36.09	32.72	40.00	-7.28	QP	100	278	
2	63.9500	-13.56	40.52	26.96	40.00	-13.04	QP	100	308	
3	107.6000	-8.49	33.03	24.54	43.50	-18.96	QP	100	140	
4	220.1200	-8.23	32.50	24.27	46.00	-21.73	QP	100	88	
5	421.8800	-1.96	29.05	27.09	46.00	-18.91	QP	100	101	
6	573.2000	0.14	29.78	29.92	46.00	-16.08	QP	100	360	


Spurious Emissions, RX Mode, 9K-30M



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC 15.209_9k-30M_3m	Ant. Polarization:	N/A
Test item:	Radiation Emission	Test Time:	2018/11/29 21:50:53
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-RX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.0098	18.48	31.48	49.96	127.76	-77.80	QP	100	351	
2	0.0399	19.12	23.14	42.26	115.57	-73.31	QP	100	154	
3	0.0476	18.97	23.50	42.47	114.04	-71.57	QP	100	154	
4	0.0509	18.91	22.50	41.41	113.46	-72.05	QP	100	147	
5	0.0953	18.39	20.23	38.62	108.01	-69.39	QP	100	154	
6	0.1430	18.35	14.57	32.92	104.49	-71.57	QP	100	154	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC 15.209_9k-30M_3m	Ant. Polarization:	N/A
Test item:	Radiation Emission	Test Time:	2018/11/29 21:53:41
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-RX-PL0		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.2993	18.44	27.01	45.45	98.08	-52.63	QP	100	114	
2	0.7172	18.66	22.16	40.82	70.50	-29.68	QP	100	164	
3	1.1948	18.66	23.38	42.04	66.08	-24.04	QP	100	111	
4	3.4932	18.76	19.52	38.28	69.50	-31.22	QP	100	328	
5	4.2693	19.12	29.83	48.95	69.50	-20.55	QP	100	328	
6	12.7169	20.76	12.36	33.12	69.50	-36.38	QP	100	45	

Module with Shielded Case, Class 2


Spurious Emissions, TX Mode, 1-18G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel: +886-2172-7000 fax: +886-2528-0018




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/30 19:23:33
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-TX-PL2		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4882.000	3.61	42.14	45.75	74.00	-28.25	peak		0	
2	7323.000	4.66	45.88	50.54	74.00	-23.46	peak		0	
3	8429.000	4.94	44.85	49.79	74.00	-24.21	peak	100	14	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/30 19:24:26
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-TX-PL2		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4882.000	3.61	42.64	46.25	74.00	-27.75	peak			
2	7323.000	4.66	46.16	50.82	74.00	-23.18	peak			
3	8259.000	4.82	46.39	51.21	74.00	-22.79	peak	100	0	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/30 19:25:55
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2441-TX-PL2		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4882.000	3.61	43.45	47.06	74.00	-26.94	peak			
2	7323.000	4.66	45.05	49.71	74.00	-24.29	peak			
3	8259.000	4.82	45.79	50.61	74.00	-23.39	peak	100	20	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/30 19:26:47
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2441-TX-PL2		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4882.000	3.61	43.76	47.37	74.00	-26.63	peak			
2	7323.000	4.66	45.39	50.05	74.00	-23.95	peak			
3	8990.000	5.93	45.20	51.13	74.00	-22.87	peak	100	238	


Spurious Emissions, TX Mode, 18-26.5G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel: +886-2172-7000 fax: +886-2528-0018




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/30 20:29:43
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-TX-PL2		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21213.000	4.59	38.51	43.10	74.00	-30.90	peak		0	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/30 20:29:50
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-TX-PL2		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21111.000	4.69	39.37	44.06	74.00	-29.94	peak			



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/30 20:30:33
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2441-TX-PL2		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	24307.000	5.32	38.01	43.33	74.00	-30.67	peak			



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/30 20:30:39
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2441-TX-PL2		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20618.000	4.33	39.34	43.67	74.00	-30.33	peak			


Spurious Emissions, TX Mode, 30M-1G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Class B 3M Radiation	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/30 20:59:47
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-TX-PL2		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	155.1300	-7.59	37.22	29.63	43.50	-13.87	QP	100	0	
2	167.7400	-8.76	42.69	33.93	43.50	-9.57	QP	100	4	
3	299.6600	-4.56	37.82	33.26	46.00	-12.74	QP	100	66	
4	350.1000	-3.32	37.89	34.57	46.00	-11.43	QP	100	79	
5	468.4400	-1.69	34.55	32.86	46.00	-13.14	QP	100	282	
6	566.4100	0.07	31.89	31.96	46.00	-14.04	QP	100	85	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Class B 3M Radiation	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/30 21:00:40
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-TX-PL2		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	32.9100	-1.75	34.01	32.26	40.00	-7.74	QP	100	134	
2	167.7400	-8.76	39.99	31.23	43.50	-12.27	QP	100	301	
3	390.8400	-2.72	34.88	32.16	46.00	-13.84	QP	100	167	
4	398.6000	-2.37	37.78	35.41	46.00	-10.59	QP	100	167	
5	489.7800	-1.36	38.61	37.25	46.00	-8.75	QP	100	174	
6	566.4100	0.07	31.04	31.11	46.00	-14.89	QP	100	130	


Spurious Emissions, TX Mode, 9K-30M



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC 15.209_9k-30M_3m	Ant. Polarization:	N/A
Test item:	Radiation Emission	Test Time:	2018/11/30 21:19:39
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-TX-PL2		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.0090	18.32	31.12	49.44	128.50	-79.06	QP	100	305	
2	0.0219	19.00	25.60	44.60	120.78	-76.18	QP	100	223	
3	0.0379	19.16	24.00	43.16	116.02	-72.86	QP	100	115	
4	0.0466	18.99	21.18	40.17	114.22	-74.05	QP	100	0	
5	0.0789	18.57	13.54	32.11	109.65	-77.54	QP	100	36	
6	0.0909	18.43	12.96	31.39	108.42	-77.03	QP	100	157	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC 15.209_9k-30M_3m	Ant. Polarization:	N/A
Test item:	Radiation Emission	Test Time:	2018/11/30 21:22:45
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-TX-PL2		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.2992	18.44	25.85	44.29	98.08	-53.79	QP	100	95	
2	1.1947	18.66	23.36	42.02	66.08	-24.06	QP	100	115	
3	4.2096	19.09	14.62	33.71	69.50	-35.79	QP	100	292	
4	11.6123	20.63	12.10	32.73	69.50	-36.77	QP	100	265	
5	15.9406	21.13	11.27	32.40	69.50	-37.10	QP	100	341	
6	20.5375	21.63	10.99	32.62	69.50	-36.88	QP	100	359	


Spurious Emissions, RX Mode, 1-18G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel: +886-2172-7000 fax: +886-2528-0018




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/30 19:29:24
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-RX-PL2		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	2989.000	-2.22	46.48	44.26	74.00	-29.74	peak	100	239	
2	3431.000	-1.77	45.72	43.95	74.00	-30.05	peak	100	38	
3	4315.000	0.88	45.00	45.88	74.00	-28.12	peak	100	41	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/30 19:30:17
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-RX-PL2		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	2173.000	-4.65	47.80	43.15	74.00	-30.85	peak	100	132	
2	3210.000	-1.98	46.74	44.76	74.00	-29.24	peak	100	264	
3	4060.000	-0.08	45.06	44.98	74.00	-29.02	peak	100	2	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/30 19:31:58
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2441-RX-PL2		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	2292.000	-4.37	47.28	42.91	74.00	-31.09	peak	100	229	
2	3414.000	-1.79	45.29	43.50	74.00	-30.50	peak	100	3	
3	3771.000	-0.94	45.79	44.85	74.00	-29.15	peak	100	167	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/30 19:32:51
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2441-RX-PL2		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	2122.000	-4.78	48.77	43.99	74.00	-30.01	peak	100	83	
2	3108.000	-2.08	46.47	44.39	74.00	-29.61	peak	100	142	
3	3703.000	-1.14	46.49	45.35	74.00	-28.65	peak	100	251	


Spurious Emissions, RX Mode, 18-26.5G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel: +886-2172-7000 fax: +886-2528-0018




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/30 20:31:08
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-RX-PL2		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20975.000	4.76	38.84	43.60	74.00	-30.40	peak			




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/30 20:31:14
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-RX-PL2		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	23610.000	5.78	37.48	43.26	74.00	-30.74	peak			



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/30 20:31:38
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2441-RX-PL2		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21791.000	4.18	40.37	44.55	74.00	-29.45	peak			



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/30 20:31:45
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	3DH5-2441-RX-PL2		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	23091.500	5.41	38.04	43.45	74.00	-30.55	peak			


Spurious Emissions, RX Mode, 30M-1G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Class B 3M Radiation	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/30 21:02:03
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-RX-PL2		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	156.1000	-7.68	38.46	30.78	43.50	-12.72	QP	100	0	
2	167.7400	-8.76	43.12	34.36	43.50	-9.14	QP	100	145	
3	312.2700	-4.47	36.55	32.08	46.00	-13.92	QP	100	63	
4	352.0400	-3.26	38.26	35.00	46.00	-11.00	QP	100	79	
5	468.4400	-1.69	33.90	32.21	46.00	-13.79	QP	100	355	
6	566.4100	0.07	30.92	30.99	46.00	-15.01	QP	100	92	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Class B 3M Radiation	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/30 21:02:57
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-RX-PL2		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	32.9100	-1.75	33.88	32.13	40.00	-7.87	QP	100	141	
2	155.1300	-7.59	38.38	30.79	43.50	-12.71	QP	100	164	
3	167.7400	-8.76	41.02	32.26	43.50	-11.24	QP	100	341	
4	352.0400	-3.26	31.59	28.33	46.00	-17.67	QP	100	98	
5	395.6900	-2.54	30.87	28.33	46.00	-17.67	QP	100	160	
6	566.4100	0.07	31.32	31.39	46.00	-14.61	QP	100	124	


Spurious Emissions, RX Mode, 9K-30M



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC 15.209_9k-30M_3m	Ant. Polarization:	N/A
Test item:	Radiation Emission	Test Time:	2018/11/30 21:20:32
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-RX-PL2		
Remark:	shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.0096	18.44	31.37	49.81	127.94	-78.13	QP	100	359	
2	0.0252	19.13	23.15	42.28	119.56	-77.28	QP	100	105	
3	0.0438	19.04	21.74	40.78	114.76	-73.98	QP	100	95	
4	0.0678	18.71	14.84	33.55	110.97	-77.42	QP	100	360	
5	0.0961	18.38	12.80	31.18	107.94	-76.76	QP	100	81	
6	0.1085	18.33	10.52	28.85	106.89	-78.04	QP	100	265	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC 15.209_9k-30M_3m	Ant. Polarization:	N/A
Test item:	Radiation Emission	Test Time:	2018/11/30 21:23:38
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	20(°C)/60%
Model No.:	BM83SM1, BM83SL1	Test Engineer:	Curry Chen
Test Mode:	1DH5-2441-RX-PL2		
Remark:	shield		



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.2993	18.44	26.11	44.55	98.08	-53.53	QP	100	108	
2	1.1948	18.66	22.96	41.62	66.08	-24.46	QP	100	111	
3	5.1947	19.51	20.20	39.71	69.50	-29.79	QP	100	207	
4	12.2094	20.69	12.92	33.61	69.50	-35.89	QP	100	164	
5	18.5078	21.44	12.08	33.52	69.50	-35.98	QP	100	121	
6	19.7316	21.57	10.81	32.38	69.50	-37.12	QP	100	216	

Module without Shielded Case, Class 1



Spurious Emissions, Band Edges, 2.35-2.5G

Radiated Bandedge (GFSK)



Low Channel (Hor)





Low Channel (Ver)



High Channel (Hor)





High Channel (Ver)





Radiated Bandedge (8DPSK)


Low Channel (Hor)




Low Channel (Ver)



High Channel (Hor)





Date: 29.NOV.2018 16:29:09



Date: 29.NOV.2018 16:31:05

High Channel (Ver)




Spurious Emissions, TX Mode, 1-18G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel: +886-2172-7000 fax: +886-2528-0018




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 14:35:21
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2402-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4804.000	3.30	49.75	53.05	74.00	-20.95	peak	100	61	
2	4804.000	3.30	42.90	46.20	54.00	-7.80	AVG	100	61	
3	6559.000	5.64	44.86	50.50	74.00	-23.50	peak	100	71	
4	7206.000	4.77	45.87	50.64	74.00	-23.36	peak	100	167	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 14:34:29
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2402-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4804.000	3.30	48.65	51.95	74.00	-22.05	peak	100	34	
2	6185.000	5.55	44.55	50.10	74.00	-23.90	peak	100	1	
3	7206.000	4.77	46.12	50.89	74.00	-23.11	peak	100	210	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 14:44:30
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4882.000	3.61	46.58	50.19	74.00	-23.81	peak	100	75	
2	6185.000	5.55	44.29	49.84	74.00	-24.16	peak	100	126	
3	7323.000	4.66	46.33	50.99	74.00	-23.01	peak	100	189	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 14:43:38
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4882.000	3.61	43.16	46.77	74.00	-27.23	peak	100	158	
2	6066.000	5.49	44.57	50.06	74.00	-23.94	peak	100	74	
3	7323.000	4.66	46.18	50.84	74.00	-23.16	peak	100	196	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 14:48:14
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2480-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4960.000	3.93	46.07	50.00	74.00	-24.00	peak	100	141	
2	6423.000	5.69	43.97	49.66	74.00	-24.34	peak	100	274	
3	7440.000	4.54	46.24	50.78	74.00	-23.22	peak	100	224	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 14:47:21
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2480-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4960.000	3.93	44.97	48.90	74.00	-25.10	peak	100	185	
2	6304.000	5.62	44.79	50.41	74.00	-23.59	peak	100	359	
3	7440.000	4.54	45.31	49.85	74.00	-24.15	peak	100	197	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 14:52:03
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	3DH5-2402-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4804.000	3.30	47.86	51.16	74.00	-22.84	peak	100	127	
2	6389.000	5.68	44.96	50.64	74.00	-23.36	peak	100	17	
3	7206.000	4.77	45.58	50.35	74.00	-23.65	peak	100	193	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 14:51:11
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	3DH5-2402-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4804.000	3.30	47.47	50.77	74.00	-23.23	peak	100	207	
2	6049.000	5.47	44.71	50.18	74.00	-23.82	peak	100	43	
3	7206.000	4.77	46.09	50.86	74.00	-23.14	peak	100	116	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 14:56:00
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	3DH5-2441-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4882.000	3.61	43.49	47.10	74.00	-26.90	peak	100	174	
2	6185.000	5.55	45.15	50.70	74.00	-23.30	peak	100	95	
3	7323.000	4.66	44.94	49.60	74.00	-24.40	peak	100	216	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 14:55:07
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	3DH5-2441-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4882.000	3.61	42.56	46.17	74.00	-27.83	peak	100	116	
2	6593.000	5.60	45.68	51.28	74.00	-22.72	peak	100	8	
3	7323.000	4.66	46.55	51.21	74.00	-22.79	peak	100	279	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 14:59:33
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	3DH5-2480-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4960.000	3.93	45.21	49.14	74.00	-24.86	peak	100	278	
2	6406.000	5.69	45.22	50.91	74.00	-23.09	peak	100	51	
3	7440.000	4.54	45.07	49.61	74.00	-24.39	peak	100	174	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 14:58:41
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	3DH5-2480-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4960.000	3.93	43.70	47.63	74.00	-26.37	peak	100	163	
2	6491.000	5.73	44.80	50.53	74.00	-23.47	peak	100	340	
3	7440.000	4.54	44.23	48.77	74.00	-25.23	peak	100	241	


Spurious Emissions, TX Mode, 18-26.5G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel: +886-2172-7000 fax: +886-2528-0018




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/30 09:39:53
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2402-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20660.000	4.38	37.88	42.26	74.00	-31.74	peak	100	126	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/30 09:41:20
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2402-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20830.500	4.59	40.02	44.61	74.00	-29.39	peak	100	163	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/30 09:42:13
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	19368.500	3.97	39.70	43.67	74.00	-30.33	peak	100	146	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/30 09:43:30
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20975.000	4.76	38.51	43.27	74.00	-30.73	peak	100	154	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/30 09:44:04
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2480-RX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20125.000	4.24	40.29	44.53	74.00	-29.47	peak	100	179	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/30 09:45:15
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2480-RX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	19921.000	4.20	39.13	43.33	74.00	-30.67	peak	100	174	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/30 09:46:34
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	3DH5-2402-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20966.500	4.75	39.27	44.02	74.00	-29.98	peak	100	113	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/30 09:47:48
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	3DH5-2402-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21723.000	4.21	39.32	43.53	74.00	-30.47	peak	100	167	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/30 09:48:20
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	3DH5-2441-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20482.000	4.19	40.30	44.49	74.00	-29.51	peak	100	193	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/30 09:49:32
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	3DH5-2441-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	19683.000	3.98	40.00	43.98	74.00	-30.02	peak	100	174	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/30 09:50:30
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	3DH5-2480-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21468.000	4.36	39.46	43.82	74.00	-30.18	peak	100	157	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/30 09:51:42
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	3DH5-2480-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20048.500	4.26	39.89	44.15	74.00	-29.85	peak	100	133	


Spurious Emissions, TX Mode, 30M-1G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Class B 3M Radiation	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/30 08:55:46
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	153.1900	-7.51	36.84	29.33	43.50	-14.17	QP	100	268	
2	249.2200	-5.78	35.88	30.10	46.00	-15.90	QP	100	118	
3	316.1500	-4.42	38.52	34.10	46.00	-11.90	QP	100	329	
4	399.5700	-2.33	36.93	34.60	46.00	-11.40	QP	100	241	
5	566.4100	0.07	31.38	31.45	46.00	-14.55	QP	100	137	
6	779.8099	2.86	30.85	33.71	46.00	-12.29	QP	100	126	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Class B 3M Radiation	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/30 08:56:50
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	41.6400	-6.75	41.38	34.63	40.00	-5.37	QP	100	278	
2	172.5900	-9.20	41.05	31.85	43.50	-11.65	QP	100	275	
3	255.0400	-5.26	36.81	31.55	46.00	-14.45	QP	100	309	
4	325.8500	-4.14	38.77	34.63	46.00	-11.37	QP	100	208	
5	566.4100	0.07	37.56	37.63	46.00	-8.37	QP	100	168	
6	585.8100	0.21	34.39	34.60	46.00	-11.40	QP	100	178	


Spurious Emissions, TX Mode, 9K-30M



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC 15.209_9k-30M_3m	Ant. Polarization:	N/A
Test item:	Radiation Emission	Test Time:	2018/11/30 09:11:38
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.0095	18.42	31.69	50.11	128.03	-77.92	QP	100	187	
2	0.0242	19.09	23.34	42.43	119.91	-77.48	QP	100	212	
3	0.0421	19.08	21.33	40.41	115.11	-74.70	QP	100	230	
4	0.0551	18.86	22.39	41.25	112.77	-71.52	QP	100	204	
5	0.0723	18.65	14.87	33.52	110.41	-76.89	QP	100	152	
6	0.1161	18.34	14.25	32.59	106.30	-73.71	QP	100	198	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC 15.209_9k-30M_3m	Ant. Polarization:	N/A
Test item:	Radiation Emission	Test Time:	2018/11/30 09:15:05
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-TX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.1798	18.37	25.26	43.63	102.50	-58.87	QP	100	0	
2	1.1947	18.66	19.30	37.96	66.08	-28.12	QP	100	252	
3	5.3439	19.53	12.73	32.26	69.50	-37.24	QP	100	291	
4	9.2243	20.29	12.58	32.87	69.50	-36.63	QP	100	78	
5	13.8810	20.90	11.26	32.16	69.50	-37.34	QP	100	260	
6	18.5376	21.44	11.00	32.44	69.50	-37.06	QP	100	41	


Spurious Emissions, RX Mode, 1-18G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel: +886-2172-7000 fax: +886-2528-0018




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 15:04:27
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-RX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4315.000	0.88	45.81	46.69	74.00	-27.31	peak	100	335	
2	6100.000	4.46	44.12	48.58	74.00	-25.42	peak	100	276	
3	7086.000	3.84	47.87	51.71	74.00	-22.29	peak	100	113	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 15:03:35
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-RX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4383.000	1.14	45.65	46.79	74.00	-27.21	peak	100	26	
2	5981.000	4.36	44.15	48.51	74.00	-25.49	peak	100	104	
3	7239.000	3.69	47.32	51.01	74.00	-22.99	peak	100	12	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 15:06:32
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	3DH5-2441-RX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4179.000	0.37	45.53	45.90	74.00	-28.10	peak	100	63	
2	5981.000	4.36	44.79	49.15	74.00	-24.85	peak	100	108	
3	7256.000	3.68	47.11	50.79	74.00	-23.21	peak	100	282	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 15:07:24
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	3DH5-2441-RX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4264.000	0.69	45.48	46.17	74.00	-27.83	peak	100	68	
2	4978.000	3.00	43.13	46.13	74.00	-27.87	peak	100	95	
3	6270.000	4.56	44.43	48.99	74.00	-25.01	peak	100	24	


Spurious Emissions, RX Mode, 18-26.5G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel: +886-2172-7000 fax: +886-2528-0018




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/30 09:52:06
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-RX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	19351.500	3.99	40.06	44.05	74.00	-29.95	peak	100	198	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/30 09:53:17
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-RX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21077.000	4.72	39.21	43.93	74.00	-30.07	peak	100	37	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/30 09:54:38
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	3DH5-2441-RX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21723.000	4.21	38.59	42.80	74.00	-31.20	peak	100	173	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/30 09:55:49
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	3DH5-2441-RX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20643.500	4.37	39.48	43.85	74.00	-30.15	peak	100	112	


Spurious Emissions, RX Mode, 30M-1G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Class B 3M Radiation	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/30 08:58:51
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-RX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	167.7400	-8.76	38.38	29.62	43.50	-13.88	QP	100	251	
2	210.4200	-8.58	39.06	30.48	43.50	-13.02	QP	100	278	
3	249.2200	-5.78	36.71	30.93	46.00	-15.07	QP	100	142	
4	313.2400	-4.46	37.56	33.10	46.00	-12.90	QP	100	337	
5	344.2799	-3.51	36.15	32.64	46.00	-13.36	QP	100	300	
6	566.4100	0.07	30.60	30.67	46.00	-15.33	QP	100	150	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Class B 3M Radiation	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/30 08:59:54
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-RX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	41.6400	-6.75	41.05	34.30	40.00	-5.70	QP	100	277	
2	210.4200	-8.58	40.92	32.34	43.50	-11.16	QP	100	196	
3	257.9500	-5.01	38.88	33.87	46.00	-12.13	QP	100	218	
4	398.6000	-2.37	43.29	40.92	46.00	-5.08	QP	100	207	
5	536.3400	-0.94	36.74	35.80	46.00	-10.20	QP	100	349	
6	566.4100	0.07	37.72	37.79	46.00	-8.21	QP	100	162	


Spurious Emissions, RX Mode, 9K-30M



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC 15.209_9k-30M_3m	Ant. Polarization:	N/A
Test item:	Radiation Emission	Test Time:	2018/11/30 09:12:42
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-RX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.0098	18.48	31.94	50.42	127.76	-77.34	QP	100	242	
2	0.0256	19.14	22.96	42.10	119.43	-77.33	QP	100	333	
3	0.0421	19.08	22.40	41.48	115.11	-73.63	QP	100	325	
4	0.0571	18.83	23.98	42.81	112.46	-69.65	QP	100	194	
5	0.0902	18.44	13.21	31.65	108.49	-76.84	QP	100	200	
6	0.1148	18.34	12.25	30.59	106.40	-75.81	QP	100	202	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC 15.209_9k-30M_3m	Ant. Polarization:	N/A
Test item:	Radiation Emission	Test Time:	2018/11/30 09:16:08
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-RX-PL0		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.2992	18.44	25.63	44.07	98.08	-54.01	QP	100	218	
2	1.1947	18.66	19.02	37.68	66.08	-28.40	QP	100	154	
3	5.6722	19.60	12.79	32.39	69.50	-37.11	QP	100	234	
4	12.2989	20.70	12.25	32.95	69.50	-36.55	QP	100	354	
5	14.2989	20.94	11.09	32.03	69.50	-37.47	QP	100	274	
6	19.0749	21.50	10.78	32.28	69.50	-37.22	QP	100	338	

Module without Shielded Case, Class 2


Spurious Emissions, TX Mode, 1-18G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel: +886-2172-7000 fax: +886-2528-0018




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 15:16:28
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-TX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4882.000	3.61	42.89	46.50	74.00	-27.50	peak	100	166	
2	6185.000	5.55	44.36	49.91	74.00	-24.09	peak	100	108	
3	7323.000	4.66	46.11	50.77	74.00	-23.23	peak	100	248	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 15:17:20
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-TX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4882.000	3.61	42.89	46.50	74.00	-27.50	peak	100	109	
2	6355.000	5.66	44.76	50.42	74.00	-23.58	peak	100	61	
3	7323.000	4.66	46.67	51.33	74.00	-22.67	peak	100	243	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 15:19:19
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	3DH5-2441-TX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4882.000	3.61	43.25	46.86	74.00	-27.14	peak	100	166	
2	6474.000	5.72	45.09	50.81	74.00	-23.19	peak	100	217	
3	7323.000	4.66	45.31	49.97	74.00	-24.03	peak	100	145	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 15:20:11
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	3DH5-2441-TX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4882.000	3.61	42.62	46.23	74.00	-27.77	peak	100	113	
2	6083.000	5.49	45.34	50.83	74.00	-23.17	peak	100	360	
3	7323.000	4.66	46.78	51.44	74.00	-22.56	peak	100	291	


Spurious Emissions, TX Mode, 18-26.5G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel: +886-2172-7000 fax: +886-2528-0018




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/12/3 11:23:30
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	22.4(°C)/57%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Kevin Kuo
Test Mode:	1DH5-2441-TX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	19955.000	4.23	40.63	44.86	74.00	-29.14	peak	100	271	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/12/3 11:24:32
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	22.4(°C)/57%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Kevin Kuo
Test Mode:	1DH5-2441-TX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	22122.500	4.21	39.34	43.55	74.00	-30.45	peak	100	205	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/12/3 11:31:27
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	22.4(°C)/57%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Kevin Kuo
Test Mode:	3DH5-2441-TX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	25871.000	5.71	40.67	46.38	74.00	-27.62	peak	100	232	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/12/3 11:32:29
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	22.4(°C)/57%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Kevin Kuo
Test Mode:	3DH5-2441-TX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20754.000	4.49	40.48	44.97	74.00	-29.03	peak	100	258	


Spurious Emissions, TX Mode, 30M-1G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Class B 3M Radiation	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/30 08:45:53
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-TX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	148.3400	-7.23	37.45	30.22	43.50	-13.28	QP	100	97	
2	211.3900	-8.58	40.13	31.55	43.50	-11.95	QP	100	297	
3	251.1600	-5.59	36.01	30.42	46.00	-15.58	QP	100	145	
4	335.5500	-3.73	37.59	33.86	46.00	-12.14	QP	100	150	
5	399.5700	-2.33	37.89	35.56	46.00	-10.44	QP	100	252	
6	773.9900	2.75	32.57	35.32	46.00	-10.68	QP	100	137	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Class B 3M Radiation	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/30 08:46:56
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-TX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	52.3100	-12.12	47.62	35.50	40.00	-4.50	QP	100	269	
2	211.3900	-8.58	41.80	33.22	43.50	-10.28	QP	100	189	
3	390.8400	-2.72	43.76	41.04	46.00	-4.96	QP	100	229	
4	398.6000	-2.37	43.60	41.23	46.00	-4.77	QP	100	202	
5	566.4100	0.07	38.14	38.21	46.00	-7.79	QP	100	156	
6	842.8600	3.80	34.60	38.40	46.00	-7.60	QP	100	285	


Spurious Emissions, TX Mode, 9K-30M



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC 15.209_9k-30M_3m	Ant. Polarization:	N/A
Test item:	Radiation Emission	Test Time:	2018/11/30 09:07:47
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-TX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.0091	18.34	32.52	50.86	128.40	-77.54	QP	100	249	
2	0.0208	18.95	24.38	43.33	121.23	-77.90	QP	100	147	
3	0.0419	19.08	22.24	41.32	115.15	-73.83	QP	100	209	
4	0.0565	18.84	21.20	40.04	112.55	-72.51	QP	100	190	
5	0.0748	18.62	14.14	32.76	110.12	-77.36	QP	100	180	
6	0.1148	18.34	12.20	30.54	106.40	-75.86	QP	100	204	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC 15.209_9k-30M_3m	Ant. Polarization:	N/A
Test item:	Radiation Emission	Test Time:	2018/11/30 09:18:11
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-TX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.2992	18.44	25.88	44.32	98.08	-53.76	QP	100	230	
2	1.1947	18.66	20.19	38.85	66.08	-27.23	QP	100	238	
3	4.7469	19.35	13.14	32.49	69.50	-37.01	QP	100	12	
4	7.2244	19.90	13.04	32.94	69.50	-36.56	QP	100	244	
5	12.7467	20.76	11.55	32.31	69.50	-37.19	QP	100	268	
6	17.4928	21.31	11.78	33.09	69.50	-36.41	QP	100	4	


Spurious Emissions, RX Mode, 1-18G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel: +886-2172-7000 fax: +886-2528-0018




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 15:25:12
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-RX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4757.000	2.34	44.27	46.61	74.00	-27.39	peak	100	336	
2	6406.000	4.65	44.39	49.04	74.00	-24.96	peak	100	169	
3	7239.000	3.69	47.52	51.21	74.00	-22.79	peak	100	134	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 15:26:04
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-RX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4213.000	0.49	46.61	47.10	74.00	-26.90	peak	100	218	
2	6117.000	4.48	43.97	48.45	74.00	-25.55	peak	100	187	
3	7069.000	3.86	46.33	50.19	74.00	-23.81	peak	100	276	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/29 15:27:18
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	3DH5-2441-RX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4111.000	0.12	46.60	46.72	74.00	-27.28	peak	100	306	
2	6576.000	4.58	44.73	49.31	74.00	-24.69	peak	100	0	
3	7239.000	3.69	46.89	50.58	74.00	-23.42	peak	100	43	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/29 15:28:10
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	24(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	3DH5-2441-RX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4315.000	0.88	45.61	46.49	74.00	-27.51	peak	100	301	
2	6066.000	4.45	44.25	48.70	74.00	-25.30	peak	100	229	
3	7154.000	3.78	46.44	50.22	74.00	-23.78	peak	100	133	


Spurious Emissions, RX Mode, 18-26.5G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel: +886-2172-7000 fax: +886-2528-0018




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/12/3 11:18:19
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	22.4(°C)/57%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Kevin Kuo
Test Mode:	1DH5-2441-RX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	19674.500	3.97	40.49	44.46	74.00	-29.54	peak	100	221	




Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/12/3 11:19:22
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	22.4(°C)/57%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Kevin Kuo
Test Mode:	1DH5-2441-RX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	22692.000	4.91	39.96	44.87	74.00	-29.13	peak	100	92	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/12/3 11:01:21
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	22.4(°C)/57%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Kevin Kuo
Test Mode:	3DH5-2441-RX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20567.000	4.27	40.28	44.55	74.00	-29.45	peak	100	10	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/12/3 11:02:24
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	22.4(°C)/57%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Kevin Kuo
Test Mode:	3DH5-2441-RX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20490.500	4.20	40.42	44.62	74.00	-29.38	peak	100	0	


Spurious Emissions, RX Mode, 30M-1G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Class B 3M Radiation	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/11/30 08:50:07
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%)	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-RX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	167.7400	-8.76	37.68	28.92	43.50	-14.58	QP	100	261	
2	211.3900	-8.58	40.05	31.47	43.50	-12.03	QP	100	296	
3	249.2200	-5.78	36.45	30.67	46.00	-15.33	QP	100	149	
4	327.7900	-4.04	37.83	33.79	46.00	-12.21	QP	100	141	
5	399.5700	-2.33	38.44	36.11	46.00	-9.89	QP	100	250	
6	893.3000	4.27	31.25	35.52	46.00	-10.48	QP	100	141	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC&ISED Class B 3M Radiation	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/30 08:52:24
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-RX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	52.3100	-12.12	47.87	35.75	40.00	-4.25	QP	100	287	
2	210.4200	-8.58	41.28	32.70	43.50	-10.80	QP	100	185	
3	323.9100	-4.23	38.40	34.17	46.00	-11.83	QP	100	201	
4	390.8400	-2.72	38.68	35.96	46.00	-10.04	QP	100	255	
5	566.4100	0.07	38.40	38.47	46.00	-7.53	QP	100	156	
6	881.6600	4.06	35.46	39.52	46.00	-6.48	QP	100	169	


Spurious Emissions, RX Mode, 9K-30M



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC 15.209_9k-30M_3m	Ant. Polarization:	N/A
Test item:	Radiation Emission	Test Time:	2018/11/30 09:08:51
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-RX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.0098	18.48	32.08	50.56	127.76	-77.20	QP	100	51	
2	0.0280	19.24	23.30	42.54	118.65	-76.11	QP	100	67	
3	0.0421	19.08	21.04	40.12	115.11	-74.99	QP	100	196	
4	0.0567	18.84	21.23	40.07	112.52	-72.45	QP	100	187	
5	0.0815	18.54	14.28	32.82	109.37	-76.55	QP	100	193	
6	0.1169	18.34	11.78	30.12	106.24	-76.12	QP	100	201	



Service No.:	114080534	Test Distance:	3m
Test Standard:	FCC 15.209_9k-30M_3m	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/11/30 09:19:14
Applicant:	Microchip Technology Inc.	Test Rating:	DC 3.8V
Product:	Bluetooth Module	Temp.(°C)/Hum.(%):	21.3(°C)/52%
Model No.:	BM83AM1, BM83AL1	Test Engineer:	Amy Hsu
Test Mode:	1DH5-2441-RX-PL2		
Remark:	un-shield		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.1500	18.36	25.25	43.61	104.08	-60.47	QP	100	216	
2	1.1948	18.66	20.02	38.68	66.08	-27.40	QP	100	248	
3	4.7171	19.33	12.54	31.87	69.50	-37.63	QP	100	232	
4	11.7020	20.64	12.27	32.91	69.50	-36.59	QP	100	280	
5	13.8213	20.88	11.26	32.14	69.50	-37.36	QP	100	258	
6	17.7018	21.34	10.94	32.28	69.50	-37.22	QP	100	1	


Mains



TUV Rheinland Taiwan Ltd.
11F., No.758, Sec.4 Bade Road, Songshan Dist, Taipei City 105
Tel:+886-2172-7000 Fax:+886-2528-0018

File: C:\EMC\Report\2018\Microchip\114083527(BM83SM1-00AA)\114083527(BM83SM1-00AA)_00001.EMI

Date: 2018-11-12 Time: 11:46:22




Trace: 1

Site : Conduction room
Condition : FCC Part15 Class B Conduction(QP) line1
Test Engineer: Amy Hsu
Applicant : Microchip Technology
Product : Bluetooth Module
Model No. : BM83SM1, BM83SL1
Test Rating : 15VDC(EVB- Host Board supply)
Tmp/Hum : 21.8°C/48%
Memo : BT link mode

		Read		Limit	Over	
	Freq	Level	Factor	Level	Line	Limit Remark
	MHz	dBuV	dB	dBuV	dBuV	dB
1	0.156	34.64	9.68	44.32	65.67	-21.35 QP
2	0.156	12.18	9.68	21.86	55.67	-33.81 Average
3	0.257	21.72	9.68	31.40	61.54	-30.14 QP
4	0.257	1.96	9.68	11.64	51.54	-39.98 Average
5	0.707	20.72	9.69	30.41	56.00	-25.59 QP
6	0.707	19.85	9.69	29.54	46.00	-16.46 Average
7	2.601	10.23	9.72	19.95	56.00	-36.05 QP
8	2.601	-2.74	9.72	6.98	46.00	-39.02 Average
9	3.720	7.72	9.74	17.46	56.00	-38.54 QP
10	3.720	-4.10	9.74	5.64	46.00	-40.36 Average
11	20.157	6.46	9.86	16.32	60.00	-43.68 QP
12	20.157	0.81	9.86	10.67	50.00	-39.33 Average

File: C:\EMC\Report\2018\Microchip\114083527(BM83SM1-00AA)\114083527(BM83SM1-00AA)_00003.EMI



Trace: 1

Site : Conduction room
Condition : FCC Part15 Class B Conduction(QP) neutral
Test Engineer: Amy Hsu
Applicant : Microchip Technology
Product : Bluetooth Module
Model No. : BM83SM1, BM83SL1
Test Rating : 15VDC(EVB- Host Board supply)
Temp/Hum : 21.8°C / 48%
Memo : BT link mode

		Read			Limit	Over	
	Freq	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.153	35.01	9.68	44.69	65.83	-21.14	QP
2	0.153	13.07	9.68	22.75	55.83	-33.08	Average
3	0.298	25.11	9.67	34.78	60.30	-25.52	QP
4	0.298	3.14	9.67	12.81	50.30	-37.49	Average
5	0.666	14.22	9.69	23.91	56.00	-32.09	QP
6	0.666	-1.81	9.69	7.88	46.00	-38.12	Average
7	1.800	9.09	9.72	18.81	56.00	-37.19	QP
8	1.800	-2.67	9.72	7.05	46.00	-38.95	Average
9	2.761	9.84	9.73	19.57	56.00	-36.43	QP
10	2.761	-0.92	9.73	8.81	46.00	-37.19	Average
11	20.359	8.58	9.91	18.49	60.00	-41.51	QP
12	20.359	2.75	9.91	12.66	50.00	-37.34	Average