

FCC PART 15 SUBPART C MEASURMENT AND TEST REPORT

For

Beijing Hisign Technology Co., Ltd.

6F, Tower 4, Hanwei International Square, Area 4, No.186, West Road, 4.th South Ring Road, Fengtai District, Beijing, China

E.U.T.: Mobile Multi-Biometric Information Collection and Identification System

Model Name: HX-B8197LP, HX-B8197LR

Brand Name: Religing Histografic Conclude

FCC ID: 2ADJEB8197LPB8197LR

Report Number: NTC1410485F

Test Date(s): October 25, 2014 to November 25, 2014

Report Date(s): November 25, 2014

Prepared by

Dongguan Nore Testing Center Co., Ltd.

Building D, Gaosheng Science and Technology Park, Hongtu Road, Nancheng District, Dongguan City, Guangdong, China

Tel: +86-769-22022444

Fax: +86-769-22022799

Prepared By

Approved & Authorized Signer

Rose Hu / Engineer

Sunm V 6 Q.A. Director

Note: This test report is for the customer shown above and their specific product only. It may not be duplicated or used in part without prior written consent from Dongguan Nore Testing Center Co., Ltd. The test results referenced from this report are relevant only to the sample tested.



Table of Contents

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST	4
1.2 RELATED SUBMITTAL(S) / GRANT (S)	6
1.3 TEST METHODOLOGY	6
1.4 EQUIPMENT MODIFICATIONS	-
1.5 SUPPORT DEVICE	
1.6 TEST FACILITY AND LOCATION	
1.7 SUMMARY OF TEST RESULTS	
2. SYSTEM TEST CONFIGURATION	8
2.1 EUT CONFIGURATION	8
2.2 SPECIAL ACCESSORIES	
2.3 DESCRIPTION OF TEST MODES	
2.4 EUT EXERCISE	
3. CONDUCTED EMISSIONS TEST	9
3.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	9
3.2 TEST CONDITION	
3.3 MEASUREMENT RESULTS	
4. RADIATED EMISSION TEST	12
4.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	12
4.2 MEASUREMENT PROCEDURE	
4.3 LIMIT	
4.4 MEASUREMENT RESULTS	
5. CHANNEL SEPARATION TEST	18
5.1 MEASUREMENT PROCEDURE	18
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	18
5.3 MEASUREMENT RESULTS	18
6. 20DB BANDWIDTH	24
6.1 MEASUREMENT PROCEDURE	24
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	24
6.3 MEASUREMENT RESULTS	24
7. HOPPING CHANNEL NUMBER	25
7.1 MEASUREMENT PROCEDURE	30
7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
7.3 MEACHDEMENT DECLILTS	30



8. TIME OF OCCUPANCY (DWELL TIME)	32
8.1 MEASUREMENT PROCEDURE	32
8.2 MEASUREMENT RESULTS	32
9. MAXIMUM PEAK OUTPUT POWER	32
9.1 MEASUREMENT PROCEDURE	38
9.2 MEASUREMENT RESULTS	
10. BAND EDGE	38
10.1 Measurement Procedure	44
10.2 LIMIT	
10.3 MEASUREMENT RESULTS	45
11. ANTENNA APPLICATION	45
11.1 ANTENNA REQUIREMENT	52
11.2 MEASUREMENT RESULTS	52
12. CONDUCTED SPURIOUS EMISSIONS	53
12.1 MEASUREMENT PROCEDURE	53
12.2. MEASUREMENT RESULTS	53
13. TEST EQUIPMENT LIST	56

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR



1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test

This device is a Mobile Multi-Biometric Information Collection and Identification System with WIFI and BT, etc functions. It's powered by DC 11.1V Li-ion battery or DC 19V come from Adapter. For more details features, please refer to User's Manual.

Manufacturer : Beijing Hisign Technology Co., Ltd.

Address : 6F, Tower 4, Hanwei International Square, Area 4,

No.186, West Road, 4.th South Ring Road, Fengtai

District, Beijing, China

Power Supply : DC 11.1V Li-ion battery

DC 19V come from Adapter,

M/N: PA-1900-24

Input: AC 100-240V 50-60Hz, 1.5 Max

Output: DC 19V 4.75A

Model name : HX-B8197LP, HX-B8197LR

Note : Both of them are the same except for the type of

identification and model name due to marketing

purpose.

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR



Technical parameters For WIFI Function

Frequency Range : 2412-2462MHz for 802.11b/g/n(HT20)

2422-2452MHz for 802.11n(HT40)

Modulation : CCK, DQPSK, DBPSK for 802.11b

OFDM for 802.11g/n

Number of Channel : 11 for 802.11b/g/n(HT20)

7 for 802.11n(HT40)

Channel space : 5MHz

Date Rate : 802.11b:1~11Mbps, 802.11g:6~54Mbps

802.11n: 6.5~135Mbps

Antenna Type : Integral

Antenna Gain : 0 dBi (declared by manufacturer)

For BT function

BT Version : BLE and backward compatible 3.0HS, 2.1+EDR

version. We prepare version BLE and 2.1+EDR for

RF test.

Frequency: : 2402-2480MHz

Modulation : For V2.1+EDR: GFSK, π/4-DQPSK, 8DPSK

For V4.0: GFSK

Number of Channel : For V2.1+EDR: 79; For V4.0: 40

Channel space : For V2.1+EDR: 1MHz; For V4.0: 2MHz

Antenna Type : Integral

Antenna Gain : 0 dBi (declared by manufacturer)

Note : N/A

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR



1.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: 2ADJEB8197LPB8197LR filing to comply with Section 15.247 of the FCC Part 15 (2013), Subpart C Rule.

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2009) and DA 00-705. Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters.

1.4 Equipment Modifications

Not available for this EUT intended for grant.

1.5 Support Device

None

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR



1.6 Test Facility and Location

Listed by FCC, August 02, 2011 The Certificate Registration Number is 665078. Listed by Industry Canada, July 01, 2011 The Certificate Registration Number is 46405-9743.

Dongguan NTC Co., Ltd.

(Full Name: Dongguan Nore Testing Center Co., Ltd.)

Building D, Gaosheng Science and Technology Park, Hongtu Road, Nancheng District, Dongguan City, Guangdong, China (Full Name: Building D, Gaosheng Science & Technology Park, Zhouxi Longxi Road, Nancheng District, Dongguan, Guangdong, China.

1.7 Summary of Test Results

FCC Rules	Description Of Test	Result
§15.247(a)(1)	Channel Separation test	Compliant
§15.247(a)(1)	20dB Bandwidth	Compliant
§15.247(a)(1)(iii)	Hopping Channel Number	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(b)	Max Peak output Power test	Compliant
§15.247(d)	Band edge test	Compliant
§15.207 (a)	AC Power Conducted Emission	Compliant
§15.247(d),§15.209, §15.205	Radiated Emission	Compliant
§15.203	Antenna Requirement	Compliant
§15.247(d)	Conducted Spurious Emission	Compliant

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR



2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 Special Accessories

Not available for this EUT intended for grant.

2.3 Description of test modes

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and normal mode is programmed. The Lowest, middle and highest channel were chosen for testing, and all packets DH1, DH3 and DH5 mode in all modulation type GFSK, $\pi/4$ -DQPSK, 8DPSK were tested.


2.4 EUT Exercise

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.



3. Conducted Emissions Test

3.1 Test SET-UP (Block Diagram of Configuration)



3.2 Test Condition

Test Requirement: FCC Part 15.207

Frequency Range: 150KHz ~ 30MHz

Detector: RBW 9KHz, VBW 30KHz

Operation Mode: BT Mode

3.3 Measurement Results

Please refer to following plots.

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR




Site: Conduction



Dongguan NTC Co., Ltd. Tel: +86-769-22022444 Fax: +86-769-22022799

ng Center Web: Http://www.ntc-c.com



Report No.: HX-B8197LP

Test Standard: FCC PART 15_Class B_QP

Test item: Conducted Emission

 Applicant:
 Hisign
 Temp.()/Hum.(%):
 25(C) / 56 %

 Product:
 Power Rating:
 AC 120V/60Hz

 Model No.:
 HX-B8197LP
 Test Engineer:
 Jason

Phase:

Test Mode: BT Mode

Remark: Mobile Multi-Biometric Information Collection and Identification System

No.	Frequency (MHz)	Factor (dBuV)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1499	10.80	39.30	50.10	66.00	-15.90	QP	Р	
2	0.1499	10.80	30.30	41.10	56.00	-14.90	AVG	Р	
3	0.2971	10.80	35.40	46.20	60.32	-14.12	QP	Р	
4	0.2971	10.80	23.80	34.60	50.32	-15.72	AVG	Р	
5	0.3810	10.80	30.30	41.10	58.26	-17.16	QP	Р	
6	0.3810	10.80	25.40	36.20	48.26	-12.06	AVG	Ρ	
7	0.4259	10.80	31.80	42.60	57.33	-14.73	QP	Р	
8	0.4259	10.80	28.30	39.10	47.33	-8.23	AVG	Ρ	
9	3.0574	10.80	26.00	36.80	56.00	-19.20	QP	Р	
10	3.0574	10.80	17.90	28.70	46.00	-17.30	AVG	Ρ	
11	5.8357	10.80	22.70	33.50	60.00	-26.50	QP	Р	
12	5.8357	10.80	10.90	21.70	50.00	-28.30	AVG	Р	

Note: Level=Reading+Factor.

Margin=Limit-Level.

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR






Dongguan NTC Co., Ltd. Tel: +86-769-22022444 Fax: +86-769-22022799

g Center Web: Http://www.ntc-c.com

Site: Conduction



Phase:

Report No.: HX-B8197LP

Test Standard: FCC PART 15_Class B_QP

Test item: Conducted Emission

 Applicant:
 Hisign
 Temp.()/Hum.(%):
 25(C) / 56 %

 Product:
 Power Rating:
 AC 120V/60Hz

 Model No.:
 HX-B8197LP
 Test Engineer:
 Jason

Test Mode: BT Mode

Remark: Mobile Multi-Biometric Information Collection and Identification System

No.	Frequency (MHz)	Factor (dBuV)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1499	10.80	37.60	48.40	66.00	-17.60	QP	Р	
2	0.1499	10.80	28.00	38.80	56.00	-17.20	AVG	Р	
3	0.2847	10.80	33.40	44.20	60.68	-16.48	QP	Р	
4	0.2847	10.80	20.40	31.20	50.68	-19.48	AVG	Ք	
5	0.3850	10.80	33.10	43.90	58.17	-14.27	QP	Р	
6	0.3850	10.80	28.80	39.60	48.17	-8.57	AVG	Р	
7	0.4259	10.80	31.90	42.70	57.33	-14.63	QP	Р	
8	0.4259	10.80	28.00	38.80	47.33	-8.53	AVG	Р	
9	3.4355	10.80	27.40	38.20	56.00	-17.80	QP	Р	
10	3.4355	10.80	17.50	28.30	46.00	-17.70	AVG	Р	
11	8.0624	10.80	21.10	31.90	60.00	-28.10	QP	Դ	
12	8.0624	10.80	10.30	21.10	50.00	-28.90	AVG	Р	

Note: Level=Reading+Factor.


Margin=Limit-Level.




4. Radiated Emission Test

4.1 Test SET-UP (Block Diagram of Configuration)


4.1.1 Radiated Emission Test Set-Up, Frequency Below 30MHz







4.1.2 Radiated Emission Test Set-Up, Frequency above 1GHz



4.2 Measurement Procedure

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode.
- e. A Quasi-peak measurement was then made for that frequency point for below 1GHz test. PK and AV for above 1GHz emission test.

For 30MHz to 1GHz:

Sept the spectrum analyzer as: RBW=120kHz, VBW=300kHz, Detector=Quasi-Peak

For Above 1GHz:

Set the spectrum analyzer as: RBW=1MHz, VBW=3MHz, Detector=Peak. Set the spectrum analyzer as: RBW=1MHz, VBW=10Hz, Detector=Peak.

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR



During the radiated emission test, the spectrum analyzer was set with the following configurations:

Frequency Band (MHz)	Level	Resolution Bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	3 MHz
Above 1000	Average	1 MHz	10 Hz

4.3 Limit

Frequency range	Distance Meters	Field Strengths Limit (15.209)
MHz		μV/m
0.009 ~ 0.490	300	2400/F(kHz)
0.490 ~ 1.705	30	24000/F(kHz)
1.705 ~ 30	30	30
30 ~ 88	3	100
88 ~ 216	3	150
216 ~ 960	3	200
Above 960	3	500

Remark : (1) Emission level (dB) μ V = 20 log Emission level μ V/m

- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
- (4) The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR



4.4 Measurement Results

Operation Mode: TX

Frequency Range: 9KHz~1GHz Temperature: 24 °C Test Result: PASS Humidity: 53 % Measured Distance: 3m Test By: Sance

Test Date: October 25, 2014

Freq.	Ant.Pol.	Emission	Limit	Margin	Note
		Level	3m		
(MHz)	H/V	(dBuV/m)	(dBuV/m)	(dB)	
31.9400	V	33.03	40.00	-6.97	QP
64.9200	V	32.73	40.00	-7.27	QP
180.3497	V	33.74	43.50	-9.76	QP
812.7898	V	38.99	46.00	-7.01	QP
161.9299	Н	33.51	43.50	-9.99	QP
180.3497	H	33.77	43.50	-9.73	QP
331.6700	Н	37.03	46.00	-8.97	QP
780.7798	Н	39.47	46.00	-6.53	QP

Other emissions are lower than 10dB below the allowable limit.


Note: (1) Emission Level= Reading Level + Factor


- (2) Factor= Antenna Gain + Cable Loss Amplifier Gain
- (3) Measurement uncertainty: ±3.4dB
- (4) Loop antenna used for the emission below 30MHz.
- (5) Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 10dB below the permissible limits.

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR







Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR



Modulation: GFSK (the worst case)

Frequency Range: 1-25GHz Test Date: October 25, 2014

Test Result: PASS Temperature: 24 °C Measured Distance: 3m Humidity: 53 %

Test By: Sance

Freq.	Ant.Pol.	Emission	Level(dBuV)	Limit 3m	(dBuV/m)	Marg	in(dB)
(MHz)	H/V	PK	AV	PK	AV	PK	AV
		Oper	ation Mode:	TX Mode	(Low)		
4804	V	55.17	41.05	74.00	54.00	-18.83	-12.95
7206	V	56.00	43.56	74.00	54.00	-18.00	-10.44
4804	Н	54.38	42.58	74.00	54.00	-19.62	-11.42
7206	Н	52.07	42.64	74.00	54.00	-21.93	-11.36
		Opei	ration Mode:	TX Mode	(Mid)		
4882	V	57.14	39.82	74.00	54.00	-16.86	-14.18
7323	V	57.39	40.63	74.00	54.00	-16.61	-13.37
4882	Н	56.07	40.81	74.00	54.00	-17.93	-13.19
7323	Н	58.21	40.36	74.00	54.00	-15.79	-13.64
	1	Oper	ation Mode:	TX Mode	(High)	T	T
4960	V	55.20	38.78	74.00	54.00	-18.80	-15.22
7440	V	52.33	37.60	74.00	54.00	-21.67	-16.40
4960	Н	53.28	40.11	74.00	54.00	-20.72	-13.89
7440	Н	54.31	41.52	74.00	54.00	-19.69	-12.48

Note:

- (1) All Readings are Peak Value and AV.
- (2) Emission Level= Reading Level + Factor
- (3) Factor= Antenna Gain + Cable Loss Amplifier Gain
- (4) Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 10dB below the permissible limits.
- (5) Measurement uncertainty: ±3.7dB.
- (6) Horn antenna used for the emission over 1000MHz.

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR



5. Channel Separation test

5.1 Measurement Procedure

Minimum Hopping Channel Carrier Frequency Separation, FCC Rule 15.247(a)(1):

Connect EUT antenna terminal to the spectrum analyzer with a low loss cable, and using the MARKER and Max-Hold function to record the separation of two adjacent channels.

5.2 Test SET-UP (Block Diagram of Configuration)



5.3 Measurement Results

Modulation: GFSK, $\pi/4$ -DQPSK, 8DPSK

RBW: 100KHz VBW: 300KHz

Packet: DH5 Spectrum Detector: PK

Test By: Sance Test Date: Oct. 27, 2014

Temperature : 24 $^{\circ}$ Humidity : 55 $^{\circ}$

Test Result: PASS


Channel number	Channel	Channel Separation Read						
	frequency (MHz)	Value (KHz)	Separation Limit (KHz)					
	GFSK							
Lowest	2402	1005	>754.8					
Middle	2441	1000	>754.8					
Highest	2480	1000	>754.8					
	π/4-DQPSK							
Lowest	2402	1000	>923.1					
Middle	2441	1000	>923.1					
Highest	2480	1000	>918.3					
	8DPSK							
Lowest	2402	1000	>942.3					
Middle	2441	1000	>942.3					
Highest	2480	1000	>942.3					

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR




GFSK Lowest Channel



Date: 27.OCT.2014 09:12:04

GFSK Middle Channel




Date: 27.OCT.2014 09:14:12

FCC ID: 2ADJEB8197LPB8197LR



GFSK Highest Channel



Date: 27.OCT.2014 09:15:45

π/4-DQPSK Lowest Channel




Date: 27.OCT.2014 09:18:45

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR



π/4-DQPSK Middle Channel



Date: 27.OCT.2014 09:22:17

$\pi/4$ -DQPSK Highest Channel



Date: 27.OCT.2014 09:24:22

FCC ID: 2ADJEB8197LPB8197LR



8DPSK Lowest Channel



Date: 27.OCT.2014 09:26:47

8DPSK Middle Channel



Date: 27.OCT.2014 09:29:57

Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR



8DPSK Highest Channel



Date: 27.OCT.2014 09:32:41

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR



6. 20dB Bandwidth

6.1 Measurement Procedure

Maximum 20dB RF Bandwidth, FCC Rule 15.247(a)(1):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RBW was chosen so that the display was a result of the hopping channel modulation. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. Use the spectrum 20dB down delta function to measure the bandwidth.

6.2 Test SET-UP (Block Diagram of Configuration)



6.3 Measurement Results

Refer to attached data chart.

Modulation: GFSK, $\pi/4$ -DQPSK, 8DPSK

RBW: 30KHz VBW: 100KHz

Packet: DH5 Spectrum Detector: PK

Test By: Sance Test Date: Oct. 27 2014

Temperature : 24 $^{\circ}$ Humidity : 55 $^{\circ}$

Test Result: PASS


Channel frequency (MHz)	20dB Down BW(kHz)		
GF	SK		
2402	754.8		
2441	754.8		
2480	754.8		
π/4-D	QPSK		
2402	923.1		
2441	923.1		
2480	918.3		
8D	PSK		
2402	942.3		
2441	942.3		
2480	942.3		

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR




GFSK Lowest Channel



Date: 27.OCT.2014 09:01:40

GFSK Middle Channel




Date: 27.0CT.2014 09:02:26

FCC ID: 2ADJEB8197LPB8197LR




GFSK Highest Channel



Date: 27.OCT.2014 09:03:19

π/4-DQPSK Lowest Channel



FCC ID: 2ADJEB8197LPB8197LR




π/4-DQPSK Middle Channel



Date: 27.OCT.2014 09:05:21

$\pi/4\text{-DQPSK}$ Highest Channel



Date: 27.OCT.2014 09:06:04

FCC ID: 2ADJEB8197LPB8197LR




8DPSK Lowest Channel



Date: 27.OCT.2014 09:06:53

8DPSK Middle Channel




Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR



8DPSK Highest Channel



Date: 27.OCT.2014 09:08:36

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR



7. Hopping Channel Number

7.1 Measurement Procedure

Minimum Number of Hopping Frequencies, FCC Rule 15.247(a)(1)(iii):

Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum, and the spectrum analyzer set to MAX HOLD readings were taken for 3-5 minutes. The channel peaks so recorded were added together, and the total number compared to the minimum number of channels required in the regulation.

7.2 Test SET-UP (Block Diagram of Configuration)

FIIT	Spectrum Analyzer
	Spectrum Analyzer

7.3 Measurement Results

Modulation GFSK, $\pi/4$ -DQPSK, 8DPSK

RBW: 100KHz VBW: 300KHz

Packet: DH5 Spectrum Detector: PK

Test By: Sance Test Date: Oct. 27, 2014

Temperature : 24 $^{\circ}$ Humidity : 55 $^{\circ}$

Test Result: PASS


Hopping Channel Frequency Range	Number of Hopping Channels	Limit
2402-2480	79	≥15

The worst case: GFSK

Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR





Date: 27.OCT.2014 10:22:39

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR



8. Time of Occupancy (Dwell Time)

8.1 Measurement Procedure

Average Channel Occupancy Time, FCC Ref:15.247(a)(1)(iii):

Connect EUT antenna terminal to the spectrum analyzer with a low loss cable. The spectrum analyzer center frequency was set to one of the known hopping channels. The Sweep was set to 10 ms, the SPAN was set to Zero SPAN. The time duration of the transmissions so captured was measured with the Marker Delta function

8.2 Measurement Results

The maximum number of hopping channels in 31.6s (0.4s/Channel x 79 Channel)

Refer to attached data chart.

Modulation : GFSK, $\pi/4$ -DQPSK, 8DPSK

RBW: 1MHz VBW: 3MHz Spectrum Detector: PK Test By: Sance Test Date: Oct. 27, 2014 Temperature: $24^{\circ}C$ Test Result: PASS Humidity: 55° %


Packet	Frequency	Result	Limit
	(MHz)	(msec)	(msec)
GFSK			
DH1	2402	0.409 (ms)*(1600/(2*79))*31.6=130.8	400
DH3	2402	1.659 (ms)*(1600/(4*79))*31.6=265.4	400
DH5	2402	2.925 (ms)*(1600/(6*79))*31.6=312.0	400
π/4-DQPSK			
2-DH1	2402	0.409 (ms)*(1600/(2*79))*31.6=130.8	400
2-DH3	2402	1.659 (ms)*(1600/(4*79))*31.6=265.4	400
2-DH5	2402	2.921 (ms)*(1600/(6*79))*31.6=311.6	400
8DPSK			
3-DH1	2402	0.413 (ms)*(1600/(2*79))*31.6=132.1	400
3-DH3	2402	1.659 (ms)*(1600/(4*79))*31.6=265.4	400
3-DH5	2402	2.849 (ms)*(1600/(6*79))*31.6=303.9	400

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR








Date: 27.OCT.2014 09:37:58

GFSK DH3




Date: 27.0CT.2014 09:38:46

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR








Date: 27.OCT.2014 09:39:38

π/4-DQPSK 2-DH1




Date: 27.0CT.2014 09:40:28

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR




π/4-DQPSK 2-DH3



Date: 27.OCT.2014 09:41:51

π/4-DQPSK 2-DH5




Date: 27.OCT.2014 09:42:23

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR




8DPSK 3-DH1



Date: 27.OCT.2014 09:43:16

8DPSK 3-DH3




Date: 27.OCT.2014 09:44:47

Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1410485F FCC ID: 2ADJEB8197LPB8197LR



8DPSK 3-DH5



Date: 27.OCT.2014 09:45:20

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR



9. MAXIMUM PEAK OUTPUT POWER

9.1 Measurement Procedure

Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(1):

Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum. The analyzer was set for RBW > 20dB bandwidth and power was read directly in dBm. Cable loss was considered during this measurement.

9.2 Measurement Results

Refer to attached data chart.

Modulation : GFSK, $\pi/4$ -DQPSK, 8DPSK

RBW: 3MHz VBW: 3MHz

Spectrum Detector: PK Test Date: Oct. 27, 2014

Test By: Sance Temperature : 24 $^{\circ}$ C Test Result: PASS Humidity : 55 $^{\circ}$


Channel Frequency (MHz)	Cable Loss dB	Peak Power output(mW)	Peak Power output(dBm)	Peak Power Limit(dBm)	Pass/Fail		
GFSK							
2402.00	1.5	1.20	0.78	30	PASS		
2441.00	1.5	1.28	1.07	30	PASS		
2480.00	1.5	1.28	1.08	30	PASS		
π/4-DQPSK							
2402.00	2402.00 1.5 0.98 -0.09 30 PAS						
2441.00	1.5	1.07	0.29	30	PASS		
2480.00	1.5	1.07	0.29	30	PASS		
8DPSK							
2402.00	1.5	0.98	-0.09	30	PASS		
2441.00	1.5	1.08	0.33	30	PASS		
2480.00	1.5	1.07	0.29	30	PASS		

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR



GFSK Lowest Channel



Date: 27.OCT.2014 09:33:27

GFSK Middle Channel



Date: 27.OCT.2014 09:33:42

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR








Date: 27.OCT.2014 09:33:59

π/4-DQPSK Lowest Channel




Date: 27.OCT.2014 09:34:26

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR



π/4-DQPSK Middle Channel



Date: 27.OCT.2014 09:34:53

$\pi/4\text{-DQPSK}$ Highest Channel




Date: 27.0CT.2014 09:35:36

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR




8DPSK Lowest Channel



Date: 27.OCT.2014 09:36:01


8DPSK Middle Channel



Date: 27.0CT.2014 09:36:21

Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1410485F FCC ID: 2ADJEB8197LPB8197LR





Date: 27.OCT.2014 09:36:40

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR



10. Band Edge

10.1 Measurement Procedure

Out of Band Conducted Emissions, FCC Rule 15.247(d):

The transmitter output is connected to spectrum analyzer. The resolution bandwidth is set to 100KHz, and the video bandwidth set to 300KHz.

A Quasi-peak measurement was then made for that frequency point for below 1GHz test. PK and AV for above 1GHz emission test.

For 30MHz to 1GHz:

Sept the spectrum analyzer as: RBW=120kHz, VBW=300kHz, Detector=Quasi-Peak

For Above 1GHz:

Set the spectrum analyzer as: RBW=1MHz, VBW=3MHz, Detector=Peak. Set the spectrum analyzer as: RBW=1MHz, VBW=10Hz, Detector=Peak.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

Frequency Band (MHz)	Level	Resolution Bandwidth	Video Bandwidth	
30 to 1000	QP	120 kHz	300 kHz	
Above 1000	Peak	1 MHz	3 MHz	
Above 1000	Average	1 MHz	10 Hz	

10.2 Limit

15.247(d)In any 100KHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100KHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR



10.3 Measurement Results

Please see below test table and plots.

For Radiated Emission The worst case: GFSK

Freq. (MHz)	Ant. Pol.	Emission Level (dBuV)		Limit 3m (dBuV/m)		Margin (dB)	
		Peak	AV	Peak	AV	Peak	AV
2399.560	Н	48.36	37.11	74.00	54.00	-25.64	-16.89
2399.420	V	49.23	36.20	74.00	54.00	-24.77	-17.80
2494.520	Н	47.27	35.76	74.00	54.00	-26.73	-18.24
2484.720	V	47.28	36.88	74.00	54.00	-26.72	-17.12

Note: (1) Emission Level= Reading Level + Factor

(2) Factor= Antenna Gain + Cable Loss – Amplifier Gain


(3) Horn antenna used for the emission over 1000MHz.


FCC ID: 2ADJEB8197LPB8197LR




For RF Conducted

GFSK Lowest Channel








Date: 27.OCT.2014 09:48:10


FCC ID: 2ADJEB8197LPB8197LR



GFSK Highest Channel



Date: 27.0CT.2014 09:49:50




Date: 27.0CT.2014 09:50:43

Report No.: NTC1410485F


FCC ID: 2ADJEB8197LPB8197LR



π/4-DQPSK Lowest Channel



Date: 27.0CT.2014 09:51:44




Date: 27.OCT.2014 09:55:21

Report No.: NTC1410485F


FCC ID: 2ADJEB8197LPB8197LR



$\pi/4\text{-DQPSK}$ Highest Channel



Date: 27.OCT.2014 09:56:29




Date: 27.OCT.2014 09:57:17

Report No.: NTC1410485F


FCC ID: 2ADJEB8197LPB8197LR



8DPSK Lowest Channel



Date: 27.0CT.2014 09:59:03




Date: 27.OCT.2014 10:01:14

Report No.: NTC1410485F


FCC ID: 2ADJEB8197LPB8197LR



8DPSK Highest Channel



Date: 27.OCT.2014 10:02:37



Date: 27.OCT.2014 10:03:44

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR



11. Antenna Application

11.1 Antenna requirement

According to of FCC part 15C section 15.203 and 15.240:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Systems operating in the 2400-2483.5MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

11.2 Measurement Results

The antenna is integrated on the main PCB and no consideration of replacement, and the best case gain of the antenna is 0dBi. So, the antenna is consider meet the requirement.

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR



12. Conducted Spurious Emissions

12.1 Measurement Procedure

Out of Band Conducted Spurious Emissions, FCC Rule 15.247(d):

The transmitter output is connected to spectrum analyzer. All spurious emission and up to the tenth harmonic was measured and they were found to be at least 20dB below the highest level of the desired power in the passband.

12.2. Measurement Results


Please refer to following plots, the worst case (GFSK) was shown.

Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR




Lowest Channel



Date: 27.0CT.2014 10:05:44

Middle Channel




Date: 27.0CT.2014 10:07:19

Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1410485F

FCC ID: 2ADJEB8197LPB8197LR





Date: 27.OCT.2014 10:08:19

Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1410485F FCC ID: 2ADJEB8197LPB8197LR



13. Test Equipment List

Description	Manufacturer	Model Number	Serial Number	Characteristics	Calibration Date	Calibration Due Date
Test Receiver	Rohde & Schwarz	ESCI7	100837	9KHz~7GHz	Nov. 25, 2013	Nov. 24, 2014
Antenna	Schwarzbeck	VULB9162	9162-010	30MHz~7GHz	Nov. 28, 2013	Nov. 27, 2014
Positioning Controller	UC	UC 3000	N/A	0~360°, 1-4m	N/A	N/A
Color Monitor	SUNSPO	SP-140A	N/A	N/A	N/A	N/A
Single Phase Power Line Filter	SAEMC	PF201A-32	110210	32A	N/A	N/A
3 Phase Power Line Filter	SAEMC	PF401A-200	110318	200A	N/A	N/A
DC Power Filter	SAEMC	PF301A-200	110245	200A	N/A	N/A
Cable	Huber+Suhner	CBL2-NN-1M	22390001	9KHz~7GHz	Nov. 09, 2013	Nov. 08, 2014
Cable	Huber+Suhner	CIL02	N/A	9KHz~7GHz	Nov. 09, 2013	Nov. 08, 2014
Power Amplifier	HP	HP 8447D	1145A00203	100KHz~1.3GHz	Nov. 09, 2013	Nov. 08, 2014
Horn Antenna	Schwarzbeck	BBHA9170	9170-372	15GHz~26.5GHz	Oct.24, 2014	Oct.23, 2015
Horn Antenna	Com-Power	AH-118	071078	1GHz~18GHz	Nov. 07, 2013	Nov. 06, 2014
Loop antenna	Daze	ZA30900A	0708	9KHz~30MHz	Oct.11, 2014	Oct.10, 2015
Spectrum Analyzer	Rohde & Schwarz	FSU26	200409/026	20Hz~26.5GHz	Sep. 02, 2014	Sep. 01, 2015
Pre-Amplifier	Agilent	8449B	3008A02964	1GHz~26.5GHz	Nov. 05, 2013	Nov. 04, 2014
L.I.S.N.	Rohde & Schwarz	ENV 216	101317	9KHz~30MHz	Nov. 09, 2013	Nov. 08, 2014