TEST REPORT

DT&C Co., Ltd.		
42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel : 031-321-2664, Fax : 031-321-1664	Report No : DRTFCC1512-0262 Pages:(1) / (91) page	Dt&C

1. Customer

  • Name : INNODEVICE Co., Ltd.

  • Address : (USpace1, Sampyeong-dong) 660, Daewangpangyo-ro, Bundang-gu, Gyeonggi-do,

    Seongnam-si, South Korea, 463-400

2. Use of Report : FCC Original Grant

3. Product Name (FCC ID): Bluetooth wireless stereo Speaker (2ADLCBTSPKFLASK2)

4. Date of Test : 2015-11-17 ~ 2015-12-17

5. Test Method Used: FCC Part 15 Subpart C.247

6. Testing Environment : See appended test report

7. Test Result : ☒ Pass   ☐ Fail

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This Test Report cannot be reproduced, except in full.

Affirmation	Tested by		Technical Manager	
	Name : Chulmin KIM	(Signature)	Name : GeunKi Son	(Signature)

2015. 12. 18.

DT&C Co., Ltd.

Test Report Version

Test Report No.	Date	Description
DRTFCC1512-0262	Dec. 18, 2015	Initial issue

Table of Contents

1. General Information

1.1 Testing Laboratory

DT&C Co., Ltd.

Standard		Site number	Address
FCC	☒	**165783**	42, Yurim-ro 154 beon-gil, Cheoin -gu, Yongin-si, Gyeonggi -do, South Korea 449-935
	☐	**804488**	42, Yurim-ro 154 beon-gil, Cheoin -gu, Yongin-si, Gyeonggi -do, South Korea 449-935
	☐	**596748**	42, Yurim-ro 154 beon-gil, Cheoin -gu, Yongin-si, Gyeonggi -do, South Korea 449-935
	☐	**678747**	683-3, Yubang-dong, Cheoin-gu, Yongin-si, Kyeonggi-do, Korea, 449-080
IC	☐	**5740A-3**	42, Yurim-ro 154 beon-gil, Cheoin -gu, Yongin-si, Gyeonggi -do, South Korea 449-935
	☐	**5740A-2**	683-3, Yubang-dong, Cheoin-gu, Yongin-si, Kyeonggi-do, Korea, 449-080

www.dtnc.net

Telephone	:	+ 82-31-321-2664
FAX	:	+ 82-31-321-1664

1.2 Details of Applicant

Applicant	:	INNODEVICE Co., Ltd.
Address	:	(USpace1, Sampyeong-dong) 660, Daewangpangyo-ro, Bundang-gu, Gyeonggi-do, Seongnam-si, South Korea, 463-400
Contact person	:	JI HOON HWANG

1.3 Description of EUT

EUT	Bluetooth wireless stereo Speaker
Model Name	INNO-FLASK2
Add Model Name	INNO-FLASK2(CG), INNO-FLASK2(RG), INNO-FLASK2(CR), INNO-FLASK2(PT)
Serial Number	Identical prototype
Hardware version	V1.0
Software version	V1.0
Power Supply	DC 3.7 V
Battery type	Standard Battery: Lithium Ion Battery
Frequency Range	2402 MHz ~ 2480 MHz
Modulation Technique	GFSK, π/4-DQPSK, 8DPSK
Number of Channels	79
Antenna Type	Internal Antenna
Antenna Gain	PK : 3.73 dBi

1.4 Declaration by the applicant / manufacturer

- NA

1.5 Information about the FHSS characteristics

- This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following :

    A) The hopping sequence is pseudorandom

    B) All channels are used equally on average

    C) The receiver input bandwidth equals the transmit bandwidth

    D) The receiver hops in sequence with the transmit signal

- 15.247(g) : In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.

- 15.247(h) : In accordance with the Bluetooth Industry Standard, the system does not coordinate its channels selection / hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

- 15.247(h) : The EUT employs Adaptive Frequency Hopping (AFH) which identifies sources of interference namely devices operating in 802.11 WLAN and excludes them from the list of available channels. The process of re-mapping reduces the number of test channels from 79 channels to a minimum number of 20 channels.

1.6 Test conditions

Ambient Condition	
▪ Temperature	+23 ℃ ~ +24 ℃
▪ Relative Humidity	43 % ~ 45 %

1.7 Test Equipment List

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal.Date (yy/mm/dd)	S/N
MXA Signal Analyzer	Agilent Technologies	N9020A	15/09/09	16/09/09	MY46471248
Digital Multimeter	Agilent Technologies	34401A	15/01/06	16/01/06	US36099541
DC Power Supply	HP	66332A	15/01/22	16/01/22	US37471368
Vector Signal Generator	Rohde Schwarz	SMBV100A	15/01/06	16/01/06	255571
Signal Generator	Rohde Schwarz	SMF100A	15/06/29	16/06/29	102341
BlueTooth Tester	TESCOM	TC-3000B	15/01/06	16/01/06	3000B770243
Thermohygrometer	BODYCOM	BJ5478	15/05/08	16/05/08	120612-2
Low Noise Pre Amplifier	tsj	MLA-010K01-B01-27	15/04/09	16/04/09	1844538
Power Splitter	Anritsu	K241B	15/10/20	16/10/20	1701061
PreAmplifier	Agilent Technologies	8449B	15/02/26	16/02/26	3008A00370
Loop Antenna	Schwarzbeck	FMZB1513	14/04/29	16/04/29	1513-128
Horn Antenna(1~18GHz)	ETS-LINDGREN	3115	15/02/09	17/02/09	9202-3820
Horn Antenna	A.H.Systems Inc.	SAS-574	15/04/30	17/04/30	154
TRILOG Broadband Test-Antenna	Schwarzbeck	VULB 9160	14/04/30	16/04/30	3358
High-pass filter	Wainwright Instruments	WHKX3.0	15/01/06	16/01/06	12
EMI TEST RECEIVER	Rohde Schwarz	ESR7	15/10/19	16/10/19	101109
Power Meter & Wide Bandwidth Sensor	Anritsu	ML2496A/ MA2411B	15/06/25	16/06/25	1338004/ 1306053
EMI TEST RECEIVER	R&S	ESCI	15/02/25	16/02/25	100364
SINGLE-PHASE MASTER	NF	4420	15/09/09	16/09/09	3049354420023
ARTIFICIAL MAINS NETWORK	Narda S.T.S. / PMM	PMM L2-16B	15/06/26	16/06/26	000WX20305

1.8 Summary of Test Results

FCC Part RSS Std.	Parameter	Limit (Using in 2400~ 2483.5 MHz)	Test Condition	Status Note 1
15.247(a) RSS-247(5.1)	Carrier Frequency Separation	>= 25 kHz or >= Two thirds of the 20 dB BW, whichever is greater.	Conducted	C
	Number of Hopping Frequencies	>= 15 hops		C
	20 dB Bandwidth	None		C
	Dwell Time	=< 0.4 seconds		C
15.247(b) RSS-247(5.4)	Transmitter Output Power	**For FCC** =< 1 Watt , if CHs >= 75 Others =< 0.125 W **For IC** if CHs >= 75 =< 1 Watt For Conducted Power =< 4 Watt For e.i.r.p, Others =< 0.125 W For Conducted Power. =< 0.5 Watt For e.i.r.p		C
15.247(d) RSS-247(5.5)	Conducted Spurious Emissions	The radiated emission to any 100 kHz of out-band shall be at least 20 dB below the highest in-band spectral density.		C
RSS Gen(6.6)	Occupied Bandwidth (99 %)	RSS-Gen		NA
15.205 & 209 RSS-247(5.5) RSS-Gen (8.9 & 8.10)	Radiated Spurious Emissions	FCC 15.209 Limits RSS-Gen 8.9	Radiated	C Note2
15.207 RSS-Gen(8.8)	AC Conducted Emissions	FCC 15.207 Limits	AC Line Conducted	C
15.203 RSS-Gen(6.7)	Antenna Requirements	FCC 15.203	-	C

Note 1 : **C** = Comply   **NC** = Not Comply   **NT** = Not Tested   **NA** = Not Applicable

Note 2 : This test item was performed in each axis and the worst case data was reported.

Note 3 : The sample was tested according to the following specifications :

- ANSI C63.10-2013

1.9 Conclusion of worst-case and operation mode

The EUT has three type of modulation (GFSK, π/4DQPSK and 8DPSK).

Therefore all applicable requirements were tested with all the modulations.

The field strength of spurious emission was measured in three orthogonal EUT positions (X-axis, Y-axis and Z-axis).

Tested frequency information,

  - Hopping Function : Enable

	TX Frequency (MHz)	**RX Frequency (MHz)**
Hopping Band	2402 ~ 2480	2402 ~ 2480

  - Hopping Function : Disable

	TX Frequency (MHz)	**RX Frequency (MHz)**
Lowest Channel	2402	2402
Middle Channel	2441	2441
Highest Channel	2480	2480

2. Maximum Peak Output Power Measurement

2.1 Test Setup

Refer to the APPENDIX I.

2.2 Limit

▣ FCC Requirements

The maximum peak output power of the intentional radiator shall not exceed the following :

1. §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

2. §15.247(b)(1), For frequency hopping systems operating in the 2400 – 2483.5 MHz employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725 – 5805 MHz band : 1 Watt.

▣ IC Requirements

1. RSS-247(5.4), For FHSs operating in the band 2400 - 2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W and the e.i.r.p. shall not exceed 4 W if the hopset uses 75 or more hopping channels the maximum peak conducted output power shall not exceed 0.125 W and the e.i.r.p. shall not exceed 0.5 W if the hopset uses less than 75 hopping channels

2.3 Test Procedure

1. The RF output power was measured with a spectrum analyzer connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency, A spectrum analyzer was used to record the shape of the transmit signal.

2. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using ;

   Span = approximately 5 times of the 20 dB bandwidth, centered on a hopping channel

   RBW ≥ 20 dB BW

   VBW ≥ RBW

   Sweep = auto

   Detector function = peak

   Trace = max hold

2.4 Test Results

Modulation	Tested Channel	Frame Average Output Power		Peak Output Power	
		dBm	mW	dBm	mW
GFSK	Lowest	-0.48	0.895	1.11	1.291
	Middle	2.86	1.932	4.25	2.661
	Highest	**3.16**	**2.070**	**5.21**	**3.319**
π/4DQPSK	Lowest	-3.51	0.446	0.75	1.189
	Middle	0.11	1.026	4.54	2.844
	Highest	**0.27**	**1.064**	**4.63**	**2.904**
8DPSK	Lowest	-3.50	0.447	0.84	1.213
	Middle	0.13	1.030	4.41	2.760
	Highest	**0.28**	**1.067**	**4.52**	**2.831**

Note 1 : Average output power was using the average power meter for reference only.

Note 2 : See next pages for actual measured spectrum plots.

Peak Output Power   *Lowest Channel & Modulation : GFSK*

Peak Output Power   *Middle Channel & Modulation : GFSK*

Peak Output Power   *Highest Channel & Modulation : GFSK*

Peak Output Power   *Lowest Channel & Modulation : π/4DQPSK*

Peak Output Power   *Middle Channel & Modulation : π/4DQPSK*

Peak Output Power   *Highest Channel & Modulation : π/4DQPSK*

Peak Output Power   *Lowest Channel & Modulation : 8DPSK*

Peak Output Power   *Middle Channel & Modulation : 8DPSK*

Peak Output Power   *Highest Channel & Modulation : 8DPSK*

3. 20 dB BW

3.1 Test Setup

Refer to the APPENDIX I.

3.2 Limit

Limit : Not Applicable

3.3 Test Procedure

1. The 20 dB bandwidth were measured with a spectrum analyzer connected to RF antenna Connector
   (conducted measurement) while EUT was operating in transmit mode. The analyzer center frequency was
   set to the EUT carrier frequency, using the analyzer.
2. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using RBW $\geq$ 1 % of
   the 20 dB bandwidth, VBW $\geq$ RBW, Span = 3 MHz.

3.4 Test Results

Modulation	Tested Channel	20 dB BW (MHz)
GFSK	Lowest	0.920
	Middle	0.890
	Highest	0.890
π/4DQPSK	Lowest	1.280
	Middle	1.280
	Highest	1.270
8DPSK	Lowest	1.250
	Middle	1.250
	Highest	1.250

Note 1 : See next pages for actual measured spectrum plots.

20 dB Bandwidth   *Lowest Channel & Modulation : GFSK*

20 dB Bandwidth   *Middle Channel & Modulation : GFSK*

20 dB Bandwidth   *Highest Channel & Modulation : GFSK*

20 dB Bandwidth   *Lowest Channel & Modulation : π/4DQPSK*

## 20 dB Bandwidth   *Middle Channel & Modulation : π/4DQPSK*

20 dB Bandwidth   *Highest Channel & Modulation : π/4DQPSK*

20 dB Bandwidth   *Lowest Channel & Modulation : 8DPSK*

20 dB Bandwidth   *Middle Channel & Modulation : 8DPSK*

## 20 dB Bandwidth   *Highest Channel & Modulation : 8DPSK*

4. Carrier Frequency Separation

4.1 Test Setup

Refer to the APPENDIX I.

4.2 Limit

Limit : ≥ 25 kHz or ≥ Two-Thirds of the 20 dB BW whichever is greater.

4.3 Procedure

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.
After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.
　The spectrum analyzer is set to :
　　Span = wide enough to capture the peaks of two adjacent channels
　　RBW = Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to
　　　　　best identify the center of each individual channel.
　　VBW ≥ RBW　　　　　　　　　Sweep = auto
　　Detector function = peak　　　　Trace = max hold

4.4 Test Results

FH mode

Hopping Mode	Test Mode	Peak of center channel (MHz)	Peak of adjacent Channel (MHz)	Test Result (MHz)
Enable	**GFSK**	**2440.985**	**2441.985**	**1.000**
	π/4-DQPSK	**2439.971**	**2440.977**	**1.006**
	8DPSK	**2440.958**	**2441.961**	**1.003**

AFH mode

Hopping Mode	Test Mode	Peak of center channel (MHz)	Peak of adjacent Channel (MHz)	Test Result (MHz)
Enable	**GFSK**	**2409.977**	**2410.980**	**1.003**
	π/4-DQPSK	**2410.958**	**2411.958**	**1.000**
	8DPSK	**2410.964**	**2411.970**	**1.006**

Note 1 : See next pages for actual measured spectrum plots.

- **Minimum Standard :**

> Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.
> Alternatively, frequency hopping systems operating in the 2400 - 2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW

Carrier Frequency Separation (FH)   *Hopping mode : Enable & GFSK*

Carrier Frequency Separation (FH)   *Hopping mode : Enable & π/4-DQPSK*

Carrier Frequency Separation (FH)   *Hopping mode : Enable & 8DPSK*

Carrier Frequency Separation (AFH)   *Hopping mode : Enable & GFSK*

Carrier Frequency Separation (AFH)   *Hopping mode : Enable & π/4-DQPSK*

Carrier Frequency Separation (AFH)   *Hopping mode : Enable & 8DPSK*

5. Number of Hopping Frequencies

5.1 Test Setup

Refer to the APPENDIX I.

5.2 Limit

Limit : >= 15 hops

5.3 Procedure

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

To get higher resolution, two frequency ranges for FH mode within the 2400 ~ 2483.5 MHz were examined.

The spectrum analyzer is set to :

Span for FH mode = 50 MHz   Start Frequency = 2391.5 MHz,   Stop Frequency = 2441.5 MHz
                                                        Start Frequency = 2441.5 MHz,   Stop Frequency = 2491.5 MHz
Span for AFH mode = 30 MHz   Start Frequency = 2396.0 MHz,   Stop Frequency = 2426.0 MHz
RBW = To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing
          or the 20 dB bandwidth, whichever is smaller.
VBW ≥ RBW   Sweep = auto
Detector function = peak   Trace = max hold

5.4 Test Results

FH mode

Hopping mode	Test mode	Test Result (Total Hops)
Enable	GFSK	79
	π/4-DQPSK	79
	8DPSK	79

AFH mode

Hopping mode	Test mode	Test Result (Total Hops)
Enable	GFSK	20
	π/4-DQPSK	20
	8DPSK	20

Note 1 : See next pages for actual measured spectrum plots.

- Minimum Standard :

At least 15 hopes

**Number of Hopping Frequencies 1(FH)**   *Hopping mode : Enable & GFSK*

Number of Hopping Frequencies 2(FH)   *Hopping mode : Enable & GFSK*

Number of Hopping Frequencies 1(FH)   *Hopping mode : Enable & π/4-DQPSK*

Number of Hopping Frequencies 2(FH)   *Hopping mode : Enable & π/4-DQPSK*

Number of Hopping Frequencies 1(FH)   *Hopping mode : Enable & 8DPSK*

Number of Hopping Frequencies 2(FH)   *Hopping mode : Enable & 8DPSK*

Number of Hopping Frequencies 1(AFH)   *Hopping mode : Enable & GFSK*

Number of Hopping Frequencies 1(AFH)   *Hopping mode : Enable & π/4-DQPSK*

Number of Hopping Frequencies 1(AFH)   *Hopping mode : Enable & 8DPSK*

6. Time of Occupancy (Dwell Time)

6.1 Test Setup

Refer to the APPENDIX I.

6.2 Limit

The maximum permissible time of occupancy is 400 ms within a period of 400 ms multiplied by the number of hopping channels employed.

6.3 Test Procedure

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to :
Center frequency = 2441 MHz   Span = zero
RBW = 1 MHz (RBW shall be $\leq$ channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel)
VBW ≥ RBW   Detector function = peak
Trace = max hold

6.4 Test Results

FH mode

Hopping mode	Packet Type	Number of hopping Channels	Burst On Time (ms)	Period (ms)	Test Result (sec)
Enable	**DH 5**	79	2.880	3.750	0.307
	2 DH 5	79	2.880	3.750	0.307
	3 DH 5	79	2.880	3.750	0.307

AFH mode

Hopping mode	Packet Type	Number of hopping Channels	Burst On Time (ms)	Period (ms)	Test Result (sec)
Enable	**DH 5**	20	2.880	3.750	0.154
	2 DH 5	20	2.880	3.750	0.154
	3 DH 5	20	2.880	3.750	0.154

Note 1 : Dwell Time = 0.4 × Hopping channel × Burst ON time × ((Hopping rate ÷ Time slots) ÷ Hopping channel)

- Time slots for DH5 = 6 slots (TX = 5 slot / RX = 1 slot)

- Hopping Rate = 1600 for FH mode   &   800 for AFH mode

Note 2 : See next pages for actual measured spectrum plots.

Time of Occupancy (FH)   *Hopping mode : Enable & GFSK*

Time of Occupancy (FH)   *Hopping mode : Enable & π/4-DQPSK*

Time of Occupancy (FH)   *Hopping mode : Enable & 8DPSK*

Time of Occupancy (AFH)   *Hopping mode : Enable & GFSK*

Time of Occupancy (AFH)   *Hopping mode : Enable & π/4-DQPSK*

Time of Occupancy (AFH)   *Hopping mode : Enable & 8DPSK*

7. Transmitter Radiated Spurious Emissions and Conducted Spurious Emission

7.1 Test Setup

Refer to the APPENDIX I.

7.2 Limit

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval , as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in section §15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section §15.205(a), must also comply the radiated emission limits specified in section §15.209(a) (see section §15.205(c))

According to § 15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table

Frequency (MHz)	Limit (uV/m)	Measurement Distance (meter)
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1705	24000/F (kHz)	30
1705 ~ 30.0	30	30
30 ~ 88	100 **	3
88 ~ 216	150 **	3
216 ~ 960	200 **	3
Above 960	500	3

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 - 72 MHz, 76 - 88 MHz, 174 - 216 MHz or 470 - 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

According to § 15.205(a) and (b), only spurious emissions are permitted in any of the frequency bands listed below :

| MHz	MHz	MHz	MHz	GHz	GHz
0.009 ~ 0.110	8.41425 ~ 8.41475	108 ~ 121.94	1300 ~ 1427	4.5 ~ 5.15	14.47 ~ 14.5
0.495 ~ 0.505	12.29 ~ 12.293	123 ~ 138	1435 ~ 1626.5	5.35 ~ 5.46	15.35 ~ 16.2
2.1735 ~ 2.1905	12.51975 ~ 12.52025	149.9 ~ 150.05	1645.5 ~ 1646.5	7.25 ~ 7.75	17.7 ~ 21.4
4.125 ~ 4.128	12.57675 ~ 12.57725	156.52475 ~ 156.52525	1660 ~ 1710	8.025 ~ 8.5	22.01 ~ 23.12
4.17725 ~ 4.17775	13.36 ~ 13.41	156.7 ~ 156.9	1718.8 ~ 1722.2	9.0 ~ 9.2	23.6 ~ 24.0
4.20725 ~ 4.20775	16.42 ~ 16.423	162.0125 ~ 167.17	2200 ~ 2300	9.3 ~ 9.5	31.2 ~ 31.8
6.215 ~ 6.218	16.69475 ~ 16.69525	167.72 ~ 173.2	2310 ~ 2390	10.6 ~ 12.7	36.43 ~ 36.5
6.26775 ~ 6.26825	16.80425 ~ 16.80475	240 ~ 285	2483.5 ~ 2500	13.25 ~ 13.4	Above 38.6
6.31175 ~ 6.31225	25.5 ~ 25.67	322 ~ 335.4	2655 ~ 2900		
8.291 ~ 8.294	37.5 ~ 38.25	399.90 ~ 410	3260 ~ 3267		
8.362 ~ 8.366	73 ~ 74.6	608 ~ 614	3332 ~ 3339		
8.37625 ~ 8.38675	74.8 ~ 75.2	960 ~ 1240	3345.8 ~ 3358		
			3600 ~ 4400		

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

7.3. Test Procedures

7.3.1. Test Procedures for Radiated Spurious Emissions

1. The EUT is placed on a non-conductive table. For emission measurements at or below 1 GHz, the table height is 80 cm. For emission measurements above 1 GHz, the table height is 1.5 m.
   The table was rotated 360 degrees to determine the position of the highest radiation.

2. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 1 or 3 meter away from the interference-receiving antenna.

3. For measurements above 1GHz absorbers are placed on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1 GHz, the absorbers are removed.

4. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

5. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.

6. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

7. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.

NOTE 2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1 GHz.

NOTE 3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 1 kHz for Average detection (AV) at frequency above 1 GHz.

7.3.2. Test Procedures for Conducted Spurious Emissions

1. The transmitter output was connected to the spectrum analyzer.

2. The **reference level** of the fundamental frequency was measured with the spectrum analyzer using RBW = 100 kHz, VBW = 300 kHz.

3. The conducted spurious emission was tested each ranges were set as below.

    Frequency range : 9 kHz ~ 30 MHz
    RBW = 100 kHz, VBW = 300 kHz, SWEEP TIME = AUTO, DETECTOR = PEAK, TRACE = MAX HOLD, SWEEP POINT : 40001

    Frequency range : 30 MHz ~ 10 GHz, 10 GHz ~ 25 GHz
    RBW = 1 MHz, VBW = 3 MHz, SWEEP TIME = AUTO, DETECTOR = PEAK, TRACE = MAX HOLD, SWEEP POINT : 40001

    LIMIT LINE = 20 dB below of the reference level of above measurement procedure Step 2. (RBW = 100 kHz, VBW = 300 kHz)

    If the emission level with above setting was close to the limit (ie, less than 3 dB margin) then zoom scan is required using RBW = 100 kHz, VBW = 300 kHz, SPAN = 100 MHz and BINS = 2001 to get accurate emission level within 100 kHz BW.

    Also the path loss for conducted measurement setup was used as described on the Appendix I of this test report.

7.3.3. Test Plot

    Refer to the APPENDIX II

7.4. Test Results

7.4.1. Radiated Emissions

9 kHz ~ 25 GHz Data (Modulation : _GFSK_)

▪ Lowest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2349.88	H	Y	PK	47.68	-3.03	0.00	N/A	44.65	74.00	29.35
2349.88	H	Y	AV	37.15	-3.03	-24.79	N/A	9.33	54.00	44.67
4804.18	H	Y	PK	49.50	6.21	0.00	N/A	55.71	74.00	18.29
4804.00	H	Y	AV	43.77	6.21	-24.79	N/A	25.19	54.00	28.81
7206.56	H	Y	PK	48.57	11.13	0.00	N/A	59.70	74.00	14.30
7205.98	H	Y	AV	41.83	11.13	-24.79	N/A	28.17	54.00	25.83

▪ Middle Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4882.22	H	Y	PK	49.21	6.29	0.00	N/A	55.50	74.00	18.50
4881.92	H	Y	AV	44.14	6.29	-24.79	N/A	25.64	54.00	28.36
7322.43	H	Y	PK	51.95	11.62	0.00	N/A	63.57	74.00	10.43
7322.94	H	Y	AV	47.03	11.62	-24.79	N/A	33.86	54.00	20.14

▪ Highest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2484.10	H	Y	PK	48.46	-2.96	0.00	N/A	45.50	74.00	28.50
2484.07	H	Y	AV	36.83	-2.96	-24.79	N/A	9.08	54.00	44.92
4959.65	H	Y	PK	51.71	6.37	0.00	N/A	58.08	74.00	15.92
4959.96	H	Y	AV	47.25	6.37	-24.79	N/A	28.83	54.00	25.17
7439.78	H	Y	PK	49.97	11.54	0.00	N/A	61.51	74.00	12.49
7439.93	H	Y	AV	44.17	11.54	-24.79	N/A	30.92	54.00	23.08

▪ **Note.**

1. No other spurious and harmonic emissions were found greater than listed emissions on above table.

2. Information of Distance Factor

   For finding emissions, the test distance might be reduced from 3m to 1m.   In this case, the distance factor(-9.54dB) is applied to the result.- Calculation of distance factor = 20 log(applied distance / required distance) = **20 log(1 m / 3 m)** = **-9.54 dB**

   When distance factor is "N/A", the distance is 3 m and distance factor is not applied.

3. D.C.F Calculation. (D.C.F = Duty Cycle Correction Factor)

   - Time to cycle through all channels = Δt = T [ms] X 20 minimum hopping channels , where T = pulse width = **2.88 ms**

   - 100 ms / Δt [ms] = H -> Round up to next highest integer, to account for worst case, H' = **100 / (2.88 X 20) = 1.736 ≒ 2**

   - The Worst Case Dwell Time = T [ms] x H' = **2.88 ms X 2 = 5.76 ms**

   - D.C.F = 20 Log(The Worst Case Dwell Time / 100 ms) dB = **20 log(5.76 / 100)** = **-24.79 dB**

4. Sample Calculation.

   Margin = Limit – Result   /   Result = Reading + T.F + D.C.F   /   T.F = AF + CL – AG

   Where, T.F = Total Factor,   AF = Antenna Factor,   CL = Cable Loss,   AG = Amplifier Gain.

9 kHz ~ 25 GHz Data (Modulation : π/4DQPSK)

▪ Lowest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2351.47	H	Y	PK	45.80	-3.03	0.00	N/A	42.77	74.00	31.23
2349.94	H	Y	AV	35.65	-3.03	-24.79	N/A	7.83	54.00	46.17
4803.63	H	Y	PK	47.24	6.21	0.00	N/A	53.45	74.00	20.55
4803.89	H	Y	AV	37.08	6.21	-24.79	N/A	18.50	54.00	35.50
7206.28	H	Y	PK	46.52	11.13	0.00	N/A	57.65	74.00	16.35
7205.87	H	Y	AV	35.15	11.13	-24.79	N/A	21.49	54.00	32.51

▪ Middle Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4881.69	H	Y	PK	47.36	6.29	0.00	N/A	53.65	74.00	20.35
4881.92	H	Y	AV	38.06	6.29	-24.79	N/A	19.56	54.00	34.44
7323.02	H	Y	PK	49.68	11.62	0.00	N/A	61.30	74.00	12.70
7322.97	H	Y	AV	40.60	11.62	-24.79	N/A	27.43	54.00	26.57

▪ Highest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.56	H	Y	PK	47.32	-2.96	0.00	N/A	44.36	74.00	29.64
2483.59	H	Y	AV	36.70	-2.96	-24.79	N/A	8.95	54.00	45.05
4959.72	H	Y	PK	49.34	6.37	0.00	N/A	55.71	74.00	18.29
4959.91	H	Y	AV	40.52	6.37	-24.79	N/A	22.10	54.00	31.90
7439.72	H	Y	PK	47.90	11.54	0.00	N/A	59.44	74.00	14.56
7439.87	H	Y	AV	38.18	11.54	-24.79	N/A	24.93	54.00	29.07

▪ **Note.**

1. No other spurious and harmonic emissions were found greater than listed emissions on above table.

2. Information of Distance Factor

   For finding emissions, the test distance might be reduced from 3m to 1m.   In this case, the distance factor(-9.54dB) is applied to the result.

   - Calculation of distance factor = 20 log(applied distance / required distance) = **20 log(1 m / 3 m) = -9.54 dB**

   When distance factor is "N/A", the distance is 3 m and distance factor is not applied.

3. D.C.F Calculation. (D.C.F = Duty Cycle Correction Factor)

   - Time to cycle through all channels = Δt = T [ms] X 20 minimum hopping channels , where T = pulse width = **2.88 ms**

   - 100 ms / Δt [ms] = H -> Round up to next highest integer, to account for worst case, H' = **100 / (2.88 X 20) = 1.736 ≒ 2**

   - The Worst Case Dwell Time = T [ms] x H' = **2.88 ms X 2 = 5.76 ms**

   - D.C.F = 20 Log(The Worst Case Dwell Time / 100 ms) dB = **20 log(5.76 / 100) = -24.79 dB**

4. Sample Calculation.

   Margin = Limit – Result   /   Result = Reading + T.F + D.C.F   /   T.F = AF + CL – AG

   Where, T.F = Total Factor,   AF = Antenna Factor,   CL = Cable Loss,   AG = Amplifier Gain.

9 kHz ~ 25 GHz Data (Modulation : _8DPSK_)

▪ Lowest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2350.55	H	Y	PK	46.70	-3.03	0.00	N/A	43.67	74.00	30.33
2349.97	H	Y	AV	35.48	-3.03	-24.79	N/A	7.66	54.00	46.34
4804.17	H	Y	PK	47.24	6.21	0.00	N/A	53.45	74.00	20.55
4804.04	H	Y	AV	37.19	6.21	-24.79	N/A	18.61	54.00	35.39
7205.96	H	Y	PK	46.43	11.13	0.00	N/A	57.56	74.00	16.44
7205.90	H	Y	AV	35.07	11.13	-24.79	N/A	21.41	54.00	32.59

▪ Middle Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4882.08	H	Y	PK	47.97	6.29	0.00	N/A	54.26	74.00	19.74
4881.77	H	Y	AV	38.10	6.29	-24.79	N/A	19.60	54.00	34.40
7322.81	H	Y	PK	49.77	11.62	0.00	N/A	61.39	74.00	12.61
7322.91	H	Y	AV	40.10	11.62	-24.79	N/A	26.93	54.00	27.07

▪ Highest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.57	H	Y	PK	47.78	-2.96	0.00	N/A	44.82	74.00	29.18
2483.50	H	Y	AV	36.60	-2.96	-24.79	N/A	8.85	54.00	45.15
4959.57	H	Y	PK	49.39	6.37	0.00	N/A	55.76	74.00	18.24
4959.97	H	Y	AV	40.41	6.37	-24.79	N/A	21.99	54.00	32.01
7440.34	H	Y	PK	48.35	11.54	0.00	N/A	59.89	74.00	14.11
7440.00	H	Y	AV	37.61	11.54	-24.79	N/A	24.36	54.00	29.64

▪ **Note.**

 1. No other spurious and harmonic emissions were found greater than listed emissions on above table.

 2. Information of Distance Factor

   For finding emissions, the test distance might be reduced from 3m to 1m.   In this case, the distance factor(-9.54dB) is applied to the result.

    - Calculation of distance factor = 20 log(applied distance / required distance) = **20 log(1 m / 3 m)** = **-9.54 dB**

   When distance factor is "N/A", the distance is 3 m and distance factor is not applied.

 3. D.C.F Calculation. (D.C.F = Duty Cycle Correction Factor)

    - Time to cycle through all channels = Δt = T [ms] X 20 minimum hopping channels , where T = pulse width = **2.88 ms**

    - 100 ms / Δt [ms] = H -> Round up to next highest integer, to account for worst case, H' = **100 / (2.88 X 20) = 1.736 ≒ 2**

    - The Worst Case Dwell Time = T [ms] x H' = **2.88 ms X 2 = 5.76 ms**

    - D.C.F = 20 Log(The Worst Case Dwell Time / 100 ms) dB = **20 log(5.76 / 100)** = **-24.79 dB**

 4. Sample Calculation.

   Margin = Limit – Result   /   Result = Reading + T.F + D.C.F   /   T.F = AF + CL – AG

   Where, T.F = Total Factor,   AF = Antenna Factor,   CL = Cable Loss,   AG = Amplifier Gain.

9 kHz ~ 25 GHz Data (Modulation : _GFSK_-_Hopping mode_)

▪ Lowest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2378.68	H	Y	PK	46.85	-3.03	0.00	N/A	43.82	74.00	30.18
2376.12	H	Y	AV	41.01	-3.03	-24.79	N/A	13.19	54.00	40.81

▪ Middle Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-

▪ Highest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2484.14	H	Y	PK	49.75	-2.96	0.00	N/A	46.79	74.00	27.21
2484.00	H	Y	AV	44.01	-2.96	-24.79	N/A	16.26	54.00	37.74

▪ **Note.**

1. No other spurious and harmonic emissions were found greater than listed emissions on above table.

2. Information of Distance Factor

   For finding emissions, the test distance might be reduced from 3m to 1m.   In this case, the distance factor(-9.54dB) is applied to the result.

   - Calculation of distance factor = 20 log(applied distance / required distance) = **20 log(1 m / 3 m)** = **-9.54 dB**

   When distance factor is "N/A", the distance is 3 m and distance factor is not applied.

3. D.C.F Calculation. (D.C.F = Duty Cycle Correction Factor)

   - Time to cycle through all channels = Δt = T [ms] X 20 minimum hopping channels , where T = pulse width = **2.88 ms**

   - 100 ms / Δt [ms] = H -> Round up to next highest integer, to account for worst case, H' = **100 / (2.88 X 20) = 1.736 ≒ 2**

   - The Worst Case Dwell Time = T [ms] x H' = **2.88 ms X 2** = **5.76 ms**

   - D.C.F = 20 Log(The Worst Case Dwell Time / 100 ms) dB = **20 log(5.76 / 100)** = **-24.79 dB**

4. Sample Calculation.

   Margin = Limit – Result   /   Result = Reading + T.F + D.C.F   /   T.F = AF + CL – AG

   Where, T.F = Total Factor,   AF = Antenna Factor,   CL = Cable Loss,   AG = Amplifier Gain.

9 kHz ~ 25 GHz Data (Modulation : π/4DQPSK-*Hopping mode*)

▪ Lowest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2371.88	H	Y	PK	46.25	-3.03	0.00	N/A	43.22	74.00	30.78
2375.04	H	Y	AV	38.07	-3.03	-24.79	N/A	10.25	54.00	43.75

▪ Middle Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-

▪ Highest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.77	H	Y	PK	48.25	-2.96	0.00	N/A	45.29	74.00	28.71
2483.99	H	Y	AV	40.18	-2.96	-24.79	N/A	12.43	54.00	41.57

▪ **Note.**

1. No other spurious and harmonic emissions were found greater than listed emissions on above table.

2. Information of Distance Factor

   For finding emissions, the test distance might be reduced from 3m to 1m.   In this case, the distance factor(-9.54dB) is applied to the result.

   - Calculation of distance factor = 20 log(applied distance / required distance) = **20 log(1 m / 3 m)** = **-9.54 dB**

   When distance factor is "N/A", the distance is 3 m and distance factor is not applied.

3. D.C.F Calculation. (D.C.F = Duty Cycle Correction Factor)

   - Time to cycle through all channels = Δt = T [ms] X 20 minimum hopping channels , where T = pulse width = **2.88 ms**

   - 100 ms / Δt [ms] = H -> Round up to next highest integer, to account for worst case, H' = **100 / (2.88 X 20) = 1.736 ≒ 2**

   - The Worst Case Dwell Time = T [ms] x H' = **2.88 ms X 2 = 5.76 ms**

   - D.C.F = 20 Log(The Worst Case Dwell Time / 100 ms) dB = **20 log(5.76 / 100)** = **-24.79 dB**

4. Sample Calculation.

   Margin = Limit – Result   /   Result = Reading + T.F + D.C.F   /   T.F = AF + CL – AG

   Where, T.F = Total Factor,   AF = Antenna Factor,   CL = Cable Loss,   AG = Amplifier Gain.