

# FCC Part 15C

## Measurement and Test Report

### For

### Xwireless LLC

11565 Old Georgetown Road, Rockville, MD, USA

**FCC ID: 2ADLJBEAT3**

**FCC Rule(s):** FCC Part 15C

**Product Description:** mobile phone

**Tested Model:** Beat 3.0

**Report No.:** STR17018116I-2

**Tested Date:** 2017-01-12 to 2017-02-20

**Issued Date:** 2017-02-21

**Tested By:** Lucy Wei / Engineer

**Reviewed By:** Silin Chen / EMC Manager

**Approved & Authorized By:** Jandy So / PSQ Manager

**Prepared By:**

**Shenzhen SEM.Test Technology Co., Ltd.**

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,  
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

*Lucy Wei*

*Silin Chen*

*Jandy So*

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

**TABLE OF CONTENTS**

<b>1. GENERAL INFORMATION.....</b>	<b>3</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY.....	4
1.4 TEST FACILITY.....	4
1.5 EUT SETUP AND TEST MODE.....	5
1.6 MEASUREMENT UNCERTAINTY.....	5
1.7 TEST EQUIPMENT LIST AND DETAILS.....	6
<b>2. SUMMARY OF TEST RESULTS.....</b>	<b>7</b>
<b>3. RF EXPOSURE.....</b>	<b>8</b>
3.1 STANDARD APPLICABLE.....	8
3.2 TEST RESULT.....	8
<b>4. ANTENNA REQUIREMENT.....</b>	<b>9</b>
4.1 STANDARD APPLICABLE.....	9
4.2 EVALUATION INFORMATION.....	9
<b>5. POWER SPECTRAL DENSITY.....</b>	<b>10</b>
5.1 STANDARD APPLICABLE.....	10
5.2 TEST PROCEDURE.....	10
5.3 ENVIRONMENTAL CONDITIONS.....	10
5.4 SUMMARY OF TEST RESULTS/PLOTS.....	11
<b>6. 6DB BANDWIDTH.....</b>	<b>18</b>
6.1 STANDARD APPLICABLE.....	18
6.2 TEST PROCEDURE.....	18
6.3 ENVIRONMENTAL CONDITIONS.....	18
6.4 SUMMARY OF TEST RESULTS/PLOTS.....	18
<b>7. RF OUTPUT POWER.....</b>	<b>25</b>
7.1 STANDARD APPLICABLE.....	25
7.2 TEST PROCEDURE.....	25
7.3 ENVIRONMENTAL CONDITIONS.....	25
7.4 SUMMARY OF TEST RESULTS/PLOTS.....	26
<b>8. FIELD STRENGTH OF SPURIOUS EMISSIONS.....</b>	<b>33</b>
8.1 STANDARD APPLICABLE.....	33
8.2 TEST PROCEDURE.....	33
8.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	34
8.4 ENVIRONMENTAL CONDITIONS.....	34
8.5 SUMMARY OF TEST RESULTS/PLOTS.....	35
<b>9. OUT OF BAND EMISSIONS.....</b>	<b>42</b>
9.1 STANDARD APPLICABLE.....	42
9.2 TEST PROCEDURE.....	42
9.3 ENVIRONMENTAL CONDITIONS.....	43
9.4 SUMMARY OF TEST RESULTS/PLOTS.....	43
<b>10. CONDUCTED EMISSIONS.....</b>	<b>55</b>
10.1 TEST PROCEDURE.....	55
10.2 BASIC TEST SETUP BLOCK DIAGRAM.....	55
10.3 ENVIRONMENTAL CONDITIONS.....	55
10.4 TEST RECEIVER SETUP.....	56
10.5 SUMMARY OF TEST RESULTS/PLOTS.....	56
10.6 CONDUCTED EMISSIONS TEST DATA.....	56

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: Xwireless LLC  
Address of applicant: 11565 Old Georgetown Road, Rockville, MD, USA

Manufacturer: Xwireless LLC  
Address of manufacturer: 11565 Old Georgetown Road, Rockville, MD, USA

General Description of EUT	
Product Name:	mobile phone
Brand Name:	/
Model No.:	Beat 3.0
Adding Model(s):	/
Power Adapter:	Beat 3.0 Input: AC100-240V, 0.2A, 50/60Hz; Output: DC5V, 1000mA
Rated Voltage:	DC 3.7V by battery
Battery Capacity:	1300mAh
Hardware version:	S139_MB_V1.11
Software version:	/
<p><i>The EUT Main board support GSM850PCS1900, WCDMA Band 2/5 function. It is intended for speech, Multimedia Message Service (MMS) transmission. It is equipped with GPRS class 12 for GSM850/900/DCS1800/PCS1900, GPS, FM, Bluetooth and Wi-Fi functions. For more information see the following datasheet</i></p>	
<p><i>Note: The test data is gathered from a production sample provided by the manufacturer.</i></p>	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n(HT20) 2422-2452MHz for 802.11n(HT40)
RF Output Power:	16.17dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 150Mbps
Quantity of Channels:	11 for 802.11b/g/n(HT20) 9 for 802.11b/g/n(HT40)
Channel Separation:	5MHz
Type of Antenna:	Integral
Antenna Gain:	1.38dBi

## 1.2 Test Standards

The following report is prepared on behalf of the Xwireless LLC in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices, and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. The measurement guide KDB 558074 D01 v03r05 for digital transmission systems shall be performed also.

## 1.4 Test Facility

### **FCC – Registration No.: 934118**

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

### **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. Has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

### **CNAS Registration No.: L4062**

Shenzhen SEM.Test Technology Co., Ltd. Is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2<sup>nd</sup> Road, Bao'an District, Shenzhen, P.R.C (518101).

## 1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	2412MHz, 2437MHz, 2462MHz
TM2	802.11g	2412MHz, 2437MHz, 2462MHz
TM3	802.11n-HT20	2412MHz, 2437MHz, 2462MHz
TM4	802.11n-HT40	2422MHz, 2437MHz, 2452MHz
Note: All test modes (different data rate and different modulation) are performed, but only the worst case is recorded in this report.		

Accessories Equipment List and Details			
Description	Manufacturer	Model No.	Serial Number
Notebook	Lenovo	E10	LR-63C8R
Accessories Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With Core/Without Core
/	/	/	/
EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With Core/Without Core
USB Cable	1.0	shielded	Without Ferrite
Earphone	1.2	Unshielded	Without Ferrite

## 1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	$\pm 2.88\text{dB}$
Transmitter Spurious Emissions	Radiated	$\pm 5.1\text{dB}$

## 1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2016-06-04	2017-06-03
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2016-06-04	2017-06-03
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2016-06-04	2017-06-03
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2016-06-04	2017-06-03
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2016-06-04	2017-06-03
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2016-06-04	2017-06-03
SEMT-1042	Horn Antenna	ETS	3117	00086197	2016-06-04	2017-06-03
SEMT-1121	Horn Antenna	ETS	3116B	00088203	2016-06-04	2017-06-03
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2016-06-04	2017-06-03
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2016-06-04	2017-06-03
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2016-06-04	2017-06-03
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2016-06-04	2017-06-03

## 2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 2.1093	RF Exposure	Compliant
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.247(e)	Power Spectral Density	Compliant
§ 15.247(a)(2)	6 dB Bandwidth	Compliant
§ 15.247(b)(3)	RF Output Power	Compliant
§ 15.209(a)	Radiated Emission	Compliant
§ 15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: not applicable

### **3. RF Exposure**

---

#### **3.1 Standard Applicable**

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

#### **3.2 Test Result**

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.



## **4. Antenna Requirement**

---

### **4.1 Standard Applicable**

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### **4.2 Evaluation Information**

This product has an integral antenna, fulfill the requirement of this section.

## 5. Power Spectral Density

### 5.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 5.2 Test Procedure

According to the KDB 558074 D01 v03r05, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set VBW  $\geq 3 \times \text{RBW}$ .
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span/RBW}$ .
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

### 5.3 Environmental Conditions


Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

#### 5.4 Summary of Test Results/Plots


Test Mode	Test Channel MHz	Power Spectral Density dBm/100kHz	Limit dBm/3kHz
802.11b	2412	-5.069	8
	2437	-4.511	8
	2462	-3.598	8
802.11g	2412	-8.392	8
	2437	-7.668	8
	2462	-6.853	8
802.11n HT20	2412	-9.887	8
	2437	-8.694	8
	2462	-9.344	8
802.11n HT40	2422	-12.919	8
	2437	-13.202	8
	2452	-13.029	8

Please refer to the following test plots:


## 802.11b-Low Channel




## 802.11b-Middle Channel




## 802.11b-High Channel




## 802.11g-Low Channel




## 802.11g-Middle Channel




## 802.11g-High Channel




## 802.11n-HT20-Low Channel




## 802.11n-HT20-Middle Channel



## 802.11n-HT20-High Channel




## 802.11n-HT40-Low Channel






## 802.11n-HT40-Middle Channel



## 802.11n-HT40-High Channel



## 6. 6dB Bandwidth

### 6.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 6.2 Test Procedure

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 6.3 Environmental Conditions


Temperature:	25° C
Relative Humidity:	53%
ATM Pressure:	1018 mbar

### 6.4 Summary of Test Results/Plots


Test Mode	Test Channel MHz	6 dB Bandwidth MHz	99% Bandwidth MHz	Limit kHz
802.11b	2412	8.918	12.653	$\geq 500$
	2437	8.904	12.710	$\geq 500$
	2462	9.485	12.659	$\geq 500$
802.11g	2412	16.48	16.422	$\geq 500$
	2437	16.47	16.408	$\geq 500$
	2462	16.49	16.411	$\geq 500$
802.11n-HT20	2412	17.62	17.575	$\geq 500$
	2437	17.33	17.564	$\geq 500$
	2462	17.62	17.576	$\geq 500$
802.11n-HT40	2422	36.14	35.897	$\geq 500$
	2437	36.12	35.850	$\geq 500$
	2452	36.11	35.835	$\geq 500$

Please refer to the following test plots:


## 802.11b-Low Channel




## 802.11b-Middle Channel




### 802.11b-High Channel




### 802.11g-Low Channel




## 802.11g-Middle Channel




## 802.11g-High Channel




## 802.11n-HT20-Low Channel




## 802.11n-HT20-Middle Channel




## 802.11n-HT20-High Channel




## 802.11n-HT40-Low Channel



## 802.11n-HT40-Middle Channel



## 802.11n-HT40-High Channel





## 7. RF Output Power

### 7.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

### 7.2 Test Procedure

According to the KDB-558074 D01 v03r05, 9.2.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW  $\geq 3 \times$  RBW.
- d) Number of points in sweep  $\geq 2 \times \text{span} / \text{RBW}$ . (This gives bin-to-bin spacing  $\leq \text{RBW}/2$ , so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle  $< 98\%$ , use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle  $\geq 98\%$ , and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run”.
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

### 7.3 Environmental Conditions


Temperature:	26° C
Relative Humidity:	57%
ATM Pressure:	1011 mbar

#### 7.4 Summary of Test Results/Plots


Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
802.11b_11Mbps	2412	14.89	30.83	1000
	2437	15.21	33.19	1000
	2462	16.17	41.40	1000
802.11g_54Mbps	2412	12.54	17.95	1000
	2437	12.27	16.87	1000
	2462	13.49	22.34	1000
802.11n HT20_MCS7	2412	11.27	13.40	1000
	2437	12.36	17.22	1000
	2462	13.10	20.42	1000
802.11n HT40_MCS7	2422	11.36	13.68	1000
	2437	11.58	14.39	1000
	2452	11.67	14.69	1000

Please refer to the following test plots:

## 802.11b-11Mbps-Low Channel




## 802.11b -11Mbps-Middle Channel




## 802.11b -11Mbps-High Channel




## 802.11g-54Mbps-Low Channel




## 802.11g-54Mbps-Middle Channel




## 802.11g-54Mbps-High Channel




## 802.11n-HT20-MCS7-Low Channel




## 802.11n-HT20-MCS7-Middle Channel




## 802.11n-HT20-MCS7-High Channel




## 802.11n-HT40-MCS7-Low Channel



## 802.11n-HT40-MCS7-Middle Channel



## 802.11n-HT40-MCS7-High Channel





## 8. Field Strength of Spurious Emissions

### 8.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

### 8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

### 8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB $\mu$ V means the emission is 6dB $\mu$ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

### 8.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

## 8.5 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst cases:

*Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.*

### Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: *mobile phone*

Tested Model: *Beat 3.0*

Operating Condition: *802.11b Transmitting Low Channel-2412MHz (Worst case)*


Comment: *DC 3.7V by battery*

Test Specification: *Horizontal*



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	39.2991	21.69	-7.85	13.84	40.00	-26.16	197	100	peak
2	69.3568	22.52	-12.62	9.90	40.00	-30.10	197	100	peak
3	96.0986	24.24	-11.70	12.54	43.50	-30.96	84	100	peak
4	261.9753	22.42	-6.87	15.55	46.00	-30.45	145	100	peak
5	366.8231	24.87	-2.86	22.01	46.00	-23.99	272	100	peak
6	618.5369	21.37	1.14	22.51	46.00	-23.49	215	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	33.2112	25.37	-9.50	15.87	40.00	-24.13	78	100	peak
2	36.0007	27.53	-8.76	18.77	40.00	-21.23	137	100	peak
3	47.9940	23.87	-8.19	15.68	40.00	-24.32	137	100	peak
4	207.1226	35.60	-8.72	26.88	43.50	-16.62	122	100	peak
5	336.0352	28.66	-4.91	23.75	46.00	-22.25	184	100	peak
6	463.9696	25.70	-2.36	23.34	46.00	-22.66	265	100	peak

Operating Condition: 802.11b Transmitting Middle Channel-2437MHz (Worst case)


Comment: DC 3.7V by battery

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	33.3279	26.21	-9.46	16.75	40.00	-23.25	289	100	peak
2	47.4918	25.91	-8.16	17.75	40.00	-22.25	244	100	peak
3	202.1005	24.98	-8.66	16.32	43.50	-27.18	95	100	peak
4	318.8170	27.40	-4.68	22.72	46.00	-23.28	98	100	peak
5	482.2156	26.48	-1.17	25.31	46.00	-20.69	211	100	peak
6	857.0247	26.04	2.78	28.82	46.00	-17.18	334	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	33.3279	29.45	-9.46	19.99	40.00	-20.01	329	100	peak
2	47.3255	28.91	-8.15	20.76	40.00	-19.24	126	100	peak
3	202.1005	23.05	-8.66	14.39	43.50	-29.11	89	100	peak
4	292.0583	25.85	-5.83	20.02	46.00	-25.98	317	100	peak
5	470.5232	25.57	-1.82	23.75	46.00	-22.25	92	100	peak
6	912.8620	24.01	3.49	27.50	46.00	-18.50	346	100	peak

Operating Condition: 802.11b Transmitting High Channel-2462MHz (Worst case)


Comment: DC 3.7V by battery

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	41.8596	27.63	-7.79	19.84	40.00	-20.16	269	100	peak
2	54.6429	29.33	-8.91	20.42	40.00	-19.58	100	100	peak
3	86.5029	38.03	-12.62	25.41	40.00	-14.59	228	100	peak
4	191.7450	36.04	-9.77	26.27	43.50	-17.23	115	100	peak
5	636.1340	27.82	0.82	28.64	46.00	-17.36	96	100	peak
6	955.4381	24.09	3.73	27.82	46.00	-18.18	238	100	peak

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	33.3279	26.05	-9.46	16.59	40.00	-23.41	314	100	peak
2	52.7600	23.50	-8.67	14.83	40.00	-25.17	98	100	peak
3	86.5029	27.49	-12.62	14.87	40.00	-25.13	215	100	peak
4	200.6881	29.57	-8.66	20.91	43.50	-22.59	102	100	peak
5	372.0045	21.81	-2.56	19.25	46.00	-26.75	156	100	peak
6	649.6597	23.35	0.52	23.87	46.00	-22.13	248	100	peak



### Spurious Emissions Above 1GHz

Test Mode: 802.11b (Worst case)

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz							
4824.000	55.76	-3.87	51.89	74.00	-22.11	H	PK
4824.000	40.60	-3.87	36.73	54.00	-17.27	H	AV
7236.000	48.07	1.14	49.21	74.00	-24.79	H	PK
7236.000	36.61	1.19	37.80	54.00	-16.20	H	AV
4824.000	59.07	-3.86	55.21	74.00	-18.79	V	PK
4824.000	41.77	-3.86	37.91	54.00	-16.09	V	AV
7236.000	50.88	1.1	51.98	74.00	-22.02	V	PK
7236.000	39.27	1.1	40.37	54.00	-13.63	V	AV
Middle Channel-2437MHz							
4874.000	56.36	-3.74	52.62	74.00	-21.38	H	PK
4874.000	41.61	-3.74	37.87	54.00	-16.13	H	AV
7311.000	49.39	1.47	50.86	74.00	-23.14	H	PK
7311.000	34.72	1.47	36.19	54.00	-17.81	H	AV
4874.000	55.59	-3.74	51.85	74.00	-22.15	V	PK
4874.000	42.51	-3.74	38.77	54.00	-15.23	V	AV
7311.000	49.60	1.47	51.07	74.00	-22.93	V	PK
7311.000	35.70	1.47	37.17	54.00	-16.83	V	AV
High Channel-2462MHz							
4924.000	57.44	-3.59	53.85	74.00	-20.15	H	PK
4924.000	43.38	-3.59	39.79	54.00	-14.21	H	AV
7386.000	48.00	1.79	49.79	74.00	-24.21	H	PK
7386.000	36.45	1.79	38.24	54.00	-15.76	H	AV
4924.000	56.56	-3.59	52.97	74.00	-21.03	V	PK
4924.000	43.66	-3.59	40.07	54.00	-13.93	V	AV
7386.000	49.61	1.79	51.40	74.00	-22.60	V	PK
7386.000	36.80	1.79	38.59	54.00	-15.41	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

---

## 9. Out of Band Emissions

---

### 9.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

### 9.2 Test Procedure

According to the KDB 558074D01 v03r05, the band-edge radiated test method as follows:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

According to the KDB 558074 D01 v03r05, the conducted spurious emissions test method as follows:

1. Set start frequency to DTS channel edge frequency.
2. Set stop frequency so as to encompass the spectrum to be examined.
3. Set RBW = 100 kHz.
4. Set VBW  $\geq$  300 kHz.
5. Detector = peak.
6. Trace Mode = max hold.
7. Sweep = auto couple.
8. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
9. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.


### 9.3 Environmental Conditions

Temperature:	23°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

### 9.4 Summary of Test Results/Plots

802.11b-Lowest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	34.07	-3.35	30.72	54.00	-23.28	Average Detector
	2310.000	45.76	-3.35	42.41	74.00	-31.59	Peak Detector
2	2390.000	42.07	-4.29	37.78	54.00	-16.22	Average Detector
	2390.000	53.17	-4.29	48.88	74.00	-25.12	Peak Detector
3	2400.000	59.05	-4.40	54.65	Delta =41.54dBc		Average Detector
4	2412.710	100.63	-4.44	96.19			Average Detector

## 802.11b-Highest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2462.206	100.85	-4.38	96.47	/	/	Average Detector
	2463.202	108.88	-4.38	104.50	/	/	Peak Detector
2	2483.500	38.37	-4.36	34.01	54.00	-19.99	Average Detector
	2483.500	50.25	-4.36	45.89	74.00	-28.11	Peak Detector
3	2500.000	36.64	-4.34	32.30	54.00	-21.70	Average Detector
	2500.000	48.64	-4.34	44.30	74.00	-29.70	Peak Detector

## 802.11g-Lowest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	34.30	-3.35	30.95	54.00	-23.05	Average Detector
	2310.000	46.26	-3.35	42.91	74.00	-31.09	Peak Detector
2	2390.000	48.63	-4.29	44.34	54.00	-9.66	Average Detector
	2390.000	66.44	-4.29	62.15	74.00	-11.85	Peak Detector
3	2400.000	63.10	-4.40	58.70	Delta =34.25dBc		Average Detector
4	2412.832	97.39	-4.44	92.95			Average Detector

## 802.11g-Highest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2462.555	96.41	-4.38	92.03	/	/	Average Detector
	2463.500	105.65	-4.38	101.27	/	/	Peak Detector
2	2483.500	51.07	-4.36	46.71	54.00	-7.29	Average Detector
	2483.500	68.49	-4.36	64.13	74.00	-9.87	Peak Detector
3	2500.000	42.79	-4.34	38.45	54.00	-15.55	Average Detector
	2500.000	57.66	-4.34	53.32	74.00	-20.68	Peak Detector

## 802.11n-HT20-Lowest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	34.11	-3.35	30.76	54.00	-23.24	Average Detector
	2310.000	45.68	-3.35	42.33	74.00	-31.67	Peak Detector
2	2390.000	46.33	-4.29	42.04	54.00	-11.96	Average Detector
	2390.000	61.34	-4.29	57.05	74.00	-16.95	Peak Detector
3	2400.000	64.82	-4.40	60.42	Delta =31.02dBc		Average Detector
4	2412.832	95.88	-4.44	91.44			Average Detector

## 802.11n-HT20-Highest Bandedge

Vertical (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2463.102	95.20	-4.38	90.82	/	/	Average Detector
	2461.212	105.33	-4.38	100.95	/	/	Peak Detector
2	2483.500	49.64	-4.36	45.28	54.00	-8.72	Average Detector
	2483.500	68.46	-4.36	64.10	74.00	-9.90	Peak Detector
3	2500.000	42.48	-4.34	38.14	54.00	-15.86	Average Detector
	2500.000	57.07	-4.34	52.73	74.00	-21.27	Peak Detector



## 802.11n-HT40-Lowest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	34.02	-3.35	30.67	54.00	-23.33	Average Detector
	2310.000	46.58	-3.35	43.23	74.00	-30.77	Peak Detector
2	2390.000	45.61	-4.29	41.32	54.00	-12.68	Average Detector
	2390.000	60.10	-4.29	55.81	74.00	-18.19	Peak Detector
3	2400.000	61.53	-4.40	57.13	Delta =30.27dBc		Average Detector
4	2417.778	91.83	-4.43	87.40			Average Detector

## 802.11n-HT40-Highest Bandedge

Vertical (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2458.041	92.58	-4.39	88.19	/	/	Average Detector
	2454.832	101.28	-4.39	96.89	/	/	Peak Detector
2	2483.500	48.57	-4.36	44.21	54.00	-9.79	Average Detector
	2483.500	66.42	-4.36	62.06	74.00	-11.94	Peak Detector
3	2500.000	46.84	-4.34	42.50	54.00	-11.50	Average Detector
	2500.000	63.64	-4.34	59.30	74.00	-14.70	Peak Detector


Spurious (Conducted)

802.11b-Lowest

Lowest



Highest




Spurious (Conducted)

802.11g-Lowest


Lowest



Highest




Spurious (Conducted)  
802.11n-HT20-Lowest  
Lowest




Highest



Spurious (Conducted)  
802.11n-HT40-Lowest  
Lowest



Highest




## 10. Conducted Emissions

### 10.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

### 10.2 Basic Test Setup Block Diagram



### 10.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

## 10.4 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency .....	150 kHz
Stop Frequency.....	30 MHz
Sweep Speed .....	Auto
IF Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth .....	9 kHz
Quasi-Peak Adapter Mode .....	Normal

## 10.5 Summary of Test Results/Plots

According to the data in section 10.6, the EUT complied with the FCC Part 15.207 Conducted margin for this device, with the *worst* margin reading of:

**-5.05 dB at 0.5060 MHz in the Neutral mode, QP detector, 0.15-30MHz**


## 10.6 Conducted Emissions Test Data



### Plot of Conducted Emissions Test Data


EUT: *mobile phone*  
 Tested Model: *Beat 3.0*  
 Operating Condition: *Transmitting(Wi-Fi)*  
 Comment: *AC 120V/60Hz; Adapter DC 5V*

Test Specification: *Neutral*



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.5060	41.15	9.80	50.95	56.00	-5.05	QP
2	0.5060	27.57	9.80	37.37	46.00	-8.63	AVG
3	0.9260	23.28	9.77	33.05	46.00	-12.95	AVG
4	1.0460	36.77	9.76	46.53	56.00	-9.47	QP
5	2.7580	19.26	9.72	28.98	46.00	-17.02	AVG
6	3.2420	32.90	9.70	42.60	56.00	-13.40	QP

Test Specification: Line



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.4980	25.78	9.80	35.58	46.03	-10.45	AVG
2*	0.5020	39.32	9.80	49.12	56.00	-6.88	QP
3	0.8900	21.47	9.77	31.24	46.00	-14.76	AVG
4	0.9620	35.78	9.76	45.54	56.00	-10.46	QP
5	2.5180	30.97	9.72	40.69	56.00	-15.31	QP
6	2.5740	17.42	9.72	27.14	46.00	-18.86	AVG

\*\*\*\*\* END OF REPORT \*\*\*\*\*