



FCC PART 15.247 TEST REPORT

For

Zeeva International Limited

Suite 1007B,10th Floor, Exchange Tower,33 Wang Chiu Road, Kowloon Bay, HongKong

FCC ID: 2ADM5-SP-0650

Report Type: **Product Type:**

Original Report TRUE WIRELESS SPEAKER

Report Number: RSZ181012830-00

Report Date: 2018-11-20

Rocky Kang

RF Engineer **Reviewed By:**

Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen)

6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone,

Rocky Kang

Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk

TABLE OF CONTENTS

Report No.: RSZ181012830-00

GENERAL INFORMATION	
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) OBJECTIVE	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
Measurement Uncertainty	
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	
DESCRIPTION OF TEST CONFIGURATION	<i>6</i>
EUT Exercise Software	
SPECIAL ACCESSORIES	
EQUIPMENT MODIFICATIONS	
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE	6
BLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	
TEST EQUIPMENT LIST	9
FCC§15.247 (i), §1.1307 (b) (1) &§2.1093 – RF EXPOSURE	11
APPLICABLE STANDARD	
FCC §15.203 – ANTENNA REQUIREMENT	
APPLICABLE STANDARD	
Antenna Connector Construction	
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	13
APPLICABLE STANDARD	13
EUT Setup.	
EMI TEST RECEIVER SETUP	
TEST PROCEDURE	
CORRECTED FACTOR & MARGIN CALCULATION	
TEST DATA	
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS	
APPLICABLE STANDARD	
EUT SETUPEMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST RESULTS SUMMARY	
TEST DATA	
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST	27
APPLICABLE STANDARD	
TEST PROCEDURE	
Test Data	27

Report No.: RSZ181012830-00

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The Zeeva International Limited's product, model number: SP-0650(FCC ID: 2ADM5-SP-0650, UPC Number: 192234007754, SKU Number: 3044229) or the "EUT" in this report was a TRUE WIRELESS SPEAKER, which was measured approximately: 6.5cm (L) *6.5 cm (W) * 4.5 cm (H), rated with input voltage: DC 3.7 V battery.

Report No.: RSZ181012830-00

Objective

This test report is prepared on behalf of *Zeeva International Limited* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

No Related Submittal(s)/Grant(s).

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Para	meter	Uncertainty
Occupied Char	nnel Bandwidth	±5%
RF Output Power	with Power meter	±0.5dB
RF conducted test with spectrum		±1.5dB
AC Power Lines Conducted Emissions		±1.95dB
Emissions,	Below 1GHz	±4.75dB
Radiated	Above 1GHz	±4.88dB
Temperature		±3℃
Humidity		±6%
Supply	voltages	±0.4%

FCC Part 15.247 Page 4 of 53

^{*}All measurement and test data in this report was gathered from production sample serial number: 181012830 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2018-10-12.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

Report No.: RSZ181012830-00

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

FCC Part 15.247 Page 5 of 53

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

EUT Exercise Software

"FCCasistant 2.4.exe" exercise software was made to the EUT tested.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
BLU	Phone	X LINK	/

Report No.: RSZ181012830-00


External I/O Cable

Cable Description	Length (m)	From Port	То
Un-shielding Detachable USB Cable	1.0	EUT	Adapter

FCC Part 15.247 Page 6 of 53

Block Diagram of Test Setup

For conducted emission:



Report No.: RSZ181012830-00

FCC Part 15.247 Page 7 of 53

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1)& §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
\$15.205, \$15.209 & \$15.247(d)	Radiated Emissions	Compliance
§15.247(a)(1)	20 dB Emission Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band edges	Compliance

Report No.: RSZ181012830-00

FCC Part 15.247 Page 8 of 53

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date			
Conducted Emissions Test								
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2018-07-11	2019-07-11			
Rohde & Schwarz	LISN	ENV216	3560.6650.12- 101613-Yb	2017-12-21	2018-12-21			
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2018-05-12	2018-11-21			
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR			
Un-known	Conducted Emission Cable	78652	UF A210B-1- 0720-504504	2018-05-12	2018-11-12			
	Radia	ated Emission T	est					
A.H. System	Horn Antenna	SAS-200/571	135	2018-09-01	2021-08-31			
Rohde & Schwarz	Signal Analyzer	FSEM	845987/005	2018-06-23	2019-06-23			
COM-POWER	Pre-amplifier	PA-122	181919	2018-05-22	2018-11-22			
Sonoma instrument	Amplifier	310N	186238	2018-05-12	2018-11-12			
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017-12-22	2020-12-21			
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2018-01-11	2019-01-11			
Ducommun technologies	RF Cable	UFA147A- 2362-100100	MFR64639 231029-003	2018-08-01	2019-02-01			
Ducommun technologies	RF Cable	104PEA	218124002	2018-05-21	2018-11-21			
Ducommun technologies	RF Cable	RG-214	1	2018-05-21	2018-11-19			
Ducommun technologies	RF Cable	RG-214	2	2018-05-22	2018-11-22			
Ducommun Technologies	Horn Antenna	ARH-4223- 02	1007726-04	2017-12-29	2020-12-28			
Heatsink Required	Amplifier	QLW- 18405536-J0	15964001002	2018-08-01	2019-02-01			
Sinoscite	Band Reject Filter	BSF2402- 2480MN- 0898-001	99632	2018-05-21	2018-11-21			
Rohde & Schwarz	Auto test software	EMC 32	V9.10	NCR	NCR			

Report No.: RSZ181012830-00

FCC Part 15.247 Page 9 of 53

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
	RF	Conducted Tes	t		
Agilent	USB wideband power meter	U2021XA	MY54250003	2018-06-23	2019-06-23
WEINSCHEL	3dB Attenuator	N/A	2018004	Each Time	
Rohde & Schwarz	Spectrum Analyzer	Spectrum Analyzer FSU26 200120 20		2017-12-24	2018-12-24
Ducommun technologies	RF Cable	RG-214	3	Each	Time

Report No.: RSZ181012830-00

FCC Part 15.247 Page 10 of 53

^{*} **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (1) &§2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Report No.: RSZ181012830-00

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- 1. f(GHz) is the RF channel transmit frequency in GHz.
- 2. Power and distance are rounded to the nearest mW and mm before calculation.
- 3. The result is rounded to one decimal place for comparison.
- 4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

For worst case:

Frequency p		Maximum Tune-up power Ca		Calculated	Threshold	SAR Test	
(MHz)	(dBm)	(mW)	Distance (mm)	Value	(1-g SAR)	Exclusion	
2480	-3	0.5	5	0.16	3.0	Yes	

Result: No Standalone SAR test is required

FCC Part 15.247 Page 11 of 53

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Report No.: RSZ181012830-00

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC Part 15.247 Page 12 of 53

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Report No.: RSZ181012830-00

Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

FCC Part 15.247 Page 13 of 53

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Correction Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Report No.: RSZ181012830-00

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions


Temperature:	25 ℃
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Shawn Xiao on 2018-11-09.

EUT operation mode: Bluetooth playing & charging

FCC Part 15.247 Page 14 of 53

AC 120V/60 Hz, Line




Report No.: RSZ181012830-00

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.198500	39.3	19.8	63.7	24.4	QP
0.209500	40.0	19.7	63.2	23.2	QP
0.318710	39.1	19.8	59.7	20.6	QP
0.336870	41.9	19.7	59.3	17.4	QP
0.348690	38.2	19.7	59.0	20.8	QP
0.510350	37.4	19.8	56.0	18.6	QP
0.198500	29.5	19.8	53.7	24.2	Ave.
0.209500	32.0	19.7	53.2	21.2	Ave.
0.318710	31.0	19.8	49.7	18.7	Ave.
0.336870	32.1	19.7	49.3	17.2	Ave.
0.348690	34.5	19.7	49.0	14.5	Ave.
0.510350	29.9	19.8	46.0	16.1	Ave.

FCC Part 15.247 Page 15 of 53

AC 120V/60 Hz, Neutral



Report No.: RSZ181012830-00

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.197500	37.9	19.7	63.7	25.8	QP
0.205500	37.6	19.7	63.4	25.8	QP
0.313350	39.9	19.8	59.9	20	QP
0.336930	39.3	19.7	59.3	20	QP
0.348690	36.6	19.7	59.0	22.4	QP
1.054250	28.0	19.8	56.0	28	QP
0.197500	29.1	19.7	53.7	24.6	Ave.
0.205500	31.6	19.7	53.4	21.8	Ave.
0.313350	33.2	19.8	49.9	16.7	Ave.
0.336930	33.1	19.7	49.3	16.2	Ave.
0.348690	31.7	19.7	49.0	17.3	Ave.
1.054250	21.8	19.8	46.0	24.2	Ave.

Note:

- 1) Correction Factor =LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
 3) Margin = Limit Corrected Amplitude

FCC Part 15.247 Page 16 of 53

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS

Applicable Standard

FCC §15.205; §15.209; §15.247(d)

EUT Setup

Below 1 GHz:



Report No.: RSZ181012830-00

Above 1GHz:



The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

FCC Part 15.247 Page 17 of 53

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 CHz	1 MHz	3 MHz	/	PK
Above 1 GHz	1 MHz	10 Hz	/	Average

Report No.: RSZ181012830-00

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.</u>

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \le L_{\rm lim} + U_{\rm cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

FCC Part 15.247 Page 18 of 53

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa


The testing was performed by Shawn Xiao on 2018-11-07.

EUT operation mode: Transmitting (Scan with GFSK, $\pi/4$ -DQPSK mode, the worst case is $\pi/4$ -DQPSK Mode)

Report No.: RSZ181012830-00

FCC Part 15.247 Page 19 of 53

30 MHz~1 GHz: (the worst case is $\pi/4$ -DQPSK Mode, High channel)



Report No.: RSZ181012830-00

Frequency (MHz)	Corrected Amplitude (dBµV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
30.332500	17.42	151.0	V	41.0	-7.8	40.00	22.58
232.739500	18.35	174.0	Н	10.0	-14.0	46.00	27.65
573.310125	19.65	236.0	V	356.0	-3.6	46.00	26.35
685.665875	21.15	338.0	Н	277.0	-1.9	46.00	24.85
838.082875	29.91	260.0	Н	107.0	5.8	46.00	16.09
958.843125	31.74	263.0	Н	204.0	9.3	46.00	14.26

FCC Part 15.247 Page 20 of 53

1 GHz - 25 GHz:

Б	Receiver Rx Antenna Corre		Corrected	Corrected Corrected	.				
Frequency (MHz)	Reading (dBµV)	PK/QP/Ave.	Turntable Degree	Height (m)		Factor (dB/m)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
			Low Ch	annel (2	2402 M	Hz)			
2402.00	60.03	PK	2	1.8	Н	33.00	93.03	/	/
2402.00	47.57	Ave.	2	1.8	Н	33.00	80.57	/	/
2402.00	53.56	PK	325	1.7	V	33.00	86.56	/	/
2402.00	42.90	Ave.	325	1.7	V	33.00	75.90	/	/
2344.15	27.70	PK	280	1.1	Н	32.97	60.67	74	13.33
2344.15	13.66	Ave.	280	1.1	Н	32.97	46.63	54	7.37
2486.18	26.91	PK	353	1.7	Н	33.20	60.11	74	13.89
2486.18	13.26	Ave.	353	1.7	Н	33.20	46.46	54	7.54
4804.00	47.74	PK	301	1.4	Н	7.88	55.62	74	18.38
4804.00	40.46	Ave.	301	1.4	Н	7.88	48.34	54	5.66
	Middle Channel (2441 MHz)								
2441.00	59.38	PK	218	1.4	Н	33.10	92.48	/	/
2441.00	46.88	Ave.	218	1.4	Н	33.10	79.98	/	/
2441.00	53.12	PK	225	2.2	V	33.10	86.22	/	/
2441.00	41.71	Ave.	225	2.2	V	33.10	74.81	/	/
4882.00	49.84	PK	285	1.8	Н	9.21	59.05	74	14.95
4882.00	41.29	Ave.	285	1.8	Н	9.21	50.50	54	3.50
			High Ch	annel (2	2480 M	Hz)			
2480.00	59.84	PK	239	2.4	Н	33.20	93.04	/	/
2480.00	50.14	Ave.	239	2.4	Н	33.20	83.34	/	/
2480.00	54.54	PK	11	2.1	V	33.20	87.74	/	/
2480.00	43.02	Ave.	11	2.1	V	33.20	76.22	/	/
2356.49	27.45	PK	100	1.1	Н	32.90	60.35	74	13.65
2356.49	13.53	Ave.	100	1.1	Н	32.90	46.43	54	7.57
2483.60	28.48	PK	200	2.0	Н	33.20	61.68	74	12.32
2483.60	16.31	Ave.	200	2.0	Н	33.20	49.51	54	4.49
4960.00	49.27	PK	280	1.3	Н	9.07	58.34	74	15.66
4960.00	41.78	Ave.	280	1.3	Н	9.07	50.85	54	3.15

Report No.: RSZ181012830-00

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor


Corrected Amplitude = Corrected Factor + Reading Margin = Limit - Corrected. Amplitude


The other spurious emission which is 20dB to the limit was not recorded. And for the pre-scan is performed with the 2400-2483.5MHz band filter.

FCC Part 15.247 Page 21 of 53

Pre-scan with middle channel Peak Horizontal

Report No.: RSZ181012830-00







FCC Part 15.247 Page 22 of 53

Vertical

Report No.: RSZ181012830-00




Date: 7.NOV.2018 15:39:06




FCC Part 15.247 Page 23 of 53

Pre-scan for Average Horizontal

Report No.: RSZ181012830-00





FCC Part 15.247 Page 24 of 53


2 MHz/

Span 20 MHz

Center 24.87374749 GHz


Date:

7.NOV.2018 16:10:24



Report No.: RSZ181012830-00


Vertical



FCC Part 15.247 Page 25 of 53

Report No.: RSZ181012830-00





FCC Part 15.247 Page 26 of 53

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hoping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Report No.: RSZ181012830-00

Test Procedure

- Set the EUT in transmitting mode, maxhold the channel. Set the adjacent channel of the EUT and maxhold another trace.
- 3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	25 ℃	
Relative Humidity:	54 %	
ATM Pressure:	101.0 kPa	

The testing was performed by Shawn Xiao on 2018-11-17.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots.


Channel	Channel Separation (MHz)	20 dBc BW (MHz)	Two-thirds of the 20 dB bandwidth (MHz)	Channel Separation Limit	Result
			BDR(GFSK)		
Low	1.005	0.875	0.583	> two-thirds of the 20 dB bandwidth	Compliance
Middle	1.000	0.865	0.577	> two-thirds of the 20 dB bandwidth	Compliance
High	1.005	0.865	0.577	> two-thirds of the 20 dB bandwidth	Compliance
	EDR(π/4-DQPSK)				
Low	1.005	1.207	0.805	> two-thirds of the 20 dB bandwidth	Compliance
Middle	1.000	1.216	0.811	> two-thirds of the 20 dB bandwidth	Compliance
High	1.005	1.221	0.814	> two-thirds of the 20 dB bandwidth	Compliance

Please refer to the following plots.

FCC Part 15.247 Page 27 of 53


BDR (GFSK): Low Channel

Report No.: RSZ181012830-00



Date: 17.NOV.2018 14:55:07

BDR (GFSK): Middle Channel




Date: 17.NOV.2018 14:58:00

FCC Part 15.247 Page 28 of 53


BDR (GFSK): High Channel

Report No.: RSZ181012830-00



Date: 17.NOV.2018 14:59:55

EDR ($\pi/4$ -DQPSK): Low Channel




Date: 17.NOV.2018 15:07:17

FCC Part 15.247 Page 29 of 53


EDR ($\pi/4$ -DQPSK): Middle Channel

Report No.: RSZ181012830-00



Date: 17.NOV.2018 15:04:55

EDR ($\pi/4$ -DQPSK): High Channel



Date: 17.NOV.2018 15:02:58

FCC Part 15.247 Page 30 of 53

FCC $\S15.247(a)$ (1) – 20 dB EMISSION BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Report No.: RSZ181012830-00

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions

Temperature:	25 ℃	
Relative Humidity:	54 %	
ATM Pressure:	101.0 kPa	

The testing was performed by Shawn Xiao on 2018-11-12.

EUT operation mode: Transmitting


Test Result: Compliance. Please refer to following table and plots.

Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
	Low	2402	0.875
BDR (GFSK)	Middle	2441	0.865
(GPSK)	High	2480	0.865
	Low	2402	1.207
EDR (π/4-DQPSK)	Middle	2441	1.216
(10, 1 2 Q1 512)	High	2480	1.221

FCC Part 15.247 Page 31 of 53


BDR (GFSK): Low Channel

Report No.: RSZ181012830-00



Date: 12.NOV.2018 13:50:18

BDR (GFSK): Middle Channel




Date: 12.NOV.2018 13:49:06

FCC Part 15.247 Page 32 of 53


BDR (GFSK): High Channel

Report No.: RSZ181012830-00



Date: 12.NOV.2018 13:33:14

EDR ($\pi/4$ -DQPSK): Low Channel




Date: 12.NOV.2018 13:26:26

FCC Part 15.247 Page 33 of 53


EDR ($\pi/4$ -DQPSK): Middle Channel

Report No.: RSZ181012830-00



Date: 12.NOV.2018 13:28:22

EDR ($\pi/4$ -DQPSK): High Channel



Date: 12.NOV.2018 13:31:17

FCC Part 15.247 Page 34 of 53

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Report No.: RSZ181012830-00

Test Procedure

- 1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- 2. Set the EUT in hopping mode from first channel to last.
- 3. By using the max-hold function record the quantity of the channel.

Test Data

Environmental Conditions

Temperature:	25 ℃	
Relative Humidity:	54 %	
ATM Pressure:	101.0 kPa	

The testing was performed by Shawn Xiao on 2018-11-12.

EUT operation mode: Transmitting


Test Result: Compliance. Please refer to following table and plots.

Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥15
EDR (π/4-DQPSK)	2400-2483.5	79	≥15

FCC Part 15.247 Page 35 of 53


BDR (GFSK): Number of Hopping Channels

Report No.: RSZ181012830-00



Date: 12.NOV.2018 15:01:24

EDR ($\pi/4$ -DQPSK): Number of Hopping Channels



Date: 12.NOV.2018 15:04:57

FCC Part 15.247 Page 36 of 53

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Report No.: RSZ181012830-00

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Zero span, centered on a hopping channel.
- b) RBW shall be \leq channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel.
- c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d) Detector function: Peak.
- e) Trace: Max hold.

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test or each variation in transmit time.

Repeat the measurement using a longer sweep time to determine the number of hops over the period pecified in the requirements. The sweep time shall be equal to, or less than, the period specified in the equirements. Determine the number of hops over the sweep time and calculate the total number of hops in he period specified in the requirements, using the following equation:

(Number of hops in the period specified in the requirements) =

(number of hops on spectrum analyzer) \times (period specified in the requirements / analyzer sweep time) The average time of occupancy is calculated from the transmit time per hop multiplied by the number of ops in the period specified in the requirements. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation.

The measured transmit time and time between hops shall be consistent with the values described in the operational description for the EUT.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by Shawn Xiao on 2018-11-12.

EUT operation mode: Transmitting

FCC Part 15.247 Page 37 of 53

Test Result: Compliance. Please refer to following table and plots

Mo	de	Pulse Time (ms)	Hopping Number	Period Time (s)	Total of Dwell (ms)	Limit (ms)	Result
DDD	DH 1	0.417	320	31.6	133.44	400	Pass
BDR (GFSK)	DH 3	1.740	150	31.6	261.00	400	Pass
	DH 5	3.013	80	31.6	241.04	400	Pass
EDR	2DH 1	0.434	310	31.6	134.54	400	Pass
(π/4- DQPSK)	2DH 3	1.745	150	31.6	261.75	400	Pass
	2DH 5	3.045	70	31.6	213.15	400	Pass

Report No.: RSZ181012830-00

Note 1: A period time=0.4*79=31.6(s), Total of Dwell=Pluse Time*Hopping Number

Note 2: Hopping Number= Hopping Number in 3.16s*10


Note 3: Hopping Number in 3.16s = Total of highest signals in 3.16s.(Second high signals were other channel)

FCC Part 15.247 Page 38 of 53

BDR (GFSK):


Report No.: RSZ181012830-00

Pulse time, DH1



Date: 12.NOV.2018 14:30:03

Hopping number in 3.16S, DH1




Date: 12.NOV.2018 14:31:53

FCC Part 15.247 Page 39 of 53


Hopping number in 31.6S, DH1

Report No.: RSZ181012830-00



Date: 12.NOV.2018 14:32:44

Pulse time, DH3




Date: 12.NOV.2018 14:35:30

FCC Part 15.247 Page 40 of 53


Hopping number in 3.16S, DH3

Report No.: RSZ181012830-00



Date: 12.NOV.2018 14:34:16

Hopping number in 31.6S, DH3




Date: 12.NOV.2018 14:33:46

FCC Part 15.247 Page 41 of 53


Pulse time, DH5

Report No.: RSZ181012830-00



Date: 12.NOV.2018 14:36:48

Hopping number in 3.16S, DH5




Date: 12.NOV.2018 14:53:40

FCC Part 15.247 Page 42 of 53

Hopping number in 31.6S, DH5


Report No.: RSZ181012830-00



Date: 12.NOV.2018 14:40:07

EDR ($\pi/4$ -DQPSK):

Pulse time, 2DH1




Date: 12.NOV.2018 14:44:08

FCC Part 15.247 Page 43 of 53


Hopping number in 3.16S, 2DH1

Report No.: RSZ181012830-00



Date: 12.NOV.2018 14:41:44

Hopping number in 31.6S, 2DH1




Date: 12.NOV.2018 14:41:01

FCC Part 15.247 Page 44 of 53


Pulse time, 2DH3

Report No.: RSZ181012830-00



Date: 12.NOV.2018 14:45:45

Hopping number in 3.16S, 2DH3




Date: 12.NOV.2018 14:46:43

FCC Part 15.247 Page 45 of 53


Hopping number in 31.6S, 2DH3

Report No.: RSZ181012830-00



Date: 12.NOV.2018 14:47:42

Pulse time, 2DH5




Date: 12.NOV.2018 14:49:59

FCC Part 15.247 Page 46 of 53


Hopping number in 3.16S, 2DH5

Report No.: RSZ181012830-00



Date: 12.NOV.2018 14:49:08

Hopping number in 31.6S, 2DH5



Date: 12.NOV.2018 14:48:47

FCC Part 15.247 Page 47 of 53

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Report No.: RSZ181012830-00

Test Procedure

- 1. Place the EUT on a bench and set in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
- 3. Add a correction factor to the display.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Shawn Xiao on 2018-11-13.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table.

Mode	Channel	Frequency (MHz)	Peak Output Power		Limit	
			(dBm)	(mW)	(mW)	
BDR (GFSK)	Low	2402	-4.51	0.354	125	
	Middle	2441	-4.29	0.372	125	
	High	2480	-4.69	0.340	125	
EDR (π/4-DQPSK)	Low	2402	-3.51	0.446	125	
	Middle	2441	-3.18	0.481	125	
	High	2480	-3.68	0.429	125	

FCC Part 15.247 Page 48 of 53

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Report No.: RSZ181012830-00

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by Shawn Xiao on 2018-11-12.


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following plots.

FCC Part 15.247 Page 49 of 53


BDR (GFSK): Band Edge-Left Side Hopping

Report No.: RSZ181012830-00



Date: 12.NOV.2018 14:09:24

Single




Date: 12.NOV.2018 14:00:05

FCC Part 15.247 Page 50 of 53


BDR (GFSK): Band Edge-Right Side Hopping

Report No.: RSZ181012830-00



Date: 12.NOV.2018 14:05:52

Single




Date: 12.NOV.2018 14:02:02

FCC Part 15.247 Page 51 of 53


EDR (π /4-DQPSK): Band Edge-Left Side Hopping

Report No.: RSZ181012830-00



Date: 12.NOV.2018 14:11:34

Single




Date: 12.NOV.2018 14:18:15

FCC Part 15.247 Page 52 of 53


EDR (π/4-DQPSK): Band Edge-Right Side Hopping

Report No.: RSZ181012830-00



Date: 12.NOV.2018 14:14:21

Single



Date: 12.NOV.2018 14:17:03

***** END OF REPORT *****

FCC Part 15.247 Page 53 of 53