



FCC PART 15.247 TEST REPORT

For

Zeeva International Limited

Suite 1007B,10th Floor, Exchange Tower 33 Wang Chiu Road, Kowloon Bay, HongKong, China

FCC ID:2ADM5-HP-0063

Report Type: **Product Type:** Original Report BT FROZEN 2 HEADPHONE **Report Number:** RSZ190731831-00 **Report Date:** 2019-08-12 Nany Wang Nancy Wang **Reviewed By:** RF Engineer Bay Area Compliance Laboratories Corp. (Shenzhen) **Prepared By:** 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "*".

The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
MEASUREMENT UNCERTAINTY	
TEST FACILITY	
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT Exercise Software	6
SPECIAL ACCESSORIES	
EQUIPMENT MODIFICATIONS	
SUPPORT EQUIPMENT LIST AND DETAILS	
EXTERNAL I/O CABLE	
BLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	8
TEST EQUIPMENT LIST	9
FCC §15.247 (i), §1.1307 (b) (1) & \$2.1093 – RF EXPOSURE	11
APPLICABLE STANDARD	11
FCC §15.203 – ANTENNA REQUIREMENT	12
APPLICABLE STANDARD	12
ANTENNA CONNECTOR CONSTRUCTION	
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	13
APPLICABLE STANDARD	13
EUT SETUP	13
EMI TEST RECEIVER SETUP	
TEST PROCEDURE	
CORRECTED FACTOR & MARGIN CALCULATION	
TEST RESULTS SUMMARY	
TEST DATA	
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS	17
APPLICABLE STANDARD	17
EUT SETUP	
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST RESULTS SUMMARY	
TEST DATA	
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST	
APPLICABLE STANDARD	
TEST PATA	25

FCC §1.247(a) (1) – 20 dB EMISSION BANDWIDTH	30
APPLICABLE STANDARD	30
TEST PROCEDURE	
TEST DATA	30
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	34
APPLICABLE STANDARD	34
TEST PROCEDURE	34
TEST DATA	34
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)	36
APPLICABLE STANDARD	36
TEST PROCEDURE	36
TEST DATA	36
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	47
APPLICABLE STANDARD	47
TEST PROCEDURE	47
TEST DATA	47
FCC §15.247(d) - BAND EDGES TESTING	48
APPLICABLE STANDARD	48
TEST PROCEDURE	48
Test Data	19

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	BT FROZEN 2 HEADPHONE
Tested Model	HP-0063
UPC Number	192234037485
SKU Number	3210911
Frequency Range	Bluetooth: 2402~2480MHz
Transmit Power	Bluetooth: -1.56dBm
Modulation Technique	Bluetooth: GFSK, π/4-DQPSK
Antenna Specification	-2dBi
Voltage Range	DC 3.7 V from battery
Date of Test	2019-08-02 to 2019-08-09
Sample serial number	190731831
Received date	2019-07-31
Sample/EUT Status	Good condition

Objective

This test report is prepared on behalf of *Zeeva International Limited* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

No Related Submittal(s)/Grant(s).

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

FCC Part 15.247 Page 4 of 52

Measurement Uncertainty

Para	meter	Uncertainty	
Occupied Char	nnel Bandwidth	±5%	
RF Output Power	with Power meter	±0.73dB	
RF conducted to	est with spectrum	±1.6dB	
AC Power Lines Conducted Emissions		±1.95dB	
Emissions,	Below 1GHz	±4.75dB	
Radiated	Above 1GHz	±4.88dB	
Temperature		±1 ℃	
Humidity		±6%	
Supply	voltages	±0.4%	

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

FCC Part 15.247 Page 5 of 52

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

EUT Exercise Software

"FCC Assist 1.0.1.1.exe" software was made to the EUT tested and the power level is 10.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	Adapter	RH-050100JP	/


External I/O Cable

Cable Description	Length (m)	From Port	То
Un-shielding detachable USB Cable	0.5	EUT	Adapter

FCC Part 15.247 Page 6 of 52

Block Diagram of Test Setup

For conducted emission:



FCC Part 15.247 Page 7 of 52

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1)& §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliance
§15.247(a)(1)	20 dB Emission Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement Complian	
§15.247(d)	Band edges Compliance	

FCC Part 15.247 Page 8 of 52

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
	Cond	ucted Emissions	Test		
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2019-07-11	2020-07-11
Rohde & Schwarz	LISN	ENV216	3560.6650.12- 101613-Yb	2019-01-25	2020-01-25
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2019-03-02	2020-03-01
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
Unknown	Conducted Emission Cable	78652	UF A210B-1- 0720-504504	2018-11-12	2019-11-12
	Rad	iated Emission T	est		
A.H. System	Horn Antenna	SAS-200/571	135	2018-09-01	2021-08-31
Rohde & Schwarz	Spectrum Analyzer	FSV40-N	102259	2019-07-22	2020-07-21
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017-12-22	2020-12-21
COM-POWER	Pre-amplifier	PA-122	181919	2018-11-12	2019-11-12
Sonoma Instrument	Amplifier	310N	186238	2018-11-12	2019-11-12
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2019-07-09	2020-07-08
UTiFLEX MICRO- C0AX	RF Cable	UFA147A- 2362-100100	MFR64639 231029-003	2018-11-12	2019-11-12
Ducommun Technologies	RF Cable	104PEA	218124002	2018-11-12	2019-11-12
Ducommun Technologies	RF Cable	RG-214	1	2019-05-21	2019-11-19
Ducommun Technologies	RF Cable	RG-214	2	2018-11-12	2019-11-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-04	2017-12-29	2020-12-28
Sinoscite	Band Reject Filter	BSF2402- 2480MN- 0898-001	99632	2018-11-12	2019-11-12
Rohde & Schwarz	Auto test software	EMC 32	V9.10	NCR	NCR

FCC Part 15.247 Page 9 of 52

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
	RF	Conducted Tes	t		
Agilent	USB wideband power meter	U2021XA	MY54250003	2019-07-10	2020-07-09
WEINSCHEL	3dB Attenuator	6231	666	Each Time	
Rohde & Schwarz	Spectrum Analyzer	FSU26	200120	2019-03-02	2020-03-01
Ducommun Technologies	RF Cable	RG-214	3	Each	Time

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC Part 15.247 Page 10 of 52

FCC §15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- 1. f(GHz) is the RF channel transmit frequency in GHz.
- 2. Power and distance are rounded to the nearest mW and mm before calculation.
- 3. The result is rounded to one decimal place for comparison.
- 4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

For worst case:

Frequency	Maximum Tune-up power		Calculated Distance	Calculated	Threshold	SAR Test
(MHz)	(dBm)	(mW)	(mm)	Value	(1-g SAR)	Exclusion
2480	-1.5	0.71	5	0.22	3.0	Yes

Result: No Standalone SAR test is required

FCC Part 15.247 Page 11 of 52

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is -2dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.


FCC Part 15.247 Page 12 of 52

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W	
150 kHz – 30 MHz	9 kHz	

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

FCC Part 15.247 Page 13 of 52

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Correction Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Haiguo Li on 2019-08-07.

EUT operation mode: Transmitting & charging (the worst case is GFSK Mode, middle channel)

FCC Part 15.247 Page 14 of 52


AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.278501	33.4	19.8	60.9	27.5	QP
0.305350	35.9	19.7	60.1	24.2	QP
0.340930	35.0	19.9	59.2	24.2	QP
0.352690	36.0	19.9	58.9	22.9	QP
0.869130	27.0	19.8	56.0	29.0	QP
0.991150	29.4	19.9	56.0	26.6	QP
0.278501	29.3	19.8	50.9	21.6	Ave.
0.305350	28.9	19.7	50.1	21.2	Ave.
0.340930	29.7	19.9	49.2	19.5	Ave.
0.352690	29.6	19.9	48.9	19.3	Ave.
0.869130	20.9	19.8	46.0	25.1	Ave.
0.991150	23.2	19.9	46.0	22.8	Ave.

FCC Part 15.247 Page 15 of 52

AC 120V/60 Hz, Neutral



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.258500	35.5	19.8	61.5	26.0	QP
0.282500	39.7	19.7	60.7	21.0	QP
0.305410	39.6	19.7	60.1	20.5	QP
0.340930	35.9	19.8	59.2	23.3	QP
0.352690	36.9	19.9	58.9	22.0	QP
1.050430	29.8	19.8	56.0	26.2	QP
0.258500	29.6	19.8	51.5	21.9	Ave.
0.282500	34.2	19.7	50.7	16.5	Ave.
0.305410	33.7	19.7	50.1	16.4	Ave.
0.340930	30.4	19.8	49.2	18.8	Ave.
0.352690	30.1	19.9	48.9	18.8	Ave.
1.050430	24.3	19.8	46.0	21.7	Ave.

Note:

- 1) Correction Factor =LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit Corrected Amplitude

FCC Part 15.247 Page 16 of 52


FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS

Applicable Standard


FCC §15.205; §15.209; §15.247(d)

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

FCC Part 15.247 Page 17 of 52

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, according to the DA 00-705 Released March 30, 2000, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Abovo 1 CHz	1 MHz	3 MHz	/	PK
Above 1 GHz	1 MHz	10 Hz	/	Average

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Title 47, Part 15, Subpart C, section 15.205, 15.209</u> and 15.247.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \le L_{\rm lim} + U_{\rm cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

FCC Part 15.247 Page 18 of 52

Test Data


Environmental Conditions

Temperature:	24~25 ℃	
Relative Humidity:	52~56 %	
ATM Pressure:	100.9~101.0 kPa	

The testing was performed by Andy Yu on 2019-08-07 and Curry Xiang on 2019-08-02.

EUT operation mode: Transmitting (Scan with GFSK, $\pi/4$ -DQPSK mode, the worst case is GFSK Mode)

30 MHz~1 GHz: (the worst case is GFSK Mode, middle channel)



FCC Part 15.247 Page 19 of 52

Frequency (MHz)	Corrected Amplitude (dBµV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
95.975750	30.88	192.0	Н	145.0	-17.9	43.50	12.62
132.000875	29.35	312.0	Н	41.0	-13.7	43.50	14.15
174.282375	15.72	141.0	Н	287.0	-15.1	43.50	27.78
287.986625	31.99	108.0	Н	93.0	-11.4	46.00	14.01
383.975875	37.16	108.0	Н	84.0	-10.5	46.00	8.84
838.617625	28.57	119.0	Н	174.0	5.8	46.00	17.43

1 GHz - 25 GHz:

	D.	eceiver		D A	4				
Frequency (MHz)	Reading (dBµV)	PK/QP/Ave.	Turntable Degree	Rx An Height (m)		Corrected Factor (dB/m)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
			Low Ch	annel (2	2402 M	Hz)			
2334.49	28.36	PK	80	1.9	Н	31.64	60.00	74	14.00
2334.49	14.48	Ave.	80	1.9	Н	31.64	46.12	54	7.88
2490.46	28.57	PK	257	1.2	Н	32.13	60.70	74	13.30
2490.46	14.63	Ave.	257	1.2	Н	32.13	46.76	54	7.24
4804.00	45.79	PK	278	1.9	Н	6.28	52.07	74	21.93
4804.00	35.63	Ave.	278	1.9	Н	6.28	41.91	54	12.09
			Middle C	hannel	(2441 N	(Hz)			
4882.00	47.07	PK	87	1.7	Н	6.76	53.83	74	20.17
4882.00	37.28	Ave.	87	1.7	Н	6.76	44.04	54	9.96
			High Ch	annel (2	2480 M	Hz)			
2370.61	27.68	PK	281	2.1	Н	31.87	59.55	74	14.45
2370.61	13.82	Ave.	281	2.1	Н	31.87	45.69	54	8.31
2489.64	27.89	PK	332	2.4	Н	32.13	60.02	74	13.98
2489.64	14.03	Ave.	332	2.4	Н	32.13	46.16	54	7.84
4960.00	47.15	PK	54	1.7	Н	6.80	53.95	74	20.05
4960.00	38.75	Ave.	350	2.4	Н	6.80	45.55	54	8.45

Note:


Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor Corrected Amplitude = Corrected Factor + Reading Margin = Limit - Corrected. Amplitude

The other spurious emission which is 20dB to the limit was not recorded.


And for the pre-scan is performed with the 2400-2483.5MHz band filter.

Page 20 of 52 FCC Part 15.247

Pre-scan with High Channel Peak Horizontal




Date: 2.AUG.2019 22:15:16




Date: 2.AUG.2019 22:51:03

FCC Part 15.247 Page 21 of 52

Vertical




Date: 2.AUG.2019 22:06:33




Date: 2.AUG.2019 22:58:15

FCC Part 15.247 Page 22 of 52

Pre-scan for Average Horizontal




Date: 2.AUG.2019 22:19:00




Date: 2.AUG.2019 22:54:33

FCC Part 15.247 Page 23 of 52

Vertical



Date: 2.AUG.2019 22:11:22



Date: 2.AUG.2019 23:02:44

FCC Part 15.247 Page 24 of 52

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hoping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Test Procedure

- 1. Set the EUT in transmitting mode, maxhold the channel.
- 2. Set the adjacent channel of the EUT and maxhold another trace.
- 3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	25 ℃	
Relative Humidity:	55 %	
ATM Pressure:	101.0 kPa	

The testing was performed by Leo Huang on 2019-08-03.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots.


FCC Part 15.247 Page 25 of 52

Channel	Channel Separation (MHz)	20 dBc BW (MHz)	Two-thirds of the 20 dB bandwidth (MHz)	Channel Separation Limit	Result	
	BDR(GFSK)					
Low	1.000	0.842	0.561	> two-thirds of the 20 dB bandwidth	Compliance	
Middle	1.000	0.845	0.563	> two-thirds of the 20 dB bandwidth	Compliance	
High	1.000	0.843	0.562	> two-thirds of the 20 dB bandwidth	Compliance	
		F	DR(π/4-DQPSK)			
Low	1.000	1.208	0.805	> two-thirds of the 20 dB bandwidth	Compliance	
Middle	1.000	1.213	0.809	> two-thirds of the 20 dB bandwidth	Compliance	
High	1.000	1.213	0.809	> two-thirds of the 20 dB bandwidth	Compliance	

Please refer to the following plots.


FCC Part 15.247 Page 26 of 52

BDR (GFSK): Low Channel



Date: 3.AUG.2019 15:36:59


BDR (GFSK): Middle Channel



Date: 3.AUG.2019 15:36:59


FCC Part 15.247 Page 27 of 52

BDR (GFSK): High Channel



Date: 3.AUG.2019 15:35:06


EDR ($\pi/4$ -DQPSK): Low Channel



Date: 3.AUG.2019 15:26:40


FCC Part 15.247 Page 28 of 52

EDR ($\pi/4$ -DQPSK): Middle Channel



Date: 3.AUG.2019 15:29:36

EDR ($\pi/4$ -DQPSK): High Channel



Date: 3.AUG.2019 15:26:40

FCC Part 15.247 Page 29 of 52

FCC $\S1.247(a)$ (1) – 20 dB EMISSION BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions

Temperature:	25 ℃	
Relative Humidity:	55 %	
ATM Pressure:	101.0 kPa	

The testing was performed by Leo Huang on 2019-08-03.


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots.

Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
	Low	2402	0.842
BDR (GFSK)	Middle	2441	0.845
	High	2480	0.843
	Low	2402	1.208
EDR (π/4-DQPSK)	Middle	2441	1.213
(···· (- 3-2)	High	2480	1.213


FCC Part 15.247 Page 30 of 52

20 dB Emission Bandwidth, BDR (GFSK): Low Channel



Date: 3.AUG.2019 14:52:10


20 dB Emission Bandwidth, BDR (GFSK): Middle Channel



Date: 3.AUG.2019 14:51:08


FCC Part 15.247 Page 31 of 52

20 dB Emission Bandwidth, BDR (GFSK): High Channel



Date: 3.AUG.2019 14:50:14


20 dB Emission Bandwidth, EDR ($\pi/4$ -DQPSK): Low Channel



Date: 3.AUG.2019 14:46:06


FCC Part 15.247 Page 32 of 52

20 dB Emission Bandwidth, EDR ($\pi/4$ -DQPSK): Middle Channel



Date: 3.AUG.2019 14:47:36

20 dB Emission Bandwidth, EDR (π/4-DQPSK): High Channel



Date: 3.AUG.2019 14:49:19

FCC Part 15.247 Page 33 of 52

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

- 1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- 2. Set the EUT in hopping mode from first channel to last.
- 3. By using the max-hold function record the quantity of the channel.

Test Data

Environmental Conditions

Temperature:	25 ℃	
Relative Humidity:	55 %	
ATM Pressure:	101.0 kPa	

The testing was performed by Leo Huang on 2019-08-03.


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots.

Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥15
EDR (π/4-DQPSK)	2400-2483.5	79	≥15


FCC Part 15.247 Page 34 of 52

BDR (GFSK): Number of Hopping Channels



Date: 3.AUG.2019 15:19:29

EDR ($\pi/4$ -DQPSK): Number of Hopping Channels



Date: 3.AUG.2019 15:23:36

FCC Part 15.247 Page 35 of 52

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

- 1. The EUT was worked in channel hopping.
- 2. Set the RBW to: 1MHz.
- 3. Set the VBW \geq 3×RBW.
- 4. Set the span to 0Hz.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Recorded the time of single pulses

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Leo Huang on 2019-08-03.

EUT operation mode: Transmitting

FCC Part 15.247 Page 36 of 52


Test Result: Compliance. Please refer to following table and plots

Mode		Channel	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Result
BDR (GFSK)	DH 1	Low	0.436	0.140	0.4	Pass
		Middle	0.436	0.140	0.4	Pass
		High	0.436	0.140	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6s				
	DH 3	Low	1.714	0.274	0.4	Pass
		Middle	1.714	0.274	0.4	Pass
		High	1.714	0.274	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6s				
	DH 5	Low	2.974	0.317	0.4	Pass
		Middle	2.974	0.317	0.4	Pass
		High	2.974	0.317	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6s				
EDR (π/4-DQPSK)	2DH 1	Low	0.442	0.141	0.4	Pass
		Middle	0.442	0.141	0.4	Pass
		High	0.442	0.141	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6s				
	2DH 3	Low	1.714	0.274	0.4	Pass
		Middle	1.714	0.274	0.4	Pass
		High	1.714	0.274	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6s				
	2DH 5	Low	2.974	0.317	0.4	Pass
		Middle	2.974	0.317	0.4	Pass
		High	2.974	0.317	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6s				

FCC Part 15.247 Page 37 of 52


BDR (GFSK):

Pulse time, Low Channel, DH1



Date: 3.AUG.2019 15:48:49


Pulse time, Middle Channel, DH1



Date: 3.AUG.2019 15:49:17


FCC Part 15.247 Page 38 of 52

Pulse time, High Channel, DH1



Date: 3.AUG.2019 15:49:57


Pulse time, Low Channel, DH3



Date: 3.AUG.2019 15:53:00


FCC Part 15.247 Page 39 of 52

Pulse time, Middle Channel, DH3



Date: 3.AUG.2019 15:53:32


Pulse time, High Channel, DH3



Date: 3.AUG.2019 15:54:01


FCC Part 15.247 Page 40 of 52

Pulse time, Low Channel, DH5



Date: 3.AUG.2019 16:07:44


Pulse time, Middle Channel, DH5



Date: 3.AUG.2019 16:07:22

FCC Part 15.247 Page 41 of 52


Pulse time, High Channel, DH5



Date: 3.AUG.2019 16:07:01

EDR ($\pi/4$ -DQPSK):


Pulse time, Low Channel, 2DH1



Date: 3.AUG.2019 15:51:40


FCC Part 15.247 Page 42 of 52

Pulse time, Middle Channel, 2DH1



Date: 3.AUG.2019 15:51:12


Pulse time, High Channel, 2DH1



Date: 3.AUG.2019 15:50:49


FCC Part 15.247 Page 43 of 52

Pulse time, Low Channel, 2DH3



Date: 3.AUG.2019 15:55:05


Pulse time, Middle Channel, 2DH3



Date: 3.AUG.2019 15:54:43


FCC Part 15.247 Page 44 of 52

Pulse time, High Channel, 2DH3



Date: 3.AUG.2019 15:54:25


Pulse time, Low Channel, 2DH5



Date: 3.AUG.2019 15:59:56


FCC Part 15.247 Page 45 of 52

Pulse time, Middle Channel, 2DH5



Date: 3.AUG.2019 15:59:08

Pulse time, High Channel, 2DH5



Date: 3.AUG.2019 16:04:33

FCC Part 15.247 Page 46 of 52

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

- 1. Place the EUT on a bench and set in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
- 3. Add a correction factor to the display.

Test Data

Environmental Conditions

Temperature:	25 ℃	
Relative Humidity:	55 %	
ATM Pressure:	101.0 kPa	

The testing was performed by Leo Huang on 2019-08-03.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table.

Mode	Channel	Frequency	Peak Output Power		Limit	
	Chamici	(MHz)	(dBm)	(mW)	(mW)	
BDR (GFSK)	Low	2402	-1.91	0.64	125	
	Middle	2441	-2.61	0.55	125	
	High	2480	-3.54	0.44	125	
EDR (π/4-DQPSK)	Low	2402	-1.56	0.70	125	
	Middle	2441	-2.17	0.61	125	
	High	2480	-3.05	0.50	125	

FCC Part 15.247 Page 47 of 52

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	25 ℃	
Relative Humidity:	55 %	
ATM Pressure:	101.0 kPa	


The testing was performed by Leo Huang on 2019-08-03 and 2019-08-09.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following plots.


FCC Part 15.247 Page 48 of 52

BDR (GFSK): Band Edge-Left Side Hopping



Date: 3.AUG.2019 15:07:21


Single



Date: 9.AUG.2019 13:54:13


FCC Part 15.247 Page 49 of 52

BDR (GFSK): Band Edge-Right Side Hopping



Date: 3.AUG.2019 15:08:42


Single



Date: 3.AUG.2019 15:16:05


FCC Part 15.247 Page 50 of 52

EDR (π /4-DQPSK): Band Edge-Left Side Hopping



Date: 3.AUG.2019 15:12:08


Single



Date: 3.AUG.2019 15:12:48


FCC Part 15.247 Page 51 of 52

EDR (π /4-DQPSK): Band Edge-Right Side Hopping



Date: 3.AUG.2019 15:10:21

Single



Date: 3.AUG.2019 15:14:06

***** END OF REPORT *****

FCC Part 15.247 Page 52 of 52