



FCC RF Test Report

APPLICANT : BungBungame Technology Co.,Ltd.
EQUIPMENT : BungBungame Tablet
BRAND NAME : BungBungame
MODEL NAME : KALOS 2
FCC ID : 2ADNC-KA2TB115
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DSS) Spread Spectrum Transmitter

The product was received on Oct. 12, 2015 and testing was completed on Jan. 06, 2016. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.



TABLE OF CONTENTS

SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	6
1.6 Testing Location	7
1.7 Applicable Standards.....	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	9
2.1 Descriptions of Test Mode	9
2.2 Test Mode.....	10
2.3 Connection Diagram of Test System.....	11
2.4 Support Unit used in test configuration and system	12
2.5 EUT Operation Test Setup	12
2.6 Measurement Results Explanation Example.....	12
3 TEST RESULT	13
3.1 Number of Channel Measurement	13
3.2 Hopping Channel Separation Measurement	15
3.3 Dwell Time Measurement.....	22
3.4 20dB Bandwidth Measurement	25
3.5 Peak Output Power Measurement	32
3.6 Conducted Band Edges Measurement.....	34
3.7 Conducted Spurious Emission Measurement	41
3.8 Radiated Band Edges and Spurious Emission Measurement	51
3.9 AC Conducted Emission Measurement.....	57
3.10 Antenna Requirements.....	67
4 LIST OF MEASURING EQUIPMENT.....	68
5 UNCERTAINTY OF EVALUATION.....	69
APPENDIX A. RADIATED TEST RESULTS	
APPENDIX B. RADIATED SPURIOUS EMISSION PLOTS	
APPENDIX C. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR5O1213A	Rev. 01	Initial issue of report	Jan. 29, 2016
FR5O1213A	Rev. 02	Adding standards imformation in section 1.7	Feb. 01, 2016

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	Number of Channels	$\geq 15\text{Chs}$	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	$\leq 0.4\text{sec}$ in 31.6sec period	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	NA	Pass	-
3.5	15.247(b)(1)	Peak Output Power	$\leq 125\text{ mW}$	Pass	-
3.6	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 2.95 dB at 218.730 MHz
3.9	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 3.90 dB at 0.454 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

BungBungame Technology Co.,Ltd.

15F., No. 19-11, Sanchong Rd., Nangang Dist., Taipei City 11501, Taiwan (R.O.C)

1.2 Manufacturer

Inventec Appliances (Jiangning) Corporation

133, Jiang-Jun Road, Jiangning District, Nanjing

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	BungBungame Tablet
Brand Name	BungBungame
Model Name	KALOS 2
FCC ID	2ADNC-KA2TB115
EUT supports Radios application	NFC/GPS WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth v4.1 EDR/LE
HW Version	PVT
SW Version	1
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	Bluetooth BR(1Mbps) : 4.49 dBm (0.0028 W) Bluetooth EDR (2Mbps) : 3.66 dBm (0.0023 W) Bluetooth EDR (3Mbps) : 3.92 dBm (0.0025 W)
Antenna Type	Chip Antenna type with gain 0.46 dBi
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : π /4-DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH02-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2009 requirement.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH11-HY	

Note: The test site complies with ANSI C63.4 2009 requirement.



1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC Public Notice DA 00-705
- ♦ ANSI C63.10-2009

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. FCC permits the use of the 1.5 meter table as an alternative in C63.10-2013 through inquiry tracking number 961829.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Preliminary tests were performed in different data rates and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power		
		Data Rate / Modulation		
		GFSK	$\pi/4$ -DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	3.63 dBm	3.24 dBm	3.42 dBm
Ch39	2441MHz	4.49 dBm	3.66 dBm	3.92 dBm
Ch78	2480MHz	4.05 dBm	2.81 dBm	3.12 dBm

Remark:

1. All the test data for each data rate were verified, but only the worst case was reported.
 2. The data rate was set in 1Mbps for all the test items due to the highest RF output power.
- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels, and different data rates were conducted to determine the final configuration (Z plane as worst plane) from all possible combinations, and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.


2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps π /4-DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth BR 1Mbps GFSK		
	Mode 1: CH00_2402 MHz		
	Mode 2: CH39_2441 MHz		
	Mode 3: CH78_2480 MHz		
AC Conducted Emission	Mode 1 :Bluetooth Link + WLAN (2.4GHz) Link + Camera + Earphone + USB Cable (Charging from Adapter)		
Remark: For radiated test cases, the worst mode data rate 1Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and the conducted spurious emissions and conducted band edge measurement for each data rate are no worse than 1Mbps, and no other significantly frequencies found in conducted spurious emission.			

2.3 Connection Diagram of Test System

<Bluetooth Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-865L	KA2IR865LA1	N/A	Unshielded, 1.8 m
3.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
5.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A
6.	SD Card	SanDisk	Micro SD HC	FCC DoC	N/A	N/A

2.5 EUT Operation Test Setup

For Bluetooth function, programmed RF utility, "k2_wifi_controller.exe" installed in the notebook make the EUT provide functions like channel selection and power level for continuous transmitting and receiving signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation;
RBW = 300kHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup




3.1.5 Test Result of Number of Hopping Frequency


Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Tommy Lee	Relative Humidity :	48~51%
Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass



Number of Hopping Channel Plot on Channel 00 - 78



Date: 8.DEC.2015 14:12:36



Date: 8.DEC.2015 14:43:59

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels;
RBW = 300kHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.


3.2.4 Test Setup



**3.2.5 Test Result of Hopping Channel Separation**

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Tommy Lee	Relative Humidity :	48~51%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.008	0.6507	Pass
39	2441	1.326	0.6480	Pass
78	2480	1.152	0.6720	Pass

Channel Separation Plot on Channel 00 - 01

Date: 8.DEC.2015 14:06:02




Channel Separation Plot on Channel 39 - 40



Date: 8.DEC.2015 14:59:38

Channel Separation Plot on Channel 77 - 78




Date: 8.DEC.2015 14:53:31



Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Tommy Lee	Relative Humidity :	48~51%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.014	0.9040	Pass
39	2441	1.002	0.9040	Pass
78	2480	1.008	0.9000	Pass

Channel Separation Plot on Channel 00 - 01

Date: 8.DEC.2015 15:20:40




Channel Separation Plot on Channel 39 - 40



Date: 8.DEC.2015 15:26:40

Channel Separation Plot on Channel 77 - 78




Date: 8.DEC.2015 15:57:14



Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Tommy Lee	Relative Humidity :	48~51%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.014	0.8760	Pass
39	2441	1.002	0.8840	Pass
78	2480	1.008	0.8760	Pass

Channel Separation Plot on Channel 00 - 01

Date: 8.DEC.2015 15:36:23




Channel Separation Plot on Channel 39 - 40



Date: 8.DEC.2015 15:39:05

Channel Separation Plot on Channel 77 - 78



Date: 8.DEC.2015 15:43:41

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW \geq RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Dwell Time

Test Mode :	DH5	Temperature :	24~26℃
Test Engineer :	Tommy Lee	Relative Humidity :	48~51%


Mode	Hopping Channel Number	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Normal	79	106.67	2.90	0.31	0.4	Pass
AFH	20	53.33	2.90	0.15	0.4	Pass

Remark:

- In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels.
With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),
Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
- In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.
With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),
Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
- Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time



Package Transfer Time Plot



Date: 26.NOV.2015 10:12:25

3.4 20dB Bandwidth Measurement

3.4.1 Limit of 20dB Bandwidth

Reporting only


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
RBW \geq 1% of the 20 dB bandwidth; VBW \geq RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. Measure and record the results in the test report.

3.4.4 Test Setup




3.4.5 Test Result of 20dB Bandwidth

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Tommy Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	0.976
39	2441	0.972
78	2480	1.008


20 dB Bandwidth Plot on Channel 00



Date: 8.DEC.2015 14:00:51




20 dB Bandwidth Plot on Channel 39



Date: 8.DEC.2015 14:56:21

20 dB Bandwidth Plot on Channel 78




Date: 8.DEC.2015 14:49:22



Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Tommy Lee	Relative Humidity :	48~51%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.356
39	2441	1.356
78	2480	1.350

20 dB Bandwidth Plot on Channel 00

Date: 8.DEC.2015 15:01:30




20 dB Bandwidth Plot on Channel 39



Date: 8.DEC.2015 15:02:05

20 dB Bandwidth Plot on Channel 78




Date: 8.DEC.2015 15:02:36

Test Mode :	3Mbps	Temperature :	24~26℃
Test Engineer :	Tommy Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.314
39	2441	1.326
78	2480	1.314


20 dB Bandwidth Plot on Channel 00



Date: 8.DEC.2015 15:04:33




20 dB Bandwidth Plot on Channel 39



Date: 8.DEC.2015 15:04:02

20 dB Bandwidth Plot on Channel 78



Date: 8.DEC.2015 15:03:29

3.5 Peak Output Power Measurement

3.5.1 Limit of Peak Output Power

Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps is 1watt, and for 2Mbps, 3Mbps and AFH are 0.125 watts.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup



**3.5.5 Test Result of Peak Output Power**

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Tommy Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	3.63	20.97	Pass
39	2441	4.49	20.97	Pass
78	2480	4.05	20.97	Pass

Note: For AFH mode using 20 hopping channels, the maximum output power limit is 20.97dBm.

Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Tommy Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		$\pi/4$ -DQPSK	Max. Limits (dBm)	Pass/Fail
		2 Mbps		
00	2402	3.24	20.97	Pass
39	2441	3.66	20.97	Pass
78	2480	2.81	20.97	Pass

Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Tommy Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	3.42	20.97	Pass
39	2441	3.92	20.97	Pass
78	2480	3.12	20.97	Pass

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.


3.6.4 Test Setup



3.6.5 Test Result of Conducted Band Edges


Test Mode :	1Mbps	Temperature :	24~26℃
Test Channel :	00 and 78	Relative Humidity :	48~51%
		Test Engineer :	Tommy Lee

Low Band Edge Plot on Channel 00



Date: 8.DEC.2015 15:05:09


High Band Edge Plot on Channel 78



Date: 8.DEC.2015 15:05:36


Test Mode :	2Mbps	Temperature :	24~26℃
Test Channel :	00 and 78	Relative Humidity :	48~51%
		Test Engineer :	Tommy Lee

Low Band Edge Plot on Channel 00



Date: 8.DEC.2015 15:52:30


High Band Edge Plot on Channel 78



Date: 8.DEC.2015 15:52:59


Test Mode :	3Mbps	Temperature :	24~26℃
Test Channel :	00 and 78	Relative Humidity :	48~51%
		Test Engineer :	Tommy Lee

Low Band Edge Plot on Channel 00



Date: 8.DEC.2015 15:53:57


High Band Edge Plot on Channel 78




Date: 8.DEC.2015 15:53:32

**3.6.6 Test Result of Conducted Hopping Mode Band Edges**

Test Mode :	1Mbps	Temperature :	24~26℃
Test Engineer :	Tommy Lee	Relative Humidity :	48~51%

1Mbps Hopping Mode Low Band Edge Plot


Date: 8.DEC.2015 14:46:37

1Mbps Hopping Mode High Band Edge Plot

Date: 8.DEC.2015 14:48:05


Test Mode :	2Mbps	Temperature :	24~26℃
Test Engineer :	Tommy Lee	Relative Humidity :	48~51%

2Mbps Hopping Mode Low Band Edge Plot



Date: 8.DEC.2015 15:51:49


2Mbps Hopping Mode High Band Edge Plot




Date: 8.DEC.2015 15:50:26



Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Tommy Lee	Relative Humidity :	48~51%

3Mbps Hopping Mode Low Band Edge Plot

Date: 8.DEC.2015 15:47:42

3Mbps Hopping Mode High Band Edge Plot

Date: 8.DEC.2015 15:48:45

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedure


1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.7.4 Test Setup




**3.7.5 Test Result of Conducted Spurious Emission**

Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	48~51%
		Test Engineer :	Tommy Lee

1Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz


Date: 8.DEC.2015 14:55:23

1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz


Date: 8.DEC.2015 14:55:45



Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	48~51%
		Test Engineer :	Tommy Lee

1Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz


Date: 8.DEC.2015 14:58:12

1Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz


Date: 8.DEC.2015 14:58:33



Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	Tommy Lee

1Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz


Date: 8.DEC.2015 14:50:30

1Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz


Date: 8.DEC.2015 14:50:52



Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	48~51%
		Test Engineer :	Tommy Lee

2Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz


Date: 8.DEC.2015 15:19:18

2Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz


Date: 8.DEC.2015 15:19:40



Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	48~51%
		Test Engineer :	Tommy Lee

2Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz


Date: 8.DEC.2015 15:23:39

2Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz


Date: 8.DEC.2015 15:25:32



Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	Tommy Lee

2Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz


Date: 8.DEC.2015 15:30:01

2Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz


Date: 8.DEC.2015 15:30:23



Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	48~51%
		Test Engineer :	Tommy Lee

3Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz


Date: 8.DEC.2015 15:33:49

3Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz


Date: 8.DEC.2015 15:34:11



Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	48~51%
		Test Engineer :	Tommy Lee

3Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz


Date: 8.DEC.2015 15:37:42

3Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz


Date: 8.DEC.2015 15:38:04



Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	Tommy Lee

3Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz

Date: 8.DEC.2015 15:40:26

3Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz

Date: 8.DEC.2015 15:40:48

3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.8.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1 \text{ GHz}$, RBW=1MHz for $f > 1 \text{ GHz}$; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).
Duty cycle = On time/100 milliseconds
On time = $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$
Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
Average Emission Level = Peak Emission Level + $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.79dB) derived from $20 \log(\text{dwell time}/100\text{ms})$. This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

3.8.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz




3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)


The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.8.6 Duty cycle correction factor for average measurement

DH5 on time (One Pulse) Plot on Channel 39



DH5 on time (Count Pulses) Plot on Channel 39



Note:

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.88 / 100 = 5.76 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.79 \text{ dB}$
3. DH5 has the highest duty cycle worst case and is reported.

Duty Cycle Correction Factor Consideration for AFH mode:

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.88 \text{ ms} \times 20 \text{ channels} = 57.6 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. $[100\text{ms} / 57.6\text{ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.76 \text{ ms}/100\text{ms}) = -24.79 \text{ dB}$$

3.8.7 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix A.

3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix A.

3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.9.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.9.4 Test Setup



AMN = Artificial mains network (LISN)
 AE = Associated equipment
 EUT = Equipment under test
 ISN = Impedance stabilization network

3.9.5 Test Result of AC Conducted Emission


Test Mode :	Mode 1	Temperature :	20~21℃
Test Engineer :	Kai Chun Chu	Relative Humidity :	53~55%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	Bluetooth Link + WLAN (2.4GHz) Link + Camera + Earphone + USB Cable (Charging from Adapter)		



Final Result : Quasi-Peak


Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.198000	59.7	Off	L1	19.7	4.0	63.7
0.262000	49.3	Off	L1	19.7	12.1	61.4
0.334000	52.7	Off	L1	19.7	6.7	59.4
0.406000	53.5	Off	L1	19.7	4.2	57.7
0.446000	46.5	Off	L1	19.6	10.4	56.9
0.518000	51.8	Off	L1	19.7	4.2	56.0
0.606000	44.8	Off	L1	19.7	11.2	56.0
0.654000	44.3	Off	L1	19.6	11.7	56.0
0.734000	44.6	Off	L1	19.7	11.4	56.0
0.782000	45.8	Off	L1	19.6	10.2	56.0
0.862000	43.6	Off	L1	19.7	12.4	56.0
0.942000	43.7	Off	L1	19.7	12.3	56.0
1.054000	43.7	Off	L1	19.7	12.3	56.0
1.214000	42.7	Off	L1	19.6	13.3	56.0
1.294000	44.2	Off	L1	19.6	11.8	56.0
1.366000	43.9	Off	L1	19.6	12.1	56.0
1.486000	42.5	Off	L1	19.7	13.5	56.0
1.574000	43.6	Off	L1	19.6	12.4	56.0
1.710000	44.0	Off	L1	19.7	12.0	56.0
1.822000	41.1	Off	L1	19.7	14.9	56.0
1.926000	43.1	Off	L1	19.7	12.9	56.0
1.990000	43.6	Off	L1	19.6	12.4	56.0

Test Mode :	Mode 1	Temperature :	20~21°C
Test Engineer :	Kai Chun Chu	Relative Humidity :	53~55%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	Bluetooth Link + WLAN (2.4GHz) Link + Camera + Earphone + USB Cable (Charging from Adapter)		


Final Result : Quasi-Peak


Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
2.134000	43.0	Off	L1	19.6	13.0	56.0
2.262000	43.5	Off	L1	19.7	12.5	56.0
2.470000	41.9	Off	L1	19.6	14.1	56.0
2.678000	42.7	Off	L1	19.6	13.3	56.0
2.838000	42.1	Off	L1	19.7	13.9	56.0
3.158000	42.1	Off	L1	19.7	13.9	56.0
3.590000	41.6	Off	L1	19.7	14.4	56.0
3.774000	41.3	Off	L1	19.7	14.7	56.0
4.078000	40.2	Off	L1	19.7	15.8	56.0
4.358000	40.1	Off	L1	19.7	15.9	56.0
4.598000	41.9	Off	L1	19.7	14.1	56.0
4.878000	39.0	Off	L1	19.8	17.0	56.0
6.454000	45.6	Off	L1	19.7	14.4	60.0
6.926000	46.1	Off	L1	19.7	13.9	60.0
7.142000	45.4	Off	L1	19.8	14.6	60.0
7.414000	43.2	Off	L1	19.7	16.8	60.0
7.830000	47.2	Off	L1	19.7	12.8	60.0
8.198000	45.3	Off	L1	19.7	14.7	60.0
8.422000	44.2	Off	L1	19.7	15.8	60.0
8.782000	40.5	Off	L1	19.8	19.5	60.0

Test Mode :	Mode 1	Temperature :	20~21°C
Test Engineer :	Kai Chun Chu	Relative Humidity :	53~55%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	Bluetooth Link + WLAN (2.4GHz) Link + Camera + Earphone + USB Cable (Charging from Adapter)		


Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.198000	44.5	Off	L1	19.7	9.2	53.7
0.262000	34.8	Off	L1	19.7	16.6	51.4
0.334000	40.5	Off	L1	19.7	8.9	49.4
0.406000	37.9	Off	L1	19.7	9.8	47.7
0.446000	29.4	Off	L1	19.6	17.5	46.9
0.518000	36.0	Off	L1	19.7	10.0	46.0
0.606000	29.8	Off	L1	19.7	16.2	46.0
0.654000	30.9	Off	L1	19.6	15.1	46.0
0.734000	31.3	Off	L1	19.7	14.7	46.0
0.782000	30.2	Off	L1	19.6	15.8	46.0
0.862000	29.4	Off	L1	19.7	16.6	46.0
0.942000	29.3	Off	L1	19.7	16.7	46.0
1.054000	28.8	Off	L1	19.7	17.2	46.0
1.214000	28.6	Off	L1	19.6	17.4	46.0
1.294000	30.4	Off	L1	19.6	15.6	46.0
1.366000	29.9	Off	L1	19.6	16.1	46.0
1.486000	29.1	Off	L1	19.7	16.9	46.0
1.574000	29.2	Off	L1	19.6	16.8	46.0
1.710000	27.9	Off	L1	19.7	18.1	46.0
1.822000	27.7	Off	L1	19.7	18.3	46.0
1.926000	28.3	Off	L1	19.7	17.7	46.0


Test Mode :	Mode 1	Temperature :	20~21°C
Test Engineer :	Kai Chun Chu	Relative Humidity :	53~55%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	Bluetooth Link + WLAN (2.4GHz) Link + Camera + Earphone + USB Cable (Charging from Adapter)		


Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
1.990000	28.5	Off	L1	19.6	17.5	46.0
2.134000	27.6	Off	L1	19.6	18.4	46.0
2.262000	28.4	Off	L1	19.7	17.6	46.0
2.470000	27.2	Off	L1	19.6	18.8	46.0
2.678000	27.2	Off	L1	19.6	18.8	46.0
2.838000	27.2	Off	L1	19.7	18.8	46.0
3.158000	27.3	Off	L1	19.7	18.7	46.0
3.590000	27.9	Off	L1	19.7	18.1	46.0
3.774000	27.4	Off	L1	19.7	18.6	46.0
4.078000	26.9	Off	L1	19.7	19.1	46.0
4.358000	27.4	Off	L1	19.7	18.6	46.0
4.598000	28.2	Off	L1	19.7	17.8	46.0
4.878000	26.9	Off	L1	19.8	19.1	46.0
6.454000	33.2	Off	L1	19.7	16.8	50.0
6.926000	33.6	Off	L1	19.7	16.4	50.0
7.142000	32.3	Off	L1	19.8	17.7	50.0
7.414000	31.3	Off	L1	19.7	18.7	50.0
7.830000	34.3	Off	L1	19.7	15.7	50.0
8.198000	33.0	Off	L1	19.7	17.0	50.0
8.422000	32.2	Off	L1	19.7	17.8	50.0
8.782000	29.1	Off	L1	19.8	20.9	50.0




Test Mode :	Mode 1	Temperature :	20~21℃
Test Engineer :	Kai Chun Chu	Relative Humidity :	53~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	Bluetooth Link + WLAN (2.4GHz) Link + Camera + Earphone + USB Cable (Charging from Adapter)		

**Final Result : Quasi-Peak**


Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.198000	56.9	Off	N	19.7	6.8	63.7
0.262000	49.5	Off	N	19.7	11.9	61.4
0.326000	54.2	Off	N	19.7	5.4	59.6
0.406000	50.9	Off	N	19.7	6.8	57.7
0.454000	52.9	Off	N	19.6	3.9	56.8
0.534000	50.9	Off	N	19.7	5.1	56.0
0.614000	49.2	Off	N	19.6	6.8	56.0
0.686000	50.1	Off	N	19.6	5.9	56.0
0.718000	49.5	Off	N	19.6	6.5	56.0
0.830000	48.8	Off	N	19.6	7.2	56.0
0.886000	49.9	Off	N	19.7	6.1	56.0
0.958000	52.1	Off	N	19.7	3.9	56.0
1.022000	50.1	Off	N	19.7	5.9	56.0
1.094000	50.7	Off	N	19.6	5.3	56.0
1.166000	49.6	Off	N	19.7	6.4	56.0
1.230000	50.9	Off	N	19.6	5.1	56.0
1.278000	49.6	Off	N	19.6	6.4	56.0
1.334000	47.2	Off	N	19.6	8.8	56.0
1.406000	49.8	Off	N	19.6	6.2	56.0
1.486000	49.8	Off	N	19.7	6.2	56.0
1.638000	48.9	Off	N	19.7	7.1	56.0
1.726000	50.9	Off	N	19.7	5.1	56.0

Test Mode :	Mode 1	Temperature :	20~21℃
Test Engineer :	Kai Chun Chu	Relative Humidity :	53~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	Bluetooth Link + WLAN (2.4GHz) Link + Camera + Earphone + USB Cable (Charging from Adapter)		


Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
1.782000	49.9	Off	N	19.7	6.1	56.0
1.918000	50.6	Off	N	19.7	5.4	56.0
2.054000	51.0	Off	N	19.6	5.0	56.0
2.174000	49.2	Off	N	19.6	6.8	56.0
2.302000	50.4	Off	N	19.7	5.6	56.0
2.398000	49.3	Off	N	19.6	6.7	56.0
2.558000	49.1	Off	N	19.7	6.9	56.0
2.814000	49.8	Off	N	19.7	6.2	56.0
2.894000	48.3	Off	N	19.6	7.7	56.0
3.070000	48.0	Off	N	19.6	8.0	56.0
3.286000	47.8	Off	N	19.7	8.2	56.0
3.846000	47.0	Off	N	19.7	9.0	56.0
4.030000	45.9	Off	N	19.7	10.1	56.0
4.214000	45.2	Off	N	19.7	10.8	56.0
4.446000	45.3	Off	N	19.7	10.7	56.0
4.814000	43.4	Off	N	19.7	12.6	56.0
6.790000	41.6	Off	N	19.7	18.4	60.0
7.054000	46.5	Off	N	19.8	13.5	60.0
7.326000	47.1	Off	N	19.7	12.9	60.0
7.670000	45.4	Off	N	19.7	14.6	60.0
8.038000	45.8	Off	N	19.7	14.2	60.0
8.422000	42.9	Off	N	19.8	17.1	60.0


Test Mode :	Mode 1	Temperature :	20~21℃
Test Engineer :	Kai Chun Chu	Relative Humidity :	53~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	Bluetooth Link + WLAN (2.4GHz) Link + Camera + Earphone + USB Cable (Charging from Adapter)		


Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.198000	43.5	Off	N	19.7	10.2	53.7
0.262000	36.9	Off	N	19.7	14.5	51.4
0.326000	41.9	Off	N	19.7	7.7	49.6
0.406000	36.3	Off	N	19.7	11.4	47.7
0.454000	38.6	Off	N	19.6	8.2	46.8
0.534000	37.8	Off	N	19.7	8.2	46.0
0.614000	30.6	Off	N	19.6	15.4	46.0
0.686000	29.8	Off	N	19.6	16.2	46.0
0.718000	34.5	Off	N	19.6	11.5	46.0
0.830000	29.9	Off	N	19.6	16.1	46.0
0.886000	32.4	Off	N	19.7	13.6	46.0
0.958000	34.5	Off	N	19.7	11.5	46.0
1.022000	33.5	Off	N	19.7	12.5	46.0
1.094000	34.4	Off	N	19.6	11.6	46.0
1.166000	33.6	Off	N	19.7	12.4	46.0
1.230000	34.9	Off	N	19.6	11.1	46.0
1.278000	33.9	Off	N	19.6	12.1	46.0
1.334000	31.5	Off	N	19.6	14.5	46.0
1.406000	33.4	Off	N	19.6	12.6	46.0
1.486000	34.7	Off	N	19.7	11.3	46.0
1.638000	33.1	Off	N	19.7	12.9	46.0
1.726000	33.1	Off	N	19.7	12.9	46.0



Test Mode :	Mode 1	Temperature :	20~21℃
Test Engineer :	Kai Chun Chu	Relative Humidity :	53~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	Bluetooth Link + WLAN (2.4GHz) Link + Camera + Earphone + USB Cable (Charging from Adapter)		

**Final Result : Average**

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
1.782000	32.7	Off	N	19.7	13.3	46.0
1.918000	34.0	Off	N	19.7	12.0	46.0
2.054000	34.1	Off	N	19.6	11.9	46.0
2.174000	33.6	Off	N	19.6	12.4	46.0
2.302000	34.0	Off	N	19.7	12.0	46.0
2.398000	32.6	Off	N	19.6	13.4	46.0
2.558000	32.3	Off	N	19.7	13.7	46.0
2.814000	32.8	Off	N	19.7	13.2	46.0
2.894000	31.6	Off	N	19.6	14.4	46.0
3.070000	32.9	Off	N	19.6	13.1	46.0
3.286000	32.6	Off	N	19.7	13.4	46.0
3.846000	31.8	Off	N	19.7	14.2	46.0
4.030000	31.4	Off	N	19.7	14.6	46.0
4.214000	31.1	Off	N	19.7	14.9	46.0
4.446000	30.9	Off	N	19.7	15.1	46.0
4.814000	29.7	Off	N	19.7	16.3	46.0
6.790000	27.6	Off	N	19.7	22.4	50.0
7.054000	31.6	Off	N	19.8	18.4	50.0
7.326000	31.6	Off	N	19.7	18.4	50.0
7.670000	28.9	Off	N	19.7	21.1	50.0
8.038000	29.8	Off	N	19.7	20.2	50.0
8.422000	27.9	Off	N	19.8	22.1	50.0



3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.10.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	608-H1	34897199	N/A	May. 04, 2015	Nov. 26, 2015 ~ Dec. 08, 2015	May. 03, 2016	Conducted (TH02-HY)
Power Meter	Agilent	E4416A	GB41292344	300MHz~40GHz	Jan. 14, 2015	Nov. 26, 2015 ~ Dec. 08, 2015	Jan. 13, 2016	Conducted (TH02-HY)
Power Sensor	Agilent	E9327A	US40441548	300MHz~40GHz	Jan. 14, 2015	Nov. 26, 2015 ~ Dec. 08, 2015	Jan. 13, 2016	Conducted (TH02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 18, 2015	Nov. 26, 2015 ~ Dec. 08, 2015	Jun. 17, 2016	Conducted (TH02-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Sep. 02, 2015	Dec. 28, 2015~ Jan. 06, 2016	Sep. 01, 2016	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Nov. 20, 2015	Dec. 28, 2015~ Jan. 06, 2016	Nov. 19, 2016	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1326	1GHz ~ 18GHz	Oct. 08, 2015	Dec. 28, 2015~ Jan. 06, 2016	Oct. 07, 2016	Radiation (03CH11-HY)
Hygrometer	TECPEL	DTN-303B	TP140325	N/A	Nov. 17, 2015	Dec. 28, 2015~ Jan. 06, 2016	Nov. 16, 2016	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Nov. 19, 2015	Dec. 28, 2015~ Jan. 06, 2016	Nov. 18, 2016	Radiation (03CH11-HY)
Preamplifier	MITEQ	AMF-7D-00101800-30-10P	1902247	1GHz~18GHz	Jul. 01, 2015	Dec. 28, 2015~ Jan. 06, 2016	Jun. 30, 2016	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz ~ 44GHz	Sep. 24, 2015	Dec. 28, 2015~ Jan. 06, 2016	Sep. 23, 2016	Radiation (03CH11-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY53290053	20Hz to 26.5GHz	Feb. 02, 2015	Dec. 28, 2015~ Jan. 06, 2016	Feb. 01, 2016	Radiation (03CH11-HY)
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Dec. 28, 2015~ Jan. 06, 2016	N/A	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Dec. 28, 2015~ Jan. 06, 2016	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0-360 degree	N/A	Dec. 28, 2015~ Jan. 06, 2016	N/A	Radiation (03CH11-HY)
Bilog Antenna	Schaffner	CBL 6112B	2892	30MHz to 2GHz	Oct. 26, 2015	Dec. 28, 2015~ Jan. 06, 2016	Oct. 25, 2016	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170576	18GHz ~ 40GHz	Apr. 20, 2015	Dec. 28, 2015~ Jan. 06, 2016	Apr. 19, 2016	Radiation (03CH11-HY)
Preamplifier	MITEQ	JS44-18004000-33-8P	1840917	18GHz ~ 40GHz	Jun. 02, 2015	Dec. 28, 2015~ Jan. 06, 2016	Jun. 01, 2016	Radiation (03CH11-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Dec. 23, 2015	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 26, 2015	Dec. 23, 2015	Aug. 25, 2016	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Apr. 20, 2015	Dec. 23, 2015	Apr. 19, 2016	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 02, 2015	Dec. 23, 2015	Dec. 01, 2016	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 07, 2015	Dec. 23, 2015	Jan. 06, 2016	Conduction (CO05-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.26
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.90
---	------