



# **FCC RADIO TEST REPORT**

## **FCC ID:2ADOI-SP968**

**Product :** Eluma Lights Speaker

**Trade Name :** Brookstone

**Model Name :** SP968

**Serial Model :** N/A

**Report No. :** HCT16090022R

### **Prepared for**

SMARTV LTD

ROOM, 1207, 33 WANG YIP STREET WEST, YUEN LONG,NT, Hong Kong

### **Prepared by**

Shenzhen HCT Technology Co.,Ltd.

Room104,Number3,Lane14,Shangshatangyan Village, Futian District,  
Shenzhen, China



**Applicant's name** ..... : SMARTV LTD

Address ..... : ROOM, 1207, 33 WANG YIP STREET WEST, YUEN LONG, NT,  
Hong Kong

**Manufacture's Name** ..... : SHENZHEN SMARTV TECHNOLOGIES LTD

Address ..... : 4TH FLOOR, BLOCK A, NO.1 XINGUI ROAD, TONGSHENG,  
DALANG, LONGHUA DISTRICT, SHENZHEN, CHINA

**Product description**

Product name ..... : Eluma Lights Speaker

Model and/or type reference : SP968

Serial Model : N/A

**Standards** ..... : FCC Part15.247:2016

Test procedure ..... ANSI C63.10-2013

This device described above has been tested by HCT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of HCT, this document may be altered or revised by HCT, personal only, and shall be noted in the revision of the document.

**Date of Test** ..... :

Date (s) of performance of tests ..... : 01 Spet. 2016 ~08 Sept. 2016

Date of Issue ..... : 08 Sept. 2016

Test Result ..... : **Pass**

Testing Engineer : \_\_\_\_\_

*Gary Wu*

(Gary wu)

Authorized Signatory : \_\_\_\_\_

*Kevin Zou*

(Kevin Zou)

**Table of Contents**

	<b>Page</b>
<b>1 . SUMMARY OF TEST RESULTS</b>	<b>6</b>
1.1 TEST FACILITY	7
1.2 MEASUREMENT UNCERTAINTY	7
<b>2 . GENERAL INFORMATION</b>	<b>8</b>
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	10
2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	10
2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	12
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	13
<b>3 . EMC EMISSION TEST</b>	<b>14</b>
3.1 CONDUCTED EMISSION MEASUREMENT	14
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	14
3.1.2 TEST PROCEDURE	15
3.1.3 DEVIATION FROM TEST STANDARD	15
3.1.4 TEST SETUP	15
3.1.5 EUT OPERATING CONDITIONS	15
3.1.6 TEST RESULTS	16
3.2 RADIATED EMISSION MEASUREMENT	18
3.2.1 RADIATED EMISSION LIMITS	18
3.2.2 TEST PROCEDURE	19
3.2.3 DEVIATION FROM TEST STANDARD	19
3.2.4 TEST SETUP	20
3.2.5 EUT OPERATING CONDITIONS	21
3.2.6 TEST RESULTS (BELOW 30 MHZ)	22
3.2.7 TEST RESULTS (BETWEEN 30M – 1000 MHZ)	23
3.2.8 TEST RESULTS (1000-25000 MHZ)	25
<b>4 . NUMBER OF HOPPING CHANNEL</b>	<b>27</b>
4.1 APPLIED PROCEDURES / LIMIT	27
4.1.1 TEST PROCEDURE	27
4.1.2 DEVIATION FROM STANDARD	27
4.1.3 TEST SETUP	27
4.1.4 EUT OPERATION CONDITIONS	27
4.1.5 TEST RESULTS	28

**Table of Contents**

	<b>Page</b>
<b>5 . AVERAGE TIME OF OCCUPANCY</b>	<b>29</b>
5.1 APPLIED PROCEDURES / LIMIT	29
5.1.1 TEST PROCEDURE	29
5.1.2 DEVIATION FROM STANDARD	29
5.1.3 TEST SETUP	30
5.1.4 EUT OPERATION CONDITIONS	30
5.1.5 TEST RESULTS	31
<b>6 . HOPPING CHANNEL SEPARATION MEASUREMENT</b>	<b>37</b>
6.1 APPLIED PROCEDURES / LIMIT	37
6.1.1 TEST PROCEDURE	37
6.1.2 DEVIATION FROM STANDARD	37
6.1.3 TEST SETUP	37
6.1.4 EUT OPERATION CONDITIONS	37
6.1.5 TEST RESULTS	38
<b>7 . BANDWIDTH TEST</b>	<b>44</b>
7.1 APPLIED PROCEDURES / LIMIT	44
7.1.1 TEST PROCEDURE	44
7.1.2 DEVIATION FROM STANDARD	44
7.1.3 TEST SETUP	44
7.1.4 EUT OPERATION CONDITIONS	44
7.1.5 TEST RESULTS	45
<b>8 . PEAK OUTPUT POWER TEST</b>	<b>51</b>
8.1 APPLIED PROCEDURES / LIMIT	51
8.1.1 TEST PROCEDURE	51
8.1.2 DEVIATION FROM STANDARD	51
8.1.3 TEST SETUP	51
8.1.4 EUT OPERATION CONDITIONS	51
8.1.5 TEST RESULTS	52
<b>9 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE</b>	<b>59</b>
9.1 DEVIATION FROM STANDARD	59
9.2 TEST SETUP	60
9.3 EUT OPERATION CONDITIONS	60
9.4 TEST RESULTS	61
<b>10 . ANTENNA REQUIREMENT</b>	<b>68</b>
10.1 STANDARD REQUIREMENT	68
10.2 EUT ANTENNA	68



**Table of Contents**

**Page**

**11 . EUT TEST PHOTO**

**69**

**APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS**

## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247(a)(1)	Hopping Channel Separation	PASS	
15.247(b)(1)	Peak Output Power	PASS	
15.247(c)	Radiated Spurious Emission	PASS	
15.247(a)(iii)	Number of Hopping Frequency	PASS	
15.247(a)(iii)	Dwell Time	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

### 1.1 TEST FACILITY

Shenzhen ISOTek Standards Technical Services Co.,Ltd.

Add.: 13/F, HuaFengRui Building, XinHu Rd., XiXiang, Bao'an District,Shenzhen,China

FCC Registration No.: **918037**

### 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately **95 %** .

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Equipment	Eluma Lights Speaker	
Trade Name	Brookstone	
Model Name	SP968	
Serial Model	N/A	
Model Difference	N/A	
Product Description	BT	
	Operation Frequency:	2402~2480 MHz
	Modulation Type:	BT(1Mbps): GFSK BT EDR(2Mbps): $\pi/4$ -DQPSK BT EDR(3Mbps): 8-DPSK
	Bit Rate of Transmitter	1Mbps/2Mbps/3Mbps
	Number Of Channel	79 CH
	Antenna Designation:	Please see Note 3.
Channel List	Please refer to the Note 2.	
Adapter	N/A	
Battery	DC 3.7V	
Connecting I/O Port(s)	Please refer to the User's Manual	
Hardware version:	SP968B-B-VA	
Software version:	V1.0	
BT version	V3.0+EDR	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3.

Table for Filed Antenna

Ant .	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	PCB Antenna	N/A	1.0	BT Antenna

## 2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78
Mode 4	Normal link

For Conducted Emission	
Final Test Mode	Description
Mode 4	Normal link

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The EUT use fully-charged battery.
- (3)The data rate was set in 1Mbps for radiated emission due to the highest RF output power.


## 2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test software Version	Test program: V1.0		
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameters(1/2/3Mbps)	DEF	DEF	DEF

## 2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Conducted Emission Test



## 2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Eluma Lights Speaker	N/A	SP968	N/A	EUT
E-2	AC Adapter	N/A	G06U-05-150	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	120cm	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

## 2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

### Radiation & other conducted test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4446A	US44300451	2016.07.06	2017.07.05	1 year
2	EMI Test Receiver	R&S	ESCI	101165	2016.07.06	2017.07.05	1 year
3	Loop Antenna	ARA	PLA - 1030/B	1029	2016.07.06	2017.07.05	1 year
4	Bilog Antenna	Schwarzbeck	VULB 9168	VULB9168-438	2016.07.06	2017.07.05	1 year
5	Horn Antenna	Schwarzbeck	BBHA 9170	9170-182	2016.07.06	2017.07.05	1 year
6	Amplifier	Schwarzbeck	BBV9743	9743-019	2016.07.06	2017.07.05	1 year
7	Test Cable Below 1GHz	ATM	R-01	3564	2016.07.06	2017.07.05	1 year
8	Test Cable Above 1GHz	ATM	R-02	3565	2016.07.06	2017.07.05	1 year
9	Horn Antenna	Sunol Sciences	DRH-118	A052604	2016.07.06	2017.07.05	1 year

### Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	LISN	messtec	AN3019	NO.1	Jul. 06, 2016	Jul. 05, 2017	1 year
2	LISN	SCHWARZBECK	NNLK 8129	8126466	Jul. 06, 2016	Jul. 05, 2017	1 year
3	Pulse Limiter	SCHWARZBECK	VTSD9596F	9618	Jul. 06, 2016	Jul. 05, 2017	1 year
4	EMI Test Receiver	R&S	ESCI	100843	Jul. 06, 2016	Jul. 05, 2017	1 year
5	Switch	Schwarzbeck	CX - 210	100196	Jul. 06, 2016	Jul. 05, 2017	1 year
6	Test Cable 9KHz-300MHz	ATM	C01	3566	Jul. 06, 2016	Jul. 05, 2017	1 year

### Auxiliary equipment

1	AC Adapter	N/A	G06U-05-150	N/A	N/A	N/A	N/A
---	------------	-----	-------------	-----	-----	-----	-----

### Temporary antenna connector

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Temporary antenna connector	Pasternack	LC	N/A	Jul. 06, 2016	Jul. 05, 2017	1 year

Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


### 3.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

### 3.1.3 DEVIATION FROM TEST STANDARD

No deviation

### 3.1.4 TEST SETUP



**Note: 1.**Support units were connected to second LISN .

**2.**Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

### 3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


### 3.1.6 TEST RESULTS

EUT :	Eluma Lights Speaker	Model Name :	SP968
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode :	Mode 4

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1620	42.78	9.62	52.40	65.36	-12.96	QP
0.1620	28.74	9.62	38.36	55.36	-17.00	AVG
0.5299	29.01	9.77	38.78	56.00	-17.22	QP
0.5299	19.21	9.77	28.98	46.00	-17.02	AVG
3.0860	25.06	9.67	34.73	56.00	-21.27	QP
3.2659	11.48	9.68	21.16	46.00	-24.84	AVG
20.8340	28.05	9.96	38.01	50.00	-11.99	AVG
21.1700	38.92	9.96	48.88	60.00	-11.12	QP

Remark:

Factor = Insertion Loss + Cable Loss.






EUT :	Eluma Lights Speaker	Model Name :	SP968
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L1
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode :	Mode 4

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1580	42.29	9.60	51.89	65.56	-13.67	QP
0.1580	27.01	9.60	36.61	55.56	-18.95	AVG
0.2020	37.41	9.61	47.02	63.52	-16.50	QP
0.2260	22.61	9.61	32.22	52.59	-20.37	AVG
0.5700	30.15	9.67	39.82	56.00	-16.18	QP
0.5700	20.00	9.67	29.67	46.00	-16.33	AVG
18.8100	36.94	9.82	46.76	60.00	-13.24	QP
20.9260	26.83	9.85	36.68	50.00	-13.32	AVG

Remark:

Factor = Insertion Loss + Cable Loss.



## 3.2 RADIATED EMISSION MEASUREMENT

### 3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

#### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to RSS-Gen.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

### 3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:


Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Peak	1 MHz	10 Hz

### 3.2.3 DEVIATION FROM TEST STANDARD


No deviation

### 3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



### (C) Radiated Emission Test-Up Frequency Above 1GHz



### 3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

### 3.2.6 TEST RESULTS (BELOW 30 MHZ)

EUT :	Eluma Lights Speaker	Model Name :	SP968
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX	Polarization :	---

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	Pass
--	--	--	--	Pass

**NOTE:**

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =  $20 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.

Mode 1Mbps(low CH) is the worst mode.


### 3.2.7 TEST RESULTS (BETWEEN 30M – 1000 MHZ)

EUT :	Eluma Lights Speaker	Model Name :	SP968
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010hPa	Test Mode :	TX
Test Voltage :	DC 3.7V		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	55.6094	24.85	9.09	33.94	40.00	-6.06	QP
V	62.6507	28.55	7.24	35.79	40.00	-4.21	QP
V	153.2004	20.35	10.44	30.79	43.50	-12.71	QP
V	301.4223	23.05	14.21	37.26	46.00	-8.74	QP
V	463.9696	16.76	19.58	36.34	46.00	-9.66	QP
V	625.0779	17.46	22.91	40.37	46.00	-5.63	QP

#### Remark:


Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level – Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	250.3012	16.33	13.59	29.92	46.00	-16.08	QP
H	284.9767	15.99	13.98	29.97	46.00	-16.03	QP
H	299.3158	22.62	14.15	36.77	46.00	-9.23	QP
H	451.1350	11.76	19.33	31.09	46.00	-14.91	QP
H	704.2259	10.17	24.91	35.08	46.00	-10.92	QP
H	750.1083	11.81	26.10	37.91	46.00	-8.09	QP

**Remark:**

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level – Limit



Mode 1Mbps(low CH) is the worst mode.





### 3.2.8 TEST RESULTS (1000-25000 MHZ)

EUT :	Eluma Lights Speaker	Model Name :	SP968
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010hPa	Test Mode :	TX
Test Mode :	DC 3.7V		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark	Comment
Low Channel (2402 MHz)-Above 1G							
4804.203	59.38	-3.64	55.74	74.00	-18.26	Pk	Vertical
4804.203	41.61	-3.64	37.97	54.00	-16.03	AV	Vertical
7206.115	52.49	-0.95	51.54	74.00	-22.46	Pk	Vertical
7206.115	37.55	-0.95	36.60	54.00	-17.40	AV	Vertical
4804.211	59.72	-3.64	56.08	74.00	-17.92	Pk	Horizontal
4804.211	41.53	-3.64	37.89	54.00	-16.11	AV	Horizontal
7206.205	53.79	-0.95	52.84	74.00	-21.16	Pk	Horizontal
7206.205	37.48	-0.95	36.53	54.00	-17.47	AV	Horizontal
Mid Channel (2441 MHz)-Above 1G							
4882.285	60.14	-3.68	56.46	74.00	-17.54	Pk	Vertical
4882.285	40.55	-3.68	36.87	54.00	-17.13	AV	Vertical
7323.362	56.61	-0.82	55.79	74.00	-18.21	Pk	Vertical
7323.362	41.42	-0.82	40.60	54.00	-13.40	AV	Vertical
4882.148	59.14	-3.68	55.46	74.00	-18.54	Pk	Horizontal
4882.148	40.28	-3.68	36.60	54.00	-17.40	AV	Horizontal
7323.206	56.51	-0.82	55.69	74.00	-18.31	Pk	Horizontal
7323.206	40.69	-0.82	39.87	54.00	-14.13	AV	Horizontal
High Channel (2480 MHz)- Above 1G							
4960.362	59.51	-3.59	55.92	74.00	-18.08	Pk	Vertical
4960.362	42.35	-3.59	38.76	54.00	-15.24	AV	Vertical
7440.256	53.98	-0.68	53.30	74.00	-20.70	Pk	Vertical
7440.256	38.22	-0.68	37.54	54.00	-16.46	AV	Vertical
4960.113	58.34	-3.59	54.75	74.00	-19.25	Pk	Horizontal
4960.113	40.51	-3.59	36.92	54.00	-17.08	AV	Horizontal
7440.362	53.85	-0.68	53.17	74.00	-20.83	Pk	Horizontal
7440.362	37.71	-0.68	37.03	54.00	-16.97	AV	Horizontal

Note: Mode 1Mbps is the worst mode.

**Radiated band edge:**

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
1Mbps Non-hopping							
2390	55.46	-13.06	42.40	74.00	-31.60	peak	Vertical
2390	56.59	-13.06	43.53	74.00	-30.47	peak	Horizontal
2483.5	55.34	-12.78	42.56	74.00	-31.44	peak	Vertical
2483.5	57.65	-12.78	44.87	74.00	-29.13	peak	Horizontal
1Mbps hopping							
2390	56.49	-13.06	43.43	74.00	-30.57	peak	Vertical
2390	57.62	-13.06	44.56	74.00	-29.44	peak	Horizontal
2483.5	55.37	-12.78	42.59	74.00	-31.41	peak	Vertical
2483.5	57.68	-12.78	44.90	74.00	-29.10	peak	Horizontal
2Mbps Non-hopping							
2390	56.35	-13.06	43.29	74.00	-30.71	peak	Vertical
2390	54.68	-13.06	41.62	74.00	-32.38	peak	Horizontal
2483.5	57.21	-12.78	44.43	74.00	-29.57	peak	Vertical
2483.5	56.52	-12.78	43.74	74.00	-30.26	peak	Horizontal
2Mbps hopping							
2390	55.38	-13.06	42.32	74.00	-31.68	peak	Vertical
2390	56.71	-13.06	43.65	74.00	-30.35	peak	Horizontal
2483.5	57.24	-12.78	44.46	74.00	-29.54	peak	Vertical
2483.5	55.56	-12.78	42.78	74.00	-31.22	peak	Horizontal
3Mbps Non-hopping							
2390	56.78	-13.06	43.72	74.00	-30.28	peak	Vertical
2390	55.95	-13.06	42.89	74.00	-31.11	peak	Horizontal
2483.5	55.74	-12.78	42.96	74.00	-31.04	peak	Vertical
2483.5	56.62	-12.78	43.84	74.00	-30.16	peak	Horizontal
3Mbps hopping							
2390	55.81	-13.06	42.75	74.00	-31.25	peak	Vertical
2390	55.98	-13.06	42.92	74.00	-31.08	peak	Horizontal
2483.5	54.77	-12.78	41.99	74.00	-32.01	peak	Vertical
2483.5	57.67	-12.78	44.89	74.00	-29.11	peak	Horizontal

#### 4. NUMBER OF HOPPING CHANNEL

##### 4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Number of Hopping Channel	$\geq 15$	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	= the frequency band of operation
RB	$\geq 1\%$ of the span
VB	$VBW \geq RBW$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

##### 4.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

##### 4.1.2 DEVIATION FROM STANDARD

No deviation.

##### 4.1.3 TEST SETUP




##### 4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

#### 4.1.5 TEST RESULTS

EUT :	Eluma Lights Speaker	Model Name :	SP968
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	Hopping Mode-GFSK		

Number of Hopping Channel	79
---------------------------	----



## 5. AVERAGE TIME OF OCCUPANCY

### 5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS

#### 5.1.1 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyzer
- Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- Use a video trigger with the trigger level set to enable triggering only on full pulses.
- Sweep Time is more than once pulse time.
- Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- Measure the maximum time duration of one single pulse.
- Set the EUT for DH5, DH3 and DH1 packet transmitting.
- Measure the maximum time duration of one single pulse.
- A Period Time = (channel number)\*0.4  
 DH1 Time Slot: Reading \* (1600/2)\*31.6/(channel number)  
 DH3 Time Slot: Reading \* (1600/4)\*31.6/(channel number)  
 DH5 Time Slot: Reading \* (1600/6)\*31.6/(channel number)

#### 5.1.2 DEVIATION FROM STANDARD

No deviation.

### 5.1.3 TEST SETUP




### 5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


### 5.1.5 TEST RESULTS

EUT :	Eluma Lights Speaker	Model Name :	SP968
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH39-DH5 ,2DH5,3DH5		


Data Packet	Frequency	Pulse Duration	Dwell Time	Limits
		(ms)	(s)	(s)
DH5	2441 MHz	2.92	0.31	0.4
2DH5	2441 MHz	2.92	0.31	0.4
3DH5	2441 MHz	2.92	0.31	0.4



### CH39-2DH5



### CH39-3DH5









EUT :	Eluma Lights Speaker	Model Name :	SP968
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH39-DH3,2DH3,3DH3		


Data Packet	Frequency	Pulse Duration	Dwell Time	Limits
		(ms)	(s)	(s)
DH3	2441 MHz	1.67	0.27	0.4
2DH3	2441 MHz	1.68	0.27	0.4
3DH3	2441 MHz	1.68	0.27	0.4



### CH39-2DH3




### CH39-3DH3




EUT :	Eluma Lights Speaker	Model Name :	SP968
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH39-DH1,2DH1,3DH1		


Data Packet	Frequency	Pulse Duration	Dwell Time	Limits
		(ms)	(s)	(s)
DH1	2441 MHz	0.42	0.13	0.4
2DH1	2441 MHz	0.43	0.14	0.4
3DH1	2441 MHz	0.43	0.14	0.4



### CH39-2DH1



### CH39-3DH1



## 6. HOPPING CHANNEL SEPARATION MEASUREMENT

### 6.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz (Channel Separation)
VB	100 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


#### 6.1.1 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for channel separation measurement.

#### 6.1.2 DEVIATION FROM STANDARD

No deviation.

#### 6.1.3 TEST SETUP



#### 6.1.4 EUT OPERATION CONDITIONS


The EUT was programmed to be in continuously transmitting mode.



### 6.1.5 TEST RESULTS

EUT :	Eluma Lights Speaker	Model Name :	SP968
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /CH78 (1Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.000	Complies
2441 MHz	1.000	Complies
2480 MHz	1.000	Complies

Ch. Separation Limits: > 20dB bandwidth






EUT :	Eluma Lights Speaker	Model Name :	SP968
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /CH78 (2Mbps Mode)		


Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.004	Complies
2441 MHz	1.004	Complies
2480 MHz	1.004	Complies

Ch. Separation Limits: >2/3 of 20dB bandwidth






### CH39 -2Mbps




### CH78 -2Mbps




EUT :	Eluma Lights Speaker	Model Name :	SP968
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /CH78 (3Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.008	Complies
2441 MHz	1.000	Complies
2480 MHz	1.000	Complies


Ch. Separation Limits: >2/3 of 20dB bandwidth



### CH39 -3Mbps



### CH78 -3Mbps



## 7. BANDWIDTH TEST

### 7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)	Bandwidth	(20dB bandwidth)	2400-2483.5	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

#### 7.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 30KHz, VBW=100KHz, Sweep time = Auto.

#### 7.1.2 DEVIATION FROM STANDARD

No deviation.

#### 7.1.3 TEST SETUP




#### 7.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

### 7.1.5 TEST RESULTS

EUT :	Eluma Lights Speaker	Model Name :	SP968
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /C78(1Mbps)		


Frequency	20dB Bandwidth (kHz)	Result
2402 MHz	834.551	PASS
2441 MHz	835.739	PASS
2480 MHz	836.830	PASS





EUT :	Eluma Lights Speaker	Model Name :	SP968
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /C78(2Mbps)		

Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.132	<b>PASS</b>
2441 MHz	1.131	<b>PASS</b>
2480 MHz	1.130	<b>PASS</b>





### CH78 -2Mbps

**Agilent** L

---

**Ch Freq** 2.48 GHz **Trig** Free

Occupied Bandwidth [ ] [ ]

---

Ref 10 dBm #Atten 20 dB

#Peak  
Log  
10  
dB/



Center 2.480 000 GHz Span 3 MHz

#Res BW 30 kHz #VBW 100 kHz Sweep 3.2 ms (601 pts)

**Occupied Bandwidth** **Occ BW % Pwr** 99.00 %

1.0659 MHz **x dB** -20.00 dB

**Transmit Freq Error** -5.783 kHz

**x dB Bandwidth** 1.130 MHz

Copyright 2000-2004 Agilent Technologies

**Trace**

Trace  
1 2 3

---

Clear Write

---

Max Hold

---

Min Hold

---

View


---


Blank



EUT :	Eluma Lights Speaker	Model Name :	SP968
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /C78(3Mbps)		

Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.166	<b>PASS</b>
2441 MHz	1.161	<b>PASS</b>
2480 MHz	1.159	<b>PASS</b>





### CH78 -3Mbps

**Agilent** L

---

**Ch Freq** 2.48 GHz **Trig** Free

Occupied Bandwidth [ ] [ ]

---

Ref 10 dBm #Atten 20 dB

#Peak  
Log  
10  
dB/



Center 2.480 000 GHz Span 3 MHz

#Res BW 30 kHz #VBW 100 kHz Sweep 3.2 ms (601 pts)

**Occupied Bandwidth** **Occ BW % Pwr** 99.00 %

1.0889 MHz **x dB** -20.00 dB

**Transmit Freq Error** 1.052 kHz

**x dB Bandwidth** 1.159 MHz

Copyright 2000-2004 Agilent Technologies

**Trace**

Trace  
1 2 3

---

Clear Write

---

Max Hold

---

Min Hold

---

View

---

Blank

## 8. PEAK OUTPUT POWER TEST

### 8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (b)(i)	Peak Output Power	0.125 w or 20.96dBm	2400-2483.5	PASS

#### 8.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW > the 20 dB bandwidth of the emission being measured  
 Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel  
 VBW ≥ RBW  
 Sweep = auto  
 Detector function = peak  
 Trace = max hold

#### 8.1.2 DEVIATION FROM STANDARD

No deviation.

#### 8.1.3 TEST SETUP




#### 8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


**8.1.5 TEST RESULTS**

EUT :	Eluma Lights Speaker	Model Name :	SP968
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00/ CH39 /CH78 (1M/2M/3Mbps Mode)		


1Mbps			
Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)
CH00	2402	4.28	30
CH39	2441	4.43	30
CH78	2480	4.37	30
2Mbps			
CH00	2402	3.67	21
CH39	2441	3.86	21
CH78	2480	3.86	21
3Mbps			
CH00	2402	4.19	21
CH39	2441	4.40	21
CH78	2480	4.40	21




### CH39 -1Mbps




### CH78 -1Mbps







### CH39 -2Mbps





### CH78 -2Mbps









## **9. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE**

### **APPLICABLE STANDARD**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### **TEST PROCEDURE**

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

### **9.1 DEVIATION FROM STANDARD**

No deviation.

## 9.2 TEST SETUP



## 9.3 EUT OPERATION CONDITIONS



The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**9.4 TEST RESULTS**



EUT :	Eluma Lights Speaker	Model Name :	SP968
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00/ CH78 (1M/2M/3Mbps Mode)		



Frequency Band	Delta Peak to band emission (dBc)	> Limit (dBc)	Result
1Mbps Non-hopping			
2400	60.33	20	Pass
2483.5	69.01	20	Pass
2Mbps Non-hopping			
2400	56.75	20	Pass
2483.5	65.05	20	Pass
3Mbps Non-hopping			
2400	59.15	20	Pass
2483.5	62.82	20	Pass
1Mbps hopping			
2400	63.41	20	Pass
2483.5	68.01	20	Pass
2Mbps hopping			
2400	63.81	20	Pass
2483.5	67.85	20	Pass
3Mbps hopping			
2400	62.58	20	Pass
2483.5	65.96	20	Pass

## BDR mode (GFSK): Band Edge-Left Side





## BDR mode (GFSK): Band Edge-Right Side





EDR mode ( $\pi/4$ -DQPSK): Band Edge-Left Side






EDR mode ( $\pi/4$ -DQPSK): Band Edge- Right Side


## EDR mode(8DPSK): Band Edge-Left Side



### EDR mode(8DPSK): Band Edge-Right Side



NOTE: Hopping enabled and disabled have evaluated, and the worst data was reported


## **10. ANTENNA REQUIREMENT**

### **10.1 STANDARD REQUIREMENT**


15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### **10.2 EUT ANTENNA**

The EUT antenna is permanent attached antenna. It comply with the standard requirement.

**11. EUT TEST PHOTO****Radiated Measurement Photos**

### CONDUCTED EMISSION Photos



\*\*\*End of the report\*\*\*