



RADIO TEST REPORT

Report No: STS1504101F03

Issued for

Piu Mobile Corp

6030 Nw 99 Av Unit 405 Miami fl 33178 USA

| | |
|----------------|-----------------|
| Product Name: | Smart Phone |
| Brand Name: | N/A |
| Model No.: | Y210D |
| Series Model: | Y320 |
| FCC ID: | 2ADOOY210DY320 |
| Test Standard: | FCC Part 15.247 |

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented test sample.

Shenzhen STS Test Services Co., Ltd.
1/F, Building B, Zhuoke Science Park, No.190,Chongqing Road,
Fuyong Street, Bao'an District, Shenzhen, Guangdong,China
TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail:sts@stsapp.com





TEST RESULT CERTIFICATION

Applicant's name..... : Piu Mobile Corp
Address..... : 6030 Nw 99 Av Unit 405 Miami fl 33178 USA
Manufacture's Name : SHENZHEN M-HORSE TECHNOLOGY CO.,LTD
Address..... : Building B13 Yintian Industry Park,Xixiang Street,Baoan District,Shenzhen,China

Product description

Product name : Smart Phone
Model and/or type reference : Y210D
Serial Model..... : Y320

Standards..... : FCC Part15.247

Test procedure..... : ANSI C63.10-2013

This device described above has been tested by STS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document may be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test..... :

Date (s) of performance of tests..... : 12 May. 2015 ~18 May. 2015

Date of Issue : 19 May. 2015

Test Result : **Pass**

Testing Engineer :

(Jin Ming)

Technical Manager :

(Vita Li)

Authorized Signatory :

(Bovey Yang)





| Table of Contents | Page |
|---|-----------|
| 1. SUMMARY OF TEST RESULTS | 6 |
| 1.1 TEST FACILITY | 7 |
| 1.2 MEASUREMENT UNCERTAINTY | 7 |
| 2. GENERAL INFORMATION | 8 |
| 2.1 GENERAL DESCRIPTION OF EUT | 8 |
| 2.2 DESCRIPTION OF TEST MODES | 10 |
| 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TEST | 10 |
| 2.4 DESCRIPTION OF SUPPORT UNITS | 11 |
| 2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS | 12 |
| 3. EMC EMISSION TEST | 13 |
| 3.1 CONDUCTED EMISSION MEASUREMENT | 13 |
| 3.1.1 POWER LINE CONDUCTED EMISSION LIMITS | 13 |
| 3.1.2 TEST RESULT | 14 |
| 3.2 RADIATED EMISSION MEASUREMENT | 16 |
| 3.2.1 RADIATED EMISSION LIMITS | 16 |
| 3.2.2 TEST PROCEDURE | 17 |
| 3.2.3 TEST SETUP | 18 |
| 3.2.4 EUT OPERATING CONDITIONS | 19 |
| 3.2.5 TEST RESULT | 20 |
| 4. CONDUCTED SPURIOUS EMISSIONS | 25 |
| 4.1 APPLIED PROCEDURES / LIMIT | 25 |
| 4.2 TEST PROCEDURE | 25 |
| 4.3 DEVIATION FROM STANDARD | 25 |
| 4.4 TEST SETUP | 25 |
| 4.5 EUT OPERATION CONDITIONS | 25 |
| 4.6 TEST RESULTS | 26 |
| 5. POWER SPECTRAL DENSITY TEST | 32 |
| 5.1 APPLIED PROCEDURES / LIMIT | 32 |
| 5.2 TEST PROCEDURE | 32 |
| 5.3 DEVIATION FROM STANDARD | 32 |
| 5.4 TEST SETUP | 32 |
| 5.5 EUT OPERATION CONDITIONS | 32 |
| 5.6 TEST RESULTS | 33 |
| 6. BANDWIDTH TEST | 37 |



| Table of Contents | Page |
|---------------------------------|------|
| 6.1 APPLIED PROCEDURES / LIMIT | 37 |
| 6.2 TEST PROCEDURE | 37 |
| 6.3 DEVIATION FROM STANDARD | 37 |
| 6.4 TEST SETUP | 37 |
| 6.5 EUT OPERATION CONDITIONS | 37 |
| 6.6 TEST RESULTS | 38 |
| 7. PEAK OUTPUT POWER TEST | 42 |
| 7.1 APPLIED PROCEDURES / LIMIT | 42 |
| 7.2 TEST PROCEDURE | 42 |
| 7.3 DEVIATION FROM STANDARD | 42 |
| 7.4 TEST SETUP | 42 |
| 7.5 EUT OPERATION CONDITIONS | 42 |
| 7.6 TEST RESULTS | 43 |
| 8. ANTENNA REQUIREMENT | 44 |
| 8.1 STANDARD REQUIREMENT | 44 |
| 8.2 EUT ANTENNA | 44 |
| APPENDIX - PHOTOS OF TEST SETUP | 45 |

**Revision History**

| Rev. | Issue Date | Report NO. | Effect Page | Contents |
|------|--------------|---------------|-------------|---------------|
| 00 | 19 May. 2015 | STS1504101F03 | ALL | Initial Issue |
| | | | | |





1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

| FCC Part15 (15.247) , Subpart C | | | |
|---|-----------------------------|----------|--------|
| Standard Section | Test Item | Judgment | Remark |
| 15.207 | Conducted Emission | PASS | |
| 15.247 (a)(2) | 6dB Bandwidth | PASS | |
| 15.247 (b) (reference KDB 558074 d05 v02. /9.1.2) | Peak Output Power | PASS | |
| 15.247 (c) | Radiated Spurious Emission | PASS | |
| 15.247 (d) | Conducted Spurious Emission | PASS | |
| 15.247 (e) | Power Spectral Density | PASS | |
| 15.205 | Band Edge Emission | PASS | |
| 15.203 | Antenna Requirement | PASS | |

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report



1.1 TEST FACILITY

Shenzhen STS Test Services Co., Ltd.

Add. : 1/F, Building B, Zhuoke Science Park, No.190, Chongqing Road,
Fuyong Street, Bao'an District, Shenzhen, Guangdong, China

CNAS Registration No.: L7649;

FCC Registration No.: 842334; IC Registration No.: 12108A-1

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

| No. | Item | Uncertainty |
|-----|--|---------------------------|
| 1 | Conducted Emission (9KHz-150KHz) | $\pm 2.88\text{dB}$ |
| 2 | Conducted Emission (150KHz-30MHz) | $\pm 2.67\text{dB}$ |
| 3 | RF power, conducted | $\pm 0.70\text{dB}$ |
| 4 | Spurious emissions, conducted | $\pm 1.19\text{dB}$ |
| 5 | All emissions, radiated (<1G) 30MHz-200MHz | $\pm 2.83\text{dB}$ |
| 6 | All emissions, radiated (<1G) 200MHz-1000MHz | $\pm 2.94\text{dB}$ |
| 7 | All emissions, radiated (>1G) | $\pm 3.03\text{dB}$ |
| 8 | Temperature | $\pm 0.5^{\circ}\text{C}$ |
| 9 | Humidity | $\pm 2\%$ |



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

| | | |
|----------------------------|--|--|
| Equipment | Smart Phone | |
| Trade Name | N/A | |
| Model Name | Y210D | |
| Serial Model | Y320 | |
| Model Difference | They are different only for model name. | |
| Product Description | The EUT is a Smart Phone | |
| | Operation Frequency: | 802.11b/g: 2412~2462 MHz |
| | Modulation Type: | CCK/OFDM/DBPSK/DAPSK |
| | Bit Rate of Transmitter | 802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6Mbps |
| | Number Of Channel | 802.11b/g: 11CH |
| | Antenna Designation: | Please see Note 3. |
| | Antenna Gain (dBi) | 1 dbi |
| | | |
| Channel List | Please refer to the Note 2. | |
| Ratings | DC 3.7V from battery | |
| Adapter | Power supply and ADP (rating) : Input:100-240V AC,50/60Hz 200mA Output:5.0V,1000mA | |
| Battery | Rated Voltage: 3.7V capacity : 1500mA | |
| Hardware version number | G621-V1.0 | |
| Software versioning number | 6820-b-G621_JinHuiMa-B12B_150324_1_user_dibaialog_dt | |
| Connecting I/O Port(s) | Please refer to the User's Manual | |

Note:

- 1 For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2

| Channel List for 802.11b/g | | | | | | | |
|----------------------------|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 01 | 2412 | 04 | 2427 | 07 | 2442 | 10 | 2457 |
| 02 | 2417 | 05 | 2432 | 08 | 2447 | 11 | 2462 |
| 03 | 2422 | 06 | 2437 | 09 | 2452 | | |

3 Table for Filed Antenna

| Ant. | Brand | Model Name | Antenna Type | Connector | Gain (dBi) | NOTE |
|------|-------|------------|--------------|-----------|------------|------|
| A | N/A | N/A | PIFA Antenna | N/A | 1 | N/A |

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

| Pretest Mode | Description |
|--------------|---------------------|
| Mode 1 | Low |
| Mode 2 | Middle |
| Mode 3 | High |
| Mode 4 | Charging+ Link Mode |


| For Conducted Emission | |
|------------------------|---------------------|
| Final Test Mode | Description |
| Mode 4 | Charging+ Link Mode |

| For Radiated Emission | |
|-----------------------|---------------------|
| Final Test Mode | Description |
| Mode 1 | Low |
| Mode 2 | Middle |
| Mode 3 | High |
| Mode 4 | Charging+ Link Mode |

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TEST





2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment | Mfr/Brand | Model/Type No. | Series No. | Note |
|------|-------------|-----------|----------------|------------|------|
| E-1 | Smart Phone | N/A | Y210D | N/A | EUT |
| E-2 | Adapter | N/A | BJ-250 | N/A | EUT |
| E-3 | Earphone | N/A | N/A | N/A | EUT |
| | | | | | |
| | | | | | |
| | | | | | |

| Item | Shielded Type | Ferrite Core | Length | Note |
|------|---------------|--------------|---------|------|
| C-1 | unshielded | NO | 82.5cm | N/A |
| C-2 | unshielded | NO | 119.1cm | N/A |
| | | | | |
| | | | | |
| | | | | |

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

| Kind of Equipment | Manufacturer | Type No. | Serial No. | Last calibration | Calibrated until |
|---------------------|--------------|---------------------|---------------|------------------|------------------|
| Spectrum Analyzer | Agilent | E4407B | MY50140340 | 2014.10.25 | 2015.10.24 |
| Test Receiver | R&S | ESCI | 101427 | 2014.10.25 | 2015.10.24 |
| Bilog Antenna | TESEQ | CBL6111D | 34678 | 2014.11.25 | 2015.11.24 |
| Horn Antenna | Schwarzbeck | BBHA 9120D(1201) | 9120D-1343 | 2015.03.06 | 2016.03.05 |
| 50Ω Coaxial Switch | Anritsu | MP59B | 6200264416 | 2014.06.06 | 2015.06.05 |
| PreAmplifier | Agilent | 8449B | 60538 | 2014.10.25 | 2015.10.24 |
| Loop Antenna | ARA | PLA-1030/B | 1029 | 2014.06.08 | 2015.06.07 |
| USB RF power sensor | DARE | RPR3006W | 15I00041SNO03 | 2014.10.25 | 2015.10.24 |

Conduction Test equipment

| Kind of Equipment | Manufacturer | Type No. | Serial No. | Last calibration | Calibrated until |
|-------------------|--------------|----------|------------|------------------|------------------|
| EMI Test Receiver | R&S | ESPI | 102086 | 2014.11.20 | 2015.11.19 |
| LISN | R&S | ENV216 | 101242 | 2014.10.25 | 2015.10.24 |



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

Operating frequency band. In case the emission fall within the restricted band specified on Part 15.247&207(a) limit in the table below has to be followed.

| FREQUENCY (MHz) | Class B (dBuV) | | Standard |
|-----------------|----------------|-----------|----------|
| | Quasi-peak | Average | |
| 0.15 -0.5 | 66 - 56 * | 56 - 46 * | CISPR |
| 0.50 -5.0 | 56.00 | 46.00 | CISPR |
| 5.0 -30.0 | 60.00 | 50.00 | CISPR |

| | | | |
|-----------|-----------|-----------|-----|
| 0.15 -0.5 | 66 - 56 * | 56 - 46 * | FCC |
| 0.50 -5.0 | 56.00 | 46.00 | FCC |
| 5.0 -30.0 | 60.00 | 50.00 | FCC |

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver



3.1.2 TEST RESULT


| | | | |
|---------------|-----------------------------------|--------------------|--------|
| EUT: | Smart Phone | Model Name.: | Y210D |
| Temperature: | 26 °C | Relative Humidity: | 54% |
| Pressure: | 1010hPa | Phase: | L |
| Test Voltage: | DC 5V from Adapter AC120V/60Hz | Test Mode: | Mode 4 |

| Frequency (MHz) | Reading (dBuV) | Correct Factor(dB) | Result (dBuV) | Limit (dBuV) | Margin (dB) | Remark |
|--------------------|-------------------|-----------------------|------------------|-----------------|----------------|--------|
| | | | | | | |
| 0.2100 | 48.82 | 9.99 | 58.81 | 63.21 | -4.40 | QP |
| 0.2100 | 39.87 | 9.99 | 49.86 | 53.21 | -3.35 | AVG |
| 0.4220 | 42.36 | 10.13 | 52.49 | 57.41 | -4.92 | QP |
| 0.4220 | 33.96 | 10.13 | 44.09 | 47.41 | -3.32 | AVG |
| 0.8380 | 41.01 | 9.95 | 50.96 | 56.00 | -5.04 | QP |
| 0.8380 | 25.63 | 9.95 | 35.58 | 46.00 | -10.42 | AVG |
| 1.3340 | 42.46 | 9.93 | 52.39 | 56.00 | -3.61 | QP |
| 1.3340 | 26.31 | 9.93 | 36.24 | 46.00 | -9.76 | AVG |
| 2.4500 | 42.47 | 10.00 | 52.47 | 56.00 | -3.53 | QP |
| 2.4500 | 24.29 | 10.00 | 34.29 | 46.00 | -11.71 | AVG |
| 2.9500 | 42.28 | 10.00 | 52.28 | 56.00 | -3.72 | QP |
| 2.9500 | 25.81 | 10.00 | 35.81 | 46.00 | -10.19 | AVG |

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

100.0 dBuV






| | | | |
|---------------|-----------------------------------|--------------------|--------|
| EUT: | Smart Phone | Model Name.: | Y210D |
| Temperature: | 26 °C | Relative Humidity: | 54% |
| Pressure: | 1010hPa | Phase: | N |
| Test Voltage: | DC 5V from Adapter AC120V/60Hz | Test Mode: | Mode 4 |

| Frequency (MHz) | Reading (dBuV) | Correct Factor(dB) | Result (dBuV) | Limit (dBuV) | Margin (dB) | Remark |
|--------------------|-------------------|-----------------------|------------------|-----------------|----------------|--------|
| 0.2100 | 48.32 | 9.99 | 58.31 | 63.21 | -4.90 | QP |
| 0.2100 | 39.87 | 9.99 | 49.86 | 53.21 | -3.35 | AVG |
| 0.4900 | 41.58 | 9.93 | 51.51 | 56.17 | -4.66 | QP |
| 0.4900 | 32.08 | 9.93 | 42.01 | 46.17 | -4.16 | AVG |
| 1.2020 | 42.81 | 9.92 | 52.73 | 56.00 | -3.27 | QP |
| 1.2020 | 30.84 | 9.92 | 40.76 | 46.00 | -5.24 | AVG |
| 1.8980 | 42.77 | 9.99 | 52.76 | 56.00 | -3.24 | QP |
| 1.8980 | 27.73 | 9.99 | 37.72 | 46.00 | -8.28 | AVG |
| 3.4500 | 39.89 | 10.17 | 50.06 | 56.00 | -5.94 | QP |
| 3.4500 | 20.85 | 10.17 | 31.02 | 46.00 | -14.98 | AVG |
| 9.0260 | 40.66 | 10.33 | 50.99 | 60.00 | -9.01 | QP |
| 9.0260 | 20.86 | 10.33 | 31.19 | 50.00 | -18.81 | AVG |

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

100.0 dBuV





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS

6 dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on Part 15.247&205(a), then the Part 15.247&209(a) limit in the table below has to be followed.

| Frequencies (MHz) | Field Strength (micorvolts/meter) | Measurement Distance (meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009~0.490 | 2400/F(KHz) | 300 |
| 0.490~1.705 | 24000/F(KHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

| FREQUENCY (MHz) | Class B (dBuV/m) (at 3M) | |
|-----------------|--------------------------|---------|
| | PEAK | AVERAGE |
| Above 1000 | 74 | 54 |

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

| Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz) | Range (MHz) |
|---|--|
| Below 1.705 | 30 |
| 1.705 – 108 | 1000 |
| 108 – 500 | 2000 |
| 500 – 1000 | 5000 |
| Above 1000 | 5 th harmonic of the highest frequency or 40 GHz, whichever is lower |



| Spectrum Parameter | Setting |
|---------------------------------------|---|
| Attenuation | Auto |
| Detector | Peak |
| Start Frequency | 1000 MHz(Peak/AV) |
| Stop Frequency | 10 th carrier hamonic(Peak/AV) |
| RB / VB (emission in restricted band) | 1 MHz / 1 MHz, AV=1 MHz / 10Hz |

| Receiver Parameter | Setting |
|------------------------|----------------------------------|
| Attenuation | Auto |
| Start ~ Stop Frequency | 9kHz~150kHz / RB 200Hz for QP |
| Start ~ Stop Frequency | 150kHz~30MHz / RB 9kHz for QP |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB 120kHz for QP |

3.2.2 TEST PROCEDURE


- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters(above 1GHz is 1.5 m) above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m(above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



3.2.5 TEST RESULT

9KHz-30MHz

| | | | |
|--------------|-------------|--------------------|--------------------------------------|
| EUT: | Smart Phone | Model Name. : | Y210D |
| Temperature: | 20 °C | Relative Humidity: | 48% |
| Pressure: | 1010 hPa | Test Voltage : | DC 5V from Adapter with AC 120V/60Hz |
| Test Mode : | Link mode | Polarization : | -- |

| Freq. | Reading | Limit | Margin | State | Test Result |
|-------|----------|----------|--------|-------|-------------|
| (MHz) | (dBuV/m) | (dBuV/m) | (dB) | P/F | |
| -- | -- | -- | -- | -- | PASS |
| -- | -- | -- | -- | -- | PASS |

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.



30MHz - 1000MHz


| | | | |
|--------------|-------------|--------------------|--------------------------------------|
| EUT: | Smart Phone | Model Name. : | Y210D |
| Temperature: | 20 °C | Relative Humidity: | 48% |
| Pressure: | 1010 hPa | Test Voltage : | DC 5V from Adapter with AC 120V/60Hz |
| Test Mode : | Mode 4 | Polarization : | Horizontal |

| Frequency | Reading | Correct | Result | Limit | Margin | Remark |
|-----------|---------|--------------|----------|----------|--------|--------|
| (MHz) | (dBuV) | Factor(dB/m) | (dBuV/m) | (dBuV/m) | (dB) | |
| 30.4237 | 4.80 | 18.74 | 23.54 | 40.00 | -16.46 | QP |
| 66.7325 | 17.11 | 5.94 | 23.05 | 40.00 | -16.95 | QP |
| 138.8735 | 5.83 | 12.88 | 18.71 | 43.50 | -24.79 | QP |
| 300.3672 | 12.59 | 15.23 | 27.82 | 46.00 | -18.18 | QP |
| 400.4318 | 20.25 | 18.84 | 39.09 | 46.00 | -6.91 | QP |
| 801.7862 | 10.31 | 26.08 | 36.39 | 46.00 | -9.61 | QP |

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

80.0 dBuV/m





30MHz - 1000MHz


| | | | |
|--------------|-------------|--------------------|--------------------------------------|
| EUT: | Smart Phone | Model Name. : | Y210D |
| Temperature: | 20 °C | Relative Humidity: | 48% |
| Pressure: | 1010 hPa | Test Voltage : | DC 5V from Adapter with AC 120V/60Hz |
| Test Mode : | Mode 4 | Polarization : | Vertical |

| Frequency | Reading | Correct | Result | Limit | Margin | Remark |
|-----------|---------|--------------|----------|----------|--------|--------|
| (MHz) | (dBuV) | Factor(dB/m) | (dBuV/m) | (dBuV/m) | (dB) | |
| 31.5093 | 5.15 | 18.17 | 23.32 | 40.00 | -16.68 | QP |
| 65.1145 | 16.84 | 5.82 | 22.66 | 40.00 | -17.34 | QP |
| 167.8241 | 20.30 | 11.06 | 31.36 | 43.50 | -12.14 | QP |
| 250.3010 | 20.56 | 14.07 | 34.63 | 46.00 | -11.37 | QP |
| 400.4318 | 20.54 | 18.84 | 39.38 | 46.00 | -6.62 | QP |
| 962.1621 | 10.73 | 29.32 | 40.05 | 54.00 | -13.95 | QP |

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

80.0 dBuV/m





Above 1000MHz

| | | | |
|---------------|-------------|---------------------|--------------------------------------|
| EUT : | Smart Phone | Model Name : | Y210D |
| Temperature : | 20 °C | Relative Humidity : | 48% |
| Pressure : | 1010 hPa | Test Voltage : | DC 5V from Adapter with AC 120V/60Hz |

| Frequency (MHz) | Reading (dBuV) | Factor (dB) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Comment |
|---|----------------|-------------|-------------------------|----------------|-------------|----------|------------|
| Low Channel (802.11b/2412 MHz) | | | | | | | |
| 4824.20 | 65.57 | -3.58 | 61.99 | 74 | -12.01 | PK | Vertical |
| 4824.22 | 45.73 | -3.58 | 42.15 | 54 | -11.85 | AV | Vertical |
| 7236.13 | 60.96 | -0.8 | 60.16 | 74 | -13.84 | PK | Vertical |
| 7236.12 | 40.19 | -0.8 | 39.39 | 54 | -14.61 | AV | Vertical |
| 4824.19 | 61.43 | -3.58 | 57.85 | 74 | -16.15 | PK | Horizontal |
| 4824.22 | 42.92 | -3.58 | 39.34 | 54 | -14.66 | AV | Horizontal |
| Mid Channel (802.11b/2437 MHz) | | | | | | | |
| 4874.05 | 63.97 | -3.56 | 60.41 | 74 | -13.59 | PK | Vertical |
| 4874.02 | 48.04 | -3.56 | 44.48 | 54 | -9.52 | AV | Vertical |
| 7311.25 | 60.47 | -0.78 | 59.69 | 74 | -14.31 | PK | Vertical |
| 7311.27 | 44.05 | -0.78 | 43.27 | 54 | -10.73 | AV | Vertical |
| 4874.14 | 60.79 | -3.56 | 57.23 | 74 | -16.77 | PK | Horizontal |
| 4874.12 | 44.38 | -3.56 | 40.82 | 54 | -13.18 | AV | Horizontal |
| High Channel (802.11b/2462 MHz) | | | | | | | |
| 4944.23 | 60.13 | -3.54 | 56.59 | 74 | -17.41 | PK | Vertical |
| 4944.32 | 44.89 | -3.54 | 41.35 | 54 | -12.65 | AV | Vertical |
| 7416.31 | 60.58 | -0.75 | 59.83 | 74 | -14.17 | PK | Vertical |
| 7416.38 | 44.36 | -0.75 | 43.61 | 54 | -10.39 | AV | Vertical |
| 4944.25 | 60.79 | -3.54 | 57.25 | 74 | -16.75 | PK | Horizontal |
| 4944.35 | 44.12 | -3.54 | 40.58 | 54 | -13.42 | AV | Horizontal |
| Remark: | | | | | | | |
| 1. Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | | |
| 2. Scan with 802.11b, 802.11g, the worst case is 802.11b. | | | | | | | |



3.2.6 TEST RESULTS (Band edge)

| | | | |
|---------------|-------------|---------------------|---|
| EUT : | Smart Phone | Model Name : | Y210D |
| Temperature : | 20 °C | Relative Humidity : | 48% |
| Pressure : | 1010 hPa | Test Voltage : | DC 5V from Adapter with AC 120V/60Hz |

| Frequency (MHz) | Reading (dBuV) | Factor (dB) | Emission Level (dBμV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Comment |
|-----------------|----------------|-------------|-------------------------|----------------|-------------|----------|------------|
| 802.11 b | | | | | | | |
| 2399.9 | 68.26 | -12.99 | 55.27 | 74 | -18.73 | pk | Vertical |
| 2399.9 | 53.83 | -12.99 | 40.84 | 54 | -13.16 | AV | Vertical |
| 2399.9 | 68.92 | -12.99 | 55.93 | 74 | -18.07 | pk | Horizontal |
| 2399.9 | 53.04 | -12.99 | 40.05 | 54 | -13.95 | AV | Horizontal |
| 2483.6 | 69.66 | -12.78 | 56.88 | 74 | -17.12 | pk | Vertical |
| 2483.6 | 52.97 | -12.78 | 40.19 | 54 | -13.81 | AV | Vertical |
| 2483.6 | 69.92 | -12.78 | 57.14 | 74 | -16.86 | pk | Horizontal |
| 2483.6 | 53.06 | -12.78 | 40.28 | 54 | -13.72 | AV | Horizontal |
| 802.11 g | | | | | | | |
| 2399.9 | 67.72 | -12.99 | 54.73 | 74 | -19.27 | pk | Vertical |
| 2399.9 | 54.16 | -12.99 | 41.17 | 54 | -12.83 | AV | Vertical |
| 2399.9 | 68.73 | -12.99 | 55.74 | 74 | -18.26 | pk | Horizontal |
| 2399.9 | 52.78 | -12.99 | 39.79 | 54 | -14.21 | AV | Horizontal |
| 2483.6 | 69.83 | -12.78 | 57.05 | 74 | -16.95 | pk | Vertical |
| 2483.6 | 53.36 | -12.78 | 40.58 | 54 | -13.42 | AV | Vertical |
| 2483.6 | 69.87 | -12.78 | 57.09 | 74 | -16.91 | pk | Horizontal |
| 2483.6 | 53.05 | -12.78 | 40.27 | 54 | -13.73 | AV | Horizontal |

4. CONDUCTED SPURIOUS EMISSIONS

4.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

4.2 TEST PROCEDURE

| Spectrum Parameter | Setting |
|---------------------------------------|---------------------------------|
| Detector | Peak |
| Start/Stop Frequency | 30 MHz to 10th carrier harmonic |
| RB / VB (emission in restricted band) | 100 KHz/300 KHz |
| Trace-Mode: | Max hold |


For Band edge

| Spectrum Parameter | Setting |
|---------------------------------------|--|
| Detector | Peak |
| Start/Stop Frequency | Lower Band Edge: 2300 to 2430 MHz Upper Band Edge: 2450 to 2500 MHz |
| RB / VB (emission in restricted band) | 100 KHz/300 KHz |
| Trace-Mode: | Max hold |

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

4.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



4.6 TEST RESULTS


| | | | |
|---------------|-----------------------------|---------------------|---------|
| EUT : | Smart Phone | Model Name : | Y210D |
| Temperature : | 25 °C | Relative Humidity : | 60% |
| Pressure : | 1015 hPa | Test Voltage : | DC 3.7V |
| Test Mode : | TX b Mode /CH01, CH06, CH11 | | |

CH 01






CH 06




CH 11






Band edge

CH 01




CH 11






| | | | |
|---------------|-----------------------------|---------------------|---------|
| EUT : | Smart Phone | Model Name : | Y210D |
| Temperature : | 25 °C | Relative Humidity : | 60% |
| Pressure : | 1015 hPa | Test Voltage : | DC 3.7V |
| Test Mode : | TX g Mode /CH01, CH06, CH11 | | |

CH 01




CH06






CH 11






Band edge

CH 01



CH11





5. POWER SPECTRAL DENSITY TEST

5.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.247) , Subpart C | | | | |
|---------------------------------|------------------------|------------------------|-----------------------|--------|
| Section | Test Item | Limit | Frequency Range (MHz) | Result |
| 15.247 | Power Spectral Density | 8 dBm (in any 3KHz) | 2400-2483.5 | PASS |

5.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW ≥ 3 kHz.
4. Set the VBW $\geq 3 \times$ RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.




5.6 TEST RESULTS

| | | | |
|---------------|-----------------------------|---------------------|---------|
| EUT : | Smart Phone | Model Name : | Y210D |
| Temperature : | 25 °C | Relative Humidity : | 60% |
| Pressure : | 1015 hPa | Test Voltage : | DC 3.7V |
| Test Mode : | TX b Mode /CH01, CH06, CH11 | | |


| Frequency | Power Density (dBm) | Limit (dBm) | Result |
|-----------|---------------------|-------------|--------|
| 2412 MHz | -5.647 | 8 | PASS |
| 2437 MHz | -7.325 | 8 | PASS |
| 2462 MHz | -7.797 | 8 | PASS |

TX CH01






TX CH06



TX CH11






| | | | |
|---------------|-----------------------------|---------------------|---------|
| EUT : | Smart Phone | Model Name : | Y210D |
| Temperature : | 25 °C | Relative Humidity : | 60% |
| Pressure : | 1015 hPa | Test Voltage : | DC 3.7V |
| Test Mode : | TX g Mode /CH01, CH06, CH11 | | |


| Frequency | Power Density (dBm) | Limit (dBm) | Result |
|-----------|---------------------|-------------|--------|
| 2412 MHz | -11.68 | 8 | PASS |
| 2437 MHz | -8.83 | 8 | PASS |
| 2462 MHz | -10.26 | 8 | PASS |

TX CH01






TX CH06



TX CH11





6. BANDWIDTH TEST

6.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.247) , Subpart C | | | | |
|---------------------------------|-----------|---|-----------------------|--------|
| Section | Test Item | Limit | Frequency Range (MHz) | Result |
| 15.247(a)(2) | Bandwidth | $\geq 500\text{KHz}$ (6dB bandwidth) | 2400-2483.5 | PASS |

6.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



6.6 TEST RESULTS


| | | | |
|---------------|-----------------------------|---------------------|---------|
| EUT : | Smart Phone | Model Name : | Y210D |
| Temperature : | 25 °C | Relative Humidity : | 60% |
| Pressure : | 1012 hPa | Test Voltage : | DC 3.7V |
| Test Mode : | TX b Mode /CH01, CH06, CH11 | | |

| Frequency | 6dB Bandwidth (MHz) | Channel Separation (KHz) | Result |
|-----------|---------------------|--------------------------|--------|
| 2412 MHz | 10.0500 | >=500KHz | PASS |
| 2437 MHz | 10.0500 | >=500KHz | PASS |
| 2462 MHz | 10.0500 | >=500KHz | PASS |






TX CH 06



TX CH 11






| | | | |
|---------------|-----------------------------|---------------------|---------|
| EUT : | Smart Phone | Model Name : | Y210D |
| Temperature : | 25 °C | Relative Humidity : | 60% |
| Pressure : | 1012 hPa | Test Voltage : | DC 3.7V |
| Test Mode : | TX g Mode /CH01, CH06, CH11 | | |


| Frequency | 6dB Bandwidth (MHz) | Channel Separation (KHz) | Result |
|-----------|---------------------|--------------------------|--------|
| 2412 MHz | 15.9600 | >=500KHz | PASS |
| 2437 MHz | 15.9600 | >=500KHz | PASS |
| 2462 MHz | 15.9600 | >=500KHz | PASS |

TX CH 01






TX CH 06



TX CH 11





7. PEAK OUTPUT POWER TEST

7.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.247) , Subpart C | | | | |
|---------------------------------|-------------------|-----------------|-----------------------|--------|
| Section | Test Item | Limit | Frequency Range (MHz) | Result |
| 15.247(b)(3) | Peak Output Power | 1 watt or 30dBm | 2400-2483.5 | PASS |

7.2 TEST PROCEDURE

- The EUT was directly connected to the Power Sensor&Power meter

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



7.6 TEST RESULTS

| | | | |
|---------------|-------------------------------|---------------------|---------|
| EUT : | Smart Phone | Model Name : | Y210D |
| Temperature : | 25 °C | Relative Humidity : | 60% |
| Pressure : | 1012 hPa | Test Voltage : | DC 3.7V |
| Test Mode : | TX b/g Mode /CH01, CH06, CH11 | | |

| TX 802.11b Mode | | | |
|-----------------|-----------|-----------------------------|-------|
| Test Channe | Frequency | Peak Conducted Output Power | LIMIT |
| | (MHz) | (dBm) | dBm |
| CH01 | 2412 | 12.91 | 30 |
| CH06 | 2437 | 13.23 | 30 |
| CH11 | 2462 | 12.84 | 30 |

| TX 802.11g Mode | | | |
|-----------------|-----------|-----------------------------|-------|
| Test Channe | Frequency | Peak Conducted Output Power | LIMIT |
| | (MHz) | (dBm) | dBm |
| CH01 | 2412 | 9.25 | 30 |
| CH06 | 2437 | 9.90 | 30 |
| CH11 | 2462 | 9.89 | 30 |



8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2 EUT ANTENNA


The EUT antenna is permanent attach Antenna. It comply with the standard requirement.





APPENDIX - PHOTOS OF TEST SETUP

Radiated Measurement Photos



Conducted Measurement Photos



*****END OF THE REPORT*****