

RF Exposure evaluation

Product Description:BOX

Model Number: GHOST Aerial,GHOST Basic

FCC ID: 2ADPF-05224339

According to 447498 D01 General RF Exposure Guidance v05 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by: $[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where $f(\text{GHz})$ is the RF channel transmit frequency in GHz
Power and distance are rounded to the nearest mW and mm before calculation

According to the follow transmitter output power (P_t) formula :

$$P_t = (E \times d)^2 / (30 \times g_t)$$

P_t =transmitter output power in watts

g_t =numeric gain of the transmitting antenna (unitless)

E=electric field strength in V/m

d=measurement distance in meters (m)

According to the above test data,

$$E_{\text{max}} = 102.28 \text{ dBuV/m} = 0.13 \text{ V/m}, d = 3 \text{ m}, g_t = 0.68$$

$$P_t = (E \times d)^2 / (30 \times g_t) = (0.13 \times 3)^2 / (30 \times 0.68) = 0.0075 \text{ W} = 7.5 \text{ mW}$$

The result is rounded to one decimal place for comparison

Worse case is as below: [2402MHz -7.5mW output power]

$$(7.5 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.402(\text{GHz})}] = 2.32 < 3.0 \text{ for 1-g SAR}$$

Then SAR evaluation is not required

NOTE: For the maximum power, you can refer FCC test report.