

## 1 Maximum Permissible Exposure

### 1.1 Maximum Permissible Exposure

### 1.1.1 Limit of Maximum Permissible Exposure

Limits for Occupational / Controlled Exposure					
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time  E ², H ² or S (minutes)	
0.3-3.0	614	1.63	(100)*	6	
3.0-30	1,842 / f	4.89 / f	(900 / f <sup>2</sup> )*	6	
30-300	61.4	0.163	1.0	6	
300-1,500	-	-	F/300	6	
1,500-100,000	-	-	5	6	

#### **Limits for General Population / Uncontrolled Exposure**

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1,500	-	-	F/1500	30
1,500-100,000	-	-	1.0	30

Note 1: f = frequency in MHz; \*Plane-wave equivalent power density

Note 2: For the applicable limit, see FCC 1.1310

#### 1.1.2 MPE Calculation Method

$$E (V/m) = \frac{\sqrt{30 \times P \times G}}{d}$$

**E** = Electric field (V/m)

**G** = EUT Antenna numeric gain (numeric)

The formula can be changed to

$$\mathbf{Pd} = \frac{30 \times P \times G}{377 \times d^2}$$

Power Density: Pd (W/m<sup>2</sup>) = 
$$\frac{E^2}{377}$$

**P** = RF output power (W)

**d** = Separation distance between radiator and human body (m)

Report No.: FA4N2531

SPORTON INTERNATIONAL INC. Page No. : 1 of 2

TEL: 886-3-327-3456 Report Version : Rev. 01

FAX: 886-3-327-0973



## RF Exposure Report

# 1.1.3 Result of Maximum Permissible Exposure

RF General Information 2400 MHz – 2483.5 MHz					
Frequency Range (MHz)	IEEE Std. 802.11 Protocol	Ch. Frequency (MHz)	Channel Number	RF Output Power (dBm)	
2400-2483.5 LE-1Mbps 2402-2480 0-39 [40] -3.71					
Note 1: RF output power specifies that Maximum Conducted (Average) Output Power.					

Report No.: FA4N2531

Worst Maximum RF Output Power Result					
Exposure Environment	General Population / Uncontrolled Exposure				
Separation Distance (cm)	0.5				
Condition	RF Output Power (dBm)				
Modulation Mode	RF Output Power (dBm)	Gain (dBi)	EIRP Power	PD (S) (mW/cm²)	
LE-1Mbps	-3.71	3.77	0.06	0.32274	
Maximum Permissible Exposure Limit (mW/cm²)				1	
Note 1: N <sub>TX</sub> = Number of Trans	mit Chains				

SPORTON INTERNATIONAL INC. Page No. : 2 of 2
TEL: 886-3-327-3456 Report Version : Rev. 01

FAX: 886-3-327-0973