

FCC TEST REPORT
for
DotW, LLC

Bluetooth Module
Model No.: AB1126

Prepared for : DotW, LLC
Address : 8721 Santa Monica Blvd, Suite 1505 Los Angeles, CA, 90069,
United States

Prepared By : Shenzhen Anbotek Compliance Laboratory Limited
Address : 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road,
Nanshan District, Shenzhen, Guangdong, China
Tel: (86) 755-26066544
Fax: (86) 755-26014772

Report Number : R011411243E
Date of Test : Nov. 14~ 28, 2014
Date of Report : Dec. 05, 2014

TABLE OF CONTENTS

Description

Page

Test Report

1. GENERAL INFORMATION	5
1.1 Description of Device (EUT).....	5
1.2 Auxiliary Equipment Used during Test.....	6
1.3 Description of Test Facility	6
1.4 Measurement Uncertainty.....	6
2. TEST PROCEDURE	7
3. RADIATION INTERFERENCE	8
3.1 Requirements (15.247, 15.209):	8
3.2 Test Procedure	8
3.3 Test Configuration	9
3.4 Test Results.....	10
4. CHANNEL SEPARATION TEST	19
4.1 Measurement Procedure	19
4.2 Test SET-UP	19
4.3 Test Equipment.....	19
4.4 Test Results.....	20
5. 20DB BANDWIDTH TEST	24
5.1 Measurement Procedure	24
5.2 Test SET-UP	24
5.3 Test Equipment.....	24
5.4 Test Results.....	24
6. QUANTITY OF HOPPING CHANNEL TEST.....	28
6.1 Measurement Procedure	28
6.2 Test SET-UP	28
6.3 Test Equipment.....	28
6.4 Test Results.....	28
7. DWELL TIME TEST.....	30
7.1 Measurement Procedure	30
7.2 Test SET-UP	30
7.3 Test Equipment.....	30
7.4 Test Results.....	30
8. MAXIMUM PEAK OUTPUT POWER TEST	33
8.1 Measurement Procedure	33
8.2 Test SET-UP	33
8.3 Test Equipment.....	33
8.4 Test Results.....	34
9. BAND EDGE TEST.....	38
9.1 Measurement Procedure	38
9.2 Test SET-UP	38
9.3 Test Equipment.....	38

9.4 Test Results.....	38
10. ANTENNA APPLICATION.....	44
10.1 Antenna requirement	44
10.2 Result.....	44
11. PHOTOGRAPH.....	45
11.1 Photo of Radiation Emission Test	45
APPENDIX I (PRODUCT PHOTOS)	46

APPENDIX I (Product Photos) (2 Pages)

TEST REPORT

Applicant : DotW, LLC
Manufacturer : Shenzhen North Technology Co., Ltd.
EUT : Bluetooth Module
Model No. : AB1126
Serial No. : N.A.
Trade Mark : Groupie Stick
Rating : DC 5V, 100mAh

Measurement Procedure Used:

FCC Part15 Subpart C, Paragraph 15.207, 15.247 & 15.209

The device described above is tested by Shenzhen Anbotech Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotech Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without

written approval of Shenzhen Anbotech Compliance Laboratory Limited.

Date of Test : Nov. 14~ 28, 2014

Prepared by :

(Tested Engineer / Kebo Zhang)

Reviewer :

(Project Manager / Amy Ding)

Approved & Authorized Signer :

(Manager / Tom Chen)

1. GENERAL INFORMATION

1.1 Description of Device (EUT)

EUT : Bluetooth Module

Model Number : AB1126

Test Power Supply : DC 5V(With DC 3.7V Battery inside)

Frequency : 2402~2480MHz

Antenna Specification : PCB Antenna: 2.3dBi

Modulation : GFSK, $\pi/4$ DQPSK, 8DPSK

Applicant : DotW, LLC
Address : 8721 Santa Monica Blvd, Suite 1505 Los Angeles, CA, 90069, United States

Manufacturer : Shenzhen North Technology Co., Ltd.
Address : Floor 3, 8th Building, Lianchuang Technical Zone, Bulan Road, Longgang District, Shenzhen, 518114, China

Factory : Shenzhen North Technology Co., Ltd.
Address : Floor 3, 8th Building, Lianchuang Technical Zone, Bulan Road, Longgang District, Shenzhen, 518114, China

Date of receipt : Nov. 14, 2014

Date of Test : Nov. 14~ 28, 2014

1.2 Auxiliary Equipment Used during Test

Mobile Phone : Manufacturer: SAMSUNG
M/N: GT-I9268
CE , FCC, DOC

Host : Product Name: Groupie Stick
Model No.: C0001
Manufacturer: North

1.3 Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS - LAB Code: L3503

Shenzhen Anbotek Compliance Laboratory Limited., Laboratory has been assessed and in compliance with CNAS/CL01: 2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

FCC-Registration No.: 752021

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 752021, July 10, 2013.

IC-Registration No.: 8058A-1

Shenzhen Anbotek Compliance Laboratory Limited., EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration 8058A, February 22, 2013.

Test Location

All Emissions tests were performed at
Shenzhen Anbotek Compliance Laboratory Limited. at 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road, Nanshan District, Shenzhen, Guangdong, China

1.4 Measurement Uncertainty

Radiation Uncertainty : Ur = 4.3dB

Conduction Uncertainty : Uc = 3.4dB

2. Test Procedure

GENERAL: This report shall NOT be reproduced except in full without the written approval of Shenzhen Anbotek Compliance Laboratory Limited. The EUT was transmitting a test signal during the testing.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-2009 using a spectrum analyzer with a pre-selector. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz up to 1.0GHz and 1.0MHz with a video BW of 3.0MHz above 1.0GHz. The ambient temperature of the EUT was 74.3oF with a humidity of 69%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF = FS
20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

ANSI STANDARD C63.4-2009 10.1.7 MEASUREMENT PROCEDURES: The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The EUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

3. Radiation Interference

3.1 Requirements (15.247, 15.209):

3.1.1. Test Limits (< 30 MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meter)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

3.1.2. Test Limits (\geq 30 MHz)

FIELD STRENGTH of Fundamental: @3M	FIELD STRENGTH of Harmonics	S15.209 30 - 88 MHz	40 dBuV/m
902-928 MHz		88 - 216 MHz	43.5
2.4-2.4835 GHz		216 - 960 MHz	46
94 dBuV/m @3m	54 dBuV/m @3m	ABOVE 960 MHz	54dBuV/m

For range 9KHz~30MHz, The measured value is really too low to be recorded.

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in 15.209, whichever is the lesser attenuation.

3.2 Test Procedure

The EUT is placed on a turn table which is 0.8 meter high above the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber.

For 30MHz to 1000MHz:

Set the spectrum analyzer as:
RBW = 120kHz, VBW =120kHz,
Detector= Quasi-Peak
Trace mode= Max hold.
Sweep- auto couple.

For Above 1GHz (Peak Measurement):

Set the spectrum analyzer as:
RBW = 1MHz, VBW =3MHz,
Detector= Peak
Trace mode= Max hold.
Sweep- auto couple.

For Above 1GHz (Average Measurement):

Set the spectrum analyzer as:

RBW =1MHz, VBW =10Hz

Detector=Peak

Trace mode= Max hold.


Sweep- auto couple.

Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analysis	Agilent	E4407B	US39390582	Aug. 08, 2014	1 Year
2.	Preamplifier	Instruments corporation	EMC011830	980100	Aug. 08, 2014	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESPI	101604	Apr. 22, 2014	1 Year
4.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Apr. 04, 2014	1 Year
5.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Apr. 24, 2014	1 Year
6.	Pre-amplifier	SONOMA	310N	186860	Aug. 08, 2014	1 Year
7.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A


3.3 Test Configuration

3.3.1. Block diagram of connection between the EUT and simulators




The EUT is only a bluetooth module, so the module was tested in the host configuration during test.


3.3.2. 9k to 30MHz emissions:



3.3.3. 30M to 1G emissions:



3.3.4. 1G to 40G emissions:




3.4 Test Results

PASS.


Please refer the following pages.

Job No.:	011411243E	Polarization:	Horizontal
Standard:	(RE)FCC PART 15C _3m	Power Source:	DC 3.7V
Test item:	Radiation Test (30~1000MHz)	Temp.(C)/Hum.(%RH):	24.3(C)/55%RH
Test Mode:	On	Distance:	3m




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	35.3750	38.90	-13.99	24.91	40.00	-15.09	peak			
2	42.1542	33.05	-11.21	21.84	40.00	-18.16	peak			
3	58.2030	32.56	-15.23	17.33	40.00	-22.67	peak			
4	239.9874	34.81	-18.09	16.72	46.00	-29.28	peak			
5	263.8190	35.46	-18.84	16.62	46.00	-29.38	peak			
6	494.1984	32.58	-11.13	21.45	46.00	-24.55	peak			

Job No.:	011411243E	Polarization:	Vertical
Standard:	(RE)FCC PART 15C _3m	Power Source:	DC 3.7V
Test item:	Radiation Test (30~1000MHz)	Temp.(C)/Hum.(%RH):	24.3(C)/55%RH
Test Mode:	On	Distance:	3m




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	39.5757	36.02	-10.70	25.32	40.00	-14.68	peak			
2	66.4989	37.40	-18.12	19.28	40.00	-20.72	peak			
3	104.1701	33.08	-15.70	17.38	43.50	-26.12	peak			
4	133.1511	37.34	-18.02	19.32	43.50	-24.18	peak			
5	253.8367	34.84	-14.03	20.81	46.00	-25.19	peak			
6	447.9822	36.83	-11.57	25.26	46.00	-20.74	peak			

Job No.:	011411243E	Polarization:	Horizontal
Standard:	(RE)FCC PART 15C_Class B_3m	Power Source:	DC 3.7V
Test item:	Radiation Test (Above 1GHz)	Temp.(C)/Hum.(%RH):	24.3(C)/55%RH
Test Mode:	TX(2402 MHz)	Distance:	3m




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	4825.000	45.64	3.34	48.98	74.00	-25.02	peak			
2	4825.000	30.22	3.34	33.56	54.00	-20.44	AVG			

Job No.:	011411243E	Polarization:	Vertical
Standard:	(RE)FCC PART 15C_Class B_3m	Power Source:	DC 3.7V
Test item:	Radiation Test (Above 1GHz)	Temp.(C)/Hum.(%RH):	24.3(C)/55%RH
Test Mode:	TX(2402 MHz)	Distance:	3m




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	4825.000	40.50	3.34	43.84	74.00	-30.16	peak			
2	4825.000	25.11	3.34	28.45	54.00	-25.55	AVG			

Job No.:	011411243E	Polarization:	Horizontal
Standard:	(RE)FCC PART 15C_Class B_3m	Power Source:	DC 3.7V
Test item:	Radiation Test (Above 1GHz)	Temp.(C)/Hum.(%RH):	24.3(C)/55%RH
Test Mode:	TX(2441 MHz)	Distance:	3m




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	4867.500	49.41	3.41	52.82	74.00	-21.18	peak			
2	4867.500	33.83	3.41	37.24	54.00	-16.76	AVG			

Job No.:	011411243E	Polarization:	Vertical
Standard:	(RE)FCC PART 15C_Class B_3m	Power Source:	DC 3.7V
Test item:	Radiation Test (Above 1GHz)	Temp.(C)/Hum.(%RH):	24.3(C)/55%RH
Test Mode:	TX(2441 MHz)	Distance:	3m




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	3805.000	41.14	1.59	42.73	74.00	-31.27	peak			
2	3805.000	25.24	1.59	26.83	54.00	-27.17	AVG			

Job No.:	011411243E	Polarization:	Horizontal
Standard:	(RE)FCC PART 15C_Class B_3m	Power Source:	DC 3.7V
Test item:	Radiation Test (Above 1GHz)	Temp.(C)/Hum.(%RH):	24.3(C)/55%RH
Test Mode:	TX(2480 MHz)	Distance:	3m



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	4952.500	46.23	3.57	49.80	74.00	-24.20	peak			
2	4952.500	31.66	3.57	35.23	54.00	-18.77	AVG			

Job No.:	011411243E	Polarization:	Vertical
Standard:	(RE)FCC PART 15C_Class B_3m	Power Source:	DC 3.7V
Test item:	Radiation Test (Above 1GHz)	Temp.(C)/Hum.(%RH):	24.3(C)/55%RH
Test Mode:	TX(2480 MHz)	Distance:	3m



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	6355.000	38.94	7.46	46.40	74.00	-27.60	peak			
2	6355.000	24.39	7.46	31.85	54.00	-22.15	AVG			


4. CHANNEL SEPARATION TEST

4.1 Measurement Procedure

The EUT must have its hopping function enabled. Using the following spectrum analyzer settings:

1. Span= Wide enough to capture the peaks of two adjacent channels
2. Set the RBW = 30 kHz.
3. Set the VBW = 100 kHz.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

4.2 Test SET-UP



4.3 Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analysis	Agilent	E4407B	US39390582	Aug. 08, 2014	1 Year
2.	Preamplifier	Instruments corporation	EMC011830	980100	Aug. 08, 2014	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESPI	101604	Apr. 22, 2014	1 Year
4.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Apr. 04, 2014	1 Year
5.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Apr. 24, 2014	1 Year
6.	Pre-amplifier	SONOMA	310N	186860	Aug. 08, 2014	1 Year
7.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A

4.4 Test Results


Test Item : Frequency Separation Test Mode : CH Low ~ CH High
Test Voltage : DC 3.7V Temperature : 24°C
Test Result : PASS Humidity : 55%RH

Channel	Frequency (MHz)	Separation Read Value (kHz)	Limit (kHz)	Mode
Low	2401	1002	850	BDR
Mid	2441	1002	860	BDR
High	2480	1002	840	BDR
Low	2401	1002	806	EDR
Mid	2441	1002	806	EDR
High	2480	1002	806	EDR


Remark:

1. The limit of mode (EDR) is 2/3 of 20dB BW;


Mode: BDR



CH Mid




CH High





Mode: EDR

CH Low



CH Mid






5. 20DB BANDWIDTH TEST

5.1 Measurement Procedure

Using the following spectrum analyzer settings:

1. Span= approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel.
2. Set the RBW = 30 kHz.
3. Set the VBW = 100 kHz.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

5.2 Test SET-UP



5.3 Test Equipment

Same as the equipment listed in 4.3.


5.4 Test Results

Test Item	: 20dB BW	Test Mode	: CH Low ~ CH High
Test Voltage	: DC 3.7V	Temperature	: 24°C
Test Result	: PASS	Humidity	: 55%RH


Channel	Frequency (MHz)	20dB Down BW(kHz)	Mode
Low	2401	850	BDR
Mid	2441	860	BDR
High	2480	840	BDR
Low	2401	1210	EDR
Mid	2441	1210	EDR
High	2480	1210	EDR

Mode: BDR


CH Low



CH Middle



CH High




Center 2.48 GHz

500 kHz/

Span 5 MHz

Modulation Mode: EDR

CH Low




Center 2.402 GHz


500 kHz/

Span 5 MHz

CH Middle



CH High




6. QUANTITY OF HOPPING CHANNEL TEST

6.1 Measurement Procedure

The EUT must have its hopping function enabled. Using the following spectrum analyzer setting:

1. Span= the frequency band of operation
2. Set the RBW = 1 MHz.
3. Set the VBW = 1 MHz.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

6.2 Test SET-UP





6.3 Test Equipment

Same as the equipment listed in 4.3.

6.4 Test Results

Test Item	: Number of Hopping Frequency	Test Mode	: CH Low ~ CH High
Test Voltage	: DC 3.7V	Temperature	: 24°C
Test Result	: PASS	Humidity	: 55%RH

Hopping Channel Frequency Range	Quantity of Hopping Channel	Quantity of Hopping Channel
2402-2480	79	> 15




7. DWELL TIME TEST

7.1 Measurement Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span= zero span, centered on a hopping channel
2. Set the RBW = 1 MHz.
3. Set the VBW = 1 MHz.
4. Sweep time = as necessary to capture the entire dwell time per hopping channel.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

7.2 Test SET-UP





7.3 Test Equipment


Same as the equipment listed in 4.3.

7.4 Test Results

Test Item	: Time of Occupancy	Test Mode	: CH Low ~ CH High
Test Voltage	: DC 3.7V	Temperature	: 24°C
Test Result	: PASS	Humidity	: 55%RH

Package Type	Pulse width (ms)	Time slot length(ms)	Dwell time (ms)	Limit (s)
DH1	0.430	time slot length *1600/2 /79 * 31.6	137.60	0.4
DH3	1.730	time slot length *1600/4 /79 * 31.6	276.80	0.4
DH5	2.970	time slot length *1600/6 /79 * 31.6	316.80	0.4





8. MAXIMUM PEAK OUTPUT POWER TEST

8.1 Measurement Procedure

- Check the calibration of the measuring instrument(SA) using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- The center frequency of the spectrum analyzer is set to the fundamental frequency and using proper RBW and VBW setting.
- Measure the captured power within the band and recording the plot.
- Repeat above procedures until all frequencies required were complete.

Using the following spectrum analyzer settings:

- Span= approximately 5 times the 20dB bandwidth, centered on a hopping channel
- Set the RBW = 3 MHz.
- Set the VBW = 3 MHz.
- Sweep time = auto couple.
- Detector function = peak.
- Trace mode = max hold.
- Allow trace to fully stabilize.

8.2 Test SET-UP



8.3 Test Equipment

Same as the equipment listed in 4.3.


8.4 Test Results

Test Item	: Max. peak output power	Test Mode	: CH Low ~ CH High
Test Voltage	: DC 3.7V	Temperature	: 24°C
Test Result	: PASS	Humidity	: 55%RH


Channel Frequency (MHz)	Peak Power output(mW)	Peak Power output(dBm)	Peak Power Limit(mW)	Results	Mode
2402	1.25	0.98	1000	PASS	BDR
2441	1.34	1.27	1000	PASS	BDR
2480	1.45	1.62	1000	PASS	BDR
2402	0.86	-0.63	125	PASS	EDR
2441	0.93	-0.30	125	PASS	EDR
2480	1.02	0.07	125	PASS	EDR


Mode: BDR

CH Low






CH Mid





Mode: EDR






9. BAND EDGE TEST

9.1 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW= 1 MHz, VBW= 3 MHz.
4. Measurement the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Report above procedures until all measured frequencies were complete.

9.2 Test SET-UP



9.3 Test Equipment

Same as the equipment listed in 4.3.

9.4 Test Results



Pass.

Please refer the following data.



Test Item	: Band eadge	Test Mode	: CH Low ~ CH High
Test Voltage	: DC 3.7V	Temperature	: 24℃
Test Result	: PASS	Humidity	: 55%RH

For Hopping Mode:

Mode: BDR



Mode: EDR



Test Item : Band eadge	Test Mode : CH Low ~ CH High
Test Voltage : DC 3.7V	Temperature : 24℃
Test Result : PASS	Humidity : 55%RH

For Non-Hopping Mode:



1. Conducted Test

Frequency (MHz)	Peak Power Output(dBm)	Emission read Value(dBm)	Result of Band edge(dBc)	Band edge Limit(dBc)	Mode
<2400	1.05	-53.06	54.11	>20dBc	BDR
	-0.72	-53.36	52.64	>20dBc	EDR
>2483.5	1.61	-53.98	55.59	>20dBc	BDR
	-0.11	-53.51	53.40	>20dBc	EDR



2. Radiated emission Test

Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Mode
		PK	AV	PK	AV	
<2400	V	57.13	37.02	74.00	54.00	BDR
	V	53.09	38.21	74.00	54.00	EDR
>2483.5	V	54.45	37.84	74.00	54.00	BDR
	V	52.19	36.95	74.00	54.00	EDR

Mode: BDR



Mode: EDR



10. ANTENNA APPLICATION

10.1 Antenna requirement


The EUT'S antenna is met the requirement of FCC part 15C section 15.203 and 15.247.

FCC part 15C section 15.247 requirements:

Systems operating in the 2402-2480MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.



10.2 Result

The EUT's antenna used a chip antenna and integrated on PCB, The antenna's gain is 2.3dBi and meets the requirement.



11. PHOTOGRAPH

11.1 Photo of Radiation Emission Test



APPENDIX I (PRODUCT PHOTOS)

Figure 1
The EUT-Front View




Figure 2
The EUT-Back View




Figure 3
The EUT-Antenna View

