



# **TEST REPORT**

## **FCC PART 15 SUBPART C 15.247**

### **RSS-247 ISSUE 2**

**Test report**  
**On Behalf of**  
**Poly-Control ApS**  
**For**  
**Electronic door lock V3**

**Model No.: V3-BTZBE**  
**FCC ID: 2ADSH-V3BTZBE**  
**IC ID: 12588A-V3BTZBE**

**Prepared for :** **Poly-Control ApS**  
**Gammel Stillingvej 427C, DK-8462 Harlev J, Denmark**

**Prepared By :** **Shenzhen HUAKE Testing Technology Co., Ltd.**  
**1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street,**  
**Bao'an District, Shenzhen City, China**

**Date of Test:** **Nov. 16, 2018 ~ Nov. 22, 2018**

**Date of Report:** **Nov. 22, 2018**

**Report Number:** **HK1811301754E**

**TEST RESULT CERTIFICATION****Applicant's name** ..... Poly-Control ApS

Address ..... Gammel Stillingvej 427C, DK-8462 Harlev J, Denmark

**Manufacture's Name** ..... Poly-Control ApS

Address ..... Gammel Stillingvej 427C, DK-8462 Harlev J, Denmark

**Factory** ..... Xiamen CMM CO. , LTD.

Address ..... NO. 136 Xin Guang Road, Haicang District | Xiamen city, Fujian Province, P.R. China

**Product description**

Trade Mark: ..... danalock

Product name ..... Electronic door lock V3

Model and/or type reference ... V3-BTZBE

**Standards** ..... **47 CFR FCC Part 15 Subpart C 15.247**  
..... **RSS-247 issue 2**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAKE Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAKE Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Date of Test** .....

Date (s) of performance of tests ..... : Nov. 16, 2018 ~ Nov. 22, 2018

Date of Issue..... : Nov. 22, 2018

Test Result..... : **Pass**

Testing Engineer :

(Gary Qian)

Technical Manager :

(Eden Hu)

Authorized Signatory :

(Jason Zhou)



## TABLE OF CONTENTS

<b>1.SUMMARY .....</b>	<b>4</b>
1.1 TEST STANDARDS .....	4
1.2 TEST DESCRIPTION.....	4
1.3 TEST FACILITY .....	5
1.4 STATEMENT OF THE MEASUREMENT UNCERTAINTY .....	5
<b>2.GENERAL INFORMATION.....</b>	<b>6</b>
2.1 ENVIRONMENTAL CONDITIONS .....	6
2.2 GENERAL DESCRIPTION OF EUT.....	6
2.3 DESCRIPTION OF TEST MODES AND TEST FREQUENCY.....	6
2.4 DESCRIPTION OF TEST SETUP.....	7
2.5 RELATED SUBMITTAL(S) / GRANT (S).....	7
2.6 MODIFICATIONS .....	7
2.7 EQUIPMENT USED.....	8
<b>3. PEAK OUTPUT POWER.....</b>	<b>9</b>
3.1. MEASUREMENT PROCEDURE .....	9
3.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	9
3.3. LIMITS AND MEASUREMENT RESULT .....	10
<b>4. 6 DB BANDWIDTH.....</b>	<b>12</b>
4.1. MEASUREMENT PROCEDURE .....	12
4.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	12
4.3. LIMITS AND MEASUREMENT RESULTS .....	12
<b>5. CONDUCTED SPURIOUS EMISSION .....</b>	<b>14</b>
5.1. MEASUREMENT PROCEDURE .....	14
5.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	14
5.3. MEASUREMENT EQUIPMENT USED .....	14
5.4. LIMITS AND MEASUREMENT RESULT .....	14
<b>6. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY .....</b>	<b>19</b>
6.1 MEASUREMENT PROCEDURE .....	19
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	19
6.3 MEASUREMENT EQUIPMENT USED .....	19
6.4 LIMITS AND MEASUREMENT RESULT .....	19
<b>7. RADIATED EMISSION .....</b>	<b>21</b>
7.1. MEASUREMENT PROCEDURE .....	21
7.2. TEST SETUP.....	22
7.3. LIMITS AND MEASUREMENT RESULT .....	23
7.4. TEST RESULT.....	23
<b>APPENDIX A: PHOTOGRAPHS OF TEST SETUP.....</b>	<b>33</b>
<b>APPENDIX B: PHOTOGRAPHS OF EUT .....</b>	<b>34</b>



## 1.SUMMARY

### 1.1 TEST STANDARDS

The tests were performed according to following standards:

**FCC Rules Part 15.247:** Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

**RSS-247-Issue 2:** Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices.

**RSS-Gen Issue 5:** General Requirements for Compliance of Radio Apparatus

**ANSI C63.10:2013** : American National Standard for Testing Unlicensed Wireless Devices

### 1.2 TEST DESCRIPTION

<b>FCC PART 15.247 &amp; RSS 247</b>	<b>DESCRIPTION OF TEST</b>	<b>RESULT</b>
	Peak Output Power	Compliant
	6 dB Bandwidth	Compliant
	Conducted Spurious Emission and Band Edges	Compliant
	Maximum Conducted Output Power Density	Compliant
	Radiated Emission	Compliant
	Line Conduction Emission	NA



### 1.3 TEST FACILITY

#### 1.3.1 ADDRESS OF THE TEST LABORATORY

Shenzhen HUAKE Testing Technology Co., Ltd.

Add.:1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 32/EN 55032 requirements.

#### 1.3.2 LABORATORY ACCREDITATION

The test facility is recognized, certified, or accredited by the following organizations:

##### IC Registration No.: 21210

The 3m alternate test site of Shenzhen HUAKE Testing Technology Co., Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration No.: 21210 on May 24, 2016.

##### FCC Registration No.: CN1229

Test Firm Registration Number : 616276

### 1.4 STATEMENT OF THE MEASUREMENT UNCERTAINTY

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Shenzhen HUAKE Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for HUAKE laboratory is reported:

Test	Measurement Uncertainty	Notes
Transmitter power conducted	±0.57 dB	(1)
Transmitter power Radiated	±2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	±2.20 dB	(1)
Occupied Bandwidth	±0.01ppm	(1)
Radiated Emission 30~1000MHz	±4.10dB	(1)
Radiated Emission Above 1GHz	±4.32dB	(1)
Conducted Disturbance0.15~30MHz	±3.20dB	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



## 2. GENERAL INFORMATION

### 2.1 ENVIRONMENTAL CONDITIONS

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

### 2.2 GENERAL DESCRIPTION OF EUT

Product Name:	Electronic door lock V3
Model/Type reference:	V3-BTZBE
Power supply:	DC 12V by Battery
Version:	Supported BT4.2
Modulation:	GFSK(BLE)
Operation frequency:	2402MHz~2480MHz
Channel number:	40
Channel separation:	2MHz
Antenna type:	Chip Antenna
Antenna gain:	-0.5dBi
Hardware Version:	101-025_D1+101-029-E1
Software Version:	0.9.6

Note: For more details, refer to the user's manual of the EUT.

### 2.3 DESCRIPTION OF TEST MODES AND TEST FREQUENCY

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	0	2402MHZ
	1	2404MHZ
	:	:
	38	2478MHZ
	39	2480MHZ

NO.	TEST MODE DESCRIPTION
1	Low channel TX
2	Middle channel TX
3	High channel TX

Note:

1. Only the result of the worst case was recorded in the report, if no other cases.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.



## 2.4 DESCRIPTION OF TEST SETUP

Configure :



Item	Equipment	Model No.	ID or Specification	Remark
1	Electronic door lock V3	V3-BTZBE	FCC ID: 2ADSH-V3BTZBE IC ID: 12588A-V3BTZBE	EUT

## 2.5 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended to comply with Section 15.247 of the FCC Part 15, Subpart C Rules and RSS-247.

## 2.6 MODIFICATIONS

No modifications were implemented to meet testing criteria.

**2.7 EQUIPMENT USED**

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	R&S	ENV216	HKE-002	Dec. 28, 2017	1 Year
2.	Receiver	R&S	ESCI 7	HKE-010	Dec. 28, 2017	1 Year
3.	RF automatic control unit	Tonscend	JS0806-2	HKE-060	Dec. 28, 2017	1 Year
4.	Horn Antenna	Schwarzbeck	BBHA 9170	HKE-090	Dec. 28, 2017	1 Year
5.	Spectrum analyzer	Agilent	N9020A	HKE-048	Dec. 28, 2017	1 Year
6.	Preamplifier	Schwarzbeck	BBV 9743	HKE-006	Dec. 28, 2017	1 Year
7.	EMI Test Receiver	Rohde & Schwarz	ESCI 7	HKE-010	Dec. 28, 2017	1 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	HKE-012	Dec. 28, 2017	1 Year
9.	Loop Antenna	Schwarzbeck	FMZB 1519 B	HKE-014	Dec. 28, 2017	1 Year
10.	Horn Antenna	Schwarzbeck	9120D	HKE-013	Dec. 28, 2017	1 Year
11.	Pre-amplifier	EMCI	EMC051845 SE	HKE-015	Dec. 28, 2017	1 Year
12.	Pre-amplifier	Agilent	83051A	HKE-016	Dec. 28, 2017	1 Year
13.	EMI Test Software EZ-EMC	Tonscend	JS1120-B Version	HKE-083	Dec. 28, 2017	N/A
14.	Shielded room	Shiel Hong	4*3*3	HKE-039	Dec. 28, 2017	3 Year

The calibration interval was one year





### 3. PEAK OUTPUT POWER


#### 3.1. MEASUREMENT PROCEDURE

For peak power test:

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2.  $RBW \geq DTS \text{ bandwidth}$
3.  $VBW \geq 3 * RBW$ .
4.  $SPAN \geq VBW$ .
5. Sweep: Auto.
6. Detector function: Peak.
7. Trace: Max hold.

Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

#### 3.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) PEAK POWER TEST SETUP






### 3.3. LIMITS AND MEASUREMENT RESULT


PEAK OUTPUT POWER MEASUREMENT RESULT FOR GFSK MOUDULATION			
Frequency (GHz)	Peak Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.402	2.838	30	Pass
2.440	3.244	30	Pass
2.480	3.192	30	Pass

CH0






## CH19



## CH39





## 4. 6 DB BANDWIDTH

### 4.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 KHz, VBW  $\geq 3 \times$  RBW.
4. Set SPA Trace 1 Max hold, then View.

**Note:** The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

### 4.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.

### 4.3. LIMITS AND MEASUREMENT RESULTS


LIMITS AND MEASUREMENT RESULT			
Applicable Limits	Applicable Limits		
	Test Data (kHz)		Criteria
>500KHZ	Low Channel	569.0	PASS
	Middle Channel	553.4	PASS
	High Channel	561.8	PASS

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL





## TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



## TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL





## 5. CONDUCTED SPURIOUS EMISSION

### 5.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Trace 1 Max hold, then View.

**Note:** The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

### 5.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.

### 5.3. MEASUREMENT EQUIPMENT USED


The same as described in section 6.

### 5.4. LIMITS AND MEASUREMENT RESULT

LIMITS AND MEASUREMENT RESULT		
Applicable Limits	Measurement Result	
	Test Data	Criteria
In any 100 KHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power.	At least -20dBc than the reference level	PASS PASS




### TEST RESULT FOR ENTIRE FREQUENCY RANGE GFSK MODULATION IN LOW CHANNEL






## GFSK MODULATION IN MIDDLE CHANNEL








## GFSK MODULATION IN HIGH CHANNEL




Note: The peak emissions without marker on the above plots are fundamental wave and need not to compare with the limit.



### TEST RESULT FOR BAND EDGE GFSK MODULATION IN LOW CHANNEL



### GFSK MODULATION IN HIGH CHANNEL





## 6. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY

### 6.1 MEASUREMENT PROCEDURE

- (1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set SPA Trace 1 Max hold, then View.

Note: The method of PKPSD in the KDB 558074 item 10.2 was used in this testing.

### 6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

Refer To Section 7.2.

### 6.3 MEASUREMENT EQUIPMENT USED

Refer To Section 6.

### 6.4 LIMITS AND MEASUREMENT RESULT


Channel No.	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Result
Low Channel	-19.942	8	Pass
Middle Channel	-19.818	8	Pass
High Channel	-19.524	8	Pass

TEST PLOT OF SPECTRAL DENSITY FOR LOW CHANNEL





## TEST PLOT OF SPECTRAL DENSITY FOR MIDDLE CHANNEL



## TEST PLOT OF SPECTRAL DENSITY FOR HIGH CHANNEL






## 7. RADIATED EMISSION

### 7.1. MEASUREMENT PROCEDURE


1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.

## 7.2. TEST SETUP


### Radiated Emission Test-Setup Frequency Below 30MHz



### RADIATED EMISSION TEST SETUP 30MHz-1000MHz



### RADIATED EMISSION TEST SETUP ABOVE 1000MHz





### 7.3. LIMITS AND MEASUREMENT RESULT

15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested For restricted band radiated emission,  
the test records reported below are the worst result compared to other modes.


### 7.4. TEST RESULT

#### RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

**RADIATED EMISSION BELOW 1GHZ**

<b>EUT</b>	Electronic door lock V3	<b>Model Name</b>	V3-BTZBE
<b>Temperature</b>	25° C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 1	<b>Antenna</b>	Horizontal

**Suspected Data List**


NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	65.8900	20.51	12.54	40.00	19.49	100	200	Horizontal
2	142.5200	20.80	14.24	43.50	22.70	100	227	Horizontal
3	243.4000	20.08	13.96	46.00	25.92	200	2	Horizontal
4	372.4100	24.39	17.62	46.00	21.61	200	78	Horizontal
5	522.7600	27.72	21.36	46.00	18.28	200	359	Horizontal
6	685.7200	31.34	24.22	46.00	14.66	100	166	Horizontal

**RESULT: PASS**





EUT	Electronic door lock V3	Model Name	V3-BTZBE
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical



Suspected Data List								
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	36.7900	22.81	13.89	40.00	17.19	150	260	Vertical
2	65.8900	29.56	12.54	40.00	10.44	100	50	Vertical
3	119.2400	19.47	12.82	43.50	24.03	150	60	Vertical
4	159.0100	20.39	14.26	43.50	23.11	150	80	Vertical
5	268.6200	22.45	14.41	46.00	23.55	150	40	Vertical
6	351.0700	23.26	16.83	46.00	22.74	100	260	Vertical

**RESULT: PASS****Note:**

- Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.
- All test modes had been tested. The mode 1 is the worst case and recorded in the report.

## RADIATED EMISSION ABOVE 1GHZ

<b>EUT</b>	Electronic door lock V3	<b>Model Name</b>	V3-BTZBE
<b>Temperature</b>	25° C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 1	<b>Antenna</b>	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4804.011	46.82	7.12	53.94	74	-20.06	peak
4804.011	40.66	7.12	47.78	54	-6.22	AVG
7206.022	42.15	9.84	51.99	74	-22.01	peak
7206.022	36.83	9.84	46.67	54	-7.33	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

<b>EUT</b>	Electronic door lock V3	<b>Model Name</b>	V3-BTZBE
<b>Temperature</b>	25° C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 1	<b>Antenna</b>	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4804.011	45.41	7.12	52.53	74	-21.47	peak
4804.011	41.16	7.12	48.28	54	-5.72	AVG
7206.022	43.28	9.84	53.12	74	-20.88	peak
7206.022	37.86	9.84	47.7	54	-6.3	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

<b>EUT</b>	Electronic door lock V3	<b>Model Name</b>	V3-BTZBE
<b>Temperature</b>	25° C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 2	<b>Antenna</b>	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4880.005	45.86	7.12	52.98	74	-21.02	peak
4880.005	42.17	7.12	49.29	54	-4.71	AVG
7320.140	43.23	9.84	53.07	74	-20.93	peak
7320.140	37.29	9.84	47.13	54	-6.87	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

<b>EUT</b>	Electronic door lock V3	<b>Model Name</b>	V3-BTZBE
<b>Temperature</b>	25° C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 2	<b>Antenna</b>	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4880.050	45.16	7.12	52.28	74	-21.72	peak
4880.050	39.71	7.12	46.83	54	-7.17	AVG
7320.080	43.98	9.84	53.82	74	-20.18	peak
7320.080	36.77	9.84	46.61	54	-7.39	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.



<b>EUT</b>	Electronic door lock V3	<b>Model Name</b>	V3-BTZBE
<b>Temperature</b>	25° C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 3	<b>Antenna</b>	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4960.012	46.81	7.12	53.93	74	-20.07	peak
4960.012	41.76	7.12	48.88	54	-5.12	AVG
7440.027	43.64	9.84	53.48	74	-20.52	peak
7440.027	37.51	9.84	47.35	54	-6.65	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

<b>EUT</b>	Electronic door lock V3	<b>Model Name</b>	V3-BTZBE
<b>Temperature</b>	25° C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 3	<b>Antenna</b>	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4960.013	44.59	7.12	51.71	74	-22.29	peak
4960.013	40.24	7.12	47.36	54	-6.64	AVG
7440.027	42.32	9.84	52.16	74	-21.84	peak
7440.027	38.17	9.84	48.01	54	-5.99	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

**RESULT: PASS**

**Note:**

Other emissions from 1G to 25 GHz are considered as ambient noise. No recording in the test report.


Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

**TEST RESULT FOR RESTRICTED BANDS REQUIREMENTS**

EUT	Electronic door lock V3	Model Name	V3-BTZBE
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

PK




AV

**RESULT: PASS**



EUT	Electronic door lock V3	Model Name	V3-BTZBE
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical

PK



AV




RESULT: PASS



EUT	Electronic door lock V3	Model Name	V3-BTZBE
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

PK



AV




RESULT: PASS



EUT	Electronic door lock V3	Model Name	V3-BTZBE
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

PK



AV



## RESULT: PASS


**Note:** The factor had been edited in the “Input Correction” of the Spectrum Analyzer. So the Amplitude of test plots is equal to Reading level plus the Factor in dB. Use the A dB(μV) to represent the Amplitude. Use the F dB(μV/m) to represent the Field Strength. So A=F.





## APPENDIX A: PHOTOGRAPHS OF TEST SETUP

### RADIATED EMISSION TEST SETUP BELOW 1GHZ




### RADIATED EMISSION TEST SETUP ABOVE 1GHZ






## APPENDIX B: PHOTOGRAPHS OF EUT

TOP VIEW OF EUT




BOTTOM VIEW OF EUT








FRONT VIEW OF EUT




BACK VIEW OF EUT






LEFT VIEW OF EUT




RIGHT VIEW OF EUT









### OPEN VIEW OF EUT




### OPEN VIEW OF EUT-2



INTERNAL VIEW OF EUT-1




INTERNAL VIEW OF EUT-2






INTERNAL VIEW OF EUT-3




INTERNAL VIEW OF EUT-4





INTERNAL VIEW OF EUT-5




INTERNAL VIEW OF EUT-6







INTERNAL VIEW OF EUT-7



----END OF REPORT----