

Report No.: SHEM191001777604

Page: 1 of 8

1 Cover Page

Factory:

RF MPE REPORT

Application No.: SHEM1910017776CR **FCC ID**: 2ADTD-D6022TL-B

Applicant: Hangzhou Hikvision Digital Technology Co., Ltd.

Address of Applicant: No. 555 Qianmo Road, Binjiang District, Hangzhou 310052, China

Manufacturer: Hangzhou Hikvision Digital Technology Co., Ltd.

Address of Manufacturer: No. 555 Qianmo Road, Binjiang District, Hangzhou 310052, China

1.Hangzhou Hikvision Technology Co., Ltd.2.Hangzhou Hikvision Electronics Co., Ltd.

3.Hangzhou Hikvision Digital Technology Co., Ltd

1. No.700, Dongliu Road, Binjiang District, Hangzhou City, Zhejiang,

310052, China

Address of Factory:

2. No.299, Qiushi Road, Tonglu Economic Development Zone, Tonglu

County, Hangzhou, Zhejiang, 310052, China

3. No. 555, Qianmo Road, Binjiang District, Hangzhou City, Zhejiang

Province, China

Equipment Under Test (EUT):

EUT Name: Digital Signage **Model No.:** DS-D6022TL-B

Add Model No.: DS-D6022FL-B, DS-D6022FN-B

Trade mark: HIKVISION

FCC Rules 47 CFR §2.1091

Standard(s): KDB447498 D01 General RF Exposure Guidance v06

Date of Receipt: 2019-10-10

Date of Test: 2019-10-11 to 2019-10-18

Date of Issue: 2019-10-22

Test Result: Pass*

Parlam Zhan E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

Driovals in writing.

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: Co.Doccheck@osc.com

NO.588 West Jindu Road,Songjiang District,Shanghai,China 201612 中国・上海・松江区金都西路588号 邮编: 201612 t(86-21) 61915666 f(86-21) 61915678 www.sgsgroup.com.cn t(86-21) 61915666 f(86-21) 61915678 e sgs.china@sgs.com

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SHEM191001777604

Page: 2 of 8

Revision Record				
Version	Description	Date	Remark	
00	Original	2019-10-23	/	

Authorized for issue by:		
	Vincent Zhu	
	Vincent Zhu / Project Engineer	
	Parlam Zhan	
	Parlam Zhan / Reviewer	



Report No.: SHEM191001777604

Page: 3 of 8

2 Contents

	Pa	jе
1 COVI	ER PAGE	 1
2 CON	TENTS	. 3
3 GENI	ERAL INFORMATION	4
3.1	GENERAL DESCRIPTION OF E.U.T.	4
3.2	TECHNICAL SPECIFICATIONS	4
3.3	TEST LOCATION	5
3.4	TEST FACILITY	5
4 TEST	「STANDARDS AND LIMITS	6
4.1	FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:	(
5 MEAS	SUREMENT AND CALCULATION	6
5.1	MAXIMUM TRANSMIT POWER	(
5.2	MPE CALCULATION	8



Report No.: SHEM191001777604

Page: 4 of 8

3 General Information

3.1 General Description of E.U.T.

Power supply:	AC 100-240V~50/60Hz
Test voltage:	AC 120V 60Hz
Cable:	AC Cable 1.5m

3.2 Technical Specifications

<u> </u>	
Antenna Gain	2.2 dBi
Antenna Type	PCB Antenna
Channel Spacing	1MHz
Modulation Type	GFSK, π/4DQPSK, 8DPSK
Number of Channels	79
Operation Frequency	2402MHz to 2480MHz
Spectrum Spread	Frequency Hopping Spread Spectrum(FHSS)
Technology	

BLE

Antenna Gain	2.2 dBi
Antenna Type	PCB Antenna
Channel Spacing	2MHz
Modulation Type	GFSK
Number of Channels	40
Operation Frequency	2402MHz to 2480MHz

2.4G WiFi

Antenna Gain	2.2 dBi	
Antenna Type	PCB Antenna	
Channel Spacing	5MHz	
Mad Jagas Torr	802.11b: DSSS (CCK, DQPSK, DBPSK)	
Modulation Type	802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)	
N. ark are f Okasarak	802.11b/g/n(HT20):11	
Number of Channels	802.11n(HT40):7	
Occupation Frances	802.11b/g/n(HT20): 2412MHz to 2462MHz	
Operation Frequency	802.11n(HT40): 2422MHz to 2452MHz	



Report No.: SHEM191001777604

Page: 5 of 8

3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shanghai Branch 588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

No tests were sub-contracted.

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L0599)

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• NVLAP (Certificate No. 201034-0)

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program(NVLAP). Certificate No. 201034-0.

• FCC -Designation Number: CN5033

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

Designation Number: CN5033. Test Firm Registration Number: 479755.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

IC Registration No.: 8617A-1. CAB Identifier: CN0020.

VCCI (Member No.: 3061)

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.



Report No.: SHEM191001777604

Page: 6 of 8

4 Test Standards and Limits

4.1 FCC Radiofrequency radiation exposure limits:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency	Power density(mW/cm²)	Averaging time(minutes)
300MHz~1.5GHz	f/1500	30
1.5GHz~100GHz	1.0	30

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM191001777601 & SHEM191001777602 & SHEM191001777603.

BT

Test Mode	Test Frequency (MHz)	Output Power (dBm)	Reading Power (mW)
	2402	1.89	1.55
GFSK	2441	2.18	1.65
	2480	1.93	1.56
	2402	3.15	2.07
π/4DQPSK	2441	3.31	2.14
	2480	3.26	2.12
	2402	3.38	2.18
8DPSK	2441	3.61	2.30
	2480	3.56	2.27

BLE

Test Mode	Test Frequency (MHz)	Output Power (dBm)	Reading Power (mW)
	2402	1.95	1.57
BLE	2442	2.18	1.65
	2480	2.02	1.59



Report No.: SHEM191001777604

Page: 7 of 8

2.4G WiFi

Test Mode	Test Channel	Power [dBm]	Power [mW]
11B	2412	14.54	28.44
11B	2437	15.12	32.51
11B	2462	15.29	33.81
11G	2412	13.89	24.49
11G	2437	14.37	27.35
11G	2462	14.59	28.77
11N20SISO	2412	13.80	23.99
11N20SISO	2437	14.18	26.18
11N20SISO	2462	14.74	29.79
11N40SISO	2422	12.67	18.49
11N40SISO	2437	13.15	20.65
11N40SISO	2452	13.31	21.43



Report No.: SHEM191001777604

Page: 8 of 8

5.2 MPE Calculation

For FCC:

According to the formula $S=P/4\pi R^2$, we can calculate S which is MPE.

Note:

- 1) P (mW)
- 2) R = distance to the center of radiation of antenna (in meter) = 20cm
- 3) MPE limit = 1mW/cm²

For BT

The max. antenna gain is 2.2 dBi Max. Gain in Linear Power Operation Limit Conducted Density Scale Distance Result Power (mW/cm²) G R(cm) (mW/cm²) P(mW) 20 2.3 1.660 0.00076 Pass

For 2.4G WiFi

The max. a	ntenna gain is	2.2	aBı	

Max. Conducted Power P(mW)	Gain in Linear Scale G	Operation Distance R(cm)	Power Density (mW/cm ²)	Limit (mW/cm²)	Result
33.81	1.660	20	0.01116	1	Pass

The BT and the DTS modules can simultaneous transmitting at frequency 2.4GHz band.But the maximum rate of MPE is 0.00076/1.0+0.01116/1.0 =0.012<=1.0. according to the KDB447498 section 7.2 determine the device is exclusion from SAR test.

-- End of the Report--