



TESTING LABORATORY  
CERTIFICATE#4323.01



## FCC PART 15.231

### TEST REPORT

For

**Hangzhou Hikvision Digital Technology Co., Ltd.**

No. 555 Qianmo Road, Binjiang District, Hangzhou 310052, China

**FCC ID: 2ADTD-D0101002**

<b>Report Type:</b> Original Report	<b>Product Type:</b> Wireless PIR Detector
<b>Test Engineer:</b> Alisa Gao	Alisa. Gao
<b>Report Number:</b> RKSA180410004-00A	
<b>Report Date:</b> 2018-05-16	
<b>Reviewed By:</b> Oscar Ye RF Leader	Oscar. Ye
<b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>	

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>3</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	3
OBJECTIVE .....	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY .....	3
MEASUREMENT UNCERTAINTY .....	4
TEST FACILITY .....	4
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>5</b>
JUSTIFICATION .....	5
EUT EXERCISE SOFTWARE .....	5
EQUIPMENT MODIFICATIONS .....	5
SUPPORT EQUIPMENT LIST AND DETAILS .....	5
EXTERNAL I/O CABLE.....	5
BLOCK DIAGRAM OF TEST SETUP .....	6
<b>SUMMARY OF TEST RESULTS .....</b>	<b>7</b>
<b>TEST EQUIPMENT LIST .....</b>	<b>8</b>
<b>FCC§15.203 - ANTENNA REQUIREMENT.....</b>	<b>9</b>
APPLICABLE STANDARD .....	9
ANTENNA CONNECTED CONSTRUCTION .....	9
<b>FCC §15.205, §15.209, §15.231 (B) - RADIATED EMISSIONS .....</b>	<b>10</b>
APPLICABLE STANDARD .....	10
EUT SETUP .....	11
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE .....	12
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	12
TEST RESULTS SUMMARY .....	12
TEST DATA .....	12
<b>FCC §15.231(A) (2) - DEACTIVATION TESTING.....</b>	<b>18</b>
APPLICABLE STANDARD .....	18
TEST PROCEDURE .....	18
TEST DATA .....	18
<b>FCC §15.231(C) - 20DB EMISSION BANDWIDTH TESTING.....</b>	<b>20</b>
APPLICABLE STANDARD .....	20
TEST PROCEDURE .....	20
TEST DATA .....	20

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

Applicant	Hangzhou Hikvision Digital Technology Co., Ltd.
Tested Model	DS-PD2-P10P-W
Series Model	DS-RD2-P10P-W; DS-QD2-P10P-W; DS-1T2-P10P-W; DS-PD2-P15C-W; DS-RD2-P15C-W; DS-QD2-P15C-W; DS-1T2-P15C-W; DS-PD2-P25-W; DS-RD2-P25-W; DS-QD2-P25-W; DS-1T2-P25-W
Product Type	Wireless PIR Detector
Dimension	117 mm(L)*69 mm(W)*50mm(H)
Power Supply	DC 3.0V from Lithium battery

*\* Note: The difference between tested model and series model was explained in the declaration letter.*

*\*All measurement and test data in this report was gathered from production sample serial number: 20180410004 (Assigned by the BACL. The EUT supplied by the applicant was received on 2018-04-10)*

### Objective

This test report is prepared on behalf of *Hangzhou Hikvision Digital Technology Co., Ltd.* All the test measurements were performed according to the measurement procedure described in ANSI C63.10 - 2013.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.209, 15.35(c) and 15.231 rules.

### Related Submittal(s)/Grant(s)

No Related Submittal(s)/Grant(s).

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10 - 2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

**Measurement Uncertainty**

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19 dB
RF conducted test with spectrum		0.9dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz ~18GHz	5.23dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

**Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

**SYSTEM TEST CONFIGURATION****Justification**

Channel List:

Channel	Frequency (MHz)
1	433.60

**EUT Exercise Software**

No software was used during the test.

**Equipment Modifications**

No modification was made to the EUT.

**Support Equipment List and Details**


Manufacturer	Description	Model	Serial Number
/	/	/	/

**External I/O Cable**


Cable Description	Length (m)	From Port	To
/	/	/	/

## Block Diagram of Test Setup

For Radiated Emissions(Below 1GHz):



For Radiated Emissions(Above 1GHz):



**SUMMARY OF TEST RESULTS**

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207(a)	Conducted Emissions	Not applicable (See Note 1)
§15.205, §15.209, §15.231(b)	Radiated Emissions	Compliance
§15.231 (a) (2)	Deactivation	Compliance
§15.231 (c)	20dB Emission Bandwidth	Compliance

Note 1: The EUT is powered by battery only.

**TEST EQUIPMENT LIST**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>Radiated Emission Test (Chamber 1#)</b>					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2017-11-12	2018-11-11
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2016-12-26	2019-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2017-08-15	2018-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2017-08-15	2018-08-14
<b>Radiated Emission Test (Chamber 2#)</b>					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2017-08-27	2018-08-26
Rohde & Schwarz	FSV40 Signal Analyzer	FSV40	101116	2017-07-22	2018-07-21
ETS-LINDGREN	Horn Antenna	3115	6229	2016-01-11	2019-01-10
Sonoma Instrument	Pre-amplifier	310N	185700	2017-08-15	2018-08-14
Narda	Pre-amplifier	AFS42-00101800	2001270	2017-12-12	2018-12-11
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2017-08-15	2018-08-14

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).



## **FCC§15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### **Antenna Connected Construction**

The EUT has a helical fixed antenna arrangement which was permanently attached and the antenna gain is -2.90 dBi; fulfill the requirement of this section. Please refer to EUT photos.

**Result:** Compliant.

**FCC §15.205, §15.209, §15.231 (b) - RADIATED EMISSIONS****Applicable Standard**

FCC §15.205, §15.209, §15.231 (b)

According to FCC §15.231(b), the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

<b>Fundamental frequency (MHz)</b>	<b>Field strength of fundamental (microvolts/meter)</b>	<b>Field strength of spurious emission (microvolts/meter)</b>
40.66-40.70	2250	225
70-130	1250	125
130-174	1250 to 3750 **	125 to 375 **
174-260	3750	375
260-470	3750 to 12500 **	375 to 1250**
Above 470	12500	1250


(1) The above field strength limits are specified at a distance of 3 meters. The tighter limits apply at the band edges.

(2) Intentional radiators operating under the provisions of this section shall demonstrate compliance with the limits on the field strength of emissions, as shown in the above table, based on the average value of the measured emissions. As an alternative, compliance with the limits in the above table may be based on the use of measurement instrumentation with a CISPR quasi-peak detector. The specific method of measurement employed shall be specified in the application for equipment authorization. If average emission measurements are employed, the provisions in §15.35 for averaging pulsed emissions and for limiting peak emissions apply. Further, compliance with the provisions of §15.205 shall be demonstrated using the measurement instrumentation specified in that section.


(3) The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in §15.209, whichever limit permits a higher field strength.

## EUT Setup

**Below 1GHz:**



**Above 1 GHz:**



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10 - 2013. The specification used was the FCC 15 § 15.209, 15.205 and 15.231.

## EMI Test Receiver Setup

The system was investigated from 30 MHz to 5 GHz.

During the radiated emission test, the EMI test Receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	/	PK
1000MHz – 5000MHz	1MHz	3MHz	/	PK

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Results Summary

According to the data in the following table, the EUT complied with the FCC §15.205, §15.209, §15.231 (b).

## Test Data

### Environmental Conditions


Temperature:	24.3 °C
Relative Humidity:	51 %
ATM Pressure:	101.3 kPa

The testing was performed by Alisa Gao on 2018-05-11.

Test mode: Transmitting

**30MHz-1GHz (GFSK modulation)**

(Pre-scan in the X,Y and Z axes of orientation, the worst case X-axis of orientation was recorded.)



Frequency (MHz)	Corrected Amplitude MaxPeak (dBμV/m)	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
		Height (cm)	Polar (H/V)				
30.00	29.21	100	H	3	-4.40	60.81	31.60
73.17	16.54	200	H	75	-17.90	40.00	23.46
127.73	22.33	100	H	50	-11.90	60.81	38.48
200.36	22.33	100	V	346	-12.80	60.81	38.48
433.60	89.15	200	H	13	-7.80	100.81	11.66
867.20	40.15	200	H	7	-0.40	80.81	40.66


**Field Strength of Average Emission**

Frequency (MHz)	Peak Measurement@3m (dBμV/m)	Height (cm)	Polar (H/V)	Duty Cycle Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.231(b)/205/209	
						Limit (dBμV/m)	Margin (dB)
433.60	89.15	200	H	-11.67	77.48	80.81	3.33
867.23	40.15	200	H	-11.67	28.48	60.81	32.33

**1GHz-5 GHz (GFSK modulation)**

(Pre-scan in the X,Y and Z axes of orientation, the worst case **X-axis of orientation** was recorded.)

Full Spectrum



Frequency (MHz)	Corrected Amplitude MaxPeak (dBμV /m)	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
		Height (cm)	Polar (H/V)				
1300.80	43.71	200	H	326	-9.60	74.00	30.29
1734.40	49.42	150	H	0	-7.00	80.81	31.39
2168.00	50.03	100	H	43	-5.50	80.81	30.78
3035.20	54.83	150	H	21	-2.00	80.81	25.98
3468.80	66.06	150	V	355	-1.00	80.81	14.75
3902.40	54.41	200	V	349	0.50	74.00	19.59
4336.00	54.45	200	V	359	1.50	74.00	19.55
4769.60	51.89	150	V	35	2.40	74.00	22.11

## Field Strength of Average Emission

Frequency (MHz)	Peak Measurement@3m (dBμV/m)	Height (cm)	Polar (H/V)	Duty Cycle Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.231(b)/205/209	
						Limit (dBμV/m)	Margin (dB)
1300.80	43.71	200	H	-11.67	32.04	54.00	21.96
1734.40	49.42	150	H	-11.67	37.75	60.81	23.06
2168.00	50.03	100	H	-11.67	38.36	60.81	22.45
3035.20	54.83	150	H	-11.67	43.16	60.81	17.65
3468.80	66.06	150	V	-11.67	54.39	60.81	6.42
3902.40	54.41	200	V	-11.67	42.74	54.00	11.26
4336.00	54.45	200	V	-11.67	42.78	54.00	11.22
4769.60	51.89	150	V	-11.67	40.22	54.00	13.78

Note 1:

Corrected Factor = Antenna factor (Rx) + Cable Loss – Amplifier Factor

Margin = Limit – Corrected Amplitude

Note 2:

Calculate Average value based on Duty Cycle correction factor:


$T_p = 100\text{ms}$

$T_{on} = 26.09\text{ms}$


Duty Cycle Corrected Factor =  $20 \cdot \log(T_{on}/T_p) = 20 \cdot \log(26.09\text{ms}/100\text{ms}) = -11.67\text{dB}$

Average = Peak + Duty Cycle Corrected Factor

### Duty Cycle 5s




### Duty Cycle 100ms





# Duty Cycle 50ms



Date: 11 MAY 2018 10:28:34

**FCC §15.231(a) (2) - DEACTIVATION TESTING****Applicable Standard**

Per FCC §15.231(a), (2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.

**Test Procedure**

1. With the EUT's antenna attached, the waveform was received by the test antenna which was connected to the spectrum analyzer.
2. Set center frequency of spectrum analyzer=operating frequency.
3. Set the spectrum analyzer as RBW=100k VBW=300k Span=0Hz.
4. Repeat above procedures until all frequency measured was complete.

**Test Data****Environmental Conditions**


<b>Temperature:</b>	24.1 °C
<b>Relative Humidity:</b>	53 %
<b>ATM Pressure:</b>	101.2 kPa

*The testing was performed by Alisa Gao on 2018-05-11.*

Test mode: Transmitting

# GFSK Modulation

5s



Date: 11 MAY 2018 10:16:57

## FCC §15.231(c) - 20dB EMISSION BANDWIDTH TESTING

### Applicable Standard

Per 15.231(c), The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.

### Test Procedure

With the EUT's antenna attached, the waveform was received by the test antenna which was connected to the spectrum analyzer, plot the 20 dB bandwidth.

### Test Data

#### Environmental Conditions

Temperature:	24.3 °C
Relative Humidity:	51 %
ATM Pressure:	101.3 kPa


*The testing was performed by Alisa Gao on 2018-05-16.*

*Test Mode: Transmitting*

**GFSK modulation:**

Channel Frequency (MHz)	20dB Bandwidth (kHz)	Limit (kHz)	Result
433.60	76.850	1084	Pass

**Note:** Limit = 0.25% \* Center Frequency = 0.25% \* 433.60 MHz = 1084 kHz

**20 dB Emission Bandwidth**

\*\*\*\*\* END OF REPORT \*\*\*\*\*