



FCC PART 15.247

TEST REPORT

For

Shenzhen Cannice Technology Co., Ltd.

20/F, Tower A, Building 7, Baoneng Science and Technology Park, Qingxiang Road
#1, Longhua New District, Shenzhen, China

FCC ID: 2ADTV-AS-R

Report Type: Original Report	Product Name: Bluetooth Earphone
Test Engineer: <u>Lorin Bian</u>	
Report Number: <u>RDG170302803</u>	
Report Date: <u>2017-04-20</u>	
Reviewed By: <u>Henry Ding</u> EMC Leader	
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Chengdu) No.5040, Huilongwan Plaza, No.1, Shawan Road, Jinniu District, Chengdu, Sichuan, China Tel: 028-65523123, Fax: 028-65525125 www.baclcorp.com

Note: This test report was prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Chengdu). Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. This report was valid only with a valid digital signature.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S)	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL CABLE	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	9
APPLICABLE STANDARD	9
FCC §15.203 - ANTENNA REQUIREMENT	10
APPLICABLE STANDARD	10
ANTENNA CONNECTOR CONSTRUCTION	10
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	11
APPLICABLE STANDARD	11
MEASUREMENT UNCERTAINTY	11
EUT SETUP	12
EMI TEST RECEIVER SETUP	12
TEST PROCEDURE	12
CORRECTED AMPLITUDE & MARGIN CALCULATION	13
TEST EQUIPMENT LIST AND DETAILS	13
TEST DATA	13
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	16
APPLICABLE STANDARD	16
MEASUREMENT UNCERTAINTY	16
EUT SETUP	17
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	18
TEST PROCEDURE	18
TEST EQUIPMENT LIST AND DETAILS	18
CORRECTED AMPLITUDE & MARGIN CALCULATION	19
TEST DATA	19
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST	23
APPLICABLE STANDARD	23
TEST EQUIPMENT LIST AND DETAILS	23
TEST PROCEDURE	23
TEST DATA	23
FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING	29
APPLICABLE STANDARD	29

TEST PROCEDURE	29
TEST EQUIPMENT LIST AND DETAILS	29
TEST DATA	29
FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST	35
APPLICABLE STANDARD	35
TEST PROCEDURE	35
TEST EQUIPMENT LIST AND DETAILS	35
TEST DATA	35
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)	39
APPLICABLE STANDARD	39
TEST PROCEDURE	39
TEST EQUIPMENT LIST AND DETAILS	39
TEST DATA	39
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	55
APPLICABLE STANDARD	55
TEST PROCEDURE	55
TEST EQUIPMENT LIST AND DETAILS	55
TEST DATA	55
FCC §15.247(d) - BAND EDGES TESTING	61
APPLICABLE STANDARD	61
TEST PROCEDURE	61
TEST EQUIPMENT LIST AND DETAILS	61
TEST DATA	62

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The **Shenzhen Cannice Technology Co., Ltd.**'s product, model number: **AS (FCC ID: 2ADTV-AS-R)** (the "EUT") in this report was a **Bluetooth Earphone**, which was measured approximately: 4.3 cm (L) x 3.5 cm (W) x 2.8 cm (H), rated input voltage: DC3.7V from lithium battery or DC 5V from USB port.

**All measurement and test data in this report was gathered from final production sample, serial number: 170302803 (assigned by the BACL, Chengdu). It may have deviation from any other sample. The EUT supplied by the applicant was received on 2017-03-02, and EUT conformed to test requirement.*

Objective

This report is prepared on behalf of **Shenzhen Cannice Technology Co., Ltd.** in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules.

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

Part of system submissions with FCC ID: 2ADTV-AS-L.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Chengdu). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.62dB
Unwanted Emissions, radiated	30M~200MHz: 4.7 dB for Horizontal, 4.7 dB for Vertical 200M~1GHz: 6.0 dB for Horizontal, 6.0 for Vertical 1G~6GHz: 5.13 dB, 6G~18GHz: 5.47 dB
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.17 dB (150 kHz to 30 MHz)

Test Facility

The test site used by BACL to collect test data is located in the No.5040, Huilongwan Plaza, No.1, Shawan Road, Jinniu District, Chengdu, Sichuan, China.

Test site at BACL has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on April 24, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 560332. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in engineering mode.

EUT Exercise Software

The software "Airoha.AB1500FamilyLabTestTool" was used during testing, the maximum output power configured as below list by software:

Test Software Version	Airoha.AB1500FamilyLabTestTool		
Test Frequency	2402MHz	2441MHz	2480MHz
GFSK	63	63	63
$\pi/4$ -DQPSK	63	63	63
8-DPSK	63	63	63

Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Baijunda	Power Supply	UT-115E-5010	/

External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	no	no	0.8	Adapter	EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The max conducted power including tune-up tolerance is 4.0 dBm (2.51 mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 2.51/5 \cdot (\sqrt{2.480}) = 0.8 < 3.0$

So the SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement for BT, and the antenna gain is 3.45dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a)

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

–compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
–non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} of Table 1, then:


–compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit;
–non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit.

Based on CISPR 16-4-2:2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Chengdu) is ± 3.17 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cispr}

Measurement	U_{cispr}
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

V_C : corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS 30	836858/0016	2016-12-02	2017-12-01
Rohde & Schwarz	PULSE LIMITER	ESH3Z2	DE14781	2016-10-31	2017-10-30
Rohde & Schwarz	L.I.S.N.	ENV216	100018	2016-12-02	2017-12-01
N/A	Conducted Cable	NO.5	N/A	2016-11-10	2017-11-09
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions

Temperature:	19 °C
Relative Humidity:	56 %
ATM Pressure:	94.6 kPa

The testing was performed by Lorin Bian on 2017-03-22.

Test Mode: Transmitting


AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.161152	42.8	9.000	L1	19.7	22.6	65.4	Compliance
0.223418	36.8	9.000	L1	19.7	25.9	62.7	Compliance
0.240029	38.6	9.000	L1	19.7	23.5	62.1	Compliance
0.245835	37.5	9.000	L1	19.7	24.4	61.9	Compliance
0.554139	36.5	9.000	L1	19.7	19.5	56.0	Compliance
1.162648	32.0	9.000	L1	19.7	24.0	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.558572	22.0	9.000	L1	19.7	24.0	46.0	Compliance
0.900972	22.5	9.000	L1	19.7	23.5	46.0	Compliance
0.952654	22.9	9.000	L1	19.7	23.1	46.0	Compliance
0.975701	24.6	9.000	L1	19.7	21.4	46.0	Compliance
1.239175	33.0	9.000	L1	19.7	13.0	46.0	Compliance
1.289541	33.0	9.000	L1	19.7	13.0	46.0	Compliance

AC120 V, 60 Hz, Neutral:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.151200	41.7	9.000	N	19.7	24.2	65.9	Compliance
0.167702	39.6	9.000	N	19.7	25.5	65.1	Compliance
0.230654	37.5	9.000	N	19.6	24.9	62.4	Compliance
0.257874	33.1	9.000	N	19.6	28.4	61.5	Compliance
1.239175	37.6	9.000	N	19.6	18.4	56.0	Compliance
1.289541	38.2	9.000	N	19.6	17.8	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.952654	21.6	9.000	N	19.7	24.4	46.0	Compliance
0.975701	21.2	9.000	N	19.7	24.8	46.0	Compliance
1.144267	26.9	9.000	N	19.7	19.1	46.0	Compliance
1.190776	28.6	9.000	N	19.6	17.4	46.0	Compliance
1.239175	32.0	9.000	N	19.6	14.0	46.0	Compliance
1.289541	31.4	9.000	N	19.6	14.6	46.0	Compliance

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 2, then:

–compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
–non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} of Table 2, then:

–compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit;
–non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Chengdu) is:

30M~200MHz: ±4.7 dB;

200M~1GHz: ±6.0 dB;

1G~6GHz: ±5.13dB;


6G~25GHz: ±5.47 dB;

Table 2 – Values of U_{cispr}


Measurement	U_{cispr}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	AV

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and average detection modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Amplifier	8447D	2944A10442	2016-12-02	2017-12-01
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
Sunol Sciences	Broadband Antenna	JB3	A121808	2016-04-10	2019-04-09
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2016-12-02	2017-12-01
ETS	Horn Antenna	3115	003-6076	2016-12-02	2017-12-01
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-0113024	2014-06-16	2017-06-15
Mini-circuits	Amplifier	ZVA-183-S+	771001215	2016-05-20	2017-05-19
HP	Amplifier	8449B	3008A00277	2016-12-02	2017-12-01
EMCT	Semi-Anechoic Chamber	966	N/A	2015-04-24	2018-04-23
N/A	RF Cable (below 1GHz)	NO.1	N/A	2016-11-10	2017-11-09
N/A	RF Cable (below 1GHz)	NO.4	N/A	2016-11-10	2017-11-09
N/A	RF Cable (above 1GHz)	NO.2	N/A	2016-11-10	2017-11-09

*** Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Data

Environmental Conditions

Temperature:	19 °C
Relative Humidity:	58 %
ATM Pressure:	95.2 kPa

** The testing was performed by Lorin Bian on 2017-03-21.*

Test Mode: Transmitting

30MHz to 25 GHz:

BDR Mode (GFSK):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2402 MHz									
2402	64.52	PK	H	23.53	3.00	0.00	91.05	N/A	N/A
2402	63.58	AV	H	23.53	3.00	0.00	90.11	N/A	N/A
2402	71.76	PK	V	23.53	3.00	0.00	98.29	N/A	N/A
2402	68.91	AV	V	23.53	3.00	0.00	95.44	N/A	N/A
2390	29.16	PK	V	23.57	3.00	0.00	55.73	74	18.27
2390	18.01	AV	V	23.57	3.00	0.00	44.58	54	9.42
4804	31.42	PK	V	30.77	5.12	26.87	40.44	74	33.56
4804	29.15	AV	V	30.77	5.12	26.87	38.17	54	15.83
7206	23.07	PK	V	34.71	6.16	26.35	37.59	74	36.41
7206	15.70	AV	V	34.71	6.16	26.35	30.22	54	23.78
1489	41.24	PK	V	24.07	2.65	26.34	41.62	74	32.38
1489	31.90	AV	V	24.07	2.65	26.34	32.28	54	21.72
300.63	43.48	QP	H	14.12	1.04	27.54	31.10	46.00	14.90
361.74	44.34	QP	H	15.70	1.49	27.93	33.60	46.00	12.40
Middle Channel: 2441 MHz									
2441	65.02	PK	H	23.40	3.00	0.00	91.42	N/A	N/A
2441	63.81	AV	H	23.40	3.00	0.00	90.21	N/A	N/A
2441	72.53	PK	V	23.40	3.00	0.00	98.93	N/A	N/A
2441	70.16	AV	V	23.40	3.00	0.00	96.56	N/A	N/A
4882	33.94	PK	V	31.02	5.09	26.87	43.18	74	30.82
4882	31.33	AV	V	31.02	5.09	26.87	40.57	54	13.43
7323	24.37	PK	V	34.95	6.22	26.40	39.14	74	34.86
7323	15.30	AV	V	34.95	6.22	26.40	30.07	54	23.93
1525	37.58	PK	V	24.14	2.69	26.35	38.06	74	35.94
1525	29.35	AV	V	24.14	2.69	26.35	29.83	54	24.17
3178	34.17	PK	V	25.20	3.70	26.47	36.6	74	37.4
3178	24.93	AV	V	25.20	3.70	26.47	27.36	54	26.64
300.63	43.75	QP	H	14.12	1.04	27.54	31.37	46.00	14.63
361.74	44.48	QP	H	15.70	1.49	27.93	33.74	46.00	12.26
High Channel: 2480 MHz									
2480	64.82	PK	H	23.27	2.99	0.00	91.08	N/A	N/A
2480	64.07	AV	H	23.27	2.99	0.00	90.33	N/A	N/A
2480	70.28	PK	V	23.27	2.99	0.00	96.54	N/A	N/A
2480	68.35	AV	V	23.27	2.99	0.00	94.61	N/A	N/A
2483.5	30.87	PK	V	23.26	2.99	0.00	57.12	74	16.88
2483.5	18.82	AV	V	23.26	2.99	0.00	45.07	54	8.93
4960	30.57	PK	V	31.27	5.05	26.88	40.01	74	33.99
4960	28.25	AV	V	31.27	5.05	26.88	37.69	54	16.31
7440	22.22	PK	V	35.18	6.27	26.45	37.22	74	36.78
7440	17.06	AV	V	35.18	6.27	26.45	32.06	54	21.94
1567	41.31	PK	V	24.21	2.72	26.40	41.84	74	32.16
1567	32.00	AV	V	24.21	2.72	26.40	32.53	54	21.47
300.63	44.59	QP	H	14.12	1.04	27.54	32.21	46.00	13.79
361.74	44.9	QP	H	15.70	1.49	27.93	34.16	46.00	11.84

EDR Mode ($\pi/4$ -DQPSK):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2402 MHz									
2402	63.36	PK	H	23.53	3.00	0.00	89.89	N/A	N/A
2402	60.02	AV	H	23.53	3.00	0.00	86.55	N/A	N/A
2402	70.93	PK	V	23.53	3.00	0.00	97.46	N/A	N/A
2402	68.18	AV	V	23.53	3.00	0.00	94.71	N/A	N/A
2390	29.64	PK	V	23.57	3.00	0.00	56.21	74	17.79
2390	17.45	AV	V	23.57	3.00	0.00	44.02	54	9.98
4804	33.53	PK	V	30.77	5.12	26.87	42.55	74	31.45
4804	28.78	AV	V	30.77	5.12	26.87	37.8	54	16.2
7206	24.16	PK	V	34.71	6.16	26.35	38.68	74	35.32
7206	15.51	AV	V	34.71	6.16	26.35	30.03	54	23.97
1489	41.03	PK	V	24.07	2.65	26.34	41.41	74	32.59
1489	30.80	AV	V	24.07	2.65	26.34	31.18	54	22.82
300.63	44.12	QP	H	14.12	1.04	27.54	31.74	46.00	14.26
361.74	45.34	QP	H	15.70	1.49	27.93	34.60	46.00	11.40
Middle Channel: 2441 MHz									
2441	62.38	PK	H	23.40	3.00	0.00	88.78	N/A	N/A
2441	59.11	AV	H	23.40	3.00	0.00	85.51	N/A	N/A
2441	69.06	PK	V	23.40	3.00	0.00	95.46	N/A	N/A
2441	67.39	AV	V	23.40	3.00	0.00	93.79	N/A	N/A
4882	34.83	PK	V	31.02	5.09	26.87	44.07	74	29.93
4882	30.90	AV	V	31.02	5.09	26.87	40.14	54	13.86
7323	23.75	PK	V	34.95	6.22	26.40	38.52	74	35.48
7323	15.10	AV	V	34.95	6.22	26.40	29.87	54	24.13
1525	40.95	PK	V	24.14	2.69	26.35	41.43	74	32.57
1525	30.69	AV	V	24.14	2.69	26.35	31.17	54	22.83
3178	32.15	PK	V	25.20	3.70	26.47	34.58	74	39.42
3178	22.28	AV	V	25.20	3.70	26.47	24.71	54	29.29
300.63	43.65	QP	H	14.12	1.04	27.54	31.27	46.00	14.73
361.74	45.78	QP	H	15.70	1.49	27.93	35.04	46.00	10.96
High Channel: 2480 MHz									
2480	65.83	PK	H	23.27	2.99	0.00	92.09	N/A	N/A
2480	63.16	AV	H	23.27	2.99	0.00	89.42	N/A	N/A
2480	72.58	PK	V	23.27	2.99	0.00	98.84	N/A	N/A
2480	69.47	AV	V	23.27	2.99	0.00	95.73	N/A	N/A
2483.5	31.25	PK	V	23.26	2.99	0.00	57.5	74	16.5
2483.5	18.82	AV	V	23.26	2.99	0.00	45.07	54	8.93
4960	32.86	PK	V	31.27	5.05	26.88	42.3	74	31.7
4960	28.15	AV	V	31.27	5.05	26.88	37.59	54	16.41
7440	23.69	PK	V	35.18	6.27	26.45	38.69	74	35.31
7440	14.16	AV	V	35.18	6.27	26.45	29.16	54	24.84
1567	40.54	PK	V	24.21	2.72	26.40	41.07	74	32.93
1567	29.90	AV	V	24.21	2.72	26.40	30.43	54	23.57
300.63	44.21	QP	H	14.12	1.04	27.54	31.83	46.00	14.17
361.74	45.07	QP	H	15.70	1.49	27.93	34.33	46.00	11.67

EDR Mode (8-DPSK):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2402 MHz									
2402	62.50	PK	H	23.53	3.00	0.00	89.03	N/A	N/A
2402	59.59	AV	H	23.53	3.00	0.00	86.12	N/A	N/A
2402	71.31	PK	V	23.53	3.00	0.00	97.84	N/A	N/A
2402	67.96	AV	V	23.53	3.00	0.00	94.49	N/A	N/A
2390	30.17	PK	V	23.57	3.00	0.00	56.74	74	17.26
2390	17.82	AV	V	23.57	3.00	0.00	44.39	54	9.61
4804	34.12	PK	V	30.77	5.12	26.87	43.14	74	30.86
4804	29.25	AV	V	30.77	5.12	26.87	38.27	54	15.73
7206	24.31	PK	V	34.71	6.16	26.35	38.83	74	35.17
7206	15.35	AV	V	34.71	6.16	26.35	29.87	54	24.13
1489	41.45	PK	V	24.07	2.65	26.34	41.83	74	32.17
1489	31.04	AV	V	24.07	2.65	26.34	31.42	54	22.58
300.63	44.48	QP	H	14.12	1.04	27.54	32.10	46.00	13.90
361.74	45.21	QP	H	15.70	1.49	27.93	34.47	46.00	11.53
Middle Channel: 2441 MHz									
2441	63.43	PK	H	23.40	3.00	0.00	89.83	N/A	N/A
2441	59.92	AV	H	23.40	3.00	0.00	86.32	N/A	N/A
2441	71.48	PK	V	23.40	3.00	0.00	97.88	N/A	N/A
2441	68.19	AV	V	23.40	3.00	0.00	94.59	N/A	N/A
4882	33.70	PK	V	31.02	5.09	26.87	42.94	74	31.06
4882	28.45	AV	V	31.02	5.09	26.87	37.69	54	16.31
7323	23.78	PK	V	34.95	6.22	26.40	38.55	74	35.45
7323	16.22	AV	V	34.95	6.22	26.40	30.99	54	23.01
1525	40.43	PK	V	24.14	2.69	26.35	40.91	74	33.09
1525	30.15	AV	V	24.14	2.69	26.35	30.63	54	23.37
3178	32.13	PK	V	25.20	3.70	26.47	34.56	74	39.44
3178	22.57	AV	V	25.20	3.70	26.47	25	54	29
300.63	45.32	QP	H	14.12	1.04	27.54	32.94	46.00	13.06
361.74	45.63	QP	H	15.70	1.49	27.93	34.89	46.00	11.11
High Channel: 2480 MHz									
2480	62.12	PK	H	23.27	2.99	0.00	88.38	N/A	N/A
2480	59.63	AV	H	23.27	2.99	0.00	85.89	N/A	N/A
2480	70.18	PK	V	23.27	2.99	0.00	96.44	N/A	N/A
2480	66.97	AV	V	23.27	2.99	0.00	93.23	N/A	N/A
2483.5	30.98	PK	V	23.26	2.99	0.00	57.23	74	16.77
2483.5	19.03	AV	V	23.26	2.99	0.00	45.28	54	8.72
4960	32.89	PK	V	31.27	5.05	26.88	42.33	74	31.67
4960	27.77	AV	V	31.27	5.05	26.88	37.21	54	16.79
7440	23.19	PK	V	35.18	6.27	26.45	38.19	74	35.81
7440	14.57	AV	V	35.18	6.27	26.45	29.57	54	24.43
1567	40.60	PK	V	24.21	2.72	26.40	41.13	74	32.87
1567	30.44	AV	V	24.21	2.72	26.40	30.97	54	23.03
300.63	44.85	QP	H	14.12	1.04	27.54	32.47	46.00	13.53
361.74	46.07	QP	H	15.70	1.49	27.93	35.33	46.00	10.67

FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
N/A	RF Cable	N/A	N/A	Each Time	/

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace.
3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	19 °C
Relative Humidity:	56 %
ATM Pressure:	96 kPa

* The testing was performed by Lorin Bian on 2017-03-24.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)
BDR (GFSK)	Low	2402	1.008	0.56
	Middle	2441	1.004	0.56
	High	2480	1.004	0.56
EDR (π/4-DQPSK)	Low	2402	1.004	0.82
	Middle	2441	1.004	0.82
	High	2480	1.004	0.82
EDR Mode (8-DPSK)	Low	2402	1.004	0.81
	Middle	2441	1.004	0.80
	High	2480	1.004	0.81


Note: Limit= (2/3) × 20dB bandwidth

BDR Mode (GFSK):




Date: 24.MAR.2017 10:10:39

Middle Channel



Date: 24.MAR.2017 10:18:03


High Channel



Date: 24.MAR.2017 10:19:52


EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 24.MAR.2017 10:23:19

Middle Channel



Date: 24.MAR.2017 10:28:42


High Channel



Date: 24.MAR.2017 10:29:44


EDR Mode (8-DPSK):

Low Channel




Date: 24.MAR.2017 10:31:13

Middle Channel



Date: 24.MAR.2017 10:32:10

High Channel



Date: 24.MAR.2017 10:33:01

FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
N/A	RF Cable	N/A	N/A	Each Time	/

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	19~20 °C
Relative Humidity:	56~60 %
ATM Pressure:	96 kPa

* The testing was performed by Lorin Bian on 2017-03-24&2017-04-20.

Test Result: Compliance.


Please refer to following tables and plots

Middle Channel



Date: 20.APR.2017 13:59:30


High Channel



Date: 20.APR.2017 14:04:20


EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 24.MAR.2017 09:45:21

Middle Channel



Date: 24.MAR.2017 09:47:36


High Channel



Date: 24.MAR.2017 09:49:10


EDR Mode (8-DPSK):

Low Channel




Date: 24.MAR.2017 09:54:18

Middle Channel



Date: 24.MAR.2017 09:52:40

High Channel



Date: 24.MAR.2017 09:51:17

FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
N/A	RF Cable	N/A	N/A	Each Time	/

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	19 °C
Relative Humidity:	56 %
ATM Pressure:	96 kPa

* The testing was performed by Lorin Bian on 2017-03-24.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15

Number of Hopping Channels




Date: 24.MAR.2017 10:13:54

EDR Mode ($\pi/4$ -DQPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15

Number of Hopping Channels




Date: 24.MAR.2017 10:27:04

EDR Mode (8-DPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15

Number of Hopping Channels



Date: 24.MAR.2017 10:45:29

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 * channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time= time slot length * hope rate/ number of hopping channels * 31.6s
Hop rate=1600/s

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
N/A	RF Cable	N/A	N/A	Each Time	/

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	19 °C
Relative Humidity:	56 %
ATM Pressure:	96 kPa

* The testing was performed by Lorin Bian on 2017-03-24.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.444	0.142	0.4	Compliance
	Middle	0.444	0.142	0.4	Compliance
	High	0.444	0.142	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/2/79) ×31.6 s				
DH3	Low	1.716	0.275	0.4	Compliance
	Middle	1.716	0.275	0.4	Compliance
	High	1.716	0.275	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/4/79) ×31.6 s				
DH5	Low	2.97	0.317	0.4	Compliance
	Middle	2.98	0.318	0.4	Compliance
	High	2.97	0.317	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s				

DH1: Low Channel




Date: 24.MAR.2017 10:14:08

DH1: Middle Channel




Date: 24.MAR.2017 10:14:15

DH1: High Channel




Date: 24.MAR.2017 10:14:21

DH3: Low Channel



Date: 24.MAR.2017 14:13:47


DH3: Middle Channel



Date: 24.MAR.2017 14:13:57


Date: 24.MAR.2017 14:13:10

DH5: Middle Channel



Date: 24.MAR.2017 14:13:16

DH5: High Channel




Date: 24.MAR.2017 14:13:23

EDR Mode ($\pi/4$ -DQPSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
2DH1	Low	0.44	0.141	0.4	Compliance
	Middle	0.44	0.141	0.4	Compliance
	High	0.44	0.141	0.4	Compliance
	Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s				
2DH3	Low	1.704	0.273	0.4	Compliance
	Middle	1.710	0.274	0.4	Compliance
	High	1.710	0.274	0.4	Compliance
	Note: Dwell time=Pulse time (ms) \times (1600/4/79) \times 31.6 s				
2DH5	Low	2.960	0.316	0.4	Compliance
	Middle	2.970	0.317	0.4	Compliance
	High	2.970	0.317	0.4	Compliance
	Note: Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s				

2DH1: Low Channel




Date: 24.MAR.2017 10:27:14

2DH1: Middle Channel




Date: 24.MAR.2017 10:27:21

2DH1: High Channel




Date: 24.MAR.2017 10:27:27

2DH3: Low Channel




Date: 24.MAR.2017 14:14:32

2DH3: Middle Channel




Date: 24.MAR.2017 14:14:39

2DH3: High Channel




Date: 24.MAR.2017 14:14:45

2DH5: Low Channel




Date: 24.MAR.2017 14:15:09

2DH5: Middle Channel



Date: 24.MAR.2017 14:15:28

2DH5: High Channel




Date: 24.MAR.2017 14:15:34

EDR Mode (8-DPSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
3DH1	Low	0.44	0.141	0.4	Compliance
	Middle	0.442	0.141	0.4	Compliance
	High	0.44	0.141	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/2/79) ×31.6 s				
3DH3	Low	1.704	0.273	0.4	Compliance
	Middle	1.704	0.273	0.4	Compliance
	High	1.704	0.273	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/4/79) ×31.6 s				
3DH5	Low	2.960	0.316	0.4	Compliance
	Middle	2.970	0.317	0.4	Compliance
	High	2.960	0.316	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s				

3DH1: Low Channel




Date: 24.MAR.2017 10:45:39

3DH1: Middle Channel




Date: 24.MAR.2017 10:45:46

3DH1: High Channel




Date: 24.MAR.2017 10:45:52

3DH3: Low Channel




Date: 24.MAR.2017 14:16:07

3DH3: Middle Channel




Date: 24.MAR.2017 14:16:13

3DH3: High Channel




Date: 24.MAR.2017 14:16:20

3DH5: Low Channel




Date: 24.MAR.2017 14:16:52

3DH5: Middle Channel



Date: 24.MAR.2017 14:17:00

3DH5: High Channel



Date: 24.MAR.2017 14:17:06

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
N/A	RF Cable	N/A	N/A	Each Time	/

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	19 °C
Relative Humidity:	56 %
ATM Pressure:	96 kPa

* The testing was performed by Lorin Bian on 2017-03-24.

Test Result: Compliance.


Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Output power (dBm)	Limit (dBm)
BDR Mode (GFSK)	Low	2402	1.29	30
	Middle	2441	1.87	30
	High	2480	2.70	30
EDR Mode ($\pi/4$ -DQPSK)	Low	2402	2.02	30
	Middle	2441	2.48	30
	High	2480	2.85	30
EDR Mode (8-DPSK)	Low	2402	2.30	30
	Middle	2441	2.73	30
	High	2480	3.15	30

Note: The data above was tested in conducted mode.


BDR Mode (GFSK):

Output Power, Low Channel




Date: 24.MAR.2017 09:19:52

Output Power, Middle Channel



Date: 24.MAR.2017 09:21:46


Output Power, High Channel



Date: 24.MAR.2017 09:22:45


EDR Mode ($\pi/4$ -DQPSK):

Output Power, Low Channel




Date: 24.MAR.2017 10:03:28

Output Power, Middle Channel



Date: 24.MAR.2017 10:04:01


Output Power, High Channel



Date: 24.MAR.2017 10:04:22


EDR Mode (8-DPSK):

Low Channel




Date: 24.MAR.2017 10:05:58

Middle Channel



Date: 24.MAR.2017 10:05:17

High Channel



Date: 24.MAR.2017 10:04:51

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
N/A	RF Cable	N/A	N/A	Each Time	/

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	19 °C
Relative Humidity:	56 %
ATM Pressure:	96 kPa

* The testing was performed by Lorin Bian on 2017-03-24.

Test Result: Compliance


BDR Mode (GFSK):

Band Edge, Left Side



Date: 24.MAR.2017 09:20:14


Band Edge, Right Side



Date: 24.MAR.2017 09:23:06


EDR Mode ($\pi/4$ -DQPSK):

Band Edge, Left Side



Date: 24.MAR.2017 09:37:17


Band Edge, Right Side



Date: 24.MAR.2017 09:33:11


EDR Mode (8-DPSK):

Band Edge, Left Side



Date: 24.MAR.2017 09:28:32

Band Edge, Right Side



Date: 24.MAR.2017 09:30:40

*****END OF REPORT*****