

FCC RF Test Report

APPLICANT : Sampson Rye Ridge Limited Liability Company
EQUIPMENT : Electronic Display Device
MODEL NAME : SW56RW
FCC ID : 2ADU4-7823
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The testing completed on Feb. 23, 2016. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Product Feature of Equipment Under Test.....	5
1.3 Product Specification subjective to this standard	5
1.4 Modification of EUT	5
1.5 Testing Location	6
1.6 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	7
2.1 Carrier Frequency Channel	7
2.2 Pre-Scanned RF Power.....	8
2.3 Test Mode.....	8
2.4 Connection Diagram of Test System.....	9
2.5 Support Unit used in test configuration and system	10
2.6 EUT Operation Test Setup	10
2.7 Measurement Results Explanation Example.....	10
3 TEST RESULT	11
3.1 6dB Bandwidth Measurement	11
3.2 Output Power Measurement.....	13
3.3 Power Spectral Density Measurement	15
3.4 Conducted Band Edges and Spurious Emission Measurement	17
3.5 Radiated Band Edges and Spurious Emission Measurement	27
3.6 AC Conducted Emission Measurement.....	33
3.7 Antenna Requirements.....	37
4 LIST OF MEASURING EQUIPMENT	38
5 UNCERTAINTY OF EVALUATION	39
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. RADIATED TEST RESULTS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR520567-03B	Rev. 01	Initial issue of report	Jul. 27, 2015
FR520567-03B	Rev. 02	Updating FCC standard.	Mar. 02, 2016



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 0.53 dB at 4824.000 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 9.50 dB at 0.534 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

Sampson Rye Ridge Limited Liability Company

199 E. Montgomery Avenue, Suite 100,
Rockville, Maryland 20850

1.2 Product Feature of Equipment Under Test

Product Feature	
Equipment	Electronic Display Device
Model Name	SW56RW
FCC ID	2ADU4-7823
EUT supports Radios application	WLAN 11b/g/n HT20 Bluetooth v3.0 EDR

1.3 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx/Rx Channel Frequency Range	802.11b/g/n : 2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to Antenna	802.11b : 17.05 dBm (0.0507 W) 802.11g : 25.57 dBm (0.3606 W) 802.11n HT20 : 25.48 dBm (0.3532 W)
Antenna Type	802.11b/g/n : Fixed Internal Antenna type with gain 1.74 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH02-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH10-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.

1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r04
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-

2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test shown in the following tables.

2.4GHz 802.11b mode				
Data Rate (MHz)	1M bps	2M bps	5.5M bps	11M bps
Peak Power (dBm)	17.05	17.01	17.02	17.02

2.4GHz 802.11g mode								
Data Rate (MHz)	6M bps	9M bps	12M bps	18M bps	24M bps	36M bps	48M bps	54M bps
Peak Power (dBm)	25.57	25.43	25.50	25.46	25.41	25.37	25.48	25.38

2.4GHz 802.11n HT20 mode								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Peak Power (dBm)	25.48	25.33	25.39	25.31	25.26	25.32	25.45	25.39

2.3 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates from the power table described in section 2.2.


<2.4GHz>

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0


Test Cases	
AC Conducted Emission	Mode 1 : WLAN 2.4 GHz Link + Bluetooth Link + USB Cable (Charging from Adapter)

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
2.	WLAN AP	D-Link	DIR-865L	KA2IR865LA1	N/A	Unshielded, 1.8 m
3.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Adapter	N/A	SR75LG	Verification	N/A	N/A

2.6 EUT Operation Test Setup

The programmed RF utility "Wifi Test", is installed in EUT to provide channel selection, power level, data rate and the application type. RF Utility can send transmitting signal for all testing. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A of this test report.



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting Antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the Antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r04 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup





3.2.5 Test Result of Peak Output Power

Please refer to Appendix A of this test report.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A of this test report.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r04
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.


3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A of this test report.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.4.4 Test Setup





3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	23~26°C
Test Band :	2.4GHz Low	Relative Humidity :	45~53%
Test Channel :	01	Test Engineer :	Tommy Lee and osolemio Chang






Test Mode :	802.11b	Temperature :	23~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~53%
Test Channel :	06	Test Engineer :	Tommy Lee and osolemio Chang


WLAN 802.11b Channel 06

100kHz PSD reference Level




Date: 3.JUN.2015 20:23:53

Spurious Emission 30MHz~3GHz



Date: 3.JUN.2015 20:24:23


Spurious Emission 2GHz~25GHz




Date: 3.JUN.2015 20:24:40




Test Mode :	802.11b	Temperature :	23~26°C
Test Band :	2.4GHz High	Relative Humidity :	45~53%
Test Channel :	11	Test Engineer :	Tommy Lee and osolemio Chang

WLAN 802.11b Channel 11**100kHz PSD reference Level**


Date: 3.JUN.2015 20:30:06

High Channel Plot

Date: 3.JUN.2015 20:30:24

Spurious Emission 30MHz~3GHz

Date: 3.JUN.2015 20:30:56

Spurious Emission 2GHz~25GHz


Date: 3.JUN.2015 20:31:14



Test Mode :	802.11g	Temperature :	23~26°C
Test Band :	2.4GHz Low	Relative Humidity :	45~53%
Test Channel :	01	Test Engineer :	Tommy Lee and osolemio Chang


WLAN 802.11g Channel 01

100kHz PSD reference Level




Date: 13.JUN.2015 08:27:16

Low Channel Plot




Date: 13.JUN.2015 08:28:19

Spurious Emission 30MHz~3GHz



Date: 13.JUN.2015 08:29:56

Spurious Emission 2GHz~25GHz




Date: 13.JUN.2015 08:30:14



Test Mode :	802.11g	Temperature :	23~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~53%
Test Channel :	06	Test Engineer :	Tommy Lee and osolemio Chang


WLAN 802.11g Channel 06

100kHz PSD reference Level




Date: 13.JUN.2015 08:34:44

Spurious Emission 30MHz~3GHz



Date: 13.JUN.2015 08:35:19

Spurious Emission 2GHz~25GHz




Date: 13.JUN.2015 08:35:37



Test Mode :	802.11g	Temperature :	23~26°C
Test Band :	2.4GHz High	Relative Humidity :	45~53%
Test Channel :	11	Test Engineer :	Tommy Lee and osolemio Chang


WLAN 802.11g Channel 11

100kHz PSD reference Level




Date: 13.JUN.2015 08:40:40

High Channel Plot




Date: 13.JUN.2015 08:41:23

Spurious Emission 30MHz~3GHz



Date: 13.JUN.2015 08:42:55

Spurious Emission 2GHz~25GHz




Date: 13.JUN.2015 08:43:13



Test Mode :	802.11n HT20	Temperature :	23~26°C
Test Band :	2.4GHz Low	Relative Humidity :	45~53%
Test Channel :	01	Test Engineer :	Tommy Lee and osolemio Chang


WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level




Date: 13.JUN.2015 08:49:03

Low Channel Plot




Date: 13.JUN.2015 08:49:30

Spurious Emission 30MHz~3GHz



Date: 13.JUN.2015 08:49:56

Spurious Emission 2GHz~25GHz




Date: 13.JUN.2015 08:50:13



Test Mode :	802.11n HT20	Temperature :	23~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~53%
Test Channel :	06	Test Engineer :	Tommy Lee and osolemio Chang


WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level




Date: 13.JUN.2015 08:54:00

Spurious Emission 30MHz~3GHz



Date: 13.JUN.2015 08:54:31

Spurious Emission 2GHz~25GHz




Date: 13.JUN.2015 08:54:49



Test Mode :	802.11n HT20	Temperature :	23~26°C
Test Band :	2.4GHz High	Relative Humidity :	45~53%
Test Channel :	11	Test Engineer :	Tommy Lee and osolemio Chang


WLAN 802.11n HT20 Channel 11

100kHz PSD reference Level




Date: 13.JUN.2015 08:57:58

High Channel Plot




Date: 13.JUN.2015 08:59:01

Spurious Emission 30MHz~3GHz



Date: 13.JUN.2015 09:00:26

Spurious Emission 2GHz~25GHz



Date: 13.JUN.2015 09:00:44



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.


For average measurement:

 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Band	Duty Cycle(%)	T(μ s)	1/T(kHz)	VBW Setting
802.11b	100.00	98.62	-	-
802.11g	99.15	93.46	1430	0.70
2.4GHz 802.11n HT20	99.01	93.06	1340	0.75

3.5.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.


3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B and C.




3.5.7 Duty Cycle

802.11b



Date: 10.JUN.2015 10:44:17


802.11g



Date: 10.JUN.2015 10:55:52



802.11n HT20



Date: 10.JUN.2015 11:09:19

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B and C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.


3.6.4 Test Setup



AMN = Artificial mains network (LISN)
 AE = Associated equipment
 EUT = Equipment under test
 ISN = Impedance stabilization network

3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	23~25°C
Test Engineer :	Eric Jeng	Relative Humidity :	56~58%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	WLAN 2.4 GHz Link + Bluetooth Link + USB Cable (Charging from Adapter)		




Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	41.3	Off	L1	19.6	24.3	65.6
0.174000	40.4	Off	L1	19.6	24.4	64.8
0.214000	37.6	Off	L1	19.6	25.4	63.0
0.270000	32.5	Off	L1	19.6	28.6	61.1
0.534000	40.1	Off	L1	19.6	15.9	56.0
0.646000	32.1	Off	L1	19.6	23.9	56.0
0.958000	32.0	Off	L1	19.6	24.0	56.0
5.934000	32.3	Off	L1	19.7	27.7	60.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	28.4	Off	L1	19.6	27.2	55.6
0.174000	28.9	Off	L1	19.6	25.9	54.8
0.214000	27.4	Off	L1	19.6	25.6	53.0
0.270000	26.1	Off	L1	19.6	25.0	51.1
0.534000	36.5	Off	L1	19.6	9.5	46.0
0.646000	27.9	Off	L1	19.6	18.1	46.0
0.958000	28.3	Off	L1	19.6	17.7	46.0
5.934000	23.3	Off	L1	19.7	26.7	50.0

Test Mode :	Mode 1	Temperature :	23~25°C
Test Engineer :	Eric Jeng	Relative Humidity :	56~58%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	WLAN 2.4 GHz Link + Bluetooth Link + USB Cable (Charging from Adapter)		


Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	42.1	Off	N	19.6	23.9	66.0
0.198000	37.9	Off	N	19.7	25.8	63.7
0.534000	40.1	Off	N	19.6	15.9	56.0
0.950000	31.0	Off	N	19.6	25.0	56.0
1.758000	27.4	Off	N	19.6	28.6	56.0
5.878000	33.8	Off	N	19.7	26.2	60.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	29.4	Off	N	19.6	26.6	56.0
0.198000	27.6	Off	N	19.7	26.1	53.7
0.534000	36.2	Off	N	19.6	9.8	46.0
0.950000	26.1	Off	N	19.6	19.9	46.0
1.758000	22.5	Off	N	19.6	23.5	46.0
5.878000	23.8	Off	N	19.7	26.2	50.0



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	1218006	300MHz~40GHz	Oct. 18, 2014	Jun. 13, 2015~ Jun. 17, 2015	Oct. 17, 2015	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	1126017	300MHz~40GHz	Oct. 18, 2014	Jun. 13, 2015~ Jun. 17, 2015	Oct. 17, 2015	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Oct. 17, 2014	Jun. 13, 2015~ Jun. 17, 2015	Oct. 16, 2015	Conducted (TH05-HY)
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170 584	18GHz- 40GHz	Nov. 03, 2014	Jun. 15, 2015~ Jun. 16, 2015	Nov. 02, 2015	Radiation (03CH10-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Jul. 28, 2014	Jun. 15, 2015~ Jun. 16, 2015	Jul. 27, 2015	Radiation (03CH10-HY)
EMI Test Receiver	Keysight	N9038A	MY541300 85	20Hz ~ 8.4GHz	Nov. 05, 2014	Jun. 15, 2015~ Jun. 16, 2015	Nov. 04, 2015	Radiation (03CH10-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-132 5	1GHz ~ 18GHz	Oct. 03, 2014	Jun. 15, 2015~ Jun. 16, 2015	Oct. 02, 2015	Radiation (03CH10-HY)
Preamplifier	Keysight	83017A	MY532700 78	1GHz~26.5GHz	Nov. 20, 2014	Jun. 15, 2015~ Jun. 16, 2015	Nov. 19, 2015	Radiation (03CH10-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1902246	1GHz~18GHz	Nov. 25, 2014	Jun. 15, 2015~ Jun. 16, 2015	Nov. 24, 2015	Radiation (03CH10-HY)
Spectrum Analyzer	Keysight	N9010A	MY542004 85	10Hz ~ 44GHz	Oct. 14, 2014	Jun. 15, 2015~ Jun. 16, 2015	Oct. 13, 2015	Radiation (03CH10-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Jun. 15, 2015~ Jun. 16, 2015	N/A	Radiation (03CH10-HY)
Turn Table	EMEC	TT 2200	N/A	0-360 degree	N/A	Jun. 15, 2015~ Jun. 16, 2015	N/A	Radiation (03CH10-HY)
Preamplifier	MITEQ	JS44-180040 00-33-8P	1840917	18GHz ~ 40GHz	Jun. 02, 2015	Jun. 15, 2015~ Jun. 16, 2015	Jun. 01, 2016	Radiation (03CH10-HY)
Amplifier	SONOMA	310N	187311	9kHz~1GHz	Nov. 16, 2015	Feb. 18, 2016	Nov. 15, 2016	Radiation (03CH10-HY)
Bilog Antenna	TESEQ	CBL 6111D	35413	30MHz~1GHz	Jan. 13, 2016	Feb. 18, 2016	Jan. 12, 2017	Radiation (03CH10-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY541300 85	20Hz ~ 8.4GHz	Nov. 04, 2015	Feb. 18, 2016	Nov. 03, 2016	Radiation (03CH10-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Feb. 23, 2016	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 26, 2015	Feb. 23, 2016	Aug. 25, 2016	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 02, 2015	Feb. 23, 2016	Dec. 01, 2016	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 08, 2016	Feb. 23, 2016	Jan. 07, 2017	Conduction (CO05-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.26
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.90
---	------

Appendix A. Conducted Test Results

Test Engineer:	Osolemio Chang/Tommy Lee	Temperature:	24-26	°C
Test Date:	2015/6/13~2015/6/17	Relative Humidity:	45-49	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band								
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	14.15	8.52	0.50	Pass
11b	1Mbps	1	6	2437	14.15	9.00	0.50	Pass
11b	1Mbps	1	11	2462	14.15	9.00	0.50	Pass
11g	6Mbps	1	1	2412	17.25	15.16	0.50	Pass
11g	6Mbps	1	6	2437	17.25	15.16	0.50	Pass
11g	6Mbps	1	11	2462	17.30	15.16	0.50	Pass
HT20	MCS0	1	1	2412	18.30	15.16	0.50	Pass
HT20	MCS0	1	6	2437	18.25	15.16	0.50	Pass
HT20	MCS0	1	11	2462	18.20	15.16	0.50	Pass

TEST RESULTS DATA
Peak Power Table

2.4GHz Band										
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	17.05	30.00	1.74	18.79	36.00	Pass
11b	1Mbps	1	6	2437	16.72	30.00	1.74	18.46	36.00	Pass
11b	1Mbps	1	11	2462	17.04	30.00	1.74	18.78	36.00	Pass
11g	6Mbps	1	1	2412	25.46	30.00	1.74	27.20	36.00	Pass
11g	6Mbps	1	6	2437	25.52	30.00	1.74	27.26	36.00	Pass
11g	6Mbps	1	11	2462	25.57	30.00	1.74	27.31	36.00	Pass
HT20	MCS0	1	1	2412	25.48	30.00	1.74	27.22	36.00	Pass
HT20	MCS0	1	6	2437	25.47	30.00	1.74	27.21	36.00	Pass
HT20	MCS0	1	11	2462	25.45	30.00	1.74	27.19	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

2.4GHz Band						
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.06	14.75
11b	1Mbps	1	6	2437	0.06	14.53
11b	1Mbps	1	11	2462	0.06	14.70
11g	6Mbps	1	1	2412	0.29	14.62
11g	6Mbps	1	6	2437	0.29	14.73
11g	6Mbps	1	11	2462	0.29	14.98
HT20	MCS0	1	1	2412	0.31	14.95
HT20	MCS0	1	6	2437	0.31	14.91
HT20	MCS0	1	11	2462	0.31	14.84

TEST RESULTS DATA
Peak Power Density

2.4GHz Band								
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-6.59	1.74	8.00	Pass
11b	1Mbps	1	6	2437	-6.96	1.74	8.00	Pass
11b	1Mbps	1	11	2462	-7.38	1.74	8.00	Pass
11g	6Mbps	1	1	2412	-9.67	1.74	8.00	Pass
11g	6Mbps	1	6	2437	-10.03	1.74	8.00	Pass
11g	6Mbps	1	11	2462	-9.29	1.74	8.00	Pass
HT20	MCS0	1	1	2412	-10.29	1.74	8.00	Pass
HT20	MCS0	1	6	2437	-9.81	1.74	8.00	Pass
HT20	MCS0	1	11	2462	-10.03	1.74	8.00	Pass



Appendix B. Radiated Spurious Emission

Test Engineer :	Elvis Chen and Stan Hsieh	Temperature :	24~25°C
		Relative Humidity :	53~54%

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2387.94	57.2	-16.8	74	57.82	27.23	5.39	33.24	146	214	P	H
		2386.95	47.11	-6.89	54	47.73	27.23	5.39	33.24	146	214	A	H
	*	2411.94	107.51	-	-	108.03	27.28	5.42	33.22	146	214	P	H
	*	2411.022	105.04	-	-	105.56	27.28	5.42	33.22	146	214	A	H
													H
													H
		2387.22	55.09	-18.91	74	55.71	27.23	5.39	33.24	342	160	P	V
		2386.86	45.91	-8.09	54	46.53	27.23	5.39	33.24	342	160	A	V
	*	2411.94	106.95	-	-	107.47	27.28	5.42	33.22	342	160	P	V
	*	2410.938	104.42	-	-	104.94	27.28	5.42	33.22	342	160	A	V
													V
													V
802.11b CH 06 2437MHz		2366.88	54.13	-19.87	74	54.84	27.14	5.39	33.24	143	215	P	H
		2384.16	43.99	-10.01	54	44.65	27.19	5.39	33.24	143	215	A	H
	*	2436.99	106.92	-	-	107.34	27.37	5.42	33.21	143	215	P	H
	*	2435.989	104.41	-	-	104.88	27.32	5.42	33.21	143	215	A	H
		2483.56	54.61	-19.39	74	54.87	27.46	5.46	33.18	143	215	P	H
		2483.88	43.43	-10.57	54	43.69	27.46	5.46	33.18	143	215	A	H
		2385.69	52.93	-21.07	74	53.55	27.23	5.39	33.24	380	150	P	V
		2389.29	42.65	-11.35	54	43.27	27.23	5.39	33.24	380	150	A	V
	*	2437.074	106.53	-	-	106.95	27.37	5.42	33.21	380	150	P	V
	*	2435.822	103.92	-	-	104.39	27.32	5.42	33.21	380	150	A	V
		2485.04	53.1	-20.9	74	53.36	27.46	5.46	33.18	380	150	P	V
		2484	42.48	-11.52	54	42.74	27.46	5.46	33.18	380	150	A	V



802.11b CH 11 2462MHz	*	2461.957	107.15	-	-	107.5	27.41	5.44	33.2	167	221	P	H
	*	2460.955	104.65	-	-	105	27.41	5.44	33.2	167	221	A	H
		2486.72	56.02	-17.98	74	56.28	27.46	5.46	33.18	167	221	P	H
		2484.28	46.45	-7.55	54	46.71	27.46	5.46	33.18	167	221	A	H
													H
													H
	*	2461.957	106.88	-	-	107.23	27.41	5.44	33.2	372	163	P	V
	*	2460.872	104.33	-	-	104.68	27.41	5.44	33.2	372	163	A	V
		2491.36	55.65	-18.35	74	55.87	27.5	5.46	33.18	372	163	P	V
		2484.4	45.7	-8.3	54	45.96	27.46	5.46	33.18	372	163	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		4824	55.31	-18.69	74	76.88	31.46	7.58	60.61	100	113	P	H
		4824	53.47	-0.53	54	75.04	31.46	7.58	60.61	100	113	A	H
													H
													H
		4824	46.62	-27.38	74	68.19	31.46	7.58	60.61	100	0	P	V
													V
													V
													V
802.11b CH 06 2437MHz		4874	53.56	-20.44	74	74.82	31.56	7.7	60.52	100	116	P	H
		4874	53.13	-0.87	54	74.39	31.56	7.7	60.52	100	116	A	H
		7311	43.88	-30.12	74	59.14	36.18	9.49	60.93	100	0	P	H
													H
		4874	45.57	-28.43	74	66.83	31.56	7.7	60.52	100	0	P	V
		7311	43.4	-30.6	74	58.66	36.18	9.49	60.93	100	0	P	V
													V
													V
802.11b CH 11 2462MHz		4924	53.72	-20.28	74	74.55	31.66	7.93	60.42	100	115	P	H
		4924	53.28	-0.72	54	74.11	31.66	7.93	60.42	100	115	A	H
		7386	42.34	-31.66	74	57.63	36.37	9.53	61.19	100	0	P	H
													H
		4924	44.56	-29.44	74	65.39	31.66	7.93	60.42	100	0	P	V
		7386	43.12	-30.88	74	58.41	36.37	9.53	61.19	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		2386.95	62.16	-11.84	74	62.78	27.23	5.39	33.24	203	213	P	H
		2389.92	48.88	-5.12	54	49.48	27.23	5.39	33.22	203	213	A	H
	*	2414.112	108.87	-	-	109.39	27.28	5.42	33.22	203	213	P	H
	*	2410.688	100.33	-	-	100.85	27.28	5.42	33.22	203	213	A	H
													H
													H
		2389.47	59.67	-14.33	74	60.29	27.23	5.39	33.24	380	151	P	V
		2389.92	46.68	-7.32	54	47.28	27.23	5.39	33.22	380	151	A	V
	*	2414.529	107.08	-	-	107.6	27.28	5.42	33.22	380	151	P	V
	*	2413.11	98.82	-	-	99.34	27.28	5.42	33.22	380	151	A	V
													V
													V
802.11g CH 06 2437MHz		2386.95	54.52	-19.48	74	55.14	27.23	5.39	33.24	117	215	P	H
		2388.93	45.24	-8.76	54	45.86	27.23	5.39	33.24	117	215	A	H
	*	2433.65	108.21	-	-	108.68	27.32	5.42	33.21	117	215	P	H
	*	2435.237	100.01	-	-	100.48	27.32	5.42	33.21	117	215	A	H
		2483.72	53.93	-20.07	74	54.19	27.46	5.46	33.18	117	215	P	H
		2485	44.12	-9.88	54	44.38	27.46	5.46	33.18	117	215	A	H
		2389.29	53.44	-20.56	74	54.06	27.23	5.39	33.24	380	152	P	V
		2389.83	43.9	-10.1	54	44.5	27.23	5.39	33.22	380	152	A	V
	*	2439.579	107.52	-	-	107.94	27.37	5.42	33.21	380	152	P	V
	*	2435.571	99.12	-	-	99.59	27.32	5.42	33.21	380	152	A	V
		2491.36	53.58	-20.42	74	53.8	27.5	5.46	33.18	380	152	P	V
		2484.08	43.35	-10.65	54	43.61	27.46	5.46	33.18	380	152	A	V



802.11g CH 11 2462MHz	*	2460.538	108.35	-	-	108.7	27.41	5.44	33.2	167	222	P	H
	*	2460.371	100.33	-	-	100.68	27.41	5.44	33.2	167	222	A	H
		2484.12	61.98	-12.02	74	62.24	27.46	5.46	33.18	167	222	P	H
		2483.88	48.18	-5.82	54	48.44	27.46	5.46	33.18	167	222	A	H
													H
													H
	*	2463.71	108.51	-	-	108.86	27.41	5.44	33.2	374	162	P	V
	*	2460.621	100.37	-	-	100.72	27.41	5.44	33.2	374	162	A	V
		2483.64	60.25	-13.75	74	60.51	27.46	5.46	33.18	374	162	P	V
		2483.52	47.25	-6.75	54	47.51	27.46	5.46	33.18	374	162	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		4824	49.88	-24.12	74	71.45	31.46	7.58	60.61	100	118	P	H
		4824	44	-10	54	65.57	31.46	7.58	60.61	100	118	A	H
													H
													H
		4824	41.07	-32.93	74	62.64	31.46	7.58	60.61	100	0	P	V
													V
													V
													V
802.11g CH 06 2437MHz		4874	51.36	-22.64	74	72.62	31.56	7.7	60.52	100	118	P	H
		4874	45.99	-8.01	54	67.25	31.56	7.7	60.52	100	118	A	H
		7311	40.71	-33.29	74	55.97	36.18	9.49	60.93	100	0	P	H
													H
		4874	44.52	-29.48	74	65.78	31.56	7.7	60.52	100	0	P	V
		7311	41.9	-32.1	74	57.16	36.18	9.49	60.93	100	0	P	V
													V
													V
802.11g CH 11 2462MHz		4924	52.99	-21.01	74	73.82	31.66	7.93	60.42	100	115	P	H
		4924	46.11	-7.89	54	66.94	31.66	7.93	60.42	100	115	A	H
		7386	43.76	-30.24	74	59.05	36.37	9.53	61.19	100	0	P	H
													H
		4924	44.58	-29.42	74	65.41	31.66	7.93	60.42	100	0	P	V
		7386	41.59	-32.41	74	56.88	36.37	9.53	61.19	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		2364.45	66.2	-7.8	74	66.91	27.14	5.39	33.24	100	212	P	H
		2390	50.65	-3.35	54	51.25	27.23	5.39	33.22	100	212	A	H
	*	2410.688	108.01	-	-	108.53	27.28	5.42	33.22	100	212	P	H
	*	2410.688	100.59	-	-	101.11	27.28	5.42	33.22	100	212	A	H
													H
													H
		2389.65	62.4	-11.6	74	63.02	27.23	5.39	33.24	344	163	P	V
		2389.74	49.36	-4.64	54	49.98	27.23	5.39	33.24	344	163	A	V
	*	2409.937	107.46	-	-	107.98	27.28	5.42	33.22	344	163	P	V
	*	2410.771	99.84	-	-	100.36	27.28	5.42	33.22	344	163	A	V
													V
													V
802.11n HT20 CH 06 2437MHz		2386.77	54.79	-19.21	74	55.41	27.23	5.39	33.24	118	211	P	H
		2389.47	45.46	-8.54	54	46.08	27.23	5.39	33.24	118	211	A	H
	*	2434.82	107.58	-	-	108.05	27.32	5.42	33.21	118	211	P	H
	*	2435.237	99.87	-	-	100.34	27.32	5.42	33.21	118	211	A	H
		2484.08	54.29	-19.71	74	54.55	27.46	5.46	33.18	118	211	P	H
		2483.8	44.07	-9.93	54	44.33	27.46	5.46	33.18	118	211	A	H
		2386.41	53.8	-20.2	74	54.42	27.23	5.39	33.24	380	150	P	V
		2389.74	43.81	-10.19	54	44.43	27.23	5.39	33.24	380	150	A	V
	*	2438.326	107.16	-	-	107.58	27.37	5.42	33.21	380	150	P	V
	*	2435.655	99.58	-	-	100.05	27.32	5.42	33.21	380	150	A	V
		2484.04	53.43	-20.57	74	53.69	27.46	5.46	33.18	380	150	P	V
		2484.12	43.34	-10.66	54	43.6	27.46	5.46	33.18	380	150	A	V



802.11n HT20 CH 11 2462MHz	*	2459.869	107.48	-	-	107.83	27.41	5.44	33.2	167	223	P	H
	*	2460.454	100.07	-	-	100.42	27.41	5.44	33.2	167	223	A	H
		2485	64.68	-9.32	74	64.94	27.46	5.46	33.18	167	223	P	H
		2484.28	48.59	-5.41	54	48.85	27.46	5.46	33.18	167	223	A	H
													H
													H
	*	2463.126	107.81	-	-	108.16	27.41	5.44	33.2	373	161	P	V
	*	2460.538	99.84	-	-	100.19	27.41	5.44	33.2	373	161	A	V
		2484.48	62.48	-11.52	74	62.74	27.46	5.46	33.18	373	161	P	V
		2483.8	48.16	-5.84	54	48.42	27.46	5.46	33.18	373	161	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		4824	52.68	-21.32	74	74.25	31.46	7.58	60.61	100	119	P	H
		4824	44.56	-9.44	54	66.13	31.46	7.58	60.61	100	119	A	H
													H
													H
		4824	43.04	-30.96	74	64.61	31.46	7.58	60.61	100	0	P	V
													V
													V
													V
802.11n HT20 CH 06 2437MHz		4874	52.83	-21.17	74	74.09	31.56	7.7	60.52	100	119	P	H
		4874	46.06	-7.94	54	67.32	31.56	7.7	60.52	100	119	A	H
		7311	41.49	-32.51	74	56.75	36.18	9.49	60.93	100	0	P	H
													H
		4874	45.07	-28.93	74	66.33	31.56	7.7	60.52	100	0	P	V
		7311	42.24	-31.76	74	57.5	36.18	9.49	60.93	100	0	P	V
													V
													V
802.11n HT20 CH 11 2462MHz		4924	51.61	-22.39	74	72.44	31.66	7.93	60.42	100	116	P	H
		4924	45.8	-8.2	54	66.63	31.66	7.93	60.42	100	116	A	H
		7386	43.16	-30.84	74	58.45	36.37	9.53	61.19	100	0	P	H
													H
		4924	44.77	-29.23	74	65.6	31.66	7.93	60.42	100	0	P	V
		7386	42.28	-31.72	74	57.57	36.37	9.53	61.19	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz WIFI 802.11b (LF)

[illegible]



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.







Appendix C. Radiated Spurious Emission Plots

Test Engineer :	Elvis Chen and Stan Hsieh	Temperature :	24~25°C
		Relative Humidity :	53~54%





Note symbol

-L	Low channel location
-R	High channel location





2.4GHz 2400~2483.5MHz
WIFI 802.11b (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH01 2412MHz	
1	Horizontal	Vertical
Peak	 <p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 4</p>	 <p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 4</p>
Avg.	 <p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 4</p>	 <p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 4</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1	Horizontal	Vertical
Peak	 <p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 5</p>	 <p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 5</p>
Avg.	 <p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 5</p>	 <p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 5</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1	Horizontal	Vertical
Peak	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 520567-03 Mode : 5</p></div>	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 520567-03 Mode : 5</p></div>
Avg.	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 520567-03 Mode : 5</p></div>	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 520567-03 Mode : 5</p></div>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH11 2462MHz	
1	Horizontal	Vertical
Peak	 <p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 520567-03 Mode : 6</p>	 <p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 520567-03 Mode : 6</p>
Avg.	 <p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 520567-03 Mode : 6</p>	 <p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 520567-03 Mode : 6</p>





2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
1	Horizontal	Vertical
Peak	 <p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 7</p>	 <p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 7</p>
Avg.	 <p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 7</p>	 <p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 7</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - L	
1	Horizontal	Vertical
Peak	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 8</p></div>	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 8</p></div>
Avg.	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 8</p></div>	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 8</p></div>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - R	
1	Horizontal	Vertical
Peak	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 520567-03 Mode : 8</p></div>	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 520567-03 Mode : 8</p></div>
Avg.	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 520567-03 Mode : 8</p></div>	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 520567-03 Mode : 8</p></div>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH11 2462MHz	
1	Horizontal	Vertical
Peak	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 520567-03 Mode : 9</p></div>	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 520567-03 Mode : 9</p></div>
Avg.	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 520567-03 Mode : 9</p></div>	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 520567-03 Mode : 9</p></div>





2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Horizontal	Vertical
Peak	 <p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 10</p>	 <p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 10</p>
Avg.	 <p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 10</p>	 <p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 10</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - L	
1	Horizontal	Vertical
Peak	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 11</p></div>	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 11</p></div>
Avg.	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 11</p></div>	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 520567-03 Mode : 11</p></div>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - R	
1	Horizontal	Vertical
Peak	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 520567-03 Mode : 11</p></div>	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 520567-03 Mode : 11</p></div>
Avg.	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 520567-03 Mode : 11</p></div>	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 520567-03 Mode : 11</p></div>



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Horizontal	Vertical
Peak	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 520567-03 Mode : 12</p></div>	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 520567-03 Mode : 12</p></div>
Avg.	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 520567-03 Mode : 12</p></div>	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 520567-03 Mode : 12</p></div>



2.4GHz 2400~2483.5MHz
WIFI 802.11b (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH01 2412MHz	
1	Horizontal	Vertical
Peak Avg.	 <p> Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN_9170_406_1404 HORIZONTAL Detector : Peak Project : 520567-03 Mode : 4 </p>	 <p> Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN_9170_406_1404 VERTICAL Detector : Peak Project : 520567-03 Mode : 4 </p>





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.	<div><p>Site : 03CH10-HV Condition : FCC CLASS-B 3m HORN_9170_406_1404 HORIZONTAL Detector : Peak Project : 520567-03 Mode : 5</p></div>	<div><p>Site : 03CH10-HV Condition : FCC CLASS-B 3m HORN_9170_406_1404 VERTICAL Detector : Peak Project : 520567-03 Mode : 5</p></div>



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN_9170_406_1404 HORIZONTAL Detector : Peak Project : 520567-03 Mode : 6</p></div>	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN_9170_406_1404 VERTICAL Detector : Peak Project : 520567-03 Mode : 6</p></div>





2.4GHz 2400~2483.5MHz
WIFI 802.11g (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH01 2412MHz	
1	Horizontal	Vertical
Peak Avg.	 <p> Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN_9170_406_1404 HORIZONTAL Detector : Peak Project : 520567-03 Mode : 7 </p>	 <p> Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN_9170_406_1404 VERTICAL Detector : Peak Project : 520567-03 Mode : 7 </p>





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN_9170_406_1404 HORIZONTAL Detector : Peak Project : 520567-03 Mode : 8</p></div>	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN_9170_406_1404 VERTICAL Detector : Peak Project : 520567-03 Mode : 8</p></div>





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN_9170_406_1404 HORIZONTAL Detector : Peak Project : 520567-03 Mode : 9</p></div>	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN_9170_406_1404 VERTICAL Detector : Peak Project : 520567-03 Mode : 9</p></div>



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Horizontal	Vertical
Peak Avg.	 <p> Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN_9170_406_1404 HORIZONTAL Detector : Peak Project : 520567-03 Mode : IO </p>	 <p> Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN_9170_406_1404 VERTICAL Detector : Peak Project : 520567-03 Mode : IO </p>





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN_9170_406_1404 HORIZONTAL Detector : Peak Project : 520567-03 Mode : 11</p></div>	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN_9170_406_1404 VERTICAL Detector : Peak Project : 520567-03 Mode : 11</p></div>



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN_9170_406_1404 HORIZONTAL Detector : Peak Project : 520567-03 Mode : 12</p></div>	<div><p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN_9170_406_1404 VERTICAL Detector : Peak Project : 520567-03 Mode : 12</p></div>

2.4GHz 2400~2483.5MHz
Emission below 1GHz
2.4GHz WIFI 802.11b (LF)

WIFI	2.4GHz 2400~2483.5MHz	
ANT	802.11b LF	
1	Horizontal	Vertical
QP / Peak	 <p>Site : 03CH10-HY Condition : FCC CLASS-B 3m BI-LOG 6111D-LF HORIZONTAL Detector : Peak Project : 520567-03 Mode : 14</p>	 <p>Site : 03CH10-HY Condition : FCC CLASS-B 3m BI-LOG 6111D-LF VERTICAL Detector : Peak Project : 520567-03 Mode : 14</p>