

FCC SAR EVALUATION REPORT

**In accordance with the requirements of
FCC 47 CFR Part 2(2.1093), ANSI/IEEE C95.1-1992 and
IEEE Std 1528-2013**

Product Name : Roam WiFi

Trademark : N/A

Model Name : RoamWiFi R10

Family Model : Aerobile3

Report No. : S19040302621001

FCC ID : 2ADUBROAMWIFIR10

Prepared for

Tianjin RoamWiFi Technology Co.,Ltd
209 (TG no. 446, TG, no. 446, animation building C, no. 126 animation
road, tianjin eco-city)

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park Sanwei, Xixiang, Bao'an District,
Shenzhen, Guangdong, China
Tel.: +86-755-6115 6588 Fax.: +86-755-6115 6599
Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION

Applicant's name.....: Tianjin RoamWiFi Technology Co.,Ltd
 Address.....: 209 (TG no. 446, TG, no. 446, animation building C, no. 126
 animation road, tianjin eco-city)
Manufacturer's Name.....: Tianjin RoamWiFi Technology Co.,Ltd
 Address.....: 209 (TG no. 446, TG, no. 446, animation building C, no. 126
 animation road, tianjin eco-city)

Product description

Product name.....: Roam WiFi
 Trademark: N/A
 Model Name: RoamWiFi R10
 Family Model.....: Aerobile3
 FCC 47 CFR Part 2(2.1093)


Standards.....: ANSI/IEEE C95.1-1992
 IEEE Std 1528-2013
 Published RF exposure KDB procedures


This device described above has been tested by Shenzhen NTEK. In accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 and KDB 865664 D01. Testing has shown that this device is capable of compliance with localized specific absorption rate (SAR) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992. The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK, this document may be altered or revised by Shenzhen NTEK, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests.....: Dec. 25, 2019 ~ Jan. 08, 2020
 Date of Issue: Jan. 13, 2020
 Test Result: **Pass**

Prepared By : 
 (Test Engineer) :
 (Cheng Jiawen)

Approved By : 
 (Lab Manager) :
 (Sam Chen)

※ ※ Revision History ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	Jan. 13, 2020	Cheng Jiawen

TABLE OF CONTENTS

1. General Information	6
1.1. RF exposure limits.....	6
1.2. Statement of Compliance	7
1.3. EUT Description	7
1.4. Test specification(s)	9
1.5. Ambient Condition.....	9
2. SAR Measurement System	10
2.1. SATIMO SAR Measurement Set-up Diagram	10
2.2. Robot	11
2.3. E-Field Probe.....	12
2.3.1. E-Field Probe Calibration	12
2.4. SAM phantoms	13
2.4.1. Technical Data	14
2.5. Device Holder	15
2.6. Test Equipment List	16
3. SAR Measurement Procedures	18
3.1. Power Reference	18
3.2. Area scan & Zoom scan.....	18
3.3. Description of interpolation/extrapolation scheme	20
3.4. Volumetric Scan	20
3.5. Power Drift	20
4. System Verification Procedure	21
4.1. Tissue Verification	21
4.1.1. Tissue Dielectric Parameter Check Results	22
4.2. System Verification Procedure	23
4.2.1. System Verification Results	24
5. SAR Measurement variability and uncertainty	25
5.1. SAR measurement variability.....	25
5.2. SAR measurement uncertainty	25
6. RF Exposure Positions	26
6.1. Wireless Router Devices	26
7. RF Output Power	27
7.1. WCDMA Conducted Power	27
7.2. LTE Conducted Power	28
7.3. WLAN Output Power.....	42
7.3.1. Output Power Results Of WLAN	42
8. Antenna Location.....	44
9. SAR Results	45
9.1. SAR measurement results	45

9.1.1.	SAR measurement Result of WCDMA Band 2	45
9.1.2.	SAR measurement Result of WCDMA Band 5	45
9.1.3.	SAR measurement Result of LTE Band 2	45
9.1.4.	SAR measurement Result of LTE Band 4	46
9.1.5.	SAR measurement Result of LTE Band 5	47
9.1.6.	SAR measurement Result of LTE Band 12	47
9.1.7.	SAR measurement Result of LTE Band 17	48
9.1.8.	SAR measurement Result of LTE Band 26	49
9.1.9.	SAR measurement Result of LTE Band 41	49
9.1.10.	SAR measurement Result of WLAN 2.4G	50
9.1.11.	SAR measurement Result of WLAN 5.2G	50
9.1.12.	SAR measurement Result of WLAN 5.8G	51
9.2.	SAR Summation Scenario	51
10.	Appendix A. Photo documentation	57
11.	Appendix B. System Check Plots	58
12.	Appendix C. Plots of High SAR Measurement	75
13.	Appendix D. Calibration Certificate	100

1. General Information

1.1. RF exposure limits

(A).Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B).Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

General Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

NOTE
 HEAD AND TRUNK LIMIT
 1.6 W/kg
 APPLIED TO THIS EUT

1.2. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for RoamWiFi R10 are as follows.

Band	Max Reported SAR Value(W/kg)	
	1-g Hotspot (Separation distance of 10mm)	Max Simultaneous Tx
WCDMA Band 2	0.758	1.342
WCDMA Band 5	0.796	
LTE Band 2	0.762	
LTE Band 4	0.789	
LTE Band 5	0.230	
LTE Band 12	0.074	
LTE Band 17	0.098	
LTE Band 26	0.310	
LTE Band 41	0.644	
WLAN 2.4G	0.147	
WLAN 5.2G	0.105	
WLAN 5.8G	0.581	

Note: The Max Simultaneous Tx is calculated based on the same configuration and test position. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 & KDB 865664 D01.

1.3. EUT Description

Device Information	
Product Name	Roam WiFi
Trade Name	N/A
Model Name	RoamWiFi R10
Family Model	Aerobile3
FCC ID	2ADUBROAMWIFIR10
Device Phase	Identical Prototype
Exposure Category	General population / Uncontrolled environment
Antenna	PIFA Antenna
Battery Information	DC 3.8V, 5000mAh, 19Wh
Device Operating Configurations	
Supporting Mode(s)	WCDMA Band 2/5, LTE Band 2/4/5/12/17/26/41, WLAN 2.4G/5.2G/5.8G

Test Modulation	WCDMA(QPSK), LTE(QPSK/16QAM), WLAN(DSSS/OFDM)		
Device Class	B		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	WCDMA Band 2	1850-1910	1930-1990
	WCDMA Band 5	824-849	869-894
	LTE Band 2	1850-1910	1930-1990
	LTE Band 4	1710-1755	2110-2155
	LTE Band 5	824-849	869-894
	LTE Band 12	699-716	729-746
	LTE Band 17	704-716	734-746
	LTE Band 26	814-849	859-894
	LTE Band 41	2496-2690	
	WLAN 2.4G	2412-2462	
	WLAN 5.2G	5180-5240	
	WLAN 5.8G	5745-5825	
Power Class	3, tested with power control “all 1”(WCDMA Band 2)		
	3, tested with power control “all 1”(WCDMA Band 5)		
	3, tested with power control all Max.(LTE Band 2)		
	3, tested with power control all Max.(LTE Band 4)		
	3, tested with power control all Max.(LTE Band 5)		
	3, tested with power control all Max.(LTE Band 12)		
	3, tested with power control all Max.(LTE Band 17)		
	3, tested with power control all Max.(LTE Band 26)		
	3, tested with power control all Max.(LTE Band 41)		
Test Channels (low-mid-high)	9262-9400-9538(WCDMA Band 2)		
	4132-4182-4233(WCDMA Band 5)		
	18607-18900-19193(LTE Band 2 BW=1.4MHz)		
	18615-18900-19185(LTE Band 2 BW=3MHz)		
	18625-18900-19175(LTE Band 2 BW=5MHz)		
	18650-18900-19150(LTE Band 2 BW=10MHz)		
	18675-18900-19125(LTE Band 2 BW=15MHz)		
	18700-18900-19100(LTE Band 2 BW=20MHz)		
	19957-20175-20393(LTE Band 4 BW=1.4MHz)		
	19965-20175-20385(LTE Band 4 BW=3MHz)		
	19975-20175-20375(LTE Band 4 BW=5MHz)		
	20000-20175-20350(LTE Band 4 BW=10MHz)		
	20025-20175-20325(LTE Band 4 BW=15MHz)		
	20050-20175-20300(LTE Band 4 BW=20MHz)		
	20407-20525-20643(LTE Band 5 BW=1.4MHz)		
	20415-20525-20635(LTE Band 5 BW=3MHz)		

20425-20525-20625(LTE Band 5 BW=5MHz)
20450-20525-20600(LTE Band 5 BW=10MHz)
23017-23095-23173 (LTE Band 12 BW=1.4MHz)
23025-23095-23165 (LTE Band 12 BW=3MHz)
23035-23095-23155 (LTE Band 12 BW=5MHz)
23060-23095-23130 (LTE Band 12 BW=10MHz)
23755-23790-23825(LTE Band 17 BW=5MHz)
23780-23790-23800(LTE Band 17 BW=10MHz)
26697-26865-27033(LTE Band 26 BW=1.4MHz)
26705-26865-27025(LTE Band 26 BW=3MHz)
26715-26865-27015(LTE Band 26 BW=5MHz)
26750-26865-26990(LTE Band 26 BW=10MHz)
26775-26865-26965(LTE Band 26 BW=15MHz)
39675-40620-41565(LTE Band 41 BW=5MHz)
39700-40620-41540(LTE Band 41 BW=10MHz)
39725-40620-41515(LTE Band 41 BW=15MHz)
39750-40620-41490(LTE Band 41 BW=20MHz)
1-3-6-9-11(WLAN 2.4G)
36-38-40-42-46-48(WLAN 5.2G)
149-151-155-157-159-165(WLAN 5.8G)

1.4. Test specification(s)


FCC 47 CFR Part 2(2.1093)
ANSI/IEEE C95.1-1992
IEEE Std 1528-2013
KDB 865664 D01 SAR measurement 100 MHz to 6 GHz
KDB 865664 D02 RF Exposure Reporting
KDB 447498 D01 General RF Exposure Guidance
KDB 248227 D01 802.11 Wi-Fi SAR
KDB 941225 D01 3G SAR Procedures
KDB 941225 D05 SAR for LTE Devices
KDB 941225 D06 Hotspot SAR

1.5. Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

2. SAR Measurement System

2.1. SATIMO SAR Measurement Set-up Diagram



These measurements were performed with the automated near-field scanning system OPENSAR from SATIMO. The system is based on a high precision robot (working range: 901 mm), which positions the probes with a positional repeatability of better than ± 0.03 mm. The SAR measurements were conducted with dosimetric probe (manufactured by SATIMO), designed in the classical triangular configuration and optimized for dosimetric evaluation.

The first step of the field measurement is the evaluation of the voltages induced on the probe by the device under test. Probe diode detectors are nonlinear. Below the diode compression point, the output voltage is proportional to the square of the applied E-field; above the diode compression point, it is linear to the applied E-field. The compression point depends on the diode, and a calibration procedure is necessary for each sensor of the probe.

The Keithley multimeter reads the voltage of each sensor and send these three values to the PC. The corresponding E field value is calculated using the probe calibration factors, which are stored in the working directory. This evaluation includes linearization of the diode characteristics. The field calculation is done separately for each sensor. Each component of the E field is displayed on the "Dipole Area Scan Interface" and the total E field is displayed on the "3D Interface"

2.2. Robot

The SATIMO SAR system uses the high precision robots from KUKA. For the 6-axis controller system, the robot controller version (KUKA) from KUKA is used. The KUKA robot series have many features that are important for our application:



- High precision (repeatability ± 0.03 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)

2.3. E-Field Probe

This E-field detection probe is composed of three orthogonal dipoles linked to special Schottky diodes with low detection thresholds. The probe allows the measurement of electric fields in liquids such as the one defined in the IEEE and CENELEC standards.

For the measurements the Specific Dosimetric E-Field Probe SN 41/18 EPGO330 with following specifications is used



- Dynamic range: 0.01-100 W/kg
 - Tip Diameter: 2.5 mm
 - Distance between probe tip and sensor center: 1 mm
 - Distance between sensor center and the inner phantom surface: 2 mm (repeatability better than ± 1 mm).
 - Probe linearity: ± 0.10 dB
 - Axial isotropy: 0.06 dB
 - Hemispherical Isotropy: 0.09 dB
 - Calibration range: 650MHz to 5900MHz for head & body simulating liquid.
 - Lower detection limit: 9mW/kg
- Angle between probe axis (evaluation axis) and surface normal line: less than 30° .

2.3.1. E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy shall be evaluated and within ± 0.25 dB. The sensitivity parameters (Norm X, Norm Y, and Norm Z), the diode compression parameter (DCP) and the conversion factor (Conv F) of the probe are tested. The calibration data can be referred to appendix D of this report.

2.4. SAM phantoms

Photo of SAM phantom SN 16/15 SAM119




The SAM phantom is used to measure the SAR relative to people exposed to electro-magnetic field radiated by mobile phones.

The test, based on ultrasonic system, allows measuring the thickness with an accuracy of 10 μm .

2.5. Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1 degree.



Serial Number	Holder Material	Permittivity	Loss Tangent
SN 16/15 MSH100	Delrin	3.7	0.005

2.6. Test Equipment List

This table gives a complete overview of the SAR measurement equipment.

Devices used during the test described are marked ☒

	Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
					Last Cal.	Due Date
<input checked="" type="checkbox"/>	MVG	E FIELD PROBE	SSE2	SN 41/18 EPG0330	May 21, 2019	May 20, 2020
<input checked="" type="checkbox"/>	MVG	750 MHz Dipole	SID750	SN 03/15 DIP 0G750-355	Apr. 19, 2018	Apr. 18, 2021
<input checked="" type="checkbox"/>	MVG	835 MHz Dipole	SID835	SN 03/15 DIP 0G835-347	Apr. 19, 2018	Apr. 18, 2021
<input type="checkbox"/>	MVG	900 MHz Dipole	SID900	SN 03/15 DIP 0G900-348	Apr. 19, 2018	Apr. 18, 2021
<input checked="" type="checkbox"/>	MVG	1800 MHz Dipole	SID1800	SN 03/15 DIP 1G800-349	Apr. 19, 2018	Apr. 18, 2021
<input checked="" type="checkbox"/>	MVG	1900 MHz Dipole	SID1900	SN 03/15 DIP 1G900-350	Apr. 19, 2018	Apr. 18, 2021
<input type="checkbox"/>	MVG	2000 MHz Dipole	SID2000	SN 03/15 DIP 2G000-351	Apr. 19, 2018	Apr. 18, 2021
<input checked="" type="checkbox"/>	MVG	2450 MHz Dipole	SID2450	SN 03/15 DIP 2G450-352	Apr. 19, 2018	Apr. 18, 2021
<input checked="" type="checkbox"/>	MVG	2600 MHz Dipole	SID2600	SN 03/15 DIP 2G600-356	Apr. 19, 2018	Apr. 18, 2021
<input checked="" type="checkbox"/>	MVG	5000 MHz Dipole	SWG5500	SN 13/14 WGA 33	Apr. 19, 2018	Apr. 18, 2021
<input checked="" type="checkbox"/>	MVG	Liquid measurement Kit	SCLMP	SN 21/15 OCPG 72	NCR	NCR
<input checked="" type="checkbox"/>	MVG	Power Amplifier	N.A	AMPLISAR_28/14_003	NCR	NCR
<input checked="" type="checkbox"/>	KEITHLEY	Millivoltmeter	2000	4072790	NCR	NCR
<input checked="" type="checkbox"/>	R&S	Universal radio communication tester	CMU200	117858	Aug. 06, 2019	Aug. 05, 2020
<input checked="" type="checkbox"/>	R&S	Wideband radio communication tester	CMW500	103917	Aug. 28, 2019	Aug. 27, 2020
<input checked="" type="checkbox"/>	HP	Network Analyzer	8753D	3410J01136	Aug. 06, 2019	Aug. 05, 2020
<input checked="" type="checkbox"/>	Agilent	PSG Analog Signal Generator	E8257D	MY51110112	Aug. 06, 2019	Aug. 05, 2020

<input checked="" type="checkbox"/>	Agilent	Power meter	E4419B	MY45102538	Aug. 06, 2019	Aug. 05, 2020
<input checked="" type="checkbox"/>	Agilent	Power sensor	E9301A	MY41495644	Aug. 06, 2019	Aug. 05, 2020
<input checked="" type="checkbox"/>	Agilent	Power sensor	E9301A	US39212148	Aug. 06, 2019	Aug. 05, 2020
<input checked="" type="checkbox"/>	MCLI/USA	Directional Coupler	CB11-20	0D2L51502	Aug. 06, 2019	Aug. 05, 2020

3. SAR Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/Bluetooth power measurement, use engineering software to configure EUT WLAN/Bluetooth continuously transmission, at maximum RF power in each supported wireless interface and frequency band.
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/Bluetooth output power.

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/Bluetooth continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix A demonstrates.
- (c) Set scan area, grid size and other setting on the OPENSAR software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band.
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg.

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

3.1. Power Reference

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

3.2. Area scan & Zoom scan

The area scan is a 2D scan to find the hot spot location on the DUT. The zoom scan is a 3D scan above the hot spot to calculate the 1g and 10g SAR value.

Measurement of the SAR distribution with a grid of 8 to 16 mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8 * 4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

From the scanned SAR distribution, identify the position of the maximum SAR value, in addition identify the positions of any local maxima with SAR values within 2 dB of the maximum value that will not be within the zoom scan of other peaks; additional peaks shall be measured only when the primary peak is within 2 dB of the SAR compliance limit (e.g., 1 W/kg for 1,6 W/kg 1 g limit, or 1,26 W/kg for 2 W/kg, 10 g limit).

Area scan & Zoom scan scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be \leq the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm *	3 – 4 GHz: ≤ 5 mm * 4 – 6 GHz: ≤ 4 mm *
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

* When zoom scan is required and the *reported* SAR from the *area scan based 1-g SAR estimation* procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

3.3. Description of interpolation/extrapolation scheme

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimise measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is used to determine this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1 mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10 grams and 1 gram requires a very fine resolution in the three dimensional scanned data array.

3.4. Volumetric Scan

The volumetric scan consists to a full 3D scan over a specific area. This 3D scan is useful for multi Tx SAR measurement. Indeed, it is possible with OpenSAR to add, point by point, several volumetric scans to calculate the SAR value of the combined measurement as it is defined in the standard IEEE1528 and IEC62209.

3.5. Power Drift

All SAR testing is under the EUT installed full charged battery and transmit maximum output power. In OpenSAR measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in V/m. If the power drifts more than $\pm 5\%$, the SAR will be retested.



4. System Verification Procedure

4.1. Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% of weight)	Head Tissue									
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5200	5800
Water	34.40	34.40	34.40	55.36	55.36	57.87	57.87	57.87	65.53	65.53
NaCl	0.79	0.79	0.79	0.35	0.35	0.16	0.16	0.16	0.00	0.00
1,2-Propanediol	64.81	64.81	64.81	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	30.45	30.45	19.97	19.97	19.97	24.24	24.24
DGBE	0.00	0.00	0.00	13.84	13.84	22.00	22.00	22.00	10.23	10.23
Ingredients (% of weight)	Body Tissue									
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5200	5800
Water	50.30	50.30	50.30	69.91	69.91	71.88	71.88	71.88	79.54	79.54
NaCl	0.60	0.60	0.60	0.13	0.13	0.16	0.16	0.16	0.00	0.00
1,2-Propanediol	49.10	49.10	49.10	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	9.99	9.99	19.97	19.97	19.97	11.24	11.24
DGBE	0.00	0.00	0.00	19.97	19.97	7.99	7.99	7.99	9.22	9.22

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid depth from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm.

Photo of Liquid depth for Head Position	Photo of Liquid depth for Body Position
	

4.1.1. Tissue Dielectric Parameter Check Results

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values.


Tissue Type	Measured Frequency (MHz)	Target Tissue		Measured Tissue		Liquid Temp.	Test Date
		ϵ_r ($\pm 5\%$)	σ (S/m) ($\pm 5\%$)	ϵ_r	σ (S/m)		
Body 750	750	55.55 (52.77~58.33)	0.96 (0.91~1.01)	55.23	0.97	21.2 °C	Jan. 05, 2020
Body 850	835	55.20 (52.44~57.96)	0.97 (0.92~1.02)	54.32	1.01	21.3 °C	Jan. 06, 2020
Body 1800	1800	53.30 (50.64~55.97)	1.52 (1.44~1.60)	53.17	1.54	21.2 °C	Jan. 08, 2020
Body 1900	1900	53.30 (50.64~55.97)	1.52 (1.44~1.60)	52.50	1.57	21.4 °C	Jan. 07, 2020
Body 2450	2450	52.70 (50.07~55.34)	1.95 (1.85~2.05)	52.02	2.03	21.2 °C	Dec. 25, 2019
Body 2600	2600	52.51 (49.88~55.14)	2.16 (2.05~2.27)	52.60	2.21	21.2 °C	Dec. 25, 2019
Body 5200	5200	49.00 (46.55~51.45)	5.30 (5.04~5.57)	49.66	5.29	21.5 °C	Dec. 26, 2019
Body 5800	5800	48.20 (45.79~50.61)	6.00 (5.70~6.30)	48.35	6.06	21.2 °C	Dec. 26, 2019

NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

4.2. System Verification Procedure

The system verification is performed for verifying the accuracy of the complete measurement system and performance of the software. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 100mW (below 5GHz) or 100mW (above 5GHz). To adjust this power a power meter is used. The power sensor is connected to the cable before the system verification to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the system verification to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot).

The system verification is shown as below picture:



4.2.1. System Verification Results

Comparing to the original SAR value provided by SATIMO, the verification data should be within its specification of $\pm 10\%$. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance verification can meet the variation criterion and the plots can be referred to Appendix B of this report.

System Verification	Target SAR (1W) ($\pm 10\%$)		Measured SAR (Normalized to 1W)		Liquid Temp.	Test Date
	1-g (W/Kg)	10-g (W/Kg)	1-g (W/Kg)	10-g (W/Kg)		
750MHz Body	8.85 (7.97~9.74)	5.91 (5.32~6.50)	8.28	6.04	21.2 °C	Jan. 05, 2020
835MHz Body	9.83 (8.85~10.81)	6.45 (5.81~7.10)	9.50	6.72	21.3 °C	Jan. 06, 2020
1800MHz Body	38.13 (34.32~41.94)	20.65 (18.59~22.72)	38.19	21.77	21.2 °C	Jan. 08, 2020
1900MHz Body	39.02 (35.12~42.92)	20.57 (18.51~22.63)	39.22	21.89	21.4 °C	Jan. 07, 2020
2450MHz Body	52.90 (47.61~58.19)	24.09 (21.68~26.50)	52.67	25.41	21.2 °C	Dec. 25, 2019
2600MHz Body	52.49 (47.24~57.74)	23.74 (21.37~26.11)	52.00	23.39	21.2 °C	Dec. 25, 2019
5200MHz Body	156.85 (141.17~172.54)	55.20 (49.68~60.72)	156.77	55.10	21.5 °C	Dec. 26, 2019
5800MHz Body	169.30 (152.37~186.23)	58.49 (52.64~64.34)	169.11	58.40	21.2 °C	Dec. 26, 2019

5. SAR Measurement variability and uncertainty

5.1. SAR measurement variability

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

5.2. SAR measurement uncertainty

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

6. RF Exposure Positions

6.1. Wireless Router Devices

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WLAN simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WLAN transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WLAN transmitter according to FCC KDB Publication 447498 D01 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

7. RF Output Power

7.1. WCDMA Conducted Power

Band	WCDMA Band 2			
Tx Channel	Tune-up	9262	9400	9538
Frequency (MHz)		1852.4	1880	1907.6
RMC 12.2Kbps	24.00	23.29	23.34	23.04
HSDPA Subtest-1	23.00	22.17	22.18	21.97
HSDPA Subtest-2	22.00	21.70	21.74	21.51
HSDPA Subtest-3	21.00	20.21	20.43	20.10
HSDPA Subtest-4	21.00	20.15	20.18	19.92
HSUPA Subtest-1	22.00	21.37	21.34	21.05
HSUPA Subtest-2	23.00	22.06	22.02	21.78
HSUPA Subtest-3	21.00	20.83	21.00	20.51
HSUPA Subtest-4	23.00	22.27	22.23	22.02
HSUPA Subtest-5	22.00	21.03	21.05	20.83
Band	WCDMA Band 5			
Tx Channel	Tune-up	4132	4182	4233
Frequency (MHz)		826.4	836.4	846.6
RMC 12.2Kbps	23.50	23.20	22.99	23.02
HSDPA Subtest-1	22.50	22.10	21.76	21.85
HSDPA Subtest-2	22.50	21.57	21.26	21.38
HSDPA Subtest-3	20.50	20.04	19.78	20.01
HSDPA Subtest-4	20.50	19.96	19.62	19.80
HSUPA Subtest-1	21.50	21.22	20.92	20.96
HSUPA Subtest-2	22.50	21.86	21.59	21.66
HSUPA Subtest-3	21.50	20.83	20.39	20.46
HSUPA Subtest-4	22.50	22.12	21.74	21.87
HSUPA Subtest-5	21.50	20.90	20.56	20.72

7.2. LTE Conducted Power

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18607/1850.7	18900/1880	19193/1909.3
LTE Band 2	1.4MHz	QPSK	1	0	24.00	22.39	23.02	23.10
			1	2	24.00	22.82	23.21	23.16
			1	5	24.00	22.68	23.21	23.10
			3	0	24.00	22.70	23.11	23.18
			3	1	24.00	22.76	23.17	23.30
			3	2	24.00	22.63	23.16	23.27
			6	0	23.00	21.66	22.13	22.23
		16QAM	1	0	23.00	21.46	21.92	22.31
			1	2	23.00	21.42	22.13	22.47
			1	5	23.00	21.36	21.96	22.26
			3	0	23.00	21.25	22.22	22.34
			3	1	23.00	21.19	22.16	22.20
			3	2	23.00	21.20	22.18	22.36
			6	0	22.00	20.69	21.10	21.54
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18615/1851.5	18900/1880	19185/1908.5
LTE Band 2	3MHz	QPSK	1	0	24.00	22.80	23.22	23.09
			1	7	24.00	23.01	23.39	23.17
			1	14	24.00	22.91	23.33	23.17
			8	0	23.00	21.83	22.18	22.27
			8	4	23.00	21.81	22.21	22.33
			8	7	23.00	21.84	22.18	22.34
			15	0	23.00	21.91	22.17	22.20
		16QAM	1	0	23.00	22.16	21.86	21.97
			1	7	23.00	22.39	22.19	22.07
			1	14	23.00	22.36	22.17	21.95
			8	0	22.00	20.75	21.05	21.07
			8	4	22.00	20.87	21.08	21.07
			8	7	22.00	20.89	21.04	21.08
			15	0	22.00	20.82	21.08	21.01
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		

			RB Size	RB Offset		18625/1852.5	18900/1880	19175/1907.5
LTE Band 2	5MHz	QPSK	1	0	24.00	22.70	23.06	22.95
			1	12	24.00	23.03	23.25	23.15
			1	24	24.00	22.77	23.17	23.24
			12	0	23.00	21.83	22.14	22.14
			12	6	23.00	21.88	22.20	22.23
			12	11	23.00	21.85	22.21	22.21
			25	0	23.00	21.78	22.22	22.18
		16QAM	1	0	23.00	21.79	21.97	22.32
			1	12	23.00	21.92	21.94	22.36
			1	24	23.00	21.73	22.03	22.25
			12	0	22.00	20.74	20.82	20.95
			12	6	22.00	20.92	20.99	21.05
			12	11	22.00	20.88	20.90	21.11
			25	0	22.00	20.88	21.18	21.02
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18650/1855	18900/1880	19150/1905
LTE Band 2	10MHz	QPSK	1	0	24.00	22.97	23.36	23.15
			1	24	24.00	22.98	23.57	23.35
			1	49	24.00	23.01	23.21	23.17
			25	0	23.00	21.97	22.22	22.23
			25	12	23.00	21.91	22.31	22.24
			25	24	23.00	21.99	22.32	22.19
			50	0	23.00	21.98	22.19	22.21
		16QAM	1	0	23.00	22.46	22.13	22.16
			1	24	23.00	22.92	21.96	22.29
			1	49	23.00	22.27	21.94	22.11
			25	0	22.00	21.07	21.25	21.40
			25	12	22.00	20.97	21.57	21.41
			25	24	22.00	20.92	21.41	21.37
			50	0	22.00	21.03	21.28	21.11
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18675/1857.5	18900/1880	19125/1902.5
LTE Band	15MHz	QPSK	1	0	24.00	22.95	23.31	23.27
			1	37	24.00	23.16	23.44	23.29

2			1	74	24.00	23.24	23.22	23.03
			36	0	23.00	22.00	22.23	22.19
			36	18	23.00	21.98	22.24	22.26
			36	37	23.00	22.05	22.19	22.20
			75	0	23.00	22.02	22.24	22.20
		16QAM	1	0	23.00	22.56	22.16	22.58
			1	37	23.00	22.86	22.42	22.83
			1	74	23.00	22.67	21.96	22.52
			36	0	22.00	21.19	21.29	21.13
			36	18	22.00	21.17	21.39	21.34
			36	37	22.00	21.17	21.22	21.20
			75	0	22.00	21.06	21.11	21.24
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18700/1860	18900/1880	19100/1900
LTE Band 2	20MHz	QPSK	1	0	24.00	22.69	23.29	22.97
			1	49	24.00	22.96	23.50	23.11
			1	99	24.00	22.87	23.22	22.93
			50	0	23.00	22.06	22.32	22.25
			50	24	23.00	22.14	22.39	22.33
			50	49	23.00	22.11	22.25	22.20
			100	0	23.00	22.14	22.27	22.23
		16QAM	1	0	23.00	21.80	22.51	21.85
			1	49	23.00	21.95	22.30	21.92
			1	99	23.00	21.52	21.71	21.89
			50	0	22.00	20.98	21.05	21.25
			50	24	22.00	21.35	21.53	21.35
			50	49	22.00	21.30	21.28	21.26
			100	0	22.00	21.12	21.34	21.24

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		19957/1710.7	20175/1732.5	20393/1754.3
LTE Band 4	1.4MHz	QPSK	1	0	24.00	23.02	22.59	22.85
			1	2	24.00	23.08	22.81	22.95
			1	5	24.00	22.95	22.78	22.80
			3	0	24.00	23.04	22.75	22.71
			3	1	24.00	23.08	22.85	22.69

			3	2	24.00	22.99	22.75	22.70
			6	0	22.00	21.89	21.83	21.65
		16QAM	1	0	23.00	22.25	21.48	21.54
			1	2	23.00	22.44	21.60	21.86
			1	5	23.00	22.25	21.43	21.63
			3	0	23.00	22.15	21.57	21.91
			3	1	23.00	22.08	21.58	21.90
			3	2	23.00	21.99	21.55	21.94
			6	0	21.00	20.79	20.73	20.85
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		19965/1711.5	20175/1732.5	20385/1753.5
LTE Band 4	3MHz	QPSK	1	0	24.00	23.11	22.78	22.62
			1	7	24.00	23.03	22.83	22.68
			1	14	24.00	23.12	22.87	22.76
			8	0	22.00	21.72	21.85	21.66
			8	4	22.00	21.93	21.90	21.68
			8	7	22.00	21.80	21.83	21.70
			15	0	22.00	21.81	21.85	21.67
		16QAM	1	0	23.00	22.64	21.40	21.46
			1	7	23.00	22.40	21.67	21.65
			1	14	23.00	22.69	21.42	21.40
			8	0	21.00	20.61	20.53	20.33
			8	4	21.00	20.63	20.60	20.36
			8	7	21.00	20.69	20.57	20.47
			15	0	21.00	20.79	20.72	20.60
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		19975/1712.5	20175/1732.5	20375/1752.5
LTE Band 4	5MHz	QPSK	1	0	23.00	22.79	22.36	22.59
			1	12	23.00	22.91	22.88	22.57
			1	24	23.00	22.85	22.71	22.80
			12	0	22.00	21.88	21.88	21.78
			12	6	22.00	21.91	21.79	21.62
			12	11	22.00	21.93	21.91	21.89
			25	0	22.00	21.88	21.89	21.91
		16QAM	1	0	22.00	21.58	21.68	21.98
			1	12	22.00	21.94	21.48	21.95

			1	24	22.00	21.82	21.62	21.66
			12	0	21.00	20.76	20.47	20.70
			12	6	21.00	20.78	20.55	20.54
			12	11	21.00	20.90	20.67	20.60
			25	0	21.00	20.90	20.82	20.84
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20000/1715	20175/1732.5	20350/1750
LTE Band 4	10MHz	QPSK	1	0	23.00	22.95	22.84	22.68
			1	24	23.00	22.88	22.89	22.83
			1	49	23.00	22.63	22.76	22.80
			25	0	22.00	21.84	21.78	21.69
			25	12	22.00	21.85	21.75	21.71
			25	24	22.00	21.71	21.79	21.70
			50	0	22.00	21.94	21.72	21.65
		16QAM	1	0	23.00	22.10	21.38	21.39
			1	24	23.00	22.18	21.37	21.70
			1	49	23.00	21.81	21.26	21.74
			25	0	21.00	20.92	20.61	20.46
			25	12	21.00	20.84	20.67	20.54
			25	24	21.00	20.68	20.80	20.69
			50	0	21.00	20.88	20.65	20.64
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20025/1717.5	20175/1732.5	20325/1747.5
LTE Band 4	15MHz	QPSK	1	0	23.00	22.72	22.65	22.70
			1	37	23.00	22.68	22.61	22.75
			1	74	23.00	22.93	22.63	22.58
			36	0	22.00	21.89	21.82	21.58
			36	18	22.00	21.72	21.80	21.63
			36	37	22.00	21.67	21.81	21.60
			75	0	22.00	21.81	21.81	21.57
		16QAM	1	0	23.00	22.09	21.57	21.97
			1	37	23.00	22.14	21.35	21.84
			1	74	23.00	22.26	21.30	21.69
			36	0	21.00	20.88	20.71	20.54
			36	18	21.00	20.69	20.79	20.61
			36	37	21.00	20.55	20.82	20.57

			75	0	21.00	20.75	20.63	20.54
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20050/1720	20175/1732.5	20300/1745
LTE Band 4	20MHz	QPSK	1	0	24.00	22.46	22.82	23.10
			1	49	24.00	22.55	22.77	22.71
			1	99	24.00	22.45	22.91	22.49
			50	0	22.00	21.89	21.83	21.80
			50	24	22.00	21.76	21.81	21.79
			50	49	22.00	21.78	21.63	21.69
			100	0	22.00	21.95	21.72	21.75
		16QAM	1	0	22.00	21.70	21.31	21.54
			1	49	22.00	21.70	21.37	21.32
			1	99	22.00	21.29	20.90	21.24
			50	0	21.00	20.89	20.53	20.75
			50	24	21.00	20.57	20.72	20.77
			50	49	21.00	20.82	20.65	20.74
			100	0	21.00	20.73	20.65	20.68

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20407/824.7	20525/836.5	20643/848.3
LTE Band 5	1.4MHz	QPSK	1	0	23.00	22.11	21.87	21.76
			1	2	23.00	22.01	22.03	22.08
			1	5	23.00	22.06	21.93	21.69
			3	0	23.00	22.21	22.21	22.14
			3	1	23.00	22.17	22.29	22.13
			3	2	23.00	22.09	22.09	21.94
			6	0	22.00	21.18	21.06	21.02
		16QAM	1	0	22.00	20.88	20.97	20.64
			1	2	22.00	21.12	21.11	20.62
			1	5	22.00	21.04	20.91	20.39
			3	0	22.00	20.98	20.83	20.90
			3	1	22.00	20.97	21.04	20.92
			3	2	22.00	21.02	21.06	20.80
			6	0	21.00	20.20	20.30	19.97
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		

			RB Size	RB Offset		20415/825.5	20525/836.5	20635/847.5
LTE Band 5	3MHz	QPSK	1	0	23.00	22.01	21.93	21.96
			1	7	23.00	22.28	22.06	22.14
			1	14	23.00	22.36	22.08	21.80
			8	0	22.00	21.03	21.04	20.98
			8	4	22.00	21.25	21.06	20.94
			8	7	22.00	21.10	20.98	20.93
			15	0	22.00	21.08	21.07	21.02
		16QAM	1	0	22.00	21.91	20.57	20.58
			1	7	22.00	21.81	20.99	20.89
			1	14	22.00	21.95	20.80	20.61
			8	0	21.00	19.90	19.91	20.08
			8	4	21.00	19.94	19.91	19.97
			8	7	21.00	19.95	19.85	19.76
			15	0	21.00	20.11	20.00	20.01
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20425/826.5	20525/836.5	20625/846.5
LTE Band 5	5MHz	QPSK	1	0	23.00	22.00	21.64	21.79
			1	12	23.00	22.33	21.96	21.89
			1	24	23.00	22.30	21.86	21.65
			12	0	22.00	21.10	21.16	20.83
			12	6	22.00	21.20	21.14	20.89
			12	11	22.00	21.11	21.03	20.88
			25	0	22.00	21.13	21.07	20.95
		16QAM	1	0	22.00	21.00	20.89	20.77
			1	12	22.00	21.09	20.77	20.82
			1	24	22.00	21.16	20.69	20.51
			12	0	20.00	19.75	19.72	19.78
			12	6	20.00	19.85	19.64	19.96
			12	11	20.00	19.93	19.70	19.63
			25	0	21.00	20.03	20.01	19.69
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20450/829	20525/836.5	20600/844
LTE Band	10MHz	QPSK	1	0	23.00	22.01	21.96	21.97
			1	24	23.00	22.47	21.91	22.07

5			1	49	23.00	22.15	21.85	21.88
			25	0	22.00	21.09	21.05	20.92
			25	12	22.00	21.13	20.95	20.90
			25	24	22.00	21.11	20.93	20.93
			50	0	22.00	21.08	20.98	20.92
		16QAM	1	0	22.00	21.49	20.65	20.78
			1	24	22.00	21.12	20.63	20.95
			1	49	22.00	21.39	20.08	20.67
			25	0	21.00	19.89	20.01	19.77
			25	12	21.00	19.95	19.90	19.96
			25	24	21.00	20.00	19.77	19.85
			50	0	21.00	20.05	19.85	19.88

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23017/699.7	23095/707.5	23173/715.3
LTE Band 12	1.4MHz	QPSK	1	0	24.00	23.61	23.25	23.18
			1	2	24.00	23.61	23.28	23.38
			1	5	24.00	23.54	23.38	23.50
			3	0	24.00	23.52	23.55	23.24
			3	1	24.00	23.47	23.77	23.41
			3	2	24.00	23.49	23.58	23.37
		16QAM	6	0	23.00	22.48	22.55	22.36
			1	0	23.00	22.47	22.18	22.06
			1	2	23.00	22.65	22.13	22.39
			1	5	23.00	22.77	22.13	22.52
			3	0	23.00	22.88	22.32	22.49
			3	1	23.00	22.88	22.42	22.67
			3	2	23.00	22.79	22.37	22.81
			6	0	22.00	21.68	21.65	21.36

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23025/700.5	23095/707.5	23165/714.5
LTE Band 12	3MHz	QPSK	1	0	24.00	23.30	23.41	23.35
			1	7	24.00	23.77	23.79	23.76
			1	14	24.00	23.79	23.49	23.64
			8	0	23.00	22.59	22.56	22.43
			8	4	23.00	22.39	22.68	22.49

			8	7	23.00	22.52	22.60	22.45
			15	0	23.00	22.50	22.65	22.34
		16QAM	1	0	24.00	22.87	22.18	22.53
			1	7	24.00	23.21	22.45	22.59
			1	14	24.00	23.31	22.20	22.40
			8	0	22.00	21.76	21.36	21.21
			8	4	22.00	21.71	21.36	21.42
			8	7	22.00	21.79	21.29	21.47
			15	0	22.00	21.74	21.50	21.36
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23035/701.5	23095/707.5	23155/713.5
LTE Band 12	5MHz	QPSK	1	0	24.00	23.16	23.13	23.19
			1	12	24.00	23.58	23.83	23.28
			1	24	24.00	23.45	23.43	23.43
			12	0	23.00	22.49	22.65	22.60
			12	6	23.00	22.63	22.75	22.61
			12	11	23.00	22.59	22.57	22.41
			25	0	23.00	22.42	22.59	22.42
		16QAM	1	0	24.00	22.57	22.34	22.51
			1	12	24.00	23.29	22.74	22.51
			1	24	24.00	22.42	22.31	22.53
			12	0	22.00	21.32	21.14	21.42
			12	6	22.00	21.61	21.23	21.42
			12	11	22.00	21.42	21.23	21.33
			25	0	22.00	21.32	21.35	21.44
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23060/704	23095/707.5	23130/711
LTE Band 12	10MHz	QPSK	1	0	24.00	23.45	23.37	23.39
			1	24	24.00	23.93	23.73	23.52
			1	49	24.00	23.76	23.41	23.30
			25	0	23.00	22.43	22.59	22.75
			25	12	23.00	22.59	22.69	22.62
			25	24	23.00	22.66	22.56	22.43
			50	0	23.00	22.50	22.64	22.61
		16QAM	1	0	24.00	22.84	22.18	22.26
			1	24	24.00	23.78	22.17	22.60

			1	49	24.00	23.17	22.08	22.35
			25	0	22.00	21.44	21.69	21.73
			25	12	22.00	21.50	21.79	21.51
			25	24	22.00	21.56	21.51	21.46
			50	0	22.00	21.29	21.46	21.60

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23755/706.5	23790/710	23825/713.5
LTE Band 17	5MHz	QPSK	1	0	22.00	21.58	21.81	21.54
			1	12	22.00	21.97	21.71	21.77
			1	24	22.00	21.73	21.41	21.71
			12	0	22.00	21.04	20.94	20.80
			12	6	22.00	21.13	20.97	20.85
			12	11	22.00	21.02	20.74	20.73
			25	0	22.00	21.05	20.90	20.77
		16QAM	1	0	22.00	20.85	21.16	20.54
			1	12	22.00	21.09	20.81	20.60
			1	24	22.00	20.60	20.16	20.43
			12	0	20.00	19.50	19.94	19.68
			12	6	20.00	19.57	19.87	19.76
			12	11	20.00	19.54	19.45	19.39
			25	0	20.00	19.92	19.83	19.76
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23780/709	23790/710	23800/711
LTE Band 17	10MHz	QPSK	1	0	23.00	22.30	21.66	21.95
			1	24	23.00	22.35	21.84	21.72
			1	49	23.00	21.60	21.53	21.49
			25	0	22.00	21.08	21.03	20.92
			25	12	22.00	21.00	20.94	20.77
			25	24	22.00	20.78	20.78	20.65
			50	0	21.00	20.92	20.89	20.90
		16QAM	1	0	22.00	21.70	20.55	20.81
			1	24	22.00	21.96	20.38	20.79
			1	49	22.00	21.19	20.34	20.44
			25	0	21.00	20.10	20.00	19.84
			25	12	21.00	20.09	19.78	19.82

			25	24	21.00	19.66	19.64	19.61
			50	0	20.00	19.99	19.76	19.72

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		26697/814.7	26865/831.5	27033/848.3
LTE Band 26	1.4MHz	QPSK	1	0	23.00	21.98	22.72	22.65
			1	2	23.00	22.81	22.80	22.76
			1	5	23.00	22.78	22.77	22.90
			3	0	24.00	22.74	22.95	22.87
			3	1	24.00	22.90	23.05	22.87
			3	2	24.00	22.82	23.06	22.79
			6	0	23.00	21.97	22.11	21.96
		16QAM	1	0	22.00	21.81	21.68	21.56
			1	2	22.00	21.94	21.62	21.71
			1	5	22.00	21.92	21.49	21.70
			3	0	23.00	21.72	21.61	22.18
			3	1	23.00	21.80	21.53	22.12
			3	2	23.00	21.73	21.54	22.11
			6	0	22.00	20.77	20.91	21.32

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		26705/815.5	26865/831.5	27025/847.5
LTE Band 26	3MHz	QPSK	1	0	24.00	22.98	22.88	22.90
			1	7	24.00	22.92	22.79	23.09
			1	14	24.00	22.93	23.06	22.94
			8	0	23.00	22.00	22.01	21.90
			8	4	23.00	22.05	22.01	22.02
			8	7	23.00	22.11	21.98	21.84
			15	0	23.00	22.13	21.95	21.88
		16QAM	1	0	23.00	22.50	21.66	21.48
			1	7	23.00	22.44	21.86	21.75
			1	14	23.00	22.47	21.57	21.56
			8	0	22.00	21.05	20.80	20.83
			8	4	22.00	21.06	20.73	21.06
			8	7	22.00	21.20	20.79	21.00
			15	0	21.00	20.97	20.89	21.00

Band	Band	Modulation	RB	Tune-up	Channel/Frequency(MHz)
------	------	------------	----	---------	------------------------

	Width		Configuration					
			RB Size	RB Offset		26715/816.5	26865/831.5	27015/846.5
LTE Band 26	5MHz	QPSK	1	0	24.00	22.71	22.61	22.60
			1	12	24.00	23.56	22.74	22.81
			1	24	24.00	22.94	22.71	22.84
			12	0	23.00	22.05	22.06	21.62
			12	6	23.00	22.27	22.00	21.84
			12	11	23.00	22.01	22.08	21.91
			25	0	23.00	22.01	22.05	21.83
		16QAM	1	0	23.00	21.94	21.87	21.91
			1	12	23.00	22.04	21.53	21.71
			1	24	23.00	21.72	21.25	21.82
			12	0	21.00	20.88	20.63	20.70
			12	6	21.00	20.89	20.64	20.93
			12	11	21.00	20.85	20.70	20.82
			25	0	22.00	21.12	20.82	20.75
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		26750/820	26865/831.5	26990/844
LTE Band 26	10MHz	QPSK	1	0	24.00	23.16	23.04	22.90
			1	24	24.00	23.13	23.06	23.03
			1	49	24.00	23.11	22.84	22.81
			25	0	23.00	22.13	22.08	21.89
			25	12	23.00	22.07	21.95	21.91
			25	24	23.00	21.97	21.97	21.83
			50	0	23.00	22.17	21.99	21.89
		16QAM	1	0	23.00	22.54	21.57	21.71
			1	24	23.00	22.59	21.59	22.00
			1	49	23.00	22.44	21.03	21.78
			25	0	22.00	21.20	21.25	20.87
			25	12	22.00	21.14	21.20	20.81
			25	24	22.00	20.96	21.03	20.78
			50	0	22.00	21.03	21.21	20.83
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		26775/822.5	26865/831.5	26965/841.5
LTE	15MHz	QPSK	1	0	24.00	23.19	22.79	22.70

Band 26			1	37	24.00	23.16	23.00	22.79
			1	74	24.00	23.35	22.90	22.69
			36	0	23.00	22.12	22.02	21.98
			36	18	23.00	22.18	22.03	21.96
			36	37	23.00	22.12	22.02	21.92
			75	0	23.00	22.04	22.00	21.89
		16QAM	1	0	23.00	22.74	21.80	22.05
			1	37	23.00	22.50	21.99	22.02
			1	74	23.00	22.21	21.67	22.67
			36	0	22.00	21.02	21.21	20.89
			36	18	22.00	20.97	21.09	20.83
			36	37	22.00	21.06	21.05	20.89
			75	0	22.00	21.03	20.97	20.82

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		39675/2498.5	40620/2593	41565/2687.5
LTE Band 41	5MHz	QPSK	1	0	25.00	23.88	23.70	23.17
			1	12	25.00	24.15	24.14	23.76
			1	24	25.00	23.77	23.92	23.14
			12	0	24.00	23.06	22.99	22.21
			12	6	24.00	23.14	22.92	22.11
			12	11	24.00	23.15	22.95	22.14
			25	0	24.00	23.03	22.91	22.18
		16QAM	1	0	23.00	22.61	22.61	22.01
			1	12	23.00	22.87	22.74	22.23
			1	24	23.00	22.78	22.55	21.86
			12	0	23.00	22.27	22.04	21.19
			12	6	23.00	22.19	22.01	21.23
			12	11	23.00	22.42	22.09	21.21
			25	0	23.00	22.54	21.83	21.21
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		39700/2501	40620/2593	41540/2685
LTE Band 41	10MHz	QPSK	1	0	25.00	24.24	23.80	23.28
			1	24	25.00	24.26	23.79	23.22
			1	49	25.00	24.45	23.94	23.14
			25	0	24.00	23.17	23.00	22.32

			25	12	24.00	23.15	23.09	22.26
			25	24	24.00	23.28	22.93	22.17
			50	0	24.00	23.13	22.97	22.30
		16QAM	1	0	24.00	23.60	22.10	22.32
			1	24	24.00	23.77	22.08	22.75
			1	49	24.00	23.91	22.00	22.60
			25	0	23.00	22.41	21.93	21.34
			25	12	23.00	22.36	21.91	21.18
			25	24	23.00	22.31	21.96	21.22
			50	0	23.00	22.19	22.04	21.32
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		39725/2503.5	40620/2593	41515/2682.5
LTE Band 41	15MHz	QPSK	1	0	25.00	24.04	23.78	23.12
			1	37	25.00	24.17	24.01	23.34
			1	74	25.00	24.09	23.79	23.10
			36	0	24.00	23.00	22.98	22.19
			36	18	24.00	23.16	23.08	22.17
			36	37	24.00	23.25	23.31	22.23
			75	0	24.00	23.14	22.95	22.28
		16QAM	1	0	24.00	23.60	22.32	22.22
			1	37	24.00	23.80	22.39	22.12
			1	74	24.00	23.82	22.31	22.10
			36	0	23.00	22.09	22.14	21.10
			36	18	23.00	22.24	22.14	21.14
			36	37	23.00	22.27	22.11	21.16
			75	0	23.00	22.19	22.12	21.33
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		39750/2506	40620/2593	41490/2680
LTE Band 41	20MHz	QPSK	1	0	25.00	23.52	23.88	23.04
			1	49	25.00	24.02	24.14	23.41
			1	99	25.00	23.74	23.99	23.46
			50	0	24.00	23.01	23.09	22.01
			50	24	24.00	23.26	23.08	22.16
			50	49	24.00	23.20	22.96	22.19
			100	0	24.00	22.98	23.08	22.26
		16QAM	1	0	24.00	22.75	22.23	22.22

			1	49	24.00	23.01	22.26	22.20
			1	99	24.00	22.75	22.18	22.07
			50	0	23.00	22.27	22.33	21.18
			50	24	23.00	22.41	22.17	21.19
			50	49	23.00	22.37	22.30	21.32
			100	0	23.00	22.13	22.32	21.28

7.3. WLAN Output Power

7.3.1. Output Power Results Of WLAN

Mode	Channel	Frequency (MHz)	Tune-up	Output Power (dBm)
802.11b	1	2412	13.00	11.76
	6	2437	13.00	12.40
	11	2462	13.00	12.36
802.11g	1	2412	12.00	11.05
	6	2437	12.00	11.35
	11	2462	12.00	11.62
802.11n HT20	1	2412	12.00	11.03
	6	2437	12.00	11.21
	11	2462	12.00	11.53
802.11n HT40	3	2422	12.00	10.92
	6	2437	12.00	11.10
	9	2452	12.00	11.65

NOTE: Power measurement results of WLAN 2.4G.

Mode	Channel	Frequency (MHz)	Tune-up	Output Power (dBm)
802.11a	36	5180	11.00	10.30
	40	5200	11.00	10.36
	48	5240	11.00	10.24
802.11n HT20	36	5180	11.00	10.20
	40	5200	11.00	10.32
	48	5240	11.00	10.23
802.11n HT40	38	5190	6.00	5.67
	46	5230	6.00	5.76
802.11ac VHT20	36	5180	11.00	10.25
	40	5200	11.00	10.27
	48	5240	11.00	10.35
802.11ac VHT40	38	5190	11.00	10.03
	46	5230	11.00	10.30
802.11ac	42	5210	11.00	10.37


VHT80

NOTE: Power measurement results of WLAN 5.2G.

Mode	Channel	Frequency (MHz)	Tune-up	Output Power (dBm)
802.11a	149	5745	11.00	9.49
	157	5785	11.00	10.42
	165	5825	11.00	10.62
802.11n HT20	149	5745	11.00	9.58
	157	5785	11.00	9.71
	165	5825	11.00	10.41
802.11n HT40	151	5755	11.00	9.53
	159	5795	11.00	10.08
802.11ac VHT20	149	5745	11.00	9.54
	157	5785	11.00	9.91
	165	5825	11.00	10.46
802.11ac VHT40	151	5755	11.00	9.48
	159	5795	11.00	10.10
802.11ac VHT80	155	5775	10.00	9.35

NOTE: Power measurement results of WLAN 5.8G.

8. Antenna Location



Distance of the Antenna to the EUT surface/edge						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WCDMA/LTE Main	≤ 25mm	≤ 25mm	≤ 25mm	≤ 25mm	≤ 25mm	>25mm
WLAN	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	>25mm	>25mm
Positions for SAR tests						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WCDMA/LTE Main	Yes	Yes	Yes	Yes	Yes	NO
WLAN	Yes	Yes	NO	Yes	NO	NO

9. SAR Results

9.1. SAR measurement results

9.1.1. SAR measurement Result of WCDMA Band 2

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	9400/1880	RMC12.2K	0.513	0.304	-2.33	23.34	24.00	0.597
Back Side	9400/1880	RMC12.2K	0.651	0.383	-1.56	23.34	24.00	0.758
Left Side	9400/1880	RMC12.2K	0.466	0.277	-1.90	23.34	24.00	0.542
Right Side	9400/1880	RMC12.2K	0.351	0.205	-2.91	23.34	24.00	0.409
Top Side	9400/1880	RMC12.2K	0.520	0.307	-0.53	23.34	24.00	0.605

NOTE: Hotspot SAR test results of WCDMA Band 2

9.1.2. SAR measurement Result of WCDMA Band 5

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	4182/836.4	RMC12.2K	0.426	0.327	2.46	22.99	23.50	0.479
Back Side	4182/836.4	RMC12.2K	0.708	0.538	-0.55	22.99	23.50	0.796
Left Side	4182/836.4	RMC12.2K	0.334	0.253	-0.83	22.99	23.50	0.376
Right Side	4182/836.4	RMC12.2K	0.359	0.272	-0.49	22.99	23.50	0.404
Top Side	4182/836.4	RMC12.2K	0.531	0.402	2.99	22.99	23.50	0.597

NOTE: Hotspot SAR test results of WCDMA Band 5

9.1.3. SAR measurement Result of LTE Band 2

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conduc ted power (dBm)	Tune-u p power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	18900/1880	20M QPSK(1,49)	0.679	0.415	0.43	23.50	24.00	0.762
Back Side	18900/1880	20M QPSK(1,49)	0.545	0.333	0.14	23.50	24.00	0.612
Left Side	18900/1880	20M QPSK(1,49)	0.451	0.262	-1.65	23.50	24.00	0.506
Right Side	18900/1880	20M	0.350	0.203	-0.89	23.50	24.00	0.393

		QPSK(1,49)						
Top Side	18900/1880	20M QPSK(1,49)	0.318	0.194	4.14	23.50	24.00	0.357
50%RB								
Front Side	18900/1880	1.4M QPSK(3,1)	0.610	0.391	-1.00	23.17	24.00	0.738
Back Side	18900/1880	1.4M QPSK(3,1)	0.602	0.373	-2.76	23.17	24.00	0.729
Left Side	18900/1880	1.4M QPSK(3,1)	0.426	0.236	-3.24	23.17	24.00	0.516
Right Side	18900/1880	1.4M QPSK(3,1)	0.332	0.186	-4.23	23.17	24.00	0.402
Top Side	18900/1880	1.4M QPSK(3,1)	0.294	0.170	4.87	23.17	24.00	0.356

NOTE: Hotspot SAR test results of LTE Band 2

9.1.4. SAR measurement Result of LTE Band 4

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conduc ted power (dBm)	Tune-u p power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	20175/1732. 5	20M QPSK(1,0)	0.236	0.176	-3.44	22.82	24.00	0.310
Back Side	20175/1732. 5	20M QPSK(1,0)	0.601	0.516	-0.05	22.82	24.00	0.789
Left Side	20175/1732. 5	20M QPSK(1,0)	0.257	0.193	4.01	22.82	24.00	0.337
Right Side	20175/1732. 5	20M QPSK(1,0)	0.284	0.214	-1.46	22.82	24.00	0.373
Top Side	20175/1732. 5	20M QPSK(1,0)	0.335	0.253	-0.79	22.82	24.00	0.440
50%RB								
Front Side	20175/1732. 5	1.4M QPSK(3,1)	0.201	0.153	1.58	22.85	24.00	0.262
Back Side	20175/1732. 5	1.4M QPSK(3,1)	0.556	0.426	-0.44	22.85	24.00	0.725
Left Side	20175/1732. 5	1.4M QPSK(3,1)	0.224	0.164	4.81	22.85	24.00	0.292
Right Side	20175/1732. 5	1.4M QPSK(3,1)	0.208	0.153	0.33	22.85	24.00	0.271
Top Side	20175/1732. 5	1.4M QPSK(3,1)	0.255	0.196	2.07	22.85	24.00	0.332

NOTE: Hotspot SAR test results of LTE Band 4

9.1.5. SAR measurement Result of LTE Band 5

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	20525/836.5	10M QPSK(1,24)	0.179	0.132	3.24	21.91	23.00	0.230
Back Side	20525/836.5	10M QPSK(1,24)	0.145	0.103	-4.21	21.91	23.00	0.186
Left Side	20525/836.5	10M QPSK(1,24)	0.138	0.104	-4.07	21.91	23.00	0.177
Right Side	20525/836.5	10M QPSK(1,24)	0.085	0.059	-3.23	21.91	23.00	0.109
Top Side	20525/836.5	10M QPSK(1,24)	0.071	0.052	-4.07	21.91	23.00	0.091
50%RB								
Front Side	20525/836.5	1.4M QPSK(3,1)	0.158	0.118	1.35	22.29	23.00	0.186
Back Side	20525/836.5	1.4M QPSK(3,1)	0.131	0.093	-0.35	22.29	23.00	0.154
Left Side	20525/836.5	1.4M QPSK(3,1)	0.121	0.098	-4.61	22.29	23.00	0.142
Right Side	20525/836.5	1.4M QPSK(3,1)	0.075	0.054	3.31	22.29	23.00	0.088
Top Side	20525/836.5	1.4M QPSK(3,1)	0.067	0.046	1.53	22.29	23.00	0.079

NOTE: Hotspot SAR test results of LTE Band 5

9.1.6. SAR measurement Result of LTE Band 12

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	23095/707.5	10M QPSK(1,24)	0.070	0.054	-1.33	23.73	24.00	0.074
Back Side	23095/707.5	10M QPSK(1,24)	0.056	0.043	-4.13	23.73	24.00	0.060

Left Side	23095/707.5	10M QPSK(1,24)	0.050	0.043	-0.56	23.73	24.00	0.053
Right Side	23095/707.5	10M QPSK(1,24)	0.030	0.023	-1.42	23.73	24.00	0.032
Top Side	23095/707.5	10M QPSK(1,24)	0.025	0.015	0.69	23.73	24.00	0.027
50%RB								
Front Side	23095/707.5	1.4M QPSK(3,1)	0.065	0.050	2.06	23.77	24.00	0.069
Back Side	23095/707.5	1.4M QPSK(3,1)	0.049	0.039	-4.23	23.77	24.00	0.052
Left Side	23095/707.5	1.4M QPSK(3,1)	0.045	0.039	-4.03	23.77	24.00	0.047
Right Side	23095/707.5	1.4M QPSK(3,1)	0.026	0.022	2.01	23.77	24.00	0.027
Top Side	23095/707.5	1.4M QPSK(3,1)	0.023	0.014	2.93	23.77	24.00	0.024

NOTE: Hotspot SAR test results of LTE Band 12

9.1.7. SAR measurement Result of LTE Band 17

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	23790/710	10M QPSK(1,24)	0.075	0.057	-1.71	21.84	23.00	0.098
Back Side	23790/710	10M QPSK(1,24)	0.056	0.045	-3.98	21.84	23.00	0.073
Left Side	23790/710	10M QPSK(1,24)	0.057	0.042	-2.33	21.84	23.00	0.074
Right Side	23790/710	10M QPSK(1,24)	0.035	0.029	3.80	21.84	23.00	0.046
Top Side	23790/710	10M QPSK(1,24)	0.026	0.022	1.90	21.84	23.00	0.034
50%RB								
Front Side	23790/710	10M QPSK(25,0)	0.038	0.032	0.90	21.03	22.00	0.048
Back Side	23790/710	10M QPSK(25,0)	0.030	0.023	-3.20	21.03	22.00	0.038
Left Side	23790/710	10M QPSK(25,0)	0.031	0.022	2.25	21.03	22.00	0.039
Right Side	23790/710	10M QPSK(25,0)	0.018	0.015	3.19	21.03	22.00	0.023
Top Side	23790/710	10M QPSK(25,0)	0.014	0.013	1.22	21.03	22.00	0.018

NOTE: Hotspot SAR test results of LTE Band 17

9.1.8. SAR measurement Result of LTE Band 26

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	26865/831.5	15M QPSK(1,74)	0.241	0.178	-0.42	22.90	24.00	0.310
Back Side	26865/831.5	15M QPSK(1,74)	0.184	0.135	-3.94	22.90	24.00	0.237
Left Side	26865/831.5	15M QPSK(1,74)	0.187	0.137	-2.99	22.90	24.00	0.241
Right Side	26865/831.5	15M QPSK(1,74)	0.117	0.083	-2.75	22.90	24.00	0.151
Top Side	26865/831.5	15M QPSK(1,74)	0.084	0.065	-4.88	22.90	24.00	0.108
50%RB								
Front Side	26865/831.5	1.4M QPSK(3,2)	0.228	0.166	1.85	23.06	24.00	0.283
Back Side	26865/831.5	1.4M QPSK(3,2)	0.210	0.155	2.60	23.06	24.00	0.261
Left Side	26865/831.5	1.4M QPSK(3,2)	0.175	0.118	0.17	23.06	24.00	0.217
Right Side	26865/831.5	1.4M QPSK(3,2)	0.107	0.072	3.90	23.06	24.00	0.133
Top Side	26865/831.5	1.4M QPSK(3,2)	0.074	0.058	1.10	23.06	24.00	0.092

NOTE: Hotspot SAR test results of LTE Band 26

9.1.9. SAR measurement Result of LTE Band 41

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	40620/2593	20M QPSK(1,49)	0.521	0.257	-1.00	24.14	25.00	0.635

Back Side	40620/2593	20M QPSK(1,49)	0.431	0.217	-4.83	24.14	25.00	0.525
Left Side	40620/2593	20M QPSK(1,49)	0.411	0.203	1.78	24.14	25.00	0.501
Right Side	40620/2593	20M QPSK(1,49)	0.259	0.133	-0.90	24.14	25.00	0.316
Top Side	40620/2593	20M QPSK(1,49)	0.198	0.099	-2.88	24.14	25.00	0.241
50%RB								
Front Side	40620/2593	20M QPSK(50,24)	0.315	0.168	-3.43	23.08	24.00	0.644
Back Side	40620/2593	20M QPSK(50,24)	0.298	0.154	0.87	23.08	24.00	0.368
Left Side	40620/2593	20M QPSK(50,24)	0.235	0.104	-1.63	23.08	24.00	0.290
Right Side	40620/2593	20M QPSK(50,24)	0.140	0.069	-2.48	23.08	24.00	0.173
Top Side	40620/2593	20M QPSK(50,24)	0.112	0.052	3.81	23.08	24.00	0.138

NOTE: Hotspot SAR test results of LTE Band 41

9.1.10. SAR measurement Result of WLAN 2.4G

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	6/2437	802.11 b	0.128	0.071	-0.03	12.40	13.00	0.147
Back Side	6/2437	802.11 b	0.100	0.059	2.29	12.40	13.00	0.115
Right Side	6/2437	802.11 b	0.060	0.031	-4.26	12.40	13.00	0.069

NOTE: Hotspot SAR test results of WLAN 2.4G

9.1.11. SAR measurement Result of WLAN 5.2G

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	40/5200	802.11a	0.091	0.066	0.55	10.36	11.00	0.105
Back Side	40/5200	802.11a	0.067	0.048	1.71	10.36	11.00	0.078
Right Side	40/5200	802.11a	0.043	0.030	4.23	10.36	11.00	0.050

NOTE: Hotspot SAR test results of WLAN 5.2G

9.1.12. SAR measurement Result of WLAN 5.8G

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	157/5785	802.11a	0.508	0.236	-0.28	10.42	11.00	0.581
Back Side	157/5785	802.11a	0.403	0.184	-3.16	10.42	11.00	0.461
Right Side	157/5785	802.11a	0.245	0.117	-4.65	10.42	11.00	0.280

NOTE: Hotspot SAR test results of WLAN 5.2G

9.2. SAR Summation Scenario

Per KDB 447498 D01, simultaneous transmission SAR is compliant if,

- 1) Scalar SAR summation < 1.6W/kg.
- 2) $SPLSR = (SAR_1 + SAR_2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan. If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 2	WLAN 2.4G			
Hotspot	Front Side	0.597	0.147	0.744	N/A	N/A
	Back Side	0.758	0.115	0.873	N/A	N/A
	Left Side	0.542	N/A	0.542	N/A	N/A
	Right Side	0.409	0.069	0.477	N/A	N/A
	Top Side	0.605	N/A	0.605	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 2 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 5	WLAN 2.4G			
Hotspot	Front Side	0.479	0.147	0.626	N/A	N/A
	Back Side	0.796	0.115	0.911	N/A	N/A
	Left Side	0.376	N/A	0.376	N/A	N/A
	Right Side	0.404	0.069	0.473	N/A	N/A
	Top Side	0.597	N/A	0.597	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 5 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 2	WLAN 2.4G			

Hotspot	Front Side	0.762	0.147	0.909	N/A	N/A
	Back Side	0.729	0.115	0.844	N/A	N/A
	Left Side	0.516	N/A	0.516	N/A	N/A
	Right Side	0.402	0.069	0.471	N/A	N/A
	Top Side	0.357	N/A	0.357	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 2 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 4	WLAN 2.4G			
Hotspot	Front Side	0.310	0.147	0.457	N/A	N/A
	Back Side	0.789	0.115	0.903	N/A	N/A
	Left Side	0.337	N/A	0.337	N/A	N/A
	Right Side	0.373	0.069	0.442	N/A	N/A
	Top Side	0.440	N/A	0.440	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 4 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 5	WLAN 2.4G			
Hotspot	Front Side	0.230	0.147	0.377	N/A	N/A
	Back Side	0.186	0.115	0.301	N/A	N/A
	Left Side	0.177	N/A	0.177	N/A	N/A
	Right Side	0.109	0.069	0.178	N/A	N/A
	Top Side	0.091	N/A	0.091	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 5 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 12	WLAN 2.4G			
Hotspot	Front Side	0.074	0.147	0.221	N/A	N/A
	Back Side	0.060	0.115	0.174	N/A	N/A
	Left Side	0.053	N/A	0.053	N/A	N/A
	Right Side	0.032	0.069	0.101	N/A	N/A
	Top Side	0.027	N/A	0.027	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 12 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 17	WLAN 2.4G			
Hotspot	Front Side	0.098	0.147	0.245	N/A	N/A
	Back Side	0.073	0.115	0.188	N/A	N/A
	Left Side	0.074	N/A	0.074	N/A	N/A

	Right Side	0.046	0.069	0.115	N/A	N/A
	Top Side	0.034	N/A	0.034	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 17 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 26	WLAN 2.4G			
Hotspot	Front Side	0.310	0.147	0.457	N/A	N/A
	Back Side	0.237	0.115	0.352	N/A	N/A
	Left Side	0.241	N/A	0.241	N/A	N/A
	Right Side	0.151	0.069	0.220	N/A	N/A
	Top Side	0.108	N/A	0.108	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 26 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 41	WLAN 2.4G			
Hotspot	Front Side	0.644	0.147	0.791	N/A	N/A
	Back Side	0.525	0.115	0.640	N/A	N/A
	Left Side	0.501	N/A	0.501	N/A	N/A
	Right Side	0.316	0.069	0.385	N/A	N/A
	Top Side	0.241	N/A	0.241	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 41 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 2	WLAN 5.2G			
Hotspot	Front Side	0.597	0.105	0.703	N/A	N/A
	Back Side	0.758	0.078	0.835	N/A	N/A
	Left Side	0.542	N/A	0.542	N/A	N/A
	Right Side	0.409	0.050	0.458	N/A	N/A
	Top Side	0.605	N/A	0.605	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 2 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 5	WLAN 5.2G			
Hotspot	Front Side	0.479	0.105	0.585	N/A	N/A
	Back Side	0.796	0.078	0.874	N/A	N/A
	Left Side	0.376	N/A	0.376	N/A	N/A
	Right Side	0.404	0.050	0.454	N/A	N/A
	Top Side	0.597	N/A	0.597	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 5 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 2	WLAN 5.2G			
Hotspot	Front Side	0.762	0.105	0.867	N/A	N/A
	Back Side	0.729	0.078	0.806	N/A	N/A
	Left Side	0.516	N/A	0.516	N/A	N/A
	Right Side	0.402	0.050	0.452	N/A	N/A
	Top Side	0.357	N/A	0.357	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 2 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 4	WLAN 5.2G			
Hotspot	Front Side	0.310	0.105	0.415	N/A	N/A
	Back Side	0.789	0.078	0.866	N/A	N/A
	Left Side	0.337	N/A	0.337	N/A	N/A
	Right Side	0.373	0.050	0.422	N/A	N/A
	Top Side	0.440	N/A	0.440	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 4 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 5	WLAN 5.2G			
Hotspot	Front Side	0.230	0.105	0.336	N/A	N/A
	Back Side	0.186	0.078	0.264	N/A	N/A
	Left Side	0.177	N/A	0.177	N/A	N/A
	Right Side	0.109	0.050	0.159	N/A	N/A
	Top Side	0.091	N/A	0.091	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 5 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 12	WLAN 5.2G			
Hotspot	Front Side	0.074	0.105	0.180	N/A	N/A
	Back Side	0.060	0.078	0.137	N/A	N/A
	Left Side	0.053	N/A	0.053	N/A	N/A
	Right Side	0.032	0.050	0.082	N/A	N/A
	Top Side	0.027	N/A	0.027	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 12 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 17	WLAN 5.2G			

Hotspot	Front Side	0.098	0.105	0.203	N/A	N/A
	Back Side	0.073	0.078	0.151	N/A	N/A
	Left Side	0.074	N/A	0.074	N/A	N/A
	Right Side	0.046	0.050	0.096	N/A	N/A
	Top Side	0.034	N/A	0.034	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 17 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 26	WLAN 5.2G			
Hotspot	Front Side	0.310	0.105	0.416	N/A	N/A
	Back Side	0.237	0.078	0.315	N/A	N/A
	Left Side	0.241	N/A	0.241	N/A	N/A
	Right Side	0.151	0.050	0.201	N/A	N/A
	Top Side	0.108	N/A	0.108	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 26 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 41	WLAN 5.2G			
Hotspot	Front Side	0.644	0.105	0.749	N/A	N/A
	Back Side	0.525	0.078	0.603	N/A	N/A
	Left Side	0.501	N/A	0.501	N/A	N/A
	Right Side	0.316	0.050	0.366	N/A	N/A
	Top Side	0.241	N/A	0.241	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 41 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 2	WLAN 5.8G			
Hotspot	Front Side	0.597	0.581	1.178	N/A	N/A
	Back Side	0.758	0.461	1.218	N/A	N/A
	Left Side	0.542	N/A	0.542	N/A	N/A
	Right Side	0.409	0.280	0.689	N/A	N/A
	Top Side	0.605	N/A	0.605	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 2 and WLAN 5.8G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 5	WLAN 5.8G			
Hotspot	Front Side	0.479	0.581	1.060	N/A	N/A
	Back Side	0.796	0.461	1.257	N/A	N/A

	Left Side	0.376	N/A	0.376	N/A	N/A
	Right Side	0.404	0.280	0.684	N/A	N/A
	Top Side	0.597	N/A	0.597	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 5 and WLAN 5.8G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 2	WLAN 5.8G			
Hotspot	Front Side	0.762	0.581	1.342	N/A	N/A
	Back Side	0.729	0.461	1.189	N/A	N/A
	Left Side	0.516	N/A	0.516	N/A	N/A
	Right Side	0.402	0.280	0.682	N/A	N/A
	Top Side	0.357	N/A	0.357	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 2 and WLAN 5.8G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 4	WLAN 5.8G			
Hotspot	Front Side	0.310	0.581	0.890	N/A	N/A
	Back Side	0.789	0.461	1.249	N/A	N/A
	Left Side	0.337	N/A	0.337	N/A	N/A
	Right Side	0.373	0.280	0.653	N/A	N/A
	Top Side	0.440	N/A	0.440	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 4 and WLAN 5.8G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 5	WLAN 5.8G			
Hotspot	Front Side	0.230	0.581	0.811	N/A	N/A
	Back Side	0.186	0.461	0.647	N/A	N/A
	Left Side	0.177	N/A	0.177	N/A	N/A
	Right Side	0.109	0.280	0.389	N/A	N/A
	Top Side	0.091	N/A	0.091	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 5 and WLAN 5.8G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 12	WLAN 5.8G			
Hotspot	Front Side	0.074	0.581	0.655	N/A	N/A
	Back Side	0.060	0.461	0.520	N/A	N/A
	Left Side	0.053	N/A	0.053	N/A	N/A
	Right Side	0.032	0.280	0.312	N/A	N/A
	Top Side	0.027	N/A	0.027	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 12 and WLAN 5.8G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 17	WLAN 5.8G			
Hotspot	Front Side	0.098	0.581	0.679	N/A	N/A
	Back Side	0.073	0.461	0.534	N/A	N/A
	Left Side	0.074	N/A	0.074	N/A	N/A
	Right Side	0.046	0.280	0.326	N/A	N/A
	Top Side	0.034	N/A	0.034	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 17 and WLAN 5.8G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 26	WLAN 5.8G			
Hotspot	Front Side	0.310	0.581	0.891	N/A	N/A
	Back Side	0.237	0.461	0.698	N/A	N/A
	Left Side	0.241	N/A	0.241	N/A	N/A
	Right Side	0.151	0.280	0.431	N/A	N/A
	Top Side	0.108	N/A	0.108	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 26 and WLAN 5.8G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 41	WLAN 5.8G			
Hotspot	Front Side	0.644	0.581	1.225	N/A	N/A
	Back Side	0.525	0.461	0.986	N/A	N/A
	Left Side	0.501	N/A	0.501	N/A	N/A
	Right Side	0.316	0.280	0.596	N/A	N/A
	Top Side	0.241	N/A	0.241	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 41 and WLAN 5.8G.

10. Appendix A. Photo documentation

Refer to appendix Test Setup photo---SAR

11. Appendix B. System Check Plots

Table of contents
MEASUREMENT 1 System Performance Check - SID750 - Body
MEASUREMENT 2 System Performance Check - SID835 - Body
MEASUREMENT 3 System Performance Check - SID1800 - Body
MEASUREMENT 4 System Performance Check - SID1900 - Body
MEASUREMENT 5 System Performance Check - SID2450 - Body
MEASUREMENT 6 System Performance Check - SID2600 - Body
MEASUREMENT 7 System Performance Check - SID5200 - Body
MEASUREMENT 8 System Performance Check - SID5800 - Body

MEASUREMENT 1


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW750</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	750.000000
Relative permittivity (real part)	55.230248
Relative permittivity (imaginary part)	23.363842
Conductivity (S/m)	0.970318
Variation (%)	-1.490000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=3.00

SAR Peak: 1.30 W/kg

SAR 10g (W/Kg)	0.604281
SAR 1g (W/Kg)	0.828263



MEASUREMENT 2


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW835</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative permittivity (real part)	54.321111
Relative permittivity (imaginary part)	21.793359
Conductivity (S/m)	1.011236
Variation (%)	-1.200000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 1.23 W/kg

SAR 10g (W/Kg)	0.672123
SAR 1g (W/Kg)	0.950356



MEASUREMENT 3


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW1800</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1800.000000
Relative permittivity (real part)	53.173510
Relative permittivity (imaginary part)	15.434016
Conductivity (S/m)	1.543096
Variation (%)	2.020000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 6.82 W/kg

SAR 10g (W/Kg)	2.177379
SAR 1g (W/Kg)	3.819268



MEASUREMENT 4


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW1900</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative permittivity (real part)	52.503335
Relative permittivity (imaginary part)	14.853503
Conductivity (S/m)	1.569566
Variation (%)	3.460000

SURFACE SAR





VOLUME SAR



Maximum location: X=5.00, Y=2.00

SAR Peak: 6.39 W/kg

SAR 10g (W/Kg)	2.189329
SAR 1g (W/Kg)	3.922402




MEASUREMENT 5

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7, dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2450</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	2450.000000
Relative permittivity (real part)	52.021497
Relative permittivity (imaginary part)	14.933566
Conductivity (S/m)	2.032816
Variation (%)	1.420000



Maximum location: X=0.00, Y=1.00

SAR Peak: 8.46 W/kg

SAR 10g (W/Kg)	2.541285
SAR 1g (W/Kg)	5.267270



MEASUREMENT 6


A. Experimental conditions.

Area Scan	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
ZoomScan	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW2600</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2600.000000
Relative permittivity (real part)	52.602866
Relative permittivity (imaginary part)	15.280101
Conductivity (S/m)	2.213465
Variation (%)	3.220000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=2.00

SAR Peak: 9.99 W/kg

SAR 10g (W/Kg)	2.339324
SAR 1g (W/Kg)	5.200188




MEASUREMENT 7

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW5200</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results

Frequency (MHz)	5200.000000
Relative permittivity (real part)	49.662845
Relative permittivity (imaginary part)	18.301441
Conductivity (S/m)	5.293842
Variation (%)	4.490000




Maximum location: X=0.00, Y=6.00


SAR Peak: 49.61 W/kg

SAR 10g (W/Kg)	5.510184
SAR 1g (W/Kg)	15.677246


Z (m m)	0.00	2.00	4.00	6.00	8.00	10.0	12.0	14.0	16.0	18.0	20.0	22.0
SAR (W/ Kg)	46.6 150	27.5 644	14.0 668	7.05 91	3.59 28	1.78 02	0.89 38	0.46 70	0.24 75	0.13 53	0.06 50	0.04 000



3D screen shot



Hot spot position




MEASUREMENT 8

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW5800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	5800.000000
Relative permittivity (real part)	48.350523
Relative permittivity (imaginary part)	18.820043
Conductivity (S/m)	6.061524
Variation (%)	1.340000



Maximum location: X=0.00, Y=6.00

SAR Peak: 51.30 W/kg

SAR 10g (W/Kg)	5.840184
SAR 1g (W/Kg)	16.911052



12. Appendix C. Plots of High SAR Measurement

Table of contents
MEASUREMENT 1 WLAN 5.2G Body
MEASUREMENT 2 WLAN 5.8G Body
MEASUREMENT 3 WLAN 2.4G Body
MEASUREMENT 4 LTE Band 2 Body
MEASUREMENT 5 LTE Band 4 Body
MEASUREMENT 6 LTE Band 5 Body
MEASUREMENT 7 LTE Band 12 Body
MEASUREMENT 8 LTE Band 17 Body
MEASUREMENT 9 LTE Band 26 Body
MEASUREMENT 10 LTE Band 41 Body
MEASUREMENT 11 WCDMA Band 2 Body
MEASUREMENT 12 WCDMA Band 5 Body

MEASUREMENT 1


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11a U-NII</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11a (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	5200.000000
Relative permittivity (real part)	49.659538
Relative permittivity (imaginary part)	18.295509
Conductivity (S/m)	5.285369
Variation (%)	0.550000

SURFACE SAR




VOLUME SAR





Maximum location: X=-5.00, Y=-23.00

SAR Peak: 0.17 W/kg

SAR 10g (W/Kg)	0.065657
SAR 1g (W/Kg)	0.090921



3D screen shot	Hot spot position
	

MEASUREMENT 2


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11a U-NII</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11a (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	5785.000000
Relative permittivity (real part)	48.428703
Relative permittivity (imaginary part)	18.696766
Conductivity (S/m)	6.008933
Variation (%)	-0.280000

SURFACE SAR




VOLUME SAR





Maximum location: X=12.00, Y=-30.00

SAR Peak: 1.46 W/kg

SAR 10g (W/Kg)	0.235898
SAR 1g (W/Kg)	0.507892



3D screen shot	Hot spot position
	

MEASUREMENT 3


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11b ISM</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11b (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2437.000000
Relative permittivity (real part)	52.081600
Relative permittivity (imaginary part)	14.885620
Conductivity (S/m)	1.849453
Variation (%)	-0.030000

SURFACE SAR





VOLUME SAR



Maximum location: X=10.00, Y=-26.00

SAR Peak: 0.23 W/kg

SAR 10g (W/Kg)	0.070669
SAR 1g (W/Kg)	0.127647



MEASUREMENT 4


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 2</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	52.585949
Relative permittivity (imaginary part)	14.946150
Conductivity (S/m)	1.560627
Variation (%)	0.430000

SURFACE SAR





VOLUME SAR



Maximum location: X=15.00, Y=39.00

SAR Peak: 1.02 W/kg

SAR 10g (W/Kg)	0.415413
SAR 1g (W/Kg)	0.679180



MEASUREMENT 5


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 4</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1732.500000
Relative permittivity (real part)	53.469101
Relative permittivity (imaginary part)	14.982650
Conductivity (S/m)	1.442080
Variation (%)	-0.050000

SURFACE SAR





VOLUME SAR



Maximum location: X=-10.00, Y=49.00

SAR Peak: 0.85 W/kg

SAR 10g (W/Kg)	0.516361
SAR 1g (W/Kg)	0.600595



MEASUREMENT 6


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 5</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.500000
Relative permittivity (real part)	54.313499
Relative permittivity (imaginary part)	21.767000
Conductivity (S/m)	1.011561
Variation (%)	3.240000

SURFACE SAR





VOLUME SAR



Maximum location: X=19.00, Y=-15.00

SAR Peak: 0.23 W/kg

SAR 10g (W/Kg)	0.131799
SAR 1g (W/Kg)	0.179113



MEASUREMENT 7


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 12</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	707.500000
Relative permittivity (real part)	55.737961
Relative permittivity (imaginary part)	23.721300
Conductivity (S/m)	0.932379
Variation (%)	-1.330000

SURFACE SAR





VOLUME SAR



Maximum location: X=10.00, Y=9.00

SAR Peak: 0.09 W/kg

SAR 10g (W/Kg)	0.054150
SAR 1g (W/Kg)	0.069820



MEASUREMENT 8


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 17</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	710.000000
Relative permittivity (real part)	55.716709
Relative permittivity (imaginary part)	23.740499
Conductivity (S/m)	0.936431
Variation (%)	-1.710000

SURFACE SAR





VOLUME SAR



Maximum location: X=14.00, Y=12.00

SAR Peak: 0.10 W/kg

SAR 10g (W/Kg)	0.057048
SAR 1g (W/Kg)	0.075491



MEASUREMENT 9


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 26</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	831.500000
Relative permittivity (real part)	54.336750
Relative permittivity (imaginary part)	21.815100
Conductivity (S/m)	1.007736
Variation (%)	-0.420000

SURFACE SAR





VOLUME SAR



Maximum location: X=7.00, Y=13.00

SAR Peak: 0.30 W/kg

SAR 10g (W/Kg)	0.177551
SAR 1g (W/Kg)	0.241041



MEASUREMENT 10


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 41</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.6)</u>


B. SAR Measurement Results

Frequency (MHz)	2593.000000
Relative permittivity (real part)	52.655445
Relative permittivity (imaginary part)	15.311440
Conductivity (S/m)	2.205698
Variation (%)	-1.000000

SURFACE SAR





VOLUME SAR



Maximum location: X=-16.00, Y=33.00

SAR Peak: 0.93 W/kg

SAR 10g (W/Kg)	0.256781
SAR 1g (W/Kg)	0.521019



MEASUREMENT 11


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band2 WCDMA1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	52.585949
Relative permittivity (imaginary part)	14.946150
Conductivity (S/m)	1.560627
Variation (%)	-1.560000

SURFACE SAR





VOLUME SAR



Maximum location: X=-26.00, Y=-56.00

SAR Peak: 1.22 W/kg

SAR 10g (W/Kg)	0.383153
SAR 1g (W/Kg)	0.650804



MEASUREMENT 12


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band5_WCDMA850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	54.313499
Relative permittivity (imaginary part)	21.767000
Conductivity (S/m)	1.011561
Variation (%)	-0.550000

SURFACE SAR





VOLUME SAR



Maximum location: X=-10.00, Y=49.00

SAR Peak: 0.84 W/kg

SAR 10g (W/Kg)	0.538017
SAR 1g (W/Kg)	0.707618



13. Appendix D. Calibration Certificate

Table of contents
E Field Probe - SN 41/18 EPGO330
750 MHz Dipole - SN 03/15 DIP 0G750-355
835 MHz Dipole - SN 03/15 DIP 0G835-347
1800 MHz Dipole - SN 03/15 DIP 1G800-349
1900 MHz Dipole - SN 03/15 DIP 1G900-350
2450 MHz Dipole - SN 03/15 DIP 2G450-352
2600 MHz Dipole - SN 03/15 DIP 2G600-356
5000-6000 MHz Dipole - SN 13/14 WGA 33
Extended Calibration Certificate



COMOSAR E-Field Probe Calibration Report

Ref : ACR.142.2.19.SATU.B

SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.
BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA
MVG COMOSAR DOSIMETRIC E-FIELD PROBE
SERIAL NO.: SN 41/18 EPG0330

Calibrated at MVG US
2105 Barrett Park Dr. - Kennesaw, GA 30144



Calibration Date: 05/21/19




Summary:

This document presents the method and results from an accredited COMOSAR Dosimetric E-Field Probe calibration performed in MVG USA using the CALISAR / CALIBAIR test bench, for use with a COMOSAR system only. All calibration results are traceable to national metrology institutions.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.142.2.19.SATU.B

	Name	Function	Date	Signature
Prepared by :	Jérôme LUC	Product Manager	5/22/2019	
Checked by :	Jérôme LUC	Product Manager	5/22/2019	
Approved by :	Kim RUTKOWSKI	Quality Manager	5/22/2019	

	Customer Name
Distribution :	CCIC SOUTHERN TESTING CO., LTD

Issue	Date	Modifications
A	5/22/2019	Initial release
B	5/27/2019	Change customer name and address



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.142.2.19.SATU.B

TABLE OF CONTENTS

1	Device Under Test	4
2	Product Description	4
2.1	General Information	4
3	Measurement Method	4
3.1	Linearity	4
3.2	Sensitivity	5
3.3	Lower Detection Limit	5
3.4	Isotropy	5
3.5	Boundary Effect	5
4	Measurement Uncertainty	5
5	Calibration Measurement Results	6
5.1	Sensitivity in air	6
5.2	Linearity	7
5.3	Sensitivity in liquid	7
5.4	Isotropy	8
6	List of Equipment	10



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.142.2.19.SATU.B

1 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR DOSIMETRIC E FIELD PROBE
Manufacturer	MVG
Model	SSE2
Serial Number	SN 41/18 EPGO330
Product Condition (new / used)	New
Frequency Range of Probe	0.15 GHz-6GHz
Resistance of Three Dipoles at Connector	Dipole 1: R1=0.186 MΩ Dipole 2: R2=0.191 MΩ Dipole 3: R3=0.201 MΩ

A yearly calibration interval is recommended.

2 PRODUCT DESCRIPTION

2.1 GENERAL INFORMATION

MVG's COMOSAR E field Probes are built in accordance to the IEEE 1528, OET 65 Bulletin C and CEI/IEC 62209 standards.



Figure 1 – MVG COMOSAR Dosimetric E field Dipole

Probe Length	330 mm
Length of Individual Dipoles	2 mm
Maximum external diameter	8 mm
Probe Tip External Diameter	2.5 mm
Distance between dipoles / probe extremity	1 mm

3 MEASUREMENT METHOD

The IEEE 1528, OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards provide recommended practices for the probe calibrations, including the performance characteristics of interest and methods by which to assess their affect. All calibrations / measurements performed meet the fore mentioned standards.

3.1 LINEARITY

The evaluation of the linearity was done in free space using the waveguide, performing a power sweep to cover the SAR range 0.01W/kg to 100W/kg.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.142.2.19.SATU.B

3.2 SENSITIVITY

The sensitivity factors of the three dipoles were determined using a two step calibration method (air and tissue simulating liquid) using waveguides as outlined in the standards.

3.3 LOWER DETECTION LIMIT

The lower detection limit was assessed using the same measurement set up as used for the linearity measurement. The required lower detection limit is 10 mW/kg.

3.4 ISOTROPY

The axial isotropy was evaluated by exposing the probe to a reference wave from a standard dipole with the dipole mounted under the flat phantom in the test configuration suggested for system validations and checks. The probe was rotated along its main axis from 0 - 360 degrees in 15 degree steps. The hemispherical isotropy is determined by inserting the probe in a thin plastic box filled with tissue-equivalent liquid, with the plastic box illuminated with the fields from a half wave dipole. The dipole is rotated about its axis (0°–180°) in 15° increments. At each step the probe is rotated about its axis (0°–360°).

3.5 BOUNDARY EFFECT

The boundary effect is defined as the deviation between the SAR measured data and the expected exponential decay in the liquid when the probe is oriented normal to the interface. To evaluate this effect, the liquid filled flat phantom is exposed to fields from either a reference dipole or waveguide. With the probe normal to the phantom surface, the peak spatial average SAR is measured and compared to the analytical value at the surface.

4 MEASUREMENT UNCERTAINTY

The guidelines outlined in the IEEE 1528, OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty associated with an E-field probe calibration using the waveguide technique. All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

Uncertainty analysis of the probe calibration in waveguide					
ERROR SOURCES	Uncertainty value (%)	Probability Distribution	Divisor	ci	Standard Uncertainty (%)
Incident or forward power	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Reflected power	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Liquid conductivity	5.00%	Rectangular	$\sqrt{3}$	1	2.887%
Liquid permittivity	4.00%	Rectangular	$\sqrt{3}$	1	2.309%
Field homogeneity	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Field probe positioning	5.00%	Rectangular	$\sqrt{3}$	1	2.887%



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.142.2.19.SATU.B

Field probe linearity	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Combined standard uncertainty					5.831%
Expanded uncertainty 95 % confidence level k = 2					12.0%

5 CALIBRATION MEASUREMENT RESULTS

Calibration Parameters	
Liquid Temperature	21 °C
Lab Temperature	21 °C
Lab Humidity	45 %


5.1 SENSITIVITY IN AIR

Normx dipole 1 ($\mu\text{V}/(\text{V}/\text{m})^2$)	Normy dipole 2 ($\mu\text{V}/(\text{V}/\text{m})^2$)	Normz dipole 3 ($\mu\text{V}/(\text{V}/\text{m})^2$)
0.92	0.79	0.63

DCP dipole 1 (mV)	DCP dipole 2 (mV)	DCP dipole 3 (mV)
90	97	92

Calibration curves $e_i=f(V)$ ($i=1,2,3$) allow to obtain H-field value using the formula:

$$E = \sqrt{E_1^2 + E_2^2 + E_3^2}$$






COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.142.2.19.SATU.B

5.2 LINEARITY

Linearity: $\pm 2.36\%$ ($\pm 0.10\text{dB}$)

5.3 SENSITIVITY IN LIQUID

Liquid	Frequency (MHz \pm 100MHz)	Permittivity	Epsilon (S/m)	ConvF
HL750	750	40.76	0.93	1.54
BL750	750	56.70	0.98	1.59
HL850	835	40.86	0.92	1.60
BL850	835	56.35	0.99	1.64
HL900	900	42.84	0.95	1.61
BL900	900	53.25	1.05	1.65
HL1800	1800	39.56	1.40	1.74
BL1800	1800	52.84	1.45	1.81
HL1900	1900	39.67	1.38	2.03
BL1900	1900	52.84	1.59	2.08
HL2000	2000	38.71	1.42	1.86
BL2000	2000	52.03	1.52	1.92
HL2450	2450	38.72	1.80	2.05
BL2450	2450	54.91	1.97	2.12
HL2600	2600	39.98	1.89	2.06
BL2600	2600	54.42	2.18	2.11
HL5200	5200	36.68	4.45	1.85
BL5200	5200	49.02	5.46	1.92
HL5400	5400	36.08	4.69	1.75
BL5400	5400	49.55	5.53	1.83
HL5600	5600	35.34	4.95	1.88
BL5600	5600	47.60	5.77	1.95
HL5800	5800	34.81	5.08	1.89
BL5800	5800	47.81	6.12	1.94

LOWER DETECTION LIMIT: 9mW/kg

Page: 7/10

This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to
be released in whole or part without written approval of MVG.




COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.142.2.19.SATU.B

5.4 ISOTROPY


HL900 MHz

- Axial isotropy: 0.05 dB
- Hemispherical isotropy: 0.07 dB



HL1800 MHz

- Axial isotropy: 0.06 dB
- Hemispherical isotropy: 0.07 dB






COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.142.2.19.SATU.B

HL5600 MHz

- Axial isotropy: 0.06 dB
- Hemispherical isotropy: 0.09 dB





COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.142.2.19.SATU.B

6 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
Flat Phantom	MVG	SN-20/09-SAM71	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rhode & Schwarz ZVA	SN100132	02/2019	02/2022
Reference Probe	MVG	EP 94 SN 37/08	10/2017	10/2019
Multimeter	Keithley 2000	1188656	01/2017	01/2020
Signal Generator	Agilent E4438C	MY49070581	01/2017	01/2020
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	HP E4418A	US38261498	01/2017	01/2020
Power Sensor	HP ECP-E26A	US37181460	01/2017	01/2020
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Waveguide	Mega Industries	069Y7-158-13-712	Validated. No cal required.	Validated. No cal required.
Waveguide Transition	Mega Industries	069Y7-158-13-701	Validated. No cal required.	Validated. No cal required.
Waveguide Termination	Mega Industries	069Y7-158-13-701	Validated. No cal required.	Validated. No cal required.
Temperature / Humidity Sensor	Control Company	150798832	11/2017	11/2020



SAR Reference Dipole Calibration Report

Ref : ACR.109.1.18.SATU.A

SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA
MVG COMOSAR REFERENCE DIPOLE

FREQUENCY: 750 MHZ

SERIAL NO.: SN 03/15 DIP 0G750-355

Calibrated at MVG US

2105 Barrett Park Dr. - Kennesaw, GA 30144



Calibration Date: 04/19/2018

Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed in MVG USA using the COMOSAR test bench. All calibration results are traceable to national metrology institutions.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.109.1.18.SATU.A

	Name	Function	Date	Signature
Prepared by :	Jérôme LUC	Product Manager	4/19/2018	<i>JS</i>
Checked by :	Jérôme LUC	Product Manager	4/19/2018	<i>JS</i>
Approved by :	Kim RUTKOWSKI	Quality Manager	4/19/2018	<i>Kim Rutkowski</i>

	Customer Name
Distribution :	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

Issue	Date	Modifications
A	4/19/2018	Initial release



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.109.1.18.SATU.A

TABLE OF CONTENTS

1	Introduction.....	4
2	Device Under Test	4
3	Product Description	4
3.1	General Information	4
4	Measurement Method	5
4.1	Return Loss Requirements	5
4.2	Mechanical Requirements	5
5	Measurement Uncertainty.....	5
5.1	Return Loss	5
5.2	Dimension Measurement	5
5.3	Validation Measurement	5
6	Calibration Measurement Results.....	6
6.1	Return Loss and Impedance In Head Liquid	6
6.2	Return Loss and Impedance In Body Liquid	6
6.3	Mechanical Dimensions	6
7	Validation measurement	7
7.1	Head Liquid Measurement	7
7.2	SAR Measurement Result With Head Liquid	8
7.3	Body Liquid Measurement	9
7.4	SAR Measurement Result With Body Liquid	10
8	List of Equipment	11



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.109.1.18.SATU.A

1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

2 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR 750 MHz REFERENCE DIPOLE
Manufacturer	MVG
Model	SID750
Serial Number	SN 03/15 DIP 0G750-355
Product Condition (new / used)	Used

A yearly calibration interval is recommended.

3 PRODUCT DESCRIPTION

3.1 GENERAL INFORMATION

MVG's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 – MVG COMOSAR Validation Dipole



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.109.1.18.SATU.A

4 MEASUREMENT METHOD

The IEEE 1528, FCC KDBs and CEI/IEC 62209 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

4.1 RETURN LOSS REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a return loss of -20 dB or better. The return loss measurement shall be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards.

4.2 MECHANICAL REQUIREMENTS

The IEEE Std. 1528 and CEI/IEC 62209 standards specify the mechanical components and dimensions of the validation dipoles, with the dimensions frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness.

5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

Frequency band	Expanded Uncertainty on Return Loss
400-6000MHz	0.1 dB

5.2 DIMENSION MEASUREMENT

The following uncertainties apply to the dimension measurements:

Length (mm)	Expanded Uncertainty on Length
3 - 300	0.05 mm

5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528, FCC KDBs, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.

Scan Volume	Expanded Uncertainty
1 g	20.3 %



SAR REFERENCE DIPOLE CALIBRATION REPORT


Ref: ACR.109.1.18.SATU.A

10 g

20.1 %


6 CALIBRATION MEASUREMENT RESULTS

6.1 RETURN LOSS AND IMPEDANCE IN HEAD LIQUID



Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
750	-35.83	-20	51.3 Ω - 1.2 j Ω

6.2 RETURN LOSS AND IMPEDANCE IN BODY LIQUID



Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
750	-32.65	-20	50.8 Ω + 2.3 j Ω

6.3 MECHANICAL DIMENSIONS

Frequency MHz	L mm		h mm		d mm	
	required	measured	required	measured	required	measured
300	420.0 \pm 1 %		250.0 \pm 1 %		6.35 \pm 1 %	

Page: 6/11

This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.109.1.18.SATU.A

450	290.0 ±1 %.		166.7 ±1 %.		6.35 ±1 %.	
750	176.0 ±1 %.	PASS	100.0 ±1 %.	PASS	6.35 ±1 %.	PASS
835	161.0 ±1 %.		89.8 ±1 %.		3.6 ±1 %.	
900	149.0 ±1 %.		83.3 ±1 %.		3.6 ±1 %.	
1450	89.1 ±1 %.		51.7 ±1 %.		3.6 ±1 %.	
1500	80.5 ±1 %.		50.0 ±1 %.		3.6 ±1 %.	
1640	79.0 ±1 %.		45.7 ±1 %.		3.6 ±1 %.	
1750	75.2 ±1 %.		42.9 ±1 %.		3.6 ±1 %.	
1800	72.0 ±1 %.		41.7 ±1 %.		3.6 ±1 %.	
1900	68.0 ±1 %.		39.5 ±1 %.		3.6 ±1 %.	
1950	66.3 ±1 %.		38.5 ±1 %.		3.6 ±1 %.	
2000	64.5 ±1 %.		37.5 ±1 %.		3.6 ±1 %.	
2100	61.0 ±1 %.		35.7 ±1 %.		3.6 ±1 %.	
2300	55.5 ±1 %.		32.6 ±1 %.		3.6 ±1 %.	
2450	51.5 ±1 %.		30.4 ±1 %.		3.6 ±1 %.	
2600	48.5 ±1 %.		28.8 ±1 %.		3.6 ±1 %.	
3000	41.5 ±1 %.		25.0 ±1 %.		3.6 ±1 %.	
3500	37.0 ±1 %.		26.4 ±1 %.		3.6 ±1 %.	
3700	34.7 ±1 %.		26.4 ±1 %.		3.6 ±1 %.	

7 VALIDATION MEASUREMENT

The IEEE Std. 1528, FCC KDBs and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

7.1 HEAD LIQUID MEASUREMENT

Frequency MHz	Relative permittivity (ϵ_r')		Conductivity (σ) S/m	
	required	measured	required	measured
300	45.3 ±5 %		0.87 ±5 %	
450	43.5 ±5 %		0.87 ±5 %	
750	41.9 ±5 %	PASS	0.89 ±5 %	PASS
835	41.5 ±5 %		0.90 ±5 %	
900	41.5 ±5 %		0.97 ±5 %	
1450	40.5 ±5 %		1.20 ±5 %	
1500	40.4 ±5 %		1.23 ±5 %	
1640	40.2 ±5 %		1.31 ±5 %	
1750	40.1 ±5 %		1.37 ±5 %	

Page: 7/11

This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.109.1.18.SATU.A

1800	40.0 ±5 %		1.40 ±5 %	
1900	40.0 ±5 %		1.40 ±5 %	
1950	40.0 ±5 %		1.40 ±5 %	
2000	40.0 ±5 %		1.40 ±5 %	
2100	39.8 ±5 %		1.49 ±5 %	
2300	39.5 ±5 %		1.67 ±5 %	
2450	39.2 ±5 %		1.80 ±5 %	
2600	39.0 ±5 %		1.96 ±5 %	
3000	38.5 ±5 %		2.40 ±5 %	
3500	37.9 ±5 %		2.91 ±5 %	

7.2 SAR MEASUREMENT RESULT WITH HEAD LIQUID

The IEEE Std. 1528 and CEI/IEC 62209 standards state that the system validation measurements should produce the SAR values shown below (for phantom thickness of 2 mm), within the uncertainty for the system validation. All SAR values are normalized to 1 W forward power. In bracket, the measured SAR is given with the used input power.

Software	OPENSAR V4
Phantom	SN 20/09 SAM71
Probe	SN 18/11 EPG122
Liquid	Head Liquid Values: ϵ_{ps}^* : 40.0 σ : 0.93
Distance between dipole center and liquid	15.0 mm
Area scan resolution	$dx=8mm/dy=8mm$
Zoon Scan Resolution	$dx=8mm/dy=8mm/dz=5mm$
Frequency	750 MHz
Input power	20 dBm
Liquid Temperature	21 °C
Lab Temperature	21 °C
Lab Humidity	45 %

Frequency MHz	1 g SAR (W/kg/W)		10 g SAR (W/kg/W)	
	required	measured	required	measured
300	2.85		1.94	
450	4.58		3.06	
750	8.49	8.56 (0.86)	5.55	5.61 (0.56)
835	9.56		6.22	
900	10.9		6.99	
1450	29		16	
1500	30.5		16.8	
1640	34.2		18.4	
1750	36.4		19.3	
1800	38.4		20.1	

Page: 8/11



This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.109.1.18.SATU.A

1900	39.7		20.5	
1950	40.5		20.9	
2000	41.1		21.1	
2100	43.6		21.9	
2300	48.7		23.3	
2450	52.4		24	
2600	55.3		24.6	
3000	63.8		25.7	
3500	67.1		25	
3700	67.4		24.2	



7.3 BODY LIQUID MEASUREMENT

Frequency MHz	Relative permittivity (ϵ_r')		Conductivity (σ) S/m	
	required	measured	required	measured
150	61.9 \pm 5 %		0.80 \pm 5 %	
300	58.2 \pm 5 %		0.92 \pm 5 %	
450	56.7 \pm 5 %		0.94 \pm 5 %	
750	55.5 \pm 5 %	PASS	0.96 \pm 5 %	PASS
835	55.2 \pm 5 %		0.97 \pm 5 %	
900	55.0 \pm 5 %		1.05 \pm 5 %	
915	55.0 \pm 5 %		1.06 \pm 5 %	
1450	54.0 \pm 5 %		1.30 \pm 5 %	
1610	53.8 \pm 5 %		1.40 \pm 5 %	
1800	53.3 \pm 5 %		1.52 \pm 5 %	
1900	53.3 \pm 5 %		1.52 \pm 5 %	
2000	53.3 \pm 5 %		1.52 \pm 5 %	
2100	53.2 \pm 5 %		1.62 \pm 5 %	

Page: 9/11

This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT



Ref: ACR.109.1.18.SATU.A

2300	52.9 ±5 %		1.81 ±5 %	
2450	52.7 ±5 %		1.95 ±5 %	
2600	52.5 ±5 %		2.16 ±5 %	
3000	52.0 ±5 %		2.73 ±5 %	
3500	51.3 ±5 %		3.31 ±5 %	
3700	51.0 ±5 %		3.55 ±5 %	
5200	49.0 ±10 %		5.30 ±10 %	
5300	48.9 ±10 %		5.42 ±10 %	
5400	48.7 ±10 %		5.53 ±10 %	
5500	48.6 ±10 %		5.65 ±10 %	
5600	48.5 ±10 %		5.77 ±10 %	
5800	48.2 ±10 %		6.00 ±10 %	

7.4 SAR MEASUREMENT RESULT WITH BODY LIQUID

Software	OPENSAR V4
Phantom	SN 20/09 SAM71
Probe	SN 18/11 EPG122
Liquid	Body Liquid Values: eps' : 56.8 sigma : 1.00
Distance between dipole center and liquid	15.0 mm
Area scan resolution	dx=8mm/dy=8mm
Zoon Scan Resolution	dx=8mm/dy=8mm/dz=5mm
Frequency	750 MHz
Input power	20 dBm
Liquid Temperature	21 °C
Lab Temperature	21 °C
Lab Humidity	45 %

Frequency MHz	1 g SAR (W/kg/W)	10 g SAR (W/kg/W)
	measured	measured
750	8.85 (0.89)	5.91 (0.59)



Page: 10/11

This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.