

FCC REPORT

Applicant: QJO Inc

Address of Applicant: 1598 nw 82 Nd ave miami fl 33126 usa

Equipment Under Test (EUT)

Product Name: smart phone

Model No.: Q55

Trade mark: QJO

FCC ID: 2ADWR-QJOQ55

Applicable standards: FCC CFR Title 47 Part 15 Subpart B

Date of sample receipt: 29 Dec., 2014

Date of Test: 29 Dec., 2014 to 06 Jan., 2015

Date of report issued: 07 Jan., 2015

Test Result: Pass *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

A blue circular stamp with the text "ZHONGJIAN NANFANG TESTING CO., LTD." around the perimeter and "CCIS" in the center. A handwritten signature in blue ink is written over the stamp.

Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	07 Jan., 2015	Original

Prepared by:

Luna Gao

Date:

07 Jan., 2015

Report Clerk

Reviewed by:

Wimer Zhang

Date:

07 Jan., 2015

Project Engineer

3 Contents

Page

1	COVER PAGE.....	1
2	VERSION.....	2
3	CONTENTS	3
4	TEST SUMMARY	4
5	GENERAL INFORMATION	5
5.1	CLIENT INFORMATION	5
5.2	GENERAL DESCRIPTION OF E.U.T.	5
5.3	TEST MODE.....	5
5.4	DESCRIPTION OF SUPPORT UNITS	6
5.5	LABORATORY FACILITY	6
5.6	LABORATORY LOCATION	6
5.7	TEST INSTRUMENTS LIST.....	7
6	TEST RESULTS AND MEASUREMENT DATA	8
6.1	CONDUCTED EMISSION.....	8
6.2	RADIATED EMISSION	13
7	TEST SETUP PHOTO.....	23
8	EUT CONSTRUCTIONAL DETAILS.....	24

4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part15.107	Pass
Radiated Emission	Part15.109	Pass

Pass: The EUT complies with the essential requirements in the standard.

5 General Information

5.1 Client Information

Applicant:	QJO Inc
Address of Applicant:	1598 nw 82 Nd ave miami fl 33126 usa
Manufacturer:	Jiuzhou Group(HK)Holdings Limited
Address of Manufacturer:	Jiuzhou Electronic Building, Hi-tech Park, Nanshan District, Shenzhen, China
Factory:	Shenzhen Ferex Electronics Co., Ltd
Address of Factory:	Block 2, Jiuzhou Industrial Park, Jiazitang Village, Gongming Town, Guangming New District, Shenzhen, China

5.2 General Description of E.U.T.

Product Name:	smart phone
Model No.:	Q55
Power supply:	Rechargeable Li-ion Battery DC3.7V-2000mAh
AC adapter :	Model: JHD-AP006U-050100BB-2 Input:100-240V AC,50/60Hz 0.2A Output:5V DC MAX 1A

5.3 Test Mode

Operating mode	Detail description
PC mode	Keep the EUT in Downloading mode(Worst case)
GPS mode	Keep the EUT in GPS mode(Worst case)
Charging+recording mode	Keep the EUT in Charging+recording mode
Charging+Play mode	Keep the EUT in Charging+Play mode
FM mode	Keep the EUT in FM receiver mode

The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

5.4 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
DELL	PC	OPTIPLEX745	N/A	DoC
DELL	MONITOR	E178FPC	N/A	DoC
DELL	KEYBOARD	SK-8115	N/A	DoC
DELL	MOUSE	MOC5UO	N/A	DoC
HP	Printer	CB495A	05257893	DoC
MERCURY	Wireless router	MW150R	12922104015	FCC ID

5.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Registration No.: 817957**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 817957, February 27, 2012.

- **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

5.6 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
Address: No.B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
Bao'an District, Shenzhen, Guangdong, China
Tel: +86-755-23118282
Fax: +86-755-23116366


5.7 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	SAEMC	9(L)*6(W)* 6(H)	CCIS0001	08-23-2014	08-22-2017
2	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	CCIS0005	04-19-2014	04-19-2015
3	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	CCIS0006	04-19-2014	04-19-2015
4	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
5	Coaxial Cable	CCIS	N/A	CCIS0016	04-01-2014	03-31-2015
6	Coaxial Cable	CCIS	N/A	CCIS0017	04-01-2014	03-31-2015
7	Coaxial cable	CCIS	N/A	CCIS0018	04-01-2014	03-31-2015
8	Coaxial Cable	CCIS	N/A	CCIS0019	04-01-2014	03-31-2015
9	Coaxial Cable	CCIS	N/A	CCIS0087	04-01-2014	03-31-2015
10	Amplifier(10kHz-1.3GHz)	HP	8447D	CCIS0003	04-01-2014	03-31-2015
11	Amplifier(1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	CCIS0011	06-09-2014	06-08-2015
12	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	04-01-2014	03-31-2015
13	Horn Antenna	ETS-LINDGREN	3160	GTS217	03-31-2014	03-29-2015
14	Printer	HP	HP LaserJet P1007	N/A	N/A	N/A
15	Positioning Controller	UC	UC3000	CCIS0015	N/A	N/A
16	Spectrum analyzer 9k-30GHz	Rohde & Schwarz	FSP	CCIS0023	04-19-2014	04-19-2015
17	EMI Test Receiver	Rohde & Schwarz	ESPI	CCIS0022	04-01-2014	03-31-2015
18	Loop antenna	Laplace instrument	RF300	EMC0701	04-01-014	03-31-2015
19	Universal radio communication tester	Rhode & Schwarz	CMU200	CCIS0069	05-29-2014	05-28-2015
20	Signal Analyzer	Rohde & Schwarz	FSIQ3	CCIS0088	04-19-2014	04-19-2015

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongShuo Electron	11.0(L)x4.0(W)x3.0(H)	CCIS0061	06-09-2014	06-08-2015
2	EMI Test Receiver	Rohde & Schwarz	ESCI	CCIS0002	04-19-2014	04-19-2015
3	LISN	CHASE	MN2050D	CCIS0074	01-10-2014	04-09-2015
4	Coaxial Cable	CCIS	N/A	CCIS0086	04-01-2014	03-31-2015

6 Test results and Measurement Data


6.1 Conducted Emission

Test Requirement:	FCC Part 15 B Section 15.107		
Test Method:	ANSI C63.4:2003		
Test Frequency Range:	150kHz to 30MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9kHz, VBW=30kHz		
Limit:	Frequency range (MHz)	Limit (dB μ V)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	0.5-30	60	50
* Decreases with the logarithm of the frequency.			
Test setup:	 <p>Remark: E.U.T.: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>		
Test procedure	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). The provide a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement. 		
Test environment:	Temp.: 23 °C	Humid.: 56%	Press.: 1 01kPa
Measurement Record:	Uncertainty: 3.28dB		
Test Instruments:	Refer to section 5.7 for details		
Test mode:	Refer to section 5.3 for details		
Test results:	Pass		

Measurement data:

PC Mode

Line:




Trace: 17

Site : CCIS Shielding Room
 Condition : FCC PART15 B QP LISN LINE
 EUT : smart phone
 Model : QJ0 Q55
 Test Mode : PC Mode
 Power Rating : AC 120V/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: MT
 Remark :

	Freq	Read	LISN	Cable	Level	Limit	Over	
	MHz	Level	Factor	Loss	Level	Line	Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.155	23.00	0.27	10.78	34.05	55.74	-21.69	Average
2	0.160	26.80	0.27	10.78	37.85	65.47	-27.62	QP
3	0.180	18.31	0.28	10.77	29.36	54.50	-25.14	Average
4	0.255	13.57	0.27	10.75	24.59	51.60	-27.01	Average
5	0.771	17.26	0.23	10.80	28.29	56.00	-27.71	QP
6	2.692	17.79	0.27	10.93	28.99	56.00	-27.01	QP
7	5.898	18.22	0.31	10.82	29.35	60.00	-30.65	QP
8	5.898	15.02	0.31	10.82	26.15	50.00	-23.85	Average
9	17.944	28.57	0.33	10.90	39.80	60.00	-20.20	QP
10	17.944	23.78	0.33	10.90	35.01	50.00	-14.99	Average
11	22.535	24.49	0.44	10.89	35.82	50.00	-14.18	Average
12	22.655	28.06	0.44	10.89	39.39	60.00	-20.61	QP

Neutral:




Trace: 19

Site : CCIS Shielding Room
Condition : FCC PART15 B QP LISN NEUTRAL
EUT : smart phone
Model : QJ0 Q55
Test Mode : PC Mode
Power Rating : AC 120V/60Hz
Environment : Temp: 23 °C Humi:56% Atmos:101KPa
Test Engineer: MT
Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.155	19.24	0.25	10.78	30.27	55.74	-25.47	Average
2	0.170	27.47	0.25	10.77	38.49	64.94	-26.45	QP
3	0.260	18.62	0.26	10.75	29.63	61.42	-31.79	QP
4	0.260	12.83	0.26	10.75	23.84	51.42	-27.58	Average
5	0.731	17.47	0.18	10.78	28.43	56.00	-27.57	QP
6	0.731	8.86	0.18	10.78	19.82	46.00	-26.18	Average
7	5.805	17.97	0.27	10.83	29.07	60.00	-30.93	QP
8	6.186	14.52	0.27	10.82	25.61	50.00	-24.39	Average
9	17.755	25.24	0.26	10.90	36.40	50.00	-13.60	Average
10	18.039	29.03	0.26	10.90	40.19	60.00	-19.81	QP
11	22.416	24.50	0.37	10.90	35.77	50.00	-14.23	Average
12	22.655	27.81	0.38	10.89	39.08	60.00	-20.92	QP

GPS Mode

Line:




Trace: 21

Site : CCIS Shielding Room
 Condition : FCC PART15 B QP LISN LINE
 EUT : smart phone
 Model : QJO Q55
 Test Mode : GPS Mode
 Power Rating : AC 120V/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: MT
 Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.178	50.53	0.28	10.77	61.58	64.59	-3.01	QP
2	0.178	36.04	0.28	10.77	47.09	54.59	-7.50	Average
3	0.226	45.09	0.27	10.75	56.11	62.61	-6.50	QP
4	0.322	25.86	0.26	10.73	36.85	49.66	-12.81	Average
5	0.343	41.00	0.27	10.73	52.00	59.13	-7.13	QP
6	0.466	39.24	0.29	10.75	50.28	56.58	-6.30	QP
7	0.466	24.65	0.29	10.75	35.69	46.58	-10.89	Average
8	0.567	22.55	0.26	10.77	33.58	46.00	-12.42	Average
9	3.922	33.83	0.28	10.89	45.00	56.00	-11.00	QP
10	4.224	18.09	0.28	10.88	29.25	46.00	-16.75	Average
11	15.635	26.53	0.32	10.91	37.76	50.00	-12.24	Average
12	18.820	41.02	0.34	10.92	52.28	60.00	-7.72	QP

Neutral:



Trace: 23



Site : CCIS Shielding Room
 Condition : FCC PART15 B QP LISN NEUTRAL
 EUT : smart phone
 Model : QJO Q55
 Test Mode : GPS Mode
 Power Rating : AC 120V/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: MT
 Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.178	49.56	0.25	10.77	60.58	64.59	-4.01	QP
2	0.178	36.07	0.25	10.77	47.09	54.59	-7.50	Average
3	0.226	44.11	0.25	10.75	55.11	62.61	-7.50	QP
4	0.322	25.86	0.26	10.73	36.85	49.66	-12.81	Average
5	0.466	38.25	0.28	10.75	49.28	56.58	-7.30	QP
6	0.466	25.66	0.28	10.75	36.69	46.58	-9.89	Average
7	0.567	23.56	0.25	10.77	34.58	46.00	-11.42	Average
8	0.958	29.11	0.21	10.86	40.18	56.00	-15.82	QP
9	3.922	32.82	0.29	10.89	44.00	56.00	-12.00	QP
10	4.224	20.08	0.29	10.88	31.25	46.00	-14.75	Average
11	15.635	27.60	0.25	10.91	38.76	50.00	-11.24	Average
12	18.820	40.10	0.26	10.92	51.28	60.00	-8.72	QP

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.

6.2 Radiated Emission

Test Requirement:	FCC Part 15 B Section 15.109				
Test Method:	ANSI C63.4:2003				
Test Frequency Range:	30MHz to 6000MHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
Peak		1MHz	10Hz	Average Value	
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.0		Quasi-peak Value
	88MHz-216MHz		43.5		Quasi-peak Value
	216MHz-960MHz		46.0		Quasi-peak Value
	960MHz-1GHz		54.0		Quasi-peak Value
	Above 1GHz		54.0		Average Value
				Peak Value	
Test setup:	Below 1GHz				
					
Test setup:	Above 1GHz				
					


Test Procedure:	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 					
Test environment:	Temp.:	25 °C	Humid.:	55%	Press.:	1 01kPa
Measurement Record:	Uncertainty: 4.88dB					
Test Instruments:	Refer to section 5.7 for details					
Test mode:	Refer to section 5.3 for details					
Test results:	Passed					

Measurement Data

PC Mode:

Below 1GHz


Horizontal:



Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M1G) HORIZONTAL
 EUT : smart phone
 Model : QJ0 Q55
 Test mode : PC Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: MT
 REMARK :

	Freq	ReadAntenna	Cable	Preamp		Limit	Over	
		Level	Factor	Loss	Factor	Level	Line	Limit
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	31.955	43.38	12.32	0.45	29.97	26.18	40.00	-13.82 QP
2	94.428	39.37	12.75	0.93	29.55	23.50	43.50	-20.00 QP
3	207.850	41.32	10.80	1.42	28.78	24.76	43.50	-18.74 QP
4	300.367	43.04	13.06	1.77	28.45	29.42	46.00	-16.58 QP
5	404.667	44.50	15.18	2.13	28.79	33.02	46.00	-12.98 QP
6	517.248	40.87	16.94	2.45	29.00	31.26	46.00	-14.74 QP

Vertical:




Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M1G) VERTICAL
 EUT : smart phone
 Model : QJ0 Q55
 Test mode : PC Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: MT
 REMARK :

	Freq	Read	Antenna	Cable	Preamp	Level	Limit	Over	
	MHz	Level	Factor	Loss	Factor	dBuV/m	dBuV/m	Limit	Remark
		dBuV	dB/m	dB	dB			dB	
1	129.923	43.64	8.93	1.19	29.33	24.43	43.50	-19.07	QP
2	196.510	42.65	10.57	1.38	28.85	25.75	43.50	-17.75	QP
3	336.035	40.68	13.99	1.89	28.53	28.03	46.00	-17.97	QP
4	365.539	40.95	14.48	2.00	28.63	28.80	46.00	-17.20	QP
5	407.515	42.74	15.22	2.14	28.79	31.31	46.00	-14.69	QP
6	517.248	42.41	16.94	2.45	29.00	32.80	46.00	-13.20	QP

Above 1GHz


Horizontal:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
 EUT : smart phone
 Model : QJ0 Q55
 Test mode : PC Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: MT
 REMARK :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier	Level	Limit	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1945.465	48.23	25.93	4.79	40.88	38.07	74.00	-35.93	Peak
2	1945.465	38.67	25.93	4.79	40.88	28.51	54.00	-25.49	Average
3	3549.432	46.90	29.08	6.18	39.96	42.20	74.00	-31.80	Peak
4	3549.432	36.49	29.08	6.18	39.96	31.79	54.00	-22.21	Average
5	4827.078	46.94	31.55	8.92	40.22	47.19	74.00	-26.81	Peak
6	4827.078	36.69	31.55	8.92	40.22	36.94	54.00	-17.06	Average

Vertical:




Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 EUT : smart phone
 Model : QJ0 Q55
 Test mode : PC Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: MT
 REMARK :

	Freq	ReadAntenna	Cable	Preamp		Limit	Over	
		Level	Factor	Loss	Factor	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	1828.018	47.58	25.44	4.70	40.96	36.76	74.00	-37.24 Peak
2	1828.018	37.58	25.44	4.70	40.96	26.76	54.00	-27.24 Average
3	3563.272	47.05	29.11	6.16	40.08	42.24	74.00	-31.76 Peak
4	3563.272	37.67	29.11	6.16	40.08	32.86	54.00	-21.14 Average
5	5499.281	47.01	32.02	9.16	40.26	47.93	74.00	-26.07 Peak
6	5499.281	37.99	32.02	9.16	40.26	38.91	54.00	-15.09 Average

GPS Mode:

Below 1GHz


Horizontal:



Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M1G) HORIZONTAL
 EUT : smart phone
 Model : QJ0 Q55
 Test mode : GPS Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: MT
 REMARK :

	Freq	ReadAntenna	Cable	Preamp		Limit	Over	
	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	92.462	42.88	12.41	0.92	29.56	26.65	43.50	-16.85 QP
2	100.229	42.99	13.11	0.96	29.53	27.53	43.50	-15.97 QP
3	195.137	40.53	10.57	1.37	28.86	23.61	43.50	-19.89 QP
4	295.147	42.74	12.95	1.76	28.46	28.99	46.00	-17.01 QP
5	404.667	42.14	15.18	2.13	28.79	30.66	46.00	-15.34 QP
6	836.244	41.88	20.46	3.23	28.06	37.51	46.00	-8.49 QP

Vertical:




Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M1G) VERTICAL
 EUT : smart phone
 Model : QJO Q55
 Test mode : GPS Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: MT
 REMARK :

	Freq	ReadAntenna	Cable	Preamp		Limit	Over	
		Level	Factor	Loss	Factor	Level	Line	Limit
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	51.301	37.57	13.19	0.62	29.81	21.57	40.00	-18.43 QP
2	83.522	40.56	9.87	0.87	29.61	21.69	40.00	-18.31 QP
3	141.330	44.84	8.20	1.27	29.27	25.04	43.50	-18.46 QP
4	401.839	44.15	15.10	2.12	28.78	32.59	46.00	-13.41 QP
5	719.200	41.56	19.05	2.96	28.59	34.98	46.00	-11.02 QP
6	833.317	45.04	20.42	3.22	28.07	40.61	46.00	-5.39 QP

Above 1GHz


Horizontal:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
 EUT : smart phone
 Model : QJ0 Q55
 Test mode : GPS Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: MT
 REMARK :

	Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1831.578	50.92	25.44	4.70	40.96	40.10	74.00	-33.90	Peak
2	1831.578	40.95	25.44	4.70	40.96	30.13	54.00	-23.87	Average
3	3487.811	49.72	28.86	6.30	39.46	45.42	74.00	-28.58	Peak
4	3487.811	39.64	28.86	6.30	39.46	35.34	54.00	-18.66	Average
5	5499.281	48.67	32.02	9.16	40.26	49.59	74.00	-24.41	Peak
6	5499.281	38.69	32.02	9.16	40.26	39.61	54.00	-14.39	Average

Vertical:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 EUT : smart phone
 Model : QJ0 Q55
 Test mode : GPS Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: MT
 REMARK :

	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over	
		Level	Factor	Loss	Factor	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	1828.018	49.00	25.44	4.70	40.96	38.18	74.00	-35.82 Peak
2	1828.018	38.56	25.44	4.70	40.96	27.74	54.00	-26.26 Average
3	3521.911	49.57	29.01	6.24	39.71	45.11	74.00	-28.89 Peak
4	3521.911	39.68	29.01	6.24	39.71	35.22	54.00	-18.78 Average
5	5553.047	47.90	32.09	9.19	40.32	48.86	74.00	-25.14 Peak
6	5553.047	37.87	32.09	9.19	40.32	38.83	54.00	-15.17 Average