

# FCC PART 15.247 TEST REPORT

For

**Telecell Mobile (H.K) Ltd.**

RM 801 Metro Ctr II, 21 Lam Hing Street, Kln Bay, Hong Kong

**FCC ID: 2ADX3A240**

<b>Report Type:</b> Original Report	<b>Product Type:</b> Mobile Phone
<b>Test Engineer:</b> <u>Kobe Li</u> <i>Kobe Li</i>	
<b>Report Number:</b> <u>RSZ160516001-00B</u>	
<b>Report Date:</b> <u>2016-05-31</u>	
<b>Reviewed By:</b> <u>RF Engineer</u> <i>Simon Wang</i>	
<b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>	

**Note:** This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	4
OBJECTIVE .....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY .....	4
TEST FACILITY .....	5
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>6</b>
SUPPORT EQUIPMENT LIST AND DETAILS .....	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP .....	7
<b>SUMMARY OF TEST RESULTS .....</b>	<b>8</b>
<b>FCC§15.247 (i), §1.1307 (b) (1) &amp;§2.1093 – RF EXPOSURE .....</b>	<b>9</b>
APPLICABLE STANDARD .....	9
<b>FCC §15.203 – ANTENNA REQUIREMENT .....</b>	<b>10</b>
APPLICABLE STANDARD .....	10
ANTENNA CONNECTOR CONSTRUCTION .....	10
<b>FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS .....</b>	<b>11</b>
APPLICABLE STANDARD .....	11
MEASUREMENT UNCERTAINTY.....	11
EUT SETUP .....	11
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE .....	12
TEST EQUIPMENT LIST AND DETAILS.....	12
CORRECTED FACTOR & MARGIN CALCULATION .....	12
TEST RESULTS SUMMARY .....	13
TEST DATA .....	13
<b>FCC §15.205, §15.209 &amp; §15.247(d) – RADIATED EMISSIONS.....</b>	<b>16</b>
APPLICABLE STANDARD .....	16
MEASUREMENT UNCERTAINTY.....	16
EUT SETUP .....	16
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....	17
TEST PROCEDURE .....	17
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	18
TEST EQUIPMENT LIST AND DETAILS.....	18
TEST RESULTS SUMMARY .....	19
TEST DATA .....	19
<b>FCC §15.247(a) (1)-CHANNEL SEPARATION TEST .....</b>	<b>21</b>
APPLICABLE STANDARD .....	21
TEST PROCEDURE .....	21
TEST EQUIPMENT LIST AND DETAILS.....	21
TEST DATA .....	21
<b>FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH.....</b>	<b>28</b>
APPLICABLE STANDARD .....	28
TEST PROCEDURE .....	28

TEST EQUIPMENT LIST AND DETAILS.....	28
TEST DATA .....	28
<b>FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST .....</b>	<b>34</b>
APPLICABLE STANDARD .....	34
TEST PROCEDURE .....	34
TEST EQUIPMENT LIST AND DETAILS.....	34
TEST DATA .....	34
<b>FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....</b>	<b>37</b>
APPLICABLE STANDARD .....	37
TEST PROCEDURE .....	37
TEST EQUIPMENT LIST AND DETAILS.....	37
TEST DATA .....	37
<b>FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT .....</b>	<b>53</b>
APPLICABLE STANDARD .....	53
TEST PROCEDURE .....	53
TEST EQUIPMENT LIST AND DETAILS.....	53
TEST DATA .....	53
<b>FCC §15.247(d) - BAND EDGES TESTING .....</b>	<b>55</b>
APPLICABLE STANDARD .....	55
TEST PROCEDURE .....	55
TEST EQUIPMENT LIST AND DETAILS.....	55
TEST DATA .....	56

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The *Telecell Mobile (H.K) Ltd.*'s product, model number: A240 (*FCC ID: 2ADX3A240*) or the "EUT" in this report was a *Mobile Phone*, which was measured approximately: 12.2 cm (L) × 5.0 cm (W) × 1.2 cm (H), rated with input voltage: DC 3.7V rechargeable Li-ion battery or DC 5.0V from adapter.

Adapter Information:

Model: DUOS A240

Input: AC 100-240V, 50/60Hz, 150mA

Output: DC 5.0V, 500mA

*Note: For the product, series model A240 and DUOS are identical schematics, the differences bewteen them are their name. A240 was selected for fully testing, the detailed differences bewteen them were explained and stated in the attached product similarity declaration letter by the applicant.*

*\*All measurement and test data in this report was gathered from production sample serial number: 1602273. (Assigned by Shenzhen BACL). The EUT supplied by the applicant was received on 2016-05-16.*

### Objective

This test report is prepared on behalf of *Telecell Mobile (H.K) Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

FCC Part 22H & 24E PCE and Part 15B JBP submissions with FCC ID: *2ADX3A240*.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.81 dB for 30MHz-1GHz, and 4.88 dB for above 1GHz, 1.95dB for conducted measurement.

## Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3<sup>rd</sup> Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on October 31, 2013. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.10-2013.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

## SYSTEM TEST CONFIGURATION

---

### Description of Test Configuration

The system was configured for testing in engineering mode.

### EUT Exercise Software

No exercise software was used.

### Special Accessories

No special accessory.

### Equipment Modifications

No modification was made to the EUT tested.

### Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
TESCOM	Bluetooth Tester	TC-3000B	3000B630010

### External I/O Cable

Cable Description	Length (m)	From Port	To
Un-shielding unDetachable USB Cable	1.0	EUT	Adapter
Un-shielding unDetachable Earphone Cable	1.1	EUT	Earphone

## Block Diagram of Test Setup

For conducted emission



**SUMMARY OF TEST RESULTS**

FCC Rules	Description of Test	Result
§15.247 (i), §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliance
§15.247(a)(1)	20 dB Emission Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band edges	Compliance



## **FCC§15.247 (i), §1.1307 (b) (1) &§2.1093 – RF EXPOSURE**

### **Applicable Standard**

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

1.  $f(\text{GHz})$  is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test Exclusion.

**For worst case:**

Frequency (MHz)	Maximum conducted Tune-up power		Calculated Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
	Power (dBm)	Power (mW)				
2480	3.50	2.239	5	0.705	3.0	Yes

**Result: No SAR test is required**

---

**FCC §15.203 – ANTENNA REQUIREMENT**

---

**Applicable Standard**

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

**Antenna Connector Construction**

The EUT has one internal antenna arrangement for bluetooth which was permanently attached and the antenna gain is -1dBi, fulfill the requirement of this section. Please refer to the EUT photos.

**Result:** Compliance.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC §15.207(a)


### Measurement Uncertainty

Input quantities to be considered for conducted disturbance measurements maybe receiver reading, attenuation of the connection between LISN and receiver, LISN voltage division factor, LISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report.

Port	Expanded Measurement uncertainty
AC Mains	3.34 dB (k=2, 95% level of confidence)
CAT 3	3.72 dB (k=2, 95% level of confidence)
CAT 5	3.74 dB (k=2, 95% level of confidence)
CAT 6	4.54 dB (k=2, 95% level of confidence)

### EUT Setup



Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

## EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

## Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2015-06-01	2016-05-31
Rohde & Schwarz	LISN	ENV216	3560.6650.12-101613-Yb	2015-12-15	2016-12-14
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2016-05-14	2017-05-14
Ducommun technologies	Conducted Emission Cable	RG-214	CB031	2015-06-15	2016-06-15
Rohde & Schwarz	CE Test software	EMC 32	V8.53	NCR	NCR

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, the worst margin reading as below:

**12.7 dB at 0.301470 MHz in the Neutral conducted mode**

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(L_m)} \leq L_{\text{lim}} + U_{\text{cispr}}$$

In BACL,  $U_{(L_m)}$  is less than  $U_{\text{cispr}}$ , if  $L_m$  is less than  $L_{\text{lim}}$ , it implies that the EUT complies with the limit.

## Test Data

### Environmental Conditions


Temperature:	25 °C
Relative Humidity:	46%
ATM Pressure:	101.0 kPa

*The testing was performed by Kobe Li on 2016-05-27.*

*EUT operation mode: Communication*

**AC 120V/60 Hz, Line:**


EMI Auto Test L



Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.249500	43.1	20	61.8	18.7	QP
0.277500	41.6	19.9	60.9	19.3	QP
0.302500	40.9	19.9	60.2	19.3	QP
0.321110	40.8	19.9	59.7	18.9	QP
0.372390	37.4	19.9	58.4	21.0	QP
1.081710	34.7	20	56	21.3	QP
0.249500	37.8	20	51.8	14.0	Ave.
0.277500	37.2	19.9	50.9	13.7	Ave.
0.302500	36	19.9	50.2	14.2	Ave.
0.321110	36.2	19.9	49.7	13.5	Ave.
0.372390	32.8	19.9	48.4	15.6	Ave.
1.081710	27.8	20	46	18.2	Ave.

**AC 120V/60 Hz, Neutral:**

EMI Auto Test N



Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.154000	41.9	20.0	65.8	23.9	QP
0.201500	46.9	20.0	63.5	16.6	QP
0.249500	42.6	20.0	61.8	19.2	QP
0.301470	42.7	19.9	60.2	17.5	QP
0.344750	39.9	19.9	59.1	19.2	QP
0.439370	31.1	19.9	57.1	26.0	QP
0.154000	30.8	20.0	55.8	25.0	Ave.
0.201500	40.4	20.0	53.5	13.1	Ave.
0.249500	38.5	20.0	51.8	13.3	Ave.
0.301470	37.5	19.9	50.2	12.7	Ave.
0.344750	35.5	19.9	49.1	13.6	Ave.
0.439370	23.9	19.9	47.1	23.2	Ave.

**Note:**

- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude

## FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS

### Applicable Standard

FCC §15.205; §15.209; §15.247(d)


### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-2:2011, the expanded combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Shenzhen) is 5.81 dB for 30MHz-1GHz, and 4.88 dB for above 1GHz. And this uncertainty will not be taken into consideration for the test data recorded in the report.

### EUT Setup

Below 1 GHz:





**Above 1GHz:**

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, 205 and FCC 15.247 limits.

**EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1 MHz	10 Hz	/	Ave.

**Test Procedure**

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

### Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	HP8447E	1937A01046	2016-05-06	2017-05-06
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2015-12-15	2016-12-14
Sunol Sciences	Bi-log Antenna	JB1	A040904-2	2014-12-07	2017-12-06
Mini	Amplifier	ZVA-183-S+	5969001149	2016-04-23	2017-04-23
A.H. System	Horn Antenna	SAS-200/571	135	2015-08-18	2018-08-17
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2015-12-11	2016-12-11
the electro-Mechanics Co.	Horn Antenna	3116	9510-2270	2013-10-14	2016-10-13
TDK	Chamber	Chamber A	2#	2013-10-15	2016-10-15
TDK	Chamber	Chamber B	1#	2015-07-23	2016-07-22
DUCOMMUN	Pre-amplifier	ALN-22093530-01	991373-01	2015-08-03	2016-08-03
R&S	Auto test Software	EMC32	V9.10	NCR	NCR
Ducommun technologies	RF Cable	UFA210A-1-4724-30050U	MFR64369 223410-001	2015-06-15	2016-06-15
Ducommun technologies	RF Cable	104PEA	218124002	2015-06-15	2016-06-15
Ducommun technologies	RF Cable	RG-214	1	2015-06-15	2016-06-15
Ducommun technologies	RF Cable	RG-214	2	2015-06-15	2016-06-15

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

### 8.0 dB at 399.88 MHz in the Horizontal polarization for Middle Channel

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(L_m)} \leq L_{lim} + U_{cisprr}$$

In BACL,  $U_{(L_m)}$  is less than  $+ U_{cisprr}$ , if  $L_m$  is less than  $L_{lim}$ , it implies that the EUT complies with the limit.

## Test Data

### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	46%
ATM Pressure:	101.0 kPa

The testing was performed by Kobe Li on 2016-05-27.

EUT operation mode: Transmitting

**30 MHz -25 GHz:** (Scan with GFSK,  $\pi/4$ -DQPSK, 8-DPSK mode, the worst case is BDR Mode (GFSK))

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2402 MHz)									
399.88	40.60	QP	181	1.0	H	-4.40	36.20	46	9.80
2402.00	97.07	PK	67	1.5	H	-6.46	90.61	/	/
2402.00	86.38	Ave.	67	1.5	H	-6.46	79.92	/	/
2402.00	96.41	PK	311	1.5	V	-6.46	89.95	/	/
2402.00	85.69	Ave.	311	1.5	V	-6.46	79.23	/	/
2370.28	42.39	PK	131	2.1	H	-6.46	35.93	74	38.07
2370.28	28.34	Ave.	131	2.1	H	-6.46	21.88	54	32.12
2380.54	43.11	PK	155	1.9	H	-6.46	36.65	74	37.35
2380.54	28.34	Ave.	155	1.9	H	-6.46	21.88	54	32.12
2499.31	42.44	PK	35	2.0	H	-4.74	37.70	74	36.30
2499.31	28.34	Ave.	35	2.0	H	-4.74	23.60	54	30.40
4804.00	50.36	PK	104	1.0	V	3.79	54.15	74	19.85
4804.00	37.56	Ave.	104	1.0	V	3.79	41.35	54	12.65
7206.00	41.99	PK	27	1.8	V	9.79	51.78	74	22.22
7206.00	28.28	Ave.	27	1.8	V	9.79	38.07	54	15.93
9608.00	38.21	PK	120	1.6	V	11.85	50.06	74	23.94
9608.00	23.71	Ave.	120	1.6	V	11.85	35.56	54	18.44

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Middle Channel (2441 MHz)									
399.88	42.40	QP	77	2.4	H	-4.40	38.00	46	8.00
2441.00	97.65	PK	3	1.1	H	-6.46	91.19	/	/
2441.00	86.51	Ave.	3	1.1	H	-6.46	80.05	/	/
2441.00	96.52	PK	41	1.3	V	-6.46	90.06	/	/
2441.00	85.29	Ave.	41	1.3	V	-6.46	78.83	/	/
2371.24	41.87	PK	145	1.8	H	-6.46	35.41	74	38.59
2371.24	28.34	AV	145	1.8	H	-6.46	21.88	54	32.12
2321.06	42.35	PK	295	1.4	H	-6.65	35.70	74	38.30
2321.06	28.34	Ave.	295	1.4	H	-6.65	21.69	54	32.31
2499.83	42.02	PK	211	1.8	H	-4.74	37.28	74	36.72
2499.83	28.34	Ave.	211	1.8	H	-4.74	23.60	54	30.40
4882.00	49.41	PK	206	2.4	V	3.56	52.97	74	21.03
4882.00	35.41	Ave.	206	2.4	V	3.56	38.97	54	15.03
7323.00	39.06	PK	17	1.1	V	10.11	49.17	74	24.83
7323.00	25.52	Ave.	17	1.1	V	10.11	35.63	54	18.37
9764.00	36.61	PK	243	1.3	V	13.21	49.82	74	24.18
9764.00	21.43	Ave.	243	1.3	V	13.21	34.64	54	19.36
High Channel (2480 MHz)									
399.88	41.48	QP	132	1.1	H	-4.40	37.08	46	8.92
2480.00	97.72	PK	24	1.3	H	-4.74	92.98	/	/
2480.00	86.61	Ave.	24	1.3	H	-4.74	81.87	/	/
2480.00	96.81	PK	103	1.3	V	-4.74	92.07	/	/
2480.00	85.39	Ave.	103	1.3	V	-4.74	80.65	/	/
2319.61	42.64	PK	80	2.4	H	-6.65	35.99	74	38.01
2319.61	28.34	Ave.	80	2.4	H	-6.65	21.69	54	32.31
2483.51	68.21	PK	235	1.1	H	-4.74	63.47	74	10.53
2483.51	43.03	Ave.	235	1.1	H	-4.74	38.29	54	15.71
2483.89	66.01	PK	115	1.5	H	-4.74	61.27	74	12.73
2483.89	40.68	Ave.	115	1.5	H	-4.74	35.94	54	18.06
4960.00	46.38	PK	73	1.3	V	3.19	49.57	74	24.43
4960.00	32.56	Ave.	73	1.3	V	3.19	35.75	54	18.25
7440.00	37.13	PK	351	2.5	V	8.17	45.3	74	28.7
7440.00	23.71	Ave.	351	2.5	V	8.17	31.88	54	22.12
9920.00	35.91	PK	269	2.4	V	13.21	49.12	74	24.88
9920.00	22.26	Ave.	269	2.4	V	13.21	35.47	54	18.53

**Note:**

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading

Margin = Limit - Corrected. Amplitude

**FCC §15.247(a) (1)-CHANNEL SEPARATION TEST****Applicable Standard**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

**Test Procedure**

1. Set the EUT in transmitting mode, maxhold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2015-12-11	2016-12-11
Ducommun technologies	RF Cable	RG-214	3	2015-06-15	2016-06-15
WEINSCHL	3dB Attenuator	5321	AU0709	2015-06-18	2016-06-18

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	46 %
ATM Pressure:	101.0 kPa

*The testing was performed by Kobe Li on 2016-05-18.*


*EUT operation mode: Transmitting*

*Test Result: Compliance. Please refer to following table and plots*


Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	$\geq$ Limit (MHz)	Result
<b>BDR (GFSK)</b>	Low	2402	1.006	0.663	Pass
	Adjacent	2403			
	Middle	2441	1.046	0.636	Pass
	Adjacent	2442			
	High	2480	0.954	0.633	Pass
	Adjacent	2479			
<b>EDR (<math>\pi/4</math>-DQPSK)</b>	Low	2402	1.006	0.910	Pass
	Adjacent	2403			
	Middle	2441	0.994	0.914	Pass
	Adjacent	2442			
	High	2480	1.014	0.838	Pass
	Adjacent	2479			
<b>EDR (8DPSK)</b>	Low	2402	1.002	0.858	Pass
	Adjacent	2403			
	Middle	2441	0.994	0.858	Pass
	Adjacent	2442			
	High	2480	0.998	0.862	Pass
	Adjacent	2479			



Note: Limit = 20 dB bandwidth \*2/3

### BDR (GFSK): Low Channel



### BDR (GFSK): Middle Channel



**BDR (GFSK): High Channel****EDR ( $\pi/4$ -DQPSK): Low Channel**



4.5 dB Offset

Ref Lvl 20.5 dBm

Delta 1 [T1] -1.40 dB

RBW 30 kHz

VBW 100 kHz

RF Att 30 dB

Unit dBm

993.98797595 kHz

1 [T1] -1.62 dBm

2.44084469 GHz

1 [T1] -1.40 dB

1MAX

Center 2.4415 GHz

200 kHz/

Span 2 MHz

Date: 18.MAY.2016 16:32:42

[illegible]

Delta 1 [T1]

Ref Lvl -0.10 dB

20.5 dBm 1.00200401 MHz

RBW 30 kHz RF Att 30 dB

VBW 100 kHz

SWT 6 ms Unit dBm

4.5 dB Offset

20.5

10

0

-10

-20

-30

-40

-50

-60

-70

-79.5

Center 2.4025 GHz

200 kHz/

Span 2 MHz

Date: 18.MAY.2016 16:31:17

Ref Lvl 20.5 dBm Delta 1 [T1] -0.68 dB RBW 30 kHz VBW 100 kHz RF Att 30 dB

20.5 dBm 993.98797595 kHz SWT 6 ms Unit dBm

4.5 dB Offset


1 [T1] -3.67 dBm 2.44084870 GHz -0.68 dB 993.98797595 kHz

MAX

Center 2.4415 GHz 200 kHz/ Span 2 MHz

Date: 18.MAY.2016 16:30:24

EDR (8DPSK): High Channel



## FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH

### Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2015-12-11	2016-12-11
Ducommun technologies	RF Cable	RG-214	3	2015-06-15	2016-06-15
WEINSCHL	3dB Attenuator	5321	AU0709	2015-06-18	2016-06-18

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	46 %
ATM Pressure:	101.0 kPa


*The testing was performed by Kobe Li on 2016-05-18.*

*EUT operation mode: Transmitting*


*Test Result: Compliance. Please refer to following table and plots.*

Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	0.994
	Middle	2441	0.954
	High	2480	0.950
EDR ( $\pi/4$ -DQPSK)	Low	2402	1.365
	Middle	2441	1.371
	High	2480	1.257
EDR (8DPSK)	Low	2402	1.287
	Middle	2441	1.287
	High	2480	1.293


### BDR (GFSK): Low Channel




### BDR (GFSK): Middle Channel




### BDR (GFSK): High Channel





### EDR ( $\pi/4$ -DQPSK): Low Channel




### EDR ( $\pi/4$ -DQPSK): Middle Channel




**EDR ( $\pi/4$ -DQPSK): High Channel****EDR (8DPSK): Low Channel**



## EDR (8DPSK): Middle Channel



## EDR (8DPSK): High Channel



## FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

### Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2015-12-11	2016-12-11
Ducommun technologies	RF Cable	RG-214	3	2015-06-15	2016-06-15
WEINSCHL	3dB Attenuator	5321	AU0709	2015-06-18	2016-06-18

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	46 %
ATM Pressure:	101.0 kPa


*The testing was performed by Kobe Li on 2016-05-18.*



*EUT operation mode: Transmitting*

*Test Result: Compliance. Please refer to following table and plots.*

Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	$\geq 15$
EDR ( $\pi/4$ -DQPSK)	2400-2483.5	79	$\geq 15$
EDR (8DPSK)	2400-2483.5	79	$\geq 15$

### BDR (GFSK): Number of Hopping Channels



**EDR ( $\pi/4$ -DQPSK): Number of Hopping Channels****EDR (8DPSK): Number of Hopping Channels**

**FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)****Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

**Test Procedure**

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 X channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2015-12-11	2016-12-11
Ducommun technologies	RF Cable	RG-214	3	2015-06-15	2016-06-15
WEINSCHL	3dB Attenuator	5321	AU0709	2015-06-18	2016-06-18

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	46 %
ATM Pressure:	101.0 kPa


*The testing was performed by Kobe Li on 2016-05-19.*

*EUT operation mode: Transmitting*


*Test Result: Compliance. Please refer to following table and plots.*

Mode		Channel	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Result
BDR (GFSK)	DH 1	Low	0.395	0.126	0.4	Pass
		Middle	0.395	0.126	0.4	Pass
		High	0.395	0.126	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH 3	Low	1.669	0.267	0.4	Pass
		Middle	1.669	0.267	0.4	Pass
		High	1.669	0.267	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH 5	Low	2.942	0.314	0.4	Pass
		Middle	2.932	0.313	0.4	Pass
		High	2.922	0.312	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR ( $\pi/4$ -DQPSK)	2DH 1	Low	0.401	0.128	0.4	Pass
		Middle	0.397	0.127	0.4	Pass
		High	0.399	0.128	0.4	Pass
		Note: 2DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	2DH 3	Low	1.659	0.265	0.4	Pass
		Middle	1.671	0.267	0.4	Pass
		High	1.671	0.267	0.4	Pass
		Note: 2DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	2DH 5	Low	2.914	0.311	0.4	Pass
		Middle	2.924	0.312	0.4	Pass
		High	2.904	0.310	0.4	Pass
		Note: 2DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR (8DPSK)	3DH 1	Low	0.399	0.128	0.4	Pass
		Middle	0.399	0.128	0.4	Pass
		High	0.399	0.128	0.4	Pass
		Note: 3DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	3DH 3	Low	1.657	0.265	0.4	Pass
		Middle	1.657	0.265	0.4	Pass
		High	1.657	0.265	0.4	Pass
		Note: 3DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	3DH 5	Low	2.904	0.310	0.4	Pass
		Middle	2.914	0.311	0.4	Pass
		High	2.914	0.311	0.4	Pass
		Note: 3DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				


### BDR (GFSK): Pulse time, Low Channel, DH1




### Pulse time, Middle Channel, DH1



### Pulse time, High Channel, DH1




### Pulse time, Low Channel, DH3







### Pulse time, Middle Channel, DH3




### Pulse time, High Channel, DH3



### Pulse time, Low Channel, DH5



### Pulse time, Middle Channel, DH5



Ref Lvl 14.5 dBm Delta 1 [T1] -3.58 dB RBW 1 MHz RF Att 20 dB  
 14.5 dBm 2.921866 ms SWT 5 ms Unit dBm

4.5 dB Offset

1 [T1] -69.73 dBm  
 1 [T1] -43.398798 V/s  
 1 [T1] -3.58 dB  
 2.921866 ms

Center 2.48 GHz 500 ns/

Date: 19.MAY.2016 10:02:01

Delta 1 [T1] 3.58 dB

Ref Lvl 14.5 dBm

RBW 1 MHz

VBW 3 MHz

SWT 1 ms

RF Att 20 dB

Unit dBm


4.5 dB Offset

100  $\mu$ s/


Center 2.402 GHz

Date: 19.MAY.2016 08:59:12

### Pulse time, Middle Channel, 2DH1



### Pulse time, High Channel, 2DH1



Ref Lvl 14.5 dBm Marker 1 [T1] -56.60 dBm RBW 1 MHz RF Att 20 dB  
 -15.342685  $\mu$ s VBW 3 MHz SWT 3 ms Unit dBm

4.5 dB Offset

1 [T1] -56.60 dBm  
 1 [T1] 3.32 dB  
 1.653319 ms

TR

Center 2.402 GHz 300  $\mu$ s/

Date: 19.MAY.2016 09:11:38

Ref Lvl 14.5 dBm

Marker 1 [T1] -58.79 dBm

RBW 1 MHz RF Att 20 dB

VBW 3 MHz

SWT 3 ms Unit dBm

4.5 dB Offset

1.46 dB


1.671343 ms

Center 2.441 GHz


300 ns/div

Date: 19.MAY.2016 09:15:37


### Pulse time, High Channel, 2DH3




### Pulse time, Low Channel, 2DH5





### Pulse time, Middle Channel, 2DH5




### Pulse time, High Channel, 2DH5




**EDR (8DPSK):  
Pulse time, Low Channel, 3DH1****Pulse time, Middle Channel, 3DH1**



### Pulse time, High Channel, 3DH1



### Pulse time, Low Channel, 3DH3



Ref Lvl 14.5 dBm  
 Marker 1 [T1] -59.11 dBm  
 RBW 1 MHz  
 VBW 3 MHz  
 SWT 3 ms  
 RF Att 20 dB  
 Unit dBm

4.5 dB Offset  
 1 [T1] -59.11 dBm  
 Δ1 [T1] 4.01 dB  
 1.658906 ms  
 TR

Center 2.441 GHz  
 300 kHz/div

Date: 19.MAY.2016 09:47:31

Ref Lvl 14.5 dBm

Marker 1 [T1] -59.36 dBm

Marker 2 [T2] -19.350701 V/s

RBW 1 MHz

VBW 3 MHz

SWT 3 ms

RF Att 20 dB

Unit dBm

4.5 dB Offset

1 [T1] -59.36 dBm

Δ1 [T1] -19.350701 V/s

1.658906 ms

TR

Center 2.48 GHz

300 V/s/

Date: 19.MAY.2016 09:48:19

Ref Lvl 14.5 dBm Delta 1 [T1] 0.46 dB RBW 1 MHz RF Att 20 dB

4.5 dB Offset 2.903808 ms SWT 3 MHz Unit dBm

14.5  
10  
0  
-10  
-20  
-30  
-40  
-50  
-60  
-70  
-80  
-85.5

4.5 dB Offset

1 [T1] -62.53 dBm

1 [T1] -37.386774 dBm

0.46 dB

2.903808 ms

TR

Center 2.402 GHz 500 ns/

Date: 19.MAY.2016 09:42:05

Delta 1 [T1] 6.53 dB

Ref Lvl 14.5 dBm

2.913828 ms

RBW 1 MHz

VBW 3 MHz

SWT 5 ms

RF Att 20 dB

Unit dBm

4.5 dB Offset

▼1 [T1] -74.66 dBm

▲1 [T1] -47.406814 dBm

6.53 dB

2.913828 ms


TR

Center 2.441 GHz

500 ns/

Date: 19.MAY.2016 09:41:32

### Pulse time, High Channel, 3DH5



## FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

### Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

### Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Power Meter	N1912A	MY5000448	2015-12-18	2016-12-17
HP	Power Sensor	N1921A	MY54210016	2015-12-18	2016-12-17
Ducommun technologies	RF Cable	RG-214	3	2015-06-15	2016-06-15
WEINSCHL	3dB Attenuator	5321	AU0709	2015-06-18	2016-06-18

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	46 %
ATM Pressure:	101.0 kPa

*The testing was performed by Kobe Li on 2016-05-18.*

*EUT operation mode: Transmitting*

*Test Result: Compliance. Please refer to following table.*

Mode	Channel	Frequency (MHz)	Reading Power (dBm)	Peak Output Power (mw)	Limit (mw)
<b>BDR (GFSK)</b>	Low	2402	2.18	1.652	1000
	Middle	2441	0.48	1.117	1000
	High	2480	-0.34	0.925	1000
<b>EDR (<math>\pi/4</math>-DQPSK)</b>	Low	2402	3.18	2.080	1000
	Middle	2441	1.81	1.517	1000
	High	2480	1.19	1.315	1000
<b>EDR (8DPSK)</b>	Low	2402	3.43	2.203	1000
	Middle	2441	2.18	1.652	1000
	High	2480	1.56	1.432	1000

## FCC §15.247(d) - BAND EDGES TESTING

### Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2015-12-11	2016-12-11
Ducommun technologies	RF Cable	RG-214	3	2015-06-15	2016-06-15
WEINSCHTEL	3dB Attenuator	5321	AU0709	2015-06-18	2016-06-18

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).


**Test Data****Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	46 %
ATM Pressure:	101.0 kPa

The testing was performed by Kobe Li on 2016-05-18


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following plots.


**BDR (GFSK): Band Edge-Left Side**




### BDR (GFSK): Band Edge-Right Side




### EDR ( $\pi/4$ -DQPSK): Band Edge-Left Side




### EDR ( $\pi/4$ -DQPSK): Band Edge-Right Side



### EDR (8DPSK): Band Edge-Left Side



BDR (8DPSK): Band Edge-Right Side



\*\*\*\*\* END OF REPORT \*\*\*\*\*