FCC ID: 2ADXM5B110BT

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency	Electric Field	Magnetic Field	Power	Average Time						
Range(MHz)	Strength(V/m)	Strength(A/m)	Density(mW/cm ²)							
(A) Limits for Occupational/Control Exposures										
300-1500			F/300	6						
1500-100000		5		6						
(B) Limits for General Population/Uncontrol Exposures										
300-1500			F/1500	6						
1500-100000			1	30						

11.1 Friis transmission formula: Pd= (Pout*G)\ (4*pi*R²)

Where

Pd= Power density in mW/cm²

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.1416

R= distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1mW/cm². If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

11.2 Measurement Result

BT DSS

טטט וט		I						1
Channel Freq. (MHz)	modulation	conducted power (mW)	conducted power (dBm)	Tune-up power (dBm)	Max tune- up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
2402	GFSK	0.56	-2.48	-3dBm to -1dBm	-1	1.3	0.00021	1
2441	GFSK	0.53	-2.72	-3dBm to -1dBm	-1	1.3	0.00021	1
2480	GFSK	0.51	-2.89	-3dBm to -1dBm	-1	1.3	0.00021	1
2402	π /4 - DQPSK	0.75	-1.25	-3dBm to -1dBm	-1	1.3	0.00021	1
2441	π /4- DQPSK	0.72	-1.41	-3dBm to -1dBm	-1	1.3	0.00021	1
2480	π /4- DQPSK	0.67	-1.73	-3dBm to -1dBm	-1	1.3	0.00021	1
2402	8DPSK	0.67	-1.73	-3dBm to -1dBm	-1	1.3	0.00021	1
2441	8DPSK	0.74	-1.29	-3dBm to -1dBm	-1	1.3	0.00021	1
2480	8DPSK	0.70	-1.52	-3dBm to -1dBm	-1	1.3	0.00021	1