

FCC PART 15.247 TEST REPORT

For

SHENZHEN TEKSUN TECHNOLOGY CO.,LTD

3F, bldg F7, F518 Idea Land, Baoyuan Road, Xixiang Avenue, Bao'an District, Shenzhen, China

FCC ID: 2ADXM53602BT

Report Type: Product Type: Original Report Bluetooth Speaker Allen Dious Test Engineer: Allen Qiao Report Number: RDG150123001-00A **Report Date:** 2015-02-11 Sola Hoof Sula Huang **Reviewed By:** RF Leader Bay Area Compliance Laboratories Corp. (Dongguan) **Test Laboratory:** No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
Objective	4
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
TEST FACILITY	4
SYSTEM TEST CONFIGURATION	5
DESCRIPTION OF TEST CONFIGURATION	5
EUT Exercise Software	
EQUIPMENT MODIFICATIONS	
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	
EXTERNAL CABLE	
BLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	7
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	8
APPLICABLE STANDARD	
FCC §15.203 - ANTENNA REQUIREMENT	9
APPLICABLE STANDARD	
ANTENNA CONNECTOR CONSTRUCTION	
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	
APPLICABLE STANDARD	
MEASUREMENT UNCERTAINTY	
EUT SETUP	
EMI TEST RECEIVER SETUP	
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST EQUIPMENT LIST AND DETAILS	
TEST RESULTS SUMMARY	
TEST DATA	12
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	15
APPLICABLE STANDARD	15
MEASUREMENT UNCERTAINTY	15
EUT SETUP	15
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST RESULTS SUMMARYTEST DATA	
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST	
APPLICABLE STANDARD	
TEST EQUIPMENT LIST AND DETAILS	
TEST PROCEDURE	
TEST DATA	26

FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING	32
APPLICABLE STANDARD	32
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS.	
TEST DATA	
FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST	38
APPLICABLE STANDARD	38
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS.	
TEST DATA	
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)	42
APPLICABLE STANDARD	42.
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS.	
Test Data	
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	58
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS.	58
TEST DATA	58
FCC §15.247(d) - BAND EDGES TESTING	64
APPLICABLE STANDARD	64
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS.	
Test Data	(1

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The SHENZHEN TEKSUN TECHNOLOGY CO.,LTD's product, model number: 53602BT (FCC ID: 2ADXM53602BT) (the "EUT") in this report was a Bluetooth Speaker, which was measured approximately:11.8 cm (L) x 7.5 cm (W) x 3.6 cm (H), rated input voltage: DC 3.7V rechargeable Li-ion battery or DC5V charging from USB port.

Report No.: RDG150123001-00A

All measurement and test data in this report was gathered from production sample serial number: 150123001 (Assigned by BACL, Dongguan). The EUT was received on 2015-01-29.

Objective

This report is prepared on behalf of *SHENZHEN TEKSUN TECHNOLOGY CO.,LTD* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

No related submittal(s).

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FCC Part 15.247 Page 4 of 67

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

EUT Exercise Software

The software "FCC Assist V1.1" was used for testing, which was provided by manufacturer. The worst condition (maximum power) was setting by the software as following table:

Report No.: RDG150123001-00A

Test Software Version		FCC Assist V1.1		
Test Frequency		2402MHz 2441MHz 2480MHz		
Da I1	GFSK			
Power Level Setting	π/4-DQPSK		_	
Setting	8DPSK			

Equipment Modifications

No modification was made to the EUT.

Local Support Equipment List and Details


Manufacturer	Description Model		Serial Number
DELL	Laptop	PP11L	QDS-BRCM1017
HP	Printer	C3941A JPTVOB2337	
DELL	Keyboard	L100	CNORH656658907BL05DC
SAST	Modem	AEM-2100	0293

External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	То
Serial Cable	Yes	No	1.2	Serial Port of Laptop	Modem
Parallel Cable	Yes	No	1.2	Parallel Port of Laptop	Printer
Keyboard Cable	Yes	No	1.8	USB Port of Laptop	Keyboard
USB Cable	No	No	0.5	USB Port of Laptop	EUT

FCC Part 15.247 Page 5 of 67

Block Diagram of Test Setup



FCC Part 15.247 Page 6 of 67

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & \$1.1310 & §2.1093	RF Exposure	Compliace
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliace
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

FCC Part 15.247 Page 7 of 67

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Report No.: RDG150123001-00A

According to KDB447498 D01 General RF Exposure Guidance v05r02:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance,

mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is ≤ 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The maximum conducted output power= -0.04 dBm (0.99 mW) at 2402 MHz [(max. power of channel, mW)/(min. test separation distance, mm)] $[\sqrt{f(GHz)}]$ = 0.99/5*($\sqrt{2}$.402) = 0.31 < 3.0

So the stand-alone SAR evaluation is not necessary.

FCC Part 15.247 Page 8 of 67

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Report No.: RDG150123001-00A

Antenna Connector Construction

The EUT has one integral antenna arrangement, which was permanently attached and the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC Part 15.247 Page 9 of 67

FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

If $U_{\rm lab}$ is less than or equal to $U_{\rm cispr}$ of Table 1, then:


- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If U_{lab} is greater than U_{cispr} of Table 1, then:
- compliance is deemed to occur if no measured disturbance level, increased by $(U_{\text{lab}} U_{\text{cispr}})$, exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level, increased by $(U_{\text{lab}} U_{\text{cispr}})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of
$$U_{\text{cispr}}$$

Measurement	$U_{ m cispr}$
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

FCC Part 15.247 Page 10 of 67

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W	
150 kHz – 30 MHz	9 kHz	

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

 V_C : corrected voltage amplitude V_R : reading voltage amplitude A_c : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The "Margin" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

FCC Part 15.247 Page 11 of 67

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2014-10-16	2015-10-16
R&S	L.I.S.N	ESH3-Z5	843331/015	N/A	N/A
R&S	Two-line V-network	ENV 216	3560.6550.12	2014-12-11	2015-12-11
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

Report No.: RDG150123001-00A

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Part 15.207</u>, with the worst margin reading of:

5.1 dB at 1.396499 MHz in the Neutral conducted mode

Test Data

Environmental Conditions

Temperature:	21°C
Relative Humidity:	39 %
ATM Pressure:	101.7 kPa


The testing was performed by Allen Qiao on 2015-02-10.

FCC Part 15.247 Page 12 of 67

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Mode: Charging&Transmitting

AC120 V, 60 Hz, Line:




Report No.: RDG150123001-00A

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.461346	38.9	9.000	L1	10.4	17.8	56.7	Compliance
0.590613	35.8	9.000	L1	10.4	20.2	56.0	Compliance
0.614619	44.5	9.000	L1	10.5	11.5	56.0	Compliance
0.639600	40.6	9.000	L1	10.5	15.4	56.0	Compliance
1.396499	42.7	9.000	L1	10.4	13.3	56.0	Compliance
2.325491	37.0	9.000	L1	10.5	19.0	56.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.465037	39.0	9.000	L1	10.4	7.6	46.6	Compliance
0.507637	32.9	9.000	L1	10.3	13.1	46.0	Compliance
0.614619	36.1	9.000	L1	10.5	9.9	46.0	Compliance
0.639600	34.1	9.000	L1	10.5	11.9	46.0	Compliance
1.396499	38.5	9.000	L1	10.4	7.5	46.0	Compliance
2.325491	32.8	9.000	L1	10.5	13.2	46.0	Compliance

FCC Part 15.247 Page 13 of 67

AC120 V, 60 Hz, Neutral:



Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.465037	45.7	9.000	N	10.5	10.9	56.6	Compliance
0.572086	36.9	9.000	N	10.4	19.1	56.0	Compliance
0.600101	40.7	9.000	N	10.5	15.3	56.0	Compliance
0.624492	42.3	9.000	N	10.5	13.7	56.0	Compliance
1.396499	45.1	9.000	N	10.5	10.9	56.0	Compliance
2.325491	44.0	9.000	N	10.5	12.0	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment	
0.465037	41.3	9.000	N	10.5	5.3	46.6	Compliance	
0.600101	25.6	9.000	N	10.5	20.4	46.0	Compliance	
0.624492	30.5	9.000	N	10.5	15.5	46.0	Compliance	
1.396499	40.9	9.000	N	10.5	5.1	46.0	Compliance	
2.325491	39.1	9.000	N	10.5	6.9	46.0	Compliance	
3.249802	21.1	9.000	N	10.7	24.9	46.0	Compliance	

FCC Part 15.247 Page 14 of 67

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

Report No.: RDG150123001-00A

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If U_{lab} is greater than U_{cispr} of Table 1, then:
- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} U_{cispr})$, exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level, increased by $(U_{\text{lab}} U_{\text{cispr}})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:


30M~200MHz: 5.0 dB 200M~1GHz: 6.2 dB 1G~6GHz: 4.45 dB 6G~18GHz: 5.23 dB

Table 1 – Values of $U_{\rm cispr}$

Measurement					
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB				
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB				
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB				


EUT Setup

Below 1GHz:



FCC Part 15.247 Page 15 of 67

Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 CHz	1MHz	3 MHz	/	PK
Above 1 GHz	1MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and Average detection modes for frequencies above 1 GHz.

FCC Part 15.247 Page 16 of 67

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2014-05-09	2015-05-09
Sunol Sciences	Antenna	JB3	A060611-3	2014-07-28	2017-07-27
HP	Amplifier	8447E	2434A02181	2014-09-01	2015-09-01
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09
ETS LINDGREN	Horn Antenna	3115	000 527 35	2012-09-06	2015-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2014-02-19	2015-02-19
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09
Ducommun Technolagies	Horn Antenna	ARH-4223-02	1007726-01 1304	2014-06-16	2017-06-15
Quinstar	Amplifier	QLW- 18405536-JO	15964001001	2014-09-06	2015-09-06

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Title 47, Part 15, Subpart C</u>, and section 15.205, 15.209 and 15.247, with the worst margin reading of:

7.90 dB at **7323 MHz** in the **Horizontal** polarization of EDR Mode (π /4-DQPSK)

Test Data

Environmental Conditions

Temperature:	23.4 °C
Relative Humidity:	64 %
ATM Pressure:	101.6 kPa

The testing was performed by Allen Qiao on 2015-02-04.

Mode: Transmitting

FCC Part 15.247 Page 17 of 67

Report No.: RDG150123001-00A

BDR Mode (GFSK):

Frequency	Re	eceiver	Rx A	ntenna	Cable	Amplifier	Corrected	FCC 1	5.247
(MHz)	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)	loss (dB)	Gain (dB)	Amplitude (dBμV/m)	Limit (dBµV/m)	Margin (dB)
]	Low Chann	el: 2402 N	МНz			
2402	56.36	PK	Н	25.65	4.42	0.00	86.43	N/A	N/A
2402	46.49	AV	Н	25.65	4.42	0.00	76.56	N/A	N/A
2402	64.15	PK	V	25.65	4.42	0.00	94.22	N/A	N/A
2402	54.24	AV	V	25.65	4.42	0.00	84.31	N/A	N/A
2390	25.81	PK	V	25.61	4.39	0.00	55.81	74.00	18.19
2390	14.67	AV	V	25.61	4.39	0.00	44.67	54.00	9.33
4804	40.13	PK	V	30.59	5.98	27.41	49.29	74.00	24.71
4804	32.06	AV	V	30.59	5.98	27.41	41.22	54.00	12.78
7206	32.25	PK	V	34.09	7.45	25.91	47.88	74.00	26.12
7206	20.29	AV	V	34.09	7.45	25.91	35.92	54.00	18.08
9608	30.15	PK	V	35.96	8.80	27.55	47.36	74.00	26.64
9608	18.39	AV	V	35.96	8.80	27.55	35.60	54.00	18.40
1894	32.26	PK	V	24.39	3.62	27.51	32.76	74.00	41.24
1894	20.84	AV	V	24.39	3.62	27.51	21.34	54.00	32.66
266.9	34.19	QP	V	13.51	2.00	21.50	28.20	46.00	17.80
			M	iddle Chan	nel: 2441	MHz			
2441	58.33	PK	Н	25.75	4.40	0.00	88.48	N/A	N/A
2441	48.19	AV	Н	25.75	4.40	0.00	78.34	N/A	N/A
2441	64.03	PK	V	25.75	4.40	0.00	94.18	N/A	N/A
2441	54.24	AV	V	25.75	4.40	0.00	84.39	N/A	N/A
4882	40.79	PK	V	30.79	6.08	27.42	50.24	74.00	23.76
4882	32.16	AV	V	30.79	6.08	27.42	41.61	54.00	12.39
7323	32.54	PK	V	34.38	7.51	25.88	48.55	74.00	25.45
7323	20.27	AV	V	34.38	7.51	25.88	36.28	54.00	17.72
9764	30.43	PK	V	36.33	8.83	27.20	48.39	74.00	25.61
9764	18.37	AV	V	36.33	8.83	27.20	36.33	54.00	17.67
1554	32.1	PK	V	23.71	3.23	27.62	31.42	74.00	42.58
1554	20.06	AV	V	23.71	3.23	27.62	19.38	54.00	34.62
266.9	34.23	QP	V	13.51	2.00	21.50	28.24	46.00	17.76
			I	High Chann	el: 2480 l	MHz	•		
2480	56.76	PK	Н	25.85	4.48	0.00	87.09	N/A	N/A
2480	46.65	AV	Н	25.85	4.48	0.00	76.98	N/A	N/A
2480	64.51	PK	V	25.85	4.48	0.00	94.84	N/A	N/A
2480	54.26	AV	V	25.85	4.48	0.00	84.59	N/A	N/A
2483.5	26.07	PK	V	25.86	4.49	0.00	56.42	74.00	17.58
2483.5	15.12	AV	V	25.86	4.49	0.00	45.47	54.00	8.53
4960	40.81	PK	V	31.00	5.90	27.43	50.28	74.00	23.72
4960	32.54	AV	V	31.00	5.90	27.43	42.01	54.00	11.99
7440	32.66	PK	V	34.66	7.58	25.97	48.93	74.00	25.07
7440	20.19	AV	V	34.66	7.58	25.97	36.46	54.00	17.54
9920	30.47	PK	V	36.71	8.87	26.66	49.39	74.00	24.61
9920	18.7	AV	V	36.71	8.87	26.66	37.62	54.00	16.38
1891	32.14	PK	V	24.38	3.63	27.51	32.64	74.00	41.36
1891	20.28	AV	V	24.38	3.63	27.51	20.78	54.00	33.22
266.9	34.38	QP	V	13.51	2.00	21.50	28.39	46.00	17.61

FCC Part 15.247 Page 18 of 67

EDR Mode ($\pi/4$ -DOPSK):

Frequency	Re	eceiver	Rx A	ntenna	Cable	Amplifier	Corrected	FCC 1	5.247
(MHz)	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)	loss (dB)	Gain (dB)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	•		I	Low Chann	el: 2402 N	ИНz	•		
2402	56.71	PK	Н	25.65	4.42	0.00	86.78	N/A	N/A
2402	44.52	AV	Н	25.65	4.42	0.00	74.59	N/A	N/A
2402	64.01	PK	V	25.65	4.42	0.00	94.08	N/A	N/A
2402	52.17	AV	V	25.65	4.42	0.00	82.24	N/A	N/A
2390	26.03	PK	Н	25.61	4.39	0.00	56.03	74.00	17.97
2390	15.39	AV	Н	25.61	4.39	0.00	45.39	54.00	8.61
4804	38.24	PK	Н	30.59	5.98	27.41	47.40	74.00	26.60
4804	26.27	AV	Н	30.59	5.98	27.41	35.43	54.00	18.57
7206	32.12	PK	Н	34.09	7.45	25.91	47.75	74.00	26.25
7206	20.27	AV	Н	34.09	7.45	25.91	35.90	54.00	18.10
9608	30.99	PK	Н	35.96	8.80	27.55	48.20	74.00	25.80
9608	18.92	AV	Н	35.96	8.80	27.55	36.13	54.00	17.87
1815	32.11	PK	Н	24.23	3.57	27.53	32.38	74.00	41.62
1815	20.63	AV	Н	24.23	3.57	27.53	20.90	54.00	33.10
266.9	34.06	QP	Н	13.51	2.00	21.50	28.07	46.00	17.93
	I		M	iddle Chan	nel: 2441			l l	
2441	58.13	PK	Н	25.75	4.40	0.00	88.28	N/A	N/A
2441	46.25	AV	Н	25.75	4.40	0.00	76.40	N/A	N/A
2441	64.1	PK	V	25.75	4.40	0.00	94.25	N/A	N/A
2441	52.07	AV	V	25.75	4.40	0.00	82.22	N/A	N/A
4882	38.2	PK	Н	30.79	6.08	27.42	47.65	74.00	26.35
4882	26.13	AV	Н	30.79	6.08	27.42	35.58	54.00	18.42
7323	32.48	PK	Н	34.38	7.51	25.88	48.49	74.00	25.51
7323	30.09	AV	Н	34.38	7.51	25.88	46.10	54.00	7.90
9764	30.83	PK	Н	36.33	8.83	27.20	48.79	74.00	25.21
9764	18.73	AV	Н	36.33	8.83	27.20	36.69	54.00	17.31
1933	32.61	PK	Н	24.47	3.73	27.50	33.31	74.00	40.69
1933	20.22	AV	Н	24.47	3.73	27.50	20.92	54.00	33.08
266.9	34.49	QP	Н	13.51	2.00	21.50	28.50	46.00	17.50
			I	ligh Chann			I.	l l	
2480	58.02	PK	Н	25.85	4.48	0.00	88.35	N/A	N/A
2480	48.16	AV	Н	25.85	4.48	0.00	78.49	N/A	N/A
2480	63.95	PK	V	25.85	4.48	0.00	94.28	N/A	N/A
2480	54.04	AV	V	25.85	4.48	0.00	84.37	N/A	N/A
2483.5	26.52	PK	Н	25.86	4.49	0.00	56.87	74.00	17.13
2483.5	15.33	AV	Н	25.86	4.49	0.00	45.68	54.00	8.32
4960	38.15	PK	Н	31.00	5.90	27.43	47.62	74.00	26.38
4960	26.28	AV	Н	31.00	5.90	27.43	35.75	54.00	18.25
7440	32.15	PK	Н	34.66	7.58	25.97	48.42	74.00	25.58
7440	20.34	AV	Н	34.66	7.58	25.97	36.61	54.00	17.39
9920	30.46	PK	Н	36.71	8.87	26.66	49.38	74.00	24.62
9920	18.78	AV	Н	36.71	8.87	26.66	37.70	54.00	16.30
1649	32.01	PK	Н	23.90	3.41	27.74	31.58	74.00	42.42
1649	20.09	AV	Н	23.90	3.41	27.74	19.66	54.00	34.34
266.9	34.05	QP	Н	13.51	2.00	21.50	28.06	46.00	17.94

FCC Part 15.247 Page 19 of 67

Report No.: RDG150123001-00A

EDR Mode (8-DPSK):


Frequency	Re	eceiver	Rx A	ntenna	Cable	Amplifier	Corrected	FCC 1	5.247
(MHz)	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)	loss (dB)	Gain (dB)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
			I	Low Chann	el: 2402 N	МНz	•		
2402	56.16	PK	Н	25.65	4.42	0.00	86.23	N/A	N/A
2402	44.23	AV	Н	25.65	4.42	0.00	74.30	N/A	N/A
2402	64.13	PK	V	25.65	4.42	0.00	94.20	N/A	N/A
2402	52.07	AV	V	25.65	4.42	0.00	82.14	N/A	N/A
2390	26.07	PK	Н	25.61	4.39	0.00	56.07	74.00	17.93
2390	15.11	AV	Н	25.61	4.39	0.00	45.11	54.00	8.89
4804	34.16	PK	Н	30.59	5.98	27.41	43.32	74.00	30.68
4804	22.08	AV	Н	30.59	5.98	27.41	31.24	54.00	22.76
7206	32.93	PK	Н	34.09	7.45	25.91	48.56	74.00	25.44
7206	20.16	AV	Н	34.09	7.45	25.91	35.79	54.00	18.21
9608	30.19	PK	Н	35.96	8.80	27.55	47.40	74.00	26.60
9608	18.51	AV	Н	35.96	8.80	27.55	35.72	54.00	18.28
2916	32.54	PK	Н	26.98	6.62	27.54	38.60	74.00	35.40
2916	20.49	AV	Н	26.98	6.62	27.54	26.55	54.00	27.45
266.9	34.66	QP	Н	13.51	2.00	21.50	28.67	46.00	17.33
			M	iddle Chan	nel: 2441	MHz			
2441	58.36	PK	Н	25.75	4.40	0.00	88.51	N/A	N/A
2441	46.41	AV	Н	25.75	4.40	0.00	76.56	N/A	N/A
2441	64.29	PK	V	25.75	4.40	0.00	94.44	N/A	N/A
2441	52.13	AV	V	25.75	4.40	0.00	82.28	N/A	N/A
4882	34.16	PK	Н	30.79	6.08	27.42	43.61	74.00	30.39
4882	22.27	AV	Н	30.79	6.08	27.42	31.72	54.00	22.28
7323	32.59	PK	Н	34.38	7.51	25.88	48.60	74.00	25.40
7323	20.42	AV	Н	34.38	7.51	25.88	36.43	54.00	17.57
9764	30.85	PK	Н	36.33	8.83	27.20	48.81	74.00	25.19
9764	18.67	AV	Н	36.33	8.83	27.20	36.63	54.00	17.37
2676	32.43	PK	Н	26.36	4.81	27.47	36.13	74.00	37.87
2676	20.29	AV	Н	26.36	4.81	27.47	23.99	54.00	30.01
266.9	34.82	QP	Н	13.51	2.00	21.50	28.83	46.00	17.17
			I	ligh Chann	el: 2480 l	MHz			
2480	58.73	PK	Н	25.85	4.48	0.00	89.06	N/A	N/A
2480	46.25	AV	Н	25.85	4.48	0.00	76.58	N/A	N/A
2480	64.08	PK	V	25.85	4.48	0.00	94.41	N/A	N/A
2480	52.1	AV	V	25.85	4.48	0.00	82.43	N/A	N/A
2483.5	27.16	PK	Н	25.86	4.49	0.00	57.51	74.00	16.49
2483.5	15.35	AV	Н	25.86	4.49	0.00	45.70	54.00	8.30
4960	34.09	PK	Н	31.00	5.90	27.43	43.56	74.00	30.44
4960	22.17	AV	Н	31.00	5.90	27.43	31.64	54.00	22.36
7440	32.15	PK	Н	34.66	7.58	25.97	48.42	74.00	25.58
7440	20.26	AV	Н	34.66	7.58	25.97	36.53	54.00	17.47
9920	30.44	PK	Н	36.71	8.87	26.66	49.36	74.00	24.64
9920	18.17	AV	Н	36.71	8.87	26.66	37.09	54.00	16.91
2793	32.35	PK	Н	26.66	5.28	27.56	36.73	74.00	37.27
2793	20.46	AV	Н	26.66	5.28	27.56	24.84	54.00	29.16
266.9	34.57	QP	Н	13.51	2.00	21.50	28.58	46.00	17.42

FCC Part 15.247 Page 20 of 67


Conducted Spurious Emissions at Antenna Port

BDR Mode (GFSK):

Low Channel




Middle Channel




FCC Part 15.247 Page 21 of 67

High Channel




EDR Mode ($\pi/4$ -DQPSK):


Low Channel



FCC Part 15.247 Page 22 of 67




High Channel




FCC Part 15.247 Page 23 of 67

Low Channel

Report No.: RDG150123001-00A




Middle Channel



FCC Part 15.247 Page 24 of 67

High Channel



FCC Part 15.247 Page 25 of 67

Applicable Standard

Frequency hopping systems shall have hoping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Report No.: RDG150123001-00A

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

- 1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
- 2. Set the adjacent channel of the EUT maxhold another trace
- 3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	22.7°C
Relative Humidity:	42 %
ATM Pressure:	101.6 kPa

^{*} The testing was performed by Allen Qiao on 2015-02-04.

Test Result: Compliance.

Please refer to following tables and plots

FCC Part 15.247 Page 26 of 67

Test Mode: Transmitting

Mode	Channel	(MHZ)		Limit (MHz)	Result
	Low	2402	1.002	0.561	Pass
	Adjacent	2403	1.002	0.301	Pass
BDR Mode	Middle	2441	1.002	0.561	Pass
(GFSK)	Adjacent	2442	1.002	0.301	Pass
	High	2480	1.002	0.561	Pass
	Adjacent	2479	1.002	0.361	r ass
	Low	2402	1.002	0.756	D
	Adjacent	2403	1.002	0.756	Pass
EDR Mode	Middle	2441	1.002	0.756	D
$(\pi/4\text{-DQPSK})$:	Adjacent	2442	1.002		Pass
	High	2480	1.002	0.756	D
	Adjacent	2479	1.002	0.756	Pass
	Low	2402	1.002	0.702	D
	Adjacent	2403	1.002	0.783	Pass
EDR Mode	Middle	2441	1.002	0.702	D
(8-DPSK):	Adjacent	2442	1.002	0.783	Pass
	High	2480	1.002	0.702	D
	Adjacent	2479	1.002	0.783	Pass

BDR Mode (GFSK):

Low Channel



FCC Part 15.247 Page 27 of 67

Middle Channel

Report No.: RDG150123001-00A



High Channel




FCC Part 15.247 Page 28 of 67

EDR Mode (\pi/4-DQPSK):






Middle Channel




FCC Part 15.247 Page 29 of 67

High Channel




EDR Mode (8-DPSK):

Low Channel




FCC Part 15.247 Page 30 of 67

Middle Channel



Date: 04.FEB.2015 15:23:39

High Channel



FCC Part 15.247 Page 31 of 67

FCC $\S15.247(a)$ (1) – 20 dB BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Report No.: RDG150123001-00A

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	22.7°C			
Relative Humidity:	42 %			
ATM Pressure:	101.6 kPa			

^{*} The testing was performed by Allen Qiao on 2015-02-04.

Test Result: Compliance.

Please refer to following tables and plots

FCC Part 15.247 Page 32 of 67


Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
BDR Mode (GFSK)	Low	2402	0.842
	Middle	2441	0.842
	High	2480	0.842
	Low	2402	1.134
EDR Mode (π/4-DQPSK):	Middle	2441	1.134
(1/14-DQI 5K).	High	2480	1.134
EDR Mode (8-DPSK):	Low	2402	1.170
	Middle	2441	1.170
	High	2480	1.174

Please refer to the following plots.

BDR Mode (GFSK):


Low Channel



FCC Part 15.247 Page 33 of 67

Middle Channel





Page 34 of 67 FCC Part 15.247

EDR Mode (\pi/4-DQPSK):

Low Channel

Report No.: RDG150123001-00A



Middle Channel




FCC Part 15.247 Page 35 of 67

High Channel




EDR Mode (8-DPSK):

Low Channel



FCC Part 15.247 Page 36 of 67

Report No.: RDG150123001-00A



High Channel



FCC Part 15.247 Page 37 of 67

FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

Report No.: RDG150123001-00A

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

- 1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- 2. Set the EUT in hopping mode from first channel to last.
- 3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Talleton, A	
Temperature:	22.7°C
Relative Humidity:	42 %
ATM Pressure:	101.6 kPa

^{*} The testing was performed by Allen Qiao on 2015-02-04.

Test Result: Compliance.

Please refer to following tables and plots

FCC Part 15.247 Page 38 of 67


Report No.: RDG150123001-00A

Test Mode: Transmitting

BDR Mode (GFSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15

Number of Hopping Channels




FCC Part 15.247 Page 39 of 67

EDR Mode (\pi/4-DQPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15

Number of Hopping Channels




FCC Part 15.247 Page 40 of 67

EDR Mode (8-DPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15

Number of Hopping Channels



FCC Part 15.247 Page 41 of 67

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Report No.: RDG150123001-00A

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 * channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time= time slot length * hope rate/ number of hopping channels * 31.6s Hop rate=1600/s

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

20010107	Wilderson Company
Temperature:	22.7°C
Relative Humidity:	42 %
ATM Pressure:	101.6 kPa

^{*} The testing was performed by Allen Qiao on 2015-02-04.

Test Result: Compliance.

Please refer to following tables and plots

FCC Part 15.247 Page 42 of 67


Test Mode: Transmitting

BDR Mode (GFSK):

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result	
	Low	0.387	0.124	0.4	Pass	
DH1	Middle	0.387	0.124	0.4	Pass	
	High	0.387	0.124	0.4	Pass	
	Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s					
	Low	1.649	0.264	0.4	Pass	
DH3	Middle	1.649	0.264	0.4	Pass	
DIIS	High	1.649	0.264	0.4	Pass	
	Note: Dwell time=Pulse time (ms) \times (1600/4/79) \times 3			79) ×31.6 s		
	Low	2.922	0.312	0.4	Pass	
DH5	Middle	2.922	0.312	0.4	Pass	
	High	2.922	0.312	0.4	Pass	
	Note: Dwell time	=Pulse time (ms	(1600/6/7)	$(9) \times 31.6 \text{ s}$		


Report No.: RDG150123001-00A

DH1: Low Channel




FCC Part 15.247 Page 43 of 67

DH1: Middle Channel




DH1: High Channel




FCC Part 15.247 Page 44 of 67

DH3: Low Channel




Date: 04.FEB.2015 16:58:18

DH3: Middle Channel




FCC Part 15.247 Page 45 of 67

DH3: High Channel




Date: 04.FEB.2015 16:57:38

DH5: Low Channel




FCC Part 15.247 Page 46 of 67

DH5: Middle Channel



Date: 04.FEB.2015 17:06:26

DH5: High Channel




Date: 04.FEB.2015 17:06:42

FCC Part 15.247 Page 47 of 67

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result	
	Low	0.395	0.126	0.4	Pass	
DH1	Middle	0.395	0.126	0.4	Pass	
DHI	High	0.395	0.126	0.4	Pass	
	Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s					
	Low	1.649	0.264	0.4	Pass	
DH3	Middle	1.649	0.264	0.4	Pass	
DH3	High	1.649	0.264	0.4	Pass	
	Note: Dwell time=Pulse time (ms) \times (1600/4/79) \times 31.6 s					
	Low	2.922	0.312	0.4	Pass	
DH5	Middle	2.922	0.312	0.4	Pass	
	High	2.922	0.312	0.4	Pass	
	Note: Dwell time	=Pulse time (ms	$(1600/6)^{-2}$	79) ×31.6 s		


Report No.: RDG150123001-00A

DH1: Low Channel




FCC Part 15.247 Page 48 of 67

DH1: Middle Channel




DH1: High Channel




FCC Part 15.247 Page 49 of 67

DH3: Low Channel




Date: 04.FEB.2015 16:58:51

DH3: Middle Channel




FCC Part 15.247 Page 50 of 67

DH3: High Channel




Date: 04.FEB.2015 16:59:48

DH5: Low Channel




FCC Part 15.247 Page 51 of 67

DH5: Middle Channel



Date: 04.FEB.2015 17:05:00

DH5: High Channel




Date: 04.FEB.2015 17:04:41

FCC Part 15.247 Page 52 of 67

EDR Mode (8-DPSK):

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result	
	Low	0.395	0.126	0.4	Pass	
DH1	Middle	0.395	0.126	0.4	Pass	
DIII	High	0.395	0.126	0.4	Pass	
	Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s					
	Low	1.649	0.264	0.4	Pass	
DH3	Middle	1.649	0.264	0.4	Pass	
DH3	High	1.649	0.264	0.4	Pass	
Note: Dwell time=Pulse time (ms) \times (10			(1600/4/7)	9) ×31.6 s		
	Low	2.922	0.312	0.4	Pass	
DH5	Middle	2.922	0.312	0.4	Pass	
DHS	High	2.922	0.312	0.4	Pass	
	Note: Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s					


DH1: Low Channel



FCC Part 15.247 Page 53 of 67


Report No.: RDG150123001-00A

DH1: Middle Channel




Date: 04.FEB.2015 16:14:15

DH1: High Channel




FCC Part 15.247 Page 54 of 67

DH3: Low Channel




Date: 04.FEB.2015 17:01:42

DH3: Middle Channel




FCC Part 15.247 Page 55 of 67

DH3: High Channel



Date: 04.FEB.2015 17:00:56


DH5: Low Channel



FCC Part 15.247 Page 56 of 67


Report No.: RDG150123001-00A

DH5: Middle Channel



Date: 04.FEB.2015 17:03:43

DH5: High Channel



Date: 04.FEB.2015 17:04:01

FCC Part 15.247 Page 57 of 67

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Report No.: RDG150123001-00A

Test Procedure

- 1. Place the EUT on a bench and set in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI test receiver.
- 3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	22.7°C
Relative Humidity:	42 %
ATM Pressure:	101.6 kPa

^{*} The testing was performed by Allen Qiao on 2015-02-04.

Test Result: Compliance.

FCC Part 15.247 Page 58 of 67


Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Output power (dBm)	Limit (dBm)
BDR Mode (GFSK)	Low	2402	-0.04	30
	Middle	2441	-0.14	30
	High	2480	-0.08	30
EDR Mode (π/4-DQPSK)	Low	2402	-0.92	30
	Middle	2441	-0.56	30
	High	2480	-0.86	30
EDR Mode (8-DPSK)	Low	2402	-0.77	30
	Middle	2441	-0.48	30
	High	2480	-0.75	30

Note: The data above was tested in conducted mode.


BDR Mode (GFSK):

Output Power, Low Channel




FCC Part 15.247 Page 59 of 67

Output Power, Middle Channel



Date: 04.FEB.2015 15:34:19


Output Power, High Channel




FCC Part 15.247 Page 60 of 67

EDR Mode (\pi/4-DQPSK):

Output Power, Low Channel




Output Power, Middle Channel



FCC Part 15.247 Page 61 of 67


Report No.: RDG150123001-00A

Output Power, High Channel




EDR Mode (8-DPSK):

Output Power, Low Channel




FCC Part 15.247 Page 62 of 67

Output Power, Middle Channel



Date: 04.FEB.2015 15:37:11

Output Power, High Channel



FCC Part 15.247 Page 63 of 67

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Report No.: RDG150123001-00A

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	22.7°C
Relative Humidity:	42 %
ATM Pressure:	101.6 kPa


^{*} The testing was performed by Allen Qiao on 2015-02-04.

FCC Part 15.247 Page 64 of 67


BDR Mode (GFSK):

Band Edge, Left Side

Report No.: RDG150123001-00A



Band Edge, Right Side




FCC Part 15.247 Page 65 of 67


EDR Mode ($\pi/4$ -DQPSK):

Band Edge, Left Side

Report No.: RDG150123001-00A



Band Edge, Right Side




FCC Part 15.247 Page 66 of 67


EDR Mode (8-DPSK):

Band Edge, Left Side

Report No.: RDG150123001-00A



Band Edge, Right Side



***** END OF REPORT *****

FCC Part 15.247 Page 67 of 67