

# FCC Part 15B

## Measurement and Test Report

For

**JIU ZHOU GROUP (HONG KONG) HOLDINGS LIMITED**

**UNITS A2&A3, 25/F, CHEUK NANG PLAZA, 250 HENNESSY ROAD,**

**WAN CHAL, HONG KONG**

**FCC ID: 2ADXNDJZ001**

**Test Rule(s):** FCC Part 15 Subpart B

**Product Description:** tablet pc

**Tested Model:** DA72

**Report No.:** STR14128197I-4

**Tested Date:** 2014-12-22 to 2014-12-25

**Issued Date:** 2014-12-26

**Tested By:** Vigoss Liang / Engineer

**Reviewed By:** Lahm Peng / EMC Manager

**Approved & Authorized By:** Jandy So / PSQ Manager

**Prepared By:**

**Shenzhen SEM.Test Technology Co., Ltd.**

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,  
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

**TABLE OF CONTENTS**

<b>1. GENERAL INFORMATION.....</b>	<b>3</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY.....	4
1.4 TEST FACILITY .....	4
1.5 EUT SETUP AND OPERATION MODE .....	5
<b>2. SUMMARY OF TEST RESULTS .....</b>	<b>6</b>
<b>3. CONDUCTED EMISSIONS .....</b>	<b>7</b>
3.1 MEASUREMENT UNCERTAINTY .....	7
3.2 TEST EQUIPMENT LIST AND DETAILS .....	7
3.3 TEST PROCEDURE.....	7
3.4 BASIC TEST SETUP BLOCK DIAGRAM.....	7
3.5 ENVIRONMENTAL CONDITIONS .....	8
3.6 SUMMARY OF TEST RESULTS/PLOTS .....	8
3.7 CONDUCTED EMISSIONS TEST DATA.....	8
<b>4. RADIATED EMISSIONS.....</b>	<b>11</b>
4.1 MEASUREMENT UNCERTAINTY .....	11
4.2 TEST EQUIPMENT LIST AND DETAILS .....	11
4.3 TEST PROCEDURE.....	11
4.4 TEST RECEIVER SETUP .....	12
4.5 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	12
4.6 ENVIRONMENTAL CONDITIONS .....	12
4.7 SUMMARY OF TEST RESULTS/PLOTS .....	12

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: JIU ZHOU GROUP (HONG KONG) HOLDINGS LIMITED  
Address of applicant: UNITS A2&A3, 25/F, CHEUK NANG PLAZA, 250  
HENNESSY ROAD, WAN CHAL, HONG KONG  
Manufacturer: Shenzhen Tablet Electronics Limited  
Address of manufacturer: B5b Building, Yingzhan Industrial Zone, Longtian  
Community, Kengzi Street, Longgang, Shenzhen, China

#### General Description of EUT

Product Name:	tablet pc
Trade Name:	/
Model No.:	DA72
Adding Model:	I999, R999, QR7

*Note: The test data is gathered from a production sample, provided by the manufacturer. The other model listed in the report has different appearance only of DA72 without circuit and electronic construction changed, declared by the manufacturer.*

#### Technical Characteristics of EUT

Rated Voltage:	5.0V
Rated Current:	1.5A
Rated Power:	7.5W
Power Adapter Model:	TSHU07R-050150
	Input 100-240V, 50/60Hz, Output DC 5V/1.5A
Lowest Internal Frequency:	32.768KHz
Highest Internal Frequency:	1.6GHz
Classification of ITE:	Class B

## 1.2 Test Standards

The following report is prepared on behalf of the JIU ZHOU GROUP (HONG KONG) HOLDINGS LIMITED in accordance with Part 2, Subpart J, and Part 15, Subparts A and B of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart B, and section 15.205, 15.107, and 15.109 rules.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

## 1.4 Test Facility

- **FCC – Registration No.: 934118**

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

- **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

- **CNAS Registration No.: L4062**

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101)

## 1.5 EUT Setup and Operation Mode

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted according to the operation manual for use, more detailed description as follows:

Test Mode List:

Test Mode	Description	Remark
TM1	Charging & Playing & HDMI	Connect to Adapter & HDMI output
TM2	Downloading	Connect to PC
TM3	Camera	/

EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	E10	LR-63C8R
Display	DELL	U2410f	50642P246601H(B) ZL

Special Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
Earphone Cable	1.2	Unshielded	Without Core
USB Cable	1.0	Shielded	Without Core
HDMI Cable	1.5	Shielded	With Core

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 15.107 (a)	Conducted Emissions	Compliant
§ 15.109 (a)	Radiated Emissions	Compliant

N/A: not applicable

### 3. Conducted Emissions

#### 3.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is  $\pm 2.88$  dB.

#### 3.2 Test Equipment List and Details


Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2014-05-28	2015-05-27
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2014-05-28	2015-05-27
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2014-05-28	2015-05-27

#### 3.3 Test Procedure

Test is conducting under the description of ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

*Note: Base on the calibrated result, for the impedance characteristic and insertion loss, the effect shall be ignored from the placed multiple outlet power strip between the device and LISN.*

#### 3.4 Basic Test Setup Block Diagram



### 3.5 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	52%
ATM Pressure:	1011 mbar


### 3.6 Summary of Test Results/Plots

According to the data in section 3.7, the EUT complied with the FCC Part 15.107(a) Conducted margin for a Class B device, with the *worst* margin reading of:

**-0.60 dB at 0.5620 MHz in the Line, AVG detector, 0.15-30MHz**


### 3.7 Conducted Emissions Test Data



**Plot of Conducted Emissions Test Data***EUT:* tablet pc*Tested Model:* DA72*Operating Condition:* TM1*Comment:* AC 120V/60Hz Adapter: DC5V/1.5A*Test Specification:* Neutral

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1780	31.30	9.50	40.80	54.58	-13.78	AVG
2	0.2100	49.38	9.50	58.88	63.21	-4.33	peak
3	0.5620	31.47	9.56	41.03	46.00	-4.97	AVG
4	0.5660	40.97	9.57	50.54	56.00	-5.46	peak
5	1.1220	36.88	10.00	46.88	56.00	-9.12	peak
6	1.1580	19.79	10.00	29.79	46.00	-16.21	AVG

Test Specification: Line



No.	Frequency	Reading	Correct	Result	Limit	Margin	Detector
	(MHz)	(dBuV)	(dB/m)	(dBuV)	(dBuV)	(dB)	
1	0.1580	49.19	9.50	58.69	65.57	-6.88	peak
2	0.1580	29.55	9.50	39.05	55.57	-16.52	AVG
3	0.5620	35.84	9.56	45.40	46.00	-0.60	AVG
4	0.5700	44.91	9.57	54.48	56.00	-1.52	peak
5	1.1460	39.33	10.00	49.33	56.00	-6.67	peak
6	1.1540	24.17	10.00	34.17	46.00	-11.83	AVG

## 4. Radiated Emissions

### 4.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any radiation emissions measurement is  $\pm 5.10$  dB.

### 4.2 Test Equipment List and Details


Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2014-05-28	2015-05-27
EMI Test Receiver	R&S	ESVB	825471/005	2014-05-28	2015-05-27
Pre-amplifier	Agilent	8447F	3113A06717	2014-05-28	2015-05-27
Pre-amplifier	Compliance Direction	PAP-0118	24002	2014-05-28	2015-05-27
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2014-05-24	2015-05-23
Horn Antenna	ETS	3117	00086197	2014-05-24	2015-05-23
Loop Antenna	SCHWARZECK	HFRA 5165	9365	2014-05-28	2015-05-27

### 4.3 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.109 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



#### 4.4 Test Receiver Setup

Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

#### 4.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} - \text{Corr. Factor}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB $\mu$ V means the emission is 6dB $\mu$ V below the maximum limit for a Class B device. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15.109(a) Limit}$$


#### 4.6 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	55 %
ATM Pressure:	1011 mbar

#### 4.7 Summary of Test Results/Plots


According to the data, the EUT complied with the FCC Part 15.109(a) rule, and had the worst margin of:

**-2.11 dB at 938.8326 MHz in the Horizontal polarization, TM3 mode, 9 kHz to 6 GHz, 3Meters**


**Plot of Radiated Emissions Test Data***EUT:* tablet pc*Tested Model:* DA72*Operating Condition:* TM1*Comment:* AC 120V/60Hz Adapter: DC5V/1.5A*Test Specification:* Horizontal

No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( ° )	Height (cm)	Remark
1	102.3597	23.44	5.88	29.32	43.50	-14.18	58	150	peak
2	144.3348	34.39	2.45	36.84	43.50	-6.66	326	100	peak
3	360.4476	26.04	9.24	35.28	46.00	-10.72	29	150	peak
4	893.8567	20.45	16.85	37.30	46.00	-8.70	209	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	Factor(dB)	(dBuV/m)	(dBuV/m)	(dB)	( ° )	(cm)	
1	32.8637	25.11	8.07	33.18	40.00	-6.82	51	100	peak
2	58.4074	26.31	5.51	31.82	40.00	-8.18	308	100	peak
3	70.8315	30.74	2.09	32.83	40.00	-7.17	120	100	peak
4	143.3261	37.23	2.45	39.68	43.50	-3.82	359	100	QP

**Plot of Radiated Emissions Test Data***EUT:* tablet pc*Tested Model:* DA72*Operating Condition:* TM2*Comment:* AC 120V/60Hz; USB 5V*Test Specification:* Horizontal


No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( ° )	Height (cm)	Remark
1	52.5753	27.04	-7.71	19.33	40.00	-20.67	158	150	peak
2	150.0108	35.05	-12.95	22.10	43.50	-21.40	226	100	peak
3	410.3825	35.90	-2.69	33.21	46.00	-12.79	129	150	peak
4	601.4265	34.69	-1.84	32.85	46.00	-13.15	109	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	Factor(dB)	(dBuV/m)	(dBuV/m)	(dB)	( ° )	(cm)	
1	30.5306	33.49	-10.43	23.06	40.00	-16.94	51	100	peak
2	121.9755	38.87	-11.56	27.31	43.50	-16.19	308	100	peak
3	272.2776	33.84	-6.88	26.96	46.00	-19.04	120	100	peak
4	640.6110	34.21	1.70	35.91	46.00	-10.09	359	100	peak



**Plot of Radiated Emissions Test Data***EUT:* tablet pc*Tested Model:* DA72*Operating Condition:* TM3*Comment:* AC 120V/60Hz Adapter: DC5V/1.5A*Test Specification:* Horizontal

No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( ° )	Height (cm)	Remark
1	72.0843	31.52	1.94	33.46	40.00	-6.54	58	150	peak
2	143.8295	37.32	2.45	39.77	43.50	-3.73	326	100	peak
3	216.0240	37.11	4.81	41.92	46.00	-4.08	29	120	peak
4	938.8326	27.65	16.24	43.89	46.00	-2.11	209	100	peak

Test Specification: Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	Factor(dB)	(dBuV/m)	(dBuV/m)	(dB)	( ° )	(cm)	
1	60.2800	27.70	5.29	32.99	40.00	-7.01	51	100	peak
2	143.8295	38.57	2.45	41.02	43.50	-2.48	308	100	peak
3	432.5457	24.81	9.78	34.59	46.00	-11.41	120	100	peak
4	938.8326	26.48	16.24	42.72	46.00	-3.28	359	100	peak

Note: Testing is carried out with frequency rang 9kHz to the 6GHz, which above 1GHz is close to the noise base even antenna close up to 1meter distance according the measurement of ANSI C63.4.

The measurements greater than 20dB below the limit from 9kHz to 30MHz and test data are not provided.

\*\*\*\*\* END OF REPORT \*\*\*\*\*