# Appendix B

# RF Test Data for 5.8G WLAN (Conducted Measurement)

Product Name: WIRELESS HDMI EXTENDER
Trade Mark: HOLLYLAND
Test Model: HLWH200B

### **Environmental Conditions**


Temperature:	24.1° C
Relative Humidity:	53.2%
ATM Pressure:	100.0 kPa
Test Engineer:	WangChuang
Supervised by:	Jayden Zhuo


# **B.1 Duty Cycle**


### Antenna 0


Test Mode	Test Frequency (MHz)	Duty Cycle (%)	10log(1/x) Factor (dB)	1/B Minimum VBW (KHz)
11A	5785	100	0.00	0.01
11N20	5785	100	0.00	0.01
11N40	5755	100	0.00	0.01

Test Mode	Test Frequency (MHz)	Duty Cycle (%)	10log(1/x) Factor (dB)	1/B Minimum VBW (KHz)
11A	5785	100	0.00	0.01
11N20	5785	100	0.00	0.01
11N40	5755	100	0.00	0.01










STATUS

0 Hz



# **B.2 Maximum Conduct Output Power**

### Antenna 0

Test Mode	Channel	Frequency (MHz)	AVG Conducted Power (dBm)	Duty Cycle Factor (dB)	Report Conducted Power (dBm)	Limit (dBm)
	149	5745	14.57	0	14.57	
11A	157	5785	14.94	0	14.94	30
	165	5825	14.57	0	14.57	
	149	5745	13.55	0	13.55	
11N20	157	5785	13.76	0	13.76	30
	165	5825	13.67	0	13.67	
11N40	151	5755	12.41	0	12.41	30
111140	159	5795	12.67	0	12.67	30

### Antenna 1

<u></u>						
		Frequency	AVG Conducted	Duty Cycle	Report	Limit
Test Mode	Channel	(MHz)	Power	Factor	Conducted Power	
			(dBm)	(dB)	(dBm)	(dBm)
	149	5745	14.84	0	14.84	
11A	157	5785	15.04	0	15.04	30
	165	5825	14.91	0	14.91	
	149	5745	13.79	0	13.79	
11N20	157	5785	13.87	0	13.87	30
	165	5825	13.52	0	13.52	
11N40	151	5755	12.32	0	12.32	30
	159	5795	12.29	0	12.29	30

### Antenna 0+Antenna 1

Antonia Vi Antonia i										
			AVG C	AVG Conducted Power			-	Report Conducted		
Test	Channel	Frequency		(dBm)			Po	ower(dBm	ገ)	Limit
Mode	Charmer	(MHz)	Ant0	Ant1	Sum	Factor (dB)	Ant0	Ant1	Sum	(dBm)
	149	5745	13.55	13.79	16.68	0	13.55	13.79	16.68	
11N20	157	5785	13.76	13.87	16.83	0	13.76	13.87	16.83	30
	165	5825	13.67	13.52	16.61	0	13.67	13.52	16.61	
11N40	151	5755	12.41	12.32	15.38	0	12.41	12.32	15.38	30
111140	159	5795	12.67	12.29	15.49	0	12.67	12.29	15.49	30

# **B.3 Power Spectral Density**

### Antenna 0


Test Mode	Channel	Frequency (MHz)	Power Density (dBm/300KHz)	Duty Cycle Factor (dB)	RBW Factor (dB)	Report Power Density (dBm/500KHz)	Limit (dBm/500KHz)
	149	5745	-3.944	0	2.218	-1.726	
11A	157	5785	-3.773	0	2.218	-1.555	30
	165	5825	-4.855	0	2.218	-2.637	
	149	5745	-4.318	0	2.218	-2.100	
11N20	157	5785	-6.239	0	2.218	-4.021	30
	165	5825	-5.925	0	2.218	-3.707	
11N40	151	5755	-14.483	0	2.218	-12.265	30
111140	159	5795	-13.400	0	2.218	-11.182	30

### Antenna 1


Test Mode	Channel	Frequency (MHz)	Power Density (dBm/300KHz)	Duty Cycle Factor (dB)	RBW Factor (dB)	Report Power Density (dBm/500KHz)	Limit (dBm/500KHz)
	149	5745	-2.839	0	2.218	-0.621	
11A	157	5785	-1.701	0	2.218	0.517	30
	165	5825	-3.121	0	2.218	-0.903	
	149	5745	-2.578	0	2.218	-0.360	
11N20	157	5785	-3.630	0	2.218	-1.412	30
	165	5825	-3.550	0	2.218	-1.332	
11N40	151	5755	-8.875	0	2.218	-6.657	30
111140	159	5795	-13.295	0	2.218	-11.077	30

### Antenna 0+Antenna 1

Test Channel Frequence (MHz)		Frequency (MHz)	Power Density (dBm/300KHz)			Duty Cycle Factor	RBW Factor		rt Power De Bm/500KH	_	Limit (dBm/
		, ,	Ant0	Ant1	Sum	(dB)	(dB)	Ant0	Ant1	Sum	500KHz)
	149	5745	-4.318	-2.578	-0.351	0	2.218	-2.100	-0.360	1.867	
11N20	157	5785	-6.239	-3.630	-1.731	0	2.218	-4.021	-1.412	0.487	27.99
	165	5825	-5.925	-3.550	-1.567	0	2.218	-3.707	-1.332	0.651	
11N40	151	5755	-14.483	-8.875	-7.820	0	2.218	-12.265	-6.657	-5.602	27.99
111140	159	5795	-13.400	-13.295	-10.337	0	2.218	-11.182	-11.077	-8.119	21.99




### 





Frequency

IEEE 802.11a / Channel 157 / 5785 MHz\_Ant0













#### IEEE 802.11n HT20 / Channel 157 / 5785 MHz Ant0




IEEE 802.11n HT20 / Channel 165 / 5825 MHz\_Ant0























### IEEE 802.11n HT20 / Channel 157 / 5785 MHz Ant1



IEEE 802.11n HT20 / Channel 165 / 5825 MHz\_Ant1







## **B.4 Emission Bandwidth**

### Antenna 0


Test Mode	Channel	Channel Frequency (MHz)		Limit (MHz)
	149	5745	17.630	
11A	157	5785	17.660	>=0.5
	165	5825	17.660	
	149	5745	17.660	
11N20	157	5785	17.660	>=0.5
	165	5825	17.650	
11N40	151	5755	36.230	->=0.5
	159	5795	36.070	)=0.5


Test Mode	Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	
	149	5745	17.610		
11A	157	5785 17.650		>=0.5	
	165	5825	17.620		
	149	5745	17.690		
11N20	157	5785	17.600	>=0.5	
	165	5825	17.700		
11N40	151	5755	36.400	>=0.5	
111140	159	5795	36.090	>=0.5	







IEEE 802.11a / Channel 157 / 5785 MHz\_Ant0






#### - The state of the AND THE PROPERTY OF THE PROPER -40.0 -50.0 Center 5.825 GHz Span 40 MHz CF Step 4.000000 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 3.867 ms <u>Auto</u> Occupied Bandwidth **Total Power** 9.51 dBm 22.777 MHz Freq Offset 0 Hz Transmit Freq Error 324.33 kHz **OBW Power** 99.00 % x dB Bandwidth 17.65 MHz x dB -6.00 dB STATUS







IEEE 802.11n HT40 / Channel 159 / 5795 MHz\_Ant0

STATUS






IEEE 802.11a / Channel 157 / 5785 MHz\_Ant1




STATUS



### Center 5.825 GHz Span 40 MHz CF Step 4.000000 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 3.867 ms <u>Auto</u> Occupied Bandwidth **Total Power** 12.0 dBm 22.945 MHz Freq Offset 0 Hz Transmit Freq Error 227.69 kHz **OBW Power** 99.00 % x dB Bandwidth 17.70 MHz x dB -6.00 dB STATUS

### IEEE 802.11n HT40 / Channel 151 / 5755 MHz\_Ant1



IEEE 802.11n HT40 / Channel 159 / 5795 MHz\_Ant1


### **B.5 Undesirable Emissions Measurement**


Test Mode	Channel	Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	EIRP (dBm/MHz)	Detector	Limit (dBm/MHz)
		5650.0	-50.394	5.00	-45.394	Peak	-27.0
	149	5700.0	-49.397	5.00	-44.397	Peak	10.0
	149	5720.0	-42.540	5.00	-37.540	Peak	15.6
11A		5725.0	-34.777	5.00	-29.777	Peak	27.0
IIA		5850.0	-28.649	5.00	-23.649	Peak	27.0
	165	5855.0	-32.390	5.00	-27.390	Peak	15.6
	103	5875.0	-46.594	5.00	-41.594	Peak	10.0
		5925.0	-48.937	5.00	-43.937	Peak	-27.0
	149	5650.0	-49.968	5.00	-44.968	Peak	-27.0
		5700.0	-49.716	5.00	-44.716	Peak	10.0
	149	5720.0	-43.897	5.00	-38.897	Peak	15.6
11N20		5725.0	-38.043	5.00	-33.043	Peak	27.0
111120	165	5850.0	-30.707	5.00	-25.707	Peak	27.0
		5855.0	-35.028	5.00	-30.028	Peak	15.6
	103	5875.0	-48.345	5.00	-43.345	Peak	10.0
		5925.0	-49.123	5.00	-44.123	Peak	-27.0
		5650.0	-49.594	5.00	-44.594	Peak	-27.0
	151	5700.0	-48.841	5.00	-43.841	Peak	10.0
	131	5720.0	-36.837	5.00	-31.837	Peak	15.6
11N40		5725.0	-34.710	5.00	-29.710	Peak	27.0
111140		5850.0	-47.811	5.00	-42.811	Peak	27.0
	159	5855.0	-49.592	5.00	-44.592	Peak	15.6
	138	5875.0	-49.038	5.00	-44.038	Peak	10.0
		5925.0	-50.002	5.00	-45.002	Peak	-27.0

Test Mode	Channel	Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	EIRP (dBm/MHz)	Detector	Limit (dBm/MHz)
11A		5650.0	-48.984	5.00	-43.984	Peak	-27.0
	149	5700.0	-45.841	5.00	-40.841	Peak	10.0
		5720.0	-39.359	5.00	-34.359	Peak	15.6
		5725.0	-30.252	5.00	-25.252	Peak	27.0
	165	5850.0	-28.462	5.00	-23.462	Peak	27.0
		5855.0	-34.646	5.00	-29.646	Peak	15.6
		5875.0	-42.525	5.00	-37.525	Peak	10.0
		5925.0	-49.507	5.00	-44.507	Peak	-27.0
11N20	149	5650.0	-49.223	5.00	-44.223	Peak	-27.0
		5700.0	-47.590	5.00	-42.590	Peak	10.0
		5720.0	-38.971	5.00	-33.971	Peak	15.6
		5725.0	-30.454	5.00	-25.454	Peak	27.0
	165	5850.0	-27.198	5.00	-22.198	Peak	27.0
		5855.0	-30.164	5.00	-25.164	Peak	15.6
		5875.0	-45.087	5.00	-40.087	Peak	10.0
		5925.0	-49.987	5.00	-44.987	Peak	-27.0
11N40		5650.0	-49.884	5.00	-44.884	Peak	-27.0
	151	5700.0	-45.893	5.00	-40.893	Peak	10.0
		5720.0	-35.570	5.00	-30.570	Peak	15.6
		5725.0	-34.355	5.00	-29.355	Peak	27.0
	159	5850.0	-48.831	5.00	-43.831	Peak	27.0
		5855.0	-49.295	5.00	-44.295	Peak	15.6
		5875.0	-49.368	5.00	-44.368	Peak	10.0
		5925.0	-49.648	5.00	-44.648	Peak	-27.0


### Antenna 0+Antenn 1


Test Mode	Channel	Frequency (MHz)	Conducted Power (dBm)			Antenna Gain	Gain EIRP (dBm/MHz)	Detector	Limit (dBm/MHz)
			Ant0	Ant1	Sum	(dBi)	(==::::::::=)		( ' ' ' '
11N20 ·	149	5650.0	-49.968	-49.223	-46.569	8.01	-38.559	Peak	-27.0
		5700.0	-49.716	-47.590	-45.514	8.01	-37.504	Peak	10.0
		5720.0	-43.897	-38.971	-37.760	8.01	-29.750	Peak	15.6
		5725.0	-38.043	-30.454	-29.757	8.01	-21.747	Peak	27.0
	165	5850.0	-30.707	-27.198	-25.597	8.01	-17.587	Peak	27.0
		5855.0	-35.028	-30.164	-28.938	8.01	-20.928	Peak	15.6
		5875.0	-48.345	-45.087	-43.407	8.01	-35.397	Peak	10.0
		5925.0	-49.123	-49.987	-46.523	8.01	-38.513	Peak	-27.0
11N40	151	5650.0	-49.594	-49.884	-46.726	8.01	-38.716	Peak	-27.0
		5700.0	-48.841	-45.893	-44.111	8.01	-36.101	Peak	10.0
		5720.0	-36.837	-35.570	-33.147	8.01	-25.137	Peak	15.6
		5725.0	-34.710	-34.355	-31.519	8.01	-23.509	Peak	27.0
	159	5850.0	-47.811	-48.831	-45.281	8.01	-37.271	Peak	27.0
		5855.0	-49.592	-49.295	-46.431	8.01	-38.421	Peak	15.6
		5875.0	-49.038	-49.368	-46.190	8.01	-38.180	Peak	10.0
		5925.0	-50.002	-49.648	-46.811	8.01	-38.801	Peak	-27.0







IEEE 802.11a / Channel 165 / 5825 MHz / Peak\_Ant0










IEEE 802.11n HT20 / Channel 165 / 5825 MHz / Peak\_Ant0













IEEE 802.11a / Channel 165 / 5825 MHz / Peak\_Ant1





Page 31 of 32

IEEE 802.11n HT20 / Channel 165 / 5825 MHz / Peak\_Ant1

