

FCC PART 15C TEST REPORT FOR CERTIFICATION  
On Behalf of

Chunghsin Technology Group CO.,LTD

10.1" ANDROID TABLET WITH DETACHABLE KEYBOARD

Model Number: ONA19TB007

Additional Model: 100005209

FCC ID: 2AE2WT1016M




Prepared for:	Chunghsin Technology Group CO.,LTD
	No. 618-2 GONGREN WEST ROAD, JIAOJIANG AREA, TAIZHOU CITY,
	ZHEJIANG, CHINA
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
	Tel: 86-769-83081888-808

Report Number:	ESTE-R1901071-1
Date of Test:	Apr. 19~May 13, 2019
Date of Report:	May 15, 2019

## TABLE OF CONTENTS

Description	Page
TEST REPORT VERIFICATION .....	3
1. GENERAL INFORMATION.....	4
1.1. Description of Device (EUT) .....	4
2. SUMMARY OF TEST .....	5
2.1. Summary of test result.....	5
2.2. Test Facilities.....	6
2.3. Measurement uncertainty .....	7
2.4. Assistant equipment used for test .....	7
2.5. Block Diagram.....	7
2.6. Test mode .....	8
2.7. Channel List.....	8
2.8. Test Equipment.....	9
3. RADIATED EMISSIONS .....	11
3.1. Limit .....	11
3.2. Block Diagram of Test setup .....	12
3.3. Test Procedure .....	13
3.4. Test Result .....	13
3.5. Test Data.....	14
4. TEST SETUP PHOTO.....	23
5. PHOTO EUT .....	24

**EST Technology Co., Ltd.**

<b>Applicant:</b>	Chunghsin Technology Group CO.,LTD		
<b>Address:</b>	No. 618-2 GONGREN WEST ROAD, JIAOJIANG AREA, TAIZHOU CITY, ZHEJIANG, CHINA		
<b>Manufacturer:</b>	Chunghsin Technology Group CO.,LTD		
<b>Address:</b>	No. 618-2 GONGREN WEST ROAD, JIAOJIANG AREA, TAIZHOU CITY, ZHEJIANG, CHINA		
<b>E.U.T:</b>	10.1" ANDROID TABLET WITH DETACHABLE KEYBOARD		
<b>Model Number:</b>	ONA19TB007		
<b>Additional Model:</b>	100005209 (They are identical except model name only)		
<b>Power Supply:</b>	DC 5V From Adapter Input AC 100~240V, 50/60Hz, 0.3A DC 3.7V From battery		
<b>Test Voltage:</b>	DC 5V From Adapter Input AC 120V/60Hz, 0.3A DC 5V From Adapter Input AC 240V/50Hz, 0.3A		
<b>Trade Name:</b>	onn.	<b>Serial No.:</b>	-----
<b>Date of Receipt:</b>	Apr. 19, 2019	<b>Date of Test:</b>	Apr. 19~May 13, 2019
<b>Test Specification:</b>	FCC Rules and Regulations Part 15 Subpart C:2018 ANSI C63.10:2013		
<b>Test Result:</b>	<p>The device described above is tested by EST Technology Co., Ltd. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC Rules and Regulations Part 15 Subpart C requirements.</p> <p>This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd.</p>		
<b>Prepared by:</b>		<b>Reviewed by:</b>	
 Ring / Assistant		 Tony / Engineer	
		<b>Date:</b> May 15, 2019  Jicman Hu / Manager	
<b>Other Aspects:</b>			
This report base on the previous report with report number: ESTE-R1901071, a new model number and two IC, two keyboard are add in this report.(IC model: SMTJ9A6ZZ5D6DKFRL-107BT PA071-107BT and SMTJ96VZZ7D6EKKFB-107FT PA054-107BT/FT); (Keyboard Model: PT022 K-SH6 and SP1215KB_V10 )			
Abbreviations: OK/P=passed    fail/F=failed    n.a/N=not applicable    E.U.T=equipment under tested			
This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd.			

## 1. GENERAL INFORMATION

### 1.1. Description of Device (EUT)

Product Name	:	10.1" ANDROID TABLET WITH DETACHABLE KEYBOARD
FCC ID	:	2AE2WT1016M
Model Number	:	ONA19TB007
Operation frequency	:	2402MHz~2480MHz
Number of channel	:	79
Antenna	:	Internal antenna (Antenna Gain:1.5 dBi)
Modulation	:	BT BDR: GFSK BT EDR: $\pi/4$ -DQPSK BT EDR: 8-DPSK
Sample Type	:	Prototype production

## 2. SUMMARY OF TEST

### 2.1. Summary of test result

Description of Test Item	Standard	Results
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) KDB 558074	N/A
20dB Bandwidth	FCC Part 15: 15.247a1 KDB 558074	N/A
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1) KDB 558074	N/A
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii) KDB 558074	N/A
Dwell Time	FCC Part 15: 15.247(a)(1)(iii) KDB 558074	N/A
Radiated Emissions	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10:2013 KDB 558074	PASS
Band Edge Compliance	FCC Part 15: 15.247(d) KDB 558074	N/A
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.10:2013 KDB 558074	N/A
Antenna requirement	FCC Part 15: 15.203	N/A
Note: KDB 558074 D01 15.247 Meas Guidance v05		

## 2.2. Test Facilities

### EMC Lab

: Certificated by CNAS, CHINA  
Registration No.: L5288  
Date of registration: November 13, 2017

Certificated by FCC, USA  
Designation Number: CN1215  
Test Firm Registration Number: 722932  
Date of registration: November 21, 2017

Certificated by A2LA, USA  
Registration No.: 4366.01  
Date of registration: November 07, 2017

Certificated by Industry Canada  
CAB identifier No.: CN0035  
Date of registration: January 04, 2019

Certificated by VCCI, Japan  
Registration No.: R-13663; C-14103  
Date of registration: July 25, 2017  
This Certificate is valid until: July 24, 2020

Certificated by TUV Rheinland, Germany  
Registration No.: UA 50413872 0001  
Date of registration: July 31, 2018

Certificated by TUV/PS, Shenzhen  
Registration No.: SCN1017  
Date of registration: January 27, 2011

Certificated by Intertek ETL SEMKO  
Registration No.: 2011-RTL-L2-64  
Date of registration: April 28, 2011

Certificated by Nemko, Hong Kong  
Registration No.: 175193  
Date of registration: May 4, 2011

Name of Firm : EST Technology Co., Ltd.

Site Location : Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China

### 2.3. Measurement uncertainty

Test Item	Uncertainty
Uncertainty for Conduction emission test	$\pm 3.48\text{dB}$
Uncertainty for spurious emissions test (30MHz-1GHz)	$\pm 4.60\text{ dB(Polarize: H)}$
	$\pm 4.68\text{ dB(Polarize: V)}$
Uncertainty for spurious emissions test (1GHz to 18GHz)	$\pm 4.96\text{dB}$
Uncertainty for radio frequency	$7 \times 10^{-8}$
Uncertainty for conducted RF Power	0.20dB
Uncertainty for Power density test	0.26dB

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .


### 2.4. Assistant equipment used for test

#### 2.4.1. Adapter


Manufacturer : onn  
 M/N : BSY01J3050200U U  
 Input : AC 100-240V, 50/60Hz, 0.3A  
 Output : DC 5V, 2.0A

### 2.5. Block Diagram

For radiated emissions test: EUT was placed on a turn table, which is 0.8 (or 1.5) meter high above ground. EUT was beset into Bluetooth test mode by software before test.



(EUT: 10.1" ANDROID TABLET WITH DETACHABLE KEYBOARD)



## 2.6. Test mode

The test software was used to control EUT work in Continuous TX mode, and select test channel, wireless mode

Mode	Channel	Frequency
GFSK	Low	2402MHz
	Middle	2441MHz
	High	2480MHz
8-DPSK	Low	2402MHz
	Middle	2441MHz
	High	2480MHz

## 2.7. Channel List

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2402	2	2403	3	2404	4	2405
5	2406	6	2407	7	2408	8	2409
9	2410	10	2411	11	2412	12	2413
13	2414	14	2415	15	2416	16	2417
17	2418	18	2419	19	2420	20	2421
21	2422	22	2423	23	2424	24	2425
25	2426	26	2427	27	2428	28	2429
29	2430	30	2431	31	2432	32	2433
33	2434	34	2435	35	2436	36	2437
37	2438	38	2439	39	2440	40	2441
41	2442	42	2443	43	2444	44	2445
45	2446	46	2447	47	2448	48	2449
49	2450	50	2451	51	2452	52	2453
53	2454	54	2455	55	2456	56	2457
57	2458	58	2459	59	2460	60	2461
61	2462	62	2463	63	2464	64	2465
65	2466	66	2467	67	2468	68	2469
69	2470	70	2471	71	2472	72	2473
73	2474	74	2475	75	2476	76	2477
77	2478	78	2479	79	2480	-	-



## 2.8. Test Equipment

### 2.8.1. For conducted emission test

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESHS30	832354	CEPREI	June 15,18	1 Year
Artificial Mains Network	Rohde & Schwarz	ENV216	101260	CEPREI	June 15,18	1 Year
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	101100	CEPREI	June 15,18	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

### 2.8.2. For radiated emission test(9 kHz-30MHz)

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	101780	CEPREI	June 15,18	1 Year
Active Loop Antenna	SCHWARZB ECK	FMZB 1519B	1519B-088	N/A	Aug. 01,18	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

### 2.8.3. For radiated emissions test (30-1000MHz)

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	101780	CEPREI	June 15,18	1 Year
Bilog Antenna	Teseq	CBL 6111D	27090	CEPREI	June 15,18	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

### 2.8.4. For radiated emission test(above 1GHz)

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
Horn Antenna	SCHWARZB ECK	BBHA 9120 D	BBHA9120D1002	CEPREI	June 18,18	1 Year
Horn Antenna	SCHWARZB ECK	BBHA9170	BBHA9170242	CEPREI	June 18,18	1 Year
Signal Amplifier	SCHWARZB ECK	BBV9718	9718-212	CEPREI	June 15,18	1 Year
Spectrum Analyzer	Rohde & Schwarz	FSV	103173	CEPREI	June 15,18	1 Year
PSA Series Spectrum Analyzer	Agilent	E4447A	MY50180031	CEPREI	June 15,18	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

## 2.8.5. For connect EUT antenna terminal test

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
Spectrum Analyzer	Rohde & Schwarz	FSV	103173	CEPREI	June 15,18	1 Year
Spectrum Analyzer	Agilent	E4408B	MY44211 139	CEPREI	June 15,18	1 Year

### 3. RADIATED EMISSIONS

#### 3.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

#### 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )

#### 15.209 Limit

Frequency (MHz)	Field Strength( $\mu$ V/m)	Distance(m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


Remark : (1) Emission level  $\text{dB}\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$

(2) The smaller limit shall apply at the cross point between two frequency bands.


(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

### 3.2. Block Diagram of Test setup


9kHz~30MHz



30~1000MHz



Above 1GHz



### 3.3. Test Procedure

EUT was placed on a turn table, which is 0.8 meter high above ground for 9kHz~1000MHz test, and which is 1.5 meter high above ground for above 1GHz test. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

The test frequency analyzer system was set to Peak Detect (300Hz RBW in 9kHz to 150kHz and 10kHz RBW in 150kHz to 30MHz) Function and Specified Bandwidth with Maximum Hold Mode.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 1MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz

PEAK detector, 1MHz/1MHz for PAEK measurement,

PEAK detector, 1MHz/10Hz for Average measurement

The frequency range from 30MHz to 10th harmonic (25GHz) are checked.

### 3.4. Test Result

Pass

Note: 1、 For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

- 2、 The frequency 2402MHz 、2441MHz and 2480MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.

### 3.5. Test Data

9 kHz – 30 MHz


Pass

Note: The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

30 MHz – 1000 MHz

EST Technology

Chilingxiang, Qishantou, Santun,  
Houjie, Dongguan, Guangdong, China  
Tel: +86-769-83081888  
Fax: +86-769-83081878



Site no. : 1# 966 Chamber Data no. : 175  
 Dis. / Ant. : 3m 37062 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 B(3M)  
 Env. / Ins. : Temp:25.4';Humi:74%;Press:101.52kPa  
 Engineer : Tea  
 EUT : 10.1 ANDROID TABLET  
 WITH DETACHABLE KEYBOARD  
 Power : DC 5V From Adapter Input AC 120V/60Hz  
 M/N : ONA19TB007  
 Test Mode : TX Mode  
 KEYBOARD : PT022 K-SH6  
 IC : SMTJ9A6Z25D6DKFRL-107BT PA071-107BT

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	212.36	8.96	1.37	10.52	20.85	43.50	22.65	QP
2	242.43	11.45	1.59	21.89	34.93	46.00	11.07	QP
3	273.47	12.93	1.75	14.08	28.76	46.00	17.24	QP
4	354.95	15.35	2.13	5.78	23.26	46.00	22.74	QP
5	533.43	18.98	2.79	6.02	27.79	46.00	18.21	QP
6	714.82	21.60	3.39	6.09	31.08	46.00	14.92	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. Margin= Limit - Emission Level.  
 3. The emission levels that are 20dB below the official limit are not reported.


## EST Technology

Chilingxiang, Qishantou, Santun,  
Houjie, Dongguan, Guangdong, China  
Tel: +86-769-83081888  
Fax: +86-769-83081878

Data: 176

File: \\EMC-966-1\\test data\\2019\\RFIC\\Chunghsin\\ONA19TB007.EM6 (206)

Date: 2019-05-11



Site no. : 1# 966 Chamber Data no. : 176  
 Dis. / Ant. : 3m 37062 Ant. pol. : VERTICAL  
 Limit : FCC PART 15 B(3M)  
 Env. / Ins. : Temp:25.4'; Humi:74%; Press:101.52kPa  
 Engineer : Tea  
 EUT : 10.1 ANDROID TABLET  
 WITH DETACHABLE KEYBOARD  
 Power : DC 5V From Adapter Input AC 120V/60Hz  
 M/N : ONA19TB007  
 Test Mode : TX Mode  
 KEYBOARD : PT022 K-SH6  
 IC : SMTJ9A6ZZ5D6DKFRL-107BT PA071-107BT

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.00	18.50	0.14	0.22	18.86	40.00	21.14	QP
2	53.28	7.50	0.33	9.06	16.89	40.00	23.11	QP
3	354.95	15.35	2.13	2.33	19.81	46.00	26.19	QP
4	425.76	16.72	2.30	4.45	23.47	46.00	22.53	QP
5	532.46	18.94	2.79	8.48	30.21	46.00	15.79	QP
6	711.91	21.60	3.37	8.67	33.64	46.00	12.36	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. Margin= Limit - Emission Level.  
 3. The emission levels that are 20dB below the official limit are not reported.




## EST Technology

Chilingxiang, Qishantou, Santun,  
Houjie, Dongguan, Guangdong, China  
Tel: +86-769-83081888  
Fax: +86-769-83081878

Data: 177

File: \\EMC-966-1\\test data\\2019\\RFIC\\Chunghsin\\ONA19TB007.EM6 (206)

Date: 2019-05-09



Site no. : 1# 966 Chamber Data no. : 177  
 Dis. / Ant. : 3m 37062 Ant. pol. : VERTICAL  
 Limit : FCC PART 15 B(3M)  
 Env. / Ins. : Temp:25.4'; Humi:74%; Press:101.52kPa  
 Engineer : Tea  
 EUT : 10.1 ANDROID TABLET  
 WITH DETACHABLE KEYBOARD  
 Power : DC 5V From Adapter Input AC 120V/60Hz  
 M/N : ONA19TB007  
 Test Mode : TX Mode  
 KEYBOARD : SP1215KB\_V10  
 IC : SMTJ9A6ZZ5D6DKFRL-107BT PA071-107BT

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	185.20	9.30	1.23	14.79	25.32	43.50	18.18	QP
2	408.30	16.26	2.10	7.41	25.77	46.00	20.23	QP
3	476.20	17.08	2.62	8.28	27.98	46.00	18.02	QP
4	533.43	18.98	2.79	8.46	30.23	46.00	15.77	QP
5	712.88	21.60	3.37	9.20	34.17	46.00	11.83	QP
6	797.27	22.77	3.59	4.89	31.25	46.00	14.75	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. Margin= Limit - Emission Level.  
 3. The emission levels that are 20dB below the official limit are not reported.


## EST Technology

Chilingxiang, Qishantou, Santun,  
Houjie, Dongguan, Guangdong, China  
Tel: +86-769-83081888  
Fax: +86-769-83081878

Data: 178

File: \\EMC-966-1\\test data\\2019\\RFIC\\Chunghsin\\ONA19TB007.EM6 (206)

Date: 2019-05-09



Site no. : 1# 966 Chamber Data no. : 178  
 Dis. / Ant. : 3m 37062 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 B(3M)  
 Env. / Ins. : Temp:25.4'; Humi:74%; Press:101.52kPa  
 Engineer : Tea  
 EUT : 10.1 ANDROID TABLET  
 WITH DETACHABLE KEYBOARD  
 Power : DC 5V From Adapter Input AC 120V/60Hz  
 M/N : ONA19TB007  
 Test Mode : TX Mode  
 KEYBOARD : SP1215KB\_V10  
 IC : SMTJ9A6ZZ5D6DKFRL-107BT PA071-107BT

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	185.20	9.30	1.23	16.62	27.15	43.50	16.35	QP
2	316.15	14.10	1.92	8.37	24.39	46.00	21.61	QP
3	426.73	16.74	2.30	9.02	28.06	46.00	17.94	QP
4	531.49	18.89	2.79	3.66	25.34	46.00	20.66	QP
5	712.88	21.60	3.37	3.30	28.27	46.00	17.73	QP
6	851.59	23.32	3.72	0.28	27.32	46.00	18.68	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. Margin= Limit - Emission Level.  
 3. The emission levels that are 20dB below the official limit are not reported.


## EST Technology

Chilingxiang, Qishantou, Santun,  
Houjie, Dongguan, Guangdong, China  
Tel: +86-769-83081888  
Fax: +86-769-83081878

Data: 179

File: \\EMC-966-1\\test data\\2019\\RFIC\\Chunghsin\\ONA19TB007.EM6 (206)

Date: 2019-05-11



Site no. : 1# 966 Chamber Data no. : 179  
 Dis. / Ant. : 3m 37062 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 B(3M)  
 Env. / Ins. : Temp:25.4'; Humi:74%; Press:101.52kPa  
 Engineer : Tea  
 EUT : 10.1 ANDROID TABLET  
 WITH DETACHABLE KEYBOARD  
 Power : DC 5V From Adapter Input AC 120V/60Hz  
 M/N : ONA19TB007  
 Test Mode : TX Mode  
 KEYBOARD : PT022 K-SH6  
 IC : SMTJ96VZZ7D6EKKFB-107FT PA054-107BT/FT

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	95.96	9.54	0.82	8.01	18.37	43.50	25.13	QP
2	242.43	11.45	1.59	16.28	29.32	46.00	16.68	QP
3	273.47	12.93	1.75	14.69	29.37	46.00	16.63	QP
4	533.43	18.98	2.79	10.47	32.24	46.00	13.76	QP
5	714.82	21.60	3.39	6.89	31.88	46.00	14.12	QP
6	847.71	23.30	3.73	2.78	29.81	46.00	16.19	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. Margin= Limit - Emission Level.  
 3. The emission levels that are 20dB below the official limit are not reported.


## EST Technology

Chilingxiang, Qishantou, Santun,  
Houjie, Dongguan, Guangdong, China  
Tel: +86-769-83081888  
Fax: +86-769-83081878

Data: 180

File: \\EMC-966-1\\test data\\2019\\RFIC\\Chunghsin\\ONA19TB007.EM6 (206)

Date: 2019-05-11



Site no. : 1# 966 Chamber Data no. : 180  
 Dis. / Ant. : 3m 37062 Ant. pol. : VERTICAL  
 Limit : FCC PART 15 B(3M)  
 Env. / Ins. : Temp:25.4'; Humi:74%; Press:101.52kPa  
 Engineer : Tea  
 EUT : 10.1 ANDROID TABLET  
 WITH DETACHABLE KEYBOARD  
 Power : DC 5V From Adapter Input AC 120V/60Hz  
 M/N : ONA19TB007  
 Test Mode : TX Mode  
 KEYBOARD : PT022 K-SH6  
 IC : SMTJ96VZZ7D6EKKFB-107FT PA054-107BT/FT

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	53.28	7.50	0.33	12.24	20.07	40.00	19.93	QP
2	160.95	11.04	1.15	4.75	16.94	43.50	26.56	QP
3	354.95	15.35	2.13	3.74	21.22	46.00	24.78	QP
4	425.76	16.72	2.30	5.21	24.23	46.00	21.77	QP
5	532.46	18.94	2.79	9.67	31.40	46.00	14.60	QP
6	711.91	21.60	3.37	6.87	31.84	46.00	14.16	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. Margin= Limit - Emission Level.  
 3. The emission levels that are 20dB below the official limit are not reported.


## EST Technology

Chilingxiang, Qishantou, Santun,  
Houjie, Dongguan, Guangdong, China  
Tel: +86-769-83081888  
Fax: +86-769-83081878

Data: 181

File: \\EMC-966-1\\test data\\2019\\RFIC\\Chunghsin\\ONA19TB007.EM6 (206)

Date: 2019-05-09



Site no. : 1# 966 Chamber Data no. : 181  
 Dis. / Ant. : 3m 37062 Ant. pol. : VERTICAL  
 Limit : FCC PART 15 B(3M)  
 Env. / Ins. : Temp:25.4'; Humi:74%; Press:101.52kPa  
 Engineer : Tea  
 EUT : 10.1 ANDROID TABLET  
 WITH DETACHABLE KEYBOARD  
 Power : DC 5V From Adapter Input AC 120V/60Hz  
 M/N : ONA19TB007  
 Test Mode : TX Mode  
 KEYBOARD : SP1215KB\_V10  
 IC : SMTJ96VZZ7D6EKKFB-107FT PA054-107BT/FT

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	185.20	9.30	1.23	19.76	30.29	43.50	13.21	QP
2	242.43	11.45	1.59	12.51	25.55	46.00	20.45	QP
3	273.47	12.93	1.75	10.24	24.92	46.00	21.08	QP
4	476.20	17.08	2.62	9.63	29.33	46.00	16.67	QP
5	533.43	18.98	2.79	9.21	30.98	46.00	15.02	QP
6	712.88	21.60	3.37	12.51	37.48	46.00	8.52	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. Margin= Limit - Emission Level.  
 3. The emission levels that are 20dB below the official limit are not reported.


## EST Technology

Chilingxiang, Qishantou, Santun,  
Houjie, Dongguan, Guangdong, China  
Tel: +86-769-83081888  
Fax: +86-769-83081878

Data: 182

File: \\EMC-966-1\\test data\\2019\\RFIC\\Chunghsin\\ONA19TB007.EM6 (206)

Date: 2019-05-09




Site no. : 1# 966 Chamber Data no. : 182  
 Dis. / Ant. : 3m 37062 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 B(3M)  
 Env. / Ins. : Temp:25.4'; Humi:74%; Press:101.52kPa  
 Engineer : Tea  
 EUT : 10.1 ANDROID TABLET  
 WITH DETACHABLE KEYBOARD  
 Power : DC 5V From Adapter Input AC 120V/60Hz  
 M/N : ONA19TB007  
 Test Mode : TX Mode  
 KEYBOARD : SP1215KB\_V10  
 IC : SMTJ96VZZ7D6EKKFB-107FT PA054-107BT/FT

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	85.29	8.10	0.75	10.56	19.41	40.00	20.59	QP
2	185.20	9.30	1.23	21.22	31.75	43.50	11.75	QP
3	316.15	14.10	1.92	10.69	26.71	46.00	19.29	QP
4	359.80	15.40	2.16	8.26	25.82	46.00	20.18	QP
5	426.73	16.74	2.30	7.15	26.19	46.00	19.81	QP
6	476.20	17.08	2.62	8.90	28.60	46.00	17.40	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. Margin= Limit - Emission Level.  
 3. The emission levels that are 20dB below the official limit are not reported.

## 4. TEST SETUP PHOTO

Radiated Test (30-1000 MHz)





## 5. PHOTO EUT

**External Photos**  
M/N: ONA19TB007







**External Photos**  
M/N: ONA19TB007



External Photos  
M/N: ONA19TB007




External Photos  
M/N: ONA19TB007







External Photos  
M/N: ONA19TB007



External Photos  
M/N: ONA19TB007





Internal Photos  
M/N: ONA19TB007







Internal Photos  
M/N: ONA19TB007



Internal Photos  
M/N: ONA19TB007


RF  
Antenna Port






**Internal Photos**

IC Model: SMTJ96VZZ7D6EKKFB-107FT PA054-107BT/FT



IC Model: SMTJ9A6ZZ5D6DKFRL-107BT PA071-107BT





Keyboard

External Photos  
M/N: PT022 K-SH6






Internal Photos  
M/N: PT022 K-SH6



**Internal Photos**  
M/N: PT022 K-SH6





External Photos  
M/N: SP1215KB\_V10





Internal Photos  
M/N: SP1215KB V10



**Internal Photos**  
M/N: SP1215KB\_V10

