

Maximum Permissive Exposure

FCC ID: 2AE3B-AEH-AR9462

Product Name: PCIE 802.11a/b/g/n 2.4GHz/5GHz + USB BT 4.0 card

Model No: AEH-AR9462

1. According to FCC CFR 47 §1.1310, the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

Table 1 Limits for Maximum Permissible Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	f/300	6
1500-100,000	5.0	6
(B) Limits For General Population / Uncontrolled Exposure (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

VoxMicro LTD. declares that the product described above has been evaluated and found to comply with the RF exposure limits for humans, as specified based on ANSI/FCC recommendation.

2. MPE Calculation

RF Exposure Calculations:

$$S = (P * G) / (4 * \pi * r^2) \text{ or } r = \sqrt{(P * G) / (4 * \pi * S)}$$

2.1. WIFI 2.4G MPE

Based on safety distance (r) **20cm**, the antenna gain (G) is **3.170 Numerical**, and the highest power output (P) is **457.088mW**, the power density (S) is **0.288263mW/cm²**.

Where :

Based on safety distance (r)=	20 cm	
Highest Power Output (P)=	26.60 dBm =	457.088 mW
Antenna Gain (G)=	5.01 dBi =	3.170 Numerical
MPE (S) = (P*G) / (4* π *r ²) =	= (457.088*3.170)/(4*π*20²)= 0.288263 mW/cm²	

2.2. BLE MPE

Based on safety distance (r) **20cm**, the antenna gain (G) is **1.585 Numerical**, and the highest power output (P) is **2.466mW**, the power density (S) is **0.000778mW/cm²**.

Where :

Based on safety distance (r)=	20 cm	
Highest Power Output (P)=	3.92 dBm =	2.466 mW
Antenna Gain (G)=	2.0 dBi =	1.585 Numerical
MPE (S) = (P*G) / (4* π *r ²) =	= (2.466*1.585)/(4*π*20²)= 0.000778 mW/cm²	

2.3. BT MPE

Based on safety distance (r) **20cm**, the antenna gain (G) is **1.585 Numerical**, and the highest power output (P) is **4.677mW**, the power density (S) is **0.001475 mW/cm²**.

Where :

Based on safety distance (r)=	20 cm	
Highest Power Output (P)=	6.70 dBm =	4.677 mW
Antenna Gain (G)=	2.0 dBi =	1.585 Numerical
MPE (S) = (P*G) / (4* π *r ²) =	= (4.677*1.585)/(4*π*20²)= 0.001475 mW/cm²	

2.4. WIFI 5G MPE

Based on safety distance (r) **20cm**, the antenna gain (G) is **3.990 Numerical**, and the highest power output (P) is **79.983mW**, the power density (S) is **0.063489 mW/cm²**.

Where :

Based on safety distance (r)=	20 cm	
Highest Power Output (P)=	19.03 dBm =	79.983 mW
Antenna Gain (G)=	6.01 dBi =	3.990 Numerical
MPE (S) = (P*G) / (4* π *r ²) =	= (79.983*3.990)/(4*π*20²)= 0.063489 mW/cm²	

MPE				
WIFI 2.4G (mW/cm ²)	BT (mW/cm ²)	BLE (mW/cm ²)	Total (mW/cm ²)	Limit (mW/cm ²)
0.288263	0.001475	0.000778	0.290516	≤ 1

MPE				
WIFI 5G (mW/cm ²)	BT (mW/cm ²)	BLE (mW/cm ²)	Total (mW/cm ²)	Limit (mW/cm ²)
0.063489	0.001475	0.000778	0.065742	≤ 1

Sincerely Yours,



Mr. Ben Cheng
Manager
AUDIX Technology Corporation