1 Human Exposure Assessment

1.1 Maximum Permissible Exposure

1.1.1 Limit of Maximum Permissible Exposure

Limits for Occupational / Controlled Exposure								
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time E ², H ² or S (minutes)				
0.3-3.0	614	1.63	(100)*	6				
3.0-30	1842 / f	4.89 / f	(900 / f ²)*	6				
30-300	61.4	0.163	1.0	6				
300-1500	-	-	F/300	6				
1500-100,000	-	-	5	6				
Limits for General Population / Uncontrolled Exposure								
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time E ², H ² or S (minutes)				
0.3-1.34	614	1.63	(100)*	30				
1.34-30	824/f	2.19/f	(180/f ²)*	30				
30-300	27.5	0.073	0.2	30				
300-1500	_		F/1500	30				
1500-100,000	-	-	1.0	30				

Note 1: f = frequency in MHz; *Plane-wave equivalent power density

Note 2: For the applicable limit, see FCC 1.1310

MPE Calculation Method

$$E (V/m) = \frac{\sqrt{30 \times P \times G}}{d}$$

E = Electric field (V/m)

G = EUT Antenna numeric gain (numeric)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

Power Density: Pd (W/m²) = $\frac{E^2}{377}$

P = RF output power (W)

d = Separation distance between radiator and human body (m)

Report No.: FA541008-01

SPORTON INTERNATIONAL INC. Page No. : 1 of 2
TEL: 886-3-327-3456 Report Version : Rev. 01

FAX: 886-3-327-0973

1.1.2 Result of Maximum Permissible Exposure (2.4G)

RF General Information 2400 MHz – 2483.5 MHz								
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Number of Transmit Chains (N _{TX})	RF Output Power (dBm)			
2400-2483.5	b	2412-2462	1-11 [11]	1	20.80			
2400-2483.5	g	2412-2462	1-11 [11]	1	19.81			
Note 1: RF output power specifies that Maximum Conducted (Average) Output Power								

Report No.: FA541008-01

Note 1: RF output power specifies that Maximum Conducted (Average) Output Power.

Worst Maximum RF Output Power Result								
Exposure Environment		General Population / Uncontrolled Exposure						
Separation Distance (cm)		20						
Condition		RF Output Power (dBm)						
Modulation Mode	N _{TX}	RF Output Power (dBm)	DG (dBi)	EIRP Power	PD (S) (mW/cm²)			
b	1	20.80	2.31	23.11	0.04071			
Maximum Permissible Exposure Limit (mW/cm²)					1			
Note 1: N _{TX} = Number of	Trans	mit Chains		,				

SPORTON INTERNATIONAL INC. Page No. : 2 of 2
TEL: 886-3-327-3456 Report Version : Rev. 01

FAX: 886-3-327-0973